



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



## CERTIFICATE OF COMPLIANCE FCC Part 22 & 24 Certification

**Applicant Name:**

Samsung Electronics, Co. Ltd.  
18600 Broadwick St.  
Rancho Dominguez, CA 90220  
United States

**Date of Testing:**

March 07, 2007

**Test Site/Location:**

PCTEST Lab., Columbia, MD, USA

**Test Report Serial No.:**

0703080163.A3L

**FCC ID:**

A3LSGHA711

**APPLICANT:**

SAMSUNG ELECTRONICS, CO. LTD.

**Application Type:**

Certification

**FCC Classification:**

PCS Licensed Transmitter Held to Ear (PCE)

**FCC Rule Part(s):**

§2; §22(H), §24(E)

**EUT Type:**

PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth

**Model(s):**

SGH-A711

**Tx Frequency Range:**

1850.20 - 1909.80MHz (PCS GSM) / 1850.20 - 1909.80MHz (EDGE1900)  
826.40 - 846.60MHz (Cell. WCDMA)

**Max. RF Output Power:**

1.122 W EIRP PCS GSM (30.5 dBm)  
0.369 W EIRP EDGE1900 (25.67dBm)  
0.204 W ERP WCDMA850 (23.1 dBm)

**Emission Designator(s):**

244KGXW (PCS GSM)  
242KG7W (EDGE1900)  
4M16F9W (Cellular WCDMA)

**Test Device Serial No.:**

*identical prototype* [S/N: FE-024-G]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is ERP for Part 22 and EIRP for Part 24.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President




|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 1 of 40                                                                          |                                 |

# TABLE OF CONTENTS

|                                                               |    |
|---------------------------------------------------------------|----|
| FCC PART 22 & 24 MEASUREMENT REPORT .....                     | 3  |
| 1.0 INTRODUCTION .....                                        | 4  |
| 1.1 MEASUREMENT PROCEDURE .....                               | 4  |
| 1.2 SCOPE .....                                               | 4  |
| 1.3 TESTING FACILITY .....                                    | 4  |
| 2.0 PRODUCT INFORMATION .....                                 | 5  |
| 2.1 EQUIPMENT DESCRIPTION .....                               | 5  |
| 2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....             | 5  |
| 3.0 DESCRIPTION OF TESTS .....                                | 6  |
| 3.1 OCCUPIED BANDWIDTH EMISSION LIMITS .....                  | 6  |
| 3.2 CELLULAR - BASE FREQUENCY BLOCKS .....                    | 6  |
| 3.3 CELLULAR - MOBILE FREQUENCY BLOCKS .....                  | 6  |
| 3.4 PCS - BASE FREQUENCY BLOCKS .....                         | 7  |
| 3.5 PCS - MOBILE FREQUENCY BLOCKS .....                       | 7  |
| 3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL ..... | 7  |
| 3.7 RADIATED SPURIOUS AND HARMONIC EMISSIONS .....            | 7  |
| 3.8 FREQUENCY STABILITY / TEMPERATURE VARIATION .....         | 8  |
| 4.0 TEST EQUIPMENT CALIBRATION DATA .....                     | 9  |
| 5.0 SAMPLE CALCULATIONS .....                                 | 10 |
| 6.0 TEST RESULTS .....                                        | 11 |
| 6.1 CONDUCTED OUTPUT POWER .....                              | 12 |
| 6.2 EFFECTIVE RADIATED POWER OUTPUT DATA .....                | 13 |
| 6.3 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA .....     | 14 |
| 6.4 CELLULAR BAND RADIATED MEASUREMENTS .....                 | 15 |
| 6.5 PCS BAND RADIATED MEASUREMENTS .....                      | 18 |
| 6.6 CELLULAR BAND FREQUENCY STABILITY MEASUREMENTS .....      | 21 |
| 6.7 PCS BAND FREQUENCY STABILITY MEASUREMENTS .....           | 23 |
| 7.0 PLOTS OF EMISSIONS .....                                  | 25 |
| 8.0 CONCLUSION .....                                          | 37 |
| EXHIBIT A – TEST SETUP PHOTOGRAPHS .....                      | 38 |
| EXHIBIT B – INTERNAL PHOTOGRAPHS .....                        | 39 |
| EXHIBIT C – EXTERNAL PHOTOGRAPHS .....                        | 40 |

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 2 of 40                                                                          |                                 |



## MEASUREMENT REPORT



### FCC Part 22 & 24

#### A. §2.1033 General Information

**APPLICANT:** Samsung Electronics, Co. Ltd.  
**APPLICANT ADDRESS:** 18600 Broadwick St.  
 Rancho Dominguez, CA 90220  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22(H), §24(E)  
**MODEL NAME:** SGH-A711  
**FCC ID:** A3LSGHA711  
**FCC CLASSIFICATION:** PCS Licensed Transmitter Held to Ear (PCE)  
 244KGXW (PCS GSM)  
 242KG7W (EDGE1900)  
 4M16F9W (Cellular WCDMA)  
**EMISSION DESIGNATOR(S):** PCS GSM/EDGE1900/Cellular WCDMA  
**MODE:** PCS GSM/EDGE1900/Cellular WCDMA  
**FREQUENCY TOLERANCE:**  $\pm 0.00025\%$  (2.5 ppm)  
**Test Device Serial No.:** FE-024-G ☐ Production ☒ Pre-Production ☐ Engineering  
**DATE(S) OF TEST:** March 07, 2007  
**TEST REPORT S/N:** 0703080163.A3L

#### A.1 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.




- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 3 of 40                                                                          |                                 |

## 1.0 INTRODUCTION

### 1.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 1-1). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



**Figure 1-1. Diagram of 3-meter outdoor test range**


Deviation from Measurement Procedure.....None

### 1.2 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

### 1.3 Testing Facility

These measurements were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.



**Figure 1-2. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.**

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 4 of 40                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth FCC ID: A3LSGHA711**. The EUT consisted of the following component(s):

| Trade Name / Model        | FCC ID     | Description                                              |
|---------------------------|------------|----------------------------------------------------------|
| Samsung / Model: SGH-A711 | A3LSGHA711 | PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth |

**Table 2-1. EUT Equipment Description**

| Mode                                  | FCC Rule Part | Frequency [MHz]                      | Notes                                                                                         |
|---------------------------------------|---------------|--------------------------------------|-----------------------------------------------------------------------------------------------|
| PCS<br>GSM/EDGE1900/Cellular<br>WCDMA | 22 / 24       | 1850.20 -<br>1909.80MHz (PCS<br>GSM) | This report contains data pertaining only to the PCS GSM/EDGE1900/Cellular WCDMA transmitter. |
| Bluetooth                             | 15.247        | 2402-2480 MHz                        | Data can be found in a separate test report under the same FCC ID.                            |
| Receiver / Digital Device             | 15B           | N/A                                  | Data can be found in a separate test report under the same FCC ID.                            |

**Table 2-2. Supported EUT Modes**

### 2.2 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing.

- None

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 5 of 40                                                                          |                                 |


## 3.0 DESCRIPTION OF TESTS

### 3.1 Occupied Bandwidth Emission Limits


§2.1049, 22.917(a), 24.238(a)

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least  $43 + 10 \log(P)$  dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

### 3.2 Cellular - Base Frequency Blocks




### 3.3 Cellular - Mobile Frequency Blocks



|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 6 of 40                    |

### 3.4 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

### 3.5 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

### 3.6 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a), 24.238(a); RSS-129 (8.1.1), RSS-133 (6.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic.

### 3.7 Radiated Spurious and Harmonic Emissions

§2.1053, 22.917(a), 24.238(a); RSS-129 (8.1.1), RSS-133 (6.5.1(i))

Spurious and harmonic radiated emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 7 of 40                    |



### 3.8 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235; RSS-132 (4.3) / RSS-133 (6.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency.*

#### Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (20°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at -30°C (usually 14-16 hours) the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within one minute after applying power to the transmitter.
4. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. At least a period of one half-hour is provided to allow stabilization of the equipment at each temperature level.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 8 of 40                                                                          |                                 |

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer      | Model / Equipment                         | Calibration Date | Cal Interval | Calibration Due | Serial No.       |
|-------------------|-------------------------------------------|------------------|--------------|-----------------|------------------|
| Agilent           | E4404B/E4407B ESA Spectrum Analyzer       | 04/20/06         | Annual       | 04/20/07        | US39210313       |
| Agilent           | E5515C Wireless Communications Test Set   | 07/27/06         | Annual       | 07/27/07        | GB41450275       |
| Agilent           | E5515C Wireless Communications Test Set   | 10/06/06         | Annual       | 10/06/07        | GB43193972       |
| Agilent           | E4432B ESG-D Series Signal Generator      | 08/08/06         | Annual       | 08/08/07        | US40053896       |
| Agilent           | 8648D (9kHz-4GHz) Signal Generator        | 10/01/06         | Annual       | 10/01/07        | 3613A00315       |
| Agilent           | E5515C Wireless Communications Test Set   | 10/26/06         | Biennial     | 10/25/08        | GB46310798       |
| EMCO              | Model 3115 (1-18GHz) Horn Antenna         | 08/24/06         | Biennial     | 08/23/08        | 9203-2178        |
| EMCO              | Model 3115 (1-18GHz) Horn Antenna         | 08/25/06         | Biennial     | 08/24/08        | 9704-5182        |
| Gigatronics       | 8657A Universal Power Meter               | 04/07/06         | Annual       | 04/07/07        | 8650319          |
| Gigatronics       | 80701A (0.05-18GHz) Power Sensor          | 04/11/06         | Annual       | 04/11/07        | 1833460          |
| Rohde & Schwarz   | NRVS Power Meter                          | 06/01/05         | Biennial     | 06/01/07        | 835360/079       |
| Rohde & Schwarz   | NRV-Z53 Power Sensor                      | 06/01/05         | Biennial     | 06/01/07        | 846076/007       |
| Rohde & Schwarz   | CMU200 Base Station Simulator             | 11/08/06         | Annual       | 11/08/07        | 107826           |
| Rohde & Schwarz   | CMU200 Base Station Simulator             | 07/26/06         | Annual       | 07/26/07        | 833855/010       |
| Rohde & Schwarz   | CMU200 Base Station Simulator             | 04/20/06         | Annual       | 04/20/07        | 836371/079       |
| Agilent           | HP 8566B (100Hz-22GHz)                    | 12/21/06         | Annual       | 12/21/07        | 3638A08713       |
| Agilent           | E4448A (3Hz-50GHz)                        | 09/22/06         | Annual       | 09/22/07        | US42510244       |
| Gigatronics       | 8651A (50MHz-18GHz)                       | 07/28/06         | Annual       | 07/28/07        | 1834052          |
| Gigatronics       | 80701A (0.05-18GHz) Power Sensor          | 08/04/06         | Annual       | 08/04/07        | 1835299          |
| Agilent           | HP 85650A Quasi-Peak Adapter              | 12/21/06         | Annual       | 12/21/07        | 2043A00301       |
| Agilent           | HP 8449B (1-26.5GHz) Pre-Amplifier        | 12/12/06         | Annual       | 12/12/07        | 3008A00985       |
| Agilent           | HP 11713A Attenuation/Switch Driver       | 12/12/06         | Annual       | 12/12/07        | N/A              |
| Agilent           | HP 85685A (20Hz-2GHz) Preselector         | 12/12/06         | Annual       | 12/12/07        | N/A              |
| Agilent           | HP 8566B Opt. 462 Impulse Bandwidth       | 12/12/06         | Annual       | 12/12/07        | 3701A22204       |
| EMCO              | 3115 (1-18GHz) Horn Antenna               | 04/04/05         | Biennial     | 04/04/07        | 9205-3874        |
| Compliance Design | A100 Roberts Dipoles                      | 08/31/05         | Biennial     | 08/31/07        | 5118             |
| EMCO              | Dipole Pair                               | 09/21/06         | Biennial     | 09/20/08        | 23951            |
| SOLAR             | 8012-50 LISN (2)                          | 11/18/05         | Biennial     | 11/18/07        | 0313233, 0310234 |
| Agilent           | HP 8901A Modulation Analyzer              | 06/05/06         | Annual       | 06/05/07        | 2432A03467       |
| Agilent           | HP 8903 B Audio Analyzer                  | 06/01/06         | Annual       | 06/01/07        | 3011A09025       |
| K & L             | 11SH10 Band Pass Filter                   | N/A              | Annual       | N/A             | 1300/4000        |
| K & L             | 11SH10 Band Pass Filter                   | N/A              | Annual       | N/A             | 4000/12000       |
| Agilent           | HP 8495A (0-70dB) DC-4GHz Attenuator      | N/A              |              | N/A             | N/A              |
| -                 | 263-10dB (DC-18GHz) 10 dB Attenuator      | N/A              |              | N/A             | N/A              |
| Pasternack        | PE2208-6 Bidirectional Coupler            | N/A              |              | N/A             | N/A              |
| -                 | No.165 (30MHz - 1000MHz) RG58 Coax Cable  | N/A              |              | N/A             | N/A              |
| -                 | No.166 (1000-26500MHz) Microwave RF Cable | N/A              |              | N/A             | N/A              |
| -                 | No.167 (100kHz - 100MHz) RG58 Coax Cable  | N/A              |              | N/A             | N/A              |

Table 4-1. Test Equipment

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 9 of 40                                                                          |                                 |

## 5.0 SAMPLE CALCULATIONS

### GSM Emission Designator

**Emission Designator = 250KGXW**

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### WCDMA Emission Designator

**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### Spurious Radiated Emission - PCS Band

**Example: GSM Channel 512 PCS Mode 2<sup>nd</sup> Harmonic (3700.40 MHz)**

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 10 of 40                   |

## 6.0 TEST RESULTS

### Summary

Company Name: Samsung Electronics, Co. Ltd.  
 FCC ID: A3LSGHA711  
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)  
 Mode(s): PCS GSM/EDGE1900/Cellular WCDMA

| FCC Part Section(s)                                 | RSS Section                                                        | Test Description                                                               | Test Limit                                                                         | Test Condition                   | Test Result | Reference           |
|-----------------------------------------------------|--------------------------------------------------------------------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------|----------------------------------|-------------|---------------------|
| TRANSMITTER MODE (TX)                               |                                                                    |                                                                                |                                                                                    |                                  |             |                     |
| 2.1049, 22.917(a), 24.238(a)                        | N/A                                                                | Occupied Bandwidth                                                             | N/A                                                                                | CONDUCTED                        | PASS        | Section 7.0         |
| 2.1051, 22.917(a), 24.238(a)                        | RSS-132 (4.5.1) / RSS-133 (6.5.1)                                  | Band Edge / Conducted Spurious Emissions                                       | < 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions |                                  | PASS        | Section 7.0         |
| SAR Measurement Procedures for 3G Devices, June '06 | N/A                                                                | Conducted Power Measurements for 3G Devices (WCDMA)                            | N/A                                                                                |                                  | PASS        | FCC 3G Power Table  |
| 2.1046                                              | N/A                                                                | GSM Conducted Output Power                                                     | N/A                                                                                |                                  | PASS        | Section 6.1         |
| 22.913(a)(2)                                        | RSS-132 (4.4) [SRSP-503(5.1.3)]                                    | Effective Radiated Power                                                       | < 7 Watts max. ERP (<6.3 Watts max. ERP (IC))                                      | RADIATED                         | PASS        | Section 6.2         |
| 24.232(c)                                           | RSS-133 (6.4) [SRSP-510 (5.1.2)]                                   | Equivalent Isotropic Radiated Power                                            | < 2 Watts max. EIRP                                                                |                                  | PASS        | Section 6.3         |
| 2.1053, 22.917(a), 24.238(a)                        | RSS-132 (4.5.1) / RSS-133 (6.5.1)                                  | Undesirable Emissions                                                          | < 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions                  |                                  | PASS        | Sections 6.4, 6.5   |
| 2.1055, 22.355, 24.235                              | RSS-132 (4.3) / RSS-133 (6.3)                                      | Frequency Stability                                                            | < 2.5 ppm                                                                          |                                  | PASS        | Sections 6.6, 6.7   |
| RECEIVER MODE (RX) / DIGITAL EMISSIONS              |                                                                    |                                                                                |                                                                                    |                                  |             |                     |
| 15.107                                              | RSS-Gen (7.2.2)                                                    | AC Conducted Emissions 150kHz – 30MHZ                                          | < FCC 15.207 limits or < RSS-Gen table 2 limits                                    | LINE CONDUCTED                   | PASS        | Pt. 15B Test Report |
| 15.109                                              | RSS-132 (4.6) / RSS-133(6.7(a) / [RSS-Gen (7.2.2)] / RSS-210 (7.3) | General Field Strength Limits (Restricted Bands and Radiated Emissions Limits) | < FCC 15.209 limits or < RSS-210 table 3 limits                                    | RADIATED (30MHz-1GHz) (1-25 GHz) | PASS        | Pt. 15B Test Report |
| RF EXPOSURE (SAR)                                   |                                                                    |                                                                                |                                                                                    |                                  |             |                     |
| 2.1091 / 2.1093                                     | RSS-102                                                            | SAR                                                                            | 1.6 W/kg (SAR Limit)<br>1 mW/cm² (MPE Limit) @ 20 cm                               | SAR                              | PASS        | SAR Report          |

**Table 6-1. Summary of Test Results**

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 11 of 40                                                                         |                                 |

## 6.1 Conducted Output Power

### §2.1046

A base station simulator (Rhode and Schwartz Model: CMU200) was used to establish communication with the **Samsung PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth FCC ID: A3LSGHA711**. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band.

| W C D M A | Channel | 12.2<br>k b p s<br>R M C<br>[d B m] | 12.2<br>k b p s<br>A M R<br>[d B m] |
|-----------|---------|-------------------------------------|-------------------------------------|
|           | 4 1 3 2 | 23.55                               | 23.58                               |
|           | 4 1 8 2 | 23.68                               | 23.68                               |
|           | 4 2 3 3 | 23.62                               | 23.61                               |

Table 6-2. WCDMA Conducted Output Powers

| Band | Channel | GSM / GPRS          |                 | EDGE            |
|------|---------|---------------------|-----------------|-----------------|
|      |         | Power Control Level | Conducted Power | Conducted Power |
|      |         |                     | [dBm]           | [dBm]           |
| PCS  | 512     | 0                   | 29.11           | 22.82           |
|      | 661     | 0                   | 29.01           | 23.64           |
|      | 810     | 0                   | 29.17           | 24.34           |

Table 6-3. GSM Conducted Output Powers




Figure 6-1. GSM Conducted Power Test Setup Diagram

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 12 of 40                   |

## 6.2 Effective Radiated Power Output Data

§22.913(a)(2); RSS-132 (4.4) [SRSP-503(5.1.3)]

POWER: All "1" bits (Cellular WCDMA Mode)

| Frequency [MHz] | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | ERP [dBm] | ERP [Watts] |
|-----------------|----------------------|------------------------|--------------------|-----------|-----------|-------------|
| 826.40          | -20.500              | 21.25                  | 1.65               | V         | 22.90     | 0.195       |
| 835.00          | -21.400              | 20.35                  | 1.65               | V         | 22.00     | 0.158       |
| 846.60          | -20.300              | 21.45                  | 1.65               | V         | 23.10     | 0.204       |

Table 6-4. Effective Radiated Power Output Data (WCDMA)

### NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 13 of 40                   |

### 6.3 Equivalent Isotropic Radiated Power Output Data

§24.232(c); RSS-133 (6.4) [SRSP-510 (5.1.2)]

POWER: PCL "0" (PCS GSM Mode)

| Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | ERP [dBm] | ERP [Watts] |          |
|----------------------|------------------------|--------------------|-----------|-----------|-------------|----------|
| -10.000              | 22.30                  | 8.00               | V         | 30.30     | 1.072       | PCS GSM  |
| -9.800               | 22.50                  | 8.00               | V         | 30.50     | 1.122       | PCS GSM  |
| -9.900               | 22.40                  | 8.00               | V         | 30.40     | 1.096       | PCS GSM  |
| -14.630              | 17.67                  | 8.00               | V         | 25.67     | 0.369       | EDGE1900 |

Table 6-5. Equivalent Isotropic Radiated Power Output Data (GSM)

#### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 14 of 40                   |

## 6.4 Cellular Band Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MEASURED OUTPUT POWER: 23.100 dBm = 0.204 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.10 dBc

| FREQ.<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA<br>GAIN<br>(dBi) | CORRECT<br>GENERATOR<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|----------------|------------------------------------------|----------------------------------------|----------------------------------------|--------------|-------|
| 1652.80        | -67.69                                   | 8.31                                   | -59.38                                 | V            | 82.5  |
| 2479.20        | -82.68                                   | 9.41                                   | -73.28                                 | V            | 96.4  |
| 3305.60        | -92.33                                   | 9.55                                   | -82.78                                 | V            | 105.9 |
| 4132.00        | -88.91                                   | 9.74                                   | -79.18                                 | V            | 102.3 |
| 4958.40        | -88.00                                   | 10.62                                  | -77.38                                 | V            | 100.5 |

**Table 6-6. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 15 of 40                   |



## Cellular Band Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 835.00 MHz  
 CHANNEL: 4175  
 MEASURED OUTPUT POWER: 23.100 dBm = 0.204 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.10 dBc

| FREQ.<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA<br>GAIN<br>(dBi) | CORRECT<br>GENERATOR<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|----------------|------------------------------------------|----------------------------------------|----------------------------------------|--------------|-------|
| 1670.00        | -64.81                                   | 8.33                                   | -56.48                                 | V            | 79.6  |
| 2505.00        | -84.13                                   | 9.45                                   | -74.68                                 | V            | 97.8  |
| 3340.00        | -92.25                                   | 9.57                                   | -82.68                                 | V            | 105.8 |
| 4175.00        | -89.18                                   | 9.90                                   | -79.28                                 | V            | 102.4 |
| 5010.00        | -87.39                                   | 10.61                                  | -76.78                                 | V            | 99.9  |

Table 6-7. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4175)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
 according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                               |                                                                                        |  |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSGHA711                 |                               | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |  | Page 16 of 40                   |



## Cellular Band Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MEASURED OUTPUT POWER: 23.100 dBm = 0.204 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  36.10 dBc

| FREQ.<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA<br>GAIN<br>(dBi) | CORRECT<br>GENERATOR<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|----------------|------------------------------------------|----------------------------------------|----------------------------------------|--------------|-------|
| 1693.20        | -56.22                                   | 8.34                                   | -47.88                                 | V            | 71.0  |
| 2539.80        | -83.42                                   | 9.45                                   | -73.98                                 | V            | 97.1  |
| 3386.40        | -91.87                                   | 9.59                                   | -82.28                                 | V            | 105.4 |
| 4233.00        | -89.23                                   | 10.06                                  | -79.18                                 | V            | 102.3 |
| 5079.60        | -87.59                                   | 10.61                                  | -76.98                                 | V            | 100.1 |

Table 6-8. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
 according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                               |                                                                                        |  |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSGHA711                 |                               | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |  | Page 17 of 40                   |

## 6.5 PCS Band Radiated Measurements

S2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 30.500 dBm = 1.122 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  43.50 dBc

| FREQ.<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA<br>GAIN<br>(dBi) | CORRECT<br>GENERATOR<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|----------------|------------------------------------------|----------------------------------------|----------------------------------------|--------------|-------|
| 3700.40        | -49.98                                   | 9.54                                   | -40.45                                 | V            | 70.9  |
| 5550.60        | -73.56                                   | 10.66                                  | -62.90                                 | V            | 93.4  |
| 7400.80        | -80.67                                   | 11.14                                  | -69.53                                 | V            | 100.0 |
| 9251.00        | -77.18                                   | 11.15                                  | -66.03                                 | V            | 96.5  |
| 11101.20       | -77.98                                   | 12.75                                  | -65.23                                 | V            | 95.7  |

**Table 6-9. Radiated Spurious Data (PCS GSM Mode – Ch. 512)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 18 of 40                   |



## PCS Band Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
CHANNEL: 661  
MEASURED OUTPUT POWER: 30.500 dBm = 1.122 W  
MODULATION SIGNAL: GSM (Internal)  
DISTANCE: 3 meters  
LIMIT:  $43 + 10 \log_{10} (W) =$  43.50 dBc

| FREQ.<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA<br>GAIN<br>(dBi) | CORRECT<br>GENERATOR<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|----------------|------------------------------------------|----------------------------------------|----------------------------------------|--------------|-------|
| 3760.00        | -48.80                                   | 9.51                                   | -39.30                                 | V            | 69.8  |
| 5640.00        | -76.09                                   | 10.76                                  | -65.33                                 | V            | 95.8  |
| 7520.00        | -80.24                                   | 11.01                                  | -69.23                                 | V            | 99.7  |
| 9400.00        | -77.15                                   | 11.32                                  | -65.83                                 | V            | 96.3  |
| 11280.00       | -77.77                                   | 12.74                                  | -65.03                                 | V            | 95.5  |

**Table 6-10. Radiated Spurious Data (PCS GSM Mode – Ch. 661)**

#### NOTES:

##### Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                               |                                                                                        |  |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|--|---------------------------------|
| FCC ID: A3LSGHA711                 |                               | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |  | Page 19 of 40                   |

## PCS Band Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 30.500 dBm = 1.122 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 43.50$  dBc

| FREQ.<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA<br>GAIN<br>(dBi) | CORRECT<br>GENERATOR<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|----------------|------------------------------------------|----------------------------------------|----------------------------------------|--------------|-------|
| 3819.60        | -50.32                                   | 9.48                                   | -40.84                                 | V            | 71.3  |
| 5729.40        | -68.88                                   | 10.86                                  | -58.02                                 | V            | 88.5  |
| 7639.20        | -80.06                                   | 11.03                                  | -69.03                                 | V            | 99.5  |
| 9549.00        | -77.02                                   | 11.49                                  | -65.53                                 | V            | 96.0  |
| 11458.80       | -77.55                                   | 12.72                                  | -64.83                                 | V            | 95.3  |

Table 6-11. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Active at 12.2 kbps RMC and TPC bits all set to "1" and in GSM mode using a Power Control Level of "0" in the PCS Band. This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 20 of 40                   |



## 6.6 Cellular Band Frequency Stability Measurements

S2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 835,000,000 Hz

CHANNEL: 4175

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT:  $\pm 0.00025$  % or 2.5 ppm

| VOLTAGE<br>(%) | POWER<br>(VDC) | TEMP<br>(°C) | FREQ.<br>(Hz) | Freq. Dev.<br>(Hz) | Deviation<br>(%) |
|----------------|----------------|--------------|---------------|--------------------|------------------|
| 100 %          | 3.70           | + 20 (Ref)   | 834,999,985   | -15                | -0.000002        |
| 100 %          |                | - 30         | 834,999,978   | -22                | -0.000003        |
| 100 %          |                | - 20         | 835,000,013   | 13                 | 0.000002         |
| 100 %          |                | - 10         | 835,000,017   | 17                 | 0.000002         |
| 100 %          |                | 0            | 834,999,991   | -9                 | -0.000001        |
| 100 %          |                | + 10         | 834,999,986   | -14                | -0.000002        |
| 100 %          |                | + 20         | 834,999,985   | -15                | -0.000002        |
| 100 %          |                | + 25         | 835,000,012   | 12                 | 0.000001         |
| 100 %          |                | + 30         | 835,000,019   | 19                 | 0.000002         |
| 100 %          |                | + 40         | 835,000,011   | 11                 | 0.000001         |
| 100 %          |                | + 50         | 835,000,014   | 14                 | 0.000002         |
| 115 %          | 4.26           | + 20         | 834,999,985   | -15                | -0.000002        |
| BATT. ENDPOINT | 3.40           | + 20         | 835,000,024   | 24                 | 0.000003         |

**Table 6-2. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4175)**


### Note:

This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 21 of 40                                                                         |                                 |

## Cellular Band Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)



**Plot 6-1. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4175)**

**Note:**

This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 22 of 40                                                                         |                                 |



## 6.7 PCS Band Frequency Stability Measurements

S2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE<br>(%) | POWER<br>(VDC) | TEMP<br>(°C) | FREQ.<br>(Hz) | Freq. Dev.<br>(Hz) | Deviation<br>(%) |
|----------------|----------------|--------------|---------------|--------------------|------------------|
| 100 %          | 3.70           | + 20 (Ref)   | 1,879,999,977 | -23                | -0.000001        |
| 100 %          |                | - 30         | 1,879,999,981 | -19                | -0.000001        |
| 100 %          |                | - 20         | 1,880,000,013 | 13                 | 0.000001         |
| 100 %          |                | - 10         | 1,880,000,022 | 22                 | 0.000001         |
| 100 %          |                | 0            | 1,879,999,991 | -9                 | 0.000000         |
| 100 %          |                | + 10         | 1,880,000,018 | 18                 | 0.000001         |
| 100 %          |                | + 20         | 1,879,999,977 | -23                | -0.000001        |
| 100 %          |                | + 25         | 1,880,000,011 | 11                 | 0.000001         |
| 100 %          |                | + 30         | 1,880,000,022 | 22                 | 0.000001         |
| 100 %          |                | + 40         | 1,880,000,027 | 27                 | 0.000001         |
| 100 %          |                | + 50         | 1,880,000,021 | 21                 | 0.000001         |
| 115 %          | 4.26           | + 20         | 1,879,999,977 | -23                | -0.000001        |
| BATT. ENDPOINT | 3.40           | + 20         | 1,880,000,029 | 29                 | 0.000002         |


**Table 6-3. Frequency Stability Data (PCS GSM Mode – Ch. 661)**

**Note:** This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 23 of 40                                                                         |                                 |

## PCS Band Frequency Stability Measurements (Cont'd)

§2.1055, 24.235; RSS-133 (6.3)




**Plot 6-2. Frequency Stability Graph (PCS GSM Mode – Ch. 661)**


**Note:** This unit was tested with its standard battery.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 24 of 40                                                                         |                                 |

## 7.0 PLOTS OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-2. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 25 of 40                   |




Plot 7-3. Band Edge Plot (PCS GSM Mode – Ch. 512)

|                                    |                               |                                                                                        |                |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSGHA711                 | <b>PCTEST</b><br>wireless     | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                | Page 26 of 40                   |




Plot 7-4. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-5. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 27 of 40                   |




Plot 7-6. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)

|                                    |                               |                                                                                        |                |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSGHA711                 | <b>PCTEST</b><br>wireless     | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                | Page 28 of 40                   |




Plot 7-7. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)




Plot 7-8. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

|                                    |                                                                                     |                                                                       |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA                         |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth |                                                                                       | Page 29 of 40                   |




Plot 7-9. Band Edge Plot (PCS GSM Mode – Ch. 810)




Plot 7-10. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)

|                                    |                               |                                                                                        |                |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSGHA711                 | <b>PCTEST</b><br>wireless     | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                | Page 30 of 40                   |



Plot 7-11. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-12. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 31 of 40                   |




Plot 7-13. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-14. 4MHz Span Plot (Cellular WCDMA Mode – Ch. 4132)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 32 of 40                   |




Plot 7-15. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4175)




Plot 7-16. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4175)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 33 of 40                   |




Plot 7-17. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4175)




Plot 7-18. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)

|                                    |                               |                                                                                        |                |                                 |
|------------------------------------|-------------------------------|----------------------------------------------------------------------------------------|----------------|---------------------------------|
| FCC ID: A3LSGHA711                 | <b>PCTEST</b><br>wireless     | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) | <b>SAMSUNG</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007 | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                | Page 34 of 40                   |




Plot 7-19. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)



Plot 7-20. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 35 of 40                   |



Plot 7-21. 4MHz Span Plot (Cellular WCDMA Mode – Ch. 4233)

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 36 of 40                   |

## 8.0 CONCLUSION

The data collected show that the **Samsung PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth FCC ID: A3LSGHA711** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  |                                                                                       | Page 37 of 40                   |



## EXHIBIT A – TEST SETUP PHOTOGRAPHS

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 38 of 40                                                                         |                                 |

**EXHIBIT B – INTERNAL PHOTOGRAPHS**

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 39 of 40                                                                         |                                 |

## EXHIBIT C – EXTERNAL PHOTOGRAPHS

|                                    |                                                                                     |                                                                                        |                                                                                       |                                 |
|------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: A3LSGHA711                 |  | FCC Pt. 22/24 PCS GSM/EDGE1900/Cellular WCDMA<br>MEASUREMENT REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0703080163.A3L | Test Dates:<br>March 07, 2007                                                       | EUT Type:<br>PCS GSM / EDGE1900 / Cellular WCDMA Phone with Bluetooth                  | Page 40 of 40                                                                         |                                 |