



SAR COMPLIANCE EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
18600 Broadwick St.
Rancho Dominguez, CA 90220
United States

Date of Testing:

07/05/11 - 07/07/11

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

OY1106281089.A3L

FCC ID: A3LSGHI777

APPLICANT: SAMSUNG ELECTRONICS, CO. LTD.

EUT Type:

850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093; FCC/OET Bulletin 65 Supplement C [June 2001]

Model(s):

SGH-I777

Test Device S/N.:

Pre-Production [S/N: FI-165-A]

Band & Mode	Tx Frequency	Conducted Power [dBm]	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
GSM 850	824.20 - 848.80 MHz (GSM 850)	32.51	0.36	0.73	0.90
GSM 1900	1850.20 - 1909.80 MHz (GSM 1900)	29.85	0.24	0.70	0.70
WCDMA 850	826.40 - 846.60 MHz (WCDMA 850)	22.58	0.35	0.56	0.63
WCDMA 1900	1852.4 - 1907.6 MHz (WCDMA 1900)	22.47	0.34	0.78	0.78
5.2 GHz WLAN	5180 - 5240 MHz (WLAN)	12.41	0.03	0.11	
5.3 GHz WLAN	5260 - 5320 MHz (WLAN)	12.08	0.03	0.09	
5.5 GHz WLAN	5500 - 5700 MHz (WLAN)	12.03	0.03	0.04	
5.8 GHz WLAN	5745 - 5825 MHz (WLAN)	12.37	0.09	0.12	
2.4 GHz WLAN	2412 - 2462 MHz (WLAN)	17.47	0.19	0.08	0.11

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001), IEEE 1528-2003 and in applicable Industry Canada Radio Standards Specifications (RSS); for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager	
Filename: OY1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 1 of 50	

T A B L E O F C O N T E N T S

1	INTRODUCTION	3
2	TEST SITE LOCATION	4
3	SAR MEASUREMENT SETUP	5
4	DASY E-FIELD PROBE SYSTEM	7
5	PROBE CALIBRATION PROCESS	8
6	PHANTOM AND EQUIVALENT TISSUES.....	9
7	DOSIMETRIC ASSESSMENT & PHANTOM SPECS.....	10
8	DEFINITION OF REFERENCE POINTS	11
9	TEST CONFIGURATION POSITIONS	12
10	FCC RF EXPOSURE LIMITS.....	15
11	FCC 3G MEASUREMENT PROCEDURES.....	16
12	SAR TESTING WITH IEEE 802.11 TRANSMITTERS.....	20
13	FCC PERSONAL WIRELESS ROUTER CONFIGURATIONS.....	23
14	SYSTEM VERIFICATION.....	25
15	SAR DATA SUMMARY	28
16	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	41
17	EQUIPMENT LIST	45
18	MEASUREMENT UNCERTAINTIES	46
19	CONCLUSION.....	48
20	REFERENCES	49

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSMA Phone with RFID, Bluetooth and WLAN				Page 2 of 50	

1 INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [24]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

Figure 1-1
SAR Mathematical Equation

1.1.1

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSGHI777		 ENGINEERING LABORATORY, INC.		SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN						Page 3 of 50

2 TEST SITE LOCATION

2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC.

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on January 27, 2006 and Industry Canada.



Figure 2-1

Map of the Greater Baltimore and Metropolitan Washington, D.C. area

2.2 Test Facility / Accreditations:

Measurements were performed at an independent accredited PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing-Aid Compatibility (HAC), Battery Safety, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and all Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS and CDMA, and EvDO mobile phones.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO Data, CDMA 1xRTT Data

FCC ID: A3LSGH177		PCTEST Engineering Laboratory, Inc.		SAR COMPLIANCE REPORT		SAMSUNG		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HS-PA Phone with RFID, Bluetooth and WLAN						Page 4 of 50

3

3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of a high precision robotics system (Staubli), robot controller, desktop computer, near-field probe, probe alignment sensor, and the SAM phantom containing the head or body equivalent material. The robot is a six-axis industrial robot, performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure 3-1).

3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, A/D conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal from the DAE and transfers data to the PC card.

3.3 System Electronics




Figure 3-1 SAR Measurement System Setup

The DAE consists of a highly sensitive electrometer-grade auto-zeroing preamplifier, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

FCC ID: A3LSGHI777		 SAR COMPLIANCE REPORT 		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 5 of 50

3.4 Automated Test System Specifications

Test Software: SPEAG DASY4 version 4.7 Measurement Software
Robot: Stäubli Unimation Corp. Robot RX60L
Repeatability: 0.02 mm
No. of Axes: 6

Data Acquisition Electronic System (DAE)

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic
Software: SEMCAD software
Connecting Lines: Optical Downlink for data and status info
Optical upload for commands and clock

PC Interface Card

Function: Link to DAE
16-bit A/D converter for surface detection system
Two Serial & Ethernet link to robotics
Direct emergency stop output for robot

Phantom

Type: SAM Twin Phantom (V4.0)
Shell Material: Composite
Thickness: 2.0 ± 0.2 mm



Figure 3-2
SAR Measurement System

4.1 Probe Measurement System



Figure 4-1
SAR System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration (see Figure 4-3) and optimized for dosimetric evaluation [9]. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2nd order curve fitting (see Figure 5-1). The approach is stopped at reaching the maximum.

4.2 Probe Specifications

Model(s):	ES3DV2, ES3DV3, EX3DV4
Frequency	10 MHz – 6.0 GHz (EX3DV4)
Range:	10 MHz – 4 GHz (ES3DV3, ES3DV2)
Calibration:	In head and body simulating tissue at Frequencies from 300 up to 6000MHz
Linearity:	± 0.2 dB (30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB (30 MHz to 4 GHz) for ES3DV3, ES3DV2
Dynamic Range:	10 mW/kg – 100 W/kg
Probe Length:	330 mm
Probe Tip	
Length:	20 mm
Body Diameter:	12 mm
Tip Diameter:	2.5 mm (3.9mm for ES3DV3)
Tip-Center:	1 mm (2.0 mm for ES3DV3)
Application:	SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields



Figure 4-2
Near-Field Probe



Figure 4-3
Triangular Probe Configuration

FCC ID: A3LSGHI777		PCTEST ENGINEERING LABORATORY, INC.		SAR COMPLIANCE REPORT		SAMSUNG		Reviewed by:
Filename:		Test Dates:		EUT Type:				Quality Manager
OY1106281089.A3L		07/05/11 - 07/07/11		850/1900 GSM/GPRS/EDGE/WCDMA/HS-PA Phone with RFID, Bluetooth and WLAN				Page 7 of 50

5 PROBE CALIBRATION PROCESS

5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm².

5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

σ = simulated tissue conductivity,

ρ = Tissue density (1.25 g/cm³ for brain tissue)

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.




Figure 5-1 E-Field and Temperature measurements at 900MHz [9]




Figure 5-2 E-Field and temperature measurements at 1.9GHz [9]

FCC ID: A3LSGHI777		 PCTEST ENGINEERING LABORATORY, INC.		SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 8 of 50

6 PHANTOM AND EQUIVALENT TISSUES

6.1 SAM Phantoms



Figure 6-1
SAM Phantoms

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to represent the 90th percentile of the population [12][13]. The phantom enables the dosimetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

6.2 Tissue Simulating Mixture Characterization




Figure 6-2
SAM Phantom with
Simulating Tissue

Table 6-1
Composition of the Tissue Equivalent Matter

Frequency (MHz)	835	835	1900	1900	2450	2450	5200-5800	5200-5800
Tissue	Head	Body	Head	Body	Head	Body	Head	Body
Ingredients (% by weight)								
Bactericide	0.1	0.1						
DGBE			44.92	29.44	7.99	26.7		
HEC	1	1						
NaCl	1.45	0.94	0.18	0.39	0.16	0.1		
Sucrose	57	44.9						
Triton X-100					19.97		17.24	10.67
Diethyleneglycol monohexylether							17.24	10.67
Water	40.45	53.06	54.9	70.17	71.88	73.2	65.52	78.66

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 9 of 50

7 DOSIMETRIC ASSESSMENT & PHANTOM SPECS

7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR distribution at the exposed side of the head was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during testing the 1 gram cube. This fixed point was measured and used as a reference value.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual for more details):
 - a. The data was extrapolated to the surface of the outer-shell of the phantom. The combined distance extrapolated was the combined distance from the center of the dipoles 2.7mm away from the tip of the probe housing plus the 1.2 mm distance between the surface and the lowest measuring point. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete. If the value deviated by more than 5%, the evaluation was repeated.
5. For 5 GHz testing finer resolution zoom scans were preformed as specified by FCC SAR Measurement Requirements for 3 – 6 GHz, KDB pub 865664. The 5 GHz zoom scan requires a minimum volume of 24mm x 24mm x 20mm and 7 x 7 x 11 points.




Figure 7-1
Sample SAR Area Scan

7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Figure 7-2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimize reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15 cm.



Figure 7-2
SAM Twin Phantom Shell

FCC ID: A3LSGHI777		 PCTEST ENGINEERING LABORATORY, INC.		SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 10 of 50

8

DEFINITION OF REFERENCE POINTS

8.1 EAR REFERENCE POINT

Figure 8-1 shows the front, back and side views of the SAM Twin Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 8-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 8-2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 8-1
Close-Up Side view
of ERP

8.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Figure 8-3). The "test device reference point" was then located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at its top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 8-2
Front, back and side view of SAM Twin Phantom




Figure 8-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSGHI777		 SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 11 of 50
© 2011 PCTEST Engineering Laboratory, Inc.					REV 9.2M

9 TEST CONFIGURATION POSITIONS

9.1 Device Holder

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

9.2 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 9-1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 9-2).

9.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 9-2).

FCC ID: A3LSGHI777		 PCTEST ENGINEERING LABORATORY, INC.		SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 12 of 50




Figure 9-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 9-3
Side view w/ relevant markings



Figure 9-4 Body SAR Sample Photo
(Not Actual EUT)

9.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. It has been known for some time that there are SAR measurement difficulties in these regions of the SAM phantom. SAR probes are calibrated in tissue equivalent liquids with sufficient separation between the probe sensors and nearby physical boundaries to ensure scattering does not affect probe calibration. When the probe tip is moved into tight regions with multiple boundaries surrounding its sensors, probe calibration and measurement accuracy can become questionable. In addition, these measurement locations often require a probe to be tilted at steep angles, where it may no longer comply with calibration requirements and measurement protocols, or satisfy the required measurement uncertainty. In some situations it is not feasible to tilt the probe or rotate the phantom, as suggested by measurement standards, to conduct these measurements.




Figure 9-5
SAR Scans near the Jaw/Mouth

In order to ensure there is sufficient conservativeness for ensuring compliance until practical solutions are available, additional measurement considerations are necessary to address these technical difficulties. When measurements are required near the mouth, nose, jaw or similar tight regions of the SAM phantom, area or zoom scans are often unable to fully enclose the peak SAR location as required by IEEE 1528

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSWA Phone with RFID, Bluetooth and WLAN		Page 13 of 50

and Supplement C, due to probe orientation and positioning difficulties. Even when limited measurements are possible, the test results could be questionable due to probe calibration and measurement uncertainty issues. Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document publication 648474. The SAR required in these regions of SAM should be measured using a flat phantom. **Rectangular shaped phones** should be positioned with its bottom edge positioned from the flat phantom with the same distance provided by the cheek touching position using SAM. The ear reference point (ERP, as defined for SAM) of the phone should be positioned ½ cm from the flat phantom shell. **Clam-shell phones** should be positioned with the hinge against a smooth edge of the flat phantom where the upper half of the phone is unfolded and extended beyond the phantom side wall. The lower half of the phone is secured in the test device holder at a fixed distance below the flat phantom determined by the minimum separation along the lower edge of the phone in the cheek touching position using SAM. Any case with substantial variation in separation distance along the lower edge of a clam shell is discussed with the FCC for best-to-use methodology.

The flat phantom data should allow test results to be compared uniformly across measurement systems, until suitable solutions are available in measurement standards to address certain probe calibration and positioning issues, due to implementation differences between horizontal and upright SAM configurations. These flat phantom procedures are only applicable for stand-alone SAR evaluation in tight regions of the SAM phantom, where measurement is not feasible or test results can be questionable due to probe calibration and accessibility issues. Details on device positioning and photos showing how separation distances are determined are included in the SAR report Photographs. SAR for other regions of the head must be evaluated using SAM; therefore, a phone with antennas at different locations may require flat and SAM phantom evaluation for the different antennas.

9.5 Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9-4). A device with a headset output is tested with a headset connected to the device.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HS-PA Phone with RFID, Bluetooth and WLAN				Page 14 of 50	

10 FCC RF EXPOSURE LIMITS

10.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

10.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 10-1

SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
SPATIAL PEAK SAR Brain	1.6	8.0
SPATIAL AVERAGE SAR Whole Body	0.08	0.4
SPATIAL PEAK SAR Hands, Feet, Ankles, Wrists	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 15 of 50	

11 FCC 3G MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

11.1 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB 941225 D01 "SAR Measurement Procedures for 3G Devices v02".

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. Any power drifts of greater than 5% were repeated.

11.2 SAR Measurement Conditions for WCDMA per FCC KDB Pub. 941225 D01

11.2.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

11.2.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

11.2.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

11.2.4 SAR Measurements for Handsets with Rel 5 HSDPA

Body SAR for HSDPA is not required for handsets with HSDPA capabilities when the maximum average output power of each RF channel with HSDPA active is less than 0.25 dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration measured in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that resulted in the highest SAR in 12.2 kbps RMC mode for that RF channel.

The H-set used in FRC for HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HSPDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the applicable H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the FRC for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 2 ms to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors of $\beta_c=9$ and $\beta_d=15$, and

FCC ID: A3LSGHI777		 SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 16 of 50

power offset parameters of $\Delta_{ACK} = \Delta_{NACK} = 5$ and $\Delta_{CQI} = 2$ is used. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the FRC.

11.2.5 SAR Measurements for Handsets with Rel 6 HSUPA

Body SAR for HSUPA is not required when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25 dB higher than as measured without

HSUPA/HSDPA using 12.2 kbps RMC and maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise SAR is measured on the maximum output channel for the body exposure configuration produced highest SAR in 12.2 kbps RMC for that RF channel, using the additional procedures under "Release 6 HSPA data devices"

Head SAR for VOIP operations under HSPA is not required when maximum average output of each RF channel with HSPA is less than 0.25 dB higher than as measured using 12.2 kbps RMC. Otherwise SAR is measured using same HSPA configuration as used for body SAR.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

FCC ID: A3LSGH177		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 17 of 50

11.3 RF Conducted Powers

11.3.1 GSM Conducted Powers

		Maximum Burst-Averaged Output Power				
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	32.38	32.37	30.40	26.25	26.13
	190	32.36	32.35	30.37	26.30	26.16
	251	32.51	32.46	30.45	26.41	26.24
GSM 1900	512	29.73	29.64	27.85	25.38	25.62
	661	29.72	29.68	27.87	25.42	25.61
	810	29.85	29.80	27.94	25.54	25.73

		Calculated Maximum Frame-Averaged Output Power				
		Voice	GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
GSM 850	128	23.35	23.34	24.38	17.22	20.11
	190	23.33	23.32	24.35	17.27	20.14
	251	23.48	23.43	24.43	17.38	20.22
GSM 1900	512	20.70	20.61	21.83	16.35	19.60
	661	20.69	20.65	21.85	16.39	19.59
	810	20.82	20.77	21.92	16.51	19.71

Note: Both burst-averaged and calculated frame-averaged powers are included. The bolded GPRS/EDGE modes were selected according to the highest frame-averaged output power table per KDB Publication 941225 D03.

The conducted Powers of GPRS/EDGE (GMSK) were measured with CS1 and the EDGE (8-PSK) conducted powers were measured with MCS7.

GSM Class: B
GPRS Multislot class: 10 (max 2 Tx Uplink slots)
EDGE Multislot class: 10 (max 2Tx Uplink slots)
DTM Multislot Class: N/A

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by:
Filename:		Test Dates:		EUT Type:				Quality Manager
0Y1106281089.A3L		07/05/11 - 07/07/11		850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 18 of 50

11.3.2 WCDMA/HSPA Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			β_c	β_d	MPR
			4132	4183	4233	9262	9400	9538			
99	WCDMA	12.2 kbps RMC	22.58	22.52	22.49	22.46	22.47	22.36	-	-	-
99		12.2 kbps AMR	22.60	22.48	22.51	22.43	22.40	22.28	-	-	-
6	HSDPA	Subtest 1	22.54	22.38	22.39	22.27	22.26	22.13	2	15	0
6		Subtest 2	21.47	21.32	21.25	21.05	21.00	21.03	11	15	0
6		Subtest 3	21.04	20.90	20.85	20.67	20.70	20.54	15	8	0.5
6		Subtest 4	20.73	20.60	20.56	20.15	20.22	20.06	15	4	0.5
6	HSUPA	Subtest 1	21.42	21.23	21.24	20.96	21.00	20.88	10	15	0
6		Subtest 2	19.38	19.30	19.34	18.45	18.41	18.38	6	15	2
6		Subtest 3	20.18	20.03	20.04	18.96	18.98	18.93	15	9	1
6		Subtest 4	19.74	19.54	19.62	18.69	18.67	18.62	2	15	2
6		Subtest 5	21.45	21.35	21.34	21.06	21.11	21.01	14	15	0

WCDMA mode in Body SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01. HSPA SAR tests were not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

MPR for some HSUPA subtests may be more than expected (i.e. up to 2.5 dB more power reduction possible than 3GPP expected MPR, but also as low as 0 dB power reduction) according to the Qualcomm chipset implementation in this model. Detailed information is included in the operational description explaining how the MPR is applied for this model.

This device is only capable of HSUPA in the uplink (QPSK in the uplink), but is capable of HSPA+ in the downlink. Information about the uplink and downlink capabilities are explained in further detail in the technical descriptions for this model.



Figure 11-1
Power Measurement Setup

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 19 of 50

12 SAR TESTING WITH IEEE 802.11 TRANSMITTERS

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

12.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

12.2 Frequency Channel Configurations [27]

802.11 a/b/g are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz §15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. These are referred to as the "default test channels". 802.11g/n modes were evaluated only if the output power was 0.25 dB higher than the 802.11b/802.11a modes.

Table 12-1
802.11 Test Channels per FCC Requirements

Mode	GHz	Channel	Turbo Channel	"Default Test Channels"			
				§15.247	802.11b	802.11g	UNII
802.11 b/g	2.412	1		✓	✓		
	2.437	6		✓	✓		
	2.462	11		✓	✓		
802.11a	5.18	36					✓
	5.20	40	42 (5.21 GHz)				*
	5.22	44					*
	5.24	48	50 (5.25 GHz)				✓
	5.26	52					✓
	5.28	56	58 (5.29 GHz)				*
	5.30	60					*
	5.32	64					✓
	5.500	100	Unknown				*
	5.520	104					✓
	5.540	108					*
	5.560	112					*
	5.580	116					✓
	5.600	120					*
	5.620	124					✓
	5.640	128					*
	5.660	132					*
	5.680	136					✓
	5.700	140					*
UNII or §15.247	5.745	149		✓			✓
	5.765	153	152 (5.76 GHz)		*		*
	5.785	157		✓			*
	5.805	161	160 (5.80 GHz)		*		✓
§15.247	5.825	165		✓			

Table 12-2
IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1	17.23	17.18	17.16	17.36
802.11b	2437	6	17.39	17.35	17.38	17.36
802.11b	2462	11	17.47	17.46	17.46	17.42

Table 12-3
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	13.61	13.67	13.65	13.71	13.72	13.69	13.67	13.61
802.11g	2437	6	13.78	13.76	13.82	13.81	13.82	13.76	13.84	13.72
802.11g	2462	11	13.88	13.79	13.76	13.84	13.83	13.85	13.81	13.83

Table 12-4
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	20	26	39	52	58	65
802.11n	2412	1	11.62	11.67	11.61	11.64	11.59	11.62	11.64	11.59
802.11n	2437	6	11.78	11.72	11.76	11.71	11.86	11.84	11.74	11.78
802.11n	2462	11	11.91	11.84	11.94	11.87	11.98	11.95	11.92	11.93

Table 12-5
IEEE 802.11a Average RF Power

Mode	Freq [MHz]	Channel	Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11a	5180	36	12.35	12.37	12.42	12.48	12.49	12.41	12.44	12.37
802.11a	5200	40	12.41	12.36	12.41	12.36	12.44	12.38	12.33	12.45
802.11a	5220	44	12.24	12.26	12.37	12.42	12.43	12.36	12.38	12.31
802.11a	5240	48	12.37	12.38	12.26	12.33	12.31	12.46	12.34	12.26
802.11a	5260	52	12.08	12.13	12.15	12.18	12.17	12.11	12.26	12.24
802.11a	5280	56	12.02	12.04	12.04	11.96	11.93	12.05	12.03	12.01
802.11a	5300	60	11.99	11.94	11.92	12.04	12.01	12.06	11.95	11.97
802.11a	5320	64	11.78	11.66	11.78	11.83	11.75	11.69	11.72	11.84
802.11a	5500	100	12.03	12.06	11.98	11.95	12.04	12.01	11.97	12.04
802.11a	5520	104	11.93	11.89	11.92	12.03	12.01	11.98	11.93	12.03
802.11a	5540	108	11.73	11.82	11.76	11.82	11.77	11.71	11.84	11.73
802.11a	5560	112	11.58	11.62	11.59	11.52	11.63	11.68	11.62	11.71
802.11a	5580	116	11.47	11.52	11.43	11.48	11.42	11.53	11.51	11.49
802.11a	5600	120	11.36	11.42	11.44	11.37	11.25	11.33	11.41	11.38
802.11a	5620	124	11.41	11.29	11.32	11.36	11.28	11.22	11.34	11.31
802.11a	5640	128	11.23	11.27	11.16	11.18	11.28	11.21	11.16	11.12
802.11a	5660	132	11.14	11.17	11.12	11.06	11.02	11.07	11.05	11.11
802.11a	5680	136	11.23	11.18	11.16	11.21	11.14	11.12	11.17	11.07
802.11a	5700	140	11.13	11.11	11.17	11.18	11.04	11.08	11.12	11.17
802.11a	5745	149	12.37	12.16	12.23	12.21	12.34	12.21	12.24	12.31
802.11a	5765	153	12.21	12.26	12.28	12.41	12.22	12.23	12.14	12.21
802.11a	5785	157	12.13	12.13	12.24	12.17	12.19	12.11	12.03	12.07
802.11a	5805	161	12.31	12.41	12.28	12.33	12.39	12.41	12.32	12.26
802.11a	5825	165	12.25	12.38	12.37	12.24	12.21	12.28	12.31	12.26

Table 12-6
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	20	26	39	52	58	65
802.11n	5180	36	9.97	9.99	10.18	10.23	10.21	10.18	10.05	10.11
802.11n	5200	40	10.01	10.02	10.04	10.07	10.19	10.16	10.11	10.14
802.11n	5220	44	10.01	9.95	9.98	10.02	10.05	10.02	9.95	9.97
802.11n	5240	48	9.89	9.79	9.82	10.02	9.97	10.09	10.05	10.02
802.11n	5260	52	10.03	10.02	10.06	9.97	9.98	10.02	10.01	9.94
802.11n	5280	56	9.84	9.82	10.02	10.10	9.96	9.91	9.96	10.02
802.11n	5300	60	9.72	9.74	9.81	9.81	9.71	9.95	10.02	10.01
802.11n	5320	64	9.47	9.55	9.41	9.47	9.52	9.64	9.58	9.53
802.11n	5500	100	9.81	9.84	9.85	10.01	10.02	9.96	9.91	9.99
802.11n	5520	104	9.76	9.71	9.74	9.84	9.81	9.72	9.84	9.81
802.11n	5540	108	9.64	9.66	9.79	9.81	9.76	9.72	9.74	9.71
802.11n	5560	112	9.69	9.57	9.52	9.54	9.63	9.61	9.63	9.57
802.11n	5580	116	9.43	9.44	9.31	9.36	9.29	9.26	9.28	9.33
802.11n	5600	120	9.23	9.28	9.21	9.24	9.27	9.16	9.19	9.24
802.11n	5620	124	9.09	9.12	9.14	9.06	9.16	9.17	9.06	9.12
802.11n	5640	128	9.03	9.06	9.12	9.14	9.05	9.02	8.94	8.99
802.11n	5660	132	9.01	9.04	8.95	8.92	9.02	9.01	9.03	8.94
802.11n	5680	136	9.04	9.12	9.14	9.04	9.01	9.02	8.94	9.05
802.11n	5700	140	8.94	8.91	9.03	9.12	9.04	9.01	9.02	9.04
802.11n	5745	149	11.56	11.67	11.73	11.63	11.69	11.62	11.53	11.62
802.11n	5765	153	11.97	11.84	11.96	11.96	12.04	12.01	11.95	11.93
802.11n	5785	157	11.84	11.94	11.91	12.03	12.01	11.94	11.92	11.96
802.11n	5805	161	11.56	11.62	11.84	11.76	11.72	11.56	11.69	11.74
802.11n	5825	165	11.65	11.59	11.57	11.69	11.72	11.69	11.58	11.62

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes:

- For 2.4 GHz WLAN, Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
- For 5 GHz WLAN, Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
- The bolded configurations were tested for SAR.




Figure 12-1
Power Measurement Setup

FCC ID: A3LSGHI777			SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 22 of 50

13 FCC PERSONAL WIRELESS ROUTER CONFIGURATIONS

13.1 Personal Wireless Router Considerations

Some battery-operated handsets have the capability to transmit and receive internet connectivity through simultaneous transmission of WIFI in conjunction with a separate licensed transmitter. The FCC has provided guidance in KDB Publication 941225 D06 where SAR test considerations are based on a composite test separation distance of 10 mm from the edges, front and back of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

13.2 SAR Test Setup for Personal Wireless Router Features

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. Therefore, SAR must be evaluated for each frequency transmission and mode separately and summed with the WIFI transmitter according to KDB 648474 publication procedures. Therefore, the measurements were performed for each standalone transmitter for the required exposure conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were valid within a single transmission frequency.

13.3 Power Reduction for Portable Hotspot Mode

This model does not support any power reduction for portable hotspot mode.

FCC ID: A3LSGHI777		 SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 23 of 50

13.4 SAR Test Configurations

Table 13-1
Mobile Hotspot Sides for SAR Testing

Mobile Hotspot Sides for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	Yes	No
GPRS 1900	Yes	Yes	No	Yes	Yes	No
WCDMA 850	Yes	Yes	No	Yes	Yes	No
WCDMA 1900	Yes	Yes	No	Yes	Yes	No
2.4 GHz WLAN	Yes	Yes	No	Yes	No	Yes

When Hotspot mode is enabled, 5 GHz WLAN is disabled.




Figure 13-1 Identification of Sides for SAR Testing (Back View)

Note: Per FCC KDB Publication 941225 D06, the edges with antennas within 2.5 cm are required to be evaluated for SAR. See Figure 13-1 for distances of the actual device.

FCC ID: A3LSGHI777			SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 24 of 50
© 2011 PCTEST Engineering Laboratory, Inc.						REV 9.2M

14 SYSTEM VERIFICATION

14.1 Tissue Verification

Table 14-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
07/05/2011	835H	820	0.871	41.32	0.898	41.571	-3.01%	-0.60%
		835	0.878	41.23	0.900	41.500	-2.44%	-0.65%
		850	0.895	41.06	0.916	41.500	-2.29%	-1.06%
07/05/2011	835B	820	0.971	55.41	0.969	55.284	0.21%	0.23%
		835	0.973	55.23	0.970	55.200	0.31%	0.05%
		850	0.992	55.14	0.988	55.154	0.40%	-0.03%
07/05/2011	1900H	1850	1.347	38.63	1.400	40.000	-3.79%	-3.42%
		1880	1.377	38.55	1.400	40.000	-1.64%	-3.63%
		1910	1.408	38.43	1.400	40.000	0.57%	-3.93%
07/05/2011	1900B	1850	1.521	51.94	1.520	53.300	0.07%	-2.55%
		1880	1.525	52.08	1.520	53.300	0.33%	-2.29%
		1910	1.552	51.44	1.520	53.300	2.11%	-3.49%
07/05/2011	2450H	2401	1.807	37.58	1.758	39.298	2.79%	-4.37%
		2450	1.875	37.43	1.800	39.200	4.17%	-4.52%
		2499	1.932	37.28	1.852	39.135	4.32%	-4.74%
07/05/2011	2450B	2401	1.822	51.95	1.903	52.765	-4.26%	-1.54%
		2450	1.905	51.77	1.950	52.700	-2.31%	-1.76%
		2499	1.963	51.62	2.019	52.638	-2.77%	-1.93%
07/07/2011	5200H-5800H	5170	4.716	35.54	4.629	36.030	1.88%	-1.36%
		5210	4.780	35.43	4.670	35.990	2.36%	-1.56%
		5250	4.841	35.38	4.710	35.950	2.78%	-1.59%
		5270	4.842	35.34	4.730	35.930	2.37%	-1.64%
		5310	4.876	35.21	4.770	35.890	2.22%	-1.89%
		5350	4.906	35.13	4.810	35.850	2.00%	-2.01%
		5470	5.076	34.94	4.934	35.695	2.88%	-2.12%
		5510	5.146	34.87	4.976	35.635	3.42%	-2.15%
		5550	5.153	34.82	5.018	35.575	2.69%	-2.12%
		5570	5.200	34.75	5.039	35.545	3.20%	-2.24%
		5610	5.228	34.71	5.080	35.490	2.91%	-2.20%
		5650	5.288	34.59	5.120	35.450	3.28%	-2.43%
		5670	5.302	34.70	5.140	35.430	3.15%	-2.06%
		5710	5.341	34.44	5.180	35.390	3.11%	-2.68%
		5750	5.403	34.45	5.220	35.350	3.51%	-2.55%
		5770	5.402	34.48	5.240	35.330	3.09%	-2.41%
		5810	5.468	34.33	5.281	35.290	3.54%	-2.72%
		5850	5.499	34.25	5.323	35.250	3.31%	-2.84%
07/06/2011	5200B-5800B	5170	5.255	47.07	5.264	49.055	-0.17%	-4.05%
		5210	5.330	47.06	5.311	49.001	0.36%	-3.96%
		5250	5.392	47.08	5.358	48.946	0.63%	-3.81%
		5270	5.388	46.92	5.381	48.919	0.13%	-4.09%
		5310	5.475	46.80	5.428	48.865	0.87%	-4.23%
		5350	5.534	46.83	5.470	48.811	1.17%	-4.06%
		5470	5.656	46.46	5.615	48.648	0.73%	-4.50%
		5510	5.792	46.55	5.661	48.594	2.31%	-4.21%
		5550	5.798	46.44	5.708	48.539	1.58%	-4.32%
		5570	5.803	46.33	5.731	48.512	1.26%	-4.50%
		5610	5.877	46.26	5.778	48.458	1.71%	-4.54%
		5650	5.898	46.20	5.825	48.404	1.25%	-4.55%
		5670	5.934	46.19	5.848	48.376	1.47%	-4.52%
		5710	6.034	46.19	5.895	48.322	2.36%	-4.41%
		5750	6.041	45.91	5.942	48.268	1.67%	-4.89%
		5770	6.092	45.99	5.965	48.241	2.13%	-4.67%
		5810	6.150	45.96	6.012	48.186	2.30%	-4.62%
		5850	6.226	45.77	6.058	48.132	2.77%	-4.91%

Note: KDB Publication 450824 was ensured to be applied for probe calibration frequencies greater than or equal to 50 MHz of the DUT frequencies.

The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies (per IEEE 1528 6.6.1.2). The SAR test plots may slightly differ from the table above since the DASY software rounds to three significant digits.

Probe calibration used within ± 100 MHz of the test frequency in either 5.725 - 5.85 or 5.47-5.725 GHz is acceptable per KDB Publication 865664 since the design of the SAR probe supports the extended frequency, provided the DASY software version recommended is used for the tests, and the expanded calibration uncertainty (k=2) is less than or equal to 15% (See SAR probe calibration certificate for this information). The dielectric and conductivities measured are within 10% and 5% respectively of the target parameters specified in Supplement C 01-01.

14.2 Measurement Procedure for Tissue verification

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity , for example from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSMA Phone with RFID, Bluetooth and WLAN				Page 26 of 50	

14.3 Test System Verification

Prior to assessment, the system is verified to $\pm 10\%$ of the manufacturer SAR measurement on the reference dipole at the time of calibration.

Table 14-2
System Verification Results

System Verification TARGET & MEASURED										
Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Tissue Frequency (MHz)	Dipole SN	Tissue Type	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation (%)
07/05/2011	22.9	21.5	0.100	835	4d047	Head	0.986	9.530	9.860	3.46%
07/05/2011	23.2	21.7	0.100	835	4d047	Body	1.02	9.850	10.200	3.55%
07/05/2011	24.9	23.9	0.040	1900	502	Head	1.55	40.200	38.750	-3.61%
07/05/2011	24.3	23.2	0.040	1900	502	Body	1.6	41.100	40.000	-2.68%
07/05/2011	23.1	21.9	0.0158	2450	797	Head	0.901	53.300	57.025	6.99%
07/05/2011	24.1	23.0	0.0158	2450	797	Body	0.791	52.300	50.063	-4.28%
07/07/2011	24.2	22.5	0.025	5200	1057	Head	2.22	83.100	88.800	6.86%
07/06/2011	22.8	21.4	0.025	5200	1057	Body	1.94	77.700	77.600	-0.13%
07/07/2011	24.3	22.8	0.025	5500	1057	Head	2.34	90.100	93.600	3.88%
07/06/2011	24.0	22.3	0.025	5500	1057	Body	2.1	84.400	84.000	-0.47%
07/07/2011	24.5	22.9	0.025	5800	1057	Head	2.1	82.900	84.000	1.33%
07/06/2011	22.9	22.0	0.025	5800	1057	Body	1.8	75.000	72.000	-4.00%




Figure 14-1
System Verification Setup Diagram



Figure 14-2
System Verification Setup Photo

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 27 of 50
© 2011 PCTEST Engineering Laboratory, Inc.								REV 9.21

15 SAR DATA SUMMARY

Table 15-1
GSM 850 Head SAR Results

MEASUREMENT RESULTS							
FREQUENCY		Mode/Band	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	SAR (1g)
MHz	Ch.						(W/kg)
836.60	190	GSM 850	32.36	0.03	Right	Touch	0.357
836.60	190	GSM 850	32.36	0.06	Right	Tilt	0.254
836.60	190	GSM 850	32.36	0.06	Left	Touch	0.328
836.60	190	GSM 850	32.36	0.03	Left	Tilt	0.237
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Head 1.6 W/kg (mW/g) averaged over 1 gram		

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 28 of 50

Table 15-2
GSM 1900 Head SAR Results

MEASUREMENT RESULTS							
FREQUENCY		Mode/Band	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	SAR (1g)
MHz	Ch.						(W/kg)
1880.00	661	GSM 1900	29.72	0.01	Right	Touch	0.217
1880.00	661	GSM 1900	29.72	0.07	Right	Tilt	0.050
1880.00	661	GSM 1900	29.72	-0.10	Left	Touch	0.238
1880.00	661	GSM 1900	29.72	0.06	Left	Tilt	0.052
ANSI / IEEE C95.1 1992 - SAFETY LIMIT					Head		
Spatial Peak					1.6 W/kg (mW/g)		
Uncontrolled Exposure/General Population					averaged over 1 gram		

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 29 of 50

Table 15-3
WCDMA 850 Head SAR Results

MEASUREMENT RESULTS							
FREQUENCY		Mode/Band	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	SAR (1g)
MHz	Ch.						(W/kg)
836.60	4183	WCDMA 850	22.52	0.02	Right	Touch	0.350
836.60	4183	WCDMA 850	22.52	0.01	Right	Tilt	0.230
836.60	4183	WCDMA 850	22.52	0.00	Left	Touch	0.289
836.60	4183	WCDMA 850	22.52	0.06	Left	Tilt	0.204
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Head 1.6 W/kg (mW/g) averaged over 1 gram		

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. WCDMA mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 30 of 50

Table 15-4
WCDMA 1900 Head SAR Results

MEASUREMENT RESULTS							
FREQUENCY		Mode	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	SAR (1g)
MHz	Ch.						(W/kg)
1880.00	9400	WCDMA 1900	22.47	0.04	Right	Touch	0.220
1880.00	9400	WCDMA 1900	22.47	0.00	Right	Tilt	0.068
1880.00	9400	WCDMA 1900	22.47	-0.09	Left	Touch	0.335
1880.00	9400	WCDMA 1900	22.47	0.02	Left	Tilt	0.084
ANSI / IEEE C95.1 1992 - SAFETY LIMIT					Head		
Spatial Peak					1.6 W/kg (mW/g)		
Uncontrolled Exposure/General Population					averaged over 1 gram		

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. WCDMA mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN	Page 31 of 50	

Table 15-5
2.4 GHz WLAN Head SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Data Rate (Mbps)	SAR (1g)
MHz	Ch.								(W/kg)
2462	11	IEEE 802.11b	DSSS	17.47	0.07	Right	Touch	1	0.107
2462	11	IEEE 802.11b	DSSS	17.47	0.07	Right	Tilt	1	0.083
2462	11	IEEE 802.11b	DSSS	17.47	0.00	Left	Touch	1	0.192
2462	11	IEEE 802.11b	DSSS	17.47	0.10	Left	Tilt	1	0.041
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head			
Spatial Peak						1.6 W/kg (mW/g)			
Uncontrolled Exposure/General Population						averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
7. WLAN transmission was verified using a spectrum analyzer.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by:
Filename:		Test Dates:		EUT Type:				Quality Manager
OY1106281089.A3L		07/05/11 - 07/07/11		850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 32 of 50

Table 15-6
5.2 GHz WLAN Head SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Data Rate (Mbps)	SAR (1g)
MHz	Ch.								(W/kg)
5200	40	IEEE 802.11a	OFDM	12.41	0.06	Right	Touch	6	0.028
5200	40	IEEE 802.11a	OFDM	12.41	0.08	Right	Tilt	6	0.026
5200	40	IEEE 802.11a	OFDM	12.41	0.10	Left	Touch	6	0.024
5200	40	IEEE 802.11a	OFDM	12.41	-0.07	Left	Tilt	6	0.019
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
7. WLAN transmission was verified using a spectrum analyzer.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 33 of 50

Table 15-7
5.3 GHz WLAN Head SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Data Rate (Mbps)	SAR (1g)
MHz	Ch.								(W/kg)
5260	52	IEEE 802.11a	OFDM	12.08	0.09	Right	Touch	6	0.034
5260	52	IEEE 802.11a	OFDM	12.08	0.09	Right	Tilt	6	0.029
5260	52	IEEE 802.11a	OFDM	12.08	0.10	Left	Touch	6	0.021
5260	52	IEEE 802.11a	OFDM	12.08	0.05	Left	Tilt	6	0.008
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Head			
Spatial Peak						1.6 W/kg (mW/g)			
Uncontrolled Exposure/General Population						averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
7. WLAN transmission was verified using a spectrum analyzer.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: OY1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 34 of 50

Table 15-8
5.5 GHz WLAN Head SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Data Rate (Mbps)	SAR (1g)
MHz	Ch.								(W/kg)
5500	100	IEEE 802.11a	OFDM	12.03	0.09	Right	Touch	6	0.030
5500	100	IEEE 802.11a	OFDM	12.03	0.09	Right	Tilt	6	0.022
5500	100	IEEE 802.11a	OFDM	12.03	0.07	Left	Touch	6	0.031
5500	100	IEEE 802.11a	OFDM	12.03	0.06	Left	Tilt	6	0.011
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
7. WLAN transmission was verified using a spectrum analyzer.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN						Page 35 of 50

Table 15-9
5.8 GHz WLAN Head SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Data Rate (Mbps)	SAR (1g)
MHz	Ch.								(W/kg)
5745	149	IEEE 802.11a	DSSS	12.37	0.09	Right	Touch	6	0.071
5745	149	IEEE 802.11a	DSSS	12.37	0.09	Right	Tilt	6	0.024
5745	149	IEEE 802.11a	DSSS	12.37	-0.07	Left	Touch	6	0.094
5745	149	IEEE 802.11a	DSSS	12.37	-0.07	Left	Tilt	6	0.068
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Head 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
7. WLAN transmission was verified using a spectrum analyzer.
8. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT					Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 36 of 50	

Table 15-10
GSM Body-Worn and Hotspot SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Spacing	# of GPRS Slots	Side	SAR (1g)
MHz	Ch.								(W/kg)
836.60	190	GSM 850	GPRS	30.37	0.01	1.0 cm	2	back	0.731
836.60	190	GSM 850	GPRS	30.37	-0.01	1.0 cm	2	front	0.552
836.60	190	GSM 850	GPRS	30.37	0.01	1.0 cm	2	bottom	0.312
824.20	128	GSM 850	GPRS	30.40	0.01	1.0 cm	2	right	0.883
836.60	190	GSM 850	GPRS	30.37	0.00	1.0 cm	2	right	0.881
848.80	251	GSM 850	GPRS	30.45	0.00	1.0 cm	2	right	0.900
1880.00	661	GSM 1900	GPRS	27.87	-0.01	1.0 cm	2	back	0.699
1880.00	661	GSM 1900	GPRS	27.87	-0.03	1.0 cm	2	front	0.324
1880.00	661	GSM 1900	GPRS	27.87	0.02	1.0 cm	2	bottom	0.606
1880.00	661	GSM 1900	GPRS	27.87	0.07	1.0 cm	2	right	0.264
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body			
Spatial Peak						1.6 W/kg (mW/g)			
Uncontrolled Exposure/General Population						averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001]
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings. Standard battery was used.
5. Liquid tissue depth was at least 15.0 cm.
6. Device was tested using a fixed spacing. A separation distance of 10 mm is chosen because Grantee has determined that it supports the types of body-worn accessories available in the marketplace to users for this handset.
7. Justification for reduced test configurations per KDB Publication 941225 D03: The source-based time-averaged output power was evaluated for all multi-slot operations. In addition to the worst-case reported, all source-based time-averaged powers within 10% of the worst-case were additionally included in the evaluation.
8. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
9. Top and Left Edges were not tested since the antenna distance from the edge was greater than 2.5 cm per FCC KDB Publication 941225 D06 guidance (see Section 13.4).
10. SAR evaluation requires a single frequency of measurement for valid measurements using the SAR probe and tissue calibrated which are calibrated for specific limited frequency ranges. Therefore, during SAR evaluation it was ensured that the WIFI transmission was disabled by the manufacturer to assess the standalone SAR to be evaluated for SAR. WIFI SAR was separately evaluated to account for the WIFI SAR for portable hotspot exposure conditions (See Section 13).
11. Per FCC KDB Publication 941225 D06, when the same wireless modes and device transmission configurations are required for body-worn accessories and hotspot mode, it is not necessary to additionally test body-worn accessory SAR for the same device orientation. Therefore, the hotspot data for the back side configuration additionally shows body-worn compliance.
12. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGH177			SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/CDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 37 of 50

Table 15-11
WCDMA Body-Worn and Hotspot SAR Results

MEASUREMENT RESULTS								
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Spacing	Side	SAR (1g)
MHz	Ch.							(W/kg)
836.60	4183	WCDMA 850	RMC	22.52	-0.01	1.0 cm	back	0.564
836.60	4183	WCDMA 850	RMC	22.52	0.00	1.0 cm	front	0.422
836.60	4183	WCDMA 850	RMC	22.52	-0.01	1.0 cm	bottom	0.214
836.60	4183	WCDMA 850	RMC	22.52	0.00	1.0 cm	right	0.632
1880.00	9400	WCDMA 1900	RMC	22.47	-0.01	1.0 cm	back	0.777
1880.00	9400	WCDMA 1900	RMC	22.47	-0.01	1.0 cm	front	0.378
1880.00	9400	WCDMA 1900	RMC	22.47	0.01	1.0 cm	bottom	0.718
1880.00	9400	WCDMA 1900	RMC	22.47	-0.06	1.0 cm	right	0.296
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						Body		
Spatial Peak						1.6 W/kg (mW/g)		
Uncontrolled Exposure/General Population						averaged over 1 gram		

Notes:

- The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001]
- All modes of operation were investigated, and worst-case results are reported.
- Tissue parameters and temperatures are listed on the SAR plots.
- Batteries are fully charged for all readings. Standard battery was used.
- Liquid tissue depth was at least 15.0 cm.
- Device was tested using a fixed spacing. A separation distance of 10 mm is chosen because Grantee has determined that it supports the types of body-worn accessories available in the marketplace to users for this handset.
- WCDMA mode in Body SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01. HSPA SAR tests were not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
- Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
- Top and Left Edges were not tested since the antenna distance from the edge was greater than 2.5 cm per FCC KDB Publication 941225 D06 guidance (see Section 13.4).
- SAR evaluation requires a single frequency of measurement for valid measurements using the SAR probe and tissue calibrated which are calibrated for specific limited frequency ranges. Therefore, during SAR evaluation it was ensured that the WIFI transmission was disabled by the manufacturer to assess the standalone SAR to be evaluated for SAR. WIFI SAR was separately evaluated to account for the WIFI SAR for portable hotspot exposure conditions (See Section 13).
- Per FCC KDB Publication 941225 D06, when the same wireless modes and device transmission configurations are required for body-worn accessories and hotspot mode, it is not necessary to additionally test body-worn accessory SAR for the same device orientation. Therefore, the hotspot data for the back side configuration additionally shows body-worn compliance.
- The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: OY1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 38 of 50

Table 15-12
Hotspot and Body-Worn 2.4 GHz Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Spacing	Data Rate (Mbps)	Side	SAR (1g)
MHz	Ch.								(W/kg)
2462	11	IEEE 802.11b	DSSS	17.47	-0.06	1.0 cm	1	back	0.082
2462	11	IEEE 802.11b	DSSS	17.47	-0.03	1.0 cm	1	front	0.112
2462	11	IEEE 802.11b	DSSS	17.47	-0.04	1.0 cm	1	bottom	0.060
2462	11	IEEE 802.11b	DSSS	17.47	0.03	1.0 cm	1	left	0.104
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is was at least 15.0 cm.
6. Device was tested using a fixed spacing. A separation distance of 10 mm is chosen because Grantee has determined that it supports the types of body-worn accessories available in the marketplace to users for this handset.
7. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
8. WLAN transmission was verified using a spectrum analyzer.
9. Top and Right Edges were not tested since the antenna distance from the edge was greater than 2.5 cm per FCC KDB Publication 941225 D06 (see Section 13.4).
10. Per FCC KDB Publication 941225 D06, when the same wireless modes and device transmission configurations are required for body-worn accessories and hotspot mode, it is not necessary to additionally test body-worn accessory SAR for the same device orientation. Therefore, the hotspot data for the back side configuration additionally shows body-worn compliance.
11. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.

FCC ID: A3LSGHI777			SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/CDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 39 of 50

Table 15-13
5 GHz WLAN Body-Worn SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Spacing	Data Rate (Mbps)	Side	SAR (1g)
MHz	Ch.								(W/kg)
5200	40	IEEE 802.11a	OFDM	12.41	0.06	1.0 cm	6	back	0.112
5260	52	IEEE 802.11a	OFDM	12.08	0.09	1.0 cm	6	back	0.087
5500	100	IEEE 802.11a	OFDM	12.03	-0.09	1.0 cm	6	back	0.038
5745	149	IEEE 802.11a	DSSS	12.37	-0.07	1.0 cm	6	back	0.116
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings. Standard battery was used.
5. Liquid tissue depth was at least 15.0 cm.
6. Device was tested using a fixed spacing. A separation distance of 10 mm is chosen because Grantee has determined that it supports the types of body-worn accessories available in the marketplace to users for this handset.
7. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
8. WLAN transmission was verified using a spectrum analyzer.
9. The standard battery cover contains a near field communications (NFC) antenna, and is the only battery cover that comes with the device. All tests were performed using the standard RFID cover. The technical description contains detailed information about the near field communications antenna.
10. When hotspot mode is enabled, 5 GHz WLAN is disabled.

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/CDMA/HSPA Phone with RFID, Bluetooth and WLAN	Page 40 of 50	

16 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

16.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” FCC KDB Publication 648474 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

16.2 FCC Power Tables & Conditions

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P_{Ref}	12	6	5	mW
Device output power should be rounded to the nearest mW to compare with values specified in this table.				

Figure 16-1
Output Power Thresholds for Unlicensed Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	SAR not required: <u>Unlicensed only</u>
Unlicensed Transmitters	When there is no simultaneous transmission – - output ≤ 60/f: SAR not required - output > 60/f: stand-alone SAR required When there is simultaneous transmission – <u>Stand-alone SAR not required when</u> - output $\leq 2 \cdot P_{Ref}$ and antenna is ≥ 5.0 cm from other antennas - output $\leq P_{Ref}$ and antenna is ≥ 2.5 cm from other antennas - output $\leq P_{Ref}$ and antenna is < 2.5 cm from other antennas, each with either output power $\leq P_{Ref}$ or 1-g SAR < 1.2 W/kg <u>Otherwise stand-alone SAR is required</u> When stand-alone SAR is required - test SAR on highest output channel for each wireless mode and exposure condition - if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedures	SAR required: <u>Licensed & Unlicensed</u> - when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas - when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas - when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3 antenna pairs with SAR to peak location separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply

Figure 16-2
SAR Evaluation Requirements for Multiple Transmitter Handsets

FCC ID: A3LSGHI777		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN	Page 41 of 50	

16.3 Multiple Antenna/Transmission Information

The separation between the main antenna and the Bluetooth and WLAN antennas is 23 mm.
RF Conducted Power of Bluetooth Tx is 12.05 mW. RF Conducted Power of WLAN is 55.85 mW.

16.4 Simultaneous Transmission Analysis

Per April 2011 FCC/TCB Workshop Guidance, Bluetooth SAR was not required since it shares the same RF path as WLAN, the conducted power is lower than that of WLAN and the WLAN SAR is <0.4 for all configurations.

2.4 GHz WLAN and 5 GHz WLAN share the same antenna path and cannot transmit simultaneously.

Table 16-1
Simultaneous Transmission Scenario (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.357	0.107	0.464	Head SAR	Right Cheek	0.217	0.107	0.324
	Right Tilt	0.254	0.083	0.337		Right Tilt	0.050	0.083	0.132
	Left Cheek	0.328	0.192	0.520		Left Cheek	0.238	0.192	0.430
	Left Tilt	0.237	0.041	0.278		Left Tilt	0.052	0.041	0.094
Simult Tx	Configuration	WCDMA 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	WCDMA 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.350	0.107	0.457	Head SAR	Right Cheek	0.220	0.107	0.327
	Right Tilt	0.230	0.083	0.313		Right Tilt	0.068	0.083	0.150
	Left Cheek	0.289	0.192	0.481		Left Cheek	0.335	0.192	0.527
	Left Tilt	0.204	0.041	0.245		Left Tilt	0.084	0.041	0.125

The above tables represent a simultaneous 2G/3G Voice Call (Held-To-Ear) with 2.4 GHz WIFI Data.

Table 16-2
Simultaneous Transmission Scenario (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.357	0.071	0.428	Head SAR	Right Cheek	0.217	0.071	0.288
	Right Tilt	0.254	0.029	0.283		Right Tilt	0.050	0.029	0.079
	Left Cheek	0.328	0.094	0.422		Left Cheek	0.238	0.094	0.332
	Left Tilt	0.237	0.068	0.305		Left Tilt	0.052	0.068	0.120
Simult Tx	Configuration	WCDMA 850 SAR (W/kg)	5 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	WCDMA 1900 SAR (W/kg)	5 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.350	0.071	0.421	Head SAR	Right Cheek	0.220	0.071	0.291
	Right Tilt	0.230	0.029	0.259		Right Tilt	0.068	0.029	0.097
	Left Cheek	0.289	0.094	0.383		Left Cheek	0.335	0.094	0.429
	Left Tilt	0.204	0.068	0.272		Left Tilt	0.084	0.068	0.152

The above tables represent a simultaneous 2G/3G Voice Call (Held-To-Ear) with 5 GHz WIFI Data.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HS-PA Phone with RFID, Bluetooth and WLAN				Page 42 of 50	

Table 16-3
Simultaneous Transmission Scenario (Body-Worn with 2.4 GHz WLAN)

Configuration	Mode	2G/3G SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Back Side	GPRS 850	0.731	0.082	0.813
Back Side	GPRS 1900	0.699	0.082	0.781
Back Side	WCDMA 850	0.564	0.082	0.646
Back Side	WCDMA 1900	0.777	0.082	0.859

The above tables represent a simultaneous 2G/3G Voice Call (Body-Worn) with 2.4 GHz WIFI Data.

Table 16-4
Simultaneous Transmission Scenario (Body-Worn with 5 GHz WLAN)

Configuration	Mode	2G/3G SAR (W/kg)	5 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Back Side	GPRS 850	0.731	0.116	0.847
Back Side	GPRS 1900	0.699	0.116	0.815
Back Side	WCDMA 850	0.564	0.116	0.680
Back Side	WCDMA 1900	0.777	0.116	0.893

The above tables represent a simultaneous 2G/3G Voice Call (Body-Worn) with 5 GHz WIFI Data.

Table 16-5
Simultaneous Transmission Scenario (Hotspot)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.731	0.082	0.813	Body SAR	Back	0.699	0.082	0.781
	Front	0.552	0.112	0.664		Front	0.324	0.112	0.436
	Top	-	-	0.000		Top	-	-	0.000
	Bottom	0.312	0.060	0.372		Bottom	0.606	0.060	0.666
	Right	0.900	-	0.900		Right	0.264	-	0.264
	Left	-	0.104	0.104		Left	-	0.104	0.104
Simult Tx	Configuration	WCDMA 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	WCDMA 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.564	0.082	0.646	Body SAR	Back	0.777	0.082	0.859
	Front	0.422	0.112	0.534		Front	0.378	0.112	0.490
	Top	-	-	0.000		Top	-	-	0.000
	Bottom	0.214	0.060	0.274		Bottom	0.718	0.060	0.778
	Right	0.632	-	0.632		Right	0.296	-	0.296
	Left	-	0.104	0.104		Left	-	0.104	0.104

The above tables represent a 2G/3G Hotspot with 2.4 GHz WIFI. When hotspot mode is enabled, 5 GHz WIFI is disabled.

Note: Per FCC KDB Publication 941225 D06, the edges with antennas more than 2.5 cm are not required to be evaluated for SAR ("").

16.5 Simultaneous Transmission Conclusion

The above numerical summed SAR was below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit. Therefore, no volumetric SAR summation is required per FCC KDB Publication 648474.

FCC ID: A3LSGHI777			SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN			Page 44 of 50

17 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85070B	Dielectric Probe Kit	8/22/2010	Annual	8/22/2011	US33020316
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/13/2010	Annual	10/13/2011	3613A00315
Agilent	8753E	(30kHz-6GHz) Network Analyzer	4/21/2011	Annual	4/21/2012	JP38020182
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46110872
Agilent	E5515C	Wireless Communications Test Set	10/8/2010	Annual	10/8/2011	GB46310798
Agilent	E5515C	Wireless Communications Test Set	8/13/2010	Annual	8/13/2011	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/8/2011	Annual	4/8/2012	MY45470194
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/11/2010	Annual	10/11/2011	1833460
Gigatronics	8651A	Universal Power Meter	10/11/2010	Annual	10/11/2011	8650319
Rohde & Schwarz	CMU200	Base Station Simulator	11/11/2010	Annual	11/11/2011	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	6/1/2011	Annual	6/1/2012	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	4/19/2011	Annual	4/19/2012	107826
Rohde & Schwarz	NRVD	Dual Channel Power Meter	4/8/2011	Biennial	4/8/2013	101695
SPEAG	D1765V2	1765 MHz SAR Dipole	6/16/2011	Annual	6/16/2012	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	2/17/2011	Annual	2/17/2012	502
SPEAG	D1900V2	1900 MHz SAR Dipole	8/18/2009	Biennial	8/18/2011	5d080
SPEAG	D2450V2	2450 MHz SAR Dipole	8/27/2009	Biennial	8/27/2011	719
SPEAG	D2450V2	2450 MHz SAR Dipole	2/8/2011	Annual	2/8/2012	797
SPEAG	D2600V2	2600 MHz SAR Dipole	4/15/2011	Annual	4/15/2012	1004
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/19/2009	Biennial	8/19/2011	1007
SPEAG	D5GHzV2	5 GHz SAR Dipole	2/11/2011	Annual	2/11/2012	1057
SPEAG	D835V2	835 MHz SAR Dipole	2/9/2011	Annual	2/9/2012	4d047
SPEAG	D835V2	835 MHz SAR Dipole	8/24/2009	Biennial	8/24/2011	4d026
SPEAG	DAE3	Dasy Data Acquisition Electronics	11/18/2010	Annual	11/18/2011	455
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2011	Annual	3/17/2012	704
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/20/2011	Annual	4/20/2012	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/21/2011	Annual	2/21/2012	649
SPEAG	ES3DV2	SAR Probe	9/21/2010	Annual	9/21/2011	3022
SPEAG	EX3DV4	SAR Probe	8/19/2010	Annual	8/19/2011	3561
SPEAG	EX3DV4	SAR Probe	2/14/2011	Annual	2/14/2012	3550
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/19/2011	Annual	5/19/2012	859
SPEAG	D750V3	750 MHz Dipole	2/14/2011	Annual	2/14/2012	1003
SPEAG	ES3DV3	SAR Probe	3/24/2011	Annual	3/24/2012	3213
SPEAG	ES3DV3	SAR Probe	4/18/2011	Annual	4/18/2012	3209
Rohde & Schwarz	SMIQ03B	Signal Generator	4/6/2011	Annual	4/6/2012	DE27259
SPEAG	D1640V2	1640 MHz Dipole	8/17/2010	Annual	8/17/2011	321
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	8/30/2010	Annual	8/30/2011	100976
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5318
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5442
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	1190013
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	98150041
Agilent	8648D	Signal Generator	4/5/2011	Annual	4/5/2012	3629U00687
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	1070030
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5821
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	8013
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5605
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	2400
Agilent	E5515C	Wireless Communications Test Set	8/13/2010	Annual	8/13/2011	GB43304447
Agilent	E5515C	Wireless Communications Tester	4/21/2011	Annual	4/21/2012	US41140256
Amplifier Research	5S1G4	5W, 800MHz-4.2GHz	N/A			21910
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	N/A			N/A
Agilent	E5515C	Wireless Communications Test Set	2/8/2011	Annual	2/8/2012	GB45360985
SPEAG	D3700V2	3700 MHz SAR Dipole	2/16/2011	Annual	2/16/2012	1002
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	3/11/2011	Annual	3/11/2012	103962
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331322
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331323
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331330
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331332
Control Company	61220-416	Long-Stem Thermometer	3/16/2011	Biennial	3/16/2013	111391601
SPEAG	ES3DV3	SAR Probe	4/8/2011	Annual	4/8/2012	3258
SPEAG	D1750V2	1750 MHz SAR Dipole	5/24/2011	Annual	5/24/2012	1051
MiniCircuits	SLP-2400+	Low Pass Filter	N/A			R8979500903
MiniCircuits	NLP-1.9+	Low Pass Filter	N/A			N/A
Narda	4772-3	Attenuator (3dB)	N/A			9406
Narda	BW-S3W2	Attenuator (3dB)	N/A			120

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager	
Filename: OY1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 45 of 50	
© 2011 PCTEST Engineering Laboratory, Inc.									
REV 9.2M 06/28/2011									

18 MEASUREMENT UNCERTAINTIES

Applicable for 750 – 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							12.1	11.7	299
Expanded Uncertainty (95% CONFIDENCE LEVEL)							24.2	23.5	

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSGHI777		 SAR COMPLIANCE REPORT 		Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 46 of 50

Applicable for 5GHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by: Quality Manager	
Filename: 0Y1106281089.A3L		Test Dates: 07/05/11 - 07/07/11		EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 47 of 50	
© 2011 PCTEST Engineering Laboratory, Inc.								REV 9.2M	

19 CONCLUSION

19.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested. Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSGHI777		 SAR COMPLIANCE REPORT				Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN		Page 48 of 50		

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, June 2001.
- [6] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [7] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [10] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [11] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [12] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [13] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [14] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [15] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [16] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [17] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [18] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT				Reviewed by:
Filename:		Test Dates:		EUT Type:				Quality Manager
OY1106281089.A3L		07/05/11 - 07/07/11		850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 49 of 50

- [19] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [20] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [21] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [22] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [23] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [24] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [25] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002
- [26] FCC SAR Measurement Procedures for 3G Devices KDB Publication 941225
- [27] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227
- [28] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publication 648474
- [29] FCC Application Note for SAR Probe Calibration and System Verification Consideration for Measurements at 150 MHz – 3 GHz, KDB Publication 450824
- [30] FCC SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens, KDB Publication 616217
- [31] FCC SAR Measurement Requirements for 3 – 6 GHz, KDB Publication 865664
- [32] FCC Mobile Portable RF Exposure Procedure, KDB Publication 447498
- [33] FCC SAR Procedures for Dongle Transmitters, KDB Publication 447498
- [34] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [35] FCC SAR Test Considerations for LTE Handsets and Data Modems, KDB Publication 941225.
- [36] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.
- [37] FCC Hot Spot SAR v01, KDB Publication 941225 D06.

FCC ID: A3LSGHI777				SAR COMPLIANCE REPORT			Reviewed by: Quality Manager
Filename: 0Y1106281089.A3L	Test Dates: 07/05/11 - 07/07/11	EUT Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN				Page 50 of 50	

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 850, Right Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.6 V/m

Peak SAR (extrapolated) = 0.453 W/kg

SAR(1 g) = 0.357 mW/g; SAR(10 g) = 0.270 mW/g



0 dB = 0.381mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 850, Right Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.6 V/m

Peak SAR (extrapolated) = 0.453 W/kg

SAR(1 g) = 0.357 mW/g; SAR(10 g) = 0.270 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 850, Right Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.9 V/m

Peak SAR (extrapolated) = 0.319 W/kg

SAR(1 g) = 0.254 mW/g; SAR(10 g) = 0.193 mW/g



0 dB = 0.267mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 850, Left Head, Touch, Mid.ch


Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.77 V/m

Peak SAR (extrapolated) = 0.408 W/kg

SAR(1 g) = 0.328 mW/g; SAR(10 g) = 0.249 mW/g



0 dB = 0.344mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 850, Left Head, Tilt, Mid.ch


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.3 V/m

Peak SAR (extrapolated) = 0.300 W/kg

SAR(1 g) = 0.237 mW/g; SAR(10 g) = 0.181 mW/g



0 dB = 0.248mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 1900, Right Head, Touch, Mid.ch


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.5 V/m

Peak SAR (extrapolated) = 0.363 W/kg

SAR(1 g) = 0.217 mW/g; SAR(10 g) = 0.126 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 1900, Right Head, Tilt, Mid.ch


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.00 V/m

Peak SAR (extrapolated) = 0.089 W/kg

SAR(1 g) = 0.0495 mW/g; SAR(10 g) = 0.028 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 1900, Left Head, Touch, Mid.ch


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.7 V/m

Peak SAR (extrapolated) = 0.378 W/kg

SAR(1 g) = 0.238 mW/g; SAR(10 g) = 0.145 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GSM 1900, Left Head, Tilt, Mid.ch


Area Scan (7x11x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.28 V/m

Peak SAR (extrapolated) = 0.086 W/kg

SAR(1 g) = 0.052 mW/g; SAR(10 g) = 0.030 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Right Head, Touch, Mid.ch


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.0 V/m

Peak SAR (extrapolated) = 0.443 W/kg

SAR(1 g) = 0.350 mW/g; SAR(10 g) = 0.263 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Right Head, Tilt, Mid.ch


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.5 V/m

Peak SAR (extrapolated) = 0.287 W/kg

SAR(1 g) = 0.230 mW/g; SAR(10 g) = 0.176 mW/g



0 dB = 0.242mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Left Head, Touch, Mid.ch


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.74 V/m

Peak SAR (extrapolated) = 0.358 W/kg

SAR(1 g) = 0.289 mW/g; SAR(10 g) = 0.218 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.88 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Left Head, Tilt, Mid.ch


Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.4 V/m

Peak SAR (extrapolated) = 0.257 W/kg

SAR(1 g) = 0.204 mW/g; SAR(10 g) = 0.156 mW/g



0 dB = 0.214mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN; Serial: FI-165-A

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Right Head, Touch, Mid.ch


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.1 V/m

Peak SAR (extrapolated) = 0.366 W/kg

SAR(1 g) = 0.220 mW/g; SAR(10 g) = 0.133 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Right Head, Tilt, Mid.ch


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.76 V/m

Peak SAR (extrapolated) = 0.116 W/kg

SAR(1 g) = 0.0675 mW/g; SAR(10 g) = 0.037 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Left Head, Touch, Mid.ch


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.3 V/m

Peak SAR (extrapolated) = 0.522 W/kg

SAR(1 g) = 0.335 mW/g; SAR(10 g) = 0.207 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Left Head, Touch, Mid.ch


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.3 V/m

Peak SAR (extrapolated) = 0.522 W/kg

SAR(1 g) = 0.335 mW/g; SAR(10 g) = 0.207 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.38 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Left Head, Tilt, Mid.ch


Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.92 V/m

Peak SAR (extrapolated) = 0.134 W/kg

SAR(1 g) = 0.084 mW/g; SAR(10 g) = 0.048 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.89 \text{ mho/m}$; $\epsilon_r = 37.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 23.1 °C; Tissue Temp: 21.9 °C

Probe: ES3DV2 - SN3022; ConvF(4.21, 4.21, 4.21); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Right Head, Touch, Ch 11, 1 Mbps


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.73 V/m

Peak SAR (extrapolated) = 0.182 W/kg

SAR(1 g) = 0.107 mW/g; SAR(10 g) = 0.060 mW/g



0 dB = 0.127mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.89 \text{ mho/m}$; $\epsilon_r = 37.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-05-2011; Ambient Temp: 23.1 °C; Tissue Temp: 21.9 °C

Probe: ES3DV2 - SN3022; ConvF(4.21, 4.21, 4.21); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Right Head, Tilt, Ch 11, 1 Mbps


Area Scan (7x14x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.87 V/m

Peak SAR (extrapolated) = 0.166 W/kg

SAR(1 g) = 0.083 mW/g; SAR(10 g) = 0.040 mW/g



0 dB = 0.106mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.89 \text{ mho/m}$; $\epsilon_r = 37.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 23.1 °C; Tissue Temp: 21.9 °C

Probe: ES3DV2 - SN3022; ConvF(4.21, 4.21, 4.21); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Left Head, Touch, Ch 11, 1 Mbps


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.2 V/m

Peak SAR (extrapolated) = 0.336 W/kg

SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.102 mW/g



0 dB = 0.236mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.89 \text{ mho/m}$; $\epsilon_r = 37.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 23.1 °C; Tissue Temp: 21.9 °C

Probe: ES3DV2 - SN3022; ConvF(4.21, 4.21, 4.21); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Left Head, Touch, Ch 11, 1 Mbps


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.2 V/m

Peak SAR (extrapolated) = 0.336 W/kg

SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.102 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.89 \text{ mho/m}$; $\epsilon_r = 37.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-05-2011; Ambient Temp: 23.1 °C; Tissue Temp: 21.9 °C

Probe: ES3DV2 - SN3022; ConvF(4.21, 4.21, 4.21); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Left Head, Tilt, Ch 11, 1 Mbps


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.39 V/m

Peak SAR (extrapolated) = 0.074 W/kg

SAR(1 g) = 0.041 mW/g; SAR(10 g) = 0.021 mW/g



0 dB = 0.053mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$$f = 5200 \text{ MHz}; \sigma = 4.76 \text{ mho/m}; \epsilon_r = 35.5; \rho = 1000 \text{ kg/m}^3$$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.2 ° C Tissue Temp: 22.5 ° C

Probe: EX3DV4 - SN3550; ConvF(4.06, 4.06, 4.06); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.2 GHz, Right Head, Touch, Ch 40, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.26 V/m

Peak SAR (extrapolated) = 0.157 W/kg

SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.0087 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 4.76 \text{ mho/m}$; $\epsilon_r = 35.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.2 °C Tissue Temp: 22.5 °C

Probe: EX3DV4 - SN3550; ConvF(4.06, 4.06, 4.06); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.2 GHz, Right Head, Tilt, Ch 40, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 1.78 V/m

Peak SAR (extrapolated) = 0.352 W/kg

SAR(1 g) = 0.026 mW/g; SAR(10 g) = 0.00777 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 4.76 \text{ mho/m}$; $\epsilon_r = 35.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.2 ° C Tissue Temp: 22.5° C

Probe: EX3DV4 - SN3550; ConvF(4.06, 4.06, 4.06); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.2 GHz Left Head, Touch, Ch 40, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.16 V/m

Peak SAR (extrapolated) = 0.295 W/kg

SAR(1 g) = 0.024 mW/g; SAR(10 g) = 0.00606 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 4.76 \text{ mho/m}$; $\epsilon_r = 35.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.2° C Tissue Temp: 22.5° C

Probe: EX3DV4 - SN3550; ConvF(4.06, 4.06, 4.06); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.2 GHz Left Head, Tilt, Ch 40, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.56 V/m

Peak SAR (extrapolated) = 0.208 W/kg

SAR(1 g) = 0.019 mW/g; SAR(10 g) = 0.00439 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5260 \text{ MHz}$; $\sigma = 4.84 \text{ mho/m}$; $\epsilon_r = 35.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.2° C Tissue Temp: 22.5° C

Probe: EX3DV4 - SN3550; ConvF(3.92, 3.92, 3.92); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.3 GHz, Right Head, Touch, Ch 52, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.27 V/m

Peak SAR (extrapolated) = 0.423 W/kg

SAR(1 g) = 0.034 mW/g; SAR(10 g) = 0.00826 mW/g



0 dB = 0.058mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5260 \text{ MHz}$; $\sigma = 4.84 \text{ mho/m}$; $\epsilon_r = 35.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.2° C Tissue Temp: 22.5° C

Probe: EX3DV4 - SN3550; ConvF(3.92, 3.92, 3.92); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.3 GHz, Right Head, Tilt, Ch 52, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.56 V/m

Peak SAR (extrapolated) = 0.260 W/kg

SAR(1 g) = 0.029 mW/g; SAR(10 g) = 0.012 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5260 \text{ MHz}$; $\sigma = 4.84 \text{ mho/m}$; $\epsilon_r = 35.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.2° C Tissue Temp: 22.5° C

Probe: EX3DV4 - SN3550; ConvF(3.92, 3.92, 3.92); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.3 GHz Left Head, Touch, Ch 52, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 2.06 V/m

Peak SAR (extrapolated) = 0.266 W/kg

SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.006 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5260 \text{ MHz}$; $\sigma = 4.84 \text{ mho/m}$; $\epsilon_r = 35.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.2° C Tissue Temp: 22.5° C

Probe: EX3DV4 - SN3550; ConvF(3.92, 3.92, 3.92); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.3 GHz Left Head, Tilt, Ch 52, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.13 V/m

Peak SAR (extrapolated) = 0.138 W/kg

SAR(1 g) = 0.00793 mW/g; SAR(10 g) = 0.000912 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN; Serial: FI-165-A

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.13 \text{ mho/m}$; $\epsilon_r = 34.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3550; ConvF(3.77, 3.77, 3.77); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.5 GHz, Right Head, Touch, Ch 100 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 2.26 V/m

Peak SAR (extrapolated) = 0.287 W/kg

SAR(1 g) = 0.030 mW/g; SAR(10 g) = 0.00952 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.13 \text{ mho/m}$; $\epsilon_r = 34.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3550; ConvF(3.77, 3.77, 3.77); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.5 GHz, Right Head, Tilt, Ch 100, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 1.98 V/m

Peak SAR (extrapolated) = 0.267 W/kg

SAR(1 g) = 0.022 mW/g; SAR(10 g) = 0.0067 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.13 \text{ mho/m}$; $\epsilon_r = 34.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3550; ConvF(3.77, 3.77, 3.77); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz Left Head, Touch, Ch 100, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 2.21 V/m

Peak SAR (extrapolated) = 0.343 W/kg

SAR(1 g) = 0.031 mW/g; SAR(10 g) = 0.00981 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.13 \text{ mho/m}$; $\epsilon_r = 34.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3550; ConvF(3.77, 3.77, 3.77); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz Left Head, Tilt, Ch 100, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.13 V/m

Peak SAR (extrapolated) = 0.187 W/kg

SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00244 mW/g



0 dB = 0.031mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 5.4 \text{ mho/m}$; $\epsilon_r = 34.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.5°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(3.64, 3.64, 3.64); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.8 GHz, Right Head, Touch, Ch 149, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 3.77 V/m

Peak SAR (extrapolated) = 0.408 W/kg

SAR(1 g) = 0.071 mW/g; SAR(10 g) = 0.022 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 5.4 \text{ mho/m}$; $\epsilon_r = 34.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 07-07-2011; Ambient Temp: 24.5°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(3.64, 3.64, 3.64); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a 5.8GHz, Right Head, Tilt, Ch 149, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 1.82 V/m

Peak SAR (extrapolated) = 0.277 W/kg

SAR(1 g) = 0.024 mW/g; SAR(10 g) = 0.00749 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone with RFID, Bluetooth and WLAN; Serial: FI-165-A

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 5.4 \text{ mho/m}$; $\epsilon_r = 34.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.5°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(3.64, 3.64, 3.64); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.8 GHz Left Head, Touch, Ch 149, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 5.31 V/m

Peak SAR (extrapolated) = 0.386 W/kg

SAR(1 g) = 0.094 mW/g; SAR(10 g) = 0.030 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 5.4 \text{ mho/m}$; $\epsilon_r = 34.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.5°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(3.64, 3.64, 3.64); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.8 GHz Left Head, Touch, Ch 149, 6 Mbps


Area Scan (10x16x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.31 V/m

Peak SAR (extrapolated) = 0.386 W/kg

SAR(1 g) = 0.094 mW/g; SAR(10 g) = 0.030 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1
Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 5.4 \text{ mho/m}$; $\epsilon_r = 34.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 07-07-2011; Ambient Temp: 24.5°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(3.64, 3.64, 3.64); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.8 GHz Left Head, Tilt, Ch 149, 6 Mbps


Area Scan (10x16x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 4.14 V/m

Peak SAR (extrapolated) = 0.310 W/kg

SAR(1 g) = 0.068 mW/g; SAR(10 g) = 0.021 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 27.8 V/m

Peak SAR (extrapolated) = 0.941 W/kg

SAR(1 g) = 0.731 mW/g; SAR(10 g) = 0.569 mW/g



0 dB = 0.759mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Front side, Mid.ch, 2 Tx Slots


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.4 V/m

Peak SAR (extrapolated) = 0.688 W/kg

SAR(1 g) = 0.552 mW/g; SAR(10 g) = 0.426 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Bottom Edge, Mid.ch, 2 Tx Slots


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.6 V/m

Peak SAR (extrapolated) = 0.561 W/kg

SAR(1 g) = 0.312 mW/g; SAR(10 g) = 0.179 mW/g



0 dB = 0.349mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 848.8 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 55.15$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Right Edge, High.ch, 2 Tx Slots


Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.2 V/m

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.900 mW/g; SAR(10 g) = 0.616 mW/g



0 dB = 0.966mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 848.8 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 848.8 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 55.15$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Right Edge, High.ch, 2 Tx Slots


Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 31.2 V/m

Peak SAR (extrapolated) = 1.29 W/kg

SAR(1 g) = 0.900 mW/g; SAR(10 g) = 0.616 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.8 V/m

Peak SAR (extrapolated) = 1.23 W/kg

SAR(1 g) = 0.699 mW/g; SAR(10 g) = 0.367 mW/g



0 dB = 0.791mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.552 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Front side, Mid.ch, 2 Tx Slots


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.3 V/m

Peak SAR (extrapolated) = 0.561 W/kg

SAR(1 g) = 0.324 mW/g; SAR(10 g) = 0.186 mW/g



0 dB = 0.345mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 2 Tx Slots


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.0 V/m

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.606 mW/g; SAR(10 g) = 0.333 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Right Edge, Mid.ch, 2 Tx Slots


Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.9 V/m

Peak SAR (extrapolated) = 0.467 W/kg

SAR(1 g) = 0.264 mW/g; SAR(10 g) = 0.142 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Back side, Mid.ch


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 24.6 V/m

Peak SAR (extrapolated) = 0.716 W/kg

SAR(1 g) = 0.564 mW/g; SAR(10 g) = 0.440 mW/g



0 dB = 0.587mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Front side, Mid.ch


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 21.3 V/m

Peak SAR (extrapolated) = 0.526 W/kg

SAR(1 g) = 0.422 mW/g; SAR(10 g) = 0.325 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Bottom Edge, Mid.ch


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.4 V/m

Peak SAR (extrapolated) = 0.383 W/kg

SAR(1 g) = 0.214 mW/g; SAR(10 g) = 0.122 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.975 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Right Edge, Mid.ch


Area Scan (5x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.2 V/m

Peak SAR (extrapolated) = 0.899 W/kg

SAR(1 g) = 0.632 mW/g; SAR(10 g) = 0.433 mW/g



0 dB = 0.677mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Back side, Mid.ch


Area Scan (7x12x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.6 V/m

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.777 mW/g; SAR(10 g) = 0.413 mW/g



0 dB = 0.890mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Back side, Mid.ch


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.6 V/m

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.777 mW/g; SAR(10 g) = 0.413 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Front side, Mid.ch


Area Scan (7x12x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.3 V/m

Peak SAR (extrapolated) = 0.591 W/kg

SAR(1 g) = 0.378 mW/g; SAR(10 g) = 0.234 mW/g



0 dB = 0.407mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Bottom Edge, Mid.ch


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.0 V/m

Peak SAR (extrapolated) = 1.26 W/kg

SAR(1 g) = 0.718 mW/g; SAR(10 g) = 0.390 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.525 \text{ mho/m}$; $\epsilon_r = 52.08$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Right Edge, Mid.ch


Area Scan (5x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.4 V/m

Peak SAR (extrapolated) = 0.515 W/kg

SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.159 mW/g



0 dB = 0.334mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-C**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.92 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.1 °C; Tissue Temp: 23.0 °C

Probe: ES3DV2 - SN3022; ConvF(4.06, 4.06, 4.06); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.95 V/m

Peak SAR (extrapolated) = 0.156 W/kg

SAR(1 g) = 0.082 mW/g; SAR(10 g) = 0.043 mW/g



0 dB = 0.101mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-C**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.92 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.1 °C; Tissue Temp: 23.0 °C

Probe: ES3DV2 - SN3022; ConvF(4.06, 4.06, 4.06); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Front Side


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.91 V/m

Peak SAR (extrapolated) = 0.216 W/kg

SAR(1 g) = 0.112 mW/g; SAR(10 g) = 0.061 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-C**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.92 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.1 °C; Tissue Temp: 23.0 °C

Probe: ES3DV2 - SN3022; ConvF(4.06, 4.06, 4.06); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Front Side


Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.91 V/m

Peak SAR (extrapolated) = 0.216 W/kg

SAR(1 g) = 0.112 mW/g; SAR(10 g) = 0.061 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-C**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.92 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.1 °C; Tissue Temp: 23.0 °C

Probe: ES3DV2 - SN3022; ConvF(4.06, 4.06, 4.06); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Bottom Edge


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.91 V/m

Peak SAR (extrapolated) = 0.110 W/kg

SAR(1 g) = 0.060 mW/g; SAR(10 g) = 0.033 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-C**

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.92 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.1 °C; Tissue Temp: 23.0 °C

Probe: ES3DV2 - SN3022; ConvF(4.06, 4.06, 4.06); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch.11, 1 Mbps, Left Edge


Area Scan (5x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 7.86 V/m

Peak SAR (extrapolated) = 0.196 W/kg

SAR(1 g) = 0.104 mW/g; SAR(10 g) = 0.055 mW/g



0 dB = 0.132mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 5.31 \text{ mho/m}$; $\epsilon_r = 47.06$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 22.8 °C; Tissue Temp: 21.4 °C

Probe: EX3DV4 - SN3550; ConvF(3.58, 3.58, 3.58); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.2 GHz, Body SAR, Ch 40, 6 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x1)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0.742 V/m

Peak SAR (extrapolated) = 0.598 W/kg

SAR(1 g) = 0.112 mW/g; SAR(10 g) = 0.035 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5260 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body: Medium parameters used (interpolated):

$f = 5260 \text{ MHz}$; $\sigma = 5.39 \text{ mho/m}$; $\epsilon_r = 47$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 22.8 °C; Tissue Temp: 21.4 °C

Probe: EX3DV4 - SN3550; ConvF(3.31, 3.31, 3.31); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.3 GHz, Body SAR, Ch 52, 6 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0.321 V/m

Peak SAR (extrapolated) = 0.483 W/kg

SAR(1 g) = 0.087 mW/g; SAR(10 g) = 0.026 mW/g



0 dB = 0.173mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body: Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.76 \text{ mho/m}$; $\epsilon_r = 46.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 24.0°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz, Body SAR, Ch 100, 6 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 0.816 V/m

Peak SAR (extrapolated) = 0.200 W/kg

SAR(1 g) = 0.038 mW/g; SAR(10 g) = 0.010 mW/g



PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body: Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 6.04 \text{ mho/m}$; $\epsilon_r = 45.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 22.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3550; ConvF(3.29, 3.29, 3.29); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 149, 6 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Reference Value = 4.48 V/m

Peak SAR (extrapolated) = 0.415 W/kg

SAR(1 g) = 0.116 mW/g; SAR(10 g) = 0.039 mW/g



0 dB = 0.237mW/g

PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSGHI777; Type: 850/1900 GSM/GPRS/EDGE/WCDMA/HSPA Phone
with RFID, Bluetooth and WLAN; Serial: FI-165-A**

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body: Medium parameters used (interpolated):

$f = 5745 \text{ MHz}$; $\sigma = 6.04 \text{ mho/m}$; $\epsilon_r = 45.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 22.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3550; ConvF(3.29, 3.29, 3.29); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 149, 6 Mbps, Back Side


Area Scan (11x17x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 4.48 V/m

Peak SAR (extrapolated) = 0.415 W/kg

SAR(1 g) = 0.116 mW/g; SAR(10 g) = 0.039 mW/g



APPENDIX B: DIPOLE VALIDATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.878 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-05-2011; Ambient Temp: 22.9 °C; Tissue Temp: 21.5 °C

Probe: EX3DV4 - SN3561; ConvF(7.96, 7.96, 7.96); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1403

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

835MHz System Verification


Area Scan (7x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20.0 dBm (100 mW)

SAR(1 g) = 0.986 mW/g; SAR(10 g) = 0.639 mW/g

Deviation = 3.46 %



0 dB = 1.06mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.973 \text{ mho/m}$; $\epsilon_r = 55.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-05-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7 °C

Probe: EX3DV4 - SN3561; ConvF(8.09, 8.09, 8.09); Calibrated: 8/19/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

835MHz System Verification


Area Scan (7x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 20.0 dBm (100 mW)

SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.668 mW/g

Deviation = 3.55 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 502

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.4 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.9°C; Tissue Temp: 23.9°C

Probe: EX3DV4 - SN3550; ConvF(7.01, 7.01, 7.01); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

1900MHz System Verification


Area Scan (5x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 16.0 dBm (40 mW)

SAR(1 g) = 1.55 mW/g; SAR(10 g) = 0.799 mW/g

Deviation = -3.61 %



0 dB = 1.73mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 502

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.54 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.3°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3550; ConvF(6.77, 6.77, 6.77); Calibrated: 2/14/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

1900MHz System Verification


Area Scan (5x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 16 dBm (40 mW)

SAR(1 g) = 1.6 mW/g; SAR(10 g) = 0.825 mW/g

Deviation = -2.68 %



PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.88 \text{ mho/m}$; $\epsilon_r = 37.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 23.1°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.21, 4.21, 4.21); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

2450MHz System Verification


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 12.0 dBm (15.8 mW)

SAR(1 g) = 0.901 mW/g; SAR(10 g) = 0.408 mW/g

Deviation = 6.99%



0 dB = 1.19mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.91 \text{ mho/m}$; $\epsilon_r = 51.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-05-2011; Ambient Temp: 24.1°C; Tissue Temp: 23.0°C

Probe: ES3DV2 - SN3022; ConvF(4.06, 4.06, 4.06); Calibrated: 9/21/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

2450MHz System Verification


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 12.0 dBm (15.8 mW)

SAR(1 g) = 0.791 mW/g; SAR(10 g) = 0.367 mW/g

Deviation = -4.28 %



0 dB = 1.02mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 4.76 \text{ mho/m}$; $\epsilon_r = 35.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-07-2011; Ambient Temp: 24.2 C Tissue Temp: 22.5 C

Probe: EX3DV4 - SN3550; ConvF(4.06, 4.06, 4.06); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5200MHz System Verification


Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Input Power = 14.0 dBm (25 mW)

SAR(1 g) = 2.22 mW/g; SAR(10 g) = 0.626 mW/g

Deviation = 6.86 %



0 dB = 4.64mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 5.31 \text{ mho/m}$; $\epsilon_r = 47.06$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 22.8 °C; Tissue Temp: 21.4 °C

Probe: EX3DV4 - SN3550; ConvF(3.58, 3.58, 3.58); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5200MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 1.94 mW/g; SAR(10 g) = 0.539 mW/g.

Deviation = -0.13 %



0 dB = 4.19mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.13 \text{ mho/m}$; $\epsilon_r = 34.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-07-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.8°C

Probe: EX3DV4 - SN3550; ConvF(3.77, 3.77, 3.77); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5500MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 2.34 mW/g; SAR(10 g) = 0.657 mW/g

Deviation = 3.88%



0 dB = 4.80mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.76 \text{ mho/m}$; $\epsilon_r = 46.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 24.0°C; Tissue Temp: 22.3°C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5500MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11) Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 2.1 mW/g; SAR(10 g) = 0.574 mW/g

Deviation = -0.47%



0 dB = 4.33mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head; Medium parameters used (interpolated):

$f = 5800 \text{ MHz}$; $\sigma = 5.45 \text{ mho/m}$; $\epsilon_r = 34.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-07-2011; Ambient Temp: 24.5°C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(3.64, 3.64, 3.64); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5800MHz System Verification


Area Scan (7x9x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11) Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Input Power = 14 dBm (25 mW)

SAR(1 g) = 2.1 mW/g; SAR(10 g) = 0.581 mW/g

Deviation = 1.33 %



0 dB = 4.45mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5800 \text{ MHz}$; $\sigma = 6.14 \text{ mho/m}$; $\epsilon_r = 46$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-06-2011; Ambient Temp: 22.9°C; Tissue Temp: 22.0°C

Probe: EX3DV4 - SN3550; ConvF(3.29, 3.29, 3.29); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5800MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 1.8 mW/g; SAR(10 g) = 0.491 mW/g

Deviation = -4.00 %



0 dB = 3.79mW/g