



SAR COMPLIANCE EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
18600 Broadwick St.
Rancho Dominguez, CA 90220
United States

Date of Testing:

07/20/11 - 08/02/11

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1107191237-R1.A3L

FCC ID:

A3LSGHT859

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

EUT Type:

Portable Tablet Computer

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093; FCC/OET Bulletin 65 Supplement C [June 2001]

Model(s):

SGH-T859

Test Device Serial No.:

Pre-Production [S/N: 859^5, 859^7]

Band & Mode	Tx Frequency	Conducted Power [dBm]	SAR
			1 gm Body (W/kg)
GSM 850	824.20 - 848.80 MHz (GSM 850)	31.48	0.71
GSM 1900	1850.20 - 1909.80 MHz (GSM 1900)	29.10	1.06
WCDMA 850	826.40 - 846.60 MHz (UMTS V)	21.89	0.53
AWS WCDMA	1712.4 - 1752.5 MHz (AWS WCDMA)	23.05	1.17
WCDMA 1900	1852.4 - 1907.6 MHz (UMTS II)	20.74	1.18
2.4 GHz WLAN	2412 - 2462 MHz (WLAN)	13.86	0.73
5.2 GHz WLAN	5180 - 5240 MHz (WLAN)	12.40	1.10
5.3 GHz WLAN	5260 - 5320 MHz (WLAN)	12.30	1.03
5.5 GHz WLAN	5500 - 5700 MHz (WLAN)	12.91	1.12
5.8 GHz WLAN	5745 - 5825 MHz (WLAN)	12.84	1.10

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001), IEEE 1528-2003 and in applicable Industry Canada Radio Standards Specifications (RSS); for North American frequency bands only.

Note: This revised Test Report (S/N: 0Y1107191237-R1.A3L) supersedes and replaces the previously issued test report on the same subject EUT for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 1 of 49

T A B L E O F C O N T E N T S

1	INTRODUCTION	3
2	TEST SITE LOCATION	4
3	SAR MEASUREMENT SETUP	5
4	DASY E-FIELD PROBE SYSTEM	7
5	PROBE CALIBRATION PROCESS	8
6	PHANTOM AND EQUIVALENT TISSUES.....	9
7	DOSIMETRIC ASSESSMENT & PHANTOM SPECS.....	10
8	FCC RF EXPOSURE LIMITS.....	11
9	ANTENNA LOCATIONS AND KEY FEATURES	12
10	SAR TESTING CONSIDERATIONS & FCC KDB INQUIRIES	14
11	FCC 3G MEASUREMENT PROCEDURES.....	23
12	SAR TESTING WITH IEEE 802.11 TRANSMITTERS.....	28
13	SYSTEM VERIFICATION.....	31
14	SAR DATA SUMMARY	34
15	SIMULTANEOUS TRANSMISSION ANALYSIS.....	41
16	EQUIPMENT LIST.....	44
17	MEASUREMENT UNCERTAINTIES	45
18	CONCLUSION.....	47
19	REFERENCES	48

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 2 of 49

1 INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [24]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

Figure 1-1
SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m^3)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 3 of 49

2 TEST SITE LOCATION

2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC.

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on January 27, 2006 and Industry Canada.



Figure 2-1

Map of the Greater Baltimore and Metropolitan Washington, D.C. area

2.2 Test Facility / Accreditations:

Measurements were performed at an independent accredited PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing-Aid Compatibility (HAC), Battery Safety, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and all Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS and CDMA, and EvDO mobile phones.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO Data, CDMA 1xRTT Data

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 4 of 49

3 SAR MEASUREMENT SETUP

3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of a high precision robotics system (Staubli), robot controller, desktop computer, near-field probe, probe alignment sensor, and the SAM phantom containing the head or body equivalent material. The robot is a six-axis industrial robot, performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure 3-1).

3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, A/D conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal from the DAE and transfers data to the PC card.

3.3 System Electronics




Figure 3-1
SAR Measurement System Setup

The DAE consists of a highly sensitive electrometer-grade auto-zeroing preamplifier, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 5 of 49

3.4 Automated Test System Specifications

Test Software: SPEAG DASY4 version 4.7 Measurement Software
Robot: Stäubli Unimation Corp. Robot RX60L
Repeatability: 0.02 mm
No. of Axes: 6

Data Acquisition Electronic System (DAE)

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic
Software: SEMCAD software
Connecting Lines: Optical Downlink for data and status info
Optical upload for commands and clock

PC Interface Card

Function: Link to DAE
16-bit A/D converter for surface detection system
Two Serial & Ethernet link to robotics
Direct emergency stop output for robot

Phantom

Type: SAM Twin Phantom (V4.0)
Shell Material: Composite
Thickness: 2.0 ± 0.2 mm



Figure 3-2
SAR Measurement System

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 6 of 49

4.1 Probe Measurement System



Figure 4-1
SAR System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration (see Figure 4-3) and optimized for dosimetric evaluation [9]. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the

maximum using a 2nd order curve fitting (see Figure 5-1). The approach is stopped at reaching the maximum.

4.2 Probe Specifications

Model(s):	ES3DV2, ES3DV3, EX3DV4
Frequency	10 MHz – 6.0 GHz (EX3DV4)
Range:	10 MHz – 4 GHz (ES3DV3)
Calibration:	In head and body simulating tissue at Frequencies from 300 up to 6000MHz
Linearity:	± 0.2 dB (30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB (30 MHz to 4 GHz) for ES3DV3
Dynamic Range:	10 mW/kg – 100 W/kg
Probe Length:	330 mm
Probe Tip	
Length:	20 mm
Body Diameter:	12 mm
Tip Diameter:	2.5 mm (3.9mm for ES3DV3)
Tip-Center:	1 mm (2.0 mm for ES3DV3)
Application:	SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields



Figure 4-2
Near-Field Probe



Figure 4-3
Triangular Probe Configuration

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 7 of 49

5 PROBE CALIBRATION PROCESS

5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm².

5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds),
 C = heat capacity of tissue (brain or muscle),
 ΔT = temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

σ = simulated tissue conductivity,
 ρ = Tissue density (1.25 g/cm³ for brain tissue)

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.




Figure 5-1 E-Field and Temperature measurements at 900MHz [9]




Figure 5-2 E-Field and temperature measurements at 1.9GHz [9]

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 8 of 49

6 PHANTOM AND EQUIVALENT TISSUES

6.1 SAM Phantoms



Figure 6-1
SAM Phantoms

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to represent the 90th percentile of the population [12][13]. The phantom enables the dosimetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

6.2 Tissue Simulating Mixture Characterization




Figure 6-2
SAM Phantom with
Simulating Tissue

Table 6-1
Composition of the Tissue Equivalent Matter

Frequency (MHz)	835	1750	1900	2450	5200-5800
Tissue	Body	Body	Body	Body	Body
Ingredients (% by weight)					
Bactericide	0.1				
DGBE		31	29.44	26.7	
HEC	1				
NaCl	0.94	0.2	0.39	0.1	
Sucrose	44.9				
Triton X-100					10.67
Diethylenglycol monohexylether					10.67
Water	53.06	68.8	70.17	73.2	78.66

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 9 of 49

7 DOSIMETRIC ASSESSMENT & PHANTOM SPECS

7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR distribution at the exposed side of the head was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during testing the 1 gram cube. This fixed point was measured and used as a reference value.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual for more details):
 - a. The data was extrapolated to the surface of the outer-shell of the phantom. The combined distance extrapolated was the combined distance from the center of the dipoles 2.7mm away from the tip of the probe housing plus the 1.2 mm distance between the surface and the lowest measuring point. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete. If the value deviated by more than 5%, the evaluation was repeated.
5. For 5 GHz testing finer resolution zoom scans were preformed as specified by FCC SAR Measurement Requirements for 3 – 6 GHz, KDB pub 865664. The 5 GHz zoom scan requires a minimum volume of 24mm x 24mm x 20mm and 7 x 7 x 11 points.




Figure 7-1
Sample SAR Area Scan

7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Figure 7-2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimize reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15 cm.



Figure 7-2
SAM Twin Phantom Shell

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 10 of 49

8 FCC RF EXPOSURE LIMITS

8.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

8.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 8-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
SPATIAL PEAK SAR Brain	1.6	8.0
SPATIAL AVERAGE SAR Whole Body	0.08	0.4
SPATIAL PEAK SAR Hands, Feet, Ankles, Wrists	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 11 of 49

9

ANTENNA LOCATIONS AND KEY FEATURES

9.1 Antenna and Key Feature Information




Figure 9-1
Front View of Device

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 12 of 49

10 SAR TESTING CONSIDERATIONS & FCC KDB INQUIRIES

10.1 Tablet testing for SAR

Lap-touching devices that have transmitting antennas located less than 20 cm from the body of the user require routine SAR evaluation. Such devices are considered portable, and are capable of being held to the body. Devices are to be setup according to KDB publication 447498 requirements and are configured with maximum output power during SAR assessment for a worst-case SAR evaluation.

10.2 HSPA Test Considerations for SAR Testing

Since the SAR test setup for HSPA is typically problematic due to static ETFCI and AG requirements for the duration of the SAR test, as long as the maximum average output power for WCDMA and HSPA are similar, testing in WCDMA mode is performed, which also facilitates the exclusion of HSPA testing. HSPA testing was excluded based on the conducted power measurement and SAR results according to KDB 941225 Publication. HSPA+ operations are in the downlink only.

10.3 SAR Testing for Tablet per KDB Publication 447498 Section 4

Per KDB 447498 4) b) i) the bottom face (back of the device) is required to be tested touching the flat phantom.

Per KDB Publication 447498 4) b) ii) (2), SAR testing applies for the tablet edges with antennas located within 5 cm of each tablet edge closest to the user (with KDB Publication 616217 applied to edges with antennas located ≥ 5 cm from the user). According to KDB Publication 447498 4) b) ii) (2), for each antenna, SAR is only required for the edge with the most conservative exposure condition.

Table 10-1 SAR Requirement Table per KDB pub 616217 D01

Antenna Output Power (mW)	$\leq 60/f_{\text{(GHz)}}$	$> 60/f_{\text{(GHz)}}$
Individual Transmitter or Antenna	SAR not required	Antenna-to-user distance – $\geq (5 + \frac{1}{2} \cdot n)$ cm: test SAR on highest output channel only $< (5 + \frac{1}{2} \cdot n)$ cm: test SAR according to normal procedures
Simultaneous Transmitting Antennas	SAR not required: antenna-to-antenna or antenna-to-person distance ≥ 5 cm	SAR not required: antenna-to-antenna $\geq (5 + \frac{1}{2} \cdot n_x + \frac{1}{2} \cdot n_y)$ and antenna-to-person $\geq (5 + \frac{1}{2} \cdot n_x)$ cm
	SAR not required: when $\sum (SAR_{1g}) < \text{SAR limit}$, antenna-to-antenna distances > 5 cm and antenna-to-user distance > 5 cm if output $> 60/f$	
	otherwise, test antenna(s) using highest SAR configuration for the individual transmitter/antenna	

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 14 of 49

Table 10-2
Distance Thresholds calculations KDB Publication 616217

Mode	Freq (GHz)	Power (dBm)	P = Power (mW)	60/f	n = P/60/f-1	distance thres (5+1/2n)
GPRS 850	0.824	24.03	253	72.80	2	6.2
GPRS 1900	1.850	20.68	117	32.43	3	6.3
WCDMA 850	0.826	21.89	155	72.60	1	5.6
WCDMA 1700	1.724	23.05	202	34.80	5	7.4
WCDMA 1900	1.908	20.74	119	31.45	3	6.4
WIFI b	2.462	13.44	22	24.37	0	5.0
WIFI g	2.462	13.86	24	24.37	0	5.0
WIFI n	2.462	12.76	19	24.37	0	4.9
WIFI a	5.240	12.40	12	11.45	0	5.0
	5.260	12.30	16.98	11.41	0.49	5.2
	5.500	12.91	19.54	10.91	0.79	5.4
	5.805	12.84	19.23	10.34	0.86	5.4

Note: GPRS powers represent highest frame-averaged power

According to KDB publication 616217 and the antenna distances from the user to the edges of the device, WWAN antenna is required to be tested for SAR for the back side, top edge and right edge for GPRS/WCDMA. The WLAN antenna is required to be tested for SAR for the back, top and left edges of the device.

Per KDB publication 447498 4) b) since the output power of the antenna (13.002 mW) is $\leq 60/f$ (GHz), Bluetooth SAR is not required for both back side and edge exposure conditions.

10.4 Additional SAR Testing for the Back and Top of the Device

Based on the type and implementation of the sensor, April 2011 FCC-TCB conference notes requires sensor information regarding: (1) additional SAR evaluation at a conservative distance from the device where power reduction is de-activated, and (2) reliability sensor activation data. Reliability sensor activation data is provided for both the back and top edge of the tablet at 0° to cover direct usage and also at 45° to cover angled usage (See Table 10-3, Table 10-4 and Table 10-5).

Since the back-off sensor activation distance at 45° was greater than 6 mm for the top edge, a conservative distance of 5 mm was tested. Details about sensing mechanism and sensor pad location are included in the technical description.

The sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensor in all applicable directions.


Table 10-3
Distance from Back of Tablet

distance in mm	9	10	11	12	13	14
Condition of Sensor in the back of the device	on	on	on	off	off	off

Please see Figure 10-1 through Figure 10-3 for power vs. back-off distance plots for each GPRS multislots and WCDMA mode.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 15 of 49

Backoff Sensor Power Reduction (back side)



Backoff Sensor Power Reduction (GPRS850, back side)




Figure 10-1

GPRS/EDGE (GMSK) 850 Back off Power Reduction Graph – Back Side

Data in Figure 10-1 demonstrates a power reduction of 5 dB for each multi-transmit slot mode at a back-off distance of 11 mm, as shown in Table 10-3

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 16 of 49

Backoff Sensor Power Reduction (GPRS1900, back side)




Figure 10-2

GPRS/EDGE (GMSK) 1900 Back off Power Reduction Graph – Back Side

Data in Figure 10-2 demonstrates a power reduction of 5 dB for each multi-transmit slot mode at a back-off distance of 11 mm, as shown in Table 10-3

Backoff Sensor Power Reduction (WCDMA, back side)




Figure 10-3

WCDMA Back off Power Reduction Graph – Back Side

Data in Figure 10-3 demonstrates a power reduction of 5 dB for WCDMA 850 and 1900, and a reduction of 7 dB for AWS WCDMA mode at a back-off distance of 11 mm, as shown in Table 10-3


FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 17 of 49

Table 10-4
Distance from Top edge of Tablet - 0° Angle

distance in mm	5	6	7	8	9	10
Condition of Sensor in the back of the device	on	on	off	off	off	off

Please see Figure 10-4 through Figure 10-6 for power vs. back-off distance plots for each GPRS multislot and WCDMA mode.

Backoff Sensor Power Reduction (top side, 0° tilted)



Note: Angle mentioned for top edge description is the perpendicular angle.
Above figure represents "0 degrees"

Backoff Sensor Power Reduction (GPRS850, top side)




Figure 10-4

GPRS/EDGE (GMSK) 850 Back off Power Reduction Graph – Top edge at 0° Angle

Data in Figure 10-4 demonstrates a power reduction of 5 dB for each multi-transmit slot mode at a back-off distance of 6 mm, as shown in Table 10-4.

FCC ID: A3LSGHT859	PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 18 of 49

Backoff Sensor Power Reduction (GPRS1900, top side)




Figure 10-5

GPRS/EDGE (GMSK) 1900 Back off Power Reduction Graph – Top edge at 0° Angle

Data in Figure 10-5 demonstrates a power reduction of 5 dB for each multi-transmit slot mode at a back-off distance of 6 mm, as shown in Table 10-4.

Backoff Sensor Power Reduction (WCDMA, top side)




Figure 10-6

WCDMA Back off Power Reduction Graph – Top edge at 0° Angle


Data in Figure 10-6 demonstrates a power reduction of 5 dB for WCDMA 850 and 1900, and a reduction of 7 dB for AWS WCDMA mode at a back-off distance of 6 mm, as shown in Table 10-4.

distance in mm	5	6	7	8	9	10
Condition of Sensor in the back of the device	on	on	off	off	off	off

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 19 of 49

Table 10-5
Distance from Top of Tablet - 45° Angle

Please see Figure 10-7 through Figure 10-9 for power vs. back-off distance plots for each GPRS multislot and WCDMA mode.



Note: Angle mentioned for top edge description is the perpendicular angle.

Above figure represents "45 degrees" between the screen face and phantom face.

Please note that the 45 degree angle tilt has been used to identify proximity sensor coverage for the top edge, since this angle is consistent with device use conditions and sensor implementation. All relevant directions of coverage, as described in the April 2011 TCB workshop slides, have been considered in order to determine the worst case activation and deactivation test distances.




Figure 10-7

GPRS/EDGE (GMSK) 850 Back off Power Reduction Graph – Back at 45° Angle

Data in Figure 10-7 demonstrates a power reduction of 5 dB for each multi-transmit slot mode at a back-off distance of 6 mm, as shown in Table 10-5.

FCC ID: A3LSGHT859	PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	SAMSUNG	Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 20 of 49

Backoff Sensor Power Reduction (GPRS1900, top side, 45° tilted)




Figure 10-8

GPRS/EDGE (GMSK) 1900 Back off Power Reduction Graph – Back at 45° Angle

Data in Figure 10-8 demonstrates a power reduction of 5 dB for each multi-transmit slot mode at a back-off distance of 6 mm, as shown in Table 10-5.

Backoff Sensor Power Reduction (WCDMA, top side, 45° tilted)




Figure 10-9

WCDMA Back off Power Reduction Graph – Back at 45° Angle

Data in Figure 10-9 demonstrates a power reduction of 5 dB for WCDMA 850 and 1900, and a reduction of 7 dB for AWS WCDMA mode at a back-off distance of 6 mm, as shown in Table 10-5.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 21 of 49

10.5 Method of SAR Measurement with Power Reduction

Based on the power-reduction activation vs. distance results for the sensors, the device was tested at 0mm distance from the phantom with the sensor activated and additionally at a conservative 10 mm distance with the sensor de-activated (max power, no power reduction) from the back side; and 5 mm from the top edge.

To test SAR with power back-off sensor active while touching (using 859^7), the device was placed in maximum power transmit mode with a base station simulator. The device was then positioned to touching position under the tissue equivalent liquid-filled flat phantom, to activate the proximity sensors.

For the additional SAR measurements with the sensors de-activated when the device is positioned away from the user (using 859^5), SAR is needed to be evaluated without power back-off at 10 mm (from the back) and 5mm (from the top edge). Since the device sensor detection mechanism is active at these distances, the sensor had to be disabled via manufacturer test software for SAR test purposes. The device was then placed in maximum power transmit mode with a base station simulator under the tissue equivalent liquid-filled flat phantom at a distance of 10 mm for the back and 5 mm for the top edge with the sensor deactivated (via manufacturer test software) and then tested at maximum power.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 22 of 49

11 FCC 3G MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

11.1 Procedures Used to Establish RF Signal for SAR

The following procedures are according to KDB 941225 D01, "SAR Test for 3G Devices v02."

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If SAR deviations of more than 5% occurred, the tests were repeated.

11.2 SAR Measurement Conditions for WCDMA (UMTS) per FCC KDB Publication 941225

11.2.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all "1s". Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH) is tabulated in the test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations is identified.

11.2.2 Procedures Used to Establish RF Signal for SAR HSDPA Data Devices

The following procedures are applicable to HSDPA data devices operating under 3GPP Release 5. Body exposure conditions are typically applicable to these devices, including handsets and data modems operating in various electronic devices. HSDPA operates in conjunction with WCDMA and requires an active DPCCH. The default test configuration is to measure SAR in WCDMA without HSDPA, with an established radio link between the DUT and a communication test set with 12.2 kbps RMC mode configured in Test Loop Mode 1; and tested with HSDPA with FRC and a 12.2 kbps RMC using the highest SAR configuration in WCDMA. SAR is selectively confirmed for other physical channel configurations according to output power, exposure conditions and device operating capabilities. Maximum output power is verified according to 3GPP TS 23.121 (Release 5) and SAR must be measured according to these maximum output conditions.

11.2.3 SAR Measurement Conditions for HSUPA Data Devices

SAR for body exposure configurations are measured according to the 'Body SAR Measurements' procedures in the 'WCDMA Handsets' section of the KDB 941225 D01 FCC 3G document. In

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 23 of 49

addition, Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least ¼ dB higher of that measured without HSPA in 12.2 kbps RMC mode or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2, according to the highest body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP is applicable for head exposure, SAR is not required when the maximum output of each RF channel with HSPA is less than ¼ dB higher than that measured using 12.2 kbps RMC; otherwise, the same HSPA configuration used for body measurements should be used to test for head exposure.

Due to inner loop power control requirements in HSPA, a commercial communication test set should be used for the output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and EDCH configurations for HSPA should be configured according to the β values indicated below as well as other applicable procedures described in the 'WCDMA Handset' and 'Release 5 HSDPA Data Devices' sections of the FCC 3G document.

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{1s}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: $\Delta_{ACK} \Delta_{NACK}$ and $\Delta_{CQI} = 8 \Leftrightarrow A_{1s} = \beta_{1s}/\beta_c = 30/15 \Leftrightarrow \beta_{1s} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{1s}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCCH, HS- DPCCCH, E-DPDCH and E-DPCCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 24 of 49

11.3 RF Conducted Powers

11.3.1 GSM Conducted Powers

Table 11-1
Maximum GSM/GPRS Powers (Proximity Sensor inactive)

		Maximum Burst-Averaged Output Power			
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
Cellular	128	31.48	30.05	25.85	25.79
	190	31.44	30.01	25.87	25.83
	251	31.47	29.99	25.83	25.82
PCS	512	29.10	26.70	25.10	25.05
	661	28.97	26.60	25.11	25.06
	810	28.98	26.65	25.14	25.14
		Calculated Maximum Frame-Averaged Output Power			
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
Cellular	128	22.45	24.03	16.82	19.77
	190	22.41	23.99	16.84	19.81
	251	22.44	23.97	16.80	19.80
PCS	512	20.07	20.68	16.07	19.03
	661	19.94	20.58	16.08	19.04
	810	19.95	20.63	16.11	19.12

Note: Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots. The bolded GPRS/EDGE modes were required for SAR testing according to the highest frame averaged output power per KDB publication 941225 D03. GPRS/EDGE (GMSK) conducted powers were measured with CS1. EDGE (8-PSK) powers were measured with MCS7.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 25 of 49

Table 11-2
Reduced GSM/GPRS Powers (Proximity Sensor active)

		Maximum Burst-Averaged Output Power			
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
Cellular	128	26.38	25.09	20.88	20.89
	190	26.41	25.16	21.03	20.94
	251	26.51	25.23	21.09	21.00
PCS	512	23.99	21.41	20.01	19.99
	661	24.01	21.37	20.04	20.00
	810	24.02	21.41	20.02	20.11

		Calculated Maximum Frame-Averaged Output Power			
		GPRS/EDGE Data (GMSK)		EDGE Data (8-PSK)	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
Cellular	128	17.35	19.07	11.85	14.87
	190	17.38	19.14	12.00	14.92
	251	17.48	19.21	12.06	14.98
PCS	512	14.96	15.39	10.98	13.97
	661	14.98	15.35	11.01	13.98
	810	14.99	15.39	10.99	14.09

Note: Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots. The bolded GPRS/EDGE modes were required for SAR testing according to the highest frame averaged output power per KDB publication 941225 D03. GPRS/EDGE (GMSK) conducted powers were measured with CS1. EDGE (8-PSK) powers were measured with MCS7.

GSM Class: C (Data only)
GPRS Multislot class: 10
EDGE Multislot class: 10
DTM Multislot Class: N/A

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 26 of 49

11.3.2 WCDMA Conducted Powers

Table 11-3
Maximum WCDMA Powers (Proximity Sensor inactive)

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			AWS Band [dBm]			β_c	β_d	MPR
			4132	4183	4233	9262	9400	9538	1312	1412	1862			
99	WCDMA	12.2 kbps RMC	21.89	21.85	21.78	20.29	20.61	20.74	23.05	22.83	22.56	-	-	-
6	HSDPA	Subtest 1	21.81	21.76	21.67	20.31	20.61	20.80	22.42	22.15	21.82	2	15	0
6		Subtest 2	21.61	21.58	21.55	20.05	20.39	20.51	23.21	22.88	22.43	11	15	0
6		Subtest 3	21.39	21.34	21.32	19.58	19.99	20.00	22.75	22.42	21.95	15	8	0.5
6		Subtest 4	21.14	21.10	21.05	19.36	19.75	19.74	22.50	22.16	21.68	15	4	0.5
6	HSUPA	Subtest 1	21.12	21.06	21.01	20.21	20.59	20.65	22.80	22.62	22.17	10	15	0
6		Subtest 2	19.75	19.73	19.70	18.28	18.58	18.71	21.41	21.07	20.66	6	15	2
6		Subtest 3	20.82	20.74	20.69	18.80	19.15	19.16	21.71	21.28	20.96	15	9	1
6		Subtest 4	20.01	20.03	19.96	18.44	18.81	18.92	21.49	21.03	20.77	2	15	2
6		Subtest 5	20.73	20.65	21.15	20.39	20.78	20.87	21.59	21.29	20.94	14	15	0

Table 11-4
Reduced WCDMA Powers (Proximity Sensor active)

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			AWS Band [dBm]			β_c	β_d	MPR
			4132	4183	4233	9262	9400	9538	1312	1412	1862			
99	WCDMA	12.2 kbps RMC	16.58	16.55	16.48	16.16	15.90	16.01	16.08	15.92	15.90	-	-	-
6	HSDPA	Subtest 1	16.70	16.60	16.61	16.25	15.95	16.09	16.08	15.90	15.97	2	15	0
6		Subtest 2	16.46	16.36	16.36	16.04	15.65	15.87	15.86	15.73	15.66	11	15	0
6		Subtest 3	16.16	16.09	16.03	15.61	15.38	15.58	15.60	15.46	15.52	15	8	0.5
6		Subtest 4	15.94	15.86	15.83	15.59	15.25	15.36	15.36	15.20	15.24	15	4	0.5
6	HSUPA	Subtest 1	16.41	16.34	16.32	16.03	15.79	15.97	15.93	15.81	15.75	10	15	0
6		Subtest 2	14.86	14.74	14.76	14.65	14.28	14.50	13.95	13.75	13.94	6	15	2
6		Subtest 3	15.51	15.38	15.41	14.92	14.55	14.82	14.87	14.74	14.82	15	9	1
6		Subtest 4	14.59	14.54	14.51	14.20	13.86	14.11	14.18	14.05	14.07	2	15	2
6		Subtest 5	16.72	16.65	16.63	16.32	16.01	16.24	16.10	15.99	16.04	14	15	0

Note: It was confirmed with the manufacturer that the device used for SAR testing with the measured output powers was not overdriven to non-linear operations.

WCDMA SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

It is expected by the manufacturer that MPR for some HSUPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model. Detailed information is included in the operational description explaining how the MPR is applied for this model.



Figure 11-1
Power Measurement Setup

11.4 Summary of Power Reduction due to Proximity Sensor

Mode	Level of Power Reduction (dB)
GPRS 850	5
GPRS 1900	5
WCDMA 850	5
AWS WCDMA	7
WCDMA 2900	5

FCC ID: A3LSGHT859	PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 27 of 49

12 SAR TESTING WITH IEEE 802.11 TRANSMITTERS

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

12.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

12.2 Frequency Channel Configurations [27]

802.11 a/b/g/n modes are tested independently according to the service requirements in each frequency band. 802.11 b/g/n modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz §15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. These are referred to as the “default test channels”. 802.11g/n modes were evaluated only if the output power was 0.25 dB higher than the corresponding 802.11b or 802.11a mode.

Table 12-1
802.11 Test Channels per FCC Requirements

Mode	GHz	Channel	Turbo Channel	“Default Test Channels”			
				§15.247	UNII		
802.11 b/g/n	2.412	1		√	▽		
	2.437	6		√	▽		
	2.462	11		√	▽		
802.11a/n	5.18	36				√	
	5.20	40	42 (5.21 GHz)				*
	5.22	44					*
	5.24	48	50 (5.25 GHz)			√	
	5.26	52				√	
	5.28	56	58 (5.29 GHz)				*
	5.30	60					*
	5.32	64				√	
	5.500	100					*
	5.520	104				√	
	5.540	108					*
	5.560	112					*
	5.580	116				√	
	5.600	120	Unknown				*
	5.620	124				√	
	5.640	128					*
	5.660	132					*
	5.680	136				√	
	5.700	140					*
	5.745	149		√		√	
	5.765	153	152 (5.76 GHz)		*		*
	5.785	157		√			*
	5.805	161	160 (5.80 GHz)		*	√	
	§15.247	5.825	165	√			

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 28 of 49

Table 12-2
IEEE 802.11b Average RF Power

Freq [MHz]	Channel	Conducted Power [dBm]			
		Data Rate [Mbps]			
		1	2	5.5	11
2412	1	12.78	12.83	12.73	12.76
2437	6	13.24	13.20	13.11	13.15
2462	11	13.44	13.38	13.47	13.41

Table 12-3
IEEE 802.11g Average RF Power

Freq [MHz]	Channel	Conducted Power [dBm]							
		Data Rate [Mbps]							
		6	9	12	18	24	36	48	54
2412	1	13.28	13.26	13.25	13.36	13.24	13.22	13.21	13.23
2437	6	13.57	13.60	13.58	13.60	13.56	13.48	13.57	13.58
2462	11	13.86	13.86	13.80	13.87	13.82	13.75	13.83	13.85

Table 12-4
IEEE 802.11n Average RF Power

Freq [MHz]	Channel	Conducted Power [dBm]							
		Data Rate [Mbps]							
		6.5	13	20	26	39	52	58	65
2412	1	12.20	12.06	12.05	12.07	12.14	12.04	12.04	12.11
2437	6	12.54	12.33	12.46	12.44	12.53	12.36	12.39	12.32
2462	11	12.76	12.65	12.68	12.65	12.68	12.74	12.70	12.72

Table 12-5
IEEE 802.11a Average RF Power

Freq [MHz]	Channel	Conducted Power [dBm]							
		Data Rate [Mbps]							
		6	9	12	18	24	36	48	54
5180	36	12.25	12.22	12.16	12.35	12.27	12.22	12.30	12.25
5200	40	12.15	12.12	12.21	12.45	12.40	12.40	12.38	12.41
5220	44	12.26	12.32	12.30	12.44	12.45	12.41	12.50	12.49
5240	48	12.40	12.30	12.31	12.41	12.37	12.38	12.45	12.48
5260	52	12.30	12.35	12.31	12.35	12.32	12.28	12.45	12.41
5280	56	12.30	12.27	12.24	12.25	12.40	12.34	12.41	12.29
5300	60	12.20	12.22	12.21	12.28	12.31	12.24	12.37	12.31
5320	64	12.09	12.15	12.20	12.20	12.30	12.31	12.31	12.22
5500	100	12.91	12.98	12.85	12.92	13.00	12.97	13.10	13.03
5520	104	12.84	12.91	13.00	12.87	12.81	12.90	12.91	12.97
5540	108	12.73	12.88	12.79	12.91	12.81	12.80	12.91	12.72
5560	112	12.40	12.42	12.31	12.45	12.40	12.47	12.51	12.52
5580	116	12.25	12.26	12.22	12.32	12.33	12.40	12.51	12.19
5600	120	11.90	11.90	11.83	11.91	11.85	11.85	11.82	11.90
5620	124	11.78	11.90	11.82	11.90	11.83	11.91	11.80	11.80
5640	128	11.82	12.02	11.98	11.96	12.00	12.00	11.99	12.10
5660	132	12.00	12.05	12.11	12.15	12.10	12.05	12.07	12.11
5680	136	12.05	12.15	12.27	12.18	12.12	12.09	12.22	12.18
5700	140	12.20	12.21	12.15	12.28	12.20	12.31	12.35	12.30
5745	149	12.60	12.55	12.59	12.63	12.57	12.60	12.65	12.67
5765	153	12.68	12.66	12.68	12.72	12.67	12.77	12.70	12.69
5785	157	12.79	12.76	12.80	12.83	12.85	12.83	12.92	12.94
5805	161	12.84	12.93	12.86	12.95	12.94	12.89	12.95	12.94
5825	165	12.72	12.63	12.61	12.63	12.56	12.64	12.66	12.71

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 29 of 49

Table 12-6
IEEE 802.11n Average RF Power

Freq [MHz]	Channel	Conducted Power [dBm]							
		Data Rate [Mbps]							
		6.5	13	20	26	39	52	58	65
5180	36	12.01	12.02	12.11	12.25	12.26	12.30	12.27	12.16
5200	40	12.05	11.96	12.10	12.21	12.20	12.04	12.15	12.20
5220	44	11.96	11.84	11.96	12.04	11.94	12.11	12.06	12.06
5240	48	11.80	11.85	11.90	11.88	11.95	11.93	12.02	12.00
5260	52	11.70	11.75	11.80	11.83	11.91	11.74	11.87	11.80
5280	56	11.55	11.61	11.73	11.65	11.81	11.77	11.72	11.77
5300	60	11.50	11.51	11.65	11.53	11.60	11.68	11.72	11.75
5320	64	11.30	11.31	11.40	11.40	11.55	11.57	11.45	11.42
5500	100	12.15	12.22	12.28	12.33	12.24	12.25	12.39	12.35
5520	104	12.22	12.15	12.40	12.38	12.34	12.40	12.37	12.42
5540	108	12.11	12.01	12.20	12.25	12.35	12.26	12.23	12.31
5560	112	12.10	11.98	12.20	12.25	12.27	12.16	12.30	12.22
5580	116	12.00	11.99	12.22	12.23	12.14	12.10	12.25	12.32
5600	120	12.04	12.12	12.21	12.12	12.20	12.32	12.29	12.24
5620	124	12.12	12.00	12.17	12.14	12.31	12.26	12.25	12.24
5640	128	12.26	12.20	12.32	12.45	12.38	12.48	12.50	12.32
5660	132	12.30	12.28	12.40	12.45	12.51	12.45	12.50	12.64
5680	136	12.39	12.41	12.55	12.56	12.54	12.60	12.70	12.72
5700	140	12.50	12.40	12.67	12.73	12.70	12.61	12.78	12.59
5745	149	12.61	12.45	12.65	12.60	12.70	12.60	12.71	12.75
5765	153	12.60	12.60	12.72	12.75	12.72	12.66	12.68	12.80
5785	157	12.65	12.67	12.80	12.81	12.70	12.81	12.87	12.98
5805	161	12.79	12.70	12.80	12.88	12.88	12.89	12.88	12.86
5825	165	12.44	12.14	12.13	12.32	12.23	12.36	12.41	12.43

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes:

- For 2.4 GHz, highest average RF output power channel for the lowest data rate were selected for SAR evaluation. 802.11n mode was not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode. 802.11 g mode was investigated since the average output powers were greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
- For 5 GHz, highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
- The underlined data rate and channel above were tested for SAR.



Figure 12-1
Power Measurement Setup

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 30 of 49

13 SYSTEM VERIFICATION

13.1 Tissue Verification

Table 13-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
07/30/2011	835B	820	0.977	54.70	0.97	55.28	0.83%	-1.06%
		835	0.989	54.63	0.97	55.20	1.96%	-1.03%
		850	0.998	54.47	0.99	55.15	1.01%	-1.24%
08/02/2011	835B	820	0.980	53.91	0.97	55.28	1.14%	-2.49%
		835	0.980	54.19	0.97	55.20	1.03%	-1.83%
		850	1.001	53.90	0.99	55.15	1.32%	-2.27%
08/01/2011	1750B	1710	1.486	52.90	1.46	53.54	1.78%	-1.20%
		1750	1.539	52.75	1.49	53.43	3.29%	-1.27%
		1790	1.571	52.64	1.51	53.33	4.04%	-1.29%
08/02/2011	1900B	1850	1.459	52.47	1.52	53.30	-4.01%	-1.56%
		1880	1.484	52.34	1.52	53.30	-2.37%	-1.80%
		1910	1.520	52.32	1.52	53.30	0.00%	-1.84%
07/21/2011	2450B	2401	1.915	51.32	1.90	52.77	0.63%	-2.74%
		2450	1.914	51.94	1.95	52.70	-1.85%	-1.44%
		2499	1.989	50.91	2.02	52.64	-1.49%	-3.28%
07/26/2011	2450B	2401	1.865	52.19	1.90	52.77	-2.00%	-1.09%
		2450	1.933	52.07	1.95	52.70	-0.87%	-1.20%
		2499	2.004	51.85	2.02	52.64	-0.74%	-1.50%
07/20/2011	5200B-5800B	5170	5.146	48.72	5.26	49.06	-2.24%	-0.68%
		5210	5.057	48.56	5.31	49.00	-4.78%	-0.90%
		5250	5.282	48.47	5.36	48.95	-1.42%	-0.97%
		5270	5.272	48.59	5.38	48.92	-2.03%	-0.67%
		5310	5.220	48.39	5.43	48.87	-3.83%	-0.97%
		5350	5.417	48.28	5.47	48.81	-0.97%	-1.09%
		5470	5.462	48.30	5.62	48.65	-2.72%	-0.72%
		5510	5.497	48.17	5.66	48.59	-2.90%	-0.87%
		5550	5.595	48.39	5.71	48.54	-1.98%	-0.31%
		5650	5.739	47.97	5.83	48.40	-1.48%	-0.90%
		5670	5.839	48.04	5.85	48.38	-0.15%	-0.69%
		5710	5.844	48.16	5.90	48.32	-0.87%	-0.34%
		5750	5.856	47.80	5.94	48.27	-1.45%	-0.97%
		5770	6.021	47.77	5.97	48.24	0.94%	-0.98%
		5810	5.939	48.05	6.01	48.19	-1.21%	-0.28%
		5850	6.013	47.78	6.06	48.13	-0.74%	-0.73%

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 31 of 49

Note: KDB Publication 450824 was ensured to be applied for probe calibration frequencies greater than or equal to 50 MHz of the DUT frequencies.

Probe calibration used within ± 100 MHz of the test frequency in either 5.725 - 5.85 or 5.47-5.725 GHz is acceptable per KDB Publication 865664 since the design of the SAR probe supports the extended frequency, provided the DASY software version recommended is used for the tests, and the expanded calibration uncertainty ($k=2$) is less than or equal to 15% (See SAR probe calibration certificate for this information). The dielectric and conductivities measured are within 10% and 5% respectively of the target parameters specified in Supplement C 01-01.

The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies (per IEEE 1528 6.6.1.2). The SAR test plots may slightly differ from the table above since the DASY software rounds to three significant digits.

13.2 Measurement Procedure for Tissue verification

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity, for example from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 32 of 49

13.3 Test System Verification

Prior to assessment, the system is verified to $\pm 10\%$ of the manufacturer SAR measurement on the reference dipole at the time of calibration.

Table 13-2
System Verification Results

System Verification TARGET & MEASURED										
Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Tissue Frequency (MHz)	Dipole SN	Tissue Type	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation (%)
07/30/2011	23.7	22.6	0.063	835	4d047	Body	0.653	9.850	10.365	5.23%
08/02/2011	22.8	21.7	0.250	835	4d047	Body	2.4	9.850	9.600	-2.54%
08/01/2011	24.3	22.6	0.040	1750	1051	Body	1.55	37.000	38.750	4.73%
08/02/2011	23.2	21.9	0.100	1900	502	Body	4.29	41.100	42.900	4.38%
07/21/2011	24.3	22.9	0.025	2450	797	Body	1.34	52.300	53.600	2.49%
07/26/2011	23.2	21.7	0.025	2450	797	Body	1.3	52.300	52.000	-0.57%
07/20/2011	23.2	22.1	0.025	5200	1057	Body	2.1	77.700	84.000	8.11%
07/20/2011	23.4	22.3	0.025	5500	1057	Body	2.19	84.400	87.600	3.79%
07/20/2011	23.5	22.4	0.025	5800	1057	Body	1.95	75.000	78.000	4.00%




Figure 13-1
System Verification Setup Diagram



Figure 13-2
System Verification Setup Photo

Note: Per KDB Publication 865664, when a reference dipole is not defined within $\pm 100\text{MHz}$ of the test frequency, the system verification may be conducted within $\pm 200\text{ MHz}$ of the center frequency of the measurement frequencies if the SAR probe calibration is valid and the same tissue-equivalent matter is used for verification and test measurements.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 33 of 49

14 SAR DATA SUMMARY

Table 14-1
GPRS Body SAR Results

MEASUREMENT RESULTS											
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Spacing	Serial Number	# of GPRS Slots	Side	SAR (1g)
MHz	Ch.										(W/kg)
836.60	190	GSM 850	GPRS	25.16	0.04	5	0.0 cm	859^7	2	back*	0.707
836.60	190	GSM 850	GPRS	30.01	0.04	0	1.0 cm	859^5	2	back	0.606
836.60	190	GSM 850	GPRS	25.16	0.03	5	0.0 cm	859^7	2	top*	0.151
836.60	190	GSM 850	GPRS	30.01	0.01	0	0.5 cm	859^5	2	top	0.615
836.60	190	GSM 850	GPRS	30.01	0.04	0	0.0 cm	859^5	2	right	0.578
1850.20	512	GSM 1900	GPRS	21.41	-0.03	5	0.0 cm	859^7	2	back*	0.831
1880.00	661	GSM 1900	GPRS	21.37	0.09	5	0.0 cm	859^7	2	back*	0.872
1909.80	810	GSM 1900	GPRS	21.41	-0.01	5	0.0 cm	859^7	2	back*	0.905
1880.00	661	GSM 1900	GPRS	26.60	-0.02	0	1.0 cm	859^5	2	back	0.797
1880.00	661	GSM 1900	GPRS	21.37	0.00	5	0.0 cm	859^7	2	top*	0.585
1850.20	512	GSM 1900	GPRS	26.70	0.00	0	0.5 cm	859^5	2	top	1.060
1880.00	661	GSM 1900	GPRS	26.60	0.00	0	0.5 cm	859^5	2	top	0.993
1909.80	810	GSM 1900	GPRS	26.65	0.00	0	0.5 cm	859^5	2	top	1.060
1880.00	661	GSM 1900	GPRS	26.60	-0.09	0	0.0 cm	859^5	2	right	0.184
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram				

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 34 of 49

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001]
2. Per KDB publication 447498 4) b) i) the back side is required to be tested touching the flat phantom.
3. This device is capable of multiple display orientations supporting both portrait and landscape positions. Therefore per KDB publication 447498 4) b) ii) (2), SAR testing applies for the tablet edges with antennas located within 5 cm of each tablet edge closest to the user (with KDB publication 616217 applied to edges with antennas located ≥ 5 cm from the user). According to KDB publication 447498 4) b) ii) (2), for each antenna, SAR is only required for the edge with the most conservative exposure condition.
4. All modes of operation were investigated, and worst-case results are reported.
5. Tissue parameters and temperatures are listed on the SAR plots.
6. Batteries are fully charged for all readings. Standard
7. Liquid tissue depth was at least 15.0 cm.
8. Justification for reduced test configurations per KDB Publication 941225 D03: The source-based time-averaged output power was evaluated for all multi-slot operations. In addition to the worst-case reported, all source-based time-averaged powers within 5% of the highest were additionally included.
9. Justification for reduced test configurations: Per KDB publication 447498 D01 1) e) i), when the SAR procedures require multiple channels to be tested and the 1-g SAR for the highest output channel is less than 0.8 W/kg, the other channels are not required.
10. Asterisk (*) denotes power reduction activated.
11. Per April 2011 TCB-FCC Workshop Notes, in addition to the 0 mm test distance required for tablet devices under KDB 447498, a conservative additional test distance of 10 mm from the back and 5 mm from the top were tested for SAR at maximum output power with the sensors de-activated. See Section 10.4 for more details.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 35 of 49

Table 14-2
WCDMA Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Spacing	Serial Number	Side	SAR (1g)
MHz	Ch.									(W/kg)
836.60	4183	WCDMA 850	RMC	16.55	0.03	5	0.0 cm	859^7	back*	0.425
836.60	4183	WCDMA 850	RMC	21.85	0.02	0	1.0 cm	857^5	back	0.530
836.60	4183	WCDMA 850	RMC	16.55	0.00	5	0.0 cm	859^7	top*	0.086
836.60	4183	WCDMA 850	RMC	21.85	0.02	0	0.5 cm	859^5	top	0.377
836.60	4183	WCDMA 850	RMC	21.85	0.01	0	0.0 cm	859^5	right	0.509
1712.40	1312	AWS WCDMA	RMC	16.08	0.01	7	0.0 cm	859^7	back*	0.811
1730.40	1412	AWS WCDMA	RMC	15.92	0.01	7	0.0 cm	859^7	back*	0.839
1752.50	1862	AWS WCDMA	RMC	15.90	0.02	7	0.0 cm	859^7	back*	0.725
1730.40	1412	AWS WCDMA	RMC	22.83	-0.02	0	1.0 cm	859^5	back	0.684
1712.40	1312	AWS WCDMA	RMC	16.08	-0.01	7	0.0 cm	859^7	top*	0.887
1730.40	1412	AWS WCDMA	RMC	15.92	0.02	7	0.0 cm	859^7	top*	0.880
1752.50	1862	AWS WCDMA	RMC	15.90	0.01	7	0.0 cm	859^7	top*	0.764
1712.40	1312	AWS WCDMA	RMC	23.05	-0.04	0	0.5 cm	859^5	top	0.965
1730.40	1412	AWS WCDMA	RMC	22.83	0.00	0	0.5 cm	859^5	top	0.854
1752.50	1862	AWS WCDMA	RMC	22.56	0.02	0	0.5 cm	859^5	top	1.170
1730.40	1412	AWS WCDMA	RMC	22.83	0.02	0	0.0 cm	859^5	right	0.262
1852.40	9262	WCDMA 1900	RMC	16.16	-0.02	5	0.0 cm	859^7	back*	0.778
1880.00	9400	WCDMA 1900	RMC	15.90	-0.01	5	0.0 cm	859^7	back*	0.818
1907.60	9538	WCDMA 1900	RMC	16.01	-0.03	5	0.0 cm	859^7	back*	0.847
1880.00	9400	WCDMA 1900	RMC	20.61	-0.01	0	1.0 cm	859^5	back	0.774
1880.00	9400	WCDMA 1900	RMC	15.90	-0.08	5	0.0 cm	859^7	top*	0.716
1852.40	9262	WCDMA 1900	RMC	20.29	0.06	0	0.5 cm	859^5	top	1.050
1880.00	9400	WCDMA 1900	RMC	20.61	-0.06	0	0.5 cm	859^5	top	0.996
1907.60	9538	WCDMA 1900	RMC	20.74	-0.09	0	0.5 cm	859^5	top	1.180
1880.00	9400	WCDMA 1900	RMC	20.61	0.01	0	0.0 cm	859^5	right	0.209
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body			
Spatial Peak							1.6 W/kg (mW/g)			
Uncontrolled Exposure/General Population							averaged over 1 gram			

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 36 of 49

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001]
2. Per KDB publication 447498 4) b) i) the back side is required to be tested touching the flat phantom.
3. This device is capable of multiple display orientations supporting both portrait and landscape positions. Therefore per KDB publication 447498 4) b) ii) (2), SAR testing applies for the tablet edges with antennas located within 5 cm of each tablet edge closest to the user (with KDB publication 616217 applied to edges with antennas located ≥ 5 cm from the user). According to KDB publication 447498 4) b) ii) (2), for each antenna, SAR is only required for the edge with the most conservative exposure condition.
4. All modes of operation were investigated, and worst-case results are reported.
5. Tissue parameters and temperatures are listed on the SAR plots.
6. Batteries are fully charged for all readings.
7. Liquid tissue depth was at least 15.0 cm.
8. WCDMA mode was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01. HSPA SAR for the body was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
9. Justification for reduced test configurations: Per KDB publication 447498 D01 1) e) i), when the SAR procedures require multiple channels to be tested and the 1-g SAR for the highest output channel is less than 0.8 W/kg, the other channels are not required.
10. Asterisk (*) denotes power reduction activated.
11. Per April 2011 TCB-FCC Workshop Notes, in addition to the 0 mm test distance required for tablet devices under KDB 447498, a conservative additional test distance of 10 mm from the back and 5 mm from the top were tested for SAR at maximum output power with the sensors de-activated. See Section 10.4 for more details.
12. SAR was measured with a probe calibrated at 1750 MHz and is valid for measuring SAR from ± 50 MHz. The 1750MHz specific body liquid was verified with specific probe calibration factors as required per FCC KDB Publication 450824 D01.

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 37 of 49

Table 14-3
2.4 GHz Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Spacing	Serial Number	Data Rate (Mbps)	Side	SAR (1g)
MHz	Ch.									(W/kg)
2462	11	IEEE 802.11b	DSSS	13.44	0.03	0.0 cm	859^5	1	back	0.707
2462	11	IEEE 802.11b	DSSS	13.44	-0.07	0.0 cm	859^5	1	top	0.065
2462	11	IEEE 802.11b	DSSS	13.44	-0.07	0.0 cm	859^5	1	left	0.050
2462	11	IEEE 802.11g	OFDM	13.86	0.01	0.0 cm	859^5	6	back	0.732
2462	11	IEEE 802.11g	OFDM	13.86	-0.03	0.0 cm	859^5	6	top	0.060
2462	11	IEEE 802.11g	OFDM	13.86	-0.07	0.0 cm	859^5	6	left	0.049
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. Per KDB publication 447498 4) b) i) the back side is required to be tested touching the flat phantom.
3. This device is capable of multiple display orientations supporting both portrait and landscape positions. Therefore per KDB publication 447498 4) b) ii) (2), SAR testing applies for the tablet edges with antennas located within 5 cm of each tablet edge closest to the user (with KDB publication 616217 applied to edges with antennas located ≥ 5 cm from the user). According to KDB publication 447498 4) b) ii) (2), for each antenna, SAR is only required for the edge with the most conservative exposure condition.
4. All modes of operation were investigated, and worst-case results are reported.
5. Batteries are fully charged for all readings.
6. Tissue parameters and temperatures are listed on the SAR plots.
7. Liquid tissue depth is was at least 15.0 cm.
8. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. IEEE 802.11g was tested since the average output power of the corresponding channel used for SAR testing was more than 0.25 dB higher than IEEE 802.11b mode. Higher data rates were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11g mode.
9. WLAN transmission was verified using a spectrum analyzer.
10. There is no proximity sensor power reduction for WIFI modes.
11. Per April 2011 FCC-TCB conference notes Bluetooth SAR is not required for both back side and edge exposure conditions since (1) 2.4 GHz WIFI and Bluetooth are implemented in the same chipset, (2) Bluetooth Power is < 60/f, and (3) the maximum peak and average output for Bluetooth are less than the maximum output power for WIFI mode.

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 38 of 49

Table 14-4
5 GHz Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Spacing	Serial Number	Data Rate (Mbps)	Side	SAR (1g)
MHz	Ch.									(W/kg)
5180	36	IEEE 802.11a	OFDM	12.25	-0.02	0.0 cm	859^5	6	back	1.040
5240	48	IEEE 802.11a	OFDM	12.40	0.10	0.0 cm	859^5	6	back	0.897
5180	36	IEEE 802.11a	OFDM	12.25	0.06	0.0 cm	859^5	6	top	1.100
5240	48	IEEE 802.11a	OFDM	12.40	0.05	0.0 cm	859^5	6	top	1.050
5240	48	IEEE 802.11a	OFDM	12.40	0.09	0.0 cm	859^5	6	left	0.102
5260	52	IEEE 802.11a	OFDM	12.30	0.05	0.0 cm	859^5	6	back	0.917
5300	60	IEEE 802.11a	OFDM	12.20	0.02	0.0 cm	859^5	6	back	0.919
5260	52	IEEE 802.11a	OFDM	12.30	0.05	0.0 cm	859^5	6	top	1.030
5300	60	IEEE 802.11a	OFDM	12.20	0.00	0.0 cm	859^5	6	top	0.958
5260	52	IEEE 802.11a	OFDM	12.30	-0.09	0.0 cm	859^5	6	left	0.105
5500	100	IEEE 802.11a	OFDM	12.91	0.04	0.0 cm	859^5	6	back	1.050
5560	112	IEEE 802.11a	OFDM	12.40	0.01	0.0 cm	859^5	6	back	1.050
5600	120	IEEE 802.11a	OFDM	11.90	0.04	0.0 cm	859^5	6	back	1.040
5700	140	IEEE 802.11a	OFDM	12.20	-0.06	0.0 cm	859^5	6	back	0.886
5500	100	IEEE 802.11a	OFDM	12.91	-0.01	0.0 cm	859^5	6	top	1.120
5560	112	IEEE 802.11a	OFDM	12.40	-0.06	0.0 cm	859^5	6	top	1.100
5600	120	IEEE 802.11a	OFDM	11.90	0.01	0.0 cm	859^5	6	top	1.110
5700	140	IEEE 802.11a	OFDM	12.20	-0.03	0.0 cm	859^5	6	top	0.948
5500	100	IEEE 802.11a	OFDM	12.91	-0.06	0.0 cm	859^5	6	left	0.143
5765	153	IEEE 802.11a	OFDM	12.68	0.00	0.0 cm	859^5	6	back	0.883
5785	157	IEEE 802.11a	OFDM	12.79	0.00	0.0 cm	859^5	6	back	0.888
5805	161	IEEE 802.11a	OFDM	12.84	0.00	0.0 cm	859^5	6	back	0.843
5765	153	IEEE 802.11a	OFDM	12.68	-0.03	0.0 cm	859^5	6	top	1.100
5785	157	IEEE 802.11a	OFDM	12.79	0.10	0.0 cm	859^5	6	top	1.070
5805	161	IEEE 802.11a	OFDM	12.84	0.08	0.0 cm	859^5	6	top	1.040
5805	161	IEEE 802.11a	OFDM	12.84	-0.06	0.0 cm	859^5	6	left	0.106
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram				

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer	Page 39 of 49	

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. Per KDB publication 447498 4) b) i) the back side is required to be tested touching the flat phantom.
3. This device is capable of multiple display orientations supporting both portrait and landscape positions. Therefore per KDB publication 447498 4) b) ii) (2), SAR testing applies for the tablet edges with antennas located within 5 cm of each tablet edge closest to the user (with KDB publication 616217 applied to edges with antennas located ≥ 5 cm from the user). According to KDB publication 447498 4) b) ii) (2), for each antenna, SAR is only required for the edge with the most conservative exposure condition.
4. All modes of operation were investigated, and worst-case results are reported.
5. Batteries are fully charged for all readings.
6. Tissue parameters and temperatures are listed on the SAR plots.
7. Liquid tissue depth is was at least 15.0 cm.
8. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n and higher data rates) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11a mode.
9. Per KDB 248227 Publication, when the SAR < 0.8 W/kg, no additional channels were required. With SAR > 0.8 either the default test channels or the corresponding adjacent test channels were evaluated.
10. WLAN transmission was verified using a spectrum analyzer.
11. There is no proximity sensor power reduction for WIFI modes.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 40 of 49

15 SIMULTANEOUS TRANSMISSION ANALYSIS

15.1 Simultaneous Transmission Information

This device contains multiple transmitters that may operate simultaneously and therefore, require a simultaneous transmission analysis according to KDB publication 447498 4) b) iii) procedures (See Section 10.3). The tablet procedures required by KDB publication 447498 generally do not require separate hotspot mode testing.

Bluetooth and WIFI cannot transmit simultaneously since it shares the same circuit path and are switched by the radio.

5GHz WIFI cannot transmit simultaneously with the 2G/3G antenna.

15.2 Simultaneous Transmission Calculations per KDB 648474 at 0.0 cm

Table 15-1
Hotspot Simultaneous Transmission Scenario Touching (2.4 GHz WLAN)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	WCDMA 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.707	0.732	1.439	Body SAR	Back	0.425	0.732	1.157
	Top	0.151	0.065	0.216		Top	0.086	0.065	0.151
	Bottom	-	-	0.000		Bottom	-	-	0.000
	Right	0.578	-	0.578		Right	0.509	-	0.509
	Left	-	0.049	0.049		Left	-	0.049	0.049

Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	SPLS Ratio	Volume
Body SAR	Back	0.905	0.732	1.637	0.090	N/A
	Top	0.585	0.065	0.650	N/A	N/A
	Bottom	-	-	0.000	N/A	N/A
	Right	0.184	-	0.184	N/A	N/A
	Left	-	0.049	0.049	N/A	N/A

Simult Tx	Configuration	WCDMA 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	AWS WCDMA SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.847	0.732	1.579	Body SAR	Back	0.839	0.732	1.571
	Top	0.716	0.065	0.781		Top	0.887	0.065	0.952
	Bottom	-	-	0.000		Bottom	-	-	0.000
	Right	0.209	-	0.209		Right	0.262	-	0.262
	Left	-	0.049	0.049		Left	-	0.049	0.049

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 41 of 49

Table 15-2
Hotspot Simultaneous Transmission Scenario 1.0 and 0.5 cm Main Antenna (2.4 GHz WLAN)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back 1.0 cm	0.568	<0.732	<1.300	Body SAR	Back 1.0 cm	0.797	<0.732	<1.529
	Top 0.5 cm	0.615	<0.065	<0.68		Top 0.5 cm	1.060	<0.065	<1.120
Simult Tx	Configuration	WCDMA 850 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	AWS WCDMA SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back 1.0 cm	0.530	<0.732	<1.262	Body SAR	Back 1.0 cm	0.684	<0.732	<1.416
	Top 0.5 cm	0.377	<0.065	<0.442		Top 0.5 cm	1.170	<0.065	<1.230

Simult Tx	Configuration	WCDMA 1900 SAR (W/kg)	2.4 GHz WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back 1.0 cm	0.774	<0.732	<1.506
	Top 0.5 cm	1.180	<0.065	<1.240


15.3 SAR Sum to Peak Location Separation (SPLS) Ratio Analysis

Per FCC KDB Publication 648474 D01, when the sum of the standalone transmitters is more than 1.6 W/kg, the SAR sum to peak locations can be analyzed to determine SAR distribution overlaps. Based on the on the 1-g SAR limit and a separation distance of 5 cm, when the SAR peak to location ratio for each pair of antennas is < 0.3, simultaneous SAR evaluation is not required.

The sum of the standalone SAR values was above 1.6 W/kg for the following:

2.4 GHz WLAN+GPRS1900 Back,

$$\sqrt{\{(-2.9+1.85)^2 + (-9.15-8.25)^2 + (-20.6+20.3)^2\}} = 17.434 \text{ cm}$$



FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 42 of 49

Table 15-3
SAR Sum to Peak Location Separation Ratio Calculation Back

Antenna Pair	Standalone 1g SAR (W/kg)		Standalone SAR Sum (W/kg)	Peak SAR Separation Distance (cm)	SPLS Ratio
GPRS 1900-2.4 WLAN	0.905	0.732	1.637	17.4	0.09

Since the SPLS Ratio for each antenna pair was less than 0.3, no volumetric simultaneous transmission scenario is required per FCC KDB 648474 Publication D01

15.4 Simultaneous Transmission Conclusion

Per FCC KDB Publication 648474 D01, no aggregate volumetric simultaneous transmission is required for the device, since the sum of the standalone SAR values or the SAR Sum to peak separation ratios are < 0.3 for each antenna pair.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 43 of 49

16 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85070B	Dielectric Probe Kit	8/22/2010	Annual	8/22/2011	US33020316
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/13/2010	Annual	10/13/2011	3613A00315
Agilent	8753E	(30kHz-6GHz) Network Analyzer	4/21/2011	Annual	4/21/2012	JP38020182
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46110872
Agilent	E5515C	Wireless Communications Test Set	10/8/2010	Annual	10/8/2011	GB46310798
Agilent	E5515C	Wireless Communications Test Set	8/13/2010	Annual	8/13/2011	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/8/2011	Annual	4/8/2012	MY45470194
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/11/2010	Annual	10/11/2011	1833460
Gigatronics	8651A	Universal Power Meter	10/11/2010	Annual	10/11/2011	8650319
Rohde & Schwarz	CMU200	Base Station Simulator	11/11/2010	Annual	11/11/2011	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	6/1/2011	Annual	6/1/2012	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	4/19/2011	Annual	4/19/2012	107826
Rohde & Schwarz	NRVD	Dual Channel Power Meter	4/8/2011	Biennial	4/8/2013	101695
SPEAG	D1765V2	1765 MHz SAR Dipole	6/16/2011	Annual	6/16/2012	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	2/17/2011	Annual	2/17/2012	502
SPEAG	D1900V2	1900 MHz SAR Dipole	8/18/2009	Biennial	8/18/2011	5d080
SPEAG	D2450V2	2450 MHz SAR Dipole	8/27/2009	Biennial	8/27/2011	719
SPEAG	D2450V2	2450 MHz SAR Dipole	2/8/2011	Annual	2/8/2012	797
SPEAG	D2600V2	2600 MHz SAR Dipole	4/15/2011	Annual	4/15/2012	1004
SPEAG	D5GHZV2	5 GHz SAR Dipole	8/19/2009	Biennial	8/19/2011	1007
SPEAG	D5GHZV2	5 GHz SAR Dipole	2/11/2011	Annual	2/11/2012	1057
SPEAG	D835V2	835 MHz SAR Dipole	2/9/2011	Annual	2/9/2012	4d047
SPEAG	D835V2	835 MHz SAR Dipole	8/24/2009	Biennial	8/24/2011	4d026
SPEAG	DAE3	Dasy Data Acquisition Electronics	11/18/2010	Annual	11/18/2011	455
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2011	Annual	3/17/2012	704
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/20/2011	Annual	4/20/2012	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/21/2011	Annual	2/21/2012	649
SPEAG	ES3DV2	SAR Probe	9/21/2010	Annual	9/21/2011	3022
SPEAG	EX3DV4	SAR Probe	8/19/2010	Annual	8/19/2011	3561
SPEAG	EX3DV4	SAR Probe	2/14/2011	Annual	2/14/2012	3550
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/19/2011	Annual	5/19/2012	859
SPEAG	D750V3	750 MHz Dipole	2/14/2011	Annual	2/14/2012	1003
SPEAG	ES3DV3	SAR Probe	3/24/2011	Annual	3/24/2012	3213
SPEAG	ES3DV3	SAR Probe	4/18/2011	Annual	4/18/2012	3209
Rohde & Schwarz	SMIQ3B	Signal Generator	4/6/2011	Annual	4/6/2012	DE27259
SPEAG	D1640V2	1640 MHz Dipole	8/17/2010	Annual	8/17/2011	321
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	8/30/2010	Annual	8/30/2011	100976
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5318
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5442
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	1190013
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	98150041
Agilent	8648D	Signal Generator	4/5/2011	Annual	4/5/2012	3629U00687
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	1070030
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5821
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	8013
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5605
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	2400
Agilent	E5515C	Wireless Communications Test Set	8/13/2010	Annual	8/13/2011	GB43304447
Agilent	E5515C	Wireless Communications Tester	4/21/2011	Annual	4/21/2012	US41140256
Amplifier Research	5S1G4	5W, 800MHz-4.2GHz	N/A			21910
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	N/A			N/A
Agilent	E5515C	Wireless Communications Test Set	2/8/2011	Annual	2/8/2012	GB45360985
SPEAG	D3700V2	3700 MHz SAR Dipole	2/16/2011	Annual	2/16/2012	1002
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	3/11/2011	Annual	3/11/2012	103962
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331322
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331323
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331330
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331332
Control Company	61220-416	Long-Stem Thermometer	3/16/2011	Biennial	3/16/2013	111391601
SPEAG	ES3DV3	SAR Probe	4/8/2011	Annual	4/8/2012	3258
SPEAG	D1750V2	1750 MHz SAR Dipole	5/24/2011	Annual	5/24/2012	1051
MiniCircuits	SLP-2400+	Low Pass Filter	N/A			R8979500903
Narda	4772-3	Attenuator (3dB)	N/A			9406
Narda	BW-S3W2	Attenuator (3dB)	N/A			120

FCC ID: A3LSGHT859	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 44 of 49

17 MEASUREMENT UNCERTAINTIES

Applicable for 750 – 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.2	23.4

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 45 of 49

Applicable for 5 GHz:

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.55	6.55	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 46 of 49

18 CONCLUSION

18.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 47 of 49

19 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, June 2001.
- [6] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [7] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [10] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [11] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [12] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [13] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [14] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [15] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [16] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [17] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 48 of 49

- [18] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [19] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [20] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [21] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [22] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [23] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [24] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [25] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002
- [26] FCC SAR Measurement Procedures for 3G Devices KDB Publication 941225
- [27] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227
- [28] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publication 648474
- [29] FCC Application Note for SAR Probe Calibration and System Verification Consideration for Measurements at 150 MHz – 3 GHz, KDB Publication 450824
- [30] FCC SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens, KDB Publication 616217
- [31] FCC SAR Measurement Requirements for 3 – 6 GHz, KDB Publication 865664
- [32] FCC Mobile Portable RF Exposure Procedure, KDB Publication 447498
- [33] FCC SAR Procedures for Dongle Transmitters, KDB Publication 447498
- [34] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [35] FCC SAR Test Considerations for LTE Handsets and Data Modems, KDB Publication 941225.
- [36] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.
- [37] FCC D06 Hot Spot SAR v01, KDB Publication 941225.

FCC ID: A3LSGHT859		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1107191237-R1.A3L	Test Dates: 07/20/11 - 08/02/11	EUT Type: Portable Tablet Computer		Page 49 of 49

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.982 \text{ mho/m}$; $\epsilon_r = 54.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 22.8° C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (7x18x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.80 V/m

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.707 mW/g; SAR(10 g) = 0.372 mW/g



0 dB = 0.827mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.982 \text{ mho/m}$; $\epsilon_r = 54.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 22.8° C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (7x18x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.80 V/m

Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.707 mW/g; SAR(10 g) = 0.372 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-30-2011; Ambient Temp: 23.7° C; Tissue Temp: 22.6° C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.6 V/m

Peak SAR (extrapolated) = 0.922 W/kg

SAR(1 g) = 0.606 mW/g; SAR(10 g) = 0.381 mW/g



0 dB = 0.670mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.982 \text{ mho/m}$; $\epsilon_r = 54.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 22.8° C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Top Edge, Mid.ch, 2 Tx Slots


Area Scan (6x21x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.97 V/m

Peak SAR (extrapolated) = 0.245 W/kg

SAR(1 g) = 0.151 mW/g; SAR(10 g) = 0.096 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 07-30-2011; Ambient Temp: 23.7°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Top Edge, Mid.ch, 2 Tx Slots


Area Scan (6x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.6 V/m

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.615 mW/g; SAR(10 g) = 0.383 mW/g



0 dB = 0.709mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM850 GPRS; 2 Tx slots; Frequency: 836.6 MHz; Duty Cycle: 1:4.15

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-30-2011; Ambient Temp: 23.7°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 850, Body SAR, Right Edge, Mid.ch, 2 Tx Slots


Area Scan (5x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.4 V/m

Peak SAR (extrapolated) = 0.883 W/kg

SAR(1 g) = 0.578 mW/g; SAR(10 g) = 0.375 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body; Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 52.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Back Edge, High.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 29.4 V/m

Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 0.905 mW/g; SAR(10 g) = 0.402 mW/g



0 dB = 1.21mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.48 \text{ mho/m}$; $\epsilon_r = 52.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Back Edge, Mid.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 25.3 V/m

Peak SAR (extrapolated) = 1.38 W/kg

SAR(1 g) = 0.797 mW/g; SAR(10 g) = 0.395 mW/g



0 dB = 0.888mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.48 \text{ mho/m}$; $\epsilon_r = 52.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Top Edge, Mid.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.6 V/m

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.585 mW/g; SAR(10 g) = 0.251 mW/g



0 dB = 0.701mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body; Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 52.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Top Edge, High.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.0 V/m

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.518 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1909.8 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body; Medium parameters used:

$f = 1910 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 52.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Top Edge, High.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.0 V/m

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 1.06 mW/g; SAR(10 g) = 0.518 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: GSM1900 GPRS; 2 Tx slots; Frequency: 1880 MHz; Duty Cycle: 1:4.15

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.48 \text{ mho/m}$; $\epsilon_r = 52.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: GPRS 1900, Body SAR, Right Edge, Mid.ch, 2 Tx Slots


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.44 V/m

Peak SAR (extrapolated) = 0.312 W/kg

SAR(1 g) = 0.184 mW/g; SAR(10 g) = 0.097 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.982 \text{ mho/m}$; $\epsilon_r = 54.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Back side, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.4 V/m

Peak SAR (extrapolated) = 0.818 W/kg

SAR(1 g) = 0.425 mW/g; SAR(10 g) = 0.222 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-30-2011; Ambient Temp: 23.7°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Back side, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 23.1 V/m

Peak SAR (extrapolated) = 0.796 W/kg

SAR(1 g) = 0.530 mW/g; SAR(10 g) = 0.336 mW/g



0 dB = 0.577mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.982 \text{ mho/m}$; $\epsilon_r = 54.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Top Edge, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 9.86 V/m

Peak SAR (extrapolated) = 0.171 W/kg

SAR(1 g) = 0.086 mW/g; SAR(10 g) = 0.054 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 07-30-2011; Ambient Temp: 23.7°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Top Edge, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.0 V/m

Peak SAR (extrapolated) = 0.576 W/kg

SAR(1 g) = 0.377 mW/g; SAR(10 g) = 0.239 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body; Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-30-2011; Ambient Temp: 23.7°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 850, Body SAR, Right Edge, Mid.ch


Area Scan (5x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.5 V/m

Peak SAR (extrapolated) = 0.773 W/kg

SAR(1 g) = 0.509 mW/g; SAR(10 g) = 0.329 mW/g



0 dB = 0.554mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA1700; Frequency: 1730.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1730.4 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 52.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-01-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: AWS WCDMA, Body SAR, Back side, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.2 V/m

Peak SAR (extrapolated) = 1.85 W/kg

SAR(1 g) = 0.839 mW/g; SAR(10 g) = 0.371 mW/g



0 dB = 0.909mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA1700; Frequency: 1730.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1730.4 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 52.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: AWS WCDMA, Body SAR, Back side, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 21.8 V/m

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.684 mW/g; SAR(10 g) = 0.345 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA1700; Frequency: 1712.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1712.4 \text{ MHz}$; $\sigma = 1.49 \text{ mho/m}$; $\epsilon_r = 52.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-01-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1700, Body SAR, Top Edge, Low.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 27.0 V/m

Peak SAR (extrapolated) = 1.99 W/kg

SAR(1 g) = 0.887 mW/g; SAR(10 g) = 0.370 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA1700; Frequency: 1752.5 MHz; Duty Cycle: 1:1
Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1752.5 \text{ MHz}$; $\sigma = 1.54 \text{ mho/m}$; $\epsilon_r = 52.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 08-01-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: AWS WCDMA, Body SAR, Top Edge, High.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 10.4 V/m

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 1.17 mW/g; SAR(10 g) = 0.544 mW/g



0 dB = 1.37mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA1700; Frequency: 1752.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body; Medium parameters used (interpolated):

$f = 1752.5 \text{ MHz}$; $\sigma = 1.54 \text{ mho/m}$; $\epsilon_r = 52.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 08-01-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: AWS WCDMA, Body SAR, Top Edge, High.ch


Area Scan (7x21x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.4 V/m

Peak SAR (extrapolated) = 2.35 W/kg

SAR(1 g) = 1.17 mW/g; SAR(10 g) = 0.544 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA1700; Frequency: 1730.4 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1730.4 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 52.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-01-2011; Ambient Temp: 24.3°C; Tissue Temp: 22.6°C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1700, Body SAR, Right Edge, Mid.ch


Area Scan (5x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 14.1 V/m

Peak SAR (extrapolated) = 0.469 W/kg

SAR(1 g) = 0.262 mW/g; SAR(10 g) = 0.138 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 52.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Back Edge, High.ch


Area Scan (7x21x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.0 V/m

Peak SAR (extrapolated) = 1.62 W/kg

SAR(1 g) = 0.847 mW/g; SAR(10 g) = 0.383 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.48 \text{ mho/m}$; $\epsilon_r = 52.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Back Edge, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.5 V/m

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.774 mW/g; SAR(10 g) = 0.393 mW/g



0 dB = 0.823mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^7

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.48 \text{ mho/m}$; $\epsilon_r = 52.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Top Edge, Mid.ch


Area Scan (6x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.9 V/m

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.716 mW/g; SAR(10 g) = 0.309 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 52.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Top Edge, High.ch


Area Scan (6x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 12.1 V/m

Peak SAR (extrapolated) = 2.06 W/kg

SAR(1 g) = 1.18 mW/g; SAR(10 g) = 0.579 mW/g



0 dB = 1.36mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: S859^5

Communication System: WCDMA1900; Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.52 \text{ mho/m}$; $\epsilon_r = 52.32$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.5 cm

Test Date: 08-02-2011; Ambient Temp: 23.2° C; Tissue Temp: 21.9° C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Top Edge, High.ch


Area Scan (6x21x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.1 V/m

Peak SAR (extrapolated) = 2.06 W/kg

SAR(1 g) = 1.18 mW/g; SAR(10 g) = 0.579 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body; Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.48 \text{ mho/m}$; $\epsilon_r = 52.34$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: WCDMA 1900, Body SAR, Right Edge, Mid.ch


Area Scan (7x21x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.74 V/m

Peak SAR (extrapolated) = 0.351 W/kg

SAR(1 g) = 0.209 mW/g; SAR(10 g) = 0.112 mW/g



0 dB = 0.239mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-21-2011; Ambient Temp: 24.3 °C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(6.25, 6.25, 6.25); Calibrated: 2/14/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch.11, 1Mbps, Back Side


Area Scan (7x19x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.3 V/m

Peak SAR (extrapolated) = 1.67 W/kg

SAR(1 g) = 0.707 mW/g; SAR(10 g) = 0.283 mW/g



0 dB = 1.00mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-21-2011; Ambient Temp: 24.3 °C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(6.25, 6.25, 6.25); Calibrated: 2/14/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch.11, 1Mbps, Top Edge


Area Scan (6x20x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.18 V/m

Peak SAR (extrapolated) = 0.168 W/kg

SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.022 mW/g



0 dB = 0.086mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 51.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-21-2011; Ambient Temp: 24.3 °C; Tissue Temp: 22.9°C

Probe: EX3DV4 - SN3550; ConvF(6.25, 6.25, 6.25); Calibrated: 2/14/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11b, Body SAR, Ch.11, 1Mbps, Left Edge


Area Scan (6x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.08 V/m

Peak SAR (extrapolated) = 0.212 W/kg

SAR(1 g) = 0.050 mW/g; SAR(10 g) = 0.023 mW/g



0 dB = 0.068mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11g; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-26-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 4/8/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11g, Body SAR, Ch.11, 6 Mbps, Back Side


Area Scan (7x19x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.1 V/m

Peak SAR (extrapolated) = 1.74

SAR(1 g) = 0.732 mW/g; SAR(10 g) = 0.293 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11g; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-26-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 4/8/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11g, Body SAR, Ch.11, 6Mbps, Back Side


Area Scan (7x19x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.1 V/m

Peak SAR (extrapolated) = 1.74

SAR(1 g) = 0.732 mW/g; SAR(10 g) = 0.293 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11g; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-26-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 4/8/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11g, Body SAR, Ch.11, 6Mbps, Top Edge


Area Scan (6x20x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.00 V/m

Peak SAR (extrapolated) = 0.134 W/kg

SAR(1 g) = 0.060 mW/g; SAR(10 g) = 0.021 mW/g



0 dB = 0.095mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11g; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.95 \text{ mho/m}$; $\epsilon_r = 52$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-26-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 4/8/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11g, Body SAR, Ch.11, 6 Mbps, Left Edge


Area Scan (6x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 4.62 V/m

Peak SAR (extrapolated) = 0.107 W/kg

SAR(1 g) = 0.049 mW/g; SAR(10 g) = 0.022 mW/g



0 dB = 0.068mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.49 \text{ mho/m}$; $\epsilon_r = 48.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.4 ° C; Tissue Temp: 22.3 ° C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz, Body SAR, Ch 100, 6 Mbps, Back Side


Area Scan (9x29x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 13.0 V/m

Peak SAR (extrapolated) = 4.47 W/kg

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.270 mW/g



0 dB = 2.04mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.49 \text{ mho/m}$; $\epsilon_r = 48.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.4 ° C; Tissue Temp: 22.3 ° C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz, Body SAR, Ch 100, 6 Mbps, Top Edge


Area Scan (7x29x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 15.9 V/m

Peak SAR (extrapolated) = 4.76 W/kg

SAR(1 g) = 1.12 mW/g; SAR(10 g) = 0.323 mW/g



0 dB = 2.42mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.49 \text{ mho/m}$; $\epsilon_r = 48.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.4 ° C; Tissue Temp: 22.3 ° C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz, Body SAR, Ch 100, 6 Mbps, Top Side


Area Scan (7x29x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 15.9 V/m

Peak SAR (extrapolated) = 4.76 W/kg

SAR(1 g) = 1.12 mW/g; SAR(10 g) = 0.323 mW/g



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSGHT859; Type: Portable Tablet Computer; Serial: 859^5

Communication System: IEEE 802.11a 5.2-5.8 GHz Band; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body; Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.49 \text{ mho/m}$; $\epsilon_r = 48.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.4 ° C; Tissue Temp: 22.3 ° C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

Mode: IEEE 802.11a, 5.5 GHz, Body SAR, Ch 100, 6 Mbps, Left Side


Area Scan (7x21x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x11)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 5.03 V/m

Peak SAR (extrapolated) = 0.452 W/kg

SAR(1 g) = 0.143 mW/g; SAR(10 g) = 0.077 mW/g



0 dB = 0.233mW/g

APPENDIX B: DIPOLE VALIDATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.989 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 07-30-2011; Ambient Temp: 23.7 ° C; Tissue Temp: 22.6 °C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

835MHz System Verification


Area Scan (7x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 18.0 dBm (63 mW)

SAR(1 g) = 0.653 mW/g; SAR(10 g) = 0.426 mW/g

Deviation = 5.23 %



0 dB = 0.706mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d047

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.98 \text{ mho/m}$; $\epsilon_r = 54.19$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space 1.5 cm

Test Date: 08-02-2011; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3258; ConvF(6.12, 6.12, 6.12); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

835MHz System Verification


Area Scan (7x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 24.0 dBm (250 mW)

SAR(1 g) = 2.4 mW/g; SAR(10 g) = 1.56 mW/g

Deviation = -2.54 %



0 dB = 2.59mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: 1051

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.54 \text{ mho/m}$; $\epsilon_r = 52.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-01-2011; Ambient Temp: 24.3 °C; Tissue Temp: 22.6 °C

Probe: ES3DV3 - SN3258; ConvF(5, 5, 5); Calibrated: 4/8/2011

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1406

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

1750 MHz System Verification


Area Scan (6x6x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 16 dBm (40 mW)

SAR(1 g) = 1.55 mW/g; SAR(10 g) = 0.812 mW/g

Deviation = 4.73 %



0 dB = 1.74mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 502

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.51 \text{ mho/m}$; $\epsilon_r = 52.33$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 08-02-2011; Ambient Temp: 23.2°C; Tissue Temp: 21.9°C

Probe: ES3DV2 - SN3022; ConvF(4.34, 4.34, 4.34); Calibrated: 9/21/2010

Sensor-Surface: 4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn704; Calibrated: 3/17/2011

Phantom: SAM with CRP; Type: SAM; Serial: TP1375

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

1900MHz System Verification


Area Scan (5x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 20 dBm (100 mW)

SAR(1 g) = 4.29 mW/g; SAR(10 g) = 2.25 mW/g

Deviation = 4.38 %



0 dB = 4.78mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body ; Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.914 \text{ mho/m}$; $\epsilon_r = 51.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-21-2011; Ambient Temp: 24.3 °C; Tissue Temp: 22.9

Probe: EX3DV4 - SN3550; ConvF(6.25, 6.25, 6.25); Calibrated: 2/14/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

2450MHz System Verification


Area Scan (5x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 1.34 mW/g; SAR(10 g) = 0.615 mW/g

Deviation = 2.49 %



0 dB = 1.73mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.93 \text{ mho/m}$; $\epsilon_r = 52.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-26-2011; Ambient Temp: 23.2 °C; Tissue Temp: 21.7° C

Probe: ES3DV3 - SN3258; ConvF(4.34, 4.34, 4.34); Calibrated: 4/8/2011

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 2/21/2011

Phantom: SAM Main; Type: SAM 4.0; Serial: TP-1114

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

2450MHz System Verification


Area Scan (5x7x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power = 14 dBm (25 mW)

SAR(1 g) = 1.3 mW/g; SAR(10 g) = 0.604 mW/g

Deviation = -0.57 %



0 dB = 1.65mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5200 \text{ MHz}$; $\sigma = 5.08 \text{ mho/m}$; $\epsilon_r = 48.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.2 ° C; Tissue Temp: 22.1 ° C

Probe: EX3DV4 - SN3550; ConvF(3.58, 3.58, 3.58); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5200MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 2.1 mW/g; SAR(10 g) = 0.579 mW/g

Deviation = 8.11 %



0 dB = 4.33mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5500 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5500 \text{ MHz}$; $\sigma = 5.49 \text{ mho/m}$; $\epsilon_r = 48.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.4 ° C; Tissue Temp: 22.3 ° C

Probe: EX3DV4 - SN3550; ConvF(3.21, 3.21, 3.21); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5500MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 2.19 mW/g; SAR(10 g) = 0.597 mW/g

Deviation = 3.79 %



0 dB = 4.62mW/g

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used (interpolated):

$f = 5800 \text{ MHz}$; $\sigma = 5.96 \text{ mho/m}$; $\epsilon_r = 48$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 07-20-2011; Ambient Temp: 23.5 ° C; Tissue Temp: 22.4 ° C

Probe: EX3DV4 - SN3550; ConvF(3.29, 3.29, 3.29); Calibrated: 2/14/2011

Sensor-Surface: 2mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 4/20/2011

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

5800MHz System Verification


Area Scan (7x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x11)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=2\text{mm}$

Input Power = 14 dBm (25 mW)

SAR(1 g) = 1.95 mW/g; SAR(10 g) = 0.530 mW/g

Deviation = 4.00 %



0 dB = 4.16mW/g