



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



MEASUREMENT REPORT

FCC Part 22, 24, & 27 / IC RSS-132/RSS-133/RSS-139

Applicant Name:

Samsung Electronics, Co. Ltd.
18600 Broadwick St.
Rancho Dominguez, CA 90220
United States

Date of Testing:

December 27-31, 2010

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1012232044.A3L

FCC ID:

A3LSGHT959V

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

Application Type:

Certification

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

§2; §22(H), §24(E), §27(L)

IC Specification(s):

RSS-132 Issue 2; RSS-133 Issue 5; RSS-139 Issue 2

EUT Type:

850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN

Model(s):

SGH-T959V

Tx Frequency Range:

824.20 - 848.80MHz (Cell. GSM) / 1850.20 - 1909.80MHz (PCS GSM)
1712.40 - 1752.5MHz (AWS WCDMA) / 1852.4 - 1907.6MHz (PCS WCDMA)

Max. RF Output Power:

0.877 W ERP Cell. GSM (29.43 dBm) / 1.259 W EIRP PCS GSM (31 dBm)
0.393 W ERP EDGE850 (25.94 dBm) / 0.526 W EIRP EDGE1900 (27.21 dBm)
0.535 W EIRP AWS WCDMA (27.28 dBm) / 0.472 W EIRP PCS WCDMA (26.74 dBm)
246KGXW (Cellular GSM), 246KGXW (PCS GSM)
243KG7W (EDGE850), 245KG7W (EDGE1900)
4M20F9W (AWS WCDMA), 4M20F9W (PCS WCDMA)

Emission Designator(s):**Test Device Serial No.:**

identical prototype [S/N: FH-281-A]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is ERP for Part 22 and EIRP for Part 24 & 27

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 1 of 59

TABLE OF CONTENTS

FCC PART 22, 24 & 27 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 SCOPE	4
1.2 TESTING FACILITY	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.3 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TESTS	6
3.1 MEASUREMENT PROCEDURE	6
3.2 OCCUPIED BANDWIDTH	6
3.3 CELLULAR - BASE FREQUENCY BLOCKS	6
3.4 CELLULAR - MOBILE FREQUENCY BLOCKS	7
3.5 PCS - BASE FREQUENCY BLOCKS	7
3.6 PCS - MOBILE FREQUENCY BLOCKS	7
3.7 AWS - BASE FREQUENCY BLOCKS	7
3.8 AWS - MOBILE FREQUENCY BLOCKS	8
3.9 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	8
3.10 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.11 PEAK-AVERAGE RATIO	9
3.12 FREQUENCY STABILITY / TEMPERATURE VARIATION	9
4.0 TEST EQUIPMENT CALIBRATION DATA	10
5.0 SAMPLE CALCULATIONS	11
6.0 TEST RESULTS	12
6.1 SUMMARY	12
6.2 EFFECTIVE RADIATED POWER OUTPUT DATA	13
6.3 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA	14
6.4 CELLULAR GSM RADIATED MEASUREMENTS	15
6.5 PCS GSM RADIATED MEASUREMENTS	18
6.6 PCS WCDMA RADIATED MEASUREMENTS	21
6.7 AWS WCDMA RADIATED MEASUREMENTS	24
6.8 CELLULAR GSM FREQUENCY STABILITY MEASUREMENTS	27
6.9 PCS GSM FREQUENCY STABILITY MEASUREMENTS	29
6.10 PCS WCDMA FREQUENCY STABILITY MEASUREMENTS	31
6.11 AWS WCDMA FREQUENCY STABILITY MEASUREMENTS	33
6.12 RECEIVER SPURIOUS EMISSIONS	35
7.0 PLOTS OF EMISSIONS	36
8.0 CONCLUSION	59

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 2 of 59



MEASUREMENT REPORT

FCC Part 22, 24 & 27



§2.1033 General Information

APPLICANT: Samsung Electronics, Co. Ltd.
APPLICANT ADDRESS: 18600 Broadwick St.
 Rancho Dominguez, CA 90220, United States
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §22(H), §24(E), §27(L)
IC SPECIFICATION(S): RSS-132 Issue 2; RSS-133 Issue 5; RSS-139 Issue 2
BASE MODEL: SGH-T959V
FCC ID: A3LSGHT959V
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
EMISSION DESIGNATOR(S): 246KGXW (Cellular GSM), 246KGXW (PCS GSM)
 243KG7W (EDGE850), 245KG7W (EDGE1900)
 4M20F9W (AWS WCDMA), 4M20F9W (PCS WCDMA)
MODE: GSM/EDGE/WCDMA
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: FH-281-A ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: December 27-31, 2010
TEST REPORT S/N: 0Y1012232044.A3L

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 3 of 59

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 28, 2009.



Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 4 of 59

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN FCC ID: A3LSGHT959V**. The EUT consisted of the following component(s):

Trade Name / Base Model	FCC ID	Description
Samsung / Model: SGH-T959V	A3LSGHT959V	850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN

Table 2-1. EUT Equipment Description

2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 5 of 59

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (See Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



Figure 3-1. Diagram of 3-meter outdoor test range


Deviation from Measurement Procedure.....None

3.2 Occupied Bandwidth

§2.1049, RSS-Gen (4.6.1)


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

3.3 Cellular - Base Frequency Blocks



FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 6 of 59

3.4 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 4: 846.5 – 849 MHz (B*)

3.5 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 2: 1945 – 1950 MHz (D)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 6: 1975 – 1990 MHz (C)

3.6 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 3: 1870 – 1885 MHz (B)


BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 6: 1895 – 1910 MHz (C)

3.7 AWS - Base Frequency Blocks

§27.5(h)



BLOCK 1: 2110 – 2120 MHz (A)

BLOCK 2: 2120 – 2130 MHz (B)

BLOCK 3: 2130 – 2135 MHz (C)

BLOCK 4: 2135 – 2140 MHz (D)


BLOCK 5: 2140 – 2145 MHz (E)

BLOCK 6: 2145 – 2155 MHz (E)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 7 of 59

3.8 AWS - Mobile Frequency Blocks

§27.5(h)



BLOCK 1: 1710 – 1720 MHz (A)

BLOCK 2: 1720 – 1730 MHz (B)

BLOCK 3: 1730 – 1735 MHz (C)

BLOCK 4: 1735 – 1740 MHz (D)

BLOCK 5: 1740 – 1745 MHz (E)

BLOCK 6: 1745 – 1755 MHz (F)

3.9 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a), 24.238(a)(b), §27.53(g); RSS-132 (4.5.1), RSS-133 (6.5.1), RSS-139 (6.5)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

3.10 Radiated Power and Radiated Spurious Emissions

§2.1053, 22.913(a)(2), 22.917(a), 24.232(c), 24.238(a), §27.53(g); RSS-132 (4.5.1), RSS-133 (6.5.1), RSS-139 (6.4.6.5)

Radiated power and radiated spurious emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This level is then measured with a broadband average power meter. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive average power meter reading. This spurious level is recorded with the power meter. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: OY1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 8 of 59

3.11 Peak-Average Ratio

§24.232(d), §27.50(d)(5); RSS-133 (6.4), RSS-139 (6.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth.

3.12 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235, §27.54; RSS-132 (4.3) / RSS-133 (6.3), RSS-139 (6.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 9 of 59

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	263-10dB	(DC-18GHz) 10 dB Attenuator	N/A		N/A	N/A
-	No.166	(1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167	(100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	85650A	Quasi-Peak Adapter	3/30/2010	Annual	3/30/2011	2043A00301
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/11/2010	Annual	10/11/2011	3613A00315
Agilent	E4407B	ESA Spectrum Analyzer	3/30/2010	Annual	3/30/2011	US39210313
Agilent	E4448A	PSA (3Hz-50GHz) Spectrum Analyzer	10/11/2010	Annual	10/11/2011	US42510244
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46110872
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46310798
Agilent	E5515C	Wireless Communications Test Set	8/12/2010	Annual	8/12/2011	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/30/2010	Annual	3/30/2011	MY45470194
Agilent	E8267C	Vector Signal Generator	10/11/2010	Annual	10/11/2011	US42340152
Agilent	N9020A	MXA Signal Analyzer	9/8/2010	Annual	9/8/2011	US46470561
Anritsu	ML2495A	Power Meter	10/13/2010	Annual	10/13/2011	941001
Anritsu	MA2411B	Pulse Sensor	11/13/2010	Annual	11/13/2011	1027293
Compliance Design	Roberts	Dipole Set	4/7/2010	Biennial	4/7/2012	146
Compliance Design	Roberts	Dipole Set	4/7/2010	Biennial	4/7/2012	147
Emco	3115	Horn Antenna (1-18GHz)	10/14/2009	Biennial	10/14/2011	9704-5182
Emco	3115	Horn Antenna (1-18GHz)	4/8/2010	Biennial	4/8/2012	9205-3874
Espec	ESX-2CA	Environmental Chamber	4/1/2010	Annual	4/1/2011	17620
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/11/2010	Annual	10/11/2011	1833460
Gigatronics	8651A	Universal Power Meter	10/11/2010	Annual	10/11/2011	8650319
K & L	11SH10	Band Pass Filter	N/A	Annual	N/A	1300/4000
K & L	11SH10	Band Pass Filter	N/A	Annual	N/A	4000/12000
MiniCircuits	VHF-1300+	High Pass Filter	N/A		N/A	30716
MiniCircuits	VHF-3100+	High Pass Filter	N/A		N/A	30721
Pasternack	PE2208-6	Bidirectional Coupler	N/A		N/A	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	11/11/2010	Annual	11/11/2011	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	6/21/2010	Annual	6/21/2011	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	6/17/2010	Annual	6/17/2011	836536/0005
Rohde & Schwarz	FSQ 26	Spectrum Analyzer	8/28/2010	Annual	8/28/2011	200452
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	8/30/2010	Annual	8/30/2011	100976
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Rx	7/17/2009	Biennial	7/17/2011	9105-2404
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Tx	7/17/2009	Biennial	7/17/2011	9105-2403
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	5/14/2009	Biennial	5/14/2011	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/17/2009	Biennial	7/17/2011	A051107

Table 4-1. Test Equipment

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 10 of 59

5.0 SAMPLE CALCULATIONS

GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission - PCS Band

Example: GSM Channel 512 PCS Mode 2nd Harmonic (3700.40 MHz)

The average receive power meter reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the power meter. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 11 of 59

6.0 TEST RESULTS

6.1 Summary

Company Name: Samsung Electronics, Co. Ltd.
 FCC ID: A3LSGHT959V
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM/EDGE/WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
2.1049 22.917(a) 24.238(a) 27.53(h)(1)	RSS-Gen (4.6.1) RSS-133 (2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a) 24.238(a) 27.53(h)	RSS-132 (4.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Band Edge / Conducted Spurious Emissions	< 43 + log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.0
24.232(d) 27.50(d)(5)	RSS-133 (6.4) RSS-139 (6.4)	Peak-Average Ratio	< 13 dB		PASS	Section 7.0
2.1046	RSS-132 (4.4) RSS-133 (4.1) RSS-139 (4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
22.913(a)(2)	RSS-132 (4.4) [SRSP-503(5.1.3)]	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 6.2
24.232(c) 27.50(d)(4)	RSS-133 (6.4) [SRSP-510 (5.1.2)] RSS-139 (6.4)	Equivalent Isotropic Radiated Power	< 1 Watt max. EIRP (AWS) < 2 Watts max. EIRP (PCS)		PASS	Section 6.3
2.1053, 22.917(a) 24.238(a) 27.53(h)	RSS-132 (4.5.1) RSS-133 (6.5.1) RSS-139 (6.5)	Undesirable Emissions	< 43 + log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Sections 6.4, 6.5, 6.6, 6.7
2.1055, 22.355, 24.235, 27.54	RSS-132 (4.3) RSS-133 (6.3) RSS-139 (6.3)	Frequency Stability	< 2.5 ppm		PASS	Sections 6.8, 6.9, 6.10, 6.11
RECEIVER MODE (RX) / DIGITAL EMISSIONS						
N/A	RSS-132 (4.6) RSS-133 (6.6) RSS-139 (6.6)	Receiver Spurious Emissions Limits	< RSS-Gen limits [Section 6; Table 1]	RADIATED	PASS	Section 6.12

Table 6-1. Summary of Test Results

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN			Page 12 of 59

6.2 Effective Radiated Power Output Data

§22.913(a)(2); RSS-132 (4.4) [SRSP-503(5.1.3)]

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Battery Type
824.20	GSM850	-9.710	28.76	0.00	V	28.76	0.752	Standard
836.60	GSM850	-9.040	29.43	0.00	V	29.43	0.877	Standard
848.80	GSM850	-9.770	28.70	0.00	V	28.70	0.741	Standard
836.60	EDGE850	-12.530	25.94	0.00	V	25.94	0.393	Standard

Table 6-2. Effective Radiated Power Output Data (GSM)

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 13 of 59

6.3 Equivalent Isotropic Radiated Power Output Data

§24.232(c), §27.50(d)(2); RSS-133 (6.4) [SRSP-510 (5.1.2)], RSS-139 (6.4)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1850.20	GSM1900	-10.130	23.00	8.00	H	31.00	1.259	Standard
1880.00	GSM1900	-10.810	22.32	8.00	H	30.32	1.076	Standard
1909.80	GSM1900	-10.460	22.67	8.00	H	30.67	1.167	Standard
1850.20	EDGE1900	-13.920	19.21	8.00	H	27.21	0.526	Standard

Table 6-3. Equivalent Isotropic Radiated Power Output Data (GSM)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1852.40	WCDMA1900	-15.350	17.78	8.00	H	25.78	0.378	Standard
1880.00	WCDMA1900	-14.390	18.74	8.00	H	26.74	0.472	Standard
1907.60	WCDMA1900	-15.410	17.72	8.00	H	25.72	0.373	Standard

Table 6-4. Equivalent Isotropic Radiated Power Output Data (WCDMA)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1712.40	WCDMA1700	-16.010	18.79	8.49	H	27.28	0.535	Standard
1732.50	WCDMA1700	-16.830	17.97	8.50	H	26.47	0.444	Standard
1752.50	WCDMA1700	-16.450	18.35	8.51	H	26.86	0.485	Standard

Table 6-5. Equivalent Isotropic Radiated Power Output Data (AWS WCDMA)

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 14 of 59

6.4 Cellular GSM Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MEASURED OUTPUT POWER: 29.430 dBm = 0.877 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 42.43 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1648.40	-47.59	6.42	-41.17	V	70.6
2472.60	-46.07	6.74	-39.33	V	68.8
3296.80	-55.97	7.55	-48.42	V	77.8
4121.00	-56.93	7.56	-49.38	V	78.8
4945.20	-54.18	9.05	-45.13	V	74.6

Table 6-6. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: OY1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 15 of 59

Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MEASURED OUTPUT POWER: 29.430 dBm = 0.877 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 42.43 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1673.20	-44.20	6.43	-37.78	V	67.2
2509.80	-44.89	6.77	-38.12	V	67.5
3346.40	-57.15	7.55	-49.60	V	79.0
4183.00	-56.82	7.81	-49.01	V	78.4
5019.60	-55.58	9.02	-46.55	V	76.0

Table 6-7. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 16 of 59

Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MEASURED OUTPUT POWER: 29.430 dBm = 0.877 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 42.43 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1697.60	-45.20	6.44	-38.76	V	68.2
2546.40	-45.57	6.83	-38.74	V	68.2
3395.20	-53.77	7.55	-46.22	V	75.7
4244.00	-57.14	8.06	-49.08	V	78.5
5092.80	-55.28	8.91	-46.36	V	75.8

Table 6-8. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 17 of 59

6.5 PCS GSM Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 31.000 dBm = 1.259 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 44.00 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3700.40	-41.70	9.49	-32.21	H	63.2
5550.60	-47.51	10.41	-37.11	H	68.1
7400.80	-52.46	11.08	-41.38	H	72.4
9251.00	-48.91	12.26	-36.65	H	67.6
11101.20	-49.68	13.19	-36.49	H	67.5

Table 6-9. Radiated Spurious Data (PCS GSM Mode – Ch. 512)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 18 of 59

PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 31.000 dBm = 1.259 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 44.00 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-42.15	9.43	-32.72	H	63.7
5640.00	-49.63	10.24	-39.39	H	70.4
7520.00	-50.97	11.12	-39.85	H	70.9
9400.00	-48.34	12.32	-36.02	H	67.0
11280.00	-49.60	13.17	-36.43	H	67.4

Table 6-10. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 19 of 59

PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MEASURED OUTPUT POWER: 31.000 dBm = 1.259 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) = 44.00$ dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3819.60	-42.72	9.37	-33.34	H	64.3
5729.40	-48.80	10.08	-38.72	H	69.7
7639.20	-50.04	11.21	-38.83	H	69.8
9549.00	-47.96	12.38	-35.59	H	66.6
11458.80	-48.93	13.15	-35.78	H	66.8

Table 6-11. Radiated Spurious Data (PCS GSM Mode – Ch. 810)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 20 of 59

6.6 PCS WCDMA Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MEASURED OUTPUT POWER: 26.740 dBm = 0.472 W
 MODULATION SIGNAL: WCDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.74 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3704.80	-49.50	9.49	-40.02	H	66.8
5557.20	-51.25	10.39	-40.86	H	67.6
7409.60	-52.30	11.08	-41.21	H	68.0
9262.00	-87.32	12.27	-75.05	H	101.8
11114.40	-85.49	13.19	-72.30	H	99.0

Table 6-12. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: OY1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 21 of 59

PCS WCDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MEASURED OUTPUT POWER: 26.740 dBm = 0.472 W
 MODULATION SIGNAL: WCDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.74 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-47.41	9.43	-37.98	H	64.7
5640.00	-49.68	10.24	-39.44	H	66.2
7520.00	-52.12	11.12	-41.00	H	67.7
9400.00	-87.50	12.32	-75.18	H	101.9
11280.00	-84.83	13.17	-71.66	H	98.4

Table 6-13. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: OY1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 22 of 59

PCS WCDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1907.60 MHz
 CHANNEL: 9538
 MEASURED OUTPUT POWER: 26.740 dBm = 0.472 W
 MODULATION SIGNAL: WCDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 39.74 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3815.20	-50.22	9.38	-40.85	H	67.6
5722.80	-50.28	10.09	-40.19	H	66.9
7630.40	-52.63	11.21	-41.43	H	68.2
9538.00	-87.57	12.37	-75.19	H	101.9
11445.60	-84.18	13.16	-71.02	H	97.8

Table 6-14. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: OY1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 23 of 59

6.7 AWS WCDMA Radiated Measurements

§2.1053, 27.53(g); RSS-139 (6.5)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1712.40 MHz
 CHANNEL: 1312
 MEASURED OUTPUT POWER: 27.280 dBm = 0.535 W
 MODULATION SIGNAL: WCDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 40.28 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3424.80	-50.42	9.70	-40.72	H	68.0
5137.20	-45.24	11.00	-34.24	H	61.5
6849.60	-48.11	11.18	-36.94	H	64.2
8562.00	-84.09	11.64	-72.46	H	99.7
10274.40	-82.98	12.74	-70.23	H	97.5

Table 6-15. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1312)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 24 of 59

AWS WCDMA Radiated Measurements (Cont'd)

§2.1053, 27.53(g); RSS-139 (6.5)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1732.50 MHz
 CHANNEL: 1412
 MEASURED OUTPUT POWER: 27.280 dBm = 0.535 W
 MODULATION SIGNAL: WCDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 40.28 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3465.00	-47.92	9.70	-38.22	H	65.5
5197.50	-45.64	10.92	-34.72	H	62.0
6930.00	-48.07	11.08	-36.99	H	64.3
8662.50	-83.94	11.76	-72.18	H	99.5
10395.00	-82.87	12.83	-70.04	H	97.3

Table 6-16. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1412)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 25 of 59

AWS WCDMA Radiated Measurements (Cont'd)

§2.1053, 27.53(g); RSS-139 (6.5)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1752.50 MHz
 CHANNEL: 1862
 MEASURED OUTPUT POWER: 27.280 dBm = 0.535 W
 MODULATION SIGNAL: WCDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 40.28 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3505.00	-48.66	9.69	-38.97	H	66.2
5257.50	-45.95	10.83	-35.12	H	62.4
7010.00	-47.66	11.00	-36.66	H	63.9
8762.50	-83.79	11.88	-71.91	H	99.2
10515.00	-82.72	12.91	-69.81	H	97.1

Table 6-17. Radiated Spurious Data (AWS WCDMA Mode – Ch. 1862)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the vertical polarity for Cellular band and horizontal polarity for AWS/PCS band. The data reported in the table above was measured in this test setup.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 26 of 59

6.8 Cellular GSM Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,600,002	2	0.000000
100 %		- 30	836,600,004	4	0.000000
100 %		- 20	836,600,016	16	0.000002
100 %		- 10	836,599,997	-3	0.000000
100 %		0	836,599,985	-15	-0.000002
100 %		+ 10	836,599,996	-4	0.000000
100 %		+ 20	836,600,008	8	0.000001
100 %		+ 30	836,600,012	12	0.000001
100 %		+ 40	836,600,017	17	0.000002
100 %		+ 50	836,600,005	5	0.000001
115 %	4.26	+ 20	836,599,996	-4	0.000000
BATT. ENDPOINT	3.40	+ 20	836,600,006	6	0.000001

Table 6-18. Frequency Stability Data (Cellular GSM Mode – Ch. 190)

Cellular GSM Frequency Stability Measurements (Cont'd)
§2.1055, 22.355; RSS-132 (4.3)




Figure 6-1. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 28 of 59

6.9 PCS GSM Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,880,000,021	21	0.000001
100 %		- 30	1,880,000,004	4	0.000000
100 %		- 20	1,880,000,007	7	0.000000
100 %		- 10	1,880,000,012	12	0.000001
100 %		0	1,880,000,003	3	0.000000
100 %		+ 10	1,879,999,993	-7	0.000000
100 %		+ 20	1,879,999,995	-5	0.000000
100 %		+ 30	1,879,999,989	-11	-0.000001
100 %		+ 40	1,880,000,008	8	0.000000
100 %		+ 50	1,879,999,997	-3	0.000000
115 %	4.26	+ 20	1,880,000,006	6	0.000000
BATT. ENDPOINT	3.40	+ 20	1,880,000,002	2	0.000000

Table 6-19. Frequency Stability Data (PCS GSM Mode – Ch. 661)

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 29 of 59

PCS GSM Frequency Stability Measurements (Cont'd)
§2.1055, 24.235; RSS-133 (6.3)




Figure 6-2. Frequency Stability Graph (PCS GSM Mode – Ch. 661)

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 30 of 59

6.10 PCS WCDMA Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 9400
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,879,999,995	-5	0.000000
100 %		- 30	1,879,999,986	-14	-0.000001
100 %		- 20	1,879,999,982	-18	-0.000001
100 %		- 10	1,880,000,021	21	0.000001
100 %		0	1,880,000,025	25	0.000001
100 %		+ 10	1,879,999,994	-6	0.000000
100 %		+ 20	1,880,000,007	7	0.000000
100 %		+ 30	1,880,000,002	2	0.000000
100 %		+ 40	1,879,999,996	-4	0.000000
100 %		+ 50	1,880,000,022	22	0.000001
115 %	4.26	+ 20	1,880,000,014	14	0.000001
BATT. ENDPOINT	3.40	+ 20	1,879,999,992	-8	0.000000

Table 6-20. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

PCS WCDMA Frequency Stability Measurements (Cont'd)
§2.1055, 24.235; RSS-133 (6.3)




Figure 6-3. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 32 of 59

6.11 AWS WCDMA Frequency Stability Measurements

§2.1055, 27.43; RSS-139 (6.3)

OPERATING FREQUENCY: 1,732,500,000 Hz

CHANNEL: 1412

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,732,500,005	5	0.000000
100 %		- 30	1,732,500,012	12	0.000001
100 %		- 20	1,732,500,004	4	0.000000
100 %		- 10	1,732,500,016	16	0.000001
100 %		0	1,732,499,995	-5	0.000000
100 %		+ 10	1,732,499,988	-12	-0.000001
100 %		+ 20	1,732,499,996	-4	0.000000
100 %		+ 30	1,732,500,002	2	0.000000
100 %		+ 40	1,732,500,014	14	0.000001
100 %		+ 50	1,732,500,011	11	0.000001
115 %	4.26	+ 20	1,732,499,997	-3	0.000000
BATT. ENDPOINT	3.39	+ 20	1,732,499,984	-16	-0.000001

Table 6-21. Frequency Stability Data (AWS WCDMA Mode – Ch. 1412)

AWS WCDMA Frequency Stability Measurements (Cont'd)

§2.1055, 24.235; RSS-133 (6.3)




Figure 6-4. Frequency Stability Graph (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 34 of 59

6.12 Receiver Spurious Emissions

RSS-132 (4.6), RSS-133 (6.6)

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol [H/V]	Height [m]	Azimuth [degrees]	Field Strength [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]
57.10	-85.19	11.67	V	1.4	125	33.48	40.00	-6.52
126.30	-85.54	12.19	V	1.3	270	33.65	43.52	-9.87
248.80	-87.30	11.21	V	1.6	235	30.91	46.02	-15.11
341.30	-89.45	14.56	V	1.4	25	32.11	46.02	-13.91
780.20	-90.65	17.13	V	2.1	70	33.48	46.02	-12.54
833.70	-89.20	23.24	H	2.6	90	41.04	46.02	-4.98

Table 6-22. Radiated Measurements at 3-meters




Figure 6-5. 3-Meter Limits


NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The EUT was set to receive mode in the middle channel of operation.
3. Radiated emissions were measured from 30MHz to three times that of the highest tunable frequency or local oscillator.
4. The radiated limits are shown on Figure 6-5. Above 960MHz the limit is 500 μ V/m.


1. All readings are calibrated by a Signal Generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
2. AFCL = Antenna Factor and Cable Loss
3. Measurements are made using CISPR quasi-peak mode. Average measurements are recorded above 1GHz.

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 35 of 59

7.0 PLOTS OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-2. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 36 of 59




Plot 7-3. Band Edge Plot (Cellular GSM Mode – Ch. 128)




Plot 7-4. Conducted Spurious (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 37 of 59




Plot 7-5. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)




Plot 7-6. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 38 of 59




Plot 7-7. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-8. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 39 of 59




Plot 7-9. Band Edge Plot (Cellular GSM Mode – Ch. 251)




Plot 7-10. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 40 of 59




Plot 7-11. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-12. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 41 of 59




Plot 7-13. Band Edge Plot (PCS GSM Mode – Ch. 512)




Plot 7-14. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 42 of 59




Plot 7-15. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-16. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 43 of 59




Plot 7-17. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)




Plot 7-18. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 44 of 59




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)



Plot 7-20. Band Edge Plot (PCS GSM Mode – Ch. 810)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 45 of 59




Plot 7-21. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)




Plot 7-22. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 46 of 59




Plot 7-23. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-24. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 47 of 59




Plot 7-25. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-26. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 48 of 59




Plot 7-27. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-28. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 49 of 59




Plot 7-29. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-30. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 50 of 59




Plot 7-31. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)




Plot 7-32. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 51 of 59




Plot 7-33. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)




Plot 7-34. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 52 of 59




Plot 7-35. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-36. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 53 of 59




Plot 7-37. Band Edge Plot (AWS WCDMA Mode – Ch. 1312)




Plot 7-38. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1312)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 54 of 59




Plot 7-39. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-40. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 55 of 59




Plot 7-41. Occupied Bandwidth Plot (AWS WCDMA Mode – Ch. 1412)




Plot 7-42. Peak-Average Ratio Plot (AWS WCDMA Mode – Ch. 1412)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 56 of 59



Plot 7-43. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)




Plot 7-44. Conducted Spurious Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 57 of 59



Plot 7-45. Band Edge Plot (AWS WCDMA Mode – Ch. 1862)



Plot 7-46. 4MHz Span Plot (AWS WCDMA Mode – Ch. 1862)

FCC ID: A3LSGHT959V	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 58 of 59

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN FCC ID: A3LSGHT959V** complies with all the requirements of Parts 2, 22, 24 and 27 of the FCC rules and RSS-132, RSS-133 and RSS-139 of the Industry Canada rules.

FCC ID: A3LSGHT959V		FCC Pt. 22/24/27 GSM/EDGE/WCDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1012232044.A3L	Test Dates: December 27-31, 2010	EUT Type: 850/1900 GSM/GPRS/EDGE and AWS/PCS WCDMA/HSPA Phone with BT and WLAN		Page 59 of 59