**SAMSUNG ELECTRONICS Co., Ltd.,**
**Regulatory Compliance Group**
**IT R&D Center**
416 Maetan3-Dong,
Yeongtong-gu, Suwon city,
Gyeonggi-Do, Korea 443-742

# FCC CFR47 PART 24 SUBPART CERTIFICATION REPORT

| | | |
|---|---|---|
| **Model Tested** | : | **SGH-X210** |
| **Additional Model** | : | **SGH-X218** |
| **FCC ID(Requested)** | : | **A3LSGHX210** |
| **Report No** | : | **FD-067-R1** |
| **Job No** | : | **FD-067** |
| **Date issued** | : | **May 17, 2006** |

- Abstract -

All measurement reported herein accordance with FCC Rules, 47CFR Part2, Part24.

| | | | |
|---|---|---|---|
| **Prepared By** | YE PARK – Test Engineer | **Date** | 2006.05.17 |
| **Checked By** | WT JANG – Assistant Manager | **Date** | 2006.05.18 |
| **Authorized By** | WW JANG – Manager | **Date** | 2006.05.19 |

© Copyright SAMSUNG Electronics 2006

# TABLE OF CONTENT

## MEASUREMENT REPORT Page


**1. FCC CERTIFICATION INFORMATION ..... 3**

1.1. §2.1033 General Information ..... 3

**2. INTRODUCTION ..... 4**

2.1. General ..... 4

**3. MEASURING INSTRUMENT CALIBRATION ..... 5**

**4. TEST EQUIPMENT LIST ..... 6**

**5. DESCRIPTION OF TESTS ..... 7**

5.1. Effective Radiated Power / Equivalent Isotropic Radiated Power ..... 7

5.2. Radiated Spurious & Harmonic Emission ..... 8

5.3. Occupied Bandwidth ..... 10

5.4. Spurious and Harmonic Emission at Antenna Terminal ..... 10

5.4.1. Occupied Bandwidth Emission Limits ..... 10

5.4.2. Conducted Spurious Emission ..... 12

5.5. Frequency Stability / Temperature Variation ..... 13

**6. TEST DATA ..... 14**

6.1. Equivalent Isotropic Radiated Power (E.I.R.P.) ..... 14

6.2. GSM1900 Radiated Spurious & Harmonic measurement ..... 15

6.3. GSM1900 Radiated Spurious & Harmonic Conversion Table ..... 16

6.4. Frequency Stability ..... 17

6.4.1. GSM1900 Frequency Stability Table ..... 17

6.4.2. GSM1900 Frequency Stability Graph ..... 18

**7. CONCLUSION ..... 20**

**8. TEST PLOTS ..... 21**

# MEASUREMENT REPORT

## 1. FCC Certification Information

The following information is in accordance with FCC Rules, 47CFR Part2, Subpart J, Sections 2.1033 – 2.1055.

### 1.1. §2.1033 General Information

- Applicant Name : SAMSUNG ELECRONICS CO., LTD.
- Address : 416 Maetan3-Dong, Yeongtong-gu, Suwon City Gyeonggi-Do, Korea 443-742
- Attention : SungJoo KIM, Engineering Manager (QA Lab)
- FCC ID : A3LSGHX210
- Additional Model : SGH-X218
- Quantity : Quantity production is planned
- Emission Designators : 248KGXW(GSM1900)
- Tx Freq. Range : 1850.2MHz -1909.8MHz (GSM1900)
- Rx Freq. Range : 1930.2MHz - 1989.8MHz (GSM1900)
- Max. Power Rating : 1.726 W EIRP GSM1900 (32.37dBm)
- FCC Classification(s) : Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type : Single-Band PCS GSM Phone
- Frequency Tolerance : ±0.00025% (2.5ppm)
- FCC Rule Part(s) : §24(E), §2.
- Dates of Test : May 15-16, 2006
- Place of Test : SAMSUNG Lab,
- Test Report S/N : FD-067-R1

# 2. INTRODUCTION

## 2.1. General

These measurement test were conducted at **SAMSUNG ELECTRONICS CO., LTD(SUWON)**.
The site address is 416 Maetan3-Dong, Yeongtong-gu, Suwon City, Gyeonggi-Do, Korea 443-742
The site have 1 Fully-anechoic chamber and measurement facility.




**Figure1. Map of the Suwon City area.**

### Measurement Procedure

The radiated and spurious measurements were made Fully-anechoic chamber at a 3-meter test range (see Figure2). The equipment under testing was placed on a Non-conducted turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The substitution antenna will replace the EUT antenna it the same position and in vertical polarization. The frequency of the signal generator shall be set to the frequencies that were measured on the EUT. The test antenna shall be raised and lowered, if necessary, to ensure that the maximum signal is still being received. The signal generator, output level, shall be adjusted until an equal or a known related level to what was measured from the EUT is obtained in the spectrum analyzer. This level was recorded.
For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



**Figure2. Photograph of 3m Fully-Anechoic Chamber**

## 3. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

## 4. TEST EQUIPMENT LIST

| Name Of Equipment | Model | Serial No. | Due Date |
|---|---|---|---|
| Spectrum Analyzer | ESI26 | 836119/010 | 2006-09-26 |
| | E4440A(3Hz~26.5GHz) | MY41000236 | 2007-04-14 |
| | E4440A(3Hz~26.5GHz) | MY41000233 | 2007-04-05 |
| Signal Generator | SMIQ03B | 83824/021 | 2006-12-07 |
| | SMR20 | 835197/030 | 2007-01-10 |
| Power Meter | E4419B | GB41293846 | 2006-09-07 |
| Power Sensor | 8481B | 3318A10325 | 2006-09-08 |
| | 8485A | 3318A19924 | 2006-09-08 |
| Amplifier | 5S1G4 | 304866 | 2006-10-18 |
| Pre-Amplifier | 8449B | 3008A00691 | 2007-01-02 |
| Communication test set | 8960 | GB42230535 | 2007-01-02 |
| | 8960 | GB42360886 | 2007-02-28 |
| Antenna Master | MA240 | 240/618 | Not Required |
| Controller | HD100 | 100/756 | Not Required |
| Environmental Chamber | SH-241 | 92000548 | 2006-11-22 |
| | SH-241 | 92000549 | 2006-11-22 |
| Horn Antenna | HF906 | 360306/011 | 2007-03-31 |
| | HF906 | 100134 | 2007-05-04 |
| Dipole Antenna | 3121C-DB4 | 9007-587 | 2006-12-02 |
| | 3121C-DB4 | 9007-588 | 2006-06-04 |
| Receive Antenna | HL040 | 353255/019 | 2006-08-24 |
| | HL040 | 353255/020 | 2007-04-25 |
| Divider | 11636B | 51941 | Not Required |
| | 11636B | 51942 | Not Required |
| | 11636B | 51946 | Not Required |
| High Pass Filter | WHK1.0/15G-10SS | 1 | Not Required |
| | WHK/3.5/18G-10SS | 4 | Not Required |
| Shielded Fully Anechoic Chamber | CHAMBER | ANT0001 | Not Required |

# 5. DESCRIPTION OF TESTS

## 5.1. Effective Radiated Power / Equivalent Isotropic Radiated Power

### Test Set-up for the ERP/EIRP TEST

Effective Radiated Power Output and Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:




**Figure 3. Diagram of ERP/EIRP test Set-up**

The EUT was placed on a Non-conducted turntable 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For GSM signals, an average detector is used, with RBW=VBW=3MHz, SPAN=10MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of dipole is measured. The ERP and EIRP are recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

## 5.2. Radiated Spurious & Harmonic Emission

### Test Set-up for the Radiated Emission TEST

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001




**Figure 4. Diagram of Radiated Spurious & Harmonic test Set-up**

The EUT was placed on a Non-conducted turntable 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. The Spectrum was investigated from 30MHz to the 10th Harmonic of the fundamental. A peak detector is used, with RBW=VBW=1MHz. The value that we could measure was only reported. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

## SAMPLE CALCULATION

**Example: Channel 661 , Second Harmonic(3760.00MHz)**

The receive analyzer reading at 3meters with the EUT on the turntable was –81.0dBm. The gain of the substituted antenna is 8.1dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0dBm of the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0dB at 3760.00MHz. So 6.1dB is added to the signal generator reading of –30.9dBm yielding –24.8dBm. The fundamental EIRP was 25.5dBm so this harmonic was 25.5dBm –(-24.8)= 50.3dBc .

## 5.3. Occupied Bandwidth

**Test Procedure**

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.
Plots of the EUT's occupied bandwidth are shown herein.

## 5.4. Spurious and Harmonic Emission at Antenna Terminal

### 5.4.1. Occupied Bandwidth Emission Limits

(a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB.

(b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

(c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

| BLOCK | Freq. Range (MHz) Transmitter (Tx) | Freq. Range (MHz) Receiver (Rx) |
|---|---|---|
| A | 1850 – 1865 | 1930 – 1945 |
| B | 1870 – 1885 | 1950 – 1965 |
| C | 1895 – 1910 | 1975 – 1990 |
| D | 1865 – 1870 | 1945 – 1950 |
| E | 1885 – 1890 | 1965 – 1970 |
| F | 1890 – 1895 | 1970 – 1975 |

**Table 1. Broadband PCS Service Frequency Blocks**

| BLOCK | Freq. Range (MHz) Transmitter (Tx) | Freq. Range (MHz) Receiver (Rx) |
|---|---|---|
| A* Low + A | 824 ~ 835 | 869 ~ 880 |
| B | 835 ~ 845 | 880 ~ 890 |
| A* High | 845 ~ 846.5 | 890 ~ 891.5 |
| B* | 846.5 ~ 849 | 891.5 ~ 894 |

**Table 2. Cellular Service Frequency Blocks**

## 5.4.2. Conducted Spurious Emission

**Minimum standard:**

On any frequency outside a license frequency block, the power of any emission shall be attenuated below the transmitter power(P) by at least 43+10log (P)dB. Limit equivalent to -13dBm, calculation shown below.

43 + 10log ( 1.726 W) = 45.37 dB
32.37 dBm – 45.37 dB = -13 dBm

Compliance with the out-of-band emissions requirement is based on test being performed with an analyzer resolution bandwidth of 1MHz. However in the 1MHz band immediately outside and adjacent to the frequency block a resolution bandwidth of at least 1% of the fundamental emissions bandwidth may be employed.

In case of GSM : 0.01 * 273KHz = 2.73KHz
A Resolution BW of 3KHz was used for measurement at the band edges.

**Test Procedure:**

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1% of the emission bandwidth to show compliance with the -13dBm limit, in the 1MHz bands immediately outside and adjacent to the edge of the frequency block. The measurements are repeated for the EUT's highest channel. For the Out-of-Band measurements a 1MHz RBW was used to scan from 10MHz to 10GHz. (GSM1900 Mode : 10MHz to 20GHz). A display line was placed at -13dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.

Plots are shown herein.

## 5.5. Frequency Stability / Temperature Variation

The frequency stability of the transmitter is measured by:

a.) Temperature: The temperature is carried from -30°C to +60°C using an environmental chamber.

b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification- The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025 (±2.5ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature(25°C to 27°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (Usually 14~16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +60°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE : The EUT is tested down to the battery endpoint.

# 6. TEST DATA

## 6.1. Equivalent Isotropic Radiated Power (E.I.R.P.)

Supply Voltage : 3.7VDC

Modulation : PCS 1900

■ **Reference level**

| Frequency (MHz) | Output (dBm) | Polarization (H/V) | S/A (dBm) | Ant gain (dBi) | Ref level (dBm) |
|---|---|---|---|---|---|
| 1850.20 | 27.00 | H | -14.53 | 8.42 | -22.95 |
| | | V | -14.48 | 8.42 | -22.90 |
| 1880.00 | 27.00 | H | -14.87 | 8.25 | -23.12 |
| | | V | -14.97 | 8.25 | -23.22 |
| 1909.80 | 27.00 | H | -14.54 | 8.40 | -22.94 |
| | | V | -14.60 | 8.40 | -23.00 |

■ **Result**

| Frequency (MHz) | Tested level (dBm) | Polarization (H/V) | Azimuth (angle) | EIRP (dBm) | EIRP (W) | Battery |
|---|---|---|---|---|---|---|
| 1850.20 | -19.17 | H1 | 14 | 30.78 | 1.197 | Standard |
| 1880.00 | -17.85 | V | 289 | 32.37 | 1.726 | Standard |
| 1909.80 | -18.98 | H1 | 5 | 30.96 | 1.247 | Standard |

NOTE : Standard batteries are the only battery options for this phone

**Radiated measurements at 3 meters by Substitution Method**

## 6.2. GSM1900 Radiated Spurious & Harmonic measurement

Operating Frequency : 1850.2 MHz(Low), 1880.00 MHz(Middle), 1909.80 MHz(High)

Measured Output Power : 32.37 dBm = 1.726 W

Modulation Signal : GSM1900

**Limit : 43 + 10log$_{10}$(P) = 45.37 dBc**

**■ Result**

| Channel | Harmonic | Frequency (MHz) | From EUT Tested level (dBm) | POL (H/V) | Result (dBc) |
|---|---|---|---|---|---|
| 512 | 2 | 3700.40 | -65.38 | H2 | 70.41 |
| | 3 | 5550.60 | -59.98 | H2 | 60.18 |
| | 4 | 7400.80 | -61.49 | H2 | 57.57 |
| | 5 | 9251.00 | -69.07 | H1 | 62.24 |
| | 6 | 11101.20 | - | - | - |
| | 7 | 12951.40 | - | - | - |
| 661 | 2 | 3760.00 | -63.73 | H2 | 69.42 |
| | 3 | 5640.00 | -58.88 | H2 | 59.29 |
| | 4 | 7520.00 | -60.93 | H2 | 57.52 |
| | 5 | 9400.00 | -67.89 | H2 | 60.74 |
| | 6 | 11280.00 | - | - | - |
| | 7 | 13160.00 | - | - | - |
| 810 | 2 | 3819.60 | -63.33 | H2 | 68.41 |
| | 3 | 5729.40 | -58.59 | V | 58.99 |
| | 4 | 7639.20 | -62.07 | H2 | 56.97 |
| | 5 | 9549.00 | -69.27 | H2 | 61.75 |
| | 6 | 11458.80 | - | - | - |
| | 7 | 13368.60 | - | - | - |

**Radiated Spurious Emission measurements at 3 meters by Substitution Method**

## 6.3. GSM1900 Radiated Spurious & Harmonic Conversion Table

Date : 2006. 05. 15

Test Engineer : JW LEE

① Tx Cable loss
② Tx Horn Ant Gain
③ Rx Cable loss + HPF Insertion loss + Attenuator
④ Pre-Amp gain
⑤ Air loss
⑥ Tested Level from EUT
⑦ = ⑥ + ⑤ + ③ - ④
⑧ = EIRP - ⑦

| CH | Har | Frequency (MHz) | ① Tx CL (dB) | ② Horn Gain (dB) | Tx Level @ (S/G 10dBm) | ⑥ Tested Level EUT : H (dBm) | ⑥ Tested Level EUT : V (dBm) | ⑦ Amplitude of Emission EUT : H (dBm) | ⑦ Amplitude of Emission EUT : V (dBm) | ⑧ Result EUT : H (dBc) | ⑧ Result EUT : V (dBc) |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 512 | 2 | 3700.40 | 12.22 | 9.62 | 7.40 | -65.38 | -65.70 | -38.04 | -38.30 | 70.41 | 70.67 |
| | 3 | 5550.60 | 16.91 | 11.05 | 4.14 | -59.98 | -60.64 | -27.81 | -29.58 | 60.18 | 61.95 |
| | 4 | 7400.80 | 20.66 | 11.70 | 1.04 | -61.49 | -63.13 | -25.20 | -28.77 | 57.57 | 61.14 |
| | 5 | 9251.00 | 24.06 | 12.38 | -1.68 | -69.07 | -69.12 | -29.87 | -30.33 | 62.24 | 62.70 |
| | 6 | 11101.20 | 27.70 | 13.52 | -4.18 | - | - | - | - | - | - |
| | 7 | 12951.40 | 31.86 | 13.03 | -8.83 | - | - | - | - | - | - |
| 661 | 2 | 3760.00 | 12.40 | 9.62 | 7.22 | -63.73 | -64.47 | -37.05 | -37.42 | 69.42 | 69.79 |
| | 3 | 5640.00 | 16.83 | 11.05 | 4.22 | -58.88 | -59.59 | -26.92 | -27.99 | 59.29 | 60.36 |
| | 4 | 7520.00 | 21.17 | 11.70 | 0.53 | -60.93 | -62.06 | -25.15 | -27.88 | 57.52 | 60.25 |
| | 5 | 9400.00 | 24.51 | 12.38 | -2.13 | -67.89 | -69.00 | -28.37 | -30.14 | 60.74 | 62.51 |
| | 6 | 11280.00 | 28.38 | 13.52 | -4.86 | - | - | - | - | - | - |
| | 7 | 13160.00 | 33.20 | 13.03 | -10.17 | - | - | - | - | - | - |
| 810 | 2 | 3819.60 | 13.76 | 9.62 | 5.86 | -63.33 | -64.71 | -36.04 | -36.82 | 68.41 | 69.19 |
| | 3 | 5729.40 | 17.34 | 11.05 | 3.71 | -59.28 | -58.59 | -26.97 | -26.62 | 59.34 | 58.99 |
| | 4 | 7639.20 | 21.14 | 11.70 | 0.56 | -62.07 | -63.44 | -24.60 | -27.16 | 56.97 | 59.53 |
| | 5 | 9549.00 | 26.03 | 12.38 | -3.65 | -69.27 | -69.65 | -29.38 | -31.02 | 61.75 | 63.39 |
| | 6 | 11458.80 | 28.52 | 13.52 | -5.00 | - | - | - | - | - | - |
| | 7 | 13368.60 | 32.87 | 13.03 | -9.84 | - | - | - | - | - | - |

## 6.4. Frequency Stability

### 6.4.1. GSM1900 Frequency Stability Table

Operating Frequency : 1,880,000,000 Hz

Channel : 661

Reference Voltage : 3.7VDC

**Deviation Limit : ±0.00025 % or 2.5ppm**

| Voltage (%) | Power (VDC) | Temp. (°C) | Frequency Error (Hz) | Frequency (Hz) | Deviation (%) | ppm |
|---|---|---|---|---|---|---|
| 100% | 3.70 | +20(Ref) | -53.98 | 1,879,999,946 | -0.000003 | -0.029 |
| 100% | | -30 | -33.96 | 1,879,999,966 | -0.000002 | -0.018 |
| 100% | | -20 | -43.78 | 1,879,999,956 | -0.000002 | -0.023 |
| 100% | | -10 | -39.26 | 1,879,999,961 | -0.000002 | -0.021 |
| 100% | | 0 | 38.01 | 1,880,000,038 | 0.000002 | 0.020 |
| 100% | | +10 | -47.64 | 1,879,999,952 | -0.000003 | -0.025 |
| 100% | | +20 | -53.98 | 1,879,999,946 | -0.000003 | -0.029 |
| 100% | | +30 | -35.84 | 1,879,999,964 | -0.000002 | -0.019 |
| 100% | | +40 | -38.27 | 1,879,999,962 | -0.000002 | -0.020 |
| 100% | | +50 | -28.73 | 1,879,999,971 | -0.000002 | -0.015 |
| 100% | | +60 | -29.64 | 1,879,999,970 | -0.000002 | -0.016 |
| 85% | 3.35 | +20 | -62.35 | 1,879,999,938 | -0.000003 | -0.033 |
| 115% | 4.26 | +20 | -42.71 | 1,879,999,957 | -0.000002 | -0.023 |
| Batt.Endpoint | 3.35 | +20 | -62.35 | 1,879,999,938 | -0.000003 | -0.033 |

**Note : The temperature is varied from -30 °C to +60 °C using an environmental chamber.**

**The EUT is tested down to the battery end point.**

## 6.4.2. GSM1900 Frequency Stability Graph



Zoom IN


Frequency Stability
0.5
-0.5
Deviation (ppm)
+20(Ref)
-20
0
+20
+40
+60
+20
Temperature (℃)

# 7. CONCLUSION

The data collected shows that the SAMSUNG Single-Band PCS GSM Phone.
FCC ID : A3LSGHX210 complies with all the requirements of Parts 2,24 of the FCC Rules.

# 8. TEST PLOTS

GSM1900


Agilent
R T
Freq/Channel
Ch Freq 1.8502 GHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSGHX210 OBW Ch.512
Ref 30 dBm
Atten 40 dB
#Peak
Log
10
dB/
Offst
8.63
dB
Center 1.850 200 GHz
Span 1 MHz
#Res BW 3 kHz
#VBW 3 kHz
#Sweep 1 s (601 pts)
Occupied Bandwidth
247.2143 kHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 2.060 kHz
x dB Bandwidth 306.764 kHz
Center Freq
1.85020000 GHz
Start Freq
1.84970000 GHz
Stop Freq
1.85070000 GHz
CF Step
100.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R T
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Occupied Bandwidth
FCC ID:A3LSGHX210 OBW Ch.661
Ref 30 dBm
Atten 40 dB
#Peak
Log
10
dB/
Offst
8.63
dB
Center 1.880 000 GHz
Span 1 MHz
#Res BW 3 kHz
#VBW 3 kHz
#Sweep 1 s (601 pts)
Occupied Bandwidth
246.1785 kHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error -232.550 Hz
x dB Bandwidth 303.464 kHz
Center Freq
1.88000000 GHz
Start Freq
1.87950000 GHz
Stop Freq
1.88050000 GHz
CF Step
100.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
File Operation Status, C:\TEMP.GIF file saved




FCC ID : A3LSGHX210 Transmit Power 512CH



FCC ID : A3LSGHX210 Transmit Power 661CH




FCC ID : A3LSGHX210 Transmit Power 810CH



FCC ID : A3LSGHX210 GMSK Power vs Time 512CH




FCC ID : A3LSGHX210 GMSK Power vs Time 661CH



FCC ID : A3LSGHX210 GMSK Power vs Time 810CH




FCC ID : A3LSGHX210 Modulation & Switching 512CH



FCC ID : A3LSGHX210 Modulation & Switching 661CH




FCC ID : A3LSGHX210 Modulation & Switching 810CH




Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.512
Ref 30 dBm
Atten 40 dB
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
Center 1.255 GHz
Span 2.49 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2005 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.512
Mkr1 1.623 GHz
Ref 30 dBm
Atten 40 dB
-32.18 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
1
Center 926 MHz
Span 1.833 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 3.08 ms (601 pts)
Center Freq
926.350000 MHz
Start Freq
10.0000000 MHz
Stop Freq
1.84270000 GHz
CF Step
183.270000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.512
Mkr1 2.445 4 GHz
Ref 30 dBm
Atten 40 dB
-33.38 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Center Freq
2.17885000 GHz
Start Freq
1.85770000 GHz
Stop Freq
2.50000000 GHz
CF Step
64.2300000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 2.178 8 GHz
Span 642.3 MHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 1.08 ms (601 pts)
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.512
Mkr1 15.83 GHz
Ref 30 dBm
Atten 40 dB
-27.61 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 11.25 GHz
Span 17.5 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.76 ms (601 pts)
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.661
Ref 30 dBm
Atten 40 dB
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 1.255 GHz
Span 2.49 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.661
Mkr1 1.820 GHz
Ref 30 dBm
Atten 40 dB
-33.78 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
Center Freq
941.250000 MHz
Start Freq
10.0000000 MHz
Stop Freq
1.87250000 GHz
CF Step
186.250000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 941 MHz
Span 1.863 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 3.12 ms (601 pts)
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.661
Mkr1 2.473 5 GHz
Ref 30 dBm
Atten 40 dB
-32.99 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Center Freq
2.19375000 GHz
Start Freq
1.88750000 GHz
Stop Freq
2.50000000 GHz
CF Step
61.2500000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 2.193 8 GHz
Span 612.5 MHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 1.04 ms (601 pts)
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.661
Mkr1 19.91 GHz
Ref 30 dBm
Atten 40 dB
-27.05 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Center 11.25 GHz
Span 17.5 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.76 ms (601 pts)
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.810
Ref 30 dBm
Atten 40 dB
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
Center 1.255 GHz
Span 2.49 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.810
Mkr1 1.287 GHz
Ref 30 dBm
Atten 40 dB
-33.53 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
AC Coupled: unspecified below 20 MHz
1
Center 956 MHz
Span 1.892 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 3.16 ms (601 pts)
Center Freq
956.150000 MHz
Start Freq
10.0000000 MHz
Stop Freq
1.90230000 GHz
CF Step
189.230000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.810
Mkr1 2.449 5 GHz
Ref 30 dBm
Atten 40 dB
-33.42 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Center 2.208 6 GHz
Span 582.7 MHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 1 ms (601 pts)
Center Freq
2.20865000 GHz
Start Freq
1.91730000 GHz
Stop Freq
2.50000000 GHz
CF Step
58.2700000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Cond Spur Ch.810
Mkr1 18.92 GHz
Ref 30 dBm
Atten 40 dB
-27.84 dBm
#Peak
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
LgAv
M1 S2
S3 FC
£(f):
FTun
Swp
Center 11.25 GHz
Span 17.5 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Band Edge Ch.512
Ref 30 dBm
Atten 40 dB
#Avg
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
PAvg
M1 S2
S3 FC
£(f):
f>50k
Swp
Center 1.850 000 0 GHz
Span 810 kHz
#Res BW 3 kHz
#VBW 3 kHz
Sweep 343.2 ms (601 pts)
Center Freq
1.85000000 GHz
Start Freq
1.84959500 GHz
Stop Freq
1.85040500 GHz
CF Step
81.0000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Band Edge Ch.512
Mkr1 1.849 981 3 GHz
Ref 30 dBm
Atten 40 dB
-18.25 dBm
#Avg
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
PAvg
M1 S2
S3 FC
£(f):
f>50k
Swp
Center 1.849 595 0 GHz
Span 810 kHz
#Res BW 3 kHz
#VBW 3 kHz
Sweep 343.2 ms (601 pts)
Center Freq
1.84959500 GHz
Start Freq
1.84919000 GHz
Stop Freq
1.85000000 GHz
CF Step
81.0000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Band Edge Ch.810
Ref 30 dBm
Atten 40 dB
#Avg
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
PAvg
M1 S2
S3 FC
£(f):
f>50k
Swp
Center 1.910 000 0 GHz
Span 810 kHz
#Res BW 3 kHz
#VBW 3 kHz
Sweep 343.2 ms (601 pts)
Center Freq
1.91000000 GHz
Start Freq
1.90959500 GHz
Stop Freq
1.91040500 GHz
CF Step
81.0000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved


Agilent
R L
Freq/Channel
FCC ID:A3LSGHX210 Band Edge Ch.810
Mkr1 1.910 014 8 GHz
Ref 30 dBm
Atten 40 dB
-17.25 dBm
#Avg
Log
10
dB/
Offst
8.63
dB
Dl
-13.0
dBm
PAvg
M1 S2
S3 FC
£(f):
f>50k
Swp
Center 1.910 405 0 GHz
Span 810 kHz
#Res BW 3 kHz
#VBW 3 kHz
Sweep 343.2 ms (601 pts)
Center Freq
1.91040500 GHz
Start Freq
1.91000000 GHz
Stop Freq
1.91081000 GHz
CF Step
81.0000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
File Operation Status, C:\TEMP.GIF file saved