PCTEST Engineering Laboratory, Inc.

6660-B Dobbin Road · Columbia, MD 21045 · U.S.A.
TEL (410) 290-6652 · FAX (410) 290-6654
http://www.pctestlab.com



CERTIFICATE OF COMPLIANCE
FCC Part 24 & 22 Certification

SAMSUNG ELECTRONICS CO., LTD.
3351 Michelson Drive, Suite 290
Irvine, CA 92612

Dates of Tests: September 27-30, 2005
Test Report S/N: 0509280668-1
Test Site: PCTEST Lab, Columbia MD

FCC ID	**A3LSGHZX10**
APPLICANT	**SAMSUNG ELECTRONICS CO., LTD.**

Classification:	**Licensed Portable Transmitter Held to Ear (PCE)**
FCC Rule Part(s):	**§24(E), §22(H); §2**
EUT Type:	**Dual-Band WCDMA Phone**
Model:	***SGH-ZX10***
Tx Frequency Range:	**826.4MHz - 846.6MHz (Cellular WCDMA)/ 1852.4MHz - 1907.6MHz (PCS WCDMA)**
Max. RF Output Power:	**0.241 W ERP WCDMA (23.82 dBm) / 0.425 W EIRP WCDMA (26.28 dBm)**
Max. SAR Measurement:	**Cellular WCDMA: 1.08 W/kg Head SAR, 0.944 W/kg Body SAR;** **PCS WCDMA: 1.38 W/kg Head SAR, 0.531 W/kg Body SAR**
Emission Designator(s):	**4M18F9W/ 4M16F9W**
Test Device Serial No.	**Identical Prototype [S/N: #2]**

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant conditions: Power output listed is ERP for Part 22 and EIRP for Part 24. SAR compliance for body-worn operating configuration is based on a separation distance of 1.8 cm between the back of the unit and the body of the user. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. Belt clips or holsters may not contain metallic components.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian
Vice President Engineering

© 2005 PCTEST ENGINEERING LABORATORY, INC.

TABLE OF CONTENTS

ATTACHMENT A: COVER LETTER(S)

ATTACHMENT B: ATTESTATION STATEMENT(S)

ATTACHMENT C: TEST REPORT

1.1 SCOPE	3
2.1 INTRODUCTION	4
3.1 INSERTS	5
4.1 DESCRIPTION OF TESTS	6-8
5.1 EFFECTIVE RADIATED POWER OUTPUT	9-10
6.1 EQUIVALENT ISOTROPIC RADIATED POWER	11
7.1 RADIATED MEASUREMENTS	12-17
8.1 FREQUENCY STABILITY	18-21
9.1 PLOTS OF EMISSIONS	22
10.1 LIST OF TEST EQUIPMENT	23
11.1 SAMPLE CALCULATIONS	24
12.1 CONCLUSION	25

ATTACHMENT D: TEST PLOTS

ATTACHMENT E: FCC ID LABEL / LOCATION

ATTACHMENT F: TEST SETUP PHOTOGRAPHS

ATTACHMENT G: EXTERNAL PHOTOGRAPHS

ATTACHMENT H: INTERNAL PHOTOGRAPHS

ATTACHMENT I: BLOCK DIAGRAM(S)

ATTACHMENT J: SCHEMATIC DIAGRAM(S)

ATTACHMENT K: OPERATIONAL / CIRCUIT DESCRIPTION

ATTACHMENT L: PARTS LIST/TUNE UP PROCEDURE

ATTACHMENT M: USER'S MANUAL

ATTACHMENT N: SAR MEASUREMENT REPORT

ATTACHMENT O: SAR TEST DATA

ATTACHMENT P: SAR TEST SETUP PHOTOGRAPHS

ATTACHMENT Q: DIPOLE VALIDATION

ATTACHMENT R: PROBE CALIBRATION

© 2005 PCTEST ENGINEERING LABORATORY, INC.



MEASUREMENT REPORT



1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

§2.1033 General Information

Applicant Name:	**SAMSUNG ELECTRONICS CO., LTD.**
Address:	**3351 Michelson Drive, Suite 290** **Irvine, CA 92612**

- FCC ID: A3LSGHZX10
- Quantity: Quantity production is planned
- Emission Designators: 4M18F9W/ 4M16F9W
- Tx Freq. Range: 826.4MHz - 846.6MHz (Cellular WCDMA)/ 1852.4MHz - 1907.6MHz (PCS WCDMA)
- Rx Freq. Range: 826.4MHz - 846.6MHz (Cellular WCDMA)/ 1852.4MHz - 1907.6MHz (PCS WCDMA)
- Max. Power Rating: 0.241 W ERP GSM850 (23.82 dBm)
0.425 W EIRP GSM1900 (26.28 dBm)
- FCC Classification(s): Licensed Portable Tx Held to Ear (PCE)
- Equipment (EUT) Type: Dual-Band WCDMA Phone
- Modulation(s): WCDMA
- Frequency Tolerance: ± 0.00025% (2.5 ppm)
- FCC Rule Part(s): § 24(E), §22(H)
- Dates of Tests: September 27-30, 2005
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 0509280668-1
- Deviation from measurement procedure - None

© 2005 PCTEST ENGINEERING LABORATORY, INC.

2.1 INTRODUCTION



Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

These measurement tests were conducted at ***PCTEST Engineering Laboratory, Inc.*** facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

Measurement Procedure

The radiated and spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



Figure 2. Diagram of 3-meter outdoor test range

© 2005 PCTEST ENGINEERING LABORATORY, INC.

3.1 INSERTS

Function of Active Devices (Confidential)

The Function of active devices are shown in Attachment K.

Block & Schematic Diagrams (Confidential)

The block diagrams are shown in Attachment I, and the schematic diagrams are shown in Attachment J.

Operating Instructions

The instruction manual is shown in Attachment M.

Parts List & Tune-Up Procedure (Confidential)

The parts list & tune-up procedure is shown in Attachment L.

Description of Freq. Stabilization Circuit (Confidential)

The description of frequency stabilization circuit is shown in Attachment K.

Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppresion Circuits (Confidential)

The description of suppression stabilization circuits is shown in Attachment K.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

4.1 DESCRIPTION OF TESTS

4.2 Occupied Bandwidth Emission Limits

(a) On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB.

(b) Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

(c) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.

(d) The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

4.3 Cellular - Base Frequency Blocks



BLOCK 1: 869 – 880 MHz (A* Low + A)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 4: 891.5 – 894 MHz (B*)

4.4 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 4: 846.5 – 849 MHz (B*)

© 2005 PCTEST ENGINEERING LABORATORY, INC.

4.1 DESCRIPTION OF TESTS (CONTINUED)

4.5 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 6: 1975 – 1990 MHz (C)

4.6 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 6: 1895 – 1910 MHz (C)

© 2005 PCTEST ENGINEERING LABORATORY, INC.

4.7 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to at least the 10th harmonic. The transmitter is modulated with a 2500Hz tone at a level of 16dB greater than that required to provided 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with on port terminated with 50 ohms) and an 870 MHz to 890 MHz bandpass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the bandpass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the bandpass filter insertion loss to be calibrated.

4.8 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and an high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.9 Radiation Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

5.0 Frequency Stability/Temperature Variation.

The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025 (±2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

5.1 Test Data

5.2 Effective Radiated Power Output

A. POWER: **High (WCDMA Mode)**

Freq. Tuned (MHz)	REF. LEVEL (dBm)	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
826.40	-19.700	H	0.154	21.875	Standard
836.60	-18.250	H	0.224	23.503	Standard
846.60	-18.150	H	0.241	23.823	Standard

Note: Standard batteries are the only options for this phone

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

6.1 Test Data

6.2 Equivalent Isotropic Radiated Power (E.I.R.P.)

Radiated measurements at 3 meters

Supply Voltage: 3.7 VDC

Modulation: PCS WCDMA

FREQ. (MHz)	REF. LEVEL (dBm)	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)	Battery
1852.40	-16.950	H	90	26.143	0.411	Standard
1880.00	-16.900	H	90	26.281	0.425	Standard
1907.60	-18.300	H	90	25.111	0.324	Standard

Note: Standard batteries are the only options for this phone

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data

7.2 Cellular WCDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 826.40
CHANNEL: 4132
MEASURED OUTPUT POWER: 23.503 dBm = 0.224 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 36.50 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1652.80	-36.18	6.10	-30.08	H	53.6
2479.20	-54.28	6.70	-47.58	V	71.1
3305.60	-56.38	6.80	-49.58	V	73.1
4132.00	-58.68	6.50	-52.18	V	75.7
4958.40	-56.48	7.00	-49.48	H	73.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.3 Cellular WCDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz
CHANNEL: 4182
MEASURED OUTPUT POWER: 23.503 dBm = 0.224 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 36.50 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.20	-35.88	6.10	-29.78	V	53.3
2509.80	-63.18	6.70	-56.48	H	80.0
3346.40	-60.88	6.80	-54.08	V	77.6
4183.00	-58.28	6.50	-51.78	V	75.3
5019.60	-56.28	7.00	-49.28	H	72.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.4 Cellular WCDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 846.60 MHz
CHANNEL: 4233
MEASURED OUTPUT POWER: 23.503 dBm = 0.224 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 36.50 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1693.20	-34.88	6.10	-28.78	H	52.3
2539.80	-53.68	6.70	-46.98	H	70.5
3386.40	-58.68	6.80	-51.88	V	75.4
4233.00	-58.78	6.50	-52.28	V	75.8
5079.60	-56.48	7.00	-49.48	H	73.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.5 PCS WCDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1852.40 MHz
CHANNEL: 9262
MEASURED OUTPUT POWER: 26.281 dBm = 0.425 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 39.28 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3704.80	-53.78	6.10	-47.68	V	74.0
5557.20	-66.58	6.70	-59.88	H	86.2
7409.60	-60.78	6.80	-53.98	H	80.3
9262.00	-56.28	6.50	-49.78	V	76.1
11114.40	-55.28	7.00	-48.28	V	74.6

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.6 PCS WCDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
CHANNEL: 9400
MEASURED OUTPUT POWER: 26.281 dBm = 0.425 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 39.28 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-63.88	6.10	-57.78	H	84.1
5640.00	-65.98	6.70	-59.28	V	85.6
7520.00	-60.68	6.80	-53.88	V	80.2
9400.00	-56.78	6.50	-50.28	H	76.6
11280.00	-55.18	7.00	-48.18	H	74.5

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

7.1 Test Data (Continued)

7.7 PCS WCDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1907.60 MHz
CHANNEL: 9538
MEASURED OUTPUT POWER: 26.281 dBm = 0.425 W
MODULATION SIGNAL: WCDMA
DISTANCE: 3 meters
LIMIT: 43 + 10 $\log_{10}$ (W) = 39.28 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3815.20	-59.08	6.10	-52.98	H	79.3
5722.80	-65.78	6.70	-59.08	V	85.4
7630.40	-60.88	6.80	-54.08	H	80.4
9538.00	-56.58	6.50	-50.08	H	76.4
11445.60	-55.48	7.00	-48.48	V	74.8

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

© 2005 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data

8.2 FREQUENCY STABILITY (WCDMA)

OPERATING FREQUENCY: 836,400,007 Hz

CHANNEL: 4182

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (ºC)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,400,007	0.00	0.000000
100 %		- 30	836,400,074	-66.91	-0.000008
100 %		- 20	836,400,066	-58.55	-0.000007
100 %		- 10	836,399,923	83.64	0.000010
100 %		0	836,399,915	92.00	0.000011
100 %		+ 10	836,399,974	33.46	0.000004
100 %		+ 20	836,400,007	0.00	0.000000
100 %		+ 25	836,399,957	50.18	0.000006
100 %		+ 30	836,399,948	58.55	0.000007
100 %		+ 40	836,399,965	41.82	0.000005
100 %		+ 50	836,399,957	50.18	0.000006
100 %		+ 60	836,399,965	41.82	0.000005
85 %	3.17	+ 20	836,400,007	0.00	0.000000
115 %	4.26	+ 20	836,400,007	0.00	0.000000
BATT. ENDPOINT	3.07	+ 20	836,400,007	0.00	0.000000

© 2005 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.3 FREQUENCY STABILITY (WCDMA)



© 2005 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data

8.4 FREQUENCY STABILITY (PCS WCDMA)

OPERATING FREQUENCY: 1,880,000,008 Hz

CHANNEL: 9400

REFERENCE VOLTAGE: 3.7 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (ºC)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,880,000,008	0.00	0.000000
100 %		- 30	1,880,000,121	-112.80	-0.000006
100 %		- 20	1,880,000,102	-94.00	-0.000005
100 %		- 10	1,879,999,764	244.40	0.000013
100 %		0	1,879,999,858	150.40	0.000008
100 %		+ 10	1,879,999,858	150.40	0.000008
100 %		+ 20	1,880,000,008	0.00	0.000000
100 %		+ 25	1,879,999,895	112.80	0.000006
100 %		+ 30	1,879,999,895	112.80	0.000006
100 %		+ 40	1,879,999,839	169.20	0.000009
100 %		+ 50	1,880,000,064	-56.40	-0.000003
100 %		+ 60	1,880,000,102	-94.00	-0.000005
85 %	3.15	+ 20	1,880,000,008	0.00	0.000000
115 %	4.26	+ 20	1,880,000,008	0.00	0.000000
BATT. ENDPOINT	3.06	+ 20	1,880,000,008	0.00	0.000000

© 2005 PCTEST ENGINEERING LABORATORY, INC.

8.1 Test Data (Continued)

8.5 FREQUENCY STABILITY (PCS WCDMA)



© 2005 PCTEST ENGINEERING LABORATORY, INC.

9.1 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT D)

© 2005 PCTEST ENGINEERING LABORATORY, INC.

10.1 TEST EQUIPMENT

Type	Model	Cal. Due Date	S/N
Microwave Spectrum Analyzer	8566B (100Hz-22GHz) HP	08/15/05	3638A08713
Microwave Spectrum Analyzer	HP 8566B (100Hz-22GHz)	04/17/06	2542A11898
Spectrum Analyzer/Tracking Gen.	HP 8591A (100Hz-1.8GHz)	08/10/05	3144A02458
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/06	2232A19558
Signal Generator*	HP 8640B (500Hz-1GHz)	06/03/06	1851A09816
Signal Generator*	Rohde & Schwarz (0.1-1000MHz)	09/11/05	894215/012
Ailtech/Eaton Receiver	NM 37/57A-SL (30-1000MHz)	04/12/06	0792-032
Ailtech/Eaton Receiver	NM 37/57A (30-1000MHz)	03/11/06	0805-03334
Ailtech/Eaton Receiver	NM 17/27A (0.1-32MHz)	09/17/05	0608-03241
Quasi-Peak Adapter	HP 85650A	08/15/05	2043A00301
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	03/11/06	0194-04082
Gigatronics Universal Power Meter	8657A		1835256
Gigatronics Power Sensor	80701A (0.05-18GHz)		1833460
Signal Generator	HP 8648D (9kHz-4GHz)		3613A00315
Amplifier Research	5S1G4 (5W, 800MHz-4.2GHz)		22322
Network Analyzer	HP 8753E (30kHz-3GHz)		JP38020182
Audio Analyzer	HP 8903B		3011A09025
Modulation Analyzer	HP 8901A		2432A03467
Power Meter	HP 437B		3125U24437
Power Sensor	HP 8482H (30µW-3W)		2237A02084
Harmonic/Flicker	Test System HP 6841A (IEC 555-2/3)		3531A00115
Broadband Amplifier (2)	HP 8447D		1145A00470, 1937A03348
Broadband Amplifier	HP 8447F		2443A03784
Horn Antenna	EMCO Model 3115 (1-18GHz)		9704-5182
Horn Antenna	EMCO Model 3115 (1-18GHz)		9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)		9203-2178
Biconical Antenna (4)	Eaton 94455/Eaton 94455-1/Singer 94455-1/Compliance Design		1295, 1332, 0355
Log-Spiral Antenna (3)	Ailtech/Eaton 93490-1		0608, 1103, 1104
Roberts Dipoles	Compliance Design (1 set)		
Ailtech Dipoles	DM-105A (1 set)		33448-111
EMCO LISN (6)	3816/2		1079
Microwave Preamplifier 40dB	Gain HP 83017A (0.5-26.5GHz)		3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)		
Ailtech/Eaton Receiver	NM37/57A-SL		0792-03271
Spectrum Analyzer	HP 8594A		3051A00187
Spectrum Analyzer (2)	HP 8591A		3034A01395, 3108A02053
Microwave Survey Meter	Holaday Model 1501 (2.450GHz)		80931
Digital Thermometer	Extech Instruments 421305		426966
Attenuator	HP 8495A (0-70dB) DC-4GHz		
Bi-Directional Coax Coupler	Narda 3020A (50-1000MHz)		
Shielded Screen Room	RF Lindgren Model 26-2/2-0		6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81		R2437 (PCT278)
Enviromental Chamber	Associated Systems Model 1025 (Temperature/Humidity)		PCT285

* Calibration traceable to the National Institute of Standards and Technology (NIST).

© 2005 PCTEST ENGINEERING LABORATORY, INC.

11.1 SAMPLE CALCULATIONS

A. Emission Designator

Emission Designator = 4M18F9W

CDMA BW = 4.18 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)
(Measured at the 99.75% power bandwidth)

B. Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The receive analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80) = 50.3 dBc

© 2005 PCTEST ENGINEERING LABORATORY, INC.

12.1 CONCLUSION

The data collected shows that the **Samsung Electronics Dual-Band WCDMA Phone FCC ID: A3LSGHZX10** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

© 2005 PCTEST ENGINEERING LABORATORY, INC.


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-4132
Mkr1 1.653 GHz
Ref 23.2 dBm
Atten 30 dB
-28.49 dBm
#Peak
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-4132
Mkr1 7.888 GHz
Ref 23.2 dBm
Atten 30 dB
-35.40 dBm
#Peak
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Power Out WCDMA C-4132
Ref 23.2 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
11.5
dB
PAvg
100
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center 826.40 MHz
Span 13 MHz
#Res BW 5 MHz
#VBW 1 MHz
Sweep 1 ms (601 pts)
Center Freq
826.400000 MHz
Start Freq
819.900000 MHz
Stop Freq
832.900000 MHz
CF Step
1.30000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Band Edge WCDMA C-4132
Mkr1 824.00 MHz
Ref 23.2 dBm
Atten 30 dB
-25.185 dBm
#Avg
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Center 824.00 MHz
Span 10 MHz
#Res BW 100 kHz
#VBW 100 kHz
Sweep 3.84 ms (601 pts)
Center Freq
824.000000 MHz
Start Freq
819.000000 MHz
Stop Freq
829.000000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 4MHz Span WCDMA C-4132
Mkr1 822.780 MHz
Ref 23.2 dBm
Atten 30 dB
-32.782 dBm
#Avg
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Center Freq
821.000000 MHz
Start Freq
819.000000 MHz
Stop Freq
823.000000 MHz
CF Step
400.000000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 819.000 MHz
Stop 823.000 MHz
#Res BW 100 kHz
#VBW 100 kHz
Sweep 1.56 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-4182
Mkr1 1.670 GHz
Ref 23.2 dBm
Atten 30 dB
-29.00 dBm
#Peak
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-4182
Mkr1 8.712 GHz
Ref 23.2 dBm
Atten 30 dB
-35.29 dBm
#Peak
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Power Out WCDMA C-4182
Ref 23.2 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
11.5
dB
PAvg
100
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center 836.40 MHz
Span 13 MHz
#Res BW 5 MHz
#VBW 1 MHz
Sweep 1 ms (601 pts)
Center Freq
836.400000 MHz
Start Freq
829.900000 MHz
Stop Freq
842.900000 MHz
CF Step
1.30000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
Ch Freq 836.4 MHz
Trig Free
Occupied Bandwidth
FCC ID: A3LSGHZX10 Occupied BW WCDMA C-4182
Ref 23.2 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
11.5
dB
Center 836.40 MHz
Span 10 MHz
#Res BW 100 kHz
#VBW 1 MHz
Sweep 2.92 ms (601 pts)
Occupied Bandwidth
4.1838 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error -16.168 kHz
x dB Bandwidth 4.656 MHz*
Center Freq
836.400000 MHz
Start Freq
831.400000 MHz
Stop Freq
841.400000 MHz
CF Step
1.00000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 836.4 MHz
Trig Free
Channel Power
FCC ID: A3LSGHZX10 Channel Pwr WCDMA C-4182
Ref 23.2 dBm
Atten 30 dB
#Peak
Log
10
dB/
Offst
11.5
dB
Center 836.400 MHz
Span 6.279 MHz
#Res BW 62 kHz
#VBW 620 kHz
Sweep 1.52 ms (601 pts)
Channel Power
23.24 dBm / 4.1859 MHz
Power Spectral Density
-42.98 dBm/Hz
Center Freq
836.400000 MHz
Start Freq
833.260600 MHz
Stop Freq
839.539400 MHz
CF Step
627.880000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-4233
Mkr1 1.695 GHz
Ref 23.2 dBm
Atten 30 dB
-24.97 dBm
#Peak
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-4233
Mkr1 8.638 GHz
Ref 23.2 dBm
Atten 30 dB
-35.47 dBm
#Peak
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 2.500 GHz
Stop 10.000 GHz
#Res BW 1 MHz
#VBW 1 MHz
Sweep 12.52 ms (601 pts)
Center Freq
6.25000000 GHz
Start Freq
2.50000000 GHz
Stop Freq
10.0000000 GHz
CF Step
750.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: A3LSGHZX10 Power Out WCDMA C-4233
Ref 23.2 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
11.5
dB
PAvg
100
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 840.10 MHz
Stop 853.10 MHz
#Res BW 5 MHz
#VBW 1 MHz
Sweep 1 ms (601 pts)
Center Freq
846.600000 MHz
Start Freq
840.100000 MHz
Stop Freq
853.100000 MHz
CF Step
1.30000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Band Edge WCDMA C-4233
Mkr1 849.00 MHz
Ref 23.2 dBm
Atten 30 dB
-24.736 dBm
#Avg
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Center 849.00 MHz
Span 10 MHz
#Res BW 100 kHz
#VBW 100 kHz
Sweep 3.84 ms (601 pts)
Center Freq
849.000000 MHz
Start Freq
844.000000 MHz
Stop Freq
854.000000 MHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 4MHz Span WCDMA C-4233
Mkr1 850.360 MHz
Ref 23.2 dBm
Atten 30 dB
-32.908 dBm
#Avg
Log
10
dB/
Offst
11.5
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
1
Start 850.000 MHz
Stop 854.000 MHz
#Res BW 100 kHz
#VBW 100 kHz
Sweep 1.56 ms (601 pts)
Center Freq
852.000000 MHz
Start Freq
850.000000 MHz
Stop Freq
854.000000 MHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-9262
Mkr1 2.488 GHz
Ref 23.2 dBm
Atten 30 dB
-37.85 dBm
#Peak
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-9262
Mkr1 14.08 GHz
Ref 23.2 dBm
Atten 30 dB
-30.07 dBm
#Peak
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 2.50 GHz
Stop 20.00 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: A3LSGHZX10 Power Out WCDMA C-9262
Ref 23.2 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
12
dB
PAvg
100
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center 1.852 40 GHz
Span 13 MHz
#Res BW 5 MHz
VBW 5 MHz
Sweep 1 ms (601 pts)
Center Freq
1.85240000 GHz
Start Freq
1.84590000 GHz
Stop Freq
1.85890000 GHz
CF Step
1.30000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Band Edge WCDMA C-9262
Mkr1 1.850 00 GHz
Ref 23.2 dBm
Atten 30 dB
-28.323 dBm
#Avg
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Center 1.850 00 GHz
Span 10 MHz
#Res BW 100 kHz
VBW 100 kHz
Sweep 3.84 ms (601 pts)
Center Freq
1.85000000 GHz
Start Freq
1.84500000 GHz
Stop Freq
1.85500000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 4 MHz Span WCDMA C-9262
Mkr1 1.848 613 GHz
Ref 23.2 dBm
Atten 30 dB
-37.209 dBm
#Avg
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Center Freq
1.84700000 GHz
Start Freq
1.84500000 GHz
Stop Freq
1.84900000 GHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Center 1.847 000 GHz
Span 4 MHz
#Res BW 100 kHz
VBW 100 kHz
Sweep 1.56 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-9400
Mkr1 2.292 GHz
Ref 23.2 dBm
Atten 30 dB
-39.08 dBm
#Peak
Log
10
dB/
Offst
12
dB
Dl
-12.6
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 4.16 ms (601 pts)
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-9400
Mkr1 14.22 GHz
Ref 23.2 dBm
Atten 30 dB
-30.42 dBm
#Peak
Log
10
dB/
Offst
12
dB
Dl
-12.6
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 2.50 GHz
Stop 20.00 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: A3LSGHZX10 Power Out WCDMA C-9400
Ref 23.2 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
12
dB
PAvg
100
W1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center 1.880 00 GHz
Span 13 MHz
#Res BW 5 MHz
VBW 5 MHz
Sweep 1 ms (601 pts)
Center Freq
1.88000000 GHz
Start Freq
1.87350000 GHz
Stop Freq
1.88650000 GHz
CF Step
1.30000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Occupied Bandwidth
FCC ID: A3LSGHZX10 Occupied BW WCDMA C-9400
Ref 23.2 dBm
Atten 30 dB
#Samp
Log
10
dB/
Offst
12
dB
Center 1.880 00 GHz
Span 10 MHz
#Res BW 30 kHz
#VBW 300 kHz
Sweep 32.44 ms (601 pts)
Occupied Bandwidth
4.1714 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB
Transmit Freq Error 2.705 kHz
x dB Bandwidth 4.583 MHz*
Center Freq
1.88000000 GHz
Start Freq
1.87500000 GHz
Stop Freq
1.88500000 GHz
CF Step
1.00000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
Ch Freq 1.88 GHz
Trig Free
Channel Power
FCC ID: A3LSGHZX10 Channel Pwr WCDMA C-9400
Ref 23.2 dBm
Atten 30 dB
#Peak
Log
10
dB/
Offst
12
dB
Center 1.880 000 GHz
Span 6.265 MHz
#Res BW 62 kHz
#VBW 620 kHz
Sweep 1.52 ms (601 pts)
Channel Power
23.30 dBm / 4.1767 MHz
Power Spectral Density
-42.90 dBm/Hz
Center Freq
1.88000000 GHz
Start Freq
1.87686750 GHz
Stop Freq
1.88313250 GHz
CF Step
626.500000 kHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-9538
Mkr1 2.247 GHz
Ref 23.2 dBm
Atten 30 dB
-38.96 dBm
#Peak
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Aligning RF Gain
Start 10 MHz
Stop 2.500 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 4.16 ms (601 pts)
Center Freq
1.25500000 GHz
Start Freq
10.0000000 MHz
Stop Freq
2.50000000 GHz
CF Step
249.000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Con Spurs WCDMA C-9538
Mkr1 14.05 GHz
Ref 23.2 dBm
Atten 30 dB
-30.81 dBm
#Peak
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
LgAv
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Start 2.50 GHz
Stop 20.00 GHz
#Res BW 1 MHz
VBW 1 MHz
Sweep 43.76 ms (601 pts)
Center Freq
11.2500000 GHz
Start Freq
2.50000000 GHz
Stop Freq
20.0000000 GHz
CF Step
1.75000000 GHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
L
Freq/Channel
FCC ID: A3LSGHZX10 Power Out WCDMA C-9538
Ref 23.2 dBm
Atten 30 dB
#Avg
Log
10
dB/
Offst
12
dB
PAvg
100
V1 S2
S3 FC
AA
¤(f):
FTun
Swp
Center 1.907 60 GHz
Span 13 MHz
#Res BW 5 MHz
VBW 5 MHz
Sweep 1 ms (601 pts)
Center Freq
1.90760000 GHz
Start Freq
1.90110000 GHz
Stop Freq
1.91410000 GHz
CF Step
1.30000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies

Agilent
R L
Freq/Channel
FCC ID: A3LSGHZX10 Band Edge WCDMA C-9538
Mkr1 1.910 00 GHz
Ref 23.2 dBm
Atten 30 dB
-26.571 dBm
#Avg
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
PAvg
100
W1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Center 1.910 00 GHz
Span 10 MHz
#Res BW 100 kHz
VBW 100 kHz
Sweep 3.84 ms (601 pts)
Center Freq
1.91000000 GHz
Start Freq
1.90500000 GHz
Stop Freq
1.91500000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies


Agilent
R L
Freq/Channel
FCC ID: A3LSGHZX10 4 MHz Span WCDMA C-9538
Mkr1 1.911 013 GHz
Ref 23.2 dBm
Atten 30 dB
-34.818 dBm
#Avg
Log
10
dB/
Offst
12
dB
Dl
-13.0
dBm
PAvg
100
V1 S2
S3 FC
AA
¤(f):
f>50k
Swp
Start 1.911 000 GHz
Stop 1.915 000 GHz
#Res BW 100 kHz
VBW 100 kHz
Sweep 1.56 ms (601 pts)
Center Freq
1.91300000 GHz
Start Freq
1.91100000 GHz
Stop Freq
1.91500000 GHz
CF Step
400.000000 kHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Copyright 2000-2002 Agilent Technologies