

6.4 Peak Power Spectral Density – 802.11a/n

§15.407 (a)(1),(5) / RSS-210 [A9.2]

The spectrum analyzer was connected to the antenna terminal while the EUT was operating in a continuous transmission mode at the appropriate center frequencies. Method SA-2, as defined in KDB 789033, was used to measure the power spectral density.

For 20MHz bandwidth signals, the maximum achievable duty cycle was found to be 93.7% for 802.11a mode and 93.1% for 802.11n mode. For 40MHz bandwidth signals, the maximum achievable duty cycle was found to be 85.7%. An RMS detector was used to average 100 traces. The measured power is offsetted by $10 \times \log(1 / \text{duty cycle}) = 0.28$ (for 20MHz BW 802.11a), 0.31 (for 20MHz BW 802.11n) and 0.67 (for 40MHz BW). The minimum number of sweep points required to ensure that the bin-to-bin spacing is such that narrowband emissions are not lost is equal to $2 \times \text{Span} / \text{RBW} = 2 \times 20\text{MHz} / 1\text{MHz} = 40$ sweep points.

The maximum permissible peak power spectral density is 4dBm/MHz in the 5.15GHz – 5.25GHz band and 11dBm/MHz in the 5.25GHz – 5.35 GHz and 5.47 – 5.725GHz bands.





Figure 6-3. Test Instrument & Measurement Setup

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 27 of 84


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/MHz]	Margin [dB]
Band I	5180	36	a	6	3.26	4.0	-0.74
	5200	40	a	6	2.95	4.0	-1.05
	5240	48	a	6	3.00	4.0	-1.00
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	0.11	4.0	-3.89
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	-0.07	4.0	-4.07
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	0.01	4.0	-3.99
	5190	38	n (40MHz)	13.5/15 (MCS0)	-4.99	4.0	-8.99
	5230	46	n (40MHz)	13.5/15 (MCS0)	-4.96	4.0	-8.96
Band II	5260	52	a	6	3.19	11.0	-7.81
	5280	56	a	6	3.48	11.0	-7.52
	5320	64	a	6	3.39	11.0	-7.61
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	0.57	11.0	-10.43
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	0.54	11.0	-10.47
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	0.38	11.0	-10.62
	5270	54	n (40MHz)	13.5/15 (MCS0)	-4.60	11.0	-15.60
	5310	62	n (40MHz)	13.5/15 (MCS0)	-4.64	11.0	-15.64
Band III	5500	100	a	6	3.81	11.0	-7.19
	5580	116	a	6	3.12	11.0	-7.88
	5700	140	a	6	1.99	11.0	-9.01
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	0.94	11.0	-10.06
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	0.30	11.0	-10.70
	5700	140	n (20MHz)	6.5/7.2 (MCS0)	-0.75	11.0	-11.75
	5510	102	n (40MHz)	13.5/15 (MCS0)	-5.14	11.0	-16.14
	5550	110	n (40MHz)	13.5/15 (MCS0)	-5.18	11.0	-16.18
	5670	134	n (40MHz)	13.5/15 (MCS0)	-6.21	11.0	-17.21

Table 6-6. Conducted Power Spectral Density Measurements

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 28 of 84




Plot 6-26. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-27. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 29 of 84




Plot 6-28. Peak Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-29. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 30 of 84




Plot 6-30. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 6-31. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 31 of 84




Plot 6-32. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 6-33. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 32 of 84




Plot 6-34. Peak Power Spectral Density Plot (802.11a (UNII Band 2) – Ch. 52)




Plot 6-35. Peak Power Spectral Density Plot (802.11a (UNII Band 2) – Ch. 56)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 33 of 84




Plot 6-36. Peak Power Spectral Density Plot (802.11a (UNII Band 2) – Ch. 64)



Plot 6-37. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 52)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 34 of 84




Plot 6-38. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 56)




Plot 6-39. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 64)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 35 of 84




Plot 6-40. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 54)




Plot 6-41. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 62)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 36 of 84



Plot 6-42. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 100)




Plot 6-43. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 116)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 37 of 84




Plot 6-44. Peak Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 140)




Plot 6-45. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 100)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 38 of 84




Plot 6-46. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 116)




Plot 6-47. Peak Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 140)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 39 of 84




Plot 6-48. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 102)



Plot 6-49. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 110)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 40 of 84



Plot 6-50. Peak Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 134)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 41 of 84

6.5 Peak Excursion Ratio – 802.11a/n

§15.407(a)(6)

The spectrum analyzer was connected to the antenna terminal while the EUT was operating in the continuous transmission mode at the appropriate center frequencies.

Method SA-2, as defined in KDB 789033 and with the settings described in Section 6.4 of this test report, was used to generate the average signal trace and the procedure outlined in section F) was used to generate the peak signal trace. For 20MHz bandwidth signals, the maximum achievable duty cycle was found to be 93.7% for 802.11a mode and 93.1% for 802.11n mode. For 40MHz bandwidth signals, the maximum achievable duty cycle was found to be 85.7%. An RMS detector was used to average 100 traces. The measured power is offsetted by $10 \times \log(1 / \text{duty cycle}) = 0.28$ (for 20MHz BW 802.11a), 0.31 (for 20MHz BW 802.11n) and 0.67 (for 40MHz BW). A minimum of 100 trace averages were used for the average signal. The peak and average traces are then used to determine the peak excursion.

The largest permissible difference between the modulation envelope (measured using a peak hold function) and the maximum conducted output power is 13 dBm/MHz.





Figure 6-4. Test Instrument & Measurement Setup

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 42 of 84


Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Peak Excursion Ratio [dBm]	Max Permissible Peak Excursion Ratio [dBm/MHz]	Margin [dB]
5180	36	a	6	8.39	13.0	-4.61
5200	40	a	6	7.69	13.0	-5.31
5240	48	a	6	8.61	13.0	-4.39
5180	36	n (20MHz)	6.5/7.2 (MCS0)	7.88	13.0	-5.12
5200	40	n (20MHz)	6.5/7.2 (MCS0)	8.36	13.0	-4.64
5240	48	n (20MHz)	6.5/7.2 (MCS0)	7.85	13.0	-5.15
5190	38	n (40MHz)	13.5/15 (MCS0)	8.17	13.0	-4.83
5230	46	n (40MHz)	13.5/15 (MCS0)	8.14	13.0	-4.86
5260	52	a	6	8.19	13.0	-4.81
5280	56	a	6	8.31	13.0	-4.69
5320	64	a	6	7.98	13.0	-5.02
5260	52	n (20MHz)	6.5/7.2 (MCS0)	7.75	13.0	-5.25
5280	56	n (20MHz)	6.5/7.2 (MCS0)	7.8	13.0	-5.20
5320	64	n (20MHz)	6.5/7.2 (MCS0)	7.53	13.0	-5.47
5270	54	n (40MHz)	13.5/15 (MCS0)	8.43	13.0	-4.57
5310	62	n (40MHz)	13.5/15 (MCS0)	8.91	13.0	-4.09
5500	100	a	6	9.07	13.0	-3.93
5580	116	a	6	8.58	13.0	-4.42
5700	140	a	6	8.31	13.0	-4.69
5500	100	n (20MHz)	6.5/7.2 (MCS0)	7.7	13.0	-5.30
5580	116	n (20MHz)	6.5/7.2 (MCS0)	7.49	13.0	-5.51
5700	140	n (20MHz)	6.5/7.2 (MCS0)	7.1	13.0	-5.90
5510	102	n (40MHz)	13.5/15 (MCS0)	8.28	13.0	-4.72
5550	110	n (40MHz)	13.5/15 (MCS0)	8.77	13.0	-4.23
5670	134	n (40MHz)	13.5/15 (MCS0)	8.01	13.0	-4.99

Table 6-7. Conducted Peak Excursion Ratio Measurements

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 43 of 84




Plot 6-51. Peak Excursion Ratio Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 6-52. Peak Excursion Ratio Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: A3LSHVE270S		 FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION) 		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 44 of 84




Plot 6-53. Peak Excursion Ratio Plot (802.11a (UNII Band 1) – Ch. 48)




Plot 6-54. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 45 of 84




Plot 6-55. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)



Plot 6-56. Peak Excursion Ratio Plot (20MHz BW 802.11a/n (UNII Band 1) – Ch. 48)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 46 of 84



Plot 6-57. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)



Plot 6-58. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 47 of 84



Plot 6-59. Peak Excursion Ratio Plot (802.11a (UNII Band 2) – Ch. 52)




Plot 6-60. Peak Excursion Ratio Plot (802.11a (UNII Band 2) – Ch. 56)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 48 of 84




Plot 6-61. Peak Excursion Ratio Plot (802.11a (UNII Band 2) – Ch. 64)



Plot 6-62. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 52)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 49 of 84




Plot 6-63. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 2) – Ch. 56)




Plot 6-64. Peak Excursion Ratio Plot (20MHz BW 802.11a/n (UNII Band 2) – Ch. 64)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 50 of 84




Plot 6-65. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 54)




Plot 6-66. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 2) – Ch. 62)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 51 of 84




Plot 6-67. Peak Excursion Ratio Plot (802.11a (UNII Band 3) – Ch. 100)




Plot 6-68. Peak Excursion Ratio Plot (802.11a (UNII Band 3) – Ch. 116)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 52 of 84




Plot 6-69. Peak Excursion Ratio Plot (802.11a (UNII Band 3) – Ch. 140)




Plot 6-70. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 100)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 53 of 84




Plot 6-71. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 116)



Plot 6-72. Peak Excursion Ratio Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 140)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 54 of 84




Plot 6-73. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 102)



Plot 6-74. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 110)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 55 of 84



Plot 6-75. Peak Excursion Ratio Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 134)

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 56 of 84

6.6 Frequency Stability

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,180,000,000 Hz
 CHANNEL: 36
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,179,999,987	-13	-0.0000003
100 %		- 30	5,180,000,014	14	0.0000003
100 %		- 20	5,179,999,999	-1	0.0000000
100 %		- 10	5,179,999,995	-5	-0.0000001
100 %		0	5,180,000,013	13	0.0000003
100 %		+ 10	5,180,000,005	5	0.0000001
100 %		+ 20	5,180,000,021	21	0.0000004
100 %		+ 30	5,179,999,972	-28	-0.0000005
100 %		+ 40	5,179,999,998	-2	0.0000000
100 %		+ 50	5,180,000,006	6	0.0000001
115 %	4.37	+ 20	5,179,999,982	-18	-0.0000003
BATT. ENDPOINT	3.22	+ 20	5,180,000,027	27	0.0000005

Table 6-8. Frequency Stability Measurements for UNII Band 1 (Ch. 36)

Note:

Based on the results of the frequency stability test at the low channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset	Page 57 of 84	

Frequency Stability (Cont'd)

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,260,000,000 Hz
 CHANNEL: 52
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,179,999,972	-28	-0.0000005
100 %		- 30	5,180,000,007	7	0.0000001
100 %		- 20	5,179,999,991	-9	-0.0000002
100 %		- 10	5,180,000,028	28	0.0000005
100 %		0	5,179,999,973	-27	-0.0000005
100 %		+ 10	5,180,000,000	0	0.0000000
100 %		+ 20	5,180,000,004	4	0.0000001
100 %		+ 30	5,179,999,980	-20	-0.0000004
100 %		+ 40	5,180,000,003	3	0.0000001
100 %		+ 50	5,179,999,972	-28	-0.0000005
115 %	4.37	+ 20	5,180,000,001	1	0.0000000
BATT. ENDPOINT	3.22	+ 20	5,180,000,000	0	0.0000000

Table 6-9. Frequency Stability Measurements for UNII Band 2 (Ch. 52)

Note:

Based on the results of the frequency stability test at the low channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset	Page 58 of 84	

Frequency Stability (Cont'd)

§15.407(g)

The EUT was placed inside of an environmental chamber as the temperature in the chamber was varied between -30°C and +50°C. The temperature was incremented by 10° intervals and the unit was allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded. Data for the worst case channel is shown below.

OPERATING FREQUENCY: 5,500,000,000 Hz
 CHANNEL: 100
 REFERENCE VOLTAGE: 3.8 VDC

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	5,179,999,971	-29	-0.0000006
100 %		- 30	5,180,000,015	15	0.0000003
100 %		- 20	5,179,999,999	-1	0.0000000
100 %		- 10	5,179,999,992	-8	-0.0000002
100 %		0	5,179,999,997	-3	-0.0000001
100 %		+ 10	5,179,999,993	-7	-0.0000001
100 %		+ 20	5,180,000,018	18	0.0000003
100 %		+ 30	5,180,000,014	14	0.0000003
100 %		+ 40	5,180,000,028	28	0.0000005
100 %		+ 50	5,179,999,984	-16	-0.0000003
115 %	4.37	+ 20	5,179,999,997	-3	-0.0000001
BATT. ENDPOINT	3.22	+ 20	5,179,999,983	-17	-0.0000003

Table 6-10. Frequency Stability Measurements for UNII Band 3 (Ch. 100)

Note:

Based on the results of the frequency stability test at the low channel the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset	Page 59 of 84	

6.7 Radiated Spurious Emission Measurements

§15.407(b)(1), (6), §15.205, §15.209; RSS-210 [A9.2]

The EUT was tested from 9kHz and up to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, peak measurements were taken using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033 and linearly polarized horn antennas. All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-11 per Section 15.209.

All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section. All measurements shown in this section were obtained using traditional radiated test methods as defined in C63.10-2009. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 789033 were not used to evaluate this device.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-11. Radiated Limits

Sample Calculation

- o Field Strength Level [dBμV/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- o AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- o Margin [dB] = Field Strength Level [dBμV/m] – Limit [dBμV/m]

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 60 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5180MHz

Channel: 36

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	10360.00	-97.41	Peak	H	45.89	0.00	55.49	68.20	-12.71
*	15540.00	-135.00	Average	H	58.35	0.00	30.35	53.98	-23.63
*	15540.00	-125.00	Peak	H	58.35	0.00	40.35	73.98	-33.63
*	20720.00	-102.37	Average	H	44.02	-9.54	39.11	53.98	-14.87
*	20720.00	-91.38	Peak	H	44.02	-9.54	50.10	73.98	-23.88
	25900.00	-96.99	Peak	H	44.85	-9.54	45.32	68.20	-22.88

Table 6-12. Radiated Measurements

NOTES:

- All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
- All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
- For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
- Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 61 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5200MHz

Channel: 40

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	10400.00	-96.77	Peak	H	45.98	0.00	56.21	68.20	-11.99
*	15600.00	-135.00	Average	H	58.64	0.00	30.64	53.98	-23.34
*	15600.00	-125.00	Peak	H	58.64	0.00	40.64	73.98	-33.34
*	20800.00	-102.00	Average	H	44.00	-9.54	39.45	53.98	-14.53
*	20800.00	-92.05	Peak	H	44.00	-9.54	49.40	73.98	-24.58
	26000.00	-98.93	Peak	H	44.88	-9.54	43.41	68.20	-24.79

Table 6-13. Radiated Measurements

NOTES:

- All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
- All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
- For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
- Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 62 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5240MHz

Channel: 48

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	-96.58	Peak	H	46.14	0.00	56.56	68.20	-11.64
* 15720.00	-135.00	Average	H	59.21	0.00	31.21	53.98	-22.77
* 15720.00	-125.00	Peak	H	59.21	0.00	41.21	73.98	-32.77
* 20960.00	-102.46	Average	H	43.99	-9.54	38.99	53.98	-14.99
* 20960.00	-92.12	Peak	H	43.99	-9.54	49.33	73.98	-24.65
26200.00	-98.85	Peak	H	44.82	-9.54	43.43	68.20	-24.77

Table 6-14. Radiated Measurements

NOTES:

- All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
- All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
- For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
- Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 63 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5260MHz

Channel: 52

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	10520.00	-97.40	Peak	H	46.23	0.00	55.82	68.20	-12.38
*	15780.00	-135.00	Average	H	59.53	0.00	31.53	53.98	-22.45
*	15780.00	-125.00	Peak	H	59.53	0.00	41.53	73.98	-32.45
*	21040.00	-103.63	Average	H	44.01	-9.54	37.84	53.98	-16.14
*	21040.00	-93.44	Peak	H	44.01	-9.54	48.03	73.98	-25.95
	26300.00	-96.65	Peak	H	44.87	-9.54	45.68	68.20	-22.52

Table 6-15. Radiated Measurements

NOTES:

- All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
- All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
- For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
- Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 64 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5280MHz

Channel: 56

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	10560.00	-97.34	Peak	H	46.32	0.00	55.99	68.20	-12.21
*	15840.00	-135.00	Average	H	59.88	0.00	31.88	53.98	-22.09
*	15840.00	-125.00	Peak	H	59.88	0.00	41.88	73.98	-32.09
*	21120.00	-103.59	Average	H	44.00	-9.54	37.87	53.98	-16.11
*	21120.00	-91.36	Peak	H	44.00	-9.54	50.10	73.98	-23.88
	26400.00	-95.40	Peak	H	44.81	-9.54	46.87	68.20	-21.33

Table 6-16. Radiated Measurements

NOTES:

- All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
- All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
- For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
- Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
- Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 65 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5320MHz

Channel: 64

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	10640.00	-107.88	Average	H	46.52	0.00	45.63	53.98	-8.34
*	10640.00	-97.04	Peak	H	46.52	0.00	56.47	73.98	-17.50
*	15960.00	-135.00	Average	H	62.27	0.00	34.27	53.98	-19.71
*	15960.00	-125.00	Peak	H	62.27	0.00	44.27	73.98	-29.71
*	21280.00	-103.31	Average	H	44.02	-9.54	38.17	53.98	-15.81
*	21280.00	-91.98	Peak	H	44.02	-9.54	49.50	73.98	-24.48
	26600.00	-116.24	Peak	H	47.47	-9.54	28.69	68.20	-39.51

Table 6-17. Radiated Measurements

NOTES:

1. All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
3. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
6. The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
7. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
8. Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
9. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 66 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5500MHz

Channel: 100

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11000.00	-107.45	Average	H	46.98	0.00	46.53	53.98	-7.45
*	11000.00	-97.07	Peak	H	46.98	0.00	56.91	73.98	-17.07
	16500.00	-125.00	Peak	H	60.10	0.00	42.10	68.20	-26.10
	22000.00	-92.03	Peak	H	44.30	-9.54	49.73	68.20	-18.47
	27500.00	-121.89	Peak	H	47.96	-9.54	23.52	68.20	-44.68

Table 6-18. Radiated Measurements

NOTES:

1. All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
3. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
6. The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
7. Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
8. Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
9. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 67 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5580MHz

Channel: 116

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11160.00	-106.60	Average	H	49.42	0.00	49.83	53.98	-4.15
*	11160.00	-97.14	Peak	H	49.42	0.00	59.29	73.98	-14.69
	16740.00	-125.00	Peak	H	58.53	0.00	40.53	68.20	-27.67
*	22320.00	-103.28	Average	H	44.40	-9.54	38.58	53.98	-15.40
*	22320.00	-91.08	Peak	H	44.40	-9.54	50.78	73.98	-23.20
	27900.00	-122.31	Peak	H	48.14	-9.54	23.29	68.20	-44.91

Table 6-19. Radiated Measurements

NOTES:

1. All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
3. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
6. The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
7. Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
8. Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
9. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 68 of 84

Radiated Spurious Emission Measurements (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 1 & 3 Meters

Operating Frequency: 5700MHz

Channel: 140

	Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11400.00	-107.43	Average	H	47.61	0.00	47.18	53.98	-6.80
*	11400.00	-97.61	Peak	H	47.61	0.00	57.00	73.98	-16.98
	17100.00	-125.00	Peak	H	56.08	0.00	38.08	68.20	-30.12
*	22800.00	-103.12	Average	H	44.45	-9.54	38.79	53.98	-15.19
*	22800.00	-93.21	Peak	H	44.45	-9.54	48.70	73.98	-25.28
	28500.00	-122.89	Peak	H	48.28	-9.54	22.84	68.20	-45.36

Table 6-20. Radiated Measurements

NOTES:

1. All harmonics that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
2. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 are below the limit shown in Table 6-11.
3. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
4. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
5. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
6. The spectrum is measured from 9kHz to 40GHz and the worst-case emissions are reported.
7. Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
8. Emissions below 18GHz were measured at a 3 meter test distance and emissions above 18GHz were measured at a 1 meter test distance.
9. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 69 of 84

6.8 Radiated Band Edge Measurements (20MHz BW)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5180MHz

Channel: 36

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5087.50	-101.14	Average	H	39.19	45.05	53.98	-8.93
5087.50	-89.65	Peak	H	39.19	56.54	73.98	-17.44
5121.90	-101.77	Average	H	39.23	44.46	53.98	-9.52
5121.90	-90.23	Peak	H	39.23	56.00	73.98	-17.98
5150.00	-100.68	Average	H	39.27	45.59	53.98	-8.39
5150.00	-83.58	Peak	H	39.27	62.69	73.98	-11.29

Table 6-21. Radiated Restricted Band Measurements (4.5 – 5.15GHz)

NOTES:

- For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
- The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
- The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
- Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
- Above 960MHz the limit is 500 μV/m (54dBμV/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 70 of 84

Radiated Band Edge Measurements (20MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5320MHz

Channel: 64

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5350.20	-101.51	Average	H	39.53	45.02	53.98	-8.96
5350.20	-89.74	Peak	H	39.53	56.79	73.98	-17.19
5367.98	-101.92	Average	H	39.55	44.63	53.98	-9.35
5367.98	-88.08	Peak	H	39.55	58.47	73.98	-15.51
5394.80	-101.90	Average	H	39.59	44.69	53.98	-9.29
5394.80	-88.91	Peak	H	39.59	57.68	73.98	-16.30

Table 6-22. Radiated Restricted Band Measurements (5.35 – 5.46GHz, 5.46 – 5.47GHz)

NOTES:

1. Emissions within 5.35 – 5.46GHz lie in a restricted band and are subject to the radiated emissions limits specified in §15.209. Emission within 5.46 – 5.47GHz are at the lower band edge of UNII Band 3 transmission and are subject to the -27dBm/MHz (68.2dBμV/m) EIRP limit specified in §15.407.
2. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
6. Above 960MHz the limit is 500 μV/m (54dBμV/m) at 3 meters radiated for emissions that lie in restricteds band specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 71 of 84

Radiated Band Edge Measurements (20MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5500MHz

Channel: 100

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5442.30	-102.08	Average	H	39.65	44.57	53.98	-9.41
5442.30	-89.37	Peak	H	39.65	57.28	73.98	-16.70
5460.00	-101.80	Average	H	39.67	44.87	53.98	-9.11
5460.00	-90.44	Peak	H	39.67	56.23	73.98	-17.75
5470.00	-87.68	Peak	H	39.68	59.00	68.20	-9.20

Table 6-23. Radiated Restricted Band Measurements (5.35 – 5.46GHz, 5.46 – 5.47GHz)

NOTES:

1. Emissions within 5.35 – 5.46GHz lie in a restricted band and are subject to the radiated emissions limits specified in §15.209. Emission within 5.46 – 5.47GHz are at the lower band edge of UNII Band 3 transmission and are subject to the -27dBm/MHz (68.2dBμV/m) EIRP limit specified in §15.407.
2. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
6. Above 960MHz the limit is 500 μV/m (54dBμV/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 72 of 84

Radiated Band Edge Measurements (20MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11a

Worst Case Transfer Rate: 6 Mbps

Distance of Measurements: 3 Meters

Operating Frequency: 5700MHz

Channel: 140

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5725.70	-84.90	Peak	H	40.18	62.28	68.20	-5.92
5726.60	-84.43	Peak	H	40.18	62.75	68.20	-5.45
5729.30	-85.80	Peak	H	40.18	61.39	68.20	-6.81

Table 6-24. Radiated Restricted Band Measurements

NOTES:

1. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
2. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
3. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
4. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
5. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 73 of 84

6.9 Radiated Band Edge Measurements (40MHz BW)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5190MHz

Channel: 38

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5025.00	-102.39	Average	H	39.10	43.71	53.98	-10.27
5025.00	-89.82	Peak	H	39.10	56.28	73.98	-17.70
5105.20	-102.19	Average	H	39.21	44.02	53.98	-9.96
5105.20	-90.09	Peak	H	39.21	56.12	73.98	-17.86
5146.90	-101.21	Average	H	39.26	45.05	53.98	-8.93
5146.90	-86.16	Peak	H	39.26	60.10	73.98	-13.88

Table 6-25. Radiated Restricted Band Measurements (4.5 – 5.15GHz)

NOTES:

1. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
2. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
3. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
4. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
5. Above 960MHz the limit is 500 μV/m (54dBμV/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 74 of 84

Radiated Band Edge Measurements (40MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5310MHz

Channel: 62

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5350.00	-101.60	Average	H	39.53	44.93	53.98	-9.05
5350.00	-88.53	Peak	H	39.53	58.00	73.98	-15.98
5352.60	-101.76	Average	H	39.53	44.78	53.98	-9.20
5352.60	-88.98	Peak	H	39.53	57.56	73.98	-16.42
5358.80	-101.87	Average	H	39.54	44.67	53.98	-9.31
5358.80	-88.99	Peak	H	39.54	57.55	73.98	-16.43

Table 6-26. Radiated Restricted Band Measurements (5.35 – 5.46GHz, 5.46 – 5.47GHz)

NOTES:

1. Emissions within 5.35 – 5.46GHz lie in a restricted band and are subject to the radiated emissions limits specified in §15.209. Emission within 5.46 – 5.47GHz are at the lower band edge of UNII Band 3 transmission and are subject to the -27dBm/MHz (68.2dBμV/m) EIRP limit specified in §15.407.
2. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
6. Above 960MHz the limit is 500 μV/m (54dBμV/m) at 3 meters radiated for emissions that lie in restricted band specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 75 of 84

Radiated Band Edge Measurements (40MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5510MHz

Channel: 102

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5444.10	-101.84	Average	H	39.65	44.81	53.98	-9.17
5444.10	-89.61	Peak	H	39.65	57.04	73.98	-16.94
5459.40	-102.03	Average	H	39.67	44.64	53.98	-9.34
5459.40	-90.55	Peak	H	39.67	56.12	73.98	-17.86
5466.90	-88.74	Peak	H	39.68	57.94	68.20	-10.26

Table 6-27. Radiated Restricted Band Measurements (5.35 – 5.46GHz, 5.46 – 5.47GHz)

NOTES:

1. Emissions within 5.35 – 5.46GHz lie in a restricted band and are subject to the radiated emissions limits specified in §15.209. Emission within 5.46 – 5.47GHz are at the lower band edge of UNII Band 3 transmission and are subject to the -27dBm/MHz (68.2dBμV/m) EIRP limit specified in §15.407.
2. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
5. Levels at -135 dBm represent the analyzer noise floor and signify that no emission was detected.
6. Above 960MHz the limit is 500 μV/m (54dBμV/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 76 of 84

Radiated Band Edge Measurements (40MHz BW) (Cont'd)

§15.407(b)(1) and (2), §15.205 & §15.209; RSS-210 [A9.2]

Worst Case Mode: 802.11n (40MHz)

Worst Case Transfer Rate: MCS0

Distance of Measurements: 3 Meters

Operating Frequency: 5690MHz

Channel: 138

Frequency [MHz]	Analyzer Level [dBm]	Detector	Pol. [H/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
5726.40	-90.08	Peak	H	40.18	57.10	68.20	-11.10
5766.10	-90.23	Peak	H	40.28	57.04	68.20	-11.16
5796.20	-89.82	Peak	H	40.37	57.55	68.20	-10.65

Table 6-28. Radiated Restricted Band Measurements


NOTES:

1. For frequencies above 1GHz, peak emissions are measured using RBW = 1MHz and VBW = 3MHz. Average emissions are measured using RBW = 1MHz, VBW = 3MHz, RMS detector, and 100 trace averages under continuous operation ("Method AD") per KDB 789033.
2. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
3. The EUT is supplied with nominal AC voltage and/or a new/fully-recharged battery.
4. Levels at - 135 dBm represent the analyzer noise floor and signify that no emission was detected.
5. Above 960MHz the limit is 500 μV/m (54dBμ/m) at 3 meters radiated for emissions that lie in restricted bands specified in §15.205.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 77 of 84

6.10 Line-Conducted Test Data

§15.207; RSS-Gen [7.2.2]



Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.150	L1	0.2	46.10	66.00	19.90	30.40	56.00	25.60
0.224	L1	0.1	38.40	62.70	24.30	21.80	52.70	30.90
0.296	L1	0.1	43.50	60.30	16.80	37.30	50.30	13.00
0.589	L1	0.1	36.80	56.00	19.20	27.80	46.00	18.20
1.178	L1	0.2	26.80	56.00	29.20	17.20	46.00	28.80
2.895	L1	0.2	29.60	56.00	26.40	21.80	46.00	24.20
3.658	L1	0.2	30.30	56.00	25.70	22.30	46.00	23.70
5.480	L1	0.3	30.10	60.00	29.90	22.10	50.00	27.90
25.998	L1	0.9	28.90	60.00	31.10	23.70	50.00	26.30
29.119	L1	1.0	31.40	60.00	28.60	25.50	50.00	24.50

Table 6-29. Line Conducted Data with 802.11a UNII Band 1 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 78 of 84

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-77. Line Conducted Plot with 802.11a UNII Band 1 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBµV	Limit dBµV	Margin dB	Average dBµV	Limit dBµV	Margin dB
0.296	N	0.2	43.30	60.30	17.00	37.30	50.30	13.00
0.589	N	0.1	37.20	56.00	18.80	28.80	46.00	17.20
3.023	N	0.2	35.50	56.00	20.50	25.30	46.00	20.70
3.658	N	0.2	35.60	56.00	20.40	26.40	46.00	19.60
4.117	N	0.2	35.70	56.00	20.30	26.30	46.00	19.70
4.407	N	0.2	36.40	56.00	19.60	26.90	46.00	19.10
4.895	N	0.2	36.10	56.00	19.90	26.50	46.00	19.50
4.970	N	0.2	35.90	56.00	20.10	26.40	46.00	19.60
28.973	N	1.0	39.30	60.00	20.70	28.60	50.00	21.40
29.056	N	1.0	39.20	60.00	20.80	28.40	50.00	21.60

Table 6-30. Line Conducted Data with 802.11a UNII Band 1 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 36. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBµV) = QP/AV Analyzer/Receiver Level (dBµV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBµV) - QP/AV Level (dBµV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 79 of 84

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-78. Line Conducted Plot with 802.11a UNII Band 2 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.150	L1	0.2	40.60	66.00	25.40	26.80	56.00	29.20
0.294	L1	0.1	44.20	60.40	16.20	38.30	50.40	12.10
0.508	L1	0.1	28.80	56.00	27.20	23.10	46.00	22.90
0.589	L1	0.1	36.90	56.00	19.10	27.80	46.00	18.20
1.570	L1	0.2	26.30	56.00	29.70	17.90	46.00	28.10
2.650	L1	0.2	29.20	56.00	26.80	21.20	46.00	24.80
3.865	L1	0.2	29.90	56.00	26.10	22.30	46.00	23.70
4.936	L1	0.2	30.60	56.00	25.40	22.40	46.00	23.60
10.232	L1	0.4	23.90	60.00	36.10	16.40	50.00	33.60
28.689	L1	0.9	32.80	60.00	27.20	27.50	50.00	22.50

Table 6-31. Line Conducted Data with 802.11a UNII Band 2 (L1)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 80 of 84

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-79. Line Conducted Plot with 802.11a UNII Band 2 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.294	N	0.2	43.90	60.40	16.50	37.70	50.40	12.70
0.589	N	0.1	35.60	56.00	20.40	26.90	46.00	19.10
3.926	N	0.2	37.90	56.00	18.10	28.40	46.00	17.60
4.247	N	0.2	37.70	56.00	18.30	28.40	46.00	17.60
4.328	N	0.2	38.20	56.00	17.80	28.60	46.00	17.40
4.405	N	0.2	38.00	56.00	18.00	28.50	46.00	17.50
4.576	N	0.2	38.20	56.00	17.80	28.60	46.00	17.40
4.700	N	0.2	38.10	56.00	17.90	28.20	46.00	17.80
4.925	N	0.2	38.10	56.00	17.90	28.50	46.00	17.50
28.869	N	1.0	39.20	60.00	20.80	29.40	50.00	20.60

Table 6-32. Line Conducted Data with 802.11a UNII Band 2 (N)


Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 52. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 81 of 84

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-80. Line Conducted Plot with 802.11a UNII Band 3 (L1)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.155	L1	0.2	37.40	65.80	28.40	24.20	55.80	31.60
0.294	L1	0.1	43.90	60.40	16.50	37.70	50.40	12.70
0.589	L1	0.1	37.60	56.00	18.40	26.80	46.00	19.20
3.606	L1	0.2	31.90	56.00	24.10	23.80	46.00	22.20
4.569	L1	0.2	32.90	56.00	23.10	24.50	46.00	21.50
4.801	L1	0.2	32.40	56.00	23.60	24.30	46.00	21.70
6.063	L1	0.3	31.30	60.00	28.70	23.60	50.00	26.40
20.504	L1	0.7	20.90	60.00	39.10	12.10	50.00	37.90
28.291	L1	0.9	31.50	60.00	28.50	25.60	50.00	24.40
29.238	L1	1.0	33.40	60.00	26.60	28.30	50.00	21.70

Table 6-33. Line Conducted Plot with 802.11a UNII Band 3 (L1)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. L1 = Phase; N = Neutral
4. Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
5. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
6. Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 82 of 84

Line-Conducted Test Data (Cont'd)

§15.207; RSS-Gen [7.2.2]



Plot 6-81. Line Conducted Plot with 802.11a UNII Band 3 (N)

Frequency MHz	Line	Corr. dB	QuasiPeak dBμV	Limit dBμV	Margin dB	Average dBμV	Limit dBμV	Margin dB
0.150	N	0.3	39.10	66.00	26.90	26.50	56.00	29.50
0.294	N	0.2	44.10	60.40	16.30	37.80	50.40	12.60
0.587	N	0.1	35.90	56.00	20.10	26.00	46.00	20.00
3.356	N	0.2	36.80	56.00	19.20	27.20	46.00	18.80
3.914	N	0.2	38.20	56.00	17.80	28.90	46.00	17.10
4.229	N	0.2	37.60	56.00	18.40	28.20	46.00	17.80
4.310	N	0.2	37.70	56.00	18.30	28.00	46.00	18.00
4.585	N	0.2	38.00	56.00	18.00	28.50	46.00	17.50
4.889	N	0.2	37.50	56.00	18.50	28.00	46.00	18.00
29.108	N	1.0	38.70	60.00	21.30	27.70	50.00	22.30

Table 6-34. Line Conducted Data with 802.11a UNII Band 3 (N)

Notes:

- All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in 802.11a mode using 6Mbps on Channel 100. The emissions found were not affected by the choice of channel used during testing.
- The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
- L1 = Phase; N = Neutral
- Corr. (dB) = Cable loss (dB) + LISN insertion factor (dB)
- QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Corr. (dB)
- Margin (dB) = QP/AVLimit (dBμV) - QP/AV Level (dBμV)
- Traces shown in plot are made using a peak detector.
- Deviations to the Specifications: None.

FCC ID: A3LSHVE270S	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 83 of 84

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSHVE270S** is in compliance with Part 15E of the FCC Rules and RSS-210 of the Industry Canada Rules.

FCC ID: A3LSHVE270S		FCC Pt. 15.407 802.11a/n UNII MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1210111489.A3L	Test Dates: Nov. 14, 2012	EUT Type: Portable Handset		Page 84 of 84