

KCTL

KP20-04286

REPORT REVISION HISTORY

Date	Revision	Page No
2020-08-13	Originally issued	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

General remarks for test reports

Nothing significant to report.

Contents

1. Applicant information	4
2. Laboratory information.....	5
3. Test system configuration.....	6
3.1 Operation environment.....	6
3.2 Measurement Uncertainty	7
4. Description of EUT	9
4.1 General information.....	9
4.2 Product description.....	10
4.3 Auxiliary equipments	11
4.4 Test configuration	12
4.5 Operating conditions	14
5. Summary of test results	16
5.1 Summary of EMI emission test results.....	16
6. Test results	17
6.1 Conducted Emissions.....	17
6.2 Radiated Emission	20

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea Tel: 82-31-285-0894 Fax: 82-505-299-8311 www.kctl.co.kr	Report No.: KR20-SEF0123 Page (4) of (40)	
---	---	---

1. Applicant information

Applicant: Samsung Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
 16677, Rep. of Korea
E-mail: sm3076.lee@samsung.com
Contact name: Sungmin Lee

Manufacturer: Samsung Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do,
 16677, Rep. of Korea
E-mail: sm3076.lee@samsung.com
Contact name: Sungmin Lee

Factory: Samsung Electronics Vietnam Co. Ltd.
Address: KCN Yen Binh I, Pho Yen, Thai Nguyen, VIETNAM

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (5) of (40)

KCTL

2. Laboratory information

Address

KCTL Inc. (Suwon Lab.)

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Telephone Number: 82 31 285 0894

Facsimile Number: 82 505 299 8311


FCC Site Designation No: KR0040

VCCI Registration No.: R-20080, G-20078, C-20059, T-20056

Industry Canada Registration No. : 8035A

KOLAS NO.: KT231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber 10 m (RE)	21.4 °C	37.2 % R.H.	-
Shielded room(CE)	21.9 °C	36.7 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted Emission measurement (Confidence level about 95 %, $k = 2$)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz: 3.7 dB	
	150 kHz ~ 30 MHz: 3.3 dB	
Shielded Room (CE#2)	9 kHz ~ 150 kHz: 3.5 dB	
	150 kHz ~ 30 MHz: 3.1 dB	
Radiated Emission measurement (Confidence level about 95 %, $k = 2$)		
10 m Chamber (4F)	30 MHz ~ 300 MHz	3 m: 5.4 dB
		10 m: 5.3 dB
	300 MHz ~ 1 000 MHz	3 m: 5.5 dB
		10 m: 5.4 dB
	1 GHz ~ 6 GHz	3 m: 6.4 dB
	6 GHz ~ 18 GHz	3 m: 6.6 dB
	18 GHz ~ 30 GHz	3 m: 6.7 dB
	30 GHz ~ 40 GHz	3 m: 6.2 dB
10 m Chamber (2F)	30 MHz ~ 300 MHz	3 m: 5.0 dB
		10 m: 5.0 dB
	300 MHz ~ 1 000 MHz	3 m: 5.2 dB
		10 m: 5.0 dB
	1 GHz ~ 6 GHz	3 m: 6.4 dB
	6 GHz ~ 18 GHz	3 m: 6.6 dB

3.3 Measurement Program

These test items were performed by software programs;

Test item	Measurement Program		Used
Conducted Emission	EP5CE_V 5.4.0(TOYO)		☒
Radiated Emission	2F	EP5RE_V 4.6.0(TOYO)	☒
	4F	EP5RE_V 5.11.10(TOYO)	

KCTL

4. Description of EUT

4.1 General information

Declared Hardware Version	REV1.0
Declared Software Version	A013M.001
IMEI No	351797380024253/01
Operating Band(s)	GSM 850/900/1800/1900 WCDMA FDD 1/2/4/5/8 LTE FDD 1/2/3/4/5/7/8/28/66

KCTL

4.2 Product description

Type of product	Mobile phone
Model name (Basic)	SM-A013M
Model name (Variant)	-
Difference	-
Serial no	-
Testing voltage	120 V, 60 Hz
Input/Output rating	Adapter (EP-TA60JBS) Input: AC 100 V - 240 V, 50/60 Hz, 0.15 A Output: DC 5.0 V, 700 mA Serial no: R37N4EP0062HM3
Internal clock frequency	Above 108 MHz
RF Frequency	Bluetooth(BDR/EDR/BLE)_2 402 MHz ~ 2 480 MHz WIFI(802.11b/g/n20)_2 412 MHz ~ 2 472 MHz LTE Band 2_1 850.7 MHz ~ 1 909.3 MHz LTE Band 4_1 710.7 MHz ~ 1 754.3 MHz LTE Band 5_824.7 MHz ~ 848.3 MHz LTE Band 66_1 710.7 MHz ~ 1 779.3 MHz GSM 850_824.2 MHz ~ 848.8 MHz GSM 1900_1 850.2 MHz ~ 1 909.8 MHz WCDMA 850(5)_826.4 MHz ~ 846.6 MHz WCDMA 1700(4)_1 712.4 MHz ~ 1 752.6 MHz WCDMA 1900(2)_1 852.4 MHz ~ 1 907.6 MHz
Note	Tested with this model SM-A013M.


4.3 Auxiliary equipments

Type	Model / Part #	S/N	Manufacturer
Adapter (EUT)	EP-TA60JBS	R37N4EP0062HM3	HAEM
Earphone (EUT)	EHS61ASFWE	-	CRESYN
Battery (EUT)	EB-BA013ABY	-	BYD
USB Cable (EUT)	-	-	-
USIM Card	-	-	-
Micro SD Card (64 GB)	Samsung Pro Plus MB-MD64G	-	SAMSUNG
Note PC #1	HP ProBook 470 G2	CND5074WT	HP
Adapter #1	PPP009C	F220881440034736	HP

KCTL

4.4 Test configuration

[Test #1 ~ Test #4_CE / Test #1_RE]



	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT	Power	Adapter(EUT)	USB	1.1	Shield
2		USIM	USIM Card	-	Direct	-
3		Micro SD	Micro SD Card	-	Direct	-
4		Earphone	Earphone(EUT)	-	1.8	Unshield
5	Adapter (EUT)	Power	AC Main	-	Direct	-


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (13) of (40)


KCTL

[Test #2 ~ Test #4_RE]



	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT	USIM	USIM Card	-	Direct	-
2		Micro SD	Micro SD Card	-	Direct	-
3		Earphone	Earphone(EUT)	-	1.8	Unshield

[Test #5_CE, RE]



	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT	USB	Note PC	USB	0.9	Shield
2		USIM	USIM Card	-	Direct	-
3		Micro SD	Micro SD Card	-	Direct	-
4		Earphone	Earphone(EUT)	-	1.8	Unshield
5	Note PC	Power	Adapter #1	-	1.2	Unshield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode		Normal operating
Test #1	CE Test	Camera(Rear) + Charging(w/TA) + FM(Low Ch.)
Test #2		Camera(Front) + Charging(w/TA) + FM(Mid Ch.)
Test #3		FM(High Ch.) + Charging(w/TA)
Test #4		Video + Audio playback from internal memory data + Charging (w/TA)
Test #5		USB Data Communication with PC(from external memory data)
Test #1	RE Test	Camera(Rear) + Charging(w/TA) + FM(Low Ch.)
Test #2		Camera(Front) + FM(Mid Ch.)
Test #3		FM(High Ch.)
Test #4		Video + Audio playback from internal memory data
Test #5		USB Data Communication with PC(from external memory data)

Note 1. It means this device needs to be tested with 3 orientations (x,y and z) and at least the worst case orientation shall be set for final test.

It was determined that Z orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in Z orientation.

5. Summary of test results

5.1 Summary of EMI emission test results

Applied	Test items	Test method	Result
☒	Conducted Emission	ANSI C63.4:2014, Class B FCC Part 15 Subpart B	Pass
☒	Radiated Emission	ANSI C63.4:2014, Class B FCC Part 15 Subpart B	Pass

KCTL

6. Test results

6.1 Conducted Emissions

Test specification	ANSI C63.4:2014, Class B FCC Part 15 Subpart B		
Testing voltage	120 V, 60 Hz		
Test facility	Shielded room (CE#1)		
Date	2020-08-08		
Temperature (°C)	21.9 °C	Humidity (% R.H.)	36.7 % R.H.
Remarks	Pass		

6.1.1 Limits of conducted emissions measurement

Frequency [MHz]	Class A (dB(μ V))		Class B (dB(μ V))	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79	66	66 ~ 56 ¹⁾	56 ~ 46 ¹⁾
0.5 ~ 5	73	60	56	46
5 ~ 30	73	60	60	50

¹⁾ The limit decreases linearly with the logarithm of frequency

6.1.2 Measurement procedure

The measurements were performed in a shielded room. EUT was setup as shown in photograph and placed on a non-metallic table height of 0.8 m above the reference ground plane. The rear of table was located 0.4 m to the vertical conducted plane. EUT was power through the LISN, which was bonded to the ground plane. The LISN power was filtered. Each EUT power lead, except ground (safety) lead was individually connected through a LISN to input power source. EUT signal cables that hung closer than 0.4 m to the Horizontal metal ground 0.3 m ~ 0.4 m long. The power cord was bundles in the center. All peripheral equipment was powered from a sub LISN. The LISN and ISN were positioned 0.8 m from the EUT. Peak and Average detection were used in preliminary testing and Quasi-peak and Average detections were used at final measurement.

6.1.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
EMI TEST RECEIVER	ESCI	100001	R&S	2020.08.22	☒
TWO-LINE V-NETWORK	ENV216	101358	R&S	2020.10.02	☒
TWO-LINE V-NETWORK	ENV216	101352	R&S	2021.04.06	☒

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (19) of (40)



6.1.4 Conducted emissions measurement result

AC Main



Final Result


--- N_A Phase ---										
No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	0.17522	22.9	17.0	10.3	33.2	27.3	64.7	54.7	31.5	27.4
2	0.44271	22.1	15.6	10.2	32.3	25.8	57.0	47.0	24.7	21.2
3	1.33759	28.0	19.9	10.3	38.3	30.2	56.0	46.0	17.7	15.8
4	4.73545	31.0	21.1	10.4	41.4	31.5	56.0	46.0	14.6	14.5
5	5.08735	31.8	22.3	10.4	42.2	32.7	60.0	50.0	17.8	17.3
6	5.94218	32.3	19.8	10.5	42.8	30.3	60.0	50.0	17.2	19.7

--- L_A Phase ---										
No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	0.39771	25.9	21.0	10.2	36.1	31.2	57.9	47.9	21.8	16.7
2	0.48659	23.5	15.4	10.2	33.7	25.6	56.2	46.2	22.5	20.6
3	2.71869	32.4	24.1	10.3	42.7	34.4	56.0	46.0	13.3	11.6
4	2.89504	24.2	15.8	10.3	34.5	26.1	56.0	46.0	21.5	19.9
5	4.33003	28.1	17.3	10.4	38.5	27.7	56.0	46.0	17.5	18.3
6	6.38522	33.5	23.3	10.5	44.0	33.8	60.0	50.0	16.0	16.2
7	6.82266	30.5	20.1	10.5	41.0	30.6	60.0	50.0	19.0	19.4

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (20) of (40)



Final Result


--- N_A Phase ---										
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.17699	22.3	14.5	10.3	32.6	24.8	64.6	54.6	32.0	29.8
2	0.266	23.6	17.9	9.9	33.5	27.8	61.2	51.2	27.7	23.4
3	2.71031	32.5	24.0	10.3	42.8	34.3	56.0	46.0	13.2	11.7
4	4.73219	32.7	22.8	10.4	43.1	33.2	56.0	46.0	12.9	12.8
5	5.87698	33.9	22.0	10.5	44.4	32.5	60.0	50.0	15.6	17.5
6	6.76819	31.7	21.9	10.5	42.2	32.4	60.0	50.0	17.8	17.6

--- L1_A Phase ---										
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.3971	25.6	20.5	10.2	35.8	30.7	57.9	47.9	22.1	17.2
2	0.48578	23.7	15.4	10.2	33.9	25.6	56.2	46.2	22.3	20.6
3	2.65313	34.4	25.2	10.3	44.7	35.5	56.0	46.0	11.3	10.5
4	3.00834	31.2	21.7	10.4	41.6	32.1	56.0	46.0	14.4	13.9
5	5.02855	32.8	23.7	10.4	43.2	34.1	60.0	50.0	16.8	15.9
6	6.32008	33.5	21.9	10.5	44.0	32.4	60.0	50.0	16.0	17.6

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (21) of (40)



Final Result

--- N_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c. f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.48429	23.5	15.2	10.2	33.7	25.4	56.3	46.3	22.6	20.9
2	3.00636	31.5	22.1	10.3	41.8	32.4	56.0	46.0	14.2	13.6
3	5.07796	32.4	23.1	10.4	42.8	33.5	60.0	50.0	17.2	16.5
4	5.92294	34.4	22.9	10.5	44.9	33.4	60.0	50.0	15.1	16.6


--- L1_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c. f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.17698	22.2	14.4	10.3	32.5	24.7	64.6	54.6	32.1	29.9
2	0.39462	25.7	20.7	10.2	35.9	30.9	58.0	48.0	22.1	17.1
3	0.43453	21.1	13.5	10.2	31.3	23.7	57.2	47.2	25.9	23.5
4	2.69754	34.2	25.1	10.3	44.5	35.4	56.0	46.0	11.5	10.6
5	4.33339	30.8	20.6	10.4	41.2	31.0	56.0	46.0	14.8	15.0
6	4.68523	33.4	23.8	10.4	43.8	34.2	56.0	46.0	12.2	11.8
7	5.57168	33.9	23.1	10.5	44.4	33.6	60.0	50.0	15.6	16.4
8	6.27585	33.4	21.4	10.5	43.9	31.9	60.0	50.0	16.1	18.1

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (22) of (40)



Final Result

--- N_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	0.26619	23.2	17.4	9.9	33.1	27.3	61.2	51.2	28.1	23.9
2	0.47727	22.5	14.7	10.2	32.7	24.9	56.4	46.4	23.7	21.5
3	2.60703	33.6	24.6	10.3	43.9	34.9	56.0	46.0	12.1	11.1
4	5.0826	33.2	23.4	10.4	43.6	33.8	60.0	50.0	16.4	16.2
5	6.23098	32.0	19.9	10.5	42.5	30.4	60.0	50.0	17.5	19.6


--- L1_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB]	Result QP [dB(μV)]	Result CAV [dB(μV)]	Limit QP [dB(μV)]	Limit AV [dB(μV)]	Margin QP [dB]	Margin CAV [dB]
1	0.39348	25.2	19.5	10.2	35.4	29.7	58.0	48.0	22.6	18.3
2	0.43688	21.3	14.8	10.2	31.5	25.0	57.1	47.1	25.6	22.1
3	2.69886	34.1	24.9	10.3	44.4	35.2	56.0	46.0	11.6	10.8
4	2.96362	31.9	22.6	10.3	42.2	32.9	56.0	46.0	13.8	13.1
5	4.73348	33.0	23.1	10.4	43.4	33.5	56.0	46.0	12.6	12.5
6	5.42702	32.0	22.3	10.5	42.5	32.8	60.0	50.0	17.5	17.2
7	5.8963	31.1	21.5	10.5	41.6	32.0	60.0	50.0	18.4	18.0

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (23) of (40)



Final Result

--- N Phase ---

No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.15316	42.1	27.5	9.8	51.9	37.3	65.8	55.8	13.9	18.5
2	0.16034	41.4	26.9	10.0	51.4	36.9	65.4	55.4	14.0	18.5
3	0.18094	38.6	23.3	10.0	48.6	33.3	64.4	54.4	15.8	21.1
4	0.2057	35.8	20.5	9.8	45.6	30.3	63.4	53.4	17.8	23.1
5	0.70927	14.0	6.2	9.8	23.8	16.0	56.0	46.0	32.2	30.0
6	2.54575	14.5	8.0	9.7	24.2	17.7	56.0	46.0	31.8	28.3
7	14.27323	12.4	6.7	9.9	22.3	16.6	60.0	50.0	37.7	33.4

--- L1 Phase ---

No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.49954	21.7	15.3	9.8	31.5	25.1	56.0	46.0	24.5	20.9
2	1.31567	10.5	2.3	9.7	20.2	12.0	56.0	46.0	35.8	34.0
3	5.23324	13.7	8.1	9.7	23.4	17.8	60.0	50.0	36.6	32.2
4	16.5202	21.5	14.5	9.9	31.4	24.4	60.0	50.0	28.6	25.6
5	18.2949	18.6	12.8	10.0	28.6	22.8	60.0	50.0	31.4	27.2

6.2 Radiated Emission

Test specification	ANSI C63.4:2014, Class B FCC Part 15 Subpart B		
Testing voltage	120 V, 60 Hz		
Test facility	10 m Chamber (4F)		
Test distance	3 m		
Date	2020-08-08		
Temperature (°C)	21.4 °C	Humidity (% R.H.)	37.2 % R.H.
Remarks	Pass		

6.2.1 Limits of radiated emission measurement

Frequency [MHz]	Class A (dB(μ V/m)) @ 10 m	Class B (dB(μ V/m)) @ 3 m
30-88	39	40
88-216	43.5	43.5
216-960	46.4	46
Above 960	49.5	54

Note- Alternative standard: CISPR, Pub. 22

6.2.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane.

Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.2.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
EMI TEST RECEIVER	ESR7	101078	R&S	2020.08.22	☑
Bilog Antenna	CBL 6112D	55545	TESEQ	2022.04.24	☑
AMPLIFIER	310N	293004	SONOMA	2020.08.22	☑
ATTENUATOR	8491B-6dB	MY39271060	KEYSIGHT	-	☑
Antenna Mast	MA4640-XP-ET	-	Innco Systems	-	☑
Turn Table	TT 3.0-3t	-	MATURO	-	☑
DOUBLE RIDGED HORN ANTENNA	3117-PA	00161083	ETS-LINDGREN	2020.09.18	☑
Horn antenna	3116	00086635	ETS-LINDGREN	2021.05.12	☑
AMPLIFIER	JS44-18004000-33-8P	2000996	L-3Narda-MITEQ	2021.01.22	☑
Spectrum Analyzer	FSV40	100988	R&S	2021.01.03	☑

6.2.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 6 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G = Amplifier Gain

6 dB Att = 6 dB Attenuator

If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 6 dB, A.G 35 dB

The result is $30 + 12 + 5 + 6 - 35 = 18 \text{ dB } (\mu\text{V/m})$

Bilog Antenna and ATTENUATOR (6 dB) were calibrated together.

AV = CAV : Abbreviation of CISPR Average

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (26) of (40)



6.2.5 Radiated emission measurement result

30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	46.442	V	35.9	-14.1	21.8	40.0	18.2	142.0	114.0
2	62.051	V	37.1	-16.7	20.4	40.0	19.6	205.0	5.0
3	90.413	H	34.8	-13.5	21.3	43.5	22.2	363.0	68.0
4	176.751	H	32.0	-11.5	20.5	43.5	23.0	288.0	165.0
5	326.541	V	35.4	-4.8	30.6	46.0	15.4	227.0	319.0
6	384.041	H	29.2	-2.6	26.6	46.0	19.4	117.0	86.0
7	638.069	V	18.0	4.0	22.0	46.0	24.0	311.0	255.0
8	917.911	V	15.0	8.8	23.8	46.0	22.2	228.0	61.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (27) of (40)



1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	7437.371	V	51.2	36.8	-4.2	47.0	32.6	74.0	54.0	27.0	21.4	220.0	19.0
2	9978.148	V	46.9	32.8	1.1	48.0	33.9	74.0	54.0	26.0	20.1	307.0	352.0
3	13355.370	H	48.2	33.7	1.7	49.9	35.4	74.0	54.0	24.1	18.6	175.0	166.0
4	15760.990	V	48.5	33.4	3.2	51.7	36.6	74.0	54.0	22.3	17.4	396.0	32.0
5	16957.000	H	46.2	32.8	7.4	53.6	40.2	74.0	54.0	20.4	13.8	112.0	297.0
6	17956.650	V	43.4	28.6	9.5	52.9	38.1	74.0	54.0	21.1	15.9	300.0	14.0




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (28) of (40)



18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	19612.280	H	51.2	34.6	2.5	53.7	37.1	74.0	54.0	20.3	16.9	277.0	64.0
2	20898.140	H	51.3	35.9	3.2	54.5	39.1	74.0	54.0	19.5	14.9	101.0	308.0
3	23475.270	V	50.0	34.5	3.8	53.8	38.3	74.0	54.0	20.2	15.7	227.0	244.0
4	25860.390	V	47.2	32.3	7.2	54.4	39.5	74.0	54.0	19.6	14.5	337.0	61.0
5	27218.260	H	46.2	31.2	8.2	54.4	39.4	74.0	54.0	19.6	14.6	392.0	334.0
6	27551.880	H	46.9	33.4	8.0	54.9	41.4	74.0	54.0	19.1	12.6	102.0	108.0

KCTL


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (29) of (40)

KCTL

30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	48.309	V	31.0	-14.9	16.1	40.0	23.9	272.0	66.0
2	69.155	H	31.9	-16.4	15.5	40.0	24.5	224.0	297.0
3	74.042	H	35.2	-16.2	19.0	40.0	21.0	308.0	311.0
4	159.452	H	27.2	-10.7	16.5	43.5	27.0	304.0	168.0
5	753.341	H	16.4	5.4	21.8	46.0	24.2	101.0	240.2
6	790.714	V	15.9	6.5	22.4	46.0	23.6	277.0	344.0
7	877.416	H	15.2	8.0	23.2	46.0	22.8	228.0	31.0
8	918.154	V	14.5	8.8	23.3	46.0	22.7	180.0	124.0

KCTL


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (30) of (40)



1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	5673.533	V	50.1	34.8	-5.1	45.0	29.7	74.0	54.0	29.0	24.3	110.0	226.0
2	7069.303	H	52.0	38.1	-4.4	47.6	33.7	74.0	54.0	26.4	20.3	337.0	352.0
3	10769.540	V	49.8	34.7	0.4	50.2	35.1	74.0	54.0	23.8	18.9	375.0	66.0
4	14945.800	H	49.0	34.7	2.1	51.1	36.8	74.0	54.0	22.9	17.2	277.0	65.0
5	17034.350	V	45.0	30.2	7.5	52.5	37.7	74.0	54.0	21.5	16.3	147.0	256.0
6	17537.570	H	45.2	31.2	7.8	53.0	39.0	74.0	54.0	21.0	15.0	228.0	34.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (31) of (40)



18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	21243.760	H	50.2	36.2	3.2	53.4	39.4	74.0	54.0	20.6	14.6	104.0	22.0
2	22808.040	H	51.0	36.8	3.3	54.3	40.1	74.0	54.0	19.7	13.9	377.0	54.0
3	23545.480	V	50.6	35.9	3.9	54.5	39.8	74.0	54.0	19.5	14.2	147.0	277.0
4	26053.000	H	48.0	33.3	7.2	55.2	40.5	74.0	54.0	18.8	13.5	144.0	196.0
5	26779.040	V	46.2	31.2	7.9	54.1	39.1	74.0	54.0	19.9	14.9	247.0	46.0
6	27844.090	V	45.9	32.5	8.2	54.1	40.7	74.0	54.0	19.9	13.3	378.0	58.0




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (32) of (40)



30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	48.188	V	31.9	-14.8	17.1	40.0	22.9	337.0	294.0
2	72.195	H	38.1	-16.3	21.8	40.0	18.2	301.0	124.0
3	73.412	H	39.4	-16.2	23.2	40.0	16.8	117.0	216.0
4	159.495	H	26.4	-10.7	15.7	43.5	27.8	334.0	168.0
5	318.924	H	25.2	-5.0	20.2	46.0	25.8	229.0	20.0
6	404.420	V	19.3	-1.8	17.5	46.0	28.5	150.0	32.0
7	638.064	V	17.5	4.0	21.5	46.0	24.5	334.0	36.0
8	902.428	V	14.9	8.4	23.3	46.0	22.7	116.0	256.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (33) of (40)

KCTL

1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	6556.727	V	49.6	36.8	-4.1	45.5	32.7	74.0	54.0	28.5	21.3	224.0	19.0
2	7444.171	H	51.9	32.8	-4.1	47.8	28.7	74.0	54.0	26.2	25.3	177.0	94.0
3	12767.990	V	48.6	35.7	1.3	49.9	37.0	74.0	54.0	24.1	17.0	120.0	303.0
4	15566.330	V	49.6	35.2	2.7	52.3	37.9	74.0	54.0	21.7	16.1	337.0	96.0
5	16965.500	H	45.8	30.7	7.4	53.2	38.1	74.0	54.0	20.8	15.9	312.0	168.0
6	17464.470	V	45.2	31.2	7.5	52.7	38.7	74.0	54.0	21.3	15.3	228.0	89.0

KCTL


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (34) of (40)



18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	20877.140	H	50.4	35.2	3.2	53.6	38.4	74.0	54.0	20.4	15.6	120.0	3.0
2	21414.750	V	51.2	36.8	3.1	54.3	39.9	74.0	54.0	19.7	14.1	117.0	251.0
3	22407.820	V	50.9	36.7	3.4	54.3	40.1	74.0	54.0	19.7	13.9	319.0	22.0
4	25901.800	V	48.3	32.7	7.1	55.4	39.8	74.0	54.0	18.6	14.2	227.0	356.0
5	27533.280	V	46.8	30.6	8.0	54.8	38.6	74.0	54.0	19.2	15.4	301.0	88.0
6	27784.690	H	46.2	32.0	8.1	54.3	40.1	74.0	54.0	19.7	13.9	227.0	3.0




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (35) of (40)

KCTL

30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	44.642	V	31.6	-13.2	18.4	40.0	21.6	388.0	264.0
2	52.352	V	33.2	-16.1	17.1	40.0	22.9	111.0	284.0
3	55.091	V	37.0	-16.6	20.4	40.0	19.6	204.0	288.0
4	72.801	H	39.5	-16.3	23.2	40.0	16.8	225.0	51.0
5	608.601	H	16.3	3.8	20.1	46.0	25.9	365.0	19.0
6	819.095	V	16.1	7.1	23.2	46.0	22.8	322.0	44.0
7	841.024	H	16.0	7.5	23.5	46.0	22.5	224.0	261.0
8	892.352	H	15.6	8.2	23.8	46.0	22.2	121.0	314.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (36) of (40)

KCTL

1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	7302.214	H	51.2	37.8	-4.3	46.9	33.5	74.0	54.0	27.1	20.5	130.0	52.0
2	12319.170	H	48.9	34.5	0.6	49.5	35.1	74.0	54.0	24.5	18.9	166.0	94.0
3	14909.240	V	50.2	34.8	2.0	52.2	36.8	74.0	54.0	21.8	17.2	279.0	43.0
4	15342.760	H	50.0	34.2	2.3	52.3	36.5	74.0	54.0	21.7	17.5	386.0	68.0
5	17038.600	V	45.2	29.6	7.6	52.8	37.2	74.0	54.0	21.2	16.8	272.0	196.0
6	17868.240	V	44.2	29.5	9.1	53.3	38.6	74.0	54.0	20.7	15.4	200.0	311.0

KCTL


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (37) of (40)

KCTL

18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(μV)]	Reading CAV [dB(μV)]	c.f [dB(1/m)]	Result PK [dB(μV/m)]	Result CAV [dB(μV/m)]	Limit PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	19732.290	V	51.2	36.9	2.5	53.7	39.4	74.0	54.0	20.3	14.6	128.0	224.0
2	23159.060	V	50.2	34.9	3.7	53.9	38.6	74.0	54.0	20.1	15.4	188.0	359.0
3	25889.200	H	47.9	33.8	7.1	55.0	40.9	74.0	54.0	19.0	13.1	320.0	352.0
4	26197.010	V	47.2	33.8	7.3	54.5	41.1	74.0	54.0	19.5	12.9	224.0	46.0
5	27242.260	H	46.9	32.8	8.2	55.1	41.0	74.0	54.0	18.9	13.0	207.0	221.0
6	27364.670	V	46.0	32.0	8.2	54.2	40.2	74.0	54.0	19.8	13.8	209.0	235.0

KCTL


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (38) of (40)

KCTL

30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	32.132	V	39.5	-6.4	33.1	40.0	6.9	107.0	55.0
2	36.443	V	39.3	-8.9	30.4	40.0	9.6	120.0	188.0
3	44.311	V	37.9	-13.0	24.9	40.0	15.1	301.0	299.0
4	175.944	H	34.9	-11.5	23.4	43.5	20.1	301.0	59.0
5	219.043	V	37.8	-9.6	28.2	46.0	17.8	120.0	8.0
6	425.043	H	26.0	-1.2	24.8	46.0	21.2	304.0	559.0
7	796.664	V	30.7	6.7	37.4	46.0	8.6	140.0	352.0
8	948.345	H	14.5	9.5	24.0	46.0	22.0	224.0	38.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (39) of (40)



1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	7916.795	V	50.9	36.9	-3.3	47.6	33.6	74.0	54.0	26.4	20.4	170.0	19.0
2	11180.110	H	49.6	34.7	0.2	49.8	34.9	74.0	54.0	24.2	19.1	120.0	335.0
3	14468.070	V	48.6	33.2	2.0	50.6	35.2	74.0	54.0	23.4	18.8	399.0	316.0
4	16222.560	V	47.2	34.6	4.8	52.0	39.4	74.0	54.0	22.0	14.6	277.0	163.0
5	16961.250	V	46.2	32.1	7.4	53.6	39.5	74.0	54.0	20.4	14.5	200.0	81.0
6	17569.030	H	45.1	31.2	7.9	53.0	39.1	74.0	54.0	21.0	14.9	178.0	22.0




KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
Tel: 82-31-285-0894 Fax: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR20-SEF0123
Page (40) of (40)



18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	20711.530	V	51.4	36.2	2.7	54.1	38.9	74.0	54.0	19.9	15.1	100.0	11.0
2	21203.560	V	51.2	36.8	3.1	54.3	39.9	74.0	54.0	19.7	14.1	110.0	84.0
3	23487.870	H	50.6	34.8	3.9	54.5	38.7	74.0	54.0	19.5	15.3	163.0	201.0
4	23735.090	H	50.4	36.9	4.2	54.6	41.1	74.0	54.0	19.4	12.9	377.0	352.0
5	25838.190	V	47.5	33.6	7.2	54.7	40.8	74.0	54.0	19.3	13.2	248.0	356.0
6	26246.210	H	47.9	33.8	7.3	55.2	41.1	74.0	54.0	18.8	12.9	370.0	341.0

