



TEST REPORT

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR19-SRF0122-B Page (1) of (56)			
1. Client ◦ Name : Samsung Electronics Co., Ltd. ◦ Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea ◦ Date of Receipt : 2019-07-25 2. Use of Report : - 3. Name of Product and Model : Mobile phone / SC-02M, SCV46 4. Manufacturer and Country of Origin : SAMSUNG ELECTRONICS VIETNAM CO.,LTD. / Vietnam 5. FCC ID : A3LSMA102JPN 6. Date of Test : 2019-07-30 to 2019-08-21 7. Test Standards : FCC Part 2 FCC Part 22 Subpart H FCC Part 24 Subpart E 8. Test Results : Refer to the test result in the test report				
Affirmation	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; padding: 5px;"> Tested by Name : Euijung Kim (Signature) </td> <td style="width: 50%; padding: 5px;"> Technical Manager Name : Seungyong Kim (Signature) </td> </tr> </table>		Tested by Name : Euijung Kim (Signature)	Technical Manager Name : Seungyong Kim (Signature)
Tested by Name : Euijung Kim (Signature)	Technical Manager Name : Seungyong Kim (Signature)			
2019-09-09 KCTL Inc. As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.				

Report revision history

Date	Revision	Page No
2019-08-23	Initial report	-
2019-08-30	Updated a typo	6
2019-09-09	Updated information for LTE Band 12, 17	4, 6

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.

KCTL

CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Accessory information	5
2.2.	Frequency/channel operations.....	6
3.	Maximum ERP/EIRP power	6
4.	Summary of tests	7
5.	Measurement uncertainty	8
6.	Measurement results explanation example	9
7.	Test results	10
7.1.	Conducted output power.....	10
7.2.	99% Occupied Bandwidth & 26dB Bandwidth	12
7.3.	Spurious Emissions at Antenna Terminal.....	21
7.4.	Band Edge Emissions at Antenna Terminal	26
7.5.	Peak to Average Power Ratio (PAPR)	31
7.6.	Frequency stability	33
7.7.	Radiated Power (ERP/EIRP)	38
7.8.	Radiated Spurious Emissions	42
8.	Measurement equipment	56

1. General information

Client : Samsung Electronics Co., Ltd.
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Manufacturer : SAMSUNG ELECTRONICS VIETNAM CO.,LTD.
Address : Kcn Yen Binh1, huyen pho Yen Tinh Thai Nguyen Vietnam
Laboratory : KCTL Inc.
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
VCCI Registration No. : R-3327, G-198, C-3706, T-1849
Industry Canada Registration No. : 8035A
KOLAS No.: KT231

2. Device information

Equipment under test : Mobile Phone
Model : SC-02M, SCV46
Difference in model name : Model SCV46 is electrically identical to model SC-02M. Two model numbers are allocated for marketing and logistic purposes only.
Frequency range : Bluetooth(BDR/EDR/BLE)_2 402 MHz ~ 2 480 MHz
2 412 MHz ~ 2 462 MHz (802.11b/g/n_HT20)
UNII-1: 5 180 MHz ~ 5 240 MHz (802.11a/n_HT20/ac_VHT20)
UNII-1: 5 190 MHz ~ 5 230 MHz (802.11n_HT40/ac_VHT40)
UNII-1: 5 210 MHz (802.11ac_VHT80)
UNII-2A: 5 260 MHz ~ 5 320 MHz (802.11a/n_HT20/ac_VHT20)
UNII-2A: 5 270 MHz ~ 5 310 MHz (802.11n_HT40/ac_VHT40)
UNII-2A: 5 290 MHz (802.11ac_VHT80)
UNII-2C: 5 500 MHz ~ 5 720 MHz (802.11a/n_HT20/ac_VHT20)
UNII-2C: 5 510 MHz ~ 5 710 MHz (802.11n_HT40/ac_VHT40)
UNII-2C: 5 530 MHz ~ 5 690 MHz (802.11ac_VHT80)
UNII-3: 5 745 MHz ~ 5 825 MHz (802.11a/n_HT20/ac_VHT20)
UNII-3: 5 755 MHz ~ 5 795 MHz (802.11n_HT40/ac_VHT40)
UNII-3: 5 775 MHz (802.11ac_VHT80)
NFC_13.56 MHz
LTE Band 12_699.7 MHz ~ 715.3 MHz
LTE Band 17_706.5 MHz ~ 713.5 MHz
LTE Band 5_824.7 MHz ~ 848.3 MHz
LTE Band 26_824.7 MHz ~ 848.3 MHz, 814.7 MHz ~ 823.3 MHz
LTE Band 41_2 498.5 MHz ~ 2 687.5 MHz
WCDMA 850_826.4 MHz ~ 846.6 MHz
GSM 850_824.2 MHz ~ 848.8 MHz

GSM 1900_1 850.2 MHz ~ 1 909.8 MHz

Modulation technique : Bluetooth(BDR/EDR)_GFSK, $\pi/4$ DQPSK, 8DPSK
 Bluetooth(BLE)_GFSK
 WIFI(802.11b/g/n20/n40/ac20/ac40/ac80)_DSSS, OFDM
 NFC_ASK
 LTE_QPSK, 16QAM
 WCDMA_QPSK
 GSM_GMSK, 8-PSK

Number of channels : Bluetooth(BDR/EDR)_79ch / Bluetooth(BLE)_40ch
 11 ch (802.11b/g/n_HT20)_2.4 GHz Band
 UNII-1: 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)
 UNII-2A: 4 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)
 UNII-2C: 12 ch (20 MHz), 6 ch (40 MHz), 3 ch (80 MHz)
 UNII-3: 5 ch (20 MHz), 2 ch (40 MHz), 1 ch (80 MHz)

Power source : DC 3.85 V

Antenna specification : LTE/WCDMA_LDS+SUS Insert Antenna
 WIFI/Bluetooth(BDR/EDR/BLE)_LDS Antenna
 NFC_FPCB Antenna

Antenna gain : WIFI/Bluetooth(BDR/EDR/BLE) : -0.9 dBi
 UNII-1 -3.3 dBi
 UNII-2A -3.7 dBi
 UNII-2C -3.1 dBi
 UNII-3 -4.2 dBi

Software version : N778.001 (SC-02M), YGI.001 (SCV46)

Hardware version : REV1.0

Test device serial No. : Conducted(R38M50A29LK, R38M50A2A8X)
 Radiated(R38M50A2MZY, R38M50A2FSZ, R38M50A2HRK,
 R38M50A2GXJ)

Operation temperature : -30 °C ~ 50 °C

2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
Earphone	Samsung Electronics Co., Ltd.	EHS64ACFWE	-	-
Travel Adapter	Samsung Electronics Co., Ltd.	EP-TA200	-	AC 100-240V 50-60 Hz, 9.0V-1.67A 5.0V-2.0A
Micro USB Data Cable	Samsung Electronics Co., Ltd.	-	-	-

2.2. Frequency/channel operations

This device contains the following capabilities:

WIFI(2.4GHz band 802.11b/g/n(HT20), 5GHz band 802.11a/n(HT20/HT40)/ac(VHT/20/40/80)),

Bluetooth(BDR/EDR/BLE), NFC

LTE Band 12, LTE Band 17, LTE Band 5, LTE Band 26, LTE Band 41,

WCDMA 850, GSM 850, GSM 1900

GSM 850

Ch.	Frequency (MHz)
128	824.2
190	836.6
251	848.8

Table 2.2.1.
GPRS/EDGE

GSM 1900

Ch.	Frequency (MHz)
512	1 850.2
661	1 880.0
810	1 909.8

Table 2.2.2.
GPRS/EDGE

WCDMA 850

Ch.	Frequency (MHz)
4132	826.4
4183	836.6
4233	846.6

Table 2.2.3.
RMC/HSDPA/HSUPA/HSPA+

3. Maximum ERP/EIRP power

GSM 850 / WCDMA 850

Mode	Tx frequency (MHz)	Emission designator	ERP	
			Max. power (dBm)	Max. power (W)
GSM 850 (GPRS)	824.2 ~ 848.8	246KGXW	30.32	1.076
GSM 850 (EDGE)	824.2 ~ 848.8	242KG7W	28.52	0.711
WCDMA 850 (RMC)	826.4 ~ 846.6	4M15F9W	20.97	0.125
WCDMA 850 (HSUPA)	826.4 ~ 846.6	4M15F9W	19.57	0.091

GSM 1900

Mode	Tx frequency (MHz)	Emission designator	EIRP	
			Max. power (dBm)	Max. power (W)
GSM 1900 (GPRS)	1 850.2 ~ 1 909.8	248KGXW	28.15	0.653
GSM 1900 (EDGE)	1 850.2 ~ 1 909.8	248KG7W	26.32	0.429

4. Summary of tests

FCC Part Section(s)	Parameter	Test Limit	Test Condition	Test results
2.1046 22.913(a)(5) 24.232(c)	Conducted Output Power	N/A	Conducted	Pass
2.1049	Occupied Bandwidth & 26 dB Bandwidth	N/A		Pass
2.1051 22.917(a) 24.238(a)	Band Edge Emissions at Antenna Terminal	>43 + 10Log ₁₀ (P) dB at Band Edge and for all out-of-band emissions		Pass
	Spurious Emissions at Antenna Terminal			Pass
24.232(d)	Peak to Average Power Ratio	< 13 dB		Pass
2.1055 22.355 24.235	Frequency stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24)		Pass
22.913(a)(5) 24.232(c)	Effective Radiated Power & Equivalent Isotropic Radiated Power	< 7 Watts max. ERP (Part 22) < 2 Watts max. EIRP (Part 24)	Radiated	Pass
2.1053 22.917(a) 24.238(a)	Radiated Spurious Emissions	>43 + 10Log ₁₀ (P) dB for all out-of-band emissions		Pass

Notes:

- All modes of operation were investigated and the worst case emissions are reported with the EUT positioning, modulations and paging service configurations in the test data.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. All final radiated testing was performed with the EUT in worst case orientation.
- The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.26-2015
 - ANSI/TIA-603-E-2016
 - KDB 971168 D01 v03r01

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ($\pm$)	
Conducted RF power	1.76 dB	
Conducted spurious emissions	4.03 dB	
Radiated spurious emissions	9 kHz ~ 30 MHz	2.28 dB
	30 MHz ~ 1 GHz	3.68 dB
	Above 1 GHz	5.72 dB

KCTL

6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	16.56	11 000	19.46
50	16.61	12 000	19.37
100	16.67	13 000	19.74
200	16.80	14 000	20.47
300	16.95	15 000	21.31
400	17.03	16 000	20.54
500	17.06	17 000	19.84
600	17.15	18 000	20.00
700	17.21	19 000	19.93
800	17.17	20 000	20.17
900	17.27	21 000	20.31
1 000	17.09	22 000	20.42
2 000	17.71	23 000	20.28
3 000	17.90	24 000	20.53
4 000	17.96	25 000	20.39
5 000	18.06	26 000	19.97
6 000	18.06	26 500	20.21
7 000	18.24	27 000	19.67
8 000	18.55	28 000	20.13
9 000	18.71	29 000	20.62
10 000	19.35	30 000	20.98


Note.

Offset(dB) = RF cable loss(dB) + Divider (dB) + Attenuator(dB)

7. Test results

7.1. Conducted output power

Test setup



Test procedure

971168 D01 v03r01 – Section 5.2

ANSI C63.26-2015 – Section 5.2.4.2

CFR 47, - Section §2.1046

Test settings

When an average power meter is used to perform RF output power measurements, the fundamental condition that measurement be performed only over durations of active transmissions at maximum output power level applies. Thus, an average power meter can always be used to perform the measurement when the EUT can be configured to transmit continuously.

If the EUT cannot be configured to transmit continuously (i.e., burst duty cycle < 98%), then the following options can be implemented to facilitate measurement of the average power with an average power meter:

- a) A gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only during active transmission bursts at maximum output power levels.
- b) A conventional average power meter with no signal gating capability can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than or equal to $\pm 2\%$) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $[10\log (1/\text{duty cycle})]$. See 5.2.4.3.4 for guidance with respect to measuring the transmitter duty cycle.

See item r) of 4.1 for more information regarding power meter functional requirements and limitations, and consult the instrumentation-specific application literature for proper set-up and use.

Notes:

1. HSPA+

Since 16QAM is not used for uplink, the uplink category and release is same as HSUPA.
 Therefore, the RF conducted power is not measured.


Test results

Maximum Burst-Average Output Power (dBm)										
Test Band	Channel	GSM	GPRS				EDGE			
		Voice	1Tx	2Tx	3Tx	4Tx	5Tx	6Tx	7Tx	8Tx
GSM850	Low	32.94	32.76	30.76	29.60	28.20	27.20	25.32	23.40	22.30
	Middle	33.12	32.95	31.18	29.70	28.30	27.57	25.72	23.60	22.40
	High	33.11	32.86	31.08	29.70	28.20	27.46	25.51	23.50	22.30
GSM1900	Low	29.81	29.80	27.09	25.90	24.40	25.41	23.06	22.10	20.90
	Middle	29.60	29.61	27.20	25.80	24.20	25.46	23.22	22.20	21.00
	High	29.60	29.59	27.06	25.70	24.20	25.48	23.29	22.30	21.10

Test Band	Test mode	Average Conducted Power (dBm)			3GPP MPR (dB)
		Frequency (MHz)			
		Low	Middle	High	
WCDMA 850	RMC	24.66	24.63	24.72	0
	HSDPA-Subtest 1	23.69	23.63	23.71	0
	HSDPA-Subtest 2	23.45	23.45	23.30	0.5
	HSDPA-Subtest 3	23.50	23.48	23.28	0.5
	HSDPA-Subtest 4	23.50	23.50	23.32	0
	HSUPA-Subtest 1	19.82	19.78	19.90	2
	HSUPA-Subtest 2	18.83	18.90	18.88	1
	HSUPA-Subtest 3	19.72	19.65	19.78	2
	HSUPA-Subtest 4	18.89	18.96	18.98	0
	HSUPA-Subtest 5	20.96	20.91	20.93	0
	DC-HSDPA-Subtest 1	23.57	23.62	23.45	0
	DC-HSDPA-Subtest 2	21.82	21.92	21.63	0.5
	DC-HSDPA-Subtest 3	21.68	21.77	21.79	0.5
	DC-HSDPA-Subtest 4	21.71	21.76	21.68	0

7.2. 99% Occupied Bandwidth & 26dB Bandwidth

Test setup



Limit

According to §2.1049, the occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

Test procedure

971168 D01 v03r01 – Section 4.2 and 4.3

ANSI C63.26-2015 – Section 5.4.3 and 5.4.4

Test settings

◆ 26dB Bandwidth

- c) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- d) The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- e) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
- d) The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target “-X dB” requirement, i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
- e) Set spectrum analyzer detection mode to peak, and the trace mode to max hold.
- f) Determine the reference value by either of the following:
 - 1) Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
 - 2) Set the EUT to transmit an unmodulated carrier. Set the spectrum analyzer marker to the level of the carrier.
- g) Determine the “-X dB amplitude” as equal to (Reference Value - X). Alternatively, this calculation can be performed on the spectrum analyzer using the delta-marker measurement function.
- h) If the reference value was determined using an unmodulated carrier, turn the EUT modulation on, then either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise the trace from step f) shall be used for step i).

- i) Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB amplitude” determined in step f). If a marker is below this “-X dB amplitude” value it should be as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- j) The spectral envelope can cross the “-X dB amplitude” at multiple points. The lowest or highest frequency shall be selected as the frequencies that are the farthest away from the center frequency at which the spectral envelope crosses the “-X dB amplitude.”
- k) The OBW shall be reported by providing plot(s) of the measuring instrument display, to include markers depicting the relevant frequency and amplitude information (e.g., marker table). The frequency and amplitude axis and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

◆ 99% Occupied Bandwidth

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times \text{OBW}$ is sufficient).
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
- d) Set the detection mode to peak, and the trace mode to max-hold.
- e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.
- f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0122-B

Page (14) of (56)

KCTL**Test results**

Test mode		Frequency (MHz)	26 dB bandwidth (MHz)	99 % bandwidth (MHz)
GSM 850	GPRS	824.2	0.316	0.246
		836.6	0.318	0.242
		848.8	0.318	0.246
	EDGE	824.2	0.312	0.242
		836.6	0.308	0.242
		848.8	0.304	0.240
GSM 1900	GPRS	1 850.2	0.316	0.248
		1 880.0	0.316	0.246
		1 909.8	0.318	0.244
	EDGE	1 850.2	0.316	0.248
		1 880.0	0.314	0.244
		1 909.8	0.322	0.244
WCDMA 850	RMC	826.4	4.74	4.14
		836.6	4.72	4.12
		846.6	4.71	4.12
	HSUPA	826.4	4.74	4.15
		836.6	4.77	4.14
		846.6	4.74	4.14

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0122-B


Page (15) of (56)




26dB Bandwidth

Test mode: GSM 850


GPRS / Low ch.




EDGE / Low ch.




GPRS / Mid ch.




EDGE / Mid ch.



GPRS / High ch.



EDGE / High ch.



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0122-B

Page (16) of (56)




Test mode: GSM 1900


GPRS / Low ch.




EDGE / Low ch.




GPRS / Mid ch.




EDGE / Mid ch.



GPRS / High ch.



EDGE / High ch.



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0122-B

Page (17) of (56)




Test mode: WCDMA 850


RMC / Low ch.




HSUPA / Low ch.




RMC / Mid ch.




HSUPA / Mid ch.



RMC / High ch.



HSUPA / High ch.



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0122-B


Page (18) of (56)




99% Occupied Bandwidth

Test mode: GSM 850


GPRS / Low ch.




EDGE / Low ch.




GPRS / Mid ch.




EDGE / Mid ch.



GPRS / High ch.



EDGE / High ch.



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0122-B

Page (19) of (56)




Test mode: GSM 1900


GPRS / Low ch.




EDGE / Low ch.




GPRS / Mid ch.




EDGE / Mid ch.



GPRS / High ch.



EDGE / High ch.



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0122-B

Page (20) of (56)




Test mode: WCDMA 850


RMC / Low ch.




HSUPA / Low ch.




RMC / Mid ch.




HSUPA / Mid ch.



RMC / High ch.



HSUPA / High ch.



This test report shall not be reproduced, except in full, without the written approval

KCTL-TIR001-003/2