

MEASUREMENT REPORT

FCC Part 15B

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

05/13 - 6/1/2021

Test Site/Location:

PCTEST Lab. Yongin-Si, Gyeonggi-do, South Korea

Test Report Serial No.:

1K2105110019-09.A3L

FCC ID:

A3LSMA127FN

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-A127F/DSN

EUT Type:

Portable Handset

FCC Classification:

Part 15 Class B Computing Device Peripheral (JBP)

FCC Rule Part(s):

FCC Part 15 Subpart B

Test Procedure(s):

ANSI C63.4-2014

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.4-2014 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Prepared by



Reviewed by

FCC ID: A3LSMA127FN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 1 of 28

TABLE OF CONTENTS

1.0	Introduction	3
1.1	Scope.....	3
1.2	PCTEST Test Location	3
1.3	Test Facility / Accreditations	3
2.0	PRODUCT INFORMATION	3
2.1	Equipment Description.....	4
2.2	Device Capabilities	4
2.3	Test Configuration	4
2.4	EMI Suppression Device(s)/Modifications.....	4
3.0	DESCRIPTION OF TESTS	5
3.1	Evaluation Procedure.....	5
3.2	AC Line Conducted Emissions	5
3.3	Radiated Emissions	6
3.4	Environmental Conditions	6
4.0	SAMPLE CALCULATIONS	7
4.1	Conducted Emission Measurement Sample Calculation	7
4.2	Radiated Emission Measurement Sample Calculation	7
5.0	Measurement Uncertainty	8
6.0	TEST EQUIPMENT CALIBRATION DATA.....	9
7.0	TEST DATA	10
7.1	Summary	10
7.2	Test Support Equipment	10
7.3	Radiated Measurement Data	11
7.4	Line Conducted Measurement Data	16
8.0	CONCLUSION	28

FCC ID: A3LSMA127FN	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 2 of 28

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST facility located at 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954, South Korea. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in 13, Heungdeok 1-ro, Giheung-gu, Yongin-si, Gyeonggi-do, 16954 South Korea.

- PCTEST is an ISO 17025-2017 accredited test facility under the National Voluntary Laboratory Accreditation Program (NVLAP) with Certificate number 600143-0 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada (ISED) rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- PCTEST facility is a registered (26168) test laboratory with the site description on file with ISED.

FCC ID: A3LSMA127FN	 Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset	Page 3 of 28	

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA127FN**. The test data contained in this report pertains only to the emissions due to the digital circuitry of the EUT.

Test Device Serial No.: 2866M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850 WCDMA/HSPA, Multi-band LTE, WLAN 802.11b/g/n, Bluetooth (1x, EDR, LE), NFC

2.3 Test Configuration

The EUT was tested in the following configurations for conducted emissions:

Conducted Test Configuration 1: Camera on (rear) + Charging (with travel adapter)
 Conducted Test Configuration 2: Camera on (front) + Charging (with travel adapter)
 Conducted Test Configuration 3: Charging (with travel adapter)
 Conducted Test Configuration 4: Video + Audio playback from internal memory data + Charging (with travel adapter)
 Conducted Test Configuration 5: USB Data Communication with PC (from external memory data)

The EUT was tested in the following configurations for radiated emissions:

Radiated Test Configuration 1: Camera on (rear) + Charging (with travel adapter)
 Radiated Test Configuration 2: USB Data Communication with PC (from external memory data)
 Radiated Test Configuration 3: Camera on (front) + USB OTG (with USB gender: mouse or keyboard)

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

For more information please see Section 7.0 for test data and the test setup photos document for the test setup photographs.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMA127FN	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset	Page 4 of 28	

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2014) was used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by SY cooperation RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.4. The EMI Receiver mode of the R&S ESW was used to perform AC line conducted emissions testing. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.20.01.

FCC ID: A3LSMA127FN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 5 of 28

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Innco is placed on top of the turn table. For measurements above 1GHz, an additional Innco table is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMA127FN	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 6 of 28

4.0 SAMPLE CALCULATIONS

4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

Class B limit = 60.0 dB μ V (Quasi-peak limit)
 Reading = - 57.8 dBm (calibrated quasi-peak level)
 Convert to dB μ V = - 57.8 + 107 = 49.2 dB μ V

 Margin = 49.2 - 60.0 = - 10.8 dB
 = **10.8 dB below limit**

4.2 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz

Class B limit = 100 μ V/m = 40.0 dB μ V/m
 Reading = - 76.0 dBm (calibrated level)
 Convert to dB μ V = - 76.0 + 107 = 31.0 dB μ V
 Antenna Factor + Cable Loss = 5.8 dB/m
 Total = 36.8 dB μ V/m

 Margin = 36.8 - 40.0 = - 3.2 dB
 = **3.2 dB below limit**

Note:

$$\text{Level [dB}\mu\text{V]} = 20 \log_{10} (\text{Level } [\mu\text{V/m}])$$

$$\text{Level [dB}\mu\text{V]} = \text{Level [dBm]} + 107$$

FCC ID: A3LSMA127FN	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 7 of 28

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Line Conducted Disturbance	3.07
Radiated Disturbance (<1GHz)	3.01
Radiated Disturbance (>1GHz)	5.56

FCC ID: A3LSMA127FN	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 8 of 28

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9030A	PXA Signal Analyzer	6/29/2020	Annual	6/28/2021	MY49432391
Anritsu	S820E	Cable and Antenna Analyzer	6/29/2020	Annual	6/28/2021	1839097
Anritsu	MA24106A	USB Power Sensor	6/29/2020	Annual	6/28/2021	1244512
Com-Power	AL-130R	Active Loop Antenna	10/29/2020	Biennial	10/28/2022	10160045
Schwarzbeck	VULB9162	Broadband TRILOG Antenna	7/9/2019	Biennial	7/8/2021	9162-217
Sunol Sciences	DRH-118	Horn Antenna	8/9/2019	Biennial	8/8/2021	A102416-1
Keysight Technologies	N9030B	PXA Signal Analyzer	5/1/2021	Annual	4/30/2022	MY57142018
Mini-Circuits	ZHDC-16-63-S+	Coupler	6/29/2020	Annual	6/28/2021	F709401716
Mini-Circuits	ZNDC-18-2G-S+	Coupler	6/29/2020	Annual	6/28/2021	F280401542
Mini-Circuits	BW-N10W5+	Attenuator	6/29/2020	Annual	6/28/2021	1607
Mini-Circuits	BW-N10W5+	Attenuator	6/29/2020	Annual	6/28/2021	1607
Rohde & Schwarz	TS-PR18	Preamplifier	6/29/2020	Annual	6/28/2021	102141
Rohde & Schwarz	TS-PR1840	Preamplifier	6/29/2020	Annual	6/28/2021	100049
Rohde & Schwarz	ENV216	Two-Line V-Network	5/24/2021	Annual	5/23/2022	101319
Rohde & Schwarz	FSW43	Signal & Spectrum Analyzer	9/17/2020	Annual	9/16/2021	101250
Rohde & Schwarz	TS-SFUNIT-Rx	Shielded Filter Unit	2/19/2021	Annual	2/18/2022	102131

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMA127FN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 9 of 28

7.0 TEST DATA

7.1 Summary

Test Date(s): 05/13 - 6/1/2021

Test Engineer:



FCC Part 15 Section	Description	Result
15.107	Conducted Emissions	PASS
15.109	Radiated Emissions	PASS

Table 7-1. Summary of Test Results

7.2 Test Support Equipment

Configuration 1				
Samsung Travel Adapter	Model:	EP-TA200	S/N:	N/A
Samsung USB Cable	Model:	EP-DR140AWE	S/N:	N/A
Configuration 2				
Samsung Travel Adapter	Model:	EP-TA200	S/N:	N/A
Samsung USB Cable	Model:	EP-DR140AWE	S/N:	N/A
Configuration 3				
Samsung Travel Adapter	Model:	EP-TA200	S/N:	N/A
Samsung USB Cable	Model:	EP-DR140AWE	S/N:	N/A
Configuration 4				
Samsung Travel Adapter	Model:	EP-TA200	S/N:	N/A
Samsung USB Cable	Model:	EP-DR140AWE	S/N:	N/A
Configuration 5				
Samsung Travel Adapter	Model:	EP-TA200	S/N:	N/A
Samsung USB Cable	Model:	EP-DR140AWE	S/N:	N/A
Sandisk Ultra microSD	Model:	N/A	S/N:	0186DXLG70HA
Samsung laptop	Model:	NT200B5C	S/N:	JHQL91KF300096K
Samsung AC adapter	Model:	A13-090P3A	S/N:	A090A071L
Iptime hub	Model:	U1003	S/N:	U1003073C73C03964
Configuration 6				
Samsung Travel Adapter	Model:	EP-TA200	S/N:	N/A
Samsung USB Cable	Model:	N/A	S/N:	N/A
Optical Mouse	Model:	HM5061A	S/N:	N/A
Samsung OTG Adapter	Model:	N/A	S/N:	EBX63212004

Table 7-2. Test Support Equipment Used

Note: See test setup photographs for actual system test setup.

FCC ID: A3LSMA127FN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 10 of 28

7.3 Radiated Measurement Data

§15.109

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions must not exceed the limits shown in Table 7-3 per FCC 15.109.

Frequency [MHz]	Field Strength Limit [μV/m]
30 – 88	100
88 – 216	150
216 – 960	200
> 960	500

Table 7-3. 3-Meter Radiated Limits (Section 15.109)

Test Procedures Used

ANSI C63.4-2014

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer frequency set to the frequency of the radiated spurious emission of interest
2. RBW = 100kHz, VBW = 300kHz (for emissions between 30MHz – 1GHz)
3. RBW = 1MHz, VBW = 3MHz (for emissions above 1GHz)
4. Detector = Quasi-peak (for emissions between 30MHz – 1GHz)
5. Detector = Peak (for emissions above 1GHz)
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown test setup photos provided.


FCC ID: A3LSMA127FN		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 11 of 28

Test Notes


1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated emissions were measured from 30MHz –18GHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. The radiated limits for unintentional radiators at a distance of 3 meters are used in the table above, as specified in 15.109(a).
4. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
5. $AFCL\ (dB/m) = Antenna\ Factor\ (dB/m) + Cable\ Loss\ (dB)$
6. $Level\ (dB\mu V/m) = Analyzer\ Reading\ (dBm) + AFCL\ (dB/m) + 107$
7. $Margin\ (dB) = Field\ strength\ (dB\mu V/m) - Limit\ (dB\mu V/m)$
8. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a RMS detector using a resolution bandwidth of 1MHz and a video bandwidth of 3MHz.
9. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
10. Calibrated low-loss microwaves cables and broadband amplifiers are used.

FCC ID: A3LSMA127FN	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 12 of 28

Radiated Test Config. 1



Plot 7-1. Radiated Spurious Plot below 1GHz [Radiated Test Config. 1]




Plot 7-2. Radiated Spurious Plot above 1GHz [Radiated Test Config. 1]

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
56.95	Quasi-Peak	V	100	129	-97.40	14.40	24.00	40.00	-16.00
78.17	Quasi-Peak	V	116	217	-78.90	9.21	37.31	40.00	-2.69
157.70	Quasi-Peak	V	147	45	-101.90	20.33	25.43	43.52	-18.09
252.89	Quasi-Peak	V	162	187	-108.00	20.92	19.92	46.02	-26.11
937.59	Quasi-Peak	V	201	163	-109.80	25.52	22.72	46.02	-23.31
991.61	Quasi-Peak	V	198	301	-110.00	26.14	23.14	53.98	-30.84


Table 7-4. Radiated Measurements [Radiated Test Config. 1]

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)		SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset			Page 13 of 28

Radiated Test Config. 2



Plot 7-3. Radiated Spurious Plot below 1GHz [Radiated Test Config. 2]




Plot 7-4. Radiated Spurious Plot above 1GHz [Radiated Test Config. 2]

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
50.00	Quasi-Peak	V	111	11	-86.04	14.87	35.83	40.00	-4.17
120.00	Quasi-Peak	V	179	351	-89.88	22.76	39.88	43.52	-3.64
125.00	Quasi-Peak	V	151	160	-89.97	22.72	39.75	43.52	-3.77
150.01	Quasi-Peak	V	161	44	-88.75	21.29	39.54	43.52	-3.99
247.56	Quasi-Peak	V	211	47	-93.22	20.86	34.64	46.02	-11.39
480.03	Quasi-Peak	V	201	112	-90.90	19.19	35.29	46.02	-10.73


Table 7-5. Radiated Measurements [Radiated Test Config. 2]

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 14 of 28

Radiated Test Config. 3



Plot 7-5. Radiated Spurious Plot below 1GHz [Radiated Test Config. 3]



Plot 7-6. Radiated Spurious Plot above 1GHz [Radiated Test Config. 3]

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
34.54	Quasi-Peak	V	148	51	-93.90	11.73	24.83	40.00	-15.17
55.29	Quasi-Peak	V	100	20	-91.80	14.51	29.71	40.00	-10.29
129.48	Quasi-Peak	V	134	17	-101.50	22.69	28.19	43.52	-15.33
296.70	Quasi-Peak	V	182	4	-96.10	16.31	27.21	46.02	-18.81
884.51	Quasi-Peak	V	210	99	-99.50	24.91	32.41	46.02	-13.62
991.24	Quasi-Peak	V	261	210	-100.10	26.13	33.03	53.98	-20.95

Table 7-6. Radiated Measurements [Radiated Test Config. 3]

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 15 of 28

7.4 Line Conducted Measurement Data

§15.107

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.107.

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-7. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.4-2014

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA127FN	 Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset	Page 16 of 28	

Test Setup


The EUT and measurement equipment were set up as shown in the test setup photos provided.

Test Notes

1. All Modes of operation were investigated and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.107.
3. L1 = Phase; N = Neutral
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Reading (dB}\mu\text{V)} + \text{Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

FCC ID: A3LSMA127FN	 Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset	Page 17 of 28	

Conducted Test Config. 1




Plot 7-7. Line Conducted Plot (L1)

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.609690	—	27.30	46.00	18.70	1000.0	9.000	L1	10.0
0.609690	35.71	—	56.00	20.29	1000.0	9.000	L1	10.0
13.081020	—	29.12	50.00	20.88	1000.0	9.000	L1	10.0
13.081020	35.89	—	60.00	24.11	1000.0	9.000	L1	10.0
13.084005	—	29.18	50.00	20.82	1000.0	9.000	L1	10.0
13.084005	35.89	—	60.00	24.11	1000.0	9.000	L1	10.0
13.125795	—	29.13	50.00	20.87	1000.0	9.000	L1	10.0
13.125795	35.91	—	60.00	24.09	1000.0	9.000	L1	10.0
13.319820	—	28.77	50.00	21.23	1000.0	9.000	L1	10.0
13.319820	35.59	—	60.00	24.41	1000.0	9.000	L1	10.0
13.340715	—	28.63	50.00	21.37	1000.0	9.000	L1	10.0
13.340715	35.50	—	60.00	24.50	1000.0	9.000	L1	10.0

Table 7-8. Line Conducted Table (L1)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 18 of 28



Plot 7-8. Line Conducted Plot (N)


Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.203730	—	41.40	53.27	11.87	1000.0	9.000	N	9.8
0.203730	53.81	—	63.46	9.64	1000.0	9.000	N	9.8
0.278355	—	33.52	50.62	17.10	1000.0	9.000	N	9.7
0.278355	45.70	—	60.87	15.17	1000.0	9.000	N	9.7
9.272160	—	31.21	50.00	18.79	1000.0	9.000	N	9.9
9.272160	39.60	—	60.00	20.40	1000.0	9.000	N	9.9
12.916845	—	31.91	50.00	18.09	1000.0	9.000	N	10.0
12.916845	40.06	—	60.00	19.94	1000.0	9.000	N	10.0
14.149650	—	32.34	50.00	17.66	1000.0	9.000	N	10.0
14.149650	40.51	—	60.00	19.49	1000.0	9.000	N	10.0
15.027240	—	28.78	50.00	21.22	1000.0	9.000	N	10.1
15.027240	38.74	—	60.00	21.26	1000.0	9.000	N	10.1

Table 7-9. Line Conducted Table (N)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 19 of 28

Conducted Test Config. 2




Plot 7-9. Line Conducted Plot (L1)

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	—	39.29	56.00	16.71	1000.0	9.000	L1	9.7
0.150000	51.19	—	66.00	14.81	1000.0	9.000	L1	9.7
0.230595	—	30.97	52.20	21.23	1000.0	9.000	L1	9.7
0.230595	43.83	—	62.43	18.60	1000.0	9.000	L1	9.7
0.633570	—	32.60	46.00	13.40	1000.0	9.000	L1	10.0
0.633570	40.17	—	56.00	15.83	1000.0	9.000	L1	10.0
0.755955	—	20.52	46.00	25.48	1000.0	9.000	L1	9.9
0.755955	29.43	—	56.00	26.57	1000.0	9.000	L1	9.9
4.269300	—	18.88	46.00	27.12	1000.0	9.000	L1	9.8
4.269300	26.71	—	56.00	29.29	1000.0	9.000	L1	9.8
4.926000	—	18.67	46.00	27.33	1000.0	9.000	L1	9.8
4.926000	27.28	—	56.00	28.72	1000.0	9.000	L1	9.8

Table 7-10. Line Conducted Table (L1)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 20 of 28



Plot 7-10. Line Conducted Plot (N)


Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155970	—	36.83	55.64	18.81	1000.0	9.000	N	9.8
0.155970	50.02	—	65.68	15.66	1000.0	9.000	N	9.8
0.227610	—	31.14	52.31	21.17	1000.0	9.000	N	9.7
0.227610	42.83	—	62.54	19.71	1000.0	9.000	N	9.7
0.636555	—	33.78	46.00	12.22	1000.0	9.000	N	9.9
0.636555	40.53	—	56.00	15.47	1000.0	9.000	N	9.9
0.702225	—	31.08	46.00	14.92	1000.0	9.000	N	9.9
0.702225	39.25	—	56.00	16.75	1000.0	9.000	N	9.9
0.785805	—	30.23	46.00	15.77	1000.0	9.000	N	9.9
0.785805	38.02	—	56.00	17.98	1000.0	9.000	N	9.9
12.194475	—	28.47	50.00	21.53	1000.0	9.000	N	10.0
12.194475	37.85	—	60.00	22.15	1000.0	9.000	N	10.0

Table 7-11. Line Conducted Table (N)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 21 of 28

Conducted Test Config. 3




Plot 7-11. Line Conducted Plot (L1)

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.152985	—	39.79	55.82	16.03	1000.0	9.000	L1	9.8
0.152985	51.34	—	65.84	14.50	1000.0	9.000	L1	9.8
0.230595	—	30.79	52.20	21.41	1000.0	9.000	L1	9.7
0.230595	42.99	—	62.43	19.44	1000.0	9.000	L1	9.7
0.233580	—	36.32	52.09	15.77	1000.0	9.000	L1	9.7
0.233580	47.13	—	62.32	15.19	1000.0	9.000	L1	9.7
0.591780	—	21.37	46.00	24.63	1000.0	9.000	L1	10.0
0.591780	34.29	—	56.00	21.71	1000.0	9.000	L1	10.0
0.624615	—	28.47	46.00	17.53	1000.0	9.000	L1	10.0
0.624615	39.36	—	56.00	16.65	1000.0	9.000	L1	10.0
18.358500	—	21.65	50.00	28.35	1000.0	9.000	L1	10.0
18.358500	38.28	—	60.00	21.72	1000.0	9.000	L1	10.0

Table 7-12. Line Conducted Table (L1)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 22 of 28



Plot 7-12. Line Conducted Plot (N)


Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155970	—	40.76	55.64	14.88	1000.0	9.000	N	9.8
0.155970	52.14	—	65.68	13.53	1000.0	9.000	N	9.8
12.839235	—	34.43	50.00	15.57	1000.0	9.000	N	10.0
12.839235	43.01	—	60.00	16.99	1000.0	9.000	N	10.0
12.895950	—	34.23	50.00	15.77	1000.0	9.000	N	10.0
12.895950	43.09	—	60.00	16.91	1000.0	9.000	N	10.0
12.925800	—	34.19	50.00	15.81	1000.0	9.000	N	10.0
12.925800	42.99	—	60.00	17.01	1000.0	9.000	N	10.0
13.072065	—	33.86	50.00	16.14	1000.0	9.000	N	10.0
13.072065	42.65	—	60.00	17.35	1000.0	9.000	N	10.0
13.478025	—	32.16	50.00	17.84	1000.0	9.000	N	10.0
13.478025	40.87	—	60.00	19.13	1000.0	9.000	N	10.0

Table 7-13. Line Conducted Table (N)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 23 of 28

Conducted Test Config. 4




Plot 7-13. Line Conducted Plot (L1)

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	—	40.02	56.00	15.98	1000.0	9.000	L1	9.7
0.150000	51.81	—	66.00	14.19	1000.0	9.000	L1	9.7
0.230595	—	31.60	52.20	20.60	1000.0	9.000	L1	9.7
0.230595	44.44	—	62.43	17.99	1000.0	9.000	L1	9.7
0.233580	—	30.56	52.09	21.53	1000.0	9.000	L1	9.7
0.233580	44.30	—	62.32	18.02	1000.0	9.000	L1	9.7
0.403725	—	20.25	47.64	27.38	1000.0	9.000	L1	10.0
0.403725	33.78	—	57.78	23.99	1000.0	9.000	L1	10.0
0.624615	—	28.36	46.00	17.64	1000.0	9.000	L1	10.0
0.624615	38.08	—	56.00	17.92	1000.0	9.000	L1	10.0
0.779835	—	28.59	46.00	17.41	1000.0	9.000	L1	9.9
0.779835	36.65	—	56.00	19.35	1000.0	9.000	L1	9.9

Table 7-14. Line Conducted Table (L1)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 24 of 28



Plot 7-14. Line Conducted Plot (N)


Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.152985	—	40.92	55.82	14.90	1000.0	9.000	N	9.7
0.152985	52.61	—	65.84	13.22	1000.0	9.000	N	9.7
0.221640	—	31.89	52.54	20.65	1000.0	9.000	N	9.7
0.221640	44.62	—	62.76	18.13	1000.0	9.000	N	9.7
0.621630	—	29.44	46.00	16.56	1000.0	9.000	N	9.9
0.621630	40.49	—	56.00	15.51	1000.0	9.000	N	9.9
0.636555	—	33.36	46.00	12.64	1000.0	9.000	N	9.9
0.636555	40.33	—	56.00	15.67	1000.0	9.000	N	9.9
0.773865	—	30.18	46.00	15.82	1000.0	9.000	N	9.9
0.773865	39.59	—	56.00	16.41	1000.0	9.000	N	9.9
11.773590	—	28.74	50.00	21.26	1000.0	9.000	N	10.0
11.773590	37.51	—	60.00	22.49	1000.0	9.000	N	10.0

Table 7-15. Line Conducted Table (N)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 25 of 28

Conducted Test Config. 5




Plot 7-15. Line Conducted Plot (L1)

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.672375	—	31.97	46.00	14.03	1000.0	9.000	L1	9.9
0.672375	43.67	—	56.00	12.33	1000.0	9.000	L1	9.9
0.693270	—	32.91	46.00	13.09	1000.0	9.000	L1	9.9
0.693270	44.10	—	56.00	11.90	1000.0	9.000	L1	9.9
3.260370	—	30.61	46.00	15.39	1000.0	9.000	L1	9.7
3.260370	42.26	—	56.00	13.74	1000.0	9.000	L1	9.7
3.391710	—	28.16	46.00	17.84	1000.0	9.000	L1	9.7
3.391710	40.22	—	56.00	15.78	1000.0	9.000	L1	9.7
3.532005	—	29.45	46.00	16.55	1000.0	9.000	L1	9.8
3.532005	41.35	—	56.00	14.65	1000.0	9.000	L1	9.8
3.723045	—	28.94	46.00	17.06	1000.0	9.000	L1	9.8
3.723045	40.83	—	56.00	15.17	1000.0	9.000	L1	9.8

Table 7-16. Line Conducted Table (L1)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 26 of 28



Plot 7-16. Line Conducted Plot (N)

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.651480	—	29.68	46.00	16.32	1000.0	9.000	N	9.9
0.651480	39.56	—	56.00	16.44	1000.0	9.000	N	9.9
0.675360	—	40.26	46.00	5.74	1000.0	9.000	N	9.9
0.675360	46.75	—	56.00	9.25	1000.0	9.000	N	9.9
0.699240	—	42.73	46.00	3.27	1000.0	9.000	N	9.9
0.699240	49.16	—	56.00	6.85	1000.0	9.000	N	9.9
3.776775	—	35.09	46.00	10.91	1000.0	9.000	N	9.8
3.776775	43.87	—	56.00	12.13	1000.0	9.000	N	9.8
3.845430	—	34.14	46.00	11.86	1000.0	9.000	N	9.8
3.845430	43.11	—	56.00	12.89	1000.0	9.000	N	9.8
4.152885	—	29.04	46.00	16.96	1000.0	9.000	N	9.8
4.152885	40.71	—	56.00	15.29	1000.0	9.000	N	9.8

Table 7-17. Line Conducted Table (N)

FCC ID: A3LSMA127FN	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset		Page 27 of 28

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA127FN** has been tested to comply with the requirements specified in §15.107 and §15.109 of the FCC rules.

FCC ID: A3LSMA127FN	 Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1K2105110019-09.A3L	Test Dates: 05/13 - 6/1/2021	EUT Type: Portable handset	Page 28 of 28	