

CERTIFICATION TEST REPORT

Report Number. : S-4791440365-E8V1

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-A166U, SM-A166U1, SM-S166V

FCC ID : A3LSMA166U

EUT Description : GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac and
NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART E

Date Of Issue:

2024-10-04

Prepared by:

UL KOREA LTD.

26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL KOREA LTD. Suwon Laboratory

218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea

TEL: (031) 337-9902

FAX: (031) 213-5433

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2024-10-04	Initial issue	Myeongjun Kwon

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY	7
4.4. DECISION RULE	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. DESCRIPTION OF AVAILABLE ANTENNAS	9
5.3. List of test reduction and modes covering other modes:	10
5.4. WORST-CASE CONFIGURATION AND MODE	10
5.5. DESCRIPTION OF TEST SETUP	11
6. TEST AND MEASUREMENT EQUIPMENT	13
7. SUMMARY TABLE	14
8. MEASUREMENT METHODS	15
9. REFERENCE MEASUREMENTS RESULTS	16
9.1. ON TIME AND DUTY CYCLE RESULTS	16
9.2. 26 dB BANDWIDTH	17
9.2.1. 802.11a	18
9.2.2. 802.11n HT20	18
9.2.3. 802.11n HT40	18
9.2.4. 802.11ac VHT80	19
9.2.5. STRADDLE CHANNEL	19
10. ANTENNA PORT TEST RESULTS	20
10.1. 6 dB BANDWIDTH	20
10.1.1. STRADDLE CHANNEL	22
10.1.2. UNII-3 BAND	23
10.2. OUTPUT POWER AND PPSD	24
10.2.1. 802.11a MODE	26
10.2.1. 802.11n HT20 MODE	27
10.2.2. 802.11n HT40 MODE	28

10.2.3.	802.11ac VHT80 MODE	29
10.2.4.	OUTPUT POWER AND PPSD PLOTS(WORST CASE)	30
11.	TRANSMITTER ABOVE 1 GHz.....	31
11.1.	TX ABOVE 1GHz 1TX MODE IN THE 5.2GHz BAND	34
11.2.	TX ABOVE 1GHz 1TX MODE IN THE 5.3GHz BAND	38
11.3.	TX ABOVE 1GHz 1TX MODE IN THE 5.5 GHz BAND	42
11.4.	TX ABOVE 1GHz 1TX MODE IN THE 5.8 GHz BAND	46
12.	WORST-CASE BELOW 1 GHz	50
13.	AC POWER LINE CONDUCTED EMISSIONS	51
14.	DYNAMIC FREQUENCY SELECTION.....	54
14.1.	OVERVIEW.....	54
14.1.1.	LIMITS	54
14.1.2.	TEST AND MEASUREMENT SYSTEM	57
14.1.3.	SETUP OF EUT.....	60
14.1.4.	DESCRIPTION OF EUT	61
14.2.	RESULTS FOR 80 MHz BANDWIDTH (UNII-2A BAND)	62
14.2.1.	TEST CHANNEL	62
14.2.2.	RADAR WAVEFORM AND TRAFFIC	62
14.2.3.	OVERLAPPING CHANNEL TESTS	63
14.2.4.	MOVE AND CLOSING TIME	63
14.1.	RESULTS FOR 80 MHz BANDWIDTH (UNII-2C BAND).....	66
14.1.1.	TEST CHANNEL	66
14.1.2.	RADAR WAVEFORM AND TRAFFIC	66
14.1.3.	OVERLAPPING CHANNEL TESTS.....	67
14.1.4.	MOVE AND CLOSING TIME	67

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac and NFC.

MODEL NUMBER: SM-A166U, SM-A166U1, SM-S166V

SERIAL NUMBER: R3CX807W82F, R3CX807W74Y, R3CX807W7RA (CONDUCTED);
R3CX807W3JV, R3CX807W8JT, R3CX807W38R (RADIATED)

DATE TESTED: 2024-08-12 - 2024-10-04

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Complies

UL KOREA LTD. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL KOREA LTD. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL KOREA LTD. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL KOREA LTD. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL KOREA LTD. By:



Seokhwan Hong
Suwon Lab Engineer
UL KOREA LTD.

Tested By:



Myeongjun Kwon
Suwon Lab Engineer
UL KOREA LTD.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 789033 D02 General UNII Test Procedures New Rules v02r01
4. KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02
5. KDB 905462 D03 UNII Clients Without Radar Detection New Rules v01r02
6. ANSI C63.10-2020.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☒	Chamber 1(3m semi-anechoic chamber)
☒	Chamber 2(3m semi-anechoic chamber)
☒	Chamber 3(3m semi-anechoic chamber)
☐	Chamber 4(3m Full-anechoic chamber)
☐	Chamber 5(3m Full-anechoic chamber)

UL KOREA LTD. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

$$\begin{aligned} \text{AC Corrected Reading (dBuV)} &= \text{Measured Voltage (dBuV)} + \text{Extension Cord} \\ &\text{Loss (dB)} + \text{Cable Loss (dB)} \\ 44.72 \text{ dBuV} &= 34.72 \text{ dBuV} + 9.9 \text{ dB} + 0.1 \text{ dB} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.79 dB
Radiated Disturbance, 9 kHz to 30 MHz	1.69 dB
Radiated Disturbance, 30 MHz to 1 GHz	4.07 dB
Radiated Disturbance, 1 GHz to 18 GHz	4.99 dB
Radiated Disturbance, Above 18 GHz	5.96 dB

Uncertainty figures are valid to a confidence level of 95%.

4.4. DECISION RULE

Decision rule for statement(s) of conformity is based on Clause 4.4.3 in IEC Guide 115:2023.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac and NFC.
This test report addresses the NII (WLAN) operational mode.

Representative model	Difference	Derivative model
		SM-A166U1, SM-S166V
SM-A166U	Hardware	Same
	Software	The UI has changed according to Service Provider

The model SM-A166U was used for final testing and is representative of the test results in this report.

MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted average output power as follows:

Band	Frequency Range [MHz]	Mode	Output Power [dBm]	Output Power [mW]
UNII-1	5180 - 5240	802.11a SISO	15.31	33.96
		802.11n(HT20) SISO	15.49	35.40
	5190 - 5230	802.11n(HT40) SISO	14.33	27.10
		802.11ac(VHT80) SISO	13.34	21.58
UNII-2A	5260 - 5320	802.11a SISO	15.47	35.24
		802.11n(HT20) SISO	15.21	33.19
	5190 - 5230	802.11n(HT40) SISO	14.38	27.42
		802.11ac(VHT80) SISO	13.16	20.70
UNII-2C	5500 - 5720	802.11a SISO	14.58	28.71
		802.11n(HT20) SISO	14.66	29.24
	5510 - 5710	802.11n(HT40) SISO	13.56	22.70
		802.11ac(VHT80) SISO	12.72	18.71
UNII-3	5745 - 5825	802.11a SISO	15.51	35.56
		802.11n(HT20) SISO	15.60	36.31
	5755 - 5795	802.11n(HT40) SISO	14.54	28.44
		802.11ac(VHT80) SISO	12.93	19.63

5.2. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**The internal antenna was Permanently attached.
Therefore this E.U.T Complies with the requirement of §15.203.**

The radio utilizes a internal antenna, with a maximum gain of:

UNII Band	Frequency Range[MHz]	ANT1 Gain [dBi]
UNII 1	5150 - 5250	-5.40
UNII 2A	5250 - 5350	-5.60
UNII 2C	5470 - 5725	-5.80
UNII 3	5725 - 5850	-5.30

“Antenna D(WiFi)” as indicated in antenna specification are written as ANT1 in this report.

5.3. List of test reduction and modes covering other modes:

The output power on covered modes is equal to or less than one referenced.

Authorized Frequency Band			
Mode	Antenna Stream	Mode	Covered by
802.11a	SISO	802.11a 1TX	
802.11n HT20		802.11n HT20 1TX	
802.11ac VHT20		802.11ac VHT20 1TX	802.11n HT20 1TX
802.11n HT40		802.11n HT40 1TX	
802.11ac VHT40		802.11ac VHT40 1TX	802.11n HT40 1TX
802.11ac VHT80		802.11ac VHT80 1TX	

5.4. WORST-CASE CONFIGURATION AND MODE

The fundamentals of the EUT were investigated in three orthogonal orientations X, Y and Z on 1TX SISO mode. It was determined that Y orientation was the worst-case for 1TX SISO mode.

Worst case of antenna axis: Y

Radiated and power line conducted tests were performed with EUT connected to AC power adapter as the worst-case configuration. Radiated harmonics spurious 1~18 GHz Low/Mid/High channels, 18-40GHz were performed with the EUT set at the worst mode. Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

For Radiated spurious test, 802.11a 1TX mode has equal or higher output power and PSD results than other modes and therefore, it was set for full test. Spot-check was performed in 802.11n 1TX, 802.11ac 1TX.

For Radiated band-edge test, 802.11a 1TX, 802.11n 1TX, 802.11ac 1TX.

Simultaneous transmission with the Bluetooth and Wi-Fi were investigated, and no noticeable emission was found.

Based on the baseline scan, the worst-case data rates were:

802.11a mode: 6 Mbps 1TX
802.11n HT20 mode: MCS0 1TX
802.11n HT40 mode: MCS0 1TX
802.11ac VHT80 mode: MCS0 1TX

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA800	R37TC7A00JBDKA	N/A
Data Cable	SAMSUNG	EP-DN980	GH39-02115A	N/A


I/O CABLE

I/O Cable List						
Cable No.	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type	Shielded	1.0 m	N/A


TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software exercised the EUT to enable NII mode.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB 9163	749	2026-08-12
Antenna, Horn, 18 GHz	ETS	3117	00168717	2026-07-17
Antenna, Horn, 18 GHz	ETS	3117	00218957	N/A
Antenna, Horn, 40 GHz	ETS	3116C	00166155	2026-07-23
Preamplifier	ETS	3116C-PA	00168841	2025-07-25
Preamplifier, 1000 MHz	Sonoma	310N	341282	2025-07-22
Preamplifier, 18 GHz	B&Z Technologies, LLC	BZR-01001800-231040-181515	23576	2025-07-25
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	2025-07-23
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	2025-07-24
Spectrum Analyzer, 44 GHz	KEYSIGHT	N9040B	MY60080268	2025-01-03
RF Switching Unit	TA Engineering	TA-018S-16	SW-1	N/A
Average Power Sensor	Agilent / HP	U2000A	MY54270007	2025-07-23
Average Power Sensor	Agilent / HP	U2000A	MY54260010	2025-07-23
Attenuator	PASTERNAK	PE7087-10	A001	2025-07-23
Attenuator	PASTERNAK	PE7087-10	A008	2025-07-23
Attenuator	PASTERNAK	PE7004-10	2	2025-07-23
Attenuator	PASTERNAK	PE7087-10	A009	2025-07-23
EMI Test Receive, 40 GHz	R&S	ESU40	100439	2025-07-23
EMI Test Receive, 40 GHz	R&S	ESU40	100457	2025-07-22
EMI Test Receive, 3 GHz	R&S	ESR 3	101832	2025-07-22
Notch Filter	Micro-Tronics	BRM50702-02	G037	2025-07-24
Notch Filter	Micro-Tronics	BRM50716-2	006	2025-07-23
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	2025-07-23
High Pass Filter 3GHz	Micro-Tronics	HPM17543	20	2025-07-23
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	2025-07-22
LISN	R&S	ENV216	101836	2025-07-22
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	2025-09-07
Termination	WEINSCHL	M1406A	T09	2025-07-23
Attenuator	WEINSCHL	WA76-30-21	A015	2025-07-23
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
15.407(e)	6dB Band width (5.8GHz)	> 500kHz	Conducted	Complies
15.407 (a)(1)(iv)	TX Cond. Power (5.150-5.250)	< 24dBm		Complies
15.407 (a)(2)	TX Cond. Power (5.250-5.350 & 5.470-5.725)	< 24dBm or 11+10Log(26dB BW)		Complies
15.407 (a)(3)(i)	TX Cond. Power (5.725-5.850)	< 30dBm		Complies
15.407 (a)(1)(iv) & (a)(2)	PSD (5.150-5.250 5.250-5.350 & 5.470-5.725)	< 11dBm/MHz		Complies
15.407 (a)(3)(i)	PSD (5.725-5.850)	< 30dBm/500kHz		Complies
15.207 (a)	AC Power Line conducted emissions	Section 13	Radiated	Complies
15.407 (b) & 15.209	Radiated Spurious Emission	< 74dBuV/m PK < 54dBuV/m AV		Complies
15.407 (h)(2)	Dynamic Frequency Selection	N/A	Condcuted	Complies ^{Note}

8. MEASUREMENT METHODS

On-Time and Duty Cycle : KDB 789033 D02 v02r01, Section II.B.

6dB Emission BW : KDB 789033 D02 v02r01, Section II.C.2.

26dB Emission BW : KDB 789033 D02 v02r01, Section II.C.1., ANSI C63.10-2020, Section 12.5.2.

99% Occupied BW : KDB 789033 D02 v02r01, Section II.D.

Conducted Output Power : KDB 789033 D02 v02r01, Section II.E.3.a(Method PM)

Conducted Output Power for Straddle Channel (ch144/142/138 for 20/40/80MHz BW):

KDB 789033 D02 v02r01, Section II.E.2.b(Method SA-1)

Power Spectral Density : KDB 789033 D02 v02r01, Section II.F.

Unwanted emissions in restricted bands : KDB 789033 D02 v02r01, Section II.G.3 – II.G.6.

Unwanted emissions in non-restricted bands : KDB 789033 D02 v02r01, Section II.G.3 – II.G.6.


AC Power Line Conducted Emission : ANSI C63.10-2020, Section 6.2.

Mode	On Time [ms]	Period [ms]	Duty Cycle X [Linear]	Duty Cycle X [%]	Duty Cycle Correction Factor[dB]
802.11a SISO	2.789	2.880	0.968	96.840	0.14
802.11n(HT20) SISO	5.125	5.229	0.980	98.011	0.00
802.11n(HT40) SISO	2.487	2.675	0.930	92.972	0.32
802.11ac(VHT80) SISO	1.175	1.274	0.922	92.229	0.35

LIMITS

PROCEDURE

DUTY CYCLE SAMPLE PLOTS



9.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.


TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v02r01: The transmitter output is connected to a spectrum analyzer with the RBW set to 1% to 5% of EBW, the VBW > RBW, peak detector and max hold.

RESULTS

- Please refer to the next page

WORST CASE TEST PLOTS



9.2.1. 802.11a

Band	Channel	Center Freq. [MHz]	26 dB BW [MHz]	Worst	99% BW [MHz]
			ANT1		ANT1
UNII-1 ^{Note}	36	5180	20.78	20.55	16.60
	40	5200	20.85		16.63
	48	5240	20.55		16.60
UNII-2A ^{Note}	52	5260	20.78	20.60	16.58
	60	5300	20.72		16.59
	64	5320	20.60		16.57
UNII-2C	100	5500	20.81	20.46	
	116	5580	20.46		
	140	5700	20.59		

Note. As a result of 99% bandwidth test, the bandwidth of UNII-1 does not interfere with UNII-2A.

9.2.2. 802.11n HT20

Band	Channel	Center Freq. [MHz]	26 dB BW [MHz]	Worst	99% BW [MHz]
			ANT1		ANT1
UNII-1 ^{Note}	36	5180	21.13	21.13	17.68
	40	5200	21.91		17.69
	48	5240	21.70		17.67
UNII-2A ^{Note}	52	5260	21.41	21.41	17.65
	60	5300	21.70		17.70
	64	5320	21.75		17.66
UNII-2C	100	5500	21.75	21.54	
	116	5580	21.93		
	140	5700	21.54		

Note. As a result of 99% bandwidth test, the bandwidth of UNII-1 does not interfere with UNII-2A.

9.2.3. 802.11n HT40

Band	Channel	Center Freq. [MHz]	26 dB BW [MHz]	Worst	99% BW [MHz]
			ANT1		ANT1
UNII-1 ^{Note}	38	5190	42.68	41.46	36.27
	46	5230	41.46		36.26
UNII-2A ^{Note}	54	5270	41.44	41.44	36.26
	62	5310	41.47		36.16
UNII-2C	102	5510	41.12	40.90	
	110	5550	41.89		
	134	5670	40.90		

Note. As a result of 99% bandwidth test, the bandwidth of UNII-1 does not interfere with UNII-2A.

9.2.4. 802.11ac VHT80

Band	Channel	Center Freq. [MHz]	26 dB BW [MHz]	Worst	99% BW [MHz]
			ANT1		ANT1
UNII-1 ^{Note}	42	5210	81.74	81.74	75.13
UNII-2A ^{Note}	58	5290	81.37	81.37	75.05
UNII-2C	106	5530	81.89	81.89	
	122	5610	82.13		

Note. As a result of 99% bandwidth test, the bandwidth of UNII-1 does not interfere with UNII-2A.

9.2.5. STRADDLE CHANNEL

Mode	Channel	Center Freq. [MHz]	26 dB BW [MHz]	
			ANT1	
			UNII-2C	UNII-3
802.11a	Straddle	5720	15.16	5.16
802.11n HT20	Straddle	5720	15.56	5.72
802.11n HT40	Straddle	5710	36.52	6.68
802.11ac VHT80	Straddle	5690	75.96	6.12

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.407

The minimum 6 dB bandwidth shall be at least 500 kHz.


TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v02r01: The transmitter output is connected to a spectrum analyzer with the RBW set to 100kHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.


RESULTS

- Please refer to the next page

WORST CASE TEST PLOTS



WORST CASE TEST PLOTS(STRADDLE CHANNELS)



10.1.1. STRADDLE CHANNEL

Mode	Channel	Center Freq. [MHz]	6 dB BW [MHz]
			UNII-3
			ANT1
802.11a	Straddle	5720	3.16
802.11ac VHT20	Straddle	5720	3.77
802.11n HT40	Straddle	5710	3.13
802.11ac VHT80	Straddle	5690	3.12

10.1.2. UNII-3 BAND

Mode	Channel	Center Freq. [MHz]	6 dB BW [MHz]	Worst	Minimum Limit [MHz]
			ANT1		
802.11a	149	5745	16.36	16.33	0.5
	157	5785	16.36		
	165	5825	16.33		
802.11n HT20	149	5745	17.30	17.27	
	157	5785	17.27		
	165	5825	17.29		
802.11n HT40	151	5755	35.85	35.85	
	159	5795	36.06		
802.11ac VHT80	155	5775	75.06	75.06	

10.2. OUTPUT POWER AND PPSD

LIMITS

FCC §15.407 (a)(1)(iv), (a)(2), (a)(3)(i)

FCC

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

KDB 789033 Method PM is used for output power. Duty correction factor has already been applied to the power meter and the average power value is measured.

KDB 789033 Method SA-2 is used for PSD. RBW set to 1MHz(500kHz for the band 5.725-5.85 GHz, the VBW $\geq 3 \times$ RBW, RMS detector and trace averaging).

Straddle Channel(UNII-2C&3)

KDB 789033 Method PM is used for output power of straddle channel.
(verification that both limit of UNII-2C and UNII-3 power are satisfied)

KDB 789033 Method SA-2 is used for PSD of straddle channel. RBW set to 1MHz, VBW $\geq 3 \times$ RBW, RMS detector and trace averaging. Peak marker value of the spectrum is used for PSD. Considering the PSD's RBW setting and test limit, the UNII-2C measurement method (RBW 1MHz) covers UNII-3 (RBW 500kHz).

DIRECTIONAL ANTENNA GAIN

For OUTPUT POWER and PSD: The TX chains are correlated and the antenna gains are unequal among the chains. The directional gain is:

Frequency Band [MHz]	ANT Gain [dBi]
UNII 1 5150 - 5250	-5.40
UNII 2A 5250 - 5350	-5.60
UNII 2C 5470 - 5725	-5.80
UNII 3 5725 - 5850	-5.30

10.2.1. 802.11a MODE

Output Power Results

Band	Channel	Center Freq. [MHz]	Average Power [dBm]	Corr'd Power [dBm]	Limit [dBm]
			ANT1		
UNII-1	36	5180	15.31	15.31	23.98
	40	5200	15.23	15.23	
	48	5240	15.28	15.28	
UNII-2A	52	5260	15.42	15.42	23.98
	60	5300	15.44	15.44	
	64	5320	15.47	15.47	
UNII-2C	100	5500	13.84	13.84	23.98
	116	5580	14.37	14.37	
	140	5700	14.34	14.34	
UNII-2C&3	144 Straddle	5720	14.58	14.58	30.00
UNII-3	149	5745	15.51	15.51	
	157	5785	15.27	15.27	
	165	5825	15.25	15.25	

* Calculation of Output Power : Average Power = Meas Power + Duty CF[dB]

PSD Results

Band	Channel	Center Freq. [MHz]	Meas PSD [dBm/MHz]	DCCF.	Corr'd PSD [dBm]	Limit [dBm/MHz]
			ANT1			
UNII-1	36	5180	3.16	0.14	3.30	11.00
	40	5200	3.08	0.14	3.22	
	48	5240	3.51	0.14	3.65	
UNII-2A	52	5260	2.38	0.14	2.52	11.00
	60	5300	3.11	0.14	3.25	
	64	5320	3.13	0.14	3.27	
UNII-2C	100	5500	2.09	0.14	2.23	11.00
	116	5580	2.18	0.14	2.32	
	140	5700	2.28	0.14	2.42	
UNII-2C&3	144 Straddle	5720	3.22	0.14	3.36	11.00 or 30.00/500kHz
UNII-3	149	5745	1.03	0.14	1.17	30.00/500kHz
	157	5785	1.34	0.14	1.48	
	165	5825	1.23	0.14	1.37	

* Calculation of PSD: Corr'd PSD = Meas PSD + Duty CF[dB]

10.2.1. 802.11n HT20 MODE

Output Power Results

Band	Channel	Center Freq. [MHz]	Average Power [dBm]	Corr'd Power [dBm]	Limit [dBm]
			ANT1		
UNII-1	36	5180	15.49	15.49	23.98
	40	5200	15.19	15.19	
	48	5240	15.04	15.04	
UNII-2A	52	5260	15.07	15.07	23.98
	60	5300	15.21	15.21	
	64	5320	14.95	14.95	
UNII-2C	100	5500	13.76	13.76	23.98
	116	5580	14.20	14.20	
	140	5700	14.02	14.02	
UNII-2C&3	144 Straddle	5720	14.66	14.66	30.00
UNII-3	149	5745	14.83	14.83	
	157	5785	15.19	15.19	
	165	5825	15.60	15.60	

* Calculation of Output Power : Average Power = Meas Power + Duty CF[dB]

PSD Results

Band	Channel	Center Freq. [MHz]	Meas PSD [dBm/MHz]	DCCF.	Corr'd PSD [dBm]	Limit [dBm/ MHz]
			ANT1			
UNII-1	36	5180	3.03	0.00	3.03	11.00
	40	5200	3.06	0.00	3.06	
	48	5240	3.31	0.00	3.31	
UNII-2A	52	5260	3.32	0.00	3.32	11.00
	60	5300	3.42	0.00	3.42	
	64	5320	3.11	0.00	3.11	
UNII-2C	100	5500	1.42	0.00	1.42	11.00
	116	5580	1.95	0.00	1.95	
	140	5700	1.97	0.00	1.97	
UNII-2C&3	144 Straddle	5720	2.79	0.00	2.79	11.00 or 30.00/500kHz
UNII-3	149	5745	0.27	0.00	0.27	30.00/500kHz
	157	5785	0.36	0.00	0.36	
	165	5825	0.78	0.00	0.78	

* Calculation of PSD: Corr'd PSD = Meas PSD + Duty CF[dB]

10.2.2. 802.11n HT40 MODE

Output Power Results

Band	Channel	Center Freq. [MHz]	Average Power [dBm]	Corr'd Power [dBm]	Limit [dBm]
			ANT1		
UNII-1	38	5190	14.33	14.33	23.98
	46	5230	14.12	14.12	
UNII-2A	54	5270	13.83	13.83	23.98
	62	5310	14.38	14.38	
UNII-2C	102	5510	13.26	13.26	23.98
	110	5550	13.56	13.56	
	134	5670	13.25	13.25	
UNII-2C&3	142 Straddle	5710	12.86	12.86	30.00
UNII-3	151	5755	14.39	14.39	
	159	5795	14.54	14.54	

* Calculation of Output Power : Average Power = Meas Power + Duty CF[dB]

PSD Results

Band	Channel	Center Freq. [MHz]	Meas PSD [dBm/MHz]	DCCF.	Corr'd PSD [dBm]	Limit [dBm/MHz]
			ANT1			
UNII-1	38	5190	-3.45	0.32	-3.13	11.00
	46	5230	-2.43	0.32	-2.11	
UNII-2A	54	5270	-1.89	0.32	-1.57	11.00
	62	5310	-1.53	0.32	-1.21	
UNII-2C	102	5510	-3.43	0.32	-3.11	11.00
	110	5550	-3.82	0.32	-3.50	
	134	5670	-4.37	0.32	-4.05	
UNII-2C&3	142 Straddle	5710	-3.81	0.32	-3.49	11.00 or 30.00/500kHz
UNII-3	151	5755	-4.80	0.32	-4.48	30.00/500kHz
	159	5795	-4.49	0.32	-4.17	

* Calculation of PSD: Corr'd PSD = Meas PSD + Duty CF[dB]

10.2.3. 802.11ac VHT80 MODE

Output Power Results

Band	Channel	Center Freq. [MHz]	Average Power [dBm]	Corr'd Power [dBm]	Limit [dBm]
			ANT1		
UNII-1	42	5210	13.34	13.34	23.98
UNII-2A	58	5290	13.16	13.16	23.98
UNII-2C	106	5530	11.94	11.94	23.98
	122	5610	12.72	12.72	
UNII-2C&3	138 Straddle	5690	12.57	12.57	23.98
UNII-3	155	5775	12.93	12.93	30.00


* Calculation of Output Power : Average Power = Meas Power + Duty CF[dB]

PSD Results

Band	Channel	Center Freq. [MHz]	Meas PSD [dBm/MHz]	DCCF.	Corr'd PSD [dBm]	Limit [dBm/MHz]
			ANT1			
UNII-1	42	5210	-6.11	0.35	-5.76	11.00
UNII-2A	58	5290	-6.34	0.35	-5.99	11.00
UNII-2C	106	5530	-7.48	0.35	-7.13	11.00
	122	5610	-7.61	0.35	-7.26	
UNII-2C&3	138 Straddle	5690	-7.22	0.35	-6.87	11.00 or 30.00/500kHz
UNII-3	155	5775	-9.17	0.35	-8.82	30.00/500kHz

* Calculation of PSD: Corr'd PSD = Meas PSD + Duty CF[dB]

10.2.4. OUTPUT POWER AND PPSD PLOTS(WORST CASE)



11. TRANSMITTER ABOVE 1 GHz

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

FCC Part 15.205 (a) : Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~ 12.52025	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.57675 ~ 12.57725	156.52475 ~ 156.52525	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	13.36 ~ 13.41	156.7 ~ 156.9	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	16.42 ~ 16.423	162.0125 ~ 167.17	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.69475 ~ 16.69525	167.72 ~ 173.2	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.80425 ~ 16.80475	240 ~ 285	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	25.5 ~ 25.67	322 ~ 335.4	2655 ~ 2900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3260 ~ 3267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3332 ~ 3339		
8.37625 ~ 8.38675	74.8 ~ 75.2	960 ~ 1240	3345.8 ~ 3358		
			3600 ~ 4400		

▪ FCC Part 15.205(b) : The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

FCC §15.407 (b)

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725–5.850 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary,
provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section.
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

Note

- Limit translation to field strength level (FCC §15.407)

$$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 = -27\text{dBm} + 95.2 = 68.2\text{dBuV/m}$$

$$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2 = -17\text{dBm} + 95.2 = 78.2\text{dBuV/m}$$

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. EUT is set 3 meters away from the receiving antenna and scan from 1m to 4m to find out the highest emission.

The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Reference to KDB 789033 D02 v02r01 UNII part G) 6) c) Method AD:

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor to the reading offset for average measurements. In UNII-4, unwanted emissions outside of restricted bands are measured with an RMS detector.

Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 kHz for peak measurements.

The spectrum from 1GHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


Note : Emission was pre-scanned from 9kHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open area test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the one of tests made in an open field based on KDB 414788.

11.1. TX ABOVE 1GHz 1TX MODE IN THE 5.2GHz BAND

BANDEDGE (WORST CASE: 802.11n HT40 / 5190 MHz)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	Antenna_907_Factor(dB /m)	10dB_Path Loss(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Pk Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 5.14999	48.23	Pk	34.4	-20.6	0	62.03	-	-	74	-11.97	246	100	V
2	* 5.14942	52.46	Pk	34.4	-20.7	0	66.16	-	-	74	-7.84	246	100	V
3	* 5.14999	35.82	RMS	34.4	-20.6	32	49.94	54	-4.06	-	-	246	100	V
4	* 5.14879	36.69	RMS	34.4	-20.7	32	50.71	54	-3.29	-	-	246	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection


BANDEDGE TEST DATA

Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5180	ANT1	* 5.14999	37.53	Pk	34.40	-20.60	0.00	51.33	-	-	74.00	-22.67	316	100	H
			* 5.14997	43.25	Pk	34.40	-20.60	0.00	57.05	-	-	74.00	-16.95	316	100	H
			* 5.14999	28.22	RMS	34.40	-20.60	0.14	42.16	54.00	-11.84	-	-	316	100	H
			* 5.13552	28.99	RMS	34.40	-20.80	0.14	42.73	54.00	-11.27	-	-	316	100	H
			* 5.14999	44.83	Pk	34.40	-20.60	0.00	58.63	-	-	74.00	-15.37	247	100	V
			* 5.14942	54.23	Pk	34.40	-20.70	0.00	67.93	-	-	74.00	-6.07	247	100	V
			* 5.14999	34.63	RMS	34.40	-20.60	0.14	48.57	54.00	-5.43	-	-	247	100	V
			* 5.14457	36.18	RMS	34.40	-20.80	0.14	49.92	54.00	-4.08	-	-	247	100	V
			* 5.14999	37.73	Pk	34.40	-20.60	0.00	51.53	-	-	74.00	-22.47	319	100	H
			* 5.14869	43.86	Pk	34.40	-20.70	0.00	57.56	-	-	74.00	-16.44	319	100	H
802.11n (HT20)	5180	ANT1	* 5.14999	27.85	RMS	34.40	-20.60	0.00	41.65	54.00	-12.35	-	-	319	100	H
			* 5.14759	28.92	RMS	34.40	-20.80	0.00	42.52	54.00	-11.48	-	-	319	100	H
			* 5.14999	52.26	Pk	34.40	-20.60	0.00	66.06	-	-	74.00	-7.94	253	100	V
			* 5.14599	53.89	Pk	34.40	-20.80	0.00	67.49	-	-	74.00	-6.51	253	100	V
			* 5.14999	34.39	RMS	34.40	-20.60	0.00	48.19	54.00	-5.81	-	-	253	100	V
			* 5.14832	36.37	RMS	34.40	-20.80	0.00	49.97	54.00	-4.03	-	-	253	100	V
			* 5.14999	38.73	Pk	34.40	-20.60	0.00	52.53	-	-	74.00	-21.47	288	103	H
			* 5.14947	40.30	Pk	34.40	-20.70	0.00	54.00	-	-	74.00	-20.00	288	103	H
			* 5.14999	27.81	RMS	34.40	-20.60	0.32	41.93	54.00	-12.07	-	-	288	103	H
			* 5.14949	28.95	RMS	34.40	-20.70	0.32	42.97	54.00	-11.03	-	-	288	103	H
802.11n (HT40)	5190	ANT1	* 5.14999	48.23	Pk	34.40	-20.60	0.00	62.03	-	-	74.00	-11.97	246	100	V
			* 5.14942	52.46	Pk	34.40	-20.70	0.00	66.16	-	-	74.00	-7.84	246	100	V
			* 5.14999	35.82	RMS	34.40	-20.60	0.32	49.94	54.00	-4.06	-	-	246	100	V
			* 5.14879	36.69	RMS	34.40	-20.70	0.32	50.71	54.00	-3.29	-	-	246	100	V
			* 5.14999	38.17	Pk	34.40	-20.60	0.00	51.97	-	-	74.00	-22.03	12	106	H
			* 5.13749	40.14	Pk	34.40	-20.80	0.00	53.74	-	-	74.00	-20.26	12	106	H
			* 5.14999	27.31	RMS	34.40	-20.60	0.35	41.46	54.00	-12.54	-	-	12	106	H
			* 5.14979	28.46	RMS	34.40	-20.60	0.35	42.61	54.00	-11.39	-	-	12	106	H
			* 5.14999	47.21	Pk	34.40	-20.60	0.00	61.01	-	-	74.00	-12.99	247	100	V
			* 5.14907	48.49	Pk	34.40	-20.70	0.00	62.19	-	-	74.00	-11.81	247	100	V
802.11ac (VHT80)	5210	ANT1	* 5.14999	34.48	RMS	34.40	-20.60	0.35	48.63	54.00	-5.37	-	-	247	100	V
			* 5.14794	35.02	RMS	34.40	-20.80	0.35	48.97	54.00	-5.03	-	-	247	100	V
			* 5.14999	38.17	Pk	34.40	-20.60	0.00	51.97	-	-	74.00	-22.03	12	106	H


Note1. Pk - Peak detector, RMS - RMS detector

Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

HARMONICS AND SPURIOUS EMISSIONS(WORST CASE: 802.11a / 5200 MHz)
5200 MHz HORIZONTAL



5200 MHz VERTICAL



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

5200 MHz DATA

Radiated Emissions

Frequency (GHz)	Meas Reading (dBuV)	Det	Antenna Ref Factor (dB)	Ref Antenna Path Loss (dB)	DC Corr (dB)	Corrected Reading (dBuV)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Antenna (dBi)	Height (m)	Polarity
7.8026	35.71	PK-U	35.9	-24.6	0	47.01	-	-	-	-	68.2	-21.19	0	100	H
7.80174	35.59	PK-U	35.9	-24.6	0	46.89	-	-	-	-	68.2	-21.31	0	100	V
10.4004	34.39	PK-U	37.5	-20.9	0	50.99	-	-	-	-	68.2	-17.21	0	100	H
10.40135	34.65	PK-U	37.5	-20.9	0	51.25	-	-	-	-	68.2	-16.95	0	100	V
* 15.60176	33.57	PK-U	40.2	-20.8	0	52.97	-	-	74	-21.03	-	-	0	100	H
* 15.60065	33.34	PK-U	40.2	-20.8	0	52.74	-	-	74	-21.26	-	-	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PK-U - U-NII: Maximum Peak
ADR - U-NII AD primary method, RMS average

HARMONICS AND SPURIOUS EMISSIONS TEST DATA

Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result dBuV/m	AV Limit dBuV/m	AV Margin [dB]	PK Limit dBuV/m	PK Margin [dB]	Non-Restricted [dBuV/m]	Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5180	ANT1	7.779	36.05	PK-U	35.90	-24.70	0.00	47.25	-	-	-	-	68.20	-20.95	0	100	H
			7.774	36.64	PK-U	35.90	-24.70	0.00	47.84	-	-	-	-	68.20	-20.36	0	100	V
			10.357	34.75	PK-U	37.50	-21.10	0.00	51.15	-	-	-	-	68.20	-17.05	0	100	H
			10.356	34.60	PK-U	37.50	-21.10	0.00	51.00	-	-	-	-	68.20	-17.20	0	100	V
			* 15.54046	34.90	PK-U	40.10	-21.00	0.00	54.00	-	-	74.00	-20.00	-	-	0	100	H
			* 15.53845	33.91	PK-U	40.10	-21.00	0.00	53.01	-	-	74.00	-20.99	-	-	0	100	V
	5200	ANT1	7.803	35.71	PK-U	35.90	-24.60	0.00	47.01	-	-	-	-	68.20	-21.19	0	100	H
			7.802	35.59	PK-U	35.90	-24.60	0.00	46.89	-	-	-	-	68.20	-21.31	0	100	V
			10.400	34.39	PK-U	37.50	-20.90	0.00	50.99	-	-	-	-	68.20	-17.21	0	100	H
			10.401	34.65	PK-U	37.50	-20.90	0.00	51.25	-	-	-	-	68.20	-16.95	0	100	V
			* 15.60176	33.57	PK-U	40.20	-20.80	0.00	52.97	-	-	74.00	-21.03	-	-	0	100	H
			* 15.60065	33.34	PK-U	40.20	-20.80	0.00	52.74	-	-	74.00	-21.26	-	-	0	100	V
	5240	ANT1	7.857	35.72	PK-U	35.90	-24.50	0.00	47.12	-	-	-	-	68.20	-21.08	0	100	H
			7.858	35.24	PK-U	35.90	-24.60	0.00	46.54	-	-	-	-	68.20	-21.66	0	100	V
			10.477	34.51	PK-U	37.60	-21.10	0.00	51.01	-	-	-	-	68.20	-17.19	0	100	H
			10.487	34.69	PK-U	37.60	-21.20	0.00	51.09	-	-	-	-	68.20	-17.11	0	100	V
			* 15.71337	34.86	PK-U	40.40	-20.60	0.00	54.66	-	-	74.00	-19.34	-	-	0	100	H
			* 15.72794	35.00	PK-U	40.50	-20.60	0.00	54.90	-	-	74.00	-19.10	-	-	0	100	V
802.11ac VHT80 Spot-check	5210	ANT1	7.824	35.11	PK-U	35.90	-24.50	0.00	46.51	-	-	-	-	68.20	-21.69	0	100	H
			10.427	34.53	PK-U	37.60	-21.10	0.00	51.03	-	-	-	-	68.20	-17.17	0	100	H
			* 15.63455	34.38	PK-U	40.30	-20.60	0.00	54.08	-	-	74.00	-19.92	-	-	0	100	H
			7.816	35.66	PK-U	35.90	-24.50	0.00	47.06	-	-	-	-	68.20	-21.14	0	100	V
			10.412	34.25	PK-U	37.50	-21.00	0.00	50.75	-	-	-	-	68.20	-17.45	0	100	V
			* 15.6387	34.40	PK-U	40.30	-20.50	0.00	54.20	-	-	74.00	-19.80	-	-	0	100	V


Note1. PK-U - U-NII: Maximum Peak

Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

11.2. TX ABOVE 1GHz 1TX MODE IN THE 5.3GHz BAND

BANDEDGE (WORST CASE: 802.11n HT40 / 5310 MHz Upper)

VERTICAL PEAK AND AVERAGE DATA



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	Antenna_957_Factor(dB /m)	10dB_Path Loss(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (m)	Polarity
1	* 5.35001	50.84	PK	34.7	-20.4	0	65.14	-	-	74	-8.86	250	115	V
2	* 5.35345	51.82	PK	34.7	-20.3	0	66.22	-	-	74	-7.78	250	115	V
3	* 5.35001	36.88	RMS	34.7	-20.4	-32	51.5	54	-2.5	-	-	250	115	V
4	* 5.35013	37.03	RMS	34.7	-20.4	-32	51.65	54	-2.35	-	-	250	115	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK - Peak detector

RMS - RMS detection



BANDEDGE TEST DATA

Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5320	ANT1	* 5.35001	39.83	Pk	34.70	-20.40	0.00	54.13	-	-	74.00	-19.87	107	307	H
			* 5.35431	43.54	Pk	34.70	-20.30	0.00	57.94	-	-	74.00	-16.06	107	307	H
			* 5.35001	27.77	RMS	34.70	-20.40	0.14	42.21	54.00	-11.79	-	-	107	307	H
			* 5.35903	28.73	RMS	34.70	-20.30	0.14	43.27	54.00	-10.73	-	-	107	307	H
			* 5.35001	42.34	Pk	34.70	-20.40	0.00	56.64	-	-	74.00	-17.36	247	100	V
			* 5.35237	49.75	Pk	34.70	-20.30	0.00	64.15	-	-	74.00	-9.85	247	100	V
			* 5.35001	32.25	RMS	34.70	-20.40	0.14	46.69	54.00	-7.31	-	-	247	100	V
			* 5.35199	33.45	RMS	34.70	-20.30	0.14	47.99	54.00	-6.01	-	-	247	100	V
			* 5.35001	39.58	Pk	34.70	-20.40	0.00	53.88	-	-	74.00	-20.12	135	385	H
			* 5.35307	43.13	Pk	34.70	-20.30	0.00	57.53	-	-	74.00	-16.47	135	385	H
802.11n (HT20)	5320	ANT1	* 5.35001	27.80	RMS	34.70	-20.40	0.00	42.10	54.00	-11.90	-	-	135	385	H
			* 5.35085	28.77	RMS	34.70	-20.40	0.00	43.07	54.00	-10.93	-	-	135	385	H
			* 5.35001	43.02	Pk	34.70	-20.40	0.00	57.32	-	-	74.00	-16.68	245	100	V
			* 5.35553	49.62	Pk	34.70	-20.30	0.00	64.02	-	-	74.00	-9.98	245	100	V
			* 5.35001	30.96	RMS	34.70	-20.40	0.00	45.26	54.00	-8.74	-	-	245	100	V
			* 5.36069	32.54	RMS	34.70	-20.30	0.00	46.94	54.00	-7.06	-	-	245	100	V
			* 5.35001	38.34	Pk	34.70	-20.40	0.00	52.64	-	-	74.00	-21.36	8	103	H
			* 5.35489	40.06	Pk	34.70	-20.30	0.00	54.46	-	-	74.00	-19.54	8	103	H
			* 5.35001	27.54	RMS	34.70	-20.40	0.32	42.16	54.00	-11.84	-	-	8	103	H
			* 5.35041	28.42	RMS	34.70	-20.40	0.32	43.04	54.00	-10.96	-	-	8	103	H
802.11n (HT40)	5310	ANT1	* 5.35001	50.84	Pk	34.70	-20.40	0.00	65.14	-	-	74.00	-8.86	250	115	V
			* 5.35345	51.82	Pk	34.70	-20.30	0.00	66.22	-	-	74.00	-7.78	250	115	V
			* 5.35001	36.88	RMS	34.70	-20.40	0.32	51.50	54.00	-2.50	-	-	250	115	V
			* 5.35013	37.03	RMS	34.70	-20.40	0.32	51.65	54.00	-2.35	-	-	250	115	V
			* 5.35001	40.49	Pk	34.70	-20.40	0.00	54.79	-	-	74.00	-19.21	115	326	H
			* 5.35261	41.62	Pk	34.70	-20.30	0.00	56.02	-	-	74.00	-17.98	115	326	H
			* 5.35001	28.90	RMS	34.70	-20.40	0.35	43.55	54.00	-10.45	-	-	115	326	H
			* 5.35023	29.63	RMS	34.70	-20.40	0.35	44.28	54.00	-9.72	-	-	115	326	H
			* 5.35001	44.79	Pk	34.70	-20.40	0.00	59.09	-	-	74.00	-14.91	247	100	V
			* 5.35049	47.59	Pk	34.70	-20.40	0.00	61.89	-	-	74.00	-12.11	247	100	V
802.11ac (VHT80)	5290	ANT1	* 5.35001	34.66	RMS	34.70	-20.40	0.35	49.31	54.00	-4.69	-	-	247	100	V
			* 5.35245	35.03	RMS	34.70	-20.30	0.35	49.78	54.00	-4.22	-	-	247	100	V

Note1. Pk - Peak detector, RMS - RMS detector

Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

HARMONICS AND SPURIOUS EMISSIONS(WORST CASE: 802.11a / 5300 MHz)



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

5300 MHz DATA

Radiated Emissions

Frequency (GHz)	Meas. Reading (dBuV)	Det	Antenna_967_Factor(dB/m)	60GHz_HP_Path Loss(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Altitude (m)	Height (cm)	Polarity
7.95683	35.8	PK-U	35.9	-24.4	0	47.3	-	-	-	-	68.2	-20.9	0	100	H
7.95698	34.99	PK-U	35.9	-24.4	0	46.49	-	-	-	-	68.2	-21.71	0	100	V
10.59929	34.1	PK-U	37.7	-21.2	0	50.6	-	-	-	-	68.2	-17.6	0	100	H
10.59931	34.93	PK-U	37.7	-21.2	0	51.43	-	-	-	-	68.2	-16.77	0	100	V
* 15.90814	33.28	PK-U	40.8	-19.8	0	54.28	-	-	74	-19.72	-	-	0	100	H
* 15.89975	33.46	PK-U	40.8	-19.9	0	54.36	-	-	74	-19.64	-	-	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

HARMONICS AND SPURIOUS EMISSIONS TEST DATA

Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result dBuV/m	AV Limit dBuV/m	AV Margin [dB]	PK Limit dBuV/m	PK Margin [dB]	Non-Restricted [dBuV/m]	Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5260	ANT1	7.899	35.57	PK-U	35.90	-24.40	0.00	47.07	-	-	-	-	68.20	-21.13	0	100	H
			7.897	35.72	PK-U	35.90	-24.40	0.00	47.22	-	-	-	-	68.20	-20.98	0	100	V
			10.513	34.29	PK-U	37.60	-21.10	0.00	50.79	-	-	-	-	68.20	-17.41	0	100	H
			10.525	34.86	PK-U	37.60	-21.20	0.00	51.26	-	-	-	-	68.20	-16.94	0	100	V
			* 15.78173	34.56	PK-U	40.60	-20.50	0.00	54.66	-	-	74.00	-19.34	-	-	0	100	H
			* 15.77092	34.33	PK-U	40.50	-20.60	0.00	54.23	-	-	74.00	-19.77	-	-	0	100	V
	5300	ANT1	7.957	35.80	PK-U	35.90	-24.40	0.00	47.30	-	-	-	-	68.20	-20.90	0	100	H
			7.957	34.99	PK-U	35.90	-24.40	0.00	46.49	-	-	-	-	68.20	-21.71	0	100	V
			10.599	34.10	PK-U	37.70	-21.20	0.00	50.60	-	-	-	-	68.20	-17.60	0	100	H
			10.594	34.93	PK-U	37.70	-21.20	0.00	51.43	-	-	-	-	68.20	-16.77	0	100	V
			* 15.90814	33.28	PK-U	40.80	-19.80	0.00	54.28	-	-	74.00	-19.72	-	-	0	100	H
			* 15.89975	33.46	PK-U	40.80	-19.90	0.00	54.36	-	-	74.00	-19.64	-	-	0	100	V
	5320	ANT1	7.977	36.48	PK-U	35.90	-24.40	0.00	47.98	-	-	-	-	68.20	-20.22	0	100	H
			7.989	35.62	PK-U	35.90	-24.40	0.00	47.12	-	-	-	-	68.20	-21.08	0	100	V
			* 10.64124	34.18	PK-U	37.70	-21.10	0.00	50.78	-	-	74.00	-23.22	-	-	0	100	H
			* 10.64419	34.03	PK-U	37.70	-21.20	0.00	50.53	-	-	74.00	-23.47	-	-	0	100	V
			* 15.95575	33.90	PK-U	40.90	-19.80	0.00	55.00	-	-	74.00	-19.00	-	-	0	100	H
			* 15.95715	33.77	PK-U	40.90	-19.70	0.00	54.97	-	-	74.00	-19.03	-	-	0	100	V


Note1. PK-U - U-NII: Maximum Peak / ADR - U-NII AD primary method, RMS average

Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

11.3. TX ABOVE 1GHz 1TX MODE IN THE 5.5 GHz BAND

BANDEDGE (WORST CASE: 802.11n HT20 / 5500 MHz)

VERTICAL PEAK AND AVERAGE DATA



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	Antenna_957_Factor(dB)	10dB_Path Loss(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (m)	Polarity
1	* 5.45998	50.18	PK	34.9	-20.1	0	64.98	-	-	74	-9.02	250	105	V
2	* 5.45739	50.9	PK	34.9	-20.1	0	65.6	-	-	74	-9.4	250	105	V
3	5.46998	48.98	PK	34.9	-20.2	0	63.68	-	-	68.2	-4.52	250	105	V
4	5.46869	51.29	PK	34.9	-20.2	0	65.99	-	-	68.2	-2.21	250	105	V
5	* 5.45998	32.26	RMS	34.9	-20.1	0	47.06	54	-6.94	-	-	250	105	V
6	* 5.45976	33.35	RMS	34.9	-20.1	0	48.15	54	-5.85	-	-	250	105	V
7	5.46998	32.5	RMS	34.9	-20.2	0	47.2	-	-	-	-	250	105	V
8	5.46563	33.92	RMS	34.9	-20.1	0	48.72	-	-	-	-	250	105	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PK - Peak detector
RMS - RMS detection


BANDEDGE TEST DATA

Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5500	ANT1	* 5.45998	38.27	Pk	34.90	-20.10	0.00	53.07	-	-	74.00	-20.93	36	100	H
			* 5.45716	41.03	Pk	34.90	-20.10	0.00	55.83	-	-	74.00	-18.17	36	100	H
			5.46998	37.15	Pk	34.90	-20.20	0.00	51.85	-	-	68.20	-16.35	36	100	H
			5.46105	42.27	Pk	34.90	-20.20	0.00	56.97	-	-	68.20	-11.23	36	100	H
			* 5.45998	27.50	RMS	34.90	-20.10	0.14	42.44	54.00	-11.56	-	-	36	100	H
			* 5.45841	28.10	RMS	34.90	-20.10	0.14	43.04	54.00	-10.96	-	-	36	100	H
			5.46998	27.51	RMS	34.90	-20.20	0.14	42.35	-	-	-	-	36	100	H
			5.46972	28.15	RMS	34.90	-20.20	0.14	42.99	-	-	-	-	36	100	H
			* 5.45998	47.84	Pk	34.90	-20.10	0.00	62.64	-	-	74.00	-11.36	252	118	V
			* 5.45574	50.47	Pk	34.90	-20.20	0.00	65.17	-	-	74.00	-8.83	252	118	V
			5.46998	49.63	Pk	34.90	-20.20	0.00	64.33	-	-	68.20	-3.87	252	118	V
			5.46989	51.27	Pk	34.90	-20.20	0.00	65.97	-	-	68.20	-2.23	252	118	V
			* 5.45998	32.13	RMS	34.90	-20.10	0.14	47.07	54.00	-6.93	-	-	252	118	V
			* 5.45466	33.35	RMS	34.90	-20.10	0.14	48.29	54.00	-5.71	-	-	252	118	V
			5.46998	32.09	RMS	34.90	-20.20	0.14	46.93	-	-	-	-	252	118	V
			5.46994	34.21	RMS	34.90	-20.20	0.14	49.05	-	-	-	-	252	118	V
	5700	ANT1	5.72500	39.22	Pk	35.00	-19.80	0.00	54.42	-	-	68.20	-13.78	142	365	H
			5.72563	41.63	Pk	35.00	-19.80	0.00	56.83	-	-	68.20	-11.37	142	365	H
			5.72500	48.04	Pk	35.00	-19.80	0.00	63.24	-	-	68.20	-4.96	245	100	V
			5.72689	48.91	Pk	35.00	-19.80	0.00	64.11	-	-	68.20	-4.09	245	100	V
			* 5.45998	39.18	Pk	34.90	-20.10	0.00	53.98	-	-	74.00	-20.02	15	100	H
			* 5.45917	41.81	Pk	34.90	-20.10	0.00	56.61	-	-	74.00	-17.39	15	100	H
802.11n (HT20)	5500	ANT1	5.46998	37.30	Pk	34.90	-20.20	0.00	52.00	-	-	68.20	-16.20	15	100	H
			5.46083	42.02	Pk	34.90	-20.20	0.00	56.72	-	-	68.20	-11.48	15	100	H
			* 5.45998	27.57	RMS	34.90	-20.10	0.00	42.37	54.00	-11.63	-	-	15	100	H
			* 5.43764	28.20	RMS	34.90	-20.10	0.00	43.00	54.00	-11.00	-	-	15	100	H
			5.46998	27.34	RMS	34.90	-20.20	0.00	42.04	-	-	-	-	15	100	H
			5.46779	28.36	RMS	34.90	-20.20	0.00	43.06	-	-	-	-	15	100	H
			* 5.45998	50.18	Pk	34.90	-20.10	0.00	64.98	-	-	74.00	-9.02	250	105	V
			* 5.45738	50.80	Pk	34.90	-20.10	0.00	65.60	-	-	74.00	-8.40	250	105	V
			5.46998	48.98	Pk	34.90	-20.20	0.00	63.68	-	-	68.20	-4.52	250	105	V
			5.46869	51.29	Pk	34.90	-20.20	0.00	65.99	-	-	68.20	-2.21	250	105	V
			* 5.45998	32.26	RMS	34.90	-20.10	0.00	47.06	54.00	-6.94	-	-	250	105	V
			* 5.45976	33.35	RMS	34.90	-20.10	0.00	48.15	54.00	-5.85	-	-	250	105	V
			5.46998	32.50	RMS	34.90	-20.20	0.00	47.20	-	-	-	-	250	105	V
			5.46563	33.92	RMS	34.90	-20.10	0.00	48.72	-	-	-	-	250	105	V
	5700	ANT1	5.72500	38.36	Pk	35.00	-19.80	0.00	53.56	-	-	68.20	-14.64	112	366	H
			5.72902	42.29	Pk	35.00	-19.80	0.00	57.49	-	-	68.20	-10.71	112	366	H
			5.72500	46.16	Pk	35.00	-19.80	0.00	61.36	-	-	68.20	-6.84	247	106	V
			5.72713	49.88	Pk	35.00	-19.80	0.00	65.08	-	-	68.20	-3.12	247	106	V
			* 5.45998	37.39	Pk	34.90	-20.10	0.00	52.19	-	-	74.00	-21.81	15	100	H
			* 5.45867	40.51	Pk	34.90	-20.10	0.00	55.31	-	-	74.00	-18.69	15	100	H
802.11n (HT40)	5510	ANT1	5.46998	38.14	Pk	34.90	-20.20	0.00	52.84	-	-	68.20	-15.36	15	100	H
			5.46547	41.13	Pk	34.90	-20.20	0.00	55.83	-	-	68.20	-12.37	15	100	H
			* 5.45998	26.81	RMS	34.90	-20.10	0.32	41.93	54.00	-12.07	-	-	15	100	H
			* 5.43904	28.16	RMS	34.90	-20.10	0.32	43.28	54.00	-10.72	-	-	15	100	H
			5.46998	28.40	RMS	34.90	-20.20	0.32	43.42	-	-	-	-	15	100	H
			5.46952	28.87	RMS	34.90	-20.20	0.32	43.89	-	-	-	-	15	100	H
			* 5.45998	47.43	Pk	34.90	-20.10	0.00	62.23	-	-	74.00	-11.77	245	103	V
			* 5.45978	49.69	Pk	34.90	-20.10	0.00	64.49	-	-	74.00	-9.51	245	103	V
			5.46998	50.12	Pk	34.90	-20.20	0.00	64.82	-	-	68.20	-3.38	245	103	V
			5.46869	51.07	Pk	34.90	-20.20	0.00	65.77	-	-	68.20	-2.43	245	103	V
			* 5.45998	32.79	RMS	34.90	-20.10	0.32	47.91	54.00	-6.09	-	-	245	103	V
			* 5.45996	33.41	RMS	34.90	-20.10	0.32	48.53	54.00	-5.47	-	-	245	103	V
			5.46998	36.88	RMS	34.90	-20.20	0.32	51.90	-	-	-	-	245	103	V
			5.46967	37.16	RMS	34.90	-20.20	0.32	52.18	-	-	-	-	245	103	V
	5670	ANT1	5.72500	38.06	Pk	35.00	-19.80	0.00	53.26	-	-	68.20	-14.94	135	364	H
			5.72938	41.08	Pk	35.00	-19.80	0.00	56.28	-	-	68.20	-11.92	135	364	H
			5.72500	46.36	Pk	35.00	-19.80	0.00	61.56	-	-	68.20	-6.64	250	116	V
			5.72632	47.93	Pk	35.00	-19.80	0.00	63.13	-	-	68.20	-5.07	250	116	V
			* 5.45998	37.08	Pk	34.90	-20.10	0.00	51.88	-	-	74.00	-22.12	13	100	H
			* 5.45399	40.25	Pk	34.90	-20.10	0.00	55.05	-	-	74.00	-18.95	13	100	H
802.11ac (VHT80)	5530	ANT1	5.46998	37.97	Pk	34.90	-20.20	0.00	52.67	-	-	68.20	-15.53	13	100	H
			5.46121	40.60	Pk	34.90	-20.20	0.00	55.30	-	-	68.20	-12.90	13	100	H
			* 5.45998	27.26	RMS	34.90	-20.10	0.35	42.41	54.00	-11.59	-	-	13	100	H
			* 5.45788	28.71	RMS	34.90	-20.10	0.35	43.86	54.00	-10.14	-	-	13	100	H
			5.46998	28.05	RMS	34.90	-20.20	0.35	43.10	-	-	-	-	13	100	H
			5.46819	28.92	RMS	34.90	-20.20	0.35	43.97	-	-	-	-	13	100	H
			* 5.45998	46.23	Pk	34.90	-20.10	0.00	61.03	-	-	74.00	-12.97	250	118	V
			* 5.45987	48.50	Pk	34.90	-20.10	0.00	63.30	-	-	74.00	-10.70	250	118	V
			5.46998	47.04	Pk	34.90	-20.20	0.00	61.74	-	-	68.20	-6.46	250	118	V
			5.46549	49.79	Pk	34.90	-20.20	0.00	64.49	-	-	68.20	-3.71	250	118	V
			* 5.45998	35.25	RMS	34.90	-20.10	0.35	50.40	54.00	-3.60	-	-	250	118	V
			* 5.45795	35.64	RMS	34.90	-20.10	0.35	50.79	54.00	-3.21	-	-	250	118	V
			5.46998	36.25	RMS	34.90	-20.20	0.35	51.30	-	-	-	-	250	118	V
			5.46716	36.85	RMS	34.90	-20.20	0.35	51.90	-	-	-	-	250	118	V
	5610	ANT1	5.72500	37.49	Pk	35.00	-19.80	0.00	52.69	-	-	68.20	-15.51	135	365	H
			5.81336	39.20	Pk	35.10	-19.60	0.00	54.70	-	-	68.20	-13.50	135	365	H
			5.72500	39.37	Pk	35.00	-19.80	0.00	54.57	-	-	68.20	-13.63	250	120	V
			5.73399	42.11	Pk	35.00	-19.80	0.00	57.31	-	-	68.20	-10.89	250	120	V

Note1. Pk - Peak detector, RMS - RMS detector

Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

HARMONICS AND SPURIOUS EMISSIONS(WORST CASE: 802.11a / 5500 MHz)



Note. Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

5500 MHz DATA

Radiated Emissions

Frequency (GHz)	Meas. Reading (dBuV)	Det	Antenna_567_Factor(dB)	5GHz_HP_Path Loss(dB)	DC Cor (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Actuals (dBi)	Height (cm)	Polarity
* 8.24694	36.35	PK-U	36	-23.8	0	48.55	-	-	74	-25.45	-	-	0	100	H
* 11.00121	33.3	PK-U	38	-21	0	50.3	-	-	74	-23.7	-	-	0	100	H
16.50141	34.03	PK-U	41.6	-18.8	0	56.83	-	-	74	-17.17	68.2	-11.37	0	100	H
* 8.25784	36.43	PK-U	36	-23.8	0	48.63	-	-	74	-25.37	-	-	0	100	V
* 11.00002	34.05	PK-U	38	-21.1	0	50.95	-	-	74	-23.05	-	-	0	100	V
16.50011	34.56	PK-U	41.6	-18.7	0	57.46	-	-	-	-	68.2	-10.74	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band
PK-U - U-NII: Maximum Peak
ADR - U-NII AD primary method, RMS average

HARMONICS AND SPURIOUS EMISSIONS TEST DATA


Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result dBuV/m	AV Limit dBuV/m	AV Margin [dB]	PK Limit dBuV/m	PK Margin [dB]	Non-Restricted [dBuV/m]	Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5500	ANT1	* 8.24694	36.35	PK-U	36.00	-23.80	0.00	48.55	-	-	74.00	-25.45	-	-	0	100	H
			* 11.00121	33.30	PK-U	38.00	-21.00	0.00	50.30	-	-	74.00	-23.70	-	-	0	100	H
			16.501	34.03	PK-U	41.60	-18.80	0.00	56.83	-	-	-	-	68.20	-11.37	0	100	H
			* 8.25784	36.43	PK-U	36.00	-23.80	0.00	48.63	-	-	74.00	-25.37	-	-	0	100	V
			* 11.00002	34.05	PK-U	38.00	-21.10	0.00	50.95	-	-	74.00	-23.05	-	-	0	100	V
			16.500	34.56	PK-U	41.60	-18.70	0.00	57.46	-	-	-	-	68.20	-10.74	0	100	V
	5580	ANT1	* 8.37929	36.58	PK-U	36.00	-23.70	0.00	48.88	-	-	74.00	-25.12	-	-	0	100	H
			* 11.15973	35.30	PK-U	38.10	-21.50	0.00	51.90	-	-	74.00	-22.10	-	-	0	100	H
			16.736	33.62	PK-U	41.80	-18.30	0.00	57.12	-	-	-	-	68.20	-11.08	0	100	H
			* 8.37675	36.34	PK-U	36.00	-23.70	0.00	48.64	-	-	74.00	-25.36	-	-	0	100	V
			* 11.15864	34.75	PK-U	38.10	-21.50	0.00	51.35	-	-	74.00	-22.65	-	-	0	100	V
			16.750	33.25	PK-U	41.80	-18.20	0.00	56.85	-	-	-	-	68.20	-11.35	0	100	V
	5700	ANT1	8.556	35.68	PK-U	36.00	-23.50	0.00	48.18	-	-	-	-	68.20	-20.02	0	100	H
			* 11.402	33.24	PK-U	38.10	-21.30	0.00	50.04	-	-	74.00	-23.96	-	-	0	100	H
			17.099	32.41	PK-U	41.40	-17.30	0.00	56.51	-	-	-	-	68.20	-11.69	0	100	H
			8.552	35.57	PK-U	36.00	-23.50	0.00	48.07	-	-	-	-	68.20	-20.13	0	100	V
			* 11.39145	33.37	PK-U	38.10	-21.40	0.00	50.07	-	-	74.00	-23.93	-	-	0	100	V
			17.105	31.45	PK-U	41.40	-17.30	0.00	55.55	-	-	-	-	68.20	-12.65	0	100	V
	5720	ANT1	8.581	35.47	PK-U	36.00	-23.40	0.00	48.07	-	-	-	-	68.20	-20.13	0	100	H
			* 11.44073	33.65	PK-U	38.20	-21.30	0.00	50.55	-	-	74.00	-23.45	-	-	0	100	H
			17.159	32.46	PK-U	41.30	-17.10	0.00	56.66	-	-	-	-	68.20	-11.54	0	100	H
			8.585	34.88	PK-U	36.00	-23.40	0.00	47.48	-	-	-	-	68.20	-20.72	0	100	V
			* 11.44411	33.22	PK-U	38.20	-21.20	0.00	50.22	-	-	74.00	-23.78	-	-	0	100	V
			17.168	32.40	PK-U	41.30	-16.90	0.00	56.80	-	-	-	-	68.20	-11.40	0	100	V

Note1. PK-U - U-NII: Maximum Peak / ADR - U-NII AD primary method, RMS average
Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

11.4. TX ABOVE 1GHz 1TX MODE IN THE 5.8 GHz BAND

BANDEDGE (WORST CASE: 802.11n HT20 / 5745 MHz)

HORIZONTAL PEAK DATA



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBm)	Det	Antenna_957_F actor(dB/m)	10dB_Path Loss(dB)	Conversion Factor (dB)	DC Corr (dB)	Corrected Reading EIRP	Peak Limit (dBm)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	5.725	-50.05	Pk	34.9	-19.8	11.8	0	-23.15	27	-50.15	250	115	V
2	5.62885	-59.15	Pk	34.9	-20	11.8	0	-32.45	-27	-5.45	250	115	V



Pk - Peak detector

BANDEDGE TEST DATA

Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBm]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	Conv. F [dB]	DC Corr [dB]	Result [dBm]	PK Limit [dBm]	PK Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5745	ANT1	5.72500	-61.30	Pk	34.90	-19.80	11.80	0.00	-34.40	27.00	-61.40	122	361	H
			5.62693	-63.42	Pk	34.90	-20.00	11.80	0.00	-36.72	-27.00	-9.72	122	361	H
			5.72500	-52.35	Pk	34.90	-19.80	11.80	0.00	-25.45	27.00	-52.45	244	100	V
			5.64203	-59.37	Pk	34.90	-20.00	11.80	0.00	-32.67	-27.00	-5.67	244	100	V
	5825	ANT1	5.85001	-65.55	Pk	35.20	-19.60	11.80	0.00	-38.15	26.99	-65.14	210	100	H
			5.94177	-64.04	Pk	35.60	-19.30	11.80	0.00	-35.94	-27.00	-8.94	210	100	H
			5.85001	-59.83	Pk	35.20	-19.60	11.80	0.00	-32.43	26.99	-59.42	245	100	V
			5.93982	-63.09	Pk	35.60	-19.40	11.80	0.00	-35.09	-27.00	-8.09	245	100	V
802.11n (HT20)	5745	ANT1	5.72500	-60.71	Pk	34.90	-19.80	11.80	0.00	-33.81	27.00	-60.81	120	361	H
			5.62521	-63.17	Pk	34.90	-20.00	11.80	0.00	-36.47	-27.00	-9.47	120	361	H
			5.72500	-50.05	Pk	34.90	-19.80	11.80	0.00	-23.15	27.00	-50.15	250	115	V
			5.62885	-59.15	Pk	34.90	-20.00	11.80	0.00	-32.45	-27.00	-5.45	250	115	V
	5825	ANT1	5.85001	-65.60	Pk	35.20	-19.60	11.80	0.00	-38.20	26.99	-65.19	210	100	H
			5.95759	-63.49	Pk	35.60	-19.30	11.80	0.00	-35.39	-27.00	-8.39	210	100	H
			5.85001	-58.33	Pk	35.20	-19.60	11.80	0.00	-30.93	26.99	-57.92	250	111	V
			5.95322	-63.13	Pk	35.60	-19.30	11.80	0.00	-35.03	-27.00	-8.03	250	111	V
802.11n (HT40)	5755	ANT1	5.72500	-60.72	Pk	34.90	-19.80	11.80	0.00	-33.82	27.00	-60.82	120	360	H
			5.63935	-63.55	Pk	34.90	-20.00	11.80	0.00	-36.85	-27.00	-9.85	120	360	H
			5.72500	-50.43	Pk	34.90	-19.80	11.80	0.00	-23.53	27.00	-50.53	250	135	V
			5.63829	-60.09	Pk	34.90	-20.00	11.80	0.00	-33.39	-27.00	-6.39	250	135	V
	5795	ANT1	5.85001	-65.70	Pk	35.20	-19.60	11.80	0.00	-38.30	26.99	-65.29	209	100	H
			5.98180	-63.87	Pk	35.70	-19.30	11.80	0.00	-35.67	-27.00	-8.67	209	100	H
			5.85001	-60.54	Pk	35.20	-19.60	11.80	0.00	-33.14	26.99	-60.13	263	100	V
			5.99392	-63.35	Pk	35.70	-19.20	11.80	0.00	-35.05	-27.00	-8.05	263	100	V
802.11ac (VHT80)	5775 (Lower Side)	ANT1	5.72500	-62.20	Pk	34.90	-19.80	11.80	0.00	-35.30	27.00	-62.30	120	361	H
			5.64930	-63.41	Pk	34.90	-19.90	11.80	0.00	-36.61	-27.00	-9.61	120	361	H
			5.72500	-53.76	Pk	34.90	-19.80	11.80	0.00	-26.86	27.00	-53.86	250	115	V
			5.64601	-60.64	Pk	34.90	-20.00	11.80	0.00	-33.94	-27.00	-6.94	250	115	V
	5775 (Upper Side)	ANT1	5.85001	-64.28	Pk	35.20	-19.60	11.80	0.00	-36.88	26.99	-63.87	186	400	H
			5.92662	-62.84	Pk	35.50	-19.40	11.80	0.00	-34.94	-27.00	-7.94	186	400	H
			5.85001	-61.77	Pk	35.20	-19.60	11.80	0.00	-34.37	26.99	-61.36	263	100	V
			5.99105	-63.57	Pk	35.70	-19.20	11.80	0.00	-35.27	-27.00	-8.27	263	100	V

Note. Pk - Peak detector

HARMONICS AND SPURIOUS EMISSIONS(WORST CASE: 802.11a / 5745 MHz)



Note: Emission was scanned up to 40GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

5745 MHz DATA

Radiated Emissions

Frequency (GHz)	Meas. Reading (dBuV)	Det	Antenna Gain Factor (dB)	60GHz HP Path Loss (dB)	DC Corr (dB)	Corrected Reading (dBuV)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	UNII Non-Restricted (dBuV/m)	Margin (dB)	Acquish (dB)	Height (cm)	Polarity
8.60824	35.99	PK-U	36	-23.4	0	48.59	-	-	-	-	68.2	-19.61	0	100	H
* 11.49542	34.31	PK-U	36.2	-21.4	0	51.11	-	-	74	-22.89	-	-	0	100	H
17.23855	33.53	PK-U	41.1	-16.5	0	56.13	-	-	-	-	68.2	-10.07	0	100	H
8.61488	34.73	PK-U	36	-23.5	0	47.23	-	-	-	-	68.2	-20.97	0	100	V
* 11.49679	33.83	PK-U	38.2	-21.4	0	50.63	-	-	74	-23.37	-	-	0	100	V
17.23777	32.98	PK-U	41.1	-16.5	0	57.58	-	-	-	-	68.2	-10.62	0	100	V

* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PK-U - U-NII: Maximum Peak

ADR - U-NII AD primary method, RMS average

HARMONICS AND SPURIOUS EMISSIONS TEST DATA


Mode	Freq. [MHz]	Antenna	Frequency [GHz]	Reading [dBuV]	Detector Mode	ANT Factor [dB/m]	Loss [dB]	DC Corr [dB]	Result [dBuV/m]	AV Limit [dBuV/m]	AV Margin [dB]	PK Limit [dBuV/m]	PK Margin [dB]	Non-Restricted [dBuV/m]	Margin [dB]	Azimuth [Degs]	Height [cm]	Polarity
802.11a	5745	ANT1	8.608	35.99	PK-U	36.00	-23.40	0.00	48.59	-	-	-	-	68.20	-19.61	0	100	H
			* 11.49542	34.31	PK-U	38.20	-21.40	0.00	51.11	-	-	74.00	-22.89	-	-	0	100	H
			17.239	33.53	PK-U	41.10	-16.50	0.00	58.13	-	-	-	-	68.20	-10.07	0	100	H
			8.614	34.73	PK-U	36.00	-23.50	0.00	47.23	-	-	-	-	68.20	-20.97	0	100	V
			* 11.49679	33.83	PK-U	38.20	-21.40	0.00	50.63	-	-	74.00	-23.37	-	-	0	100	V
			17.238	32.98	PK-U	41.10	-16.50	0.00	57.58	-	-	-	-	68.20	-10.62	0	100	V
	5785	ANT1	8.680	34.60	PK-U	36.10	-23.20	0.00	47.50	-	-	-	-	68.20	-20.70	0	100	H
			* 11.57806	34.26	PK-U	38.30	-21.60	0.00	50.96	-	-	74.00	-23.04	-	-	0	100	H
			17.363	32.87	PK-U	41.10	-16.60	0.00	57.37	-	-	-	-	68.20	-10.83	0	100	H
			8.679	35.06	PK-U	36.10	-23.20	0.00	47.96	-	-	-	-	68.20	-20.24	0	100	V
			* 11.57379	34.97	PK-U	38.20	-21.50	0.00	51.67	-	-	74.00	-22.33	-	-	0	100	V
			17.346	32.81	PK-U	41.10	-16.50	0.00	57.41	-	-	-	-	68.20	-10.79	0	100	V
	5825	ANT1	8.733	36.34	PK-U	36.10	-23.10	0.00	49.34	-	-	-	-	68.20	-18.86	0	100	H
			* 11.65352	34.56	PK-U	38.30	-21.60	0.00	51.26	-	-	74.00	-22.74	-	-	0	100	H
			17.473	32.63	PK-U	41.10	-16.30	0.00	57.43	-	-	-	-	68.20	-10.77	0	100	H
			8.736	35.46	PK-U	36.10	-23.10	0.00	48.46	-	-	-	-	68.20	-19.74	0	100	V
			* 11.65478	34.13	PK-U	38.30	-21.60	0.00	50.83	-	-	74.00	-23.17	-	-	0	100	V
			17.476	32.53	PK-U	41.20	-16.30	0.00	57.43	-	-	-	-	68.20	-10.77	0	100	V
802.11n (HT20) Spot-Check	5825	ANT1	8.734	34.77	PK-U	36.10	-23.10	0.00	47.77	-	-	-	-	68.20	-20.43	0	100	H
			* 11.65057	34.49	PK-U	38.30	-21.60	0.00	51.19	-	-	74.00	-22.81	-	-	0	100	H
			17.480	32.40	PK-U	41.20	-16.40	0.00	57.20	-	-	-	-	68.20	-11.00	0	100	H
			8.728	35.36	PK-U	36.10	-23.10	0.00	48.36	-	-	-	-	68.20	-19.84	0	100	V
			* 11.65615	34.63	PK-U	38.30	-21.70	0.00	51.23	-	-	74.00	-22.77	-	-	0	100	V
			17.477	33.11	PK-U	41.20	-16.40	0.00	57.91	-	-	-	-	68.20	-10.29	0	100	V
802.11n (HT40) Spot-Check	5795	ANT1	8.689	34.53	PK-U	36.10	-23.30	0.00	47.33	-	-	-	-	68.20	-20.87	0	100	H
			* 11.5936	35.14	PK-U	38.30	-21.70	0.00	51.74	-	-	74.00	-22.26	-	-	0	100	H
			17.391	33.15	PK-U	41.10	-16.50	0.00	57.75	-	-	-	-	68.20	-10.45	0	100	H
			8.683	34.66	PK-U	36.10	-23.30	0.00	47.46	-	-	-	-	68.20	-20.74	0	100	V
			* 11.5914	34.54	PK-U	38.30	-21.70	0.00	51.14	-	-	74.00	-22.86	-	-	0	100	V
			17.386	32.70	PK-U	41.10	-16.60	0.00	57.20	-	-	-	-	68.20	-11.00	0	100	V

Note1. PK-U - U-NII: Maximum Peak / ADR - U-NII AD primary method, RMS average


Note2. * - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

12. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna, 845_Factor(dB/m)	Below_1G_Path Loss(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	OPK Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	47.7528	38.08	Pk	19.8	-31.8	0	26.08	40	-13.92	0-360	300	H
3	174.2539	49.27	Pk	14.6	-30.9	0	32.97	43.52	-10.55	0-360	100	H
5	350.036	38.8	Pk	20.5	-30.1	0	29.2	46.02	-16.82	0-360	100	H
2	46.6857	43.67	Pk	19.7	-31.9	0	31.47	40	-8.53	0-360	100	V
4	* 173.1868	44.11	Pk	14.5	-30.9	0	27.71	43.52	-15.81	0-360	100	V
6	534.549	40.18	Pk	23	-29.8	0	33.38	46.02	-12.64	0-360	300	V

Pk - Peak detector

13. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)
IC RSS-GEN Clause 8.8

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

WORST EMISSIONS

LINE 1 DATA



Trace Markers


Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_L1 [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
1	.15	40.92	Pk	9.7	.1	50.72	66	-15.28	-	-
2	.15	27.26	Av	9.7	.1	37.06	-	-	56	-18.94
3	.18	36.28	Pk	9.9	.1	46.28	64.49	-18.21	-	-
4	.186	19.41	Av	9.9	.1	29.41	-	-	54.21	-24.8
5	.414	32.78	Pk	9.8	.1	42.68	57.57	-14.89	-	-
6	.414	18.29	Av	9.8	.1	28.19	-	-	47.57	-19.38
7	2.457	26.22	Pk	9.7	.1	36.02	56	-19.98	-	-
8	2.382	11.21	Av	9.7	.1	21.01	-	-	46	-24.99
9	3.807	26.88	Pk	9.7	.1	36.68	56	-19.32	-	-
10	3.75	12.04	Av	9.7	.1	21.84	-	-	46	-24.16
11	6.051	27.29	Pk	9.8	.2	37.29	60	-22.71	-	-
12	5.871	12.93	Av	9.8	.2	22.93	-	-	50	-27.07

Pk - Peak detector

Av - Average detection

LINE 2 DATA



Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_Wit h EX_N [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
13	.162	38.25	Pk	9.9	.1	48.25	65.36	-17.11	-	-
14	.168	22.9	Av	10	.1	33	-	-	55.06	-22.06
15	.198	34.16	Pk	9.9	.1	44.16	63.69	-19.53	-	-
16	.204	16.63	Av	9.8	.1	26.53	-	-	53.45	-26.92
17	.417	31.52	Pk	9.8	.1	41.42	57.51	-16.09	-	-
18	.417	17.26	Av	9.8	.1	27.16	-	-	47.51	-20.35
19	1.038	22.1	Pk	9.7	.1	31.9	56	-24.1	-	-
20	1.005	9.95	Av	9.7	.1	19.75	-	-	46	-26.25
21	2.106	21.01	Pk	9.7	.1	30.81	56	-25.19	-	-
22	2.169	8.74	Av	9.7	.1	18.54	-	-	46	-27.46
23	7.158	20.75	Pk	9.8	.2	30.75	60	-29.25	-	-
24	7.209	7.67	Av	9.8	.2	17.67	-	-	50	-32.33

Pk - Peak detector

Av - Average detection

14. DYNAMIC FREQUENCY SELECTION

14.1. OVERVIEW

14.1.1. LIMITS

FCC

§15.407 (h), FCC KDB 905462 D02 “COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION” and KDB 905462 D03 “U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY”.

Table 1: Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar DFS	Client (without DFS)
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in all 20 MHz channel blocks and a null frequency between the bonded 20 MHz channel blocks.

Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes)
E.I.R.P. $\geq$ 200 mill watt	-64 dBm
E.I.R.P. < 200 mill watt and power spectral density < 10 dBm/MHz	-62 dBm
E.I.R.P. < 200 mill watt that do not meet power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: E.I.R.P. is based on the highest antenna gain. For SISO devices refer to KDB publication 662911 D01.	

Table 4: DFS Response requirement values

Parameter	Value
<i>Non-occupancy period</i>	30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds (See Note 1)
<i>Channel Closing Transmission Time</i>	200 milliseconds + approx. 60 milliseconds over remaining 10 second period. (See Notes 1 and 2)
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. (See Note 3)
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (usec)	PRI (usec)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in table 5a	Roundup: (1/360) x (19 x 10 ⁶ PRI _{usec})	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 usec. With a minimum increment of 1 usec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the <i>Detection Bandwidth</i> test, <i>Channel Move Time</i> , and <i>Channel Closing Time</i> tests.					

Table 6 – Long Pulse Radar Test Signal


Radar Waveform Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 7 – Frequency Hopping Radar Test Signal

Radar Waveform Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

14.1.2. TEST AND MEASUREMENT SYSTEM

CONDUCTED METHOD SYSTEM BLOCK DIAGRAM



SYSTEM OVERVIEW

The short pulse and long pulse signal generating system utilizes the Keysite Signal Studio for Pulse Building as N5172B. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.

The short pulse types 1, 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of KDB 905462 D02. The frequency of the signal generator is incremented in 1 MHz steps from F_L to F_H for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

SYSTEM CALIBRATION

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a horn antenna via a coaxial cable, with the reference level offset set to (horn antenna gain – coaxial cable loss). The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of –64 dBm as measured on the spectrum analyzer.

Without changing any of the instrument settings, the spectrum analyzer is reconnected to the Common port of the Spectrum Analyzer Combiner/Divider. The Reference Level Offset of the spectrum analyzer is adjusted so that the displayed amplitude of the signal is –64 dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of –64 dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

ADJUSTMENT OF DISPLAYED TRAFFIC LEVEL

A link is established between the Master and Slave and the distance between the units is adjusted as needed to provide a suitable received level at the Master and Slave devices. The video test file is streamed to generate WLAN traffic. The monitoring antenna is adjusted so that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold.


TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the DFS tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	S/N	Next Cal Due
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY54200580	07-23-25
Vector Signal Generator, 6GHz	Agilent / HP	N5182B	MY53051241	07-24-25
Combiner	WEINSCHEL	WA1534	UL001	01-16-25
Combiner	WEINSCHEL	WA1534	UL003	01-02-25

14.1.3. SETUP OF EUT

CONDUCTED METHOD EUT TEST SETUP



SUPPORT EQUIPMENT

The following support equipment was utilized for the DFS tests documented in this report:

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
Wireless Access Point	ASUS	GT-AXE11000	M3IAJF200742	MSQ-RTAXJF00
Notebook PC (Controller/Server)	HP	HP EliteDesk 800 G1 TWR	CZC4125J25	DoC

14.1.4. DESCRIPTION OF EUT

The EUT operates over the 5250-5350 MHz and 5470-5725 MHz ranges.

The EUT is a Slave Device without Radar Detection.

The highest power level of the widest bandwidth (802.11ac VHT80) within these bands is 13.16 dBm in the 5250-5350 MHz band and 5470-5725 MHz band.

The antenna assembly utilized two antenna.

Gain of ANT1 : -5.60 dBi for UNII 2A and -5.80 dBi for UNII 2C.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required conducted threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

The EUT uses one transmitter/receiver chain connected to an antenna to perform radiated tests. WLAN traffic that meets or exceeds the minimum required loading was generated by transferring a data stream from the controller/server PC to the EUT using iPerf version 2.0.5 software package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11 architecture. 4 nominal channel bandwidth are implemented: 20 MHz, 40 MHz, 80 MHz.

The software installed in the access point is 12.4(25d)JA1.

UNIFORM CHANNEL SPREADING

This requirement is not applicable to Slave radio devices.

OVERVIEW OF MASTER DEVICE WITH RESPECT TO §15.407 (h) REQUIREMENTS

The Master Device is a ASUS Access Point, FCC ID: MSQ-RTAXJF00. The minimum antenna gain for the Master Device is 6 dBi.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

14.2. RESULTS FOR 80 MHz BANDWIDTH (UNII-2A BAND)

14.2.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5290 MHz.

14.2.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



14.2.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.2.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS


Channel Move Time (sec)	Limit (sec)
0.775	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
4.125	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME


No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.



14.1. RESULTS FOR 80 MHz BANDWIDTH (UNII-2C BAND)

14.1.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5530 MHz.

14.1.2. RADAR WAVEFORM AND TRAFFIC

RADAR WAVEFORM



14.1.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.1.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS


Channel Move Time (sec)	Limit (sec)
0.714	10

Aggregate Channel Closing Transmission Time (msec)	Limit (msec)
4.500	60

MOVE TIME & CHANNEL CLOSING TIME

AGGREGATE CHANNEL CLOSING TRANSMISSION TIME


No transmissions are observed during the aggregate monitoring period.



NON-OCCUPANCY PERIOD

RESULTS

No EUT transmissions were observed on the test channel during the 10-minute observation time.



END OF TEST REPORT