

TEST REPORT

FCC ULCA 48C Test for SM-A176U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2510-FC027-R1

DATE OF ISSUE
November 20, 2025

Tested by
Jae Ryang Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO



HCT CO.,LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2510-FC027-R1

DATE OF ISSUE

November 20, 2025

Additional Model

SM-A176U1, SM-S176V

Applicant

SAMSUNG Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-A176U

Date of Test

August 28, 2025 ~ September 29, 2025

FCC ID

A3LSMA176U

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

Citizens Band End User Devices (CBE)

Test Standard Used

FCC Rule Part: § 96

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	October 15, 2025	Initial Release
1	November 20, 2025	Revised the Emission Designator (Page 6.)

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER.....	6
2. INTRODUCTION	7
2.1. DESCRIPTION OF EUT	7
2.2. MEASURING INSTRUMENT CALIBRATION	7
2.3. TEST FACILITY	7
2.4. EQUIPMENT.....	7
3. DESCRIPTION OF TESTS	8
3.1 TEST PROCEDURE.....	8
3.2 RADIATED POWER.....	9
3.3 RADIATED SPURIOUS EMISSIONS.....	10
3.4 PEAK- TO- AVERAGE RATIO	11
3.5 OCCUPIED BANDWIDTH.....	13
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	14
3.7 CHANNEL EDGE.....	15
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	16
3.9 Adjacent Channel Leakage Ratio	17
4. LIST OF TEST EQUIPMENT.....	18
5. MEASUREMENT UNCERTAINTY	19
6. SUMMARY OF TEST RESULTS	20
7. SAMPLE CALCULATION.....	21
8. TEST DATA.....	23
8.1 Conducted Power	26
8.2 Equivalent Isotropic Radiated Power.....	29
8.3 Conducted Spurious Emissions.....	32
8.4 Channel Edge.....	51
8.5 Frequency Stability / Variation Of Ambient Temperature.....	66
8.6 Radiated Spurious Emissions	74
8.7 Occupied Bandwidth	77
8.8 Peak- to- Average Ratio.....	83
8.9 Adjacent Channel Leakage Ratio(ACLR)	89
9. ANNEX A_ TEST SETUP PHOTO	93

MEASUREMENT REPORT

1. GENERAL INFORMATION

Model(s):	SM-A176U
Additional Model(s)	SM-A176U1, SM-S176V
Tx Frequency:	3553.3 - 3690.0: 5 MHz+20 MHz 3555.5 - 3690.0: 10 MHz+20 MHz 3557.8 - 3690.0: 15 MHz+20 MHz 3560.0 - 3696.7: 20 MHz+5 MHz 3560.0 - 3694.5: 20 MHz+10 MHz 3560.0 - 3692.2: 20 MHz+15 MHz 3560.0 - 3690.0: 20 MHz+20 MHz
Serial number:	Radiated : R3CY70RH2BA Conducted : R3CY70RH2BA
LTE CA :	CA 48C (Uplink)
Antenna Information	Please refer to the Antenna Specification document.

1.1. MAXIMUM OUTPUT POWER

Mode (PCC+SCC)	Tx Frequency (MHz)	Modulation	Emission Designator	EIRP	
				Max. Power (dBm)	Max. Power (W)
5 MHz+20 MHz	3553.3 - 3690.0	QPSK	22M8G7D	15.09	0.032
		16QAM	22M8W7D	15.59	0.036
		64QAM	22M8W7D	15.50	0.035
		256QAM	23M0W7D	15.46	0.035
10 MHz+20 MHz	3555.5 - 3690.0	QPSK	27M6G7D	14.44	0.028
		16QAM	27M5W7D	14.88	0.031
		64QAM	27M6W7D	14.84	0.030
		256QAM	27M6W7D	14.76	0.030
15 MHz+20 MHz	3557.8 - 3690.0	QPSK	32M8G7D	14.44	0.028
		16QAM	32M4W7D	14.80	0.030
		64QAM	32M6W7D	14.75	0.030
		256QAM	32M8W7D	14.64	0.029
20 MHz+5 MHz	3560.0 - 3696.7	QPSK	22M8G7D	15.27	0.034
		16QAM	22M9W7D	15.66	0.037
		64QAM	22M8W7D	15.64	0.037
		256QAM	22M8W7D	15.55	0.036
20 MHz+10 MHz	3560.0 - 3694.5	QPSK	27M8G7D	14.50	0.028
		16QAM	27M9W7D	14.80	0.030
		64QAM	27M8W7D	14.74	0.030
		256QAM	27M7W7D	14.56	0.029
20 MHz+15 MHz	3560.0 - 3692.2	QPSK	32M5G7D	14.35	0.027
		16QAM	32M9W7D	14.73	0.030
		64QAM	32M7W7D	14.70	0.030
		256QAM	32M6W7D	14.58	0.029
20 MHz+20 MHz	3560.0 - 3690.0	QPSK	37M6G7D	16.15	0.041
		16QAM	37M6W7D	16.53	0.045
		64QAM	37M8W7D	16.47	0.044
		256QAM	37M7W7D	16.26	0.042

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea.

Detailed description of test facility was submitted to the Commission and accepted dated March 11, 2024 (Registration Number: KR0032).

2.4. EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to ANSI/USEMCSC C63.2-2023, "American National Standard for Specifications of Electromagnetic Interference and Field Strength Measuring Instrumentation in the Frequency Range 9 kHz to 40 GHz".

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Channel Edge/ ACLR	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7 - KDB 940660 D01 v01
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- KDB 971168 D01 v03r01 - Section 5.2.4 - ANSI C63.26-2015 - Section 5.2.1 & 5.2.4.2
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated. The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = RMS
4. Trace Mode = trace average
5. Sweep time $>$ (Number of points in sweep $\times$ Transmitter period)
6. Number of points in sweep $\geq 2 \times \text{Span} / \text{RBW}$

3.7 CHANNEL EDGE



Test setup

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. Within 1 MHz of the channel edge the RBW should be 2 % of EBW, then 1 MHz after that.
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep Time > (Number of Points) $\times$ (Symbol Period)
9. The trace was allowed to stabilize


Test Notes

The conducted power of any emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0-10 megahertz above the upper SAS-assigned channel edge and within 0-10 megahertz below the lower SAS-assigned channel edge. At all frequencies greater than 10 megahertz above the upper SAS assigned channel edge and less than 10 MHz below the lower SAS assigned channel edge, the conducted power of any emission shall not exceed -25 dBm/MHz .

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40 dBm/MHz

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz/RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.


2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 Adjacent Channel Leakage Ratio



Test setup

Test Settings

1. Use ACP measurement function of Spectrum analyzer to measure adjacent channel leakage ratio
2. Integ BW = Assigned channel bandwidth
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = Sweep time > Number of points in sweep $\times$ Transmitter period
9. The trace was allowed to stabilize

Test Notes

the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1.2 G HPF+LNA)	HCT CO., LTD.	F1L1	11/11/2025	Annual
RF Switching System	Switch box(3.3 G HPF+LNA)	HCT CO., LTD.	F1L2	11/11/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.	F1L4	11/11/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.	F1L7	11/11/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/10/2026	Annual
DC Power Supply	E3632A	Agilent	MY40010147	07/29/2026	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/11/2026	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/07/2026	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	08/27/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/23/2027	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/14/2026	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/10/2026	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	07/28/2026	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	07/29/2026	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	11/13/2025	Annual
Radio Communication Test Station	MT8000A	Anritsu Corp.	6272613402	08/18/2026	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/22/2026	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/14/2026	Annual
Signal Analyzer(2 Hz ~ 50.0 GHz)	N9040B	KEYSIGHT	US55230216	12/09/2025	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	05/27/2026	Annual
Automation Software	FCC 2G/3G/4G Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC NR Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC LTE Radiated	HCT CO., LTD	-	-	-
Automation Software	FCC NR Radiated	HCT CO., LTD	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)

Parameter	Expanded Uncertainty ($\pm$ kHz)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.68 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.75 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

-. The decision rule applies 'simple acceptance'

6.1 Test Condition: Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 96.41(e)	■ -13 dBm/MHz at frequencies within 0-10 MHz of channel edge ■ -25 dBm/MHz at frequencies greater than 10 MHz above and below channel edge ■ -40 dBm/MHz at frequencies below 3530 MHz and above 3720 MHz	PASS
Adjacent Channel Leakage Ratio	§ 96.41(e)	At least 30 dB.	PASS
Conducted Output Power	§ 2.1046	N/A	PASS
Frequency stability / variation of ambient temperature	§ 2.1055,	Emission must remain in band	PASS
Peak- to- Average Ratio	§ 96.41	< 13 dB	PASS

6.2 Test Condition: Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 96.41(b)	23 dBm/10 MHz	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 96.41(e)	-40 dBm/MHz	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA

Test Overview

The EUT is set up to transmit two contiguous LTE channels. The power level of both carriers and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Note

1. All tests were evaluated for the two contiguous channels using various combinations of RB size, RB offset, modulation, and channel bandwidth.
2. Channel bandwidth is shown in the tables below based only on the channel bandwidths that were supported in this device.

Channel Bandwidth (PCC)	Channel Bandwidth (SCC)	Maximum aggregated bandwidth (MHz)
5	20	25
10	20	30
15	20	35
20	5	25
20	10	30
20	15	35
20	20	40

3. All modes of operation were investigated and the worst case configuration results are reported in this section.
Please refer to the table below.

- Worst case(Conducted Spurious Emissions, Band Edge)
: We have selected higher of the Conduction Output Power.
- Worst case(Radiated Spurious Emissions) : We have selected higher of the EIRP.
- Worst case(OBW, PAR, Frequency stability)
: All modes of operation were investigated and the worst case configuration results are reported.

4. All modes of operation were investigated and the worst case configuration results are reported.

Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)

Worst case : Stand alone

5. All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.

Therefore, only the worst case(stand-alone) results were reported.

6. All 3 channels(low/mid/high) of conducted power and radiated power were investigated and the worst case channel results are reported.

[Worst case]

Test Description	Mod	Operating frequency	PCC					SCC				
			BW (MHz)	Freq. (MHz)	Ch.	RB	RB Offset	BW (MHz)	Freq. (MHz)	Ch.	RB	RB Offset
Conducted Spurious Emissions/ Band Edge	16QAM	Low	20	3560.0	55340	1	99	20	3579.8	55538	1	0
		Mid	20	3615.1	55891	1	99	20	3634.9	56089	1	0
		High	20	3670.2	56442	1	99	20	3690.0	56640	1	0
		Low	20	3560.0	55340	1	0	20	3579.8	55538	1	99
		Mid	20	3615.1	55891	1	0	20	3634.9	56089	1	99
		High	20	3670.2	56442	1	0	20	3690.0	56640	1	99
		Low	20	3560.0	55340	100	0	20	3579.8	55538	100	0
		Mid	20	3615.1	55891	100	0	20	3634.9	56089	100	0
		High	20	3670.2	56442	100	0	20	3690.0	56640	100	0
Radiated Spurious Emissions	16QAM	Low	20	3560.0	55340	1	99	20	3579.8	55538	1	0
		Mid	20	3615.1	55891	1	99	20	3634.9	56089	1	0
		High	20	3670.2	56442	1	99	20	3690.0	56640	1	0

[Worst case]

Test Description	Mod	Operating frequency	PCC					SCC				
			BW (MHz)	Freq. (MHz)	Ch.	RB	RB Offset	BW (MHz)	Freq. (MHz)	Ch.	RB	RB Offset
OBW, PAR	QPSK, 16QAM, 64QAM, 256QAM	Mid	5	3615.8	55898	25	0	20	3627.5	56015	100	0
			10	3615.6	55896	50	0	20	3630.0	56040	100	0
			15	3615.3	55893	75	0	20	3632.4	56064	100	0
			20	3622.5	55965	100	0	5	3634.2	56082	25	0
			20	3620.1	55941	100	0	10	3634.5	56085	50	0
			20	3617.6	55916	100	0	15	3634.7	56087	75	0
			20	3615.1	55891	100	0	20	3634.9	56089	100	0
Frequency stability	16QAM	Low	5	3553.3	55273	25	0	20	3565.0	55390	100	0
			10	3555.5	55295	50	0	20	3569.9	55439	100	0
			15	3557.8	55318	75	0	20	3574.9	55489	50	0
			20	3560.0	55340	100	0	20	3579.8	55538	100	0
		High	5	3678.3	56523	25	0	20	3690.0	56640	100	0
			10	3675.6	56496	50	0	20	3690.0	56640	100	0
			15	3672.9	56469	75	0	20	3690.0	56640	50	0
			20	3670.2	56442	100	0	20	3690.0	56640	100	0

8.1 Conducted Power

Operating frequency	PCC					SCC					Conducted. Power [dBm]
	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	
Low	5	3553.3	55273	1	24	20	55390	3565.0	1	0	15.61
	10	3555.5	55295	1	49	20	55439	3569.9	1	0	14.98
	15	3557.8	55318	1	74	20	55489	3574.9	1	0	15.31
	20	3560.0	55340	1	99	5	55457	3571.7	1	0	16.63
	20	3560.0	55340	1	99	10	55484	3574.4	1	0	15.67
	20	3560.0	55340	1	99	15	55511	3577.1	1	0	15.70
	20	3560.0	55340	1	99	20	55538	3579.8	1	0	17.72
Mid	5	3615.8	55898	1	24	20	56015	3627.5	1	0	17.28
	10	3615.6	55896	1	49	20	56040	3630.0	1	0	16.18
	15	3615.3	55893	1	74	20	56064	3632.4	1	0	15.92
	20	3622.5	55965	1	99	5	56082	3634.2	1	0	16.10
	20	3620.1	55941	1	99	10	56085	3634.5	1	0	15.30
	20	3617.6	55916	1	99	15	56087	3634.7	1	0	15.52
	20	3615.1	55891	1	99	20	56089	3634.9	1	0	17.74
High	5	3678.3	56523	1	24	20	56640	3690.0	1	0	13.15
	10	3675.6	56496	1	49	20	56640	3690.0	1	0	12.19
	15	3672.9	56469	1	74	20	56640	3690.0	1	0	12.17
	20	3685.0	56590	1	99	5	56707	3696.7	1	0	13.07
	20	3680.1	56541	1	99	10	56685	3694.5	1	0	12.01
	20	3675.1	56491	1	99	15	56662	3692.2	1	0	12.09
	20	3670.2	56442	1	99	20	56640	3690.0	1	0	14.19

Note:

Modulation : QPSK(1RB)

Operating frequency	PCC					SCC					Conducted. Power [dBm]
	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	
Low	5	3553.3	55273	25	0	20	55390	3565.0	100	0	8.89
	10	3555.5	55295	50	0	20	55439	3569.9	100	0	10.10
	15	3557.8	55318	75	0	20	55489	3574.9	100	0	10.31
	20	3560.0	55340	100	0	5	55457	3571.7	25	0	9.41
	20	3560.0	55340	100	0	10	55484	3574.4	50	0	10.45
	20	3560.0	55340	100	0	15	55511	3577.1	75	0	10.49
	20	3560.0	55340	100	0	20	55538	3579.8	100	0	10.57
Mid	5	3615.8	55898	25	0	20	56015	3627.5	100	0	10.41
	10	3615.6	55896	50	0	20	56040	3630.0	100	0	11.38
	15	3615.3	55893	75	0	20	56064	3632.4	100	0	11.37
	20	3622.5	55965	100	0	5	56082	3634.2	25	0	9.87
	20	3620.1	55941	100	0	10	56085	3634.5	50	0	11.04
	20	3617.6	55916	100	0	15	56087	3634.7	75	0	11.18
	20	3615.1	55891	100	0	20	56089	3634.9	100	0	11.39
High	5	3678.3	56523	25	0	20	56640	3690.0	100	0	6.35
	10	3675.6	56496	50	0	20	56640	3690.0	100	0	7.41
	15	3672.9	56469	75	0	20	56640	3690.0	100	0	7.46
	20	3685.0	56590	100	0	5	56707	3696.7	25	0	6.36
	20	3680.1	56541	100	0	10	56685	3694.5	50	0	7.34
	20	3675.1	56491	100	0	15	56662	3692.2	75	0	7.43
	20	3670.2	56442	100	0	20	56640	3690.0	100	0	7.51

Note:

Modulation : QPSK(Full RB)

Operating frequency	PCC					SCC					Conducted. Power [dBm]
	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	
Low	20	3560.0	55340	1	99	20	3579.8	55538	1	0	18.50
Mid	20	3615.1	55891	1	99	20	3634.9	56089	1	0	18.63
High	20	3670.2	56442	1	99	20	3690.0	56640	1	0	15.01
Low	20	3560.0	55340	100	0	20	3579.8	55538	100	0	10.69
Mid	20	3615.1	55891	100	0	20	3634.9	56089	100	0	11.51
High	20	3670.2	56442	100	0	20	3690.0	56640	100	0	7.64

Note:

Modulation : 16QAM

Operating frequency	PCC					SCC					Conducted. Power [dBm]
	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	
Low	20	3560.0	55340	1	99	20	3579.8	55538	1	0	18.06
Mid	20	3615.1	55891	1	99	20	3634.9	56089	1	0	18.12
High	20	3670.2	56442	1	99	20	3690.0	56640	1	0	14.48
Low	20	3560.0	55340	100	0	20	3579.8	55538	100	0	10.67
Mid	20	3615.1	55891	100	0	10	3634.9	56089	100	0	11.48
High	20	3670.2	56442	100	0	20	3690.0	56640	100	0	7.63

Note:

Modulation : 64QAM

Operating frequency	PCC					SCC					Conducted. Power [dBm]
	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	Bandwidth [MHz]	Freq. (MHz)	Channel	RB	RB Offset	
Low	20	3560.0	55340	1	99	20	3579.8	55538	1	0	18.01
Mid	20	3615.1	55891	1	99	20	3634.9	56089	1	0	18.11
High	20	3670.2	56442	1	99	20	3690.0	56640	1	0	14.44
Low	20	3560.0	55340	100	0	20	3579.8	55538	100	0	10.66
Mid	20	3615.1	55891	100	0	10	3634.9	56089	100	0	11.44
High	20	3670.2	56442	100	0	20	3690.0	56640	100	0	7.60

Note:

Modulation : 256QAM

8.2 Equivalent Isotropic Radiated Power

	PCC			SCC			Measured	Substitute	Ant.	C.L	Pol.	E.I.R.P	
	BW [MHz]	Channel	RB/ Offset	BW [MHz]	Channel	RB/ Offset	Level (dBm)	Level (dBm)	Gain (dBi)			W	dBm
Low	5	55273	1/24	20	55390	1/0	-33.92	5.15	12.38	3.09	H	0.028	14.44
	10	55295	1/49	20	55439	1/0	-34.73	4.34	12.38	3.09	H	0.023	13.63
	15	55318	1/74	20	55489	1/0	-34.66	4.47	12.37	3.09	H	0.024	13.75
	20	55340	1/99	5	55457	1/0	-33.66	5.47	12.37	3.09	H	0.030	14.75
	20	55340	1/99	10	55484	1/0	-34.58	4.55	12.37	3.09	H	0.024	13.83
	20	55340	1/99	15	55511	1/0	-34.65	4.55	12.36	3.09	H	0.024	13.82
	20	55340	1/99	20	55538	1/0	-32.99	6.21	12.36	3.09	H	0.035	15.48
Mid	5	55898	1/24	20	56015	1/0	-33.37	5.97	12.26	3.14	H	0.032	15.09
	10	55896	1/49	20	56040	1/0	-34.02	5.32	12.26	3.14	H	0.028	14.44
	15	55893	1/74	20	56064	1/0	-34.04	5.32	12.25	3.13	H	0.028	14.44
	20	55965	1/99	5	56082	1/0	-33.21	6.15	12.25	3.13	H	0.034	15.27
	20	55941	1/99	10	56085	1/0	-33.98	5.38	12.25	3.13	H	0.028	14.50
	20	55916	1/99	15	56087	1/0	-34.13	5.23	12.25	3.13	H	0.027	14.35
	20	55891	1/99	20	56089	1/0	-32.33	7.03	12.25	3.13	H	0.041	16.15
High	5	56523	1/24	20	56640	1/0	-34.57	4.88	12.27	3.10	H	0.025	14.06
	10	56496	1/49	20	56640	1/0	-35.26	4.19	12.27	3.10	H	0.022	13.37
	15	56469	1/74	20	56640	1/0	-35.33	4.18	12.26	3.11	H	0.022	13.33
	20	56590	1/99	5	56707	1/0	-34.19	5.20	12.28	3.08	H	0.028	14.41
	20	56541	1/99	10	56685	1/0	-35.23	4.22	12.27	3.10	H	0.022	13.40
	20	56491	1/99	15	56662	1/0	-35.40	4.05	12.27	3.10	H	0.021	13.23
	20	56442	1/99	20	56640	1/0	-33.52	5.99	12.26	3.11	H	0.033	15.14

Note:

1. Modulation : QPSK
2. Limit : < 23 dBm

	PCC			SCC			Measured	Substitute	Ant.	C.L	Pol.	E.I.R.P	
	BW [MHz]	Channel	RB/Offset	BW [MHz]	Channel	RB/Offset	Level (dBm)	Level (dBm)	Gain (dBi)			W	dBm
Low	5	55273	1/24	20	55390	1/0	-33.55	5.52	12.38	3.09	H	0.030	14.81
	10	55295	1/49	20	55439	1/0	-34.23	4.84	12.38	3.09	H	0.026	14.13
	15	55318	1/74	20	55489	1/0	-34.30	4.83	12.37	3.09	H	0.026	14.11
	20	55340	1/99	5	55457	1/0	-33.32	5.81	12.37	3.09	H	0.032	15.09
	20	55340	1/99	10	55484	1/0	-34.14	4.99	12.37	3.09	H	0.027	14.27
	20	55340	1/99	15	55511	1/0	-34.20	5.00	12.36	3.09	H	0.027	14.27
	20	55340	1/99	20	55538	1/0	-32.50	6.70	12.36	3.09	H	0.040	15.97
Mid	5	55898	1/24	20	56015	1/0	-32.87	6.47	12.26	3.14	H	0.036	15.59
	10	55896	1/49	20	56040	1/0	-33.58	5.76	12.26	3.14	H	0.031	14.88
	15	55893	1/74	20	56064	1/0	-33.68	5.68	12.25	3.13	H	0.030	14.80
	20	55965	1/99	5	56082	1/0	-32.82	6.54	12.25	3.13	H	0.037	15.66
	20	55941	1/99	10	56085	1/0	-33.68	5.68	12.25	3.13	H	0.030	14.80
	20	55916	1/99	15	56087	1/0	-33.75	5.61	12.25	3.13	H	0.030	14.73
	20	55891	1/99	20	56089	1/0	-31.95	7.41	12.25	3.13	H	0.045	16.53
High	5	56523	1/24	20	56640	1/0	-34.17	5.28	12.27	3.10	H	0.028	14.46
	10	56496	1/49	20	56640	1/0	-35.04	4.41	12.27	3.10	H	0.023	13.59
	15	56469	1/74	20	56640	1/0	-34.96	4.55	12.26	3.11	H	0.023	13.70
	20	56590	1/99	5	56707	1/0	-33.86	5.53	12.28	3.08	H	0.030	14.74
	20	56541	1/99	10	56685	1/0	-34.94	4.51	12.27	3.10	H	0.023	13.69
	20	56491	1/99	15	56662	1/0	-34.90	4.55	12.27	3.10	H	0.024	13.73
	20	56442	1/99	20	56640	1/0	-33.05	6.46	12.26	3.11	H	0.036	15.61

Note:

1. Modulation : 16QAM
2. Limit : < 23 dBm

PCC			SCC			Measured	Substitute	Ant.			E.I.R.P	
BW [MHz]	Channel	RB/ Offset	BW [MHz]	Channel	RB/ Offset	Level (dBm)	Level (dBm)	Gain (dBi)	C.L	Pol.	W	dBm
20	55340	1/99	20	55538	1/0	-32.54	6.66	12.36	3.09	H	0.039	15.93
5	55898	1/24	20	56015	1/0	-32.96	6.38	12.26	3.14	H	0.035	15.50
10	55896	1/49	20	56040	1/0	-33.62	5.72	12.26	3.14	H	0.030	14.84
15	55893	1/74	20	56064	1/0	-33.73	5.63	12.25	3.13	H	0.030	14.75
20	55965	1/99	5	56082	1/0	-32.84	6.52	12.25	3.13	H	0.037	15.64
20	55941	1/99	10	56085	1/0	-33.74	5.62	12.25	3.13	H	0.030	14.74
20	55916	1/99	15	56087	1/0	-33.78	5.58	12.25	3.13	H	0.030	14.70
20	55891	1/99	20	56089	1/0	-32.01	7.35	12.25	3.13	H	0.044	16.47
20	56442	1/99	20	56640	1/0	-33.16	6.35	12.26	3.11	H	0.035	15.50

Note:

1. Modulation : 64QAM
2. Limit : < 23 dBm

PCC			SCC			Measured	Substitute	Ant.			E.I.R.P	
BW [MHz]	Channel	RB/ Offset	BW [MHz]	Channel	RB/ Offset	Level (dBm)	Level (dBm)	Gain (dBi)	C.L	Pol.	W	dBm
20	55340	1/99	20	55538	1/0	-32.73	6.47	12.36	3.09	H	0.037	15.74
5	55898	1/24	20	56015	1/0	-33.00	6.34	12.26	3.14	H	0.035	15.46
10	55896	1/49	20	56040	1/0	-33.70	5.64	12.26	3.14	H	0.030	14.76
15	55893	1/74	20	56064	1/0	-33.84	5.52	12.25	3.13	H	0.029	14.64
20	55965	1/99	5	56082	1/0	-32.93	6.43	12.25	3.13	H	0.036	15.55
20	55941	1/99	10	56085	1/0	-33.92	5.44	12.25	3.13	H	0.029	14.56
20	55916	1/99	15	56087	1/0	-33.90	5.46	12.25	3.13	H	0.029	14.58
20	55891	1/99	20	56089	1/0	-32.22	7.14	12.25	3.13	H	0.042	16.26
20	56442	1/99	20	56640	1/0	-33.33	6.18	12.26	3.11	H	0.034	15.33

Note:

1. Modulation : 256QAM
2. Limit : < 23 dBm

8.3 Conducted Spurious Emissions

Operating frequency	PCC				SCC				Measurement	Factor (dB)	Measurement	Result (dBm)
	BW [MHz]	Ch.	Freq. (MHz)	RB/ Offset	BW [MHz]	Ch.	Freq. (MHz)	RB/ Offset	Maximum Frequency (GHz)		Maximum Data (dBm)	
Low	20	55340	3560.0	1/99	20	55538	3579.8	1/0	3.4991	31.955	-86.08	-54.13
Mid	20	55891	3615.1	1/99	20	56089	3634.9	1/0	8.2792	32.570	-86.70	-54.13
High	20	56442	3670.2	1/99	20	56640	3690.0	1/0	3.4731	31.955	-83.80	-51.85
Low	20	55340	3560.0	1/0	20	55538	3579.8	1/99	8.2877	32.570	-86.57	-54.00
Mid	20	55891	3615.1	1/0	20	56089	3634.9	1/99	8.2607	32.570	-87.53	-54.96
High	20	56442	3670.2	1/0	20	56640	3690.0	1/99	8.2752	32.570	-87.68	-55.11
Low	20	55340	3560.0	100/0	20	55538	3579.8	100/0	8.2847	32.570	-87.66	-55.09
Mid	20	55891	3615.1	100/0	20	56089	3634.9	100/0	8.2752	32.570	-87.49	-54.92
High	20	56442	3670.2	100/0	20	56640	3690.0	100/0	8.2792	32.570	-87.32	-54.75

Note:


1. Modulation : 16QAM
2. Duty Cycle factor already applied on the factor.
- Duty Cycle factor(dB) = 3.979
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB) + Duty Cycle factor(dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	29.249
1 – 5	31.955
5 – 10	32.570
10 – 15	33.095
15 – 20	33.468
Above 20(26.5)	34.110

5. Limit : -40.0 dBm

Frequency Range : 30 MHz ~ 10 GHz

PCC 20MHz Ch55340 RB1 Offset0 SCC 20MHz Ch55538 RB1 Offset99



PCC 20MHz Ch55340 RB1 Offset99 SCC 20MHz Ch55538 RB1 Offset0



PCC 20MHz Ch55340 RB100 Offset0 SCC 20MHz Ch55538 RB100 Offset0



PCC 20MHz Ch55891 RB1 Offset0 SCC 20MHz Ch56089 RB1 Offset99



PCC 20MHz Ch55891 RB1 Offset99 SCC 20MHz Ch56089 RB1 Offset0



PCC 20MHz Ch55891 RB100 Offset0 SCC 20MHz Ch56089 RB100 Offset0



PCC 20MHz Ch56442 RB1 Offset0 SCC 20MHz Ch56640 RB1 Offset99



PCC 20MHz Ch56442 RB1 Offset99 SCC 20MHz Ch56640 RB1 Offset0



PCC 20MHz Ch56442 RB100 Offset0 SCC 20MHz Ch56640 RB100 Offset0



Frequency Range : 10 GHz ~ 26.5 GHz

PCC 20MHz Ch55340 RB1 Offset0, SCC 20MHz Ch55538 RB1 Offset99



PCC 20MHz Ch55340 RB1 Offset99, SCC 20MHz Ch55538 RB1 Offset0



PCC 20MHz Ch55340 RB100 Offset0, SCC 20MHz Ch55538 RB100 Offset0



PCC 20MHz Ch55891 RB1 Offset0, SCC 20MHz Ch56089 RB1 Offset99



PCC 20MHz Ch55891 RB1 Offset99, SCC 20MHz Ch56089 RB1 Offset0



PCC 20MHz Ch55891 RB100 Offset0, SCC 20MHz Ch56089 RB100 Offset0



PCC 20MHz Ch56442 RB1 Offset0, SCC 20MHz Ch56640 RB1 Offset99



PCC 20MHz Ch56442 RB1 Offset99, SCC 20MHz Ch56640 RB1 Offset0



PCC 20MHz Ch56442 RB100 Offset0, SCC 20MHz Ch56640 RB100 Offset0




8.4 Channel Edge


PCC 20MHz Ch56442 RB100 Offset0, SCC 20MHz Ch56640 RB100 Offset0-2




PCC 20MHz Ch56442 RB100 Offset0, SCC 20MHz Ch56640 RB100 Offset0-1




PCC 20MHz Ch56442 RB1 Offset99, SCC 20MHz Ch56640 RB1 Offset0-2




PCC 20MHz Ch56442 RB1 Offset99, SCC 20MHz Ch56640 RB1 Offset0-1




PCC 20MHz Ch56442 RB1 Offset0, SCC 20MHz Ch56640 RB1 Offset99-2




PCC 20MHz Ch56442 RB1 Offset0, SCC 20MHz Ch56640 RB1 Offset99-1




PCC 20MHz Ch55891 RB100 Offset0, SCC 20MHz Ch56089 RB100 Offset0



PCC 20MHz Ch55891 RB1 Offset99, SCC 20MHz Ch56089 RB1 Offset0



PCC 20MHz Ch55891 RB1 Offset0, SCC 20MHz Ch56089 RB1 Offset99




PCC 20MHz Ch55340 RB100 Offset0, SCC 20MHz Ch55538 RB100 Offset0-2




PCC 20MHz Ch55340 RB100 Offset0, SCC 20MHz Ch55538 RB100 Offset0-1




PCC 20MHz Ch55340 RB1 Offset99, SCC 20MHz Ch55538 RB1 Offset0-2




PCC 20MHz Ch55340 RB1 Offset99, SCC 20MHz Ch55538 RB1 Offset0-1



PCC 20MHz Ch55340 RB1 Offset0, SCC 20MHz Ch55538 RB1 Offset99-2



PCC 20MHz Ch55340 RB1 Offset0, SCC 20MHz Ch55538 RB1 Offset99-1



8.5 Frequency Stability / Variation Of Ambient Temperature

▣ PCC Channel:	55273	
▣ PCC Frequency:	3553.3	MHz
▣ PCC BandWidth:	5	MHz
▣ SCC Channel:	55390	
▣ SCC Frequency:	3565.0	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0009	-0.0044	3553.30094	3565.00436
100 %		-30	0.0011	-0.0028	3553.29895	3565.00279
100 %		-20	-0.0085	-0.0103	3553.30851	3565.01035
100 %		-10	-0.0034	-0.0075	3553.30336	3565.00745
100 %		0	-0.0026	-0.0030	3553.30262	3565.00300
100 %		10	-0.0088	-0.0042	3553.30884	3565.00417
100 %		30	-0.0033	-0.0017	3553.30327	3565.00172
100 %		40	-0.0033	-0.0021	3553.30326	3565.00208
100 %		50	-0.0074	-0.0050	3553.30744	3565.00499
Batt. Endpoint	3.400	20	-0.0087	-0.0069	3553.30868	3565.00693

▣ PCC Channel:	55295	
▣ PCC Frequency:	3555.5	MHz
▣ PCC BandWidth:	10	MHz
▣ SCC Channel:	55439	
▣ SCC Frequency:	3569.9	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0057	-0.0014	3555.50574	3569.90136
100 %		-30	0.0010	-0.0103	3555.49905	3569.91029
100 %		-20	-0.0097	-0.0103	3555.50971	3569.91035
100 %		-10	-0.0038	-0.0079	3555.50376	3569.90785
100 %		0	-0.0088	-0.0013	3555.50882	3569.90130
100 %		10	-0.0019	-0.0120	3555.50194	3569.91197
100 %		30	-0.0026	-0.0023	3555.50257	3569.90232
100 %		40	-0.0046	-0.0051	3555.50456	3569.90508
100 %		50	-0.0021	-0.0046	3555.50214	3569.90459
Batt. Endpoint	3.400	20	-0.0002	-0.0100	3555.50018	3569.91003

▣ PCC Channel:	55318	
▣ PCC Frequency:	3557.8	MHz
▣ PCC BandWidth:	15	MHz
▣ SCC Channel:	55489	
▣ SCC Frequency:	3574.9	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0078	-0.0078	3557.80784	3574.90776
100 %		-30	0.0028	-0.0079	3557.79725	3574.90789
100 %		-20	-0.0008	-0.0017	3557.80081	3574.90175
100 %		-10	-0.0086	-0.0063	3557.80856	3574.90625
100 %		0	-0.0015	0.0007	3557.80152	3574.89930
100 %		10	-0.0032	-0.0093	3557.80324	3574.90927
100 %		30	-0.0085	-0.0051	3557.80847	3574.90512
100 %		40	-0.0072	-0.0035	3557.80716	3574.90348
100 %		50	-0.0027	-0.0050	3557.80274	3574.90499
Batt. Endpoint	3.400	20	-0.0014	-0.0049	3557.80138	3574.90493

▣ PCC Channel:	55340	
▣ PCC Frequency:	3560.0	MHz
▣ PCC BandWidth:	20	MHz
▣ SCC Channel:	55538	
▣ SCC Frequency:	3579.8	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0063	-0.0046	3560.00634	3579.80456
100 %		-30	0.0025	-0.0063	3559.99755	3579.80629
100 %		-20	-0.0014	-0.0036	3560.00141	3579.80365
100 %		-10	-0.0015	-0.0123	3560.00146	3579.81225
100 %		0	-0.0044	0.0005	3560.00442	3579.79950
100 %		10	-0.0041	-0.0093	3560.00414	3579.80927
100 %		30	-0.0108	-0.0018	3560.01077	3579.80182
100 %		40	-0.0067	-0.0053	3560.00666	3579.80528
100 %		50	-0.0101	-0.0031	3560.01014	3579.80309
Batt. Endpoint	3.400	20	-0.0065	-0.0062	3560.00648	3579.80623

▣ PCC Channel:	56523	
▣ PCC Frequency:	3678.3	MHz
▣ PCC BandWidth:	5	MHz
▣ SCC Channel:	56640	
▣ SCC Frequency:	3690.0	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0083	-0.0057	3678.30834	3690.00566
100 %		-30	-0.0042	-0.0091	3678.30425	3690.00909
100 %		-20	-0.0087	-0.0073	3678.30871	3690.00735
100 %		-10	-0.0026	-0.0091	3678.30256	3690.00905
100 %		0	-0.0088	-0.0030	3678.30882	3690.00300
100 %		10	-0.0038	-0.0127	3678.30384	3690.01267
100 %		30	-0.0048	-0.0103	3678.30477	3690.01032
100 %		40	-0.0042	-0.0078	3678.30416	3690.00778
100 %		50	-0.0018	-0.0010	3678.30184	3690.00099
Batt. Endpoint	3.400	20	-0.0035	-0.0088	3678.30348	3690.00883

▣ PCC Channel:	56496	
▣ PCC Frequency:	3675.6	MHz
▣ PCC BandWidth:	10	MHz
▣ SCC Channel:	56640	
▣ SCC Frequency:	3690.0	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0065	-0.0092	3675.60654	3690.00916
100 %		-30	-0.0041	-0.0067	3675.60415	3690.00669
100 %		-20	-0.0075	-0.0045	3675.60751	3690.00455
100 %		-10	-0.0065	-0.0029	3675.60646	3690.00285
100 %		0	-0.0090	-0.0040	3675.60902	3690.00400
100 %		10	-0.0081	-0.0111	3675.60814	3690.01107
100 %		30	-0.0026	-0.0071	3675.60257	3690.00712
100 %		40	-0.0090	-0.0059	3675.60896	3690.00588
100 %		50	-0.0034	-0.0003	3675.60344	3690.00029
Batt. Endpoint	3.400	20	-0.0055	-0.0050	3675.60548	3690.00503

▣ PCC Channel:	56469	
▣ PCC Frequency:	3672.9	MHz
▣ PCC BandWidth:	15	MHz
▣ SCC Channel:	56640	
▣ SCC Frequency:	3690.0	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	VDC
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0025	-0.0069	3672.90254	3690.00686
100 %		-30	-0.0031	-0.0097	3672.90315	3690.00969
100 %		-20	-0.0093	-0.0049	3672.90931	3690.00495
100 %		-10	-0.0019	-0.0075	3672.90186	3690.00745
100 %		0	-0.0045	-0.0036	3672.90452	3690.00360
100 %		10	-0.0034	-0.0046	3672.90344	3690.00457
100 %		30	-0.0067	-0.0083	3672.90667	3690.00832
100 %		40	-0.0021	-0.0070	3672.90206	3690.00698
100 %		50	-0.0025	-0.0062	3672.90254	3690.00619
Batt. Endpoint	3.400	20	-0.0057	-0.0105	3672.90568	3690.01053

▣ PCC Channel:	56442	
▣ PCC Frequency:	3670.2	MHz
▣ PCC BandWidth:	20	MHz
▣ SCC Channel:	56640	
▣ SCC Frequency:	3690.0	MHz
▣ SCC BandWidth:	20	MHz
▣ Voltage :	3.880	MHz
▣ LIMIT:	Emission must remain in band	

Voltage (%)	Power (VDC)	Temp. (°C)	PPM		Frequency Error (MHz)	
			PCC	SCC	PCC	SCC
100 %	3.880	+20(Ref)	-0.0007	-0.0062	3670.20074	3690.00616
100 %		-30	-0.0005	-0.0062	3670.20055	3690.00619
100 %		-20	-0.0030	-0.0023	3670.20301	3690.00235
100 %		-10	-0.0003	-0.0031	3670.20026	3690.00305
100 %		0	-0.0102	-0.0045	3670.21022	3690.00450
100 %		10	-0.0018	-0.0122	3670.20184	3690.01217
100 %		30	-0.0043	-0.0100	3670.20427	3690.01002
100 %		40	-0.0062	-0.0049	3670.20616	3690.00488
100 %		50	-0.0059	-0.0021	3670.20594	3690.00209
Batt. Endpoint	3.400	20	-0.0043	-0.0105	3670.20428	3690.01053

8.6 Radiated Spurious Emissions

▣ PCC Channel :	<u>55340 (3560.0 MHz)</u>
▣ PCC BW(MHz) :	<u>20</u>
▣ PCC RB/ RB Offset :	<u>1/ 99</u>
▣ SCC Channel :	<u>55538 (3579.8 MHz)</u>
▣ SCC BW(MHz) :	<u>20</u>
▣ SCC RB/ RB Offset :	<u>1/ 0</u>
▣ DISTANCE:	<u>1 meters</u>
▣ LIMIT:	<u>-40.0 dBm</u>

Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	Result (dBm)
7,139.80	-44.23	11.26	-60.18	4.48	V	-53.40
10,709.70	-47.08	10.92	-55.88	5.65	V	-50.61
14,279.60	-47.01	11.80	-50.21	6.57	H	-44.98

☐ PCC Channel : 55891 (3615.1 MHz)
☐ PCC BW(MHz) : 20
☐ PCC RB/ RB Offset : 1/99
☐ SCC Channel : 56089 (3634.9 MHz)
☐ SCC BW(MHz) : 20
☐ SCC RB/ RB Offset : 1/0
☐ DISTANCE: 1 meters
☐ LIMIT: -40.0 dBm

Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	Result (dBm)
7,250.00	-44.08	11.18	-60.68	4.53	V	-54.03
10,875.00	-46.02	10.61	-54.41	5.82	H	-49.62
14,500.00	-45.79	11.61	-50.19	6.69	H	-45.27

☐ PCC Channel : 56442 (3670.2 MHz)
☐ PCC BW(MHz) : 20
☐ PCC RB/ RB Offset : 1/99
☐ SCC Channel : 56640 (3690.0 MHz)
☐ SCC BW(MHz) : 20
☐ SCC RB/ RB Offset : 1/0
☐ DISTANCE: 1 meters
☐ LIMIT: -40.0 dBm

Freq.(MHz)	Measured Level [dBm]	Ant. Gain (dBi)	Substitute Level [dBm]	C.L	Pol.	Result (dBm)
7,360.20	-43.67	11.16	-59.85	4.59	V	-53.28
11,040.30	-45.86	10.93	-54.08	5.79	H	-48.94
14,720.40	-46.26	11.66	-51.96	6.71	V	-47.01

8.7 Occupied Bandwidth

PCC					SCC					Data (MHz)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	
5	55898	3615.8	QPSK	25/0	20	56015	3627.5	QPSK	100/0	22.775
10	55896	3615.6	QPSK	50/0	20	56040	3630	QPSK	100/0	27.593
15	55893	3615.3	QPSK	75/0	20	56064	3632.4	QPSK	100/0	32.808
20	55965	3622.5	QPSK	100/0	5	56082	3634.2	QPSK	25/0	22.836
20	55941	3620.1	QPSK	100/0	10	56085	3634.5	QPSK	50/0	27.762
20	55916	3617.6	QPSK	100/0	15	56087	3634.7	QPSK	75/0	32.489
20	55891	3615.1	QPSK	100/0	20	56089	3634.9	QPSK	100/0	37.581

PCC					SCC					Data (MHz)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	
5	55898	3615.8	16QAM	25/0	20	56015	3627.5	16QAM	100/0	22.807
10	55896	3615.6	16QAM	50/0	20	56040	3630	16QAM	100/0	27.506
15	55893	3615.3	16QAM	75/0	20	56064	3632.4	16QAM	100/0	32.442
20	55965	3622.5	16QAM	100/0	5	56082	3634.2	16QAM	25/0	22.893
20	55941	3620.1	16QAM	100/0	10	56085	3634.5	16QAM	50/0	27.924
20	55916	3617.6	16QAM	100/0	15	56087	3634.7	16QAM	75/0	32.855
20	55891	3615.1	16QAM	100/0	20	56089	3634.9	16QAM	100/0	37.562


PCC					SCC					Data (MHz)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	
5	55898	3615.8	64QAM	25/0	20	56015	3627.5	64QAM	100/0	22.784
10	55896	3615.6	64QAM	50/0	20	56040	3630	64QAM	100/0	27.576
15	55893	3615.3	64QAM	75/0	20	56064	3632.4	64QAM	100/0	32.624
20	55965	3622.5	64QAM	100/0	5	56082	3634.2	64QAM	25/0	22.830
20	55941	3620.1	64QAM	100/0	10	56085	3634.5	64QAM	50/0	27.788
20	55916	3617.6	64QAM	100/0	15	56087	3634.7	64QAM	75/0	32.683
20	55891	3615.1	64QAM	100/0	20	56089	3634.9	64QAM	100/0	37.772

PCC					SCC					Data (MHz)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	
5	55898	3615.8	256QAM	25/0	20	56015	3627.5	256QAM	100/0	22.954
10	55896	3615.6	256QAM	50/0	20	56040	3630	256QAM	100/0	27.638
15	55893	3615.3	256QAM	75/0	20	56064	3632.4	256QAM	100/0	32.749
20	55965	3622.5	256QAM	100/0	5	56082	3634.2	256QAM	25/0	22.759
20	55941	3620.1	256QAM	100/0	10	56085	3634.5	256QAM	50/0	27.650
20	55916	3617.6	256QAM	100/0	15	56087	3634.7	256QAM	75/0	32.573
20	55891	3615.1	256QAM	100/0	20	56089	3634.9	256QAM	100/0	37.653


Note:

In order to simplify the report, attached plots were only Max.Bandwidth(20+20)


PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(QPSK)




PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(16QAM)



PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(64QAM)



PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(256QAM))



8.8 Peak- to- Average Ratio

PCC					SCC					Data (dB)	Limit (dB)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset		
5	55898	3615.8	QPSK	25/0	20	56015	3627.5	QPSK	100/0	7.04	13.00
10	55896	3615.6	QPSK	50/0	20	56040	3630	QPSK	100/0	7.23	
15	55893	3615.3	QPSK	75/0	20	56064	3632.4	QPSK	100/0	6.97	
20	55965	3622.5	QPSK	100/0	5	56082	3634.2	QPSK	25/0	7.03	
20	55941	3620.1	QPSK	100/0	10	56085	3634.5	QPSK	50/0	7.23	
20	55916	3617.6	QPSK	100/0	15	56087	3634.7	QPSK	75/0	7.24	
20	55891	3615.1	QPSK	100/0	20	56089	3634.9	QPSK	100/0	7.88	

PCC					SCC					Data (dB)	Limit (dB)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/ Offset		
5	55898	3615.8	16QAM	25/0	20	56015	3627.5	16QAM	100/0	7.64	13.00
10	55896	3615.6	16QAM	50/0	20	56040	3630	16QAM	100/0	7.57	
15	55893	3615.3	16QAM	75/0	20	56064	3632.4	16QAM	100/0	7.59	
20	55965	3622.5	16QAM	100/0	5	56082	3634.2	16QAM	25/0	7.48	
20	55941	3620.1	16QAM	100/0	10	56085	3634.5	16QAM	50/0	7.86	
20	55916	3617.6	16QAM	100/0	15	56087	3634.7	16QAM	75/0	7.65	
20	55891	3615.1	16QAM	100/0	20	56089	3634.9	16QAM	100/0	8.60	

PCC					SCC					Data (dB)	Limit (dB)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/Offset		
5	55898	3615.8	64QAM	25/0	20	56015	3627.5	64QAM	100/0	7.61	13.00
10	55896	3615.6	64QAM	50/0	20	56040	3630	64QAM	100/0	7.95	
15	55893	3615.3	64QAM	75/0	20	56064	3632.4	64QAM	100/0	7.67	
20	55965	3622.5	64QAM	100/0	5	56082	3634.2	64QAM	25/0	7.72	
20	55941	3620.1	64QAM	100/0	10	56085	3634.5	64QAM	50/0	7.73	
20	55916	3617.6	64QAM	100/0	15	56087	3634.7	64QAM	75/0	7.63	
20	55891	3615.1	64QAM	100/0	20	56089	3634.9	64QAM	100/0	7.72	

PCC					SCC					Data (dB)	Limit (dB)
BW [MHz]	Ch	Freq [MHz]	Mod	RB/Offset	BW [MHz]	Ch	Freq [MHz]	Mod	RB/Offset		
5	55898	3615.8	256QAM	25/0	20	56015	3627.5	256QAM	100/0	7.52	13.00
10	55896	3615.6	256QAM	50/0	20	56040	3630	256QAM	100/0	7.87	
15	55893	3615.3	256QAM	75/0	20	56064	3632.4	256QAM	100/0	7.52	
20	55965	3622.5	256QAM	100/0	5	56082	3634.2	256QAM	25/0	7.70	
20	55941	3620.1	256QAM	100/0	10	56085	3634.5	256QAM	50/0	7.86	
20	55916	3617.6	256QAM	100/0	15	56087	3634.7	256QAM	75/0	7.83	
20	55891	3615.1	256QAM	100/0	20	56089	3634.9	256QAM	100/0	7.62	

Note:

In order to simplify the report, attached plots were only Max.Bandwidth(20+20)

PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(QPSK)



PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(16QAM)



PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(64QAM)



PCC 20 MHz Ch55891 RB100 Offset0, SCC 20 MHz Ch56089 RB100 Offset0_(256QAM)




8.9 Adjacent Channel Leakage Ratio(ACLR)

Operating frequency	PCC				SCC				Adjacent Channel Leakage Ratio(dB)	
	BW [MHz]	Ch.	Freq. (MHz)	RB/ Offset	BW [MHz]	Ch.	Freq. (MHz)	RB/ Offset	Lower Side	Upper Side
Low	20	55340	3560.0	100/0	20	55538	3579.8	100/0	37.86	41.37
Mid	20	55891	3615.1	100/0	20	56089	3634.9	100/0	37.82	41.16
High	20	56442	3670.2	100/0	20	56640	3690.0	100/0	38.95	41.01
Limit (dB)									ACLR > 30 dB	ACLR > 30 dB


Note:

1. Modulation : 16QAM
2. Duty Cycle factor already applied on the factor.
 - Duty Cycle factor(dB) = 3.979
 - Factor(dB) = Duty Cycle factor + Cable Loss + Ext. Attenuator + Power Splitter


PCC 20 MHz Ch55340 RB100 Offset0, SCC 20 MHz Ch55538 RB100 Offset0



PCC 20MHz Ch55891 RB100 Offset0, SCC 20MHz Ch56089 RB100 Offset0



PCC 20MHz Ch56442 RB100 Offset0, SCC 20MHz Ch56640 RB100 Offset0



9. ANNEX A_ TEST SETUP PHOTO

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-2510-FC027-P