



**ELEMENT MATERIALS TECHNOLOGY,
Columbia MD**

(formerly PCTEST)

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

**MEASUREMENT REPORT
FCC Part 15.247 Bluetooth (Low Energy)**

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

7/15/2026 - 7/28/2026

Test Report Issue Date:

8/12/2026

Test Site/Location:

Element Lab., Columbia, MD, USA

Element Lab., Yongin-Si, Gyeonggi-do, South Korea

Test Report Serial No.:

1M2607060061-07.A3L

FCC ID:

A3LSMA185G

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-A185G/DS

Additional Model(s):

SM-A185G

EUT Type:

Portable Handset

Max. RF Output Power:

5.484 mW (7.39 dBm) Peak Conducted

Frequency Range:

2402 – 2480MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

FCC Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to
C63.10a:2024

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 1M2607060061-07-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M2607060061-07.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**RJ Ortanez
Executive Vice President**



FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 1 of 63

TEST REPORT REVISION HISTORY

Revision	Date	Comment	Revised By
-	8/11/2026	Initial Release	WKR0000025833
1	8/12/2026	Addressed comments made by TCB Reviewer	WKR0000023296

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 2 of 63

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope.....	4
1.2	Element Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description.....	5
2.4	Test Configuration.....	6
2.5	Software and Firmware	6
2.6	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure.....	7
3.2	AC Line Conducted Emissions.....	7
3.3	Radiated Emissions	8
3.4	Environmental Conditions	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS	13
7.1	Summary.....	13
7.2	6dB Bandwidth Measurement – Bluetooth (LE)	14
7.3	Output Power Measurement – Bluetooth (LE)	22
7.4	Power Spectral Density – Bluetooth (LE).....	30
7.5	Conducted Emissions at the Band Edge.....	38
7.6	Conducted Spurious Emissions	43
7.7	Radiated Spurious Emission Measurements	48
7.8	Radiated Restricted Band Edge Measurements	55
7.9	Radiated Spurious Emissions Measurements – Below 1GHz.....	56
7.10	Line-Conducted Test Data	60
8.0	CONCLUSION.....	63

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 3 of 63

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

Measurements were conducted at the Element laboratory(ies) indicated in Section 1.3 below. All measurement facilities are compliant with the test site requirements specified in ANSI C63.4:2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A. ("MD")

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISSED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISSED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

Measurements were performed at Element Materials Technology Suwon, Ltd. located in Yongin-si, Gyeonggi-do, 16954, South Korea. ("KR")

- Element Materials Technology Suwon, Ltd. is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation(A2LA) with Certificate number 2041.04 for Specific Absorption Rate (SAR), and Electromagnetic Compatibility (EMC) & Telecommunications testing for FCC and Innovation, Science, and Economic Development Canada rules.

Element Materials Technology Suwon, Ltd. facility is accredited, designated, and recognized in accordance with the provision of Radio Wave Act and International Standard ISO/IEC 17025:2017 under the National Radio Research Agency.

- Designation Number / CABID: KR0169
- Test Firm Registration Number of FCC: 417945
- Test Firm Registration Number of ISSED: 26168

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 4 of 63

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA185G**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

Test Device Serial No.: 0126M, 0093M, 0108M, 0164M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/RDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII (5GHz), Bluetooth (1x, EDR, LE), NFC

Ch.	Frequency (MHz)
37	2402
:	:
17	2440
:	:
39	2480

Table 2-1. Frequency / Channel Operations – 1Mbps

Ch.	Frequency (MHz)
0	2404
:	:
17	2440
:	:
36	2478

Table 2-2. Frequency / Channel Operations – 2Mbps

2.3 Antenna Description

The manufacturer provided the antenna gains which can affect the validity of test results used for determination of compliance. The following antenna gains are used in this device per the “Unlicensed Band Antenna Gain” document provided by the client. This document is also included in the filing as a public exhibit.

Frequency [GHz]	Antenna Gain (dBi)
2.4	-3.9

Table 2-3. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 5 of 63

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020. ANSI C63.10:2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 0, 7.5, and 7.6 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst-case configuration was found between the two variants. The EUT was also investigated with and without charger.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report. The worst orientation was found to be Y-orientation (landscape).

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB cable with wire charger

2.5 Software and Firmware

The test was conducted with software/firmware version A185GXXU0AZG1 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 6 of 63

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that those cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 7 of 63

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4:2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4:2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 8 of 63

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 9 of 63

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10:2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget – MD

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.95
Radiated Disturbance (<1GHz)	4.10
Radiated Disturbance (>1GHz)	4.82
Radiated Disturbance (>18GHz)	4.96

Table 5-2. Measurement Uncertainty Budget - KR

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 10 of 63

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	MD 1M 40	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	MD 1M 40
-	AP1-002	EMC Cable and Switch System	2/3/2026	Annual	2/3/2027	AP1-002
-	WL25-1	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	1/30/2026	Annual	1/30/2027	WL25-2
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	4/21/2025	Biennial	4/21/2027	114451
ETS-Lindgren	3116C	DRG Horn Antenna	4/22/2025	Biennial	4/22/2027	218893
Keysight Technologies	N9038A	MXE EMI Receiver	11/10/2025	Annual	11/10/2026	MY51210133
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	7/15/2026	Annual	7/15/2027	MY52350166
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	1/30/2026	Annual	1/30/2027	NMLC-2
Rohde & Schwarz	ENV216	Two-Line V-Network	2/4/2026	Biennial	2/4/2028	101379
Rohde & Schwarz	FSW26	2Hz-26.5GHz Signal and Spectrum Analyzer	11/18/2025	Annual	11/18/2026	103187
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Test Antenna (1-18GHz)	12/10/2024	Biennial	12/10/2026	101073

Table 6-1. Test Equipment Calibration Table - MD

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9030A	PXA Signal Analyzer	04/13/2026	Annual	04/12/2027	MY49432391
Sunol Sciences	DRH-118	Horn Antenna	05/14/2026	Annual	05/13/2027	A102416-1
Rohde & Schwarz	VULB9162	Broadband TRILOG Antenna	06/05/2025	Biennial	06/04/2027	9162-217
RFCOREA	MA-18G10-5W-NMF	Attenuator	03/04/2026	Annual	03/03/2027	ESR10-1
Rohde & Schwarz	TS-SFUNIT-Rx	Shielded Filter Unit	01/28/2026	Annual	01/27/2027	102151
Rohde & Schwarz	ESW	EMI Test Receiver	09/15/2025	Annual	09/14/2026	103550
-	UEK1	EMC Cable and Switch System	01/28/2026	Annual	01/27/2027	UEK1

Table 6-2. Test Equipment Calibration Table - KR

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

Component	Serial Number
MegaPhase Cable TM40-K1K1-30	20233002-004
UTIPLEX Cable, 64639	232063-001
Rohde & Schwarz Pre-amp TS-PR1840 18G-40G	9037.7670.02

Table 6-3. MD 1M 18-40 EMC Cable and Switch System Components

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 11 of 63

Component	Serial Number
Sucoflex 106A Cable	501992
MegaPhase Cable N29-N1N1-324	20335606 001
Rohde & Schwarz SF Unit	102133
MiniCircuits Cable CBL-2FT-SMSM+	77745
MegaPhase Cable 10511-1	15034701 001
MiniCircuits Switch RC 2SPDT-A18	11703270 041
Sucoflex 104 Cable	320259/4
Sucoflex 104 Cable	321999/4
Sucoflex 104 Cable	321995/4

Table 6-4. AP1-002 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase Cable, Model: TM26-S1S1-36	18160103 003
Pasternack 6dB Attenuator, Model: PE7005-6	N/A

Table 6-5. WL25-1 Conducted Cable Set Components

Component	Serial Number
Mini-Circuits Cable, Model: CBL-2FT-SMSM+	77743
MCL 6dB Attenuator, Model: BW-S6W2+	1314

Table 6-6. WL25-2 Conducted Cable Set Components

Component	Serial Number
Rohde & Schwarz SF Unit	102151
ALPHA WIRE H1	6340
HUBER+SUHNER, Inc. SUCOFLEX_104_PE Cable	305916
HUBER+SUHNER, Inc. SUCOFLEX_100	803242-6

Table 6-7. UEK1 EMC Cable Switch System Components

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 12 of 63

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA185G
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Test Lab Location
15.247(a)(2)	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2	MD
15.247(b)(3)	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3	MD
15.247(e)	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4	MD
15.247(d)	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6	MD
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Sections 7.7, 7.8, 7.9	MD, KR
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 7.10	MD

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Bluetooth LE Automation,” Version 3.6.
5. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 1.3.1.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 13 of 63

7.2 6dB Bandwidth Measurement – Bluetooth (LE)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10:2020 – Section 11.8.2 Option 2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 14 of 63

Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	125 kbps	37	LE	690.9	500	Pass
2440	125 kbps	17	LE	689.3	500	Pass
2480	125 kbps	39	LE	686.0	500	Pass
2402	500 kbps	37	LE	665.9	500	Pass
2440	500 kbps	17	LE	665.5	500	Pass
2480	500 kbps	39	LE	664.3	500	Pass
2402	1 Mbps	37	LE	715.0	500	Pass
2440	1 Mbps	17	LE	712.0	500	Pass
2480	1 Mbps	39	LE	708.8	500	Pass
2404	2 Mbps	0	LE	1172.6	500	Pass
2440	2 Mbps	17	LE	1174.2	500	Pass
2478	2 Mbps	36	LE	1172.8	500	Pass

Table 7-2. Conducted Bandwidth Measurements

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 15 of 63




Plot 7-1. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 37)



Plot 7-2. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 17)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 16 of 63




Plot 7-3. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 39)



Plot 7-4. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 37)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 17 of 63




Plot 7-5. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 17)



Plot 7-6. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 18 of 63



Plot 7-7. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 37)



Plot 7-8. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 19 of 63




Plot 7-9. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39)



Plot 7-10. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 20 of 63



Plot 7-11. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-12. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 21 of 63

7.3 Output Power Measurement – Bluetooth (LE)

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

ANSI C63.10:2020 – Section 11.9.1.1

Test Settings

1. RBW = 3MHz
2. VBW = 50MHz
3. Span $\geq 3 \times$ RBW
4. Sweep = auto couple
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 22 of 63


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power		Limit [dBm]	Margin [dB]
				[dBm]	[mW]		
2402	125 kbps	37	LE	7.04	5.062	30.00	-22.96
2440	125 kbps	17	LE	7.18	5.220	30.00	-22.82
2480	125 kbps	39	LE	7.21	5.260	30.00	-22.79
2402	500 kbps	37	LE	7.07	5.089	30.00	-22.93
2440	500 kbps	17	LE	7.21	5.260	30.00	-22.79
2480	500 kbps	39	LE	7.24	5.298	30.00	-22.76
2402	1 Mbps	37	LE	7.07	5.094	30.00	-22.93
2440	1 Mbps	17	LE	7.21	5.260	30.00	-22.79
2480	1 Mbps	39	LE	7.24	5.294	30.00	-22.76
2404	2 Mbps	0	LE	7.19	5.236	30.00	-22.81
2440	2 Mbps	17	LE	7.27	5.330	30.00	-22.73
2478	2 Mbps	36	LE	7.39	5.484	30.00	-22.61

Table 7-3. Conducted Output Power Measurements (Bluetooth (LE))

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 23 of 63




Plot 7-13. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 37)




Plot 7-14. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 17)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 24 of 63




Plot 7-15. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 39)




Plot 7-16. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 37)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 25 of 63




Plot 7-17. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 17)




Plot 7-18. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 26 of 63




Plot 7-19. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-20. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 27 of 63




Plot 7-21. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-22. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 28 of 63



Plot 7-23. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-24. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 29 of 63

7.4 Power Spectral Density – Bluetooth (LE)

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10:2020 – Section 11.10.2 Method PKPSD

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 30 of 63


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	125 kbps	37	LE	0.49	8.0	-7.51
2440	125 kbps	17	LE	0.72	8.0	-7.28
2480	125 kbps	39	LE	0.69	8.0	-7.31
2402	500 kbps	37	LE	0.37	8.0	-7.63
2440	500 kbps	17	LE	0.62	8.0	-7.38
2480	500 kbps	39	LE	0.59	8.0	-7.41
2402	1 Mbps	37	LE	-8.49	8.0	-16.49
2440	1 Mbps	17	LE	-8.29	8.0	-16.29
2480	1 Mbps	39	LE	-8.26	8.0	-16.26
2404	2 Mbps	0	LE	-10.55	8.0	-18.55
2440	2 Mbps	17	LE	-10.42	8.0	-18.42
2478	2 Mbps	36	LE	-10.34	8.0	-18.34

Table 7-4. Conducted Power Density Measurements

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 31 of 63




Plot 7-27. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 39)




Plot 7-28. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 37)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 33 of 63




Plot 7-29. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 17)




Plot 7-30. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 34 of 63




Plot 7-31. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-32. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 35 of 63




Plot 7-33. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-34. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 36 of 63



Plot 7-35. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-36. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 37 of 63

7.5 Conducted Emissions at the Band Edge

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 38 of 63




Plot 7-37. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 37)




Plot 7-38. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 39 of 63




Plot 7-39. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 37)




Plot 7-40. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 40 of 63




Plot 7-41. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 37)



Plot 7-42. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 41 of 63



Plot 7-43. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0)



Plot 7-44. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 42 of 63

7.6 Conducted Spurious Emissions

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11.3 of ANSI C63.10:2020.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup


FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 43 of 63


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 44 of 63







7.7 Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d)

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-5 per Section 15.209.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-5. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 – Section 6.6.4.3

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3kHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 48 of 63

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-6 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-6. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 49 of 63

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of ANSI C63.10:2020 Section 11.12.2 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-5.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Average measurements were recorded using a VBW of 3kHz, per Section 4.1.4.2.3 of ANSI C63.10:2020, since 1/T is equal to just under 3kHz. This method was used because the EUT could not be configured to operate with a duty cycle > 98%. Both average and peak measurements were made using a peak detector
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. No significant radiated band edge emissions were found in the 2310 – 2390MHz restricted band.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 50 of 63

Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d)



Plot 7-51. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 37)



Plot 7-52. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 17)




Plot 7-53. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 51 of 63

Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209



Plot 7-54. Radiated Spurious Plot above 18GHz (Bluetooth (LE))

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 52 of 63

Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d)

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2402MHz
 Channel: 37

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	H	-	-	-79.60	7.88	0.00	35.28	53.98	-18.70
4804.00	Peak	H	-	-	-68.40	7.88	0.00	46.48	73.98	-27.50
12010.00	Avg	H	-	-	-81.82	19.53	0.00	44.71	53.98	-9.27
12010.00	Peak	H	-	-	-70.44	19.53	0.00	56.09	73.98	-17.89

Table 7-7. Radiated Measurements @ 3 meters

Bluetooth Mode: LE
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	V	-	-	-79.69	8.18	0.00	35.49	53.98	-18.49
4880.00	Peak	V	-	-	-67.24	8.18	0.00	47.94	73.98	-26.04
7320.00	Avg	V	-	-	-80.76	13.80	0.00	40.04	53.98	-13.94
7320.00	Peak	V	-	-	-70.18	13.80	0.00	50.62	73.98	-23.36
12200.00	Avg	V	-	-	-81.91	20.14	0.00	45.23	53.98	-8.75
12200.00	Peak	V	-	-	-71.14	20.14	0.00	56.00	73.98	-17.98

Table 7-8. Radiated Measurements @ 3 meters

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 53 of 63



Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d)

Bluetooth Mode: LE
Distance of Measurements: 3 Meters
Operating Frequency: 2480MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
3865.00	Avg	H	-	-	-78.88	5.85	0.00	33.97	53.98	-20.01
3865.00	Peak	H	-	-	-68.18	5.85	0.00	44.67	73.98	-29.31
4960.00	Avg	H	-	-	-79.36	7.76	0.00	35.40	53.98	-18.58
4960.00	Peak	H	-	-	-69.00	7.76	0.00	45.76	73.98	-28.22
7440.00	Avg	V	-	-	-80.68	13.46	0.00	39.78	53.98	-14.20
7440.00	Peak	V	-	-	-69.48	13.46	0.00	50.98	73.98	-23.00
12400.00	Avg	H	-	-	-81.64	19.91	0.00	45.27	53.98	-8.71
12400.00	Peak	H	-	-	-70.78	19.91	0.00	56.13	73.98	-17.85

Table 7-9. Radiated Measurements @ 3 meters

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 54 of 63

7.8 Radiated Restricted Band Edge Measurements


\$15.205 \$15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Bluetooth Mode:	LE
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	39



Plot 7-55. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-56. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 55 of 63

7.9 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-10 per Section 15.209.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-10. Radiated Limits

Test Procedures Used

ANSI C63.10:2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 56 of 63

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 57 of 63


Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 58 of 63

Radiated Spurious Emissions Measurements (Below 1GHz)

\$15.209



Plot 7-57. Radiated Spurious Plot below 1GHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
214.00	Quasi-Peak	V	-	-	-102.12	17.67	22.55	43.52	-20.97
255.00	Quasi-Peak	V	-	-	-102.21	18.90	23.69	46.02	-22.33
270.00	Quasi-Peak	H	-	-	-102.39	20.63	25.24	46.02	-20.78
333.00	Quasi-Peak	H	-	-	-101.98	21.66	26.68	46.02	-19.34

Table 7-11. Radiated Spurious Emissions below 1GHz

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 59 of 63

7.10 Line-Conducted Test Data

§15.207

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-12. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 60 of 63

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 61 of 63



Plot 7-58. Line Conducted Plot with Bluetooth LE (L1)



Plot 7-59. Line Conducted Plot with Bluetooth LE (N)

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 62 of 63

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA185G** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules.

- END OF TEST REPORT -

FCC ID: A3LSMA185G		Test Dates: 7/15/2026 - 7/28/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2607060061-07.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 63 of 63