9.2.1. BAND EDGE RESULT

GSM

GSM 850



GSM850 GPRS Low channel



GSM850 EGPRS Low channel



GSM850 GPR High channel



GSM850 EGPRS High channel

GSM 1900



GSM1900 GPRS Low channel



GSM1900 EGPRS Low channel



GSM1900 GPRS High channel



GSM1900 EGPRS High channel

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA

Band 5	 REL99 Low channel	 HSDPA Low channel
	 REL99 High channel	 HSDPA High channel

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 2	 REL99 Low channel	 HSDPA Low channel
	 REL99 High channel	 HSDPA High channel

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 5

Band 5

10MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 5

5MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 5

3MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 5

1.4MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.2.2. EMISSION MASK RESULT

LTE Band 41

Band 41

20MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 41

15MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 41

10MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 41

5MHz



QPSK Low channel FRB



QPSK Low channel 1RB



QPSK High channel FRB



QPSK High channel 1RB



16QAM Low channel FRB



16QAM Low channel 1RB



16QAM High channel FRB



16QAM High channel 1RB

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.3. OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §22.901, §22.917 and §27.53

LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

Part 27.53:
(m) (4) For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v03r01
The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

a) Set the RBW = 100KHz for emission below 1GHz and 1MHz for emissions above 1GHz (Tests were performed 1MHz [Worst case], to sweep 1 time for all frequency range)

b) Set VBW ≥ 3 × RBW;

c) Set span ≥ 1.5 times the OBW;

d) Sweep time = auto couple;

e) Detector = rms;

f) Ensure that the number of measurement points = Max (40001);

g) Trace mode = average(WCDMA, LTE), Maxhold(GSM, LTE Band41);

RESULTS

See the following pages.

NOTE : Please refer to section 5.4 for bandwidth and RB setting about LTE bands.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.3.1. OUT OF BAND EMISSIONS RESULT

GSM 850

GSM 850



GSM850 GPRS Low channel



GSM850 EGPRS Low channel



GSM850 GPRS Mid channel



GSM850 EGPRS Mid channel



GSM850 GPRS High channel



GSM850 EGPRS High channel

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

GSM 1900

GSM 1900	 GSM1900 GPRS Low channel	 GSM1900 EGPRS Low channel
	 GSM1900 GPRS Mid channel	 GSM1900 EGPRS Mid channel
	 GSM1900 GPRS High channel	 GSM1900 EGPRS High channel

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5

Band 5	 REL99 Low channel	 HSDPA Low channel
	 REL99 Mid channel	 HSDPA Mid channel
	 REL99 High channel	 HSDPA High channel

WCDMA Band 2

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

Band 2	 REL99 Low channel	 HSDPA Low channel
	 REL99 Mid channel	 HSDPA Mid channel
	 REL99 High channel	 HSDPA High channel

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 5

Band 5 5MHz	 QPSK Low channel	 QPSK Mid channel
	 QPSK High channel	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

Band 41 10MHz	 QPSK Low channel	 QPSK Mid channel
	 QPSK High channel	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.4. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235 and §27.54

LIMITS

§22.355 - The carrier frequency shall not depart from the reference frequency in excess of ±2.5 ppm for mobile stations.

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

§27.54 - The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

.

TEST PROCEDURE

Per KDB 971168 D01 Power Meas License Digital Systems v03r01

RESULTS

See the following pages.

NOTE : Test were performed each lowest or highest frequency on the modulation condition of more wide bandwidth.(Please refer to section 9.1.1 OBW results)

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.4.1. FREQUENCY STABILITY RESULTS

GSM 850, Channel 128/251, Frequency 824.2/848.8 MHz

Reference Frequency : GSM850 Low Channel 824.2 MHz / High Channel 848.8 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2060.500	Hz	High Channel	2122.000	Hz
Power Supply [Vdc]	Environment Temperature [ºC]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	50	824.19998776	0.002	848.79998511	-0.005	2.5
3.85	40	824.19998314	0.007	848.79998099	-0.001	2.5
3.85	30	824.19998013	0.011	848.79998062	0.000	2.5
3.85	***20***	***824.19998927***	***0.000***	***848.79998045***	***0.000***	***2.5***
3.85	10	824.19998602	0.004	848.79998685	-0.008	2.5
3.85	0	824.19999066	-0.002	848.79998475	-0.005	2.5
3.85	-10	824.19998459	0.006	848.79998841	-0.009	2.5
3.85	-20	824.19999065	-0.002	848.79998459	-0.005	2.5
3.85	-30	824.19998925	0.000	848.79998195	-0.002	2.5

Reference Frequency : GSM850 Low Channel 824.2 MHz / High Channel 848.8 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2060.500	Hz	High Channel	2122.000	Hz
Power Supply [Vdc]	Environment Temperature [ºC]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	***20***	***824.19998927***	***0***	***848.79998045***	***0***	***2.5***
4.40	20	824.19998236	0.008	848.79998038	0.000	2.5
3.60	20	824.19998773	0.002	848.79998036	0.000	2.5

GSM 1900, Channel 512/810, Frequency 1850.0/1910.0 MHz

Limit		1850	1910	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1850.0764	1909.9237		
Extreme (50C)		1850.0764	1909.9236	-24.8	-0.013
Extreme (40C)		1850.0764	1909.9236	-28.1	-0.015
Extreme (30C)		1850.0764	1909.9236	-19.3	-0.010
Extreme (10C)		1850.0764	1909.9236	-19.7	-0.010
Extreme (0C)		1850.0764	1909.9236	-20.0	-0.011
Extreme (-10C)		1850.0764	1909.9236	-26.9	-0.014
Extreme (-20C)		1850.0764	1909.9236	-28.1	-0.015
Extreme (-30C)		1850.0764	1909.9236	-27.8	-0.015
20C	15%	1850.0764	1909.9236	-23.8	-0.013
	-15%	1850.0764	1909.9236	-21.0	-0.011
	End Point	1850.0764	1909.9236	-29.3	-0.016

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5 Lowest Frequency: HSDPA / Highest Frequency: Rel. 99)

Reference Frequency : WCDMA Band 5 Low Channel 826.4 MHz / High Channel 846.6 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2066.000	Hz	High Channel	2116.500	Hz
Power Supply [Vdc]	Environment Temperature [ºC]	Frequency Deviation Measureed with Time Elapse				
		Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	50	826.39998406	-0.009	846.59997547	0.001	2.5
3.85	40	826.39998452	-0.009	846.59998132	-0.005	2.5
3.85	30	826.39997564	0.001	846.59997754	-0.001	2.5
3.85	***20***	***826.39997678***	***0.000***	***846.59997667***	***0.000***	***2.5***
3.85	10	826.39998413	-0.009	846.59998432	-0.009	2.5
3.85	0	826.39998567	-0.011	846.59997657	0.000	2.5
3.85	-10	826.39997611	0.001	846.59997916	-0.003	2.5
3.85	-20	826.39998271	-0.007	846.59998451	-0.009	2.5
3.85	-30	826.39998246	-0.007	846.59998123	-0.005	2.5

Reference Frequency : WCDMA Band 5 Low Channel 826.4 MHz / High Channel 846.6 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2066.000	Hz	High Channel	2116.500	Hz
Power Supply [Vdc]	Environment Temperature [ºC]	Frequency Deviation Measureed with Time Elapse				
		Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	***20***	**826.39997678**	***0***	**846.59997667**	***0***	***2.5***
4.40	20	826.39997890	-0.003	846.59998468	-0.009	2.5
3.60	20	826.39997859	-0.002	846.59997949	-0.003	2.5

WCDMA Band 2 (Lowest Frequency: Rel. 99 / Highest Frequency: HSDPA)

Limit		1850	1910	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1852.3979	1907.6021		
Extreme (50C)		1852.3979	1907.6021	-21.8	-0.012
Extreme (40C)		1852.3979	1907.6021	-21.4	-0.011
Extreme (30C)		1852.3979	1907.6021	-26.3	-0.014
Extreme (10C)		1852.3979	1907.6021	-28.4	-0.015
Extreme (0C)		1852.3979	1907.6021	-23.7	-0.013
Extreme (-10C)		1852.3979	1907.6021	-19.7	-0.010
Extreme (-20C)		1852.3979	1907.6021	-23.4	-0.012
Extreme (-30C)		1852.3979	1907.6021	-29.3	-0.016
20C	15%	1852.3979	1907.6021	-20.5	-0.011
	-15%	1852.3979	1907.6021	-29.2	-0.016
	End Point	1852.3979	1907.6021	-19.3	-0.010

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 5 (Lowest Frequency: 16QAM / Highest Frequency: QPSK)

Reference Frequency : LTE Band 5 Low Channel 824.7 MHz / High Channel 848.3 MHz @ 20°C						
Limit: +- 2.5 ppm =	Low Channel	2061.750	Hz	High Channel	2120.750	Hz
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measureed with Time Elapse				
		Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	50	824.69997705	0.008	848.29998056	0.005	2.5
3.85	40	824.69997965	0.005	848.29998552	-0.001	2.5
3.85	30	824.69998387	0.000	848.29997759	0.009	2.5
3.85	***20***	***824.69998366***	***0.000***	***848.29998491***	***0.000***	***2.5***
3.85	10	824.69998217	0.002	848.29998551	-0.001	2.5
3.85	0	824.69997663	0.009	848.29998356	0.002	2.5
3.85	-10	824.69997968	0.005	848.29998435	0.001	2.5
3.85	-20	824.69997860	0.006	848.29998438	0.001	2.5
3.85	-30	824.69998208	0.002	848.29997684	0.010	2.5

Reference Frequency : LTE Band 5 Low Channel 824.7 MHz / High Channel 848.3 MHz @ 20°C						
Limit: +- 2.5 ppm =	Low Channel	2061.750	Hz	High Channel	2120.750	Hz
Power Supply [Vdc]	Environment Temperature [°C]	Frequency Deviation Measureed with Time Elapse				
		Low Channel		High Channel		Limit [ppm]
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.85	***20***	***824.69998366***	***0***	***848.29998491***	***0***	***2.5***
4.40	20	824.69997734	0.008	848.29997631	0.010	2.5
3.60	20	824.69997739	0.008	848.29997778	0.008	2.5

LTE Band 41 (QPSK)

Limit		2496	2690	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	2498.4977	2687.5022		
Extreme (50C)		2498.4977	2687.5022	-24.8	-0.010
Extreme (40C)		2498.4977	2687.5022	-30.9	-0.012
Extreme (30C)		2498.4977	2687.5022	-24.7	-0.010
Extreme (10C)		2498.4977	2687.5022	-28.5	-0.011
Extreme (0C)		2498.4977	2687.5022	-33.3	-0.013
Extreme (-10C)		2498.4977	2687.5022	-25.0	-0.010
Extreme (-20C)		2498.4977	2687.5022	-29.2	-0.011
Extreme (-30C)		2498.4977	2687.5022	-29.9	-0.012
20C	15%	2498.4977	2687.5022	-27.2	-0.011
	-15%	2498.4977	2687.5022	-26.5	-0.010
	End Point	2498.4977	2687.5022	-32.2	-0.012

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

10. RADIATED TEST RESULTS

10.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232, §27.50 and §27.53

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50:

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13dB.

TEST PROCEDURE

ANSI / TIA / EIA 603 E Clause 2.2.17; ESU40 setting reference to 971168 D01 v03r01

For radiated output power measurement with a ESU40:

a) Set the RBW ≥ OBW; b) Set VBW ≥ 3 × RBW; c) Set span ≥ 2 x RBW; d) Sweep time = auto couple; e) Detector = rms; f) Ensure that the number of measurement points ≥ span/RBW; g) Trace mode = max hold(GSM, WCDMA), average(LTE);

TEST RESULTS

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

10.1.1. ERP/EIRP Results

GSM

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
GSM850	GPRS	512	824.2	26.38	434.51
		661	836.6	25.9	389.05
		810	848.8	26.18	414.95
	EGPRS	512	824.2	21.16	130.62
		661	836.6	20.75	118.85
		810	848.8	21.09	128.53
GSM1900	GPRS	512	1850.2	26.21	417.83
		661	1880	26.82	480.84
		810	1909.8	27.5	562.34
	EGPRS	512	1850.2	25.12	325.09
		661	1880	24.81	302.69
		810	1909.8	25.24	334.20

WCDMA

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
Band 5	REL99	4132	826.4	17.32	53.95
		4183	836.6	**17.71**	**59.02**
		4233	846.6	16.68	46.56
	HSDPA	4132	826.4	16.43	43.95
		4183	836.6	**16.57**	**45.39**
		4233	846.6	14.42	27.67
Band 2	REL99	9262	1852.4	20.64	115.88
		9400	1880.0	**22.11**	**162.55**
		9538	1907.6	21.15	130.32
	HSDPA	9262	1852.4	20.34	108.14
		9400	1880.0	**22.11**	**162.55**
		9538	1907.6	20.96	124.74

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 5

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 5	10	QPSK	1 / 0	829.0	**19.52**	**89.54**
			1 / 0	836.5	18.11	64.71
			1 / 0	844.0	18.17	65.61
		16QAM	1 / 0	829.0	**18.11**	**64.71**
			1 / 0	836.5	17.15	51.88
			1 / 25	844.0	**18.11**	**64.71**
	5	QPSK	1 / 0	826.5	19.31	85.31
			1 / 0	836.5	**19.61**	**91.41**
			1 / 12	846.5	15.40	34.67
		16QAM	1 / 0	826.5	18.01	63.24
			1 / 0	836.5	**18.35**	**68.39**
			1 / 12	846.5	14.67	29.31
	3	QPSK	1 / 8	825.5	**18.71**	**74.30**
			1 / 14	836.5	18.54	71.45
			1 / 8	847.5	17.78	59.98
		16QAM	1 / 14	825.5	**17.19**	**52.36**
			1 / 14	836.5	17.12	51.52
			1 / 0	847.5	16.65	46.24
	1.4	QPSK	1 / 3	824.7	18.84	76.56
			1 / 3	836.5	**18.88**	**77.27**
			1 / 0	848.3	17.86	61.09
		16QAM	1 / 0	824.7	**17.65**	**58.21**
			1 / 0	836.5	17.37	54.58
			1 / 0	848.3	16.84	48.31

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 41	20	QPSK	1 / 99	2506.0	**22.08**	161.44
			1 / 99	2593.0	21.92	155.60
			1 / 99	2680.0	20.02	100.46
		16QAM	1 / 99	2506.0	21.18	131.22
			1 / 99	2593.0	**21.42**	138.68
			1 / 49	2680.0	19.37	86.50
	15	QPSK	1 / 74	2503.5	21.82	152.05
			1 / 37	2593.0	**22.18**	165.20
			1 / 0	2682.5	20.57	114.02
		16QAM	1 / 74	2503.5	21.03	126.77
			1 / 37	2593.0	**22.30**	169.82
			1 / 0	2682.5	20.39	109.40
	10	QPSK	1 / 49	2501.0	**22.39**	**173.38**
			1 / 49	2593.0	21.87	153.82
			1 / 49	2685.0	20.30	107.15
		16QAM	1 / 49	2501.0	21.42	138.68
			1 / 25	2593.0	**21.68**	147.23
			1 / 49	2685.0	20.57	114.02
	5	QPSK	1 / 24	2498.5	21.99	158.12
			1 / 24	2593.0	**22.00**	158.49
			1 / 24	2687.5	20.51	112.46
		16QAM	1 / 24	2498.5	20.67	116.68
			1 / 24	2593.0	**21.25**	133.35
			1 / 24	2687.5	19.60	91.20

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

10.1.2. ERP/EIRP DATA

GSM850

GSM850

GPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788869685
Date: 2019-02-13
Test Engineer: 47989
Configuration: EUT / X-Position
Location: Chamber 1
Mode: GPRS 850 MHz Fundamentals

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 2.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
824.20	23.96	V	3.0	-1.5	19.47	38.5	-19.0	
824.20	30.87	H	3.0	-1.5	26.38	38.5	-12.1	
Mid Ch								
836.60	24.06	V	3.0	-1.4	19.60	38.5	-18.9	
836.60	30.37	H	3.0	-1.4	25.90	38.5	-12.6	
High Ch								
848.80	24.03	V	3.1	-1.4	19.59	38.5	-18.9	
848.80	30.62	H	3.1	-1.4	26.18	38.5	-12.3	

GSM850

EGPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788869685
Date: 2019-02-13
Test Engineer: 47989
Configuration: EUT / X-Position
Location: Chamber 1
Mode: EGPRS 850 MHz Fundamentals

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 2.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
824.20	18.67	V	3.0	-1.5	14.18	38.5	-24.3	
824.20	25.65	H	3.0	-1.5	21.16	38.5	-17.3	
Mid Ch								
836.60	18.55	V	3.0	-1.4	14.09	38.5	-24.4	
836.60	25.22	H	3.0	-1.4	20.75	38.5	-17.7	
High Ch								
848.80	18.75	V	3.1	-1.4	14.31	38.5	-24.2	
848.80	25.53	H	3.1	-1.4	21.09	38.5	-17.4	

GSM1900

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

GSM1900

GPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788869685
Date: 2019-02-12
Test Engineer: 45585
Configuration: EUT, X-Position
Location: Chamber 2
Mode: GPRS 1900 MHz Fundamentals

Test Equpment:
Receiving: Horn 3117[00168724], and Chamber 2 SMA Cables
Substitution: Horn 3115[00167451], 2.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.20	14.74	V	4.5	9.4	19.66	33.0	-13.3	
1850.20	21.29	H	4.5	9.4	26.21	33.0	-6.8	
Mid Ch								
1880.00	14.14	V	4.5	9.2	18.80	33.0	-14.2	
1880.00	22.15	H	4.5	9.2	26.82	33.0	-6.2	
High Ch								
1909.80	13.34	V	4.6	8.9	17.70	33.0	-15.3	
1909.80	23.14	H	4.6	8.9	27.50	33.0	-5.5	

GSM1900

EGPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4788869685
Date: 2019-02-12
Test Engineer: 45585
Configuration: EUT, X-Position
Location: Chamber 2
Mode: EGPRS 1900 MHz Fundamentals

Test Equpment:
Receiving: Horn 3117[00168724], and Chamber 2 SMA Cables
Substitution: Horn 3115[00167451], 2.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.20	13.55	V	4.5	9.4	18.47	33.0	-14.5	
1850.20	20.20	H	4.5	9.4	25.12	33.0	-7.9	
Mid Ch								
1880.00	12.85	V	4.5	9.2	17.51	33.0	-15.5	
1880.00	20.14	H	4.5	9.2	24.81	33.0	-8.2	
High Ch								
1909.80	11.98	V	4.6	8.9	16.34	33.0	-16.7	
1909.80	20.88	H	4.6	8.9	25.24	33.0	-7.8	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.