DESIGN SPECIFICATION

DESIGN	**INTERNAL ANTENNA**
MODEL / TYPE	**SM-A276B / BT/WIFI INTENNA**
KYOCERA AVX P/N	**MF20189**
SEC CODE	**GH42-07201A**
CUSTOMER	**SAMSUNG ELECTRONICS CO., LTD.**
SUPPLIER	**KYOCERA AVX INC.**
TEST DATE	**2026.03.10**

ENGINEERING MANAGER CHECKED	MECHANICAL MANAGER CHECKED	DESIGN MANAGER CHECKED
JH Lee	TW Kim	GC Choi

LEAD-FREE

MSL 1

2026 © COPYRIGHT KYOCERA AVX INC.

This document is issued by Kyocera AVX Inc. (hereinafter called Kyocera AVX) in confidence, and is not to be reproduced in whole or in part without the prior written permission of Kyocera AVX. The information contained herein is the property of Kyocera AVX and is to be used only for the purpose for which it is BT/WIFI mitted and is not to be released in whole or in part without the prior written permission of Kyocera AVX.

CONTENTS

1. Abbreviations and Definitions 3
2. ELECTRICAL SPECIFICATION FOR SM-A276B 4
2.1. Frequency Band 4
2.2. Electrical Characteristics 4
2.2.1. VSWR 4
2.3. Passive Measurement 5
2.3.1. Input Return Loss and VSWR 5
2.4. SM-A276B Handset WIFI INTENNA 6
3. TEST METHOD 8
3.1. Measurement information 8
3.2. Return Loss & VSWR Test 9
3.3. Return Loss & VSWR Test 9
3.4. Radiation Pattern Test 10

Kyocera AVX, Inc. Confidential & Proprietary

Purpose and Scope

The purpose of this document is to establish a design specification for the antenna DESIGN that Kyocera AVX is developing for the Samsung SM-A276B wireless device. Any changes or additions to this specification can affect schedule and/or cost or the DESIGN and should be negotiated between Kyocera AVX and Samsung before being incorporated into the specification. Upon agreement of this specification, Kyocera AVX will make no changes without the written approval from Samsung. Any changes requested by Samsung will be given to Kyocera AVX with sufficient time to evaluate the cost impact and react as required.

1. Abbreviations and Definitions

AVG	Average
˚	Degree
˚C	Celsius (degrees Centigrade)
cm	Centimeter
G	Gravitational Force
g	Grams
Hz	Hertz
In	Inches
IQC	Incoming Quality Control
MHz	Megahertz
m	Meter
mm	Millimeter
N	Newton
PCB	Printed Circuit Board
TX	Transmit Band
RH	Relative Humidity
RX	Receive Band
VSWR	Voltage Standing Wave Ratio
W	Watt

Design specification: A target specification to guide design process.
DESIGN Specification: A final specification for the qualified DESIGN.

Kyocera AVX, Inc. Confidential & Proprietary

2. ELECTRICAL SPECIFICATION FOR SM-A276B

2.1. Frequency Band

Mode	Frequency Band (MHz)
WIFI	2,400~2,485 MHz, 5,150~5,850 MHz

2.2. Electrical Characteristics

2.2.1. VSWR

< Handset mounted typical measurements >

Frequency Range	2,400 MHz	2,485 MHz	5,150 MHz	5,850 MHz
V.S.W.R	1.7 ± 0.5:1	2.2 ± 0.5:1	1.9 ± 0.5:1	1.8 ± 0.5:1

<BT/WiFi Antenna>

Matching Requirements

In order to assure the best performance of the antenna, the matching will be evaluated in free space and in talk position. The antenna will comply with the Electrical Specification requirements, as set out below, while mounted on the device containing the PCB. The device and PCB are to be provided by the customer and should be representative of the latest design version of all parts. Any modifications in the device or PCB can affect the performance of the antenna and should be discussed with Kyocera AVX to determine the affect of such changes on the antenna performance and delivery requirements.



Kyocera AVX, Inc. Confidential & Proprietary

2.3. Passive Measurement

2.3.1. Input Return Loss and VSWR

WiFi Antenna

Kyocera AVX, Inc. Confidential & Proprietary

2.4. SM-A276B Handset WIFI INTENNA





<Handset mounted typical measurements>

Frequency	Efficiency	Average Gain			Max Gain		
		Ver	Hor	Total	Ver	Hor	Total
2,400,000,000 Hz	12.2 %	-11.6 dBi	-12.7 dBi	-9.1 dBi	-5.2 dBi	-7.2 dBi	-4.4 dBi
2,412,000,000 Hz	13.7 %	-11.2 dBi	-12.2 dBi	-8.6 dBi	-4.5 dBi	-6.7 dBi	-3.8 dBi
2,437,000,000 Hz	13.2 %	-11.3 dBi	-12.4 dBi	-8.8 dBi	-4.5 dBi	-6.9 dBi	-3.8 dBi
2,451,000,000 Hz	11.5 %	-11.9 dBi	-12.9 dBi	-9.4 dBi	-5.1 dBi	-7.6 dBi	-4.3 dBi
2,472,000,000 Hz	11.2 %	-12.0 dBi	-13.1 dBi	-9.5 dBi	-5.0 dBi	-7.7 dBi	-4.0 dBi
2,485,000,000 Hz	10.5 %	-12.3 dBi	-13.3 dBi	-9.8 dBi	-5.1 dBi	-7.8 dBi	-4.1 dBi

Kyocera AVX, Inc. Confidential & Proprietary





<Handset mounted typical measurements>

Frequency	Efficiency	Average Gain			Max Gain		
		Ver	Hor	Total	Ver	Hor	Total
5,150,000,000 Hz	8.4 %	-12.6 dBi	-15.4 dBi	-10.8 dBi	-5.7 dBi	-8.5 dBi	-5.1 dBi
5,290,000,000 Hz	10.2 %	-11.8 dBi	-14.4 dBi	-9.9 dBi	-6.3 dBi	-5.4 dBi	-4.1 dBi
5,430,000,000 Hz	11.2 %	-10.9 dBi	-15.1 dBi	-9.5 dBi	-5.1 dBi	-6.3 dBi	-4.6 dBi
5,570,000,000 Hz	5.8 %	-15.7 dBi	-15.1 dBi	-12.4 dBi	-6.8 dBi	-5.8 dBi	-4.8 dBi
5,710,000,000 Hz	12.5 %	-12.5 dBi	-11.7 dBi	-9.0 dBi	-8.1 dBi	-6.6 dBi	-4.6 dBi
5,850,000,000 Hz	9.0 %	-12.2 dBi	-15.3 dBi	-10.5 dBi	-7.0 dBi	-6.5 dBi	-4.3 dBi

Kyocera AVX, Inc. Confidential & Proprietary

3. TEST METHOD

3.1. Measurement information

-. Measurement: KYOCERA AVX Ant Lab.
-. Equipment: KSS Chamber, ZNB 8 Network Analyzer

* KSS Chamber
The Bluetest Reverberation Test Systems is the ideal choice for developers of wireless devices and components as well as operators wanting to verify their suppliers' wireless devices. Over-The-Air (OTA) measurements reflect the true performance of the device and ensure that the tested product performs as intended once released to the market. The patented design creates a rich and isotropic multipath environment inside the chamber allowing for fast, easy and realistic performance measurements on SISO as well as MIMO devices like LTE and WLAN. The RTS is capable of performing passive measurements like antenna efficiency, diversity and MIMO gain as well as active measurements like TRP, TIS and Throughput (TPUT).

- Chamber Information
- Location : Kyocera-Avx
- Size : 3 x 2.5 x 2.5m
- Frequency : 600MHz to 6000MHz
- Tx Antenna : KSS-HA600 (Double Rigid Horn Antenna)
- KSS 3D Motion Controller

* Test Equipment list

Part	Model Name	Specification	
Tx Antenna	KSS-HA600	600MHz to 6000MHz	
Reference Antenna	KSS-HA600	600MHz to 6000MHz	
Network Analyzer	Agilent E5071B	300kHz to 8.5GHz	Cal. Due : 2026.10.05
Measurement Software	KSS-ANT		

* **Test Date : 2026-03-10**
* **Test Person : JHLee / Senior Antenna Engineer / Kyocera AVX Components.**

Signature :

Kyocera AVX, Inc. Confidential & Proprietary

3.2. Return Loss & VSWR Test

The VSWR measurement of antennas assembled into a fully operating SM-A276B Handset is measured on the Network Analyzer. The Handset is set up with a 50 Ohm coaxial cable connected to the 50 Ohm point. Calibration is done at the end of the 50 Ohm coaxial cable connection. The other end of the 50 Ohm coaxial cable is connected to a network analyzer. The device is positioned on a non-conductive table for free space measurements.



Figure 1: Testing with network analyzer

3.3. Return Loss & VSWR Test

Samsung Antenna Lab has a system that can measure VSWR using KSS chamber and ZNB8 network analyzer. In order to measure the VSWR of each antenna, the lab connects the coaxial cable to the point in contact with the antenna on the main board. The VSWR is measured through the coaxial cable connected in the set. At this time, SM-A276B is assembled in the same state as the user environment.

Kyocera AVX, Inc. Confidential & Proprietary

3.4. Radiation Pattern Test

Antennas tested for Gain and Efficiency must be assembled into the enclosure and tested in the fully assembled and operating SM-A276B Handset. The antenna is tested in free space in the anechoic chamber in the H, E1 and, E2 planes. The radiation patterns are measured at the center of transmit and receive bands.

Test Method (Manufacturing)
All measurements are done with SM-A276B fully assembled. Measure in consideration of the customer's usage environment. Use a fully shielded chamber environment to prevent any noise-induced errors. Typically, the electrical properties of the antenna are measured using a jig that can hold the set.

Kyocera AVX, Inc. Confidential & Proprietary