

EX3DM4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                        | Group    | PAR (dB) | Unc <sup>2</sup> k = 2 |
|-------|-----|--------------------------------------------------|----------|----------|------------------------|
| 10230 | CAE | 8.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 10.25    | ±9.6                   |
| 10231 | CAE | 8.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB        | LTE-TDD  | 9.19     | ±9.6                   |
| 10232 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.48     | ±9.6                   |
| 10233 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB        | LTE-TDD  | 9.21     | ±9.6                   |
| 10235 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 9.48     | ±9.6                   |
| 10236 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 10.25    | ±9.6                   |
| 10237 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 9.48     | ±9.6                   |
| 10239 | CAG | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB      | LTE-TDD  | 10.25    | ±9.6                   |
| 10240 | CAG | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB       | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.82     | ±9.6                   |
| 10242 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.80     | ±9.6                   |
| 10243 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.46     | ±9.6                   |
| 10244 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.05    | ±9.6                   |
| 10245 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.05    | ±9.6                   |
| 10246 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.30     | ±9.6                   |
| 10247 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.91     | ±9.6                   |
| 10248 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB      | LTE-TDD  | 9.29     | ±9.6                   |
| 10250 | CAH | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 9.91     | ±9.6                   |
| 10251 | CAH | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 10.17    | ±9.6                   |
| 10252 | CAH | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.29     | ±9.6                   |
| 10253 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 9.80     | ±9.6                   |
| 10254 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB    | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB     | LTE-TDD  | 9.20     | ±9.6                   |
| 10256 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.66     | ±9.6                   |
| 10257 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 10.08    | ±9.6                   |
| 10258 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.94     | ±9.6                   |
| 10259 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.98     | ±9.6                   |
| 10260 | CAE | 3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.24     | ±9.6                   |
| 10262 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.82     | ±9.6                   |
| 10263 | CAH | 5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 10.16    | ±9.6                   |
| 10264 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB     | LTE-TDD  | 9.22     | ±9.6                   |
| 10265 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 9.92     | ±9.6                   |
| 10266 | CAH | 10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.30     | ±9.6                   |
| 10268 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.05    | ±9.6                   |
| 10269 | CAG | 15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB   | LTE-TDD  | 10.13    | ±9.6                   |
| 10270 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB    | LTE-TDD  | 9.55     | ±9.6                   |
| 10274 | CAC | Rel. 6 HSUPA Subsect 2, beta-d0, QPSK, 5.0 MHz   | WCDMA    | 4.67     | ±9.6                   |
| 10275 | CAC | Rel. 6 HSUPA Subsect 2, beta-d15, QPSK, 5.0 MHz  | WCDMA    | 3.95     | ±9.6                   |
| 10290 | AAB | PC1, SC55, Full frame rate, 1xRTT                | CDMA2000 | 3.91     | ±9.6                   |
| 10291 | AAB | PC3, SC55, Full frame rate, 1xRTT                | CDMA2000 | 3.45     | ±9.6                   |
| 10292 | AAB | PC3, SC32, Full frame rate, SCH0 disabled, 1xRTT | CDMA2000 | 3.39     | ±9.6                   |
| 10293 | AAB | PC3, SC3, Full frame rate, 1xRTT                 | CDMA2000 | 3.50     | ±9.6                   |
| 10295 | AAB | PC3, SC3, 1/8 frame rate, 1xRTT                  | CDMA2000 | 12.49    | ±9.6                   |
| 10297 | AAE | 20.0 MHz, QPSK, 50% RB                           | LTE-FDD  | 5.81     | ±9.6                   |
| 10298 | AAE | 3.0 MHz, QPSK, 50% RB                            | LTE-FDD  | 5.72     | ±9.6                   |
| 10299 | AAE | 3.0 MHz, 16QAM, 50% RB                           | LTE-FDD  | 6.39     | ±9.6                   |
| 10300 | AAE | 3.0 MHz, 64QAM, 50% RB                           | LTE-FDD  | 6.60     | ±9.6                   |
| 10301 | AAA | PUSC 28.18, QPSK, 5.0 ms, 18 TRAF SYM            | WiMAX    | 12.03    | ±9.6                   |
| 10302 | AAA | PUSC 28.18, QPSK, 5.0 ms, 15 TRAF SYM            | WiMAX    | 12.57    | ±9.6                   |
| 10303 | AAA | PUSC 31.15, 64QAM, 5.0 ms, 15 TRAF SYM           | WiMAX    | 12.52    | ±9.6                   |
| 10304 | AAA | PUSC 28.18, 64QAM, 5.0 ms, 18 TRAF SYM           | WiMAX    | 11.86    | ±9.6                   |
| 10305 | AAA | PUSC 31.15, 64QAM, 10.0 ms, 15 TRAF SYM          | WiMAX    | 15.24    | ±9.6                   |
| 10306 | AAA | PUSC 28.18, 64QAM, 10.0 ms, 18 TRAF SYM          | WiMAX    | 14.67    | ±9.6                   |
| 10307 | AAA | PUSC 28.18, QPSK, 10.0 ms, 18 TRAF SYM           | WiMAX    | 14.48    | ±9.6                   |
| 10308 | AAA | PUSC 28.18, 16QAM, 10.0 ms, 18 TRAF SYM          | WiMAX    | 14.46    | ±9.6                   |
| 10309 | AAA | AMC 2x3, 20.16, 16QAM, 10.0 ms, 18 TRAF SYM      | WiMAX    | 14.58    | ±9.6                   |
| 10310 | AAA | AMC 2x3, 20.16, QPSK, 10.0 ms, 18 TRAF SYM       | WiMAX    | 14.57    | ±9.6                   |
| 10311 | AAE | 15.0 MHz, QPSK, 100% RB                          | LTE-FDD  | 6.06     | ±9.6                   |
| 10315 | AAB | CRSS, DBPSK, 1.0 Mbps, 95.0% DC                  | WLAN     | 1.71     | ±9.6                   |
| 10316 | AAB | OFDM, BPSK, 6.0 Mbps, 95.0% DC                   | WLAN     | 8.26     | ±9.6                   |
| 10317 | AAE | OFDM, BPSK, 6.0 Mbps, 95.0% DC                   | WLAN     | 8.26     | ±9.6                   |

Certificate No: EX-3768\_Oct25

Page 12 of 20

EX3DV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                                   | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|-------------------------------------------------------------|----------|----------|------------------------|
| 10352 | AAA | Pulse (D=10%, T=5 ms)                                       | Generic  | 10.00    | ±0.6                   |
| 10353 | AAA | Pulse (D=20%, T=5 ms)                                       | Generic  | 9.98     | ±0.6                   |
| 10354 | AAA | Pulse (D=40%, T=5 ms)                                       | Generic  | 9.80     | ±0.6                   |
| 10355 | AAA | Pulse (D=60%, T=5 ms)                                       | Generic  | 9.22     | ±0.6                   |
| 10356 | AAA | Pulse (D=80%, T=5 ms)                                       | Generic  | 8.67     | ±0.6                   |
| 10367 | AAA | Random (BW=1 MHz, MOD=QPSK)                                 | Generic  | 5.10     | ±0.6                   |
| 10368 | AAA | Random (BW=10 MHz, MOD=QPSK)                                | Generic  | 5.22     | ±0.6                   |
| 10369 | AAA | Random (BW=100 kHz, MOD=64QAM)                              | Generic  | 6.27     | ±0.6                   |
| 10370 | AAA | Random (BW=40 MHz, MOD=64QAM)                               | Generic  | 6.27     | ±0.6                   |
| 10400 | AAF | VHT80, MCS5 (32.0 Mbps), 99.0% DC                           | WLAN     | 8.37     | ±0.6                   |
| 10401 | AAF | VHT40, MCS6 (108.0 Mbps), 99.7% DC                          | WLAN     | 8.50     | ±0.6                   |
| 10402 | AAF | VHT80, MCS5 (32.0 Mbps), 99.0% DC                           | WLAN     | 8.53     | ±0.6                   |
| 10403 | AAB | Rev. 0, 1xLV-DD                                             | CDMA2000 | 3.75     | ±0.6                   |
| 10404 | AAB | Rev. A, 1xLV-DD                                             | CDMA2000 | 3.77     | ±0.6                   |
| 10405 | AAB | RCJ, SCSS, Full frame rate, SCH0 enabled, 1xRTT             | CDMA2000 | 5.22     | ±0.6                   |
| 10410 | AAH | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 4, 1 RB                  | LTE-TDD  | 7.82     | ±0.6                   |
| 10411 | AAA | Random (BW=10 MHz, HIGH PAR)                                | Generic  | 6.54     | ±0.6                   |
| 10415 | AAA | DSSS, DQPSK, 1.0 Mbps, 99.8% DC                             | WLAN     | 1.54     | ±0.6                   |
| 10416 | AAA | OFDM, BPSK, 6.0 Mbps, 99.8% DC                              | WLAN     | 8.23     | ±0.6                   |
| 10417 | AAD | OFDM, BPSK, 6.0 Mbps, 99.8% DC                              | WLAN     | 8.23     | ±0.6                   |
| 10419 | AAA | OFDM (LTF), BPSK, 6.0 Mbps, 99.8% DC                        | WLAN     | 8.14     | ±0.6                   |
| 10419 | AAA | OFDM (STF), BPSK, 6.0 Mbps, 99.8% DC                        | WLAN     | 8.19     | ±0.6                   |
| 10422 | AAD | HT20 Greenfield, MCS0 (7.2 Mbps), 99.3% DC                  | WLAN     | 6.32     | ±0.6                   |
| 10423 | AAD | HT20 Greenfield, MCS4 (43.3 Mbps), 99.3% DC                 | WLAN     | 6.47     | ±0.6                   |
| 10424 | AAD | HT20 Greenfield, MCS7 (72.2 Mbps), 99.3% DC                 | WLAN     | 6.40     | ±0.6                   |
| 10425 | AAD | HT40 Greenfield, MCS0 (15.6 Mbps), 99.2% DC                 | WLAN     | 6.41     | ±0.6                   |
| 10426 | AAD | HT40 Greenfield, MCS4 (90.0 Mbps), 99.2% DC                 | WLAN     | 6.45     | ±0.6                   |
| 10427 | AAD | HT40 Greenfield, MCS7 (150.0 Mbps), 99.2% DC                | WLAN     | 6.41     | ±0.6                   |
| 10430 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 8.28     | ±0.6                   |
| 10431 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.36     | ±0.6                   |
| 10432 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±0.6                   |
| 10438 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±0.6                   |
| 10439 | AAB | RS Test Model 1, 64-QPCH, 64QAM, 5.0 MHz (DL)               | WCDMA    | 8.50     | ±0.6                   |
| 10439 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.62     | ±0.6                   |
| 10447 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 7.55     | ±0.6                   |
| 10448 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.53     | ±0.6                   |
| 10449 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.51     | ±0.6                   |
| 10450 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.49     | ±0.6                   |
| 10451 | AAB | RS Test Model 1, 64-QPCH, Clipping 44%, 64QAM, 5.0 MHz (DL) | WCDMA    | 7.59     | ±0.6                   |
| 10456 | AAD | VHT160, MCS5 (58.5 Mbps), 99.0% DC                          | WLAN     | 8.63     | ±0.6                   |
| 10457 | AAF | Ref. 5 DG-HSDPA, QPSK, 10.0 MHz                             | WCDMA    | 8.62     | ±0.6                   |
| 10458 | AAA | Rev. B, 2 carriers, 1xEV-DO                                 | CDMA2000 | 8.55     | ±0.6                   |
| 10458 | AAA | Rev. B, 3 carriers, 1xEV-DO                                 | CDMA2000 | 8.25     | ±0.6                   |
| 10460 | AAB | Ref. 99, AMR, QPSK, 5.0 MHz                                 | WCDMA    | 2.39     | ±0.6                   |
| 10461 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±0.6                   |
| 10462 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.30     | ±0.6                   |
| 10463 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.58     | ±0.6                   |
| 10464 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±0.6                   |
| 10465 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±0.6                   |
| 10466 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.57     | ±0.6                   |
| 10467 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±0.6                   |
| 10468 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±0.6                   |
| 10469 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.56     | ±0.6                   |
| 10470 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±0.6                   |
| 10471 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±0.6                   |
| 10472 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±0.6                   |
| 10473 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.62     | ±0.6                   |
| 10474 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±0.6                   |
| 10475 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±0.6                   |
| 10477 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±0.6                   |
| 10478 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±0.6                   |
| 10479 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.74     | ±0.6                   |
| 10480 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.18     | ±0.6                   |
| 10481 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.45     | ±0.6                   |
| 10482 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.71     | ±0.6                   |
| 10483 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.39     | ±0.6                   |

EX3DV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                      | Group   | PAR (dB) | Unc <sup>E</sup> $k=2$ |
|-------|-----|------------------------------------------------|---------|----------|------------------------|
| 10484 | AAD | 8.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.47     | $\pm 0.6$              |
| 10486 | AAG | 8.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB    | LTE-TDD | 7.59     | $\pm 0.6$              |
| 10486 | AAG | 8.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.30     | $\pm 0.6$              |
| 10487 | AAG | 8.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.60     | $\pm 0.6$              |
| 10488 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.70     | $\pm 0.6$              |
| 10489 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.31     | $\pm 0.6$              |
| 10490 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | $\pm 0.6$              |
| 10491 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | $\pm 0.6$              |
| 10492 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.41     | $\pm 0.6$              |
| 10493 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.55     | $\pm 0.6$              |
| 10494 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | $\pm 0.6$              |
| 10495 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.37     | $\pm 0.6$              |
| 10498 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | $\pm 0.6$              |
| 10497 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.87     | $\pm 0.6$              |
| 10498 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.40     | $\pm 0.6$              |
| 10499 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.69     | $\pm 0.6$              |
| 10500 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.67     | $\pm 0.6$              |
| 10501 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.44     | $\pm 0.6$              |
| 10502 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.62     | $\pm 0.6$              |
| 10503 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.72     | $\pm 0.6$              |
| 10504 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.21     | $\pm 0.6$              |
| 10505 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.64     | $\pm 0.6$              |
| 10506 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | $\pm 0.6$              |
| 10507 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.36     | $\pm 0.6$              |
| 10508 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.55     | $\pm 0.6$              |
| 10509 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.99     | $\pm 0.6$              |
| 10510 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.49     | $\pm 0.6$              |
| 10511 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.51     | $\pm 0.6$              |
| 10512 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | $\pm 0.6$              |
| 10513 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.42     | $\pm 0.6$              |
| 10514 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.45     | $\pm 0.6$              |
| 10516 | AAA | CRBS, DQPSK, 2.0 Mbps, 99.0% DC                | WLAN    | 1.58     | $\pm 0.6$              |
| 10516 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 99.0% DC             | WLAN    | 1.57     | $\pm 0.6$              |
| 10517 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 99.0% DC            | WLAN    | 1.58     | $\pm 0.6$              |
| 10518 | AAD | OFDM, BPSK, 8.0 Mbps, 99.0% DC                 | WLAN    | 8.23     | $\pm 0.6$              |
| 10519 | AAD | OFDM, QPSK, 12.0 Mbps, 99.0% DC                | WLAN    | 8.39     | $\pm 0.6$              |
| 10520 | AAD | OFDM, QPSK, 18.0 Mbps, 99.0% DC                | WLAN    | 8.12     | $\pm 0.6$              |
| 10521 | AAD | OFDM, 16QAM, 24.0 Mbps, 99.0% DC               | WLAN    | 7.97     | $\pm 0.6$              |
| 10522 | AAD | OFDM, 16QAM, 36.0 Mbps, 99.0% DC               | WLAN    | 8.49     | $\pm 0.6$              |
| 10523 | AAD | OFDM, 64QAM, 48.0 Mbps, 99.0% DC               | WLAN    | 8.68     | $\pm 0.6$              |
| 10524 | AAD | OFDM, 64QAM, 54.0 Mbps, 99.0% DC               | WLAN    | 8.27     | $\pm 0.6$              |
| 10525 | AAD | VHT20, MCS0 (8.5 Mbps), 99.0% DC               | WLAN    | 8.38     | $\pm 0.6$              |
| 10526 | AAD | VHT20, MCS1 (13.0 Mbps), 99.0% DC              | WLAN    | 8.42     | $\pm 0.6$              |
| 10527 | AAD | VHT20, MCS2 (19.5 Mbps), 99.0% DC              | WLAN    | 8.21     | $\pm 0.6$              |
| 10528 | AAD | VHT20, MCS3 (26.0 Mbps), 99.0% DC              | WLAN    | 8.26     | $\pm 0.6$              |
| 10529 | AAD | VHT20, MCS4 (30.0 Mbps), 99.0% DC              | WLAN    | 8.36     | $\pm 0.6$              |
| 10531 | AAD | VHT20, MCS5 (38.5 Mbps), 99.0% DC              | WLAN    | 8.43     | $\pm 0.6$              |
| 10532 | AAD | VHT20, MCS7 (55.0 Mbps), 99.0% DC              | WLAN    | 8.29     | $\pm 0.6$              |
| 10533 | AAD | VHT20, MCS8 (78.0 Mbps), 99.0% DC              | WLAN    | 8.35     | $\pm 0.6$              |
| 10534 | AAD | VHT40, MCS0 (13.5 Mbps), 99.0% DC              | WLAN    | 8.45     | $\pm 0.6$              |
| 10535 | AAD | VHT40, MCS1 (27.0 Mbps), 99.0% DC              | WLAN    | 8.45     | $\pm 0.6$              |
| 10536 | AAD | VHT40, MCS2 (40.5 Mbps), 99.0% DC              | WLAN    | 8.32     | $\pm 0.6$              |
| 10537 | AAD | VHT40, MCS3 (54.0 Mbps), 99.0% DC              | WLAN    | 8.44     | $\pm 0.6$              |
| 10538 | AAD | VHT40, MCS4 (81.0 Mbps), 99.0% DC              | WLAN    | 8.54     | $\pm 0.6$              |
| 10540 | AAD | VHT40, MCS6 (121.5 Mbps), 99.0% DC             | WLAN    | 8.39     | $\pm 0.6$              |
| 10541 | AAD | VHT40, MCS7 (135.0 Mbps), 99.0% DC             | WLAN    | 8.48     | $\pm 0.6$              |
| 10542 | AAD | VHT40, MCS8 (162.0 Mbps), 99.0% DC             | WLAN    | 8.65     | $\pm 0.6$              |
| 10543 | AAD | VHT40, MCS9 (180.0 Mbps), 99.0% DC             | WLAN    | 8.65     | $\pm 0.6$              |
| 10544 | AAD | VHT80, MCS0 (29.3 Mbps), 99.0% DC              | WLAN    | 8.47     | $\pm 0.6$              |
| 10545 | AAD | VHT80, MCS1 (58.5 Mbps), 99.0% DC              | WLAN    | 8.55     | $\pm 0.6$              |
| 10546 | AAD | VHT80, MCS2 (87.8 Mbps), 99.0% DC              | WLAN    | 8.35     | $\pm 0.6$              |
| 10547 | AAD | VHT80, MCS3 (117.0 Mbps), 99.0% DC             | WLAN    | 8.48     | $\pm 0.6$              |
| 10548 | AAD | VHT80, MCS4 (175.5 Mbps), 99.0% DC             | WLAN    | 8.27     | $\pm 0.6$              |
| 10550 | AAD | VHT80, MCS6 (263.3 Mbps), 99.0% DC             | WLAN    | 8.28     | $\pm 0.6$              |
| 10551 | AAD | VHT80, MCS7 (329.2 Mbps), 99.0% DC             | WLAN    | 8.50     | $\pm 0.6$              |
| 10552 | AAD | VHT80, MCS9 (351.0 Mbps), 99.0% DC             | WLAN    | 8.42     | $\pm 0.6$              |

Certificate No: EX-3768\_Oct25

Page 14 of 20

EX3DV4 - SN-3768

October 20, 2025

| UID   | Rev | Communication System Name             | Group | PAR (dB) | Unc <sup>0</sup> k = 2 |
|-------|-----|---------------------------------------|-------|----------|------------------------|
| 10558 | AAD | VHT180, MCS9 (899.0 Mbps), 99.0% DC   | WLAN  | 8.45     | +9.6                   |
| 10559 | AAD | VHT180, MCS10 (999.0 Mbps), 99.0% DC  | WLAN  | 8.48     | +9.6                   |
| 10560 | AAD | VHT180, MCS11 (1117.5 Mbps), 99.0% DC | WLAN  | 8.47     | +9.6                   |
| 10561 | AAD | VHT180, MCS12 (1236.0 Mbps), 99.0% DC | WLAN  | 8.50     | +9.6                   |
| 10562 | AAD | VHT180, MCS13 (1354.5 Mbps), 99.0% DC | WLAN  | 8.52     | +9.6                   |
| 10563 | AAD | VHT180, MCS14 (1473.0 Mbps), 99.0% DC | WLAN  | 8.61     | +9.6                   |
| 10564 | AAD | VHT180, MCS15 (1591.5 Mbps), 99.0% DC | WLAN  | 8.73     | +9.6                   |
| 10565 | AAD | VHT180, MCS16 (1710.0 Mbps), 99.0% DC | WLAN  | 8.86     | +9.6                   |
| 10566 | AAD | VHT180, MCS17 (1828.5 Mbps), 99.0% DC | WLAN  | 8.97     | +9.6                   |
| 10567 | AAD | VHT180, MCS18 (1947.0 Mbps), 99.0% DC | WLAN  | 9.08     | +9.6                   |
| 10568 | AAD | VHT180, MCS19 (2065.5 Mbps), 99.0% DC | WLAN  | 9.19     | +9.6                   |
| 10569 | AAD | VHT180, MCS20 (2184.0 Mbps), 99.0% DC | WLAN  | 9.30     | +9.6                   |
| 10570 | AAD | VHT180, MCS21 (2302.5 Mbps), 99.0% DC | WLAN  | 9.41     | +9.6                   |
| 10571 | AAD | VHT180, MCS22 (2421.0 Mbps), 99.0% DC | WLAN  | 9.52     | +9.6                   |
| 10572 | AAD | VHT180, MCS23 (2539.5 Mbps), 99.0% DC | WLAN  | 9.63     | +9.6                   |
| 10573 | AAD | VHT180, MCS24 (2658.0 Mbps), 99.0% DC | WLAN  | 9.74     | +9.6                   |
| 10574 | AAD | VHT180, MCS25 (2776.5 Mbps), 99.0% DC | WLAN  | 9.85     | +9.6                   |
| 10575 | AAD | VHT180, MCS26 (2895.0 Mbps), 99.0% DC | WLAN  | 9.96     | +9.6                   |
| 10576 | AAD | VHT180, MCS27 (3013.5 Mbps), 99.0% DC | WLAN  | 10.07    | +9.6                   |
| 10577 | AAD | VHT180, MCS28 (3132.0 Mbps), 99.0% DC | WLAN  | 10.18    | +9.6                   |
| 10578 | AAD | VHT180, MCS29 (3250.5 Mbps), 99.0% DC | WLAN  | 10.29    | +9.6                   |
| 10579 | AAD | VHT180, MCS30 (3369.0 Mbps), 99.0% DC | WLAN  | 10.40    | +9.6                   |
| 10580 | AAD | VHT180, MCS31 (3487.5 Mbps), 99.0% DC | WLAN  | 10.51    | +9.6                   |
| 10581 | AAD | VHT180, MCS32 (3606.0 Mbps), 99.0% DC | WLAN  | 10.62    | +9.6                   |
| 10582 | AAD | VHT180, MCS33 (3724.5 Mbps), 99.0% DC | WLAN  | 10.73    | +9.6                   |
| 10583 | AAD | VHT180, MCS34 (3843.0 Mbps), 99.0% DC | WLAN  | 10.84    | +9.6                   |
| 10584 | AAD | VHT180, MCS35 (3961.5 Mbps), 99.0% DC | WLAN  | 10.95    | +9.6                   |
| 10585 | AAD | VHT180, MCS36 (4080.0 Mbps), 99.0% DC | WLAN  | 11.06    | +9.6                   |
| 10586 | AAD | VHT180, MCS37 (4198.5 Mbps), 99.0% DC | WLAN  | 11.17    | +9.6                   |
| 10587 | AAD | VHT180, MCS38 (4317.0 Mbps), 99.0% DC | WLAN  | 11.28    | +9.6                   |
| 10588 | AAD | VHT180, MCS39 (4435.5 Mbps), 99.0% DC | WLAN  | 11.39    | +9.6                   |
| 10589 | AAD | VHT180, MCS40 (4554.0 Mbps), 99.0% DC | WLAN  | 11.50    | +9.6                   |
| 10590 | AAD | VHT180, MCS41 (4672.5 Mbps), 99.0% DC | WLAN  | 11.61    | +9.6                   |
| 10591 | AAD | VHT180, MCS42 (4791.0 Mbps), 99.0% DC | WLAN  | 11.72    | +9.6                   |
| 10592 | AAD | VHT180, MCS43 (4909.5 Mbps), 99.0% DC | WLAN  | 11.83    | +9.6                   |
| 10593 | AAD | VHT180, MCS44 (5028.0 Mbps), 99.0% DC | WLAN  | 11.94    | +9.6                   |
| 10594 | AAD | VHT180, MCS45 (5146.5 Mbps), 99.0% DC | WLAN  | 12.05    | +9.6                   |
| 10595 | AAD | VHT180, MCS46 (5265.0 Mbps), 99.0% DC | WLAN  | 12.16    | +9.6                   |
| 10596 | AAD | VHT180, MCS47 (5383.5 Mbps), 99.0% DC | WLAN  | 12.27    | +9.6                   |
| 10597 | AAD | VHT180, MCS48 (5502.0 Mbps), 99.0% DC | WLAN  | 12.38    | +9.6                   |
| 10598 | AAD | VHT180, MCS49 (5620.5 Mbps), 99.0% DC | WLAN  | 12.49    | +9.6                   |
| 10599 | AAD | VHT180, MCS50 (5739.0 Mbps), 99.0% DC | WLAN  | 12.60    | +9.6                   |
| 10600 | AAD | VHT180, MCS51 (5857.5 Mbps), 99.0% DC | WLAN  | 12.71    | +9.6                   |
| 10601 | AAD | VHT180, MCS52 (5976.0 Mbps), 99.0% DC | WLAN  | 12.82    | +9.6                   |
| 10602 | AAD | VHT180, MCS53 (6094.5 Mbps), 99.0% DC | WLAN  | 12.93    | +9.6                   |
| 10603 | AAD | VHT180, MCS54 (6213.0 Mbps), 99.0% DC | WLAN  | 13.04    | +9.6                   |
| 10604 | AAD | VHT180, MCS55 (6331.5 Mbps), 99.0% DC | WLAN  | 13.15    | +9.6                   |
| 10605 | AAD | VHT180, MCS56 (6450.0 Mbps), 99.0% DC | WLAN  | 13.26    | +9.6                   |
| 10606 | AAD | VHT180, MCS57 (6568.5 Mbps), 99.0% DC | WLAN  | 13.37    | +9.6                   |
| 10607 | AAD | VHT180, MCS58 (6687.0 Mbps), 99.0% DC | WLAN  | 13.48    | +9.6                   |
| 10608 | AAD | VHT180, MCS59 (6805.5 Mbps), 99.0% DC | WLAN  | 13.59    | +9.6                   |
| 10609 | AAD | VHT180, MCS60 (6924.0 Mbps), 99.0% DC | WLAN  | 13.70    | +9.6                   |
| 10610 | AAD | VHT180, MCS61 (7042.5 Mbps), 99.0% DC | WLAN  | 13.81    | +9.6                   |
| 10611 | AAD | VHT180, MCS62 (7161.0 Mbps), 99.0% DC | WLAN  | 13.92    | +9.6                   |
| 10612 | AAD | VHT180, MCS63 (7279.5 Mbps), 99.0% DC | WLAN  | 14.03    | +9.6                   |
| 10613 | AAD | VHT180, MCS64 (7398.0 Mbps), 99.0% DC | WLAN  | 14.14    | +9.6                   |
| 10614 | AAD | VHT180, MCS65 (7516.5 Mbps), 99.0% DC | WLAN  | 14.25    | +9.6                   |
| 10615 | AAD | VHT180, MCS66 (7635.0 Mbps), 99.0% DC | WLAN  | 14.36    | +9.6                   |
| 10616 | AAD | VHT180, MCS67 (7753.5 Mbps), 99.0% DC | WLAN  | 14.47    | +9.6                   |
| 10617 | AAD | VHT180, MCS68 (7872.0 Mbps), 99.0% DC | WLAN  | 14.58    | +9.6                   |
| 10618 | AAD | VHT180, MCS69 (7990.5 Mbps), 99.0% DC | WLAN  | 14.69    | +9.6                   |
| 10619 | AAD | VHT180, MCS70 (8109.0 Mbps), 99.0% DC | WLAN  | 14.80    | +9.6                   |

Certificate No: EX-3768 Oct25

Page 15 of 20

EXSDV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                  | Group     | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|--------------------------------------------|-----------|----------|------------------------|
| 10620 | AAD | VHT40, MCS4 (81.0 Mbps), 99.2% DC          | WLAN      | 8.87     | ±9.5                   |
| 10621 | AAD | VHT40, MCS5 (106.0 Mbps), 98.8% DC         | WLAN      | 8.77     | ±9.5                   |
| 10622 | AAD | VHT40, MCS6 (121.5 Mbps), 98.8% DC         | WLAN      | 8.93     | ±9.5                   |
| 10623 | AAD | VHT40, MCS7 (135.0 Mbps), 98.6% DC         | WLAN      | 8.82     | ±9.5                   |
| 10624 | AAD | VHT40, MCS9 (192.0 Mbps), 98.4% DC         | WLAN      | 8.95     | ±9.5                   |
| 10625 | AAD | VHT40, MCS9 (192.0 Mbps), 98.2% DC         | WLAN      | 8.95     | ±9.5                   |
| 10626 | AAD | VHT80, MCS9 (29.3 Mbps), 99.0% DC          | WLAN      | 8.93     | ±9.5                   |
| 10627 | AAD | VHT80, MCS1 (80.5 Mbps), 99.0% DC          | WLAN      | 8.99     | ±9.5                   |
| 10628 | AAD | VHT80, MCS2 (87.8 Mbps), 99.0% DC          | WLAN      | 8.71     | ±9.5                   |
| 10629 | AAD | VHT80, MCS3 (117.0 Mbps), 99.0% DC         | WLAN      | 8.95     | ±9.5                   |
| 10630 | AAD | VHT80, MCS4 (175.5 Mbps), 99.0% DC         | WLAN      | 8.72     | ±9.5                   |
| 10631 | AAD | VHT80, MCS6 (234.0 Mbps), 99.0% DC         | WLAN      | 8.81     | ±9.5                   |
| 10632 | AAD | VHT80, MCS6 (263.3 Mbps), 99.0% DC         | WLAN      | 8.74     | ±9.5                   |
| 10633 | AAD | VHT80, MCS7 (282.5 Mbps), 99.0% DC         | WLAN      | 8.83     | ±9.5                   |
| 10634 | AAD | VHT80, MCS8 (351.6 Mbps), 99.0% DC         | WLAN      | 8.80     | ±9.5                   |
| 10635 | AAD | VHT80, MCS8 (390.0 Mbps), 99.0% DC         | WLAN      | 8.81     | ±9.5                   |
| 10636 | AAD | VHT160, MCS6 (58.9 Mbps), 99.0% DC         | WLAN      | 8.83     | ±9.5                   |
| 10637 | AAD | VHT160, MCS1 (117.0 Mbps), 99.0% DC        | WLAN      | 8.79     | ±9.5                   |
| 10638 | AAD | VHT160, MCS2 (175.5 Mbps), 99.0% DC        | WLAN      | 8.85     | ±9.5                   |
| 10639 | AAD | VHT160, MCS3 (254.0 Mbps), 99.0% DC        | WLAN      | 8.85     | ±9.5                   |
| 10640 | AAD | VHT160, MCS4 (351.6 Mbps), 99.0% DC        | WLAN      | 8.95     | ±9.5                   |
| 10641 | AAD | VHT160, MCS5 (468.0 Mbps), 99.0% DC        | WLAN      | 8.95     | ±9.5                   |
| 10642 | AAD | VHT160, MCS6 (526.0 Mbps), 99.0% DC        | WLAN      | 8.95     | ±9.5                   |
| 10643 | AAD | VHT160, MCS7 (585.0 Mbps), 99.0% DC        | WLAN      | 8.99     | ±9.5                   |
| 10644 | AAD | VHT160, MCS8 (702.0 Mbps), 99.0% DC        | WLAN      | 8.95     | ±9.5                   |
| 10645 | AAD | VHT160, MCS9 (760.0 Mbps), 99.0% DC        | WLAN      | 8.11     | ±9.5                   |
| 10646 | AAH | 5.0 MHz, QPSK, UL/DL CFC: 2, SSC: 4, 1 RB  | LTE-TDD   | 11.86    | ±9.6                   |
| 10647 | AAH | 25.0 MHz, QPSK, UL/DL CFC: 2, SSC: 7, 1 RB | LTE-TDD   | 11.86    | ±9.6                   |
| 10648 | AAA | RC9, 3075, 1xPowerload                     | CUMAZ000  | 3.45     | ±9.6                   |
| 10649 | AAA | LE Test, OFSK                              | Bluetooth | 2.19     | ±9.6                   |
| 10671 | AAC | ET20, MCS0 (9.8 Mbps), 99.0% DC            | WLAN      | 8.98     | ±9.5                   |
| 10672 | AAC | ET20, MCS1 (17.0 Mbps), 99.0% DC           | WLAN      | 8.57     | ±9.5                   |
| 10673 | AAC | ET20, MCS2 (26.0 Mbps), 99.0% DC           | WLAN      | 8.78     | ±9.5                   |
| 10674 | AAC | ET20, MCS3 (34.0 Mbps), 99.0% DC           | WLAN      | 8.74     | ±9.5                   |
| 10675 | AAC | ET20, MCS4 (52.0 Mbps), 99.0% DC           | WLAN      | 8.90     | ±9.5                   |
| 10676 | AAC | ET20, MCS5 (69.0 Mbps), 99.0% DC           | WLAN      | 8.77     | ±9.5                   |
| 10677 | AAC | ET20, MCS6 (77.0 Mbps), 99.0% DC           | WLAN      | 8.75     | ±9.5                   |
| 10678 | AAC | ET20, MCS7 (86.0 Mbps), 99.0% DC           | WLAN      | 8.78     | ±9.5                   |
| 10679 | AAC | ET20, MCS8 (109.0 Mbps), 99.0% DC          | WLAN      | 8.89     | ±9.5                   |
| 10680 | AAC | ET20, MCS9 (115.0 Mbps), 99.0% DC          | WLAN      | 8.90     | ±9.5                   |
| 10681 | AAC | ET20, MCS10 (122.0 Mbps), 99.0% DC         | WLAN      | 8.92     | ±9.5                   |
| 10682 | AAC | ET20, MCS11 (135.0 Mbps), 99.0% DC         | WLAN      | 8.93     | ±9.5                   |
| 10683 | AAC | ET20, MCS0 (8.8 Mbps), 100.0% DC           | WLAN      | 8.82     | ±9.5                   |
| 10684 | AAC | ET20, MCS1 (17.0 Mbps), 100.0% DC          | WLAN      | 8.25     | ±9.5                   |
| 10685 | AAC | ET20, MCS2 (26.0 Mbps), 100.0% DC          | WLAN      | 8.39     | ±9.5                   |
| 10686 | AAC | ET20, MCS3 (34.0 Mbps), 100.0% DC          | WLAN      | 8.29     | ±9.5                   |
| 10687 | AAC | ET20, MCS4 (52.0 Mbps), 100.0% DC          | WLAN      | 8.45     | ±9.5                   |
| 10688 | AAC | ET20, MCS5 (69.0 Mbps), 100.0% DC          | WLAN      | 8.28     | ±9.5                   |
| 10689 | AAC | ET20, MCS6 (77.0 Mbps), 100.0% DC          | WLAN      | 8.55     | ±9.5                   |
| 10690 | AAC | ET20, MCS7 (86.0 Mbps), 100.0% DC          | WLAN      | 8.28     | ±9.5                   |
| 10691 | AAC | ET20, MCS8 (109.0 Mbps), 100.0% DC         | WLAN      | 8.25     | ±9.5                   |
| 10692 | AAC | ET20, MCS9 (115.0 Mbps), 100.0% DC         | WLAN      | 8.28     | ±9.5                   |
| 10693 | AAC | ET20, MCS10 (122.0 Mbps), 100.0% DC        | WLAN      | 8.25     | ±9.5                   |
| 10694 | AAC | ET20, MCS11 (135.0 Mbps), 100.0% DC        | WLAN      | 8.57     | ±9.5                   |
| 10695 | AAC | ET40, MCS0 (17.2 Mbps), 89.3% DC           | WLAN      | 8.78     | ±9.5                   |
| 10696 | AAC | ET40, MCS1 (34.0 Mbps), 89.3% DC           | WLAN      | 8.91     | ±9.5                   |
| 10697 | AAC | ET40, MCS2 (52.0 Mbps), 89.7% DC           | WLAN      | 8.81     | ±9.5                   |
| 10698 | AAC | ET40, MCS3 (69.0 Mbps), 89.7% DC           | WLAN      | 8.80     | ±9.5                   |
| 10699 | AAC | ET40, MCS4 (103.0 Mbps), 89.9% DC          | WLAN      | 8.82     | ±9.5                   |
| 10700 | AAC | ET40, MCS5 (138.0 Mbps), 89.3% DC          | WLAN      | 8.73     | ±9.5                   |
| 10701 | AAC | ET40, MCS6 (155.0 Mbps), 89.3% DC          | WLAN      | 8.88     | ±9.5                   |
| 10702 | AAC | ET40, MCS7 (172.0 Mbps), 89.3% DC          | WLAN      | 8.79     | ±9.5                   |
| 10703 | AAC | ET40, MCS8 (207.0 Mbps), 89.3% DC          | WLAN      | 8.82     | ±9.5                   |
| 10704 | AAC | ET40, MCS9 (229.0 Mbps), 89.3% DC          | WLAN      | 8.58     | ±9.5                   |
| 10705 | AAC | ET40, MCS10 (258.0 Mbps), 89.3% DC         | WLAN      | 8.59     | ±9.5                   |
| 10706 | AAC | ET40, MCS11 (257.0 Mbps), 89.3% DC         | WLAN      | 8.65     | ±9.5                   |

EX3DV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                        | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------|---------------|----------|------------------------|
| 10707 | AAC | ET40, MCS0 (17.2 Mbps), 99.8% DC                 | WLAN          | 8.32     | ±0.6                   |
| 10708 | AAC | ET40, MCS1 (34.0 Mbps), 99.7% DC                 | WLAN          | 8.55     | ±0.6                   |
| 10709 | AAC | ET40, MCS2 (52.0 Mbps), 99.7% DC                 | WLAN          | 8.33     | ±0.6                   |
| 10710 | AAC | ET40, MCS3 (99.0 Mbps), 99.7% DC                 | WLAN          | 8.20     | ±0.6                   |
| 10711 | AAC | ET40, MCS4 (103.0 Mbps), 99.8% DC                | WLAN          | 8.30     | ±0.6                   |
| 10712 | AAC | ET40, MCS5 (138.0 Mbps), 99.8% DC                | WLAN          | 8.87     | ±0.6                   |
| 10713 | AAC | ET40, MCS6 (155.0 Mbps), 99.8% DC                | WLAN          | 8.33     | ±0.6                   |
| 10714 | AAC | ET40, MCS7 (172.0 Mbps), 99.8% DC                | WLAN          | 8.25     | ±0.6                   |
| 10715 | AAC | ET40, MCS8 (207.0 Mbps), 99.8% DC                | WLAN          | 8.45     | ±0.6                   |
| 10716 | AAC | ET40, MCS9 (229.0 Mbps), 99.8% DC                | WLAN          | 8.30     | ±0.6                   |
| 10717 | AAC | ET40, MCS10 (255.0 Mbps), 99.8% DC               | WLAN          | 8.48     | ±0.6                   |
| 10718 | AAC | ET40, MCS11 (287.0 Mbps), 99.8% DC               | WLAN          | 8.24     | ±0.6                   |
| 10719 | AAC | ET80, MCS0 (38.0 Mbps), 99.0% DC                 | WLAN          | 8.91     | ±0.6                   |
| 10720 | AAC | ET80, MCS1 (72.1 Mbps), 99.0% DC                 | WLAN          | 8.97     | ±0.6                   |
| 10721 | AAC | ET80, MCS2 (108.1 Mbps), 99.0% DC                | WLAN          | 8.76     | ±0.6                   |
| 10722 | AAC | ET80, MCS3 (144.1 Mbps), 99.0% DC                | WLAN          | 8.55     | ±0.6                   |
| 10723 | AAC | ET80, MCS4 (181.2 Mbps), 99.0% DC                | WLAN          | 8.70     | ±0.6                   |
| 10724 | AAC | ET80, MCS5 (218.2 Mbps), 99.0% DC                | WLAN          | 8.90     | ±0.6                   |
| 10725 | AAC | ET80, MCS6 (254.4 Mbps), 99.0% DC                | WLAN          | 8.74     | ±0.6                   |
| 10726 | AAC | ET80, MCS7 (280.3 Mbps), 99.0% DC                | WLAN          | 8.72     | ±0.6                   |
| 10727 | AAC | ET80, MCS8 (322.4 Mbps), 99.0% DC                | WLAN          | 8.66     | ±0.6                   |
| 10728 | AAC | ET80, MCS9 (480.4 Mbps), 99.0% DC                | WLAN          | 8.66     | ±0.6                   |
| 10729 | AAC | ET80, MCS10 (540.4 Mbps), 99.0% DC               | WLAN          | 8.64     | ±0.6                   |
| 10730 | AAC | ET80, MCS11 (720.3 Mbps), 99.0% DC               | WLAN          | 8.67     | ±0.6                   |
| 10731 | AAC | ET80, MCS0 (36.0 Mbps), 100.0% DC                | WLAN          | 8.45     | ±0.6                   |
| 10732 | AAC | ET80, MCS1 (72.1 Mbps), 100.0% DC                | WLAN          | 8.46     | ±0.6                   |
| 10733 | AAC | ET80, MCS2 (108.1 Mbps), 100.0% DC               | WLAN          | 8.40     | ±0.6                   |
| 10734 | AAC | ET80, MCS3 (144.1 Mbps), 100.0% DC               | WLAN          | 8.25     | ±0.6                   |
| 10735 | AAC | ET80, MCS4 (216.2 Mbps), 100.0% DC               | WLAN          | 8.33     | ±0.6                   |
| 10736 | AAC | ET80, MCS5 (288.2 Mbps), 100.0% DC               | WLAN          | 8.27     | ±0.6                   |
| 10737 | AAC | ET80, MCS6 (324.4 Mbps), 100.0% DC               | WLAN          | 8.35     | ±0.6                   |
| 10738 | AAC | ET80, MCS7 (360.3 Mbps), 100.0% DC               | WLAN          | 8.42     | ±0.6                   |
| 10739 | AAC | ET80, MCS8 (432.4 Mbps), 100.0% DC               | WLAN          | 8.29     | ±0.6                   |
| 10740 | AAC | ET80, MCS9 (480.4 Mbps), 100.0% DC               | WLAN          | 8.45     | ±0.6                   |
| 10741 | AAC | ET80, MCS10 (540.4 Mbps), 100.0% DC              | WLAN          | 8.40     | ±0.6                   |
| 10742 | AAC | ET80, MCS11 (600.5 Mbps), 100.0% DC              | WLAN          | 8.43     | ±0.6                   |
| 10743 | AAC | ET160, MCS0 (72.0 Mbps), 98.2% DC                | WLAN          | 9.91     | ±0.6                   |
| 10744 | AAC | ET160, MCS1 (144.0 Mbps), 97.1% DC               | WLAN          | 9.15     | ±0.6                   |
| 10745 | AAC | ET160, MCS2 (216.0 Mbps), 97.4% DC               | WLAN          | 9.93     | ±0.6                   |
| 10746 | AAC | ET160, MCS3 (288.0 Mbps), 97.1% DC               | WLAN          | 9.11     | ±0.6                   |
| 10747 | AAC | ET160, MCS4 (432.0 Mbps), 97.4% DC               | WLAN          | 9.04     | ±0.6                   |
| 10748 | AAC | ET160, MCS5 (576.0 Mbps), 96.9% DC               | WLAN          | 9.93     | ±0.6                   |
| 10749 | AAC | ET160, MCS6 (648.0 Mbps), 96.7% DC               | WLAN          | 9.90     | ±0.6                   |
| 10750 | AAC | ET160, MCS7 (721.0 Mbps), 96.7% DC               | WLAN          | 9.79     | ±0.6                   |
| 10751 | AAC | ET160, MCS8 (865.0 Mbps), 96.3% DC               | WLAN          | 9.80     | ±0.6                   |
| 10752 | AAC | ET160, MCS9 (981.0 Mbps), 96.3% DC               | WLAN          | 9.81     | ±0.6                   |
| 10753 | AAC | ET160, MCS10 (1081.0 Mbps), 96.7% DC             | WLAN          | 9.80     | ±0.6                   |
| 10754 | AAC | ET160, MCS11 (1201.0 Mbps), 96.7% DC             | WLAN          | 9.84     | ±0.6                   |
| 10755 | AAC | ET160, MCS0 (72.0 Mbps), 96.8% DC                | WLAN          | 9.64     | ±0.6                   |
| 10756 | AAC | ET160, MCS1 (144.0 Mbps), 96.8% DC               | WLAN          | 9.77     | ±0.6                   |
| 10757 | AAC | ET160, MCS2 (216.0 Mbps), 97.1% DC               | WLAN          | 9.77     | ±0.6                   |
| 10758 | AAC | ET160, MCS3 (288.0 Mbps), 96.8% DC               | WLAN          | 9.69     | ±0.6                   |
| 10759 | AAC | ET160, MCS4 (432.0 Mbps), 97.1% DC               | WLAN          | 9.58     | ±0.6                   |
| 10760 | AAC | ET160, MCS5 (576.0 Mbps), 96.5% DC               | WLAN          | 9.49     | ±0.6                   |
| 10761 | AAC | ET160, MCS6 (648.0 Mbps), 96.3% DC               | WLAN          | 9.59     | ±0.6                   |
| 10762 | AAC | ET160, MCS7 (721.0 Mbps), 96.3% DC               | WLAN          | 9.49     | ±0.6                   |
| 10763 | AAC | ET160, MCS8 (865.0 Mbps), 95.9% DC               | WLAN          | 9.53     | ±0.6                   |
| 10764 | AAC | ET160, MCS9 (981.0 Mbps), 95.9% DC               | WLAN          | 9.54     | ±0.6                   |
| 10765 | AAC | ET160, MCS10 (1081.0 Mbps), 96.3% DC             | WLAN          | 9.54     | ±0.6                   |
| 10766 | AAC | ET160, MCS11 (1201.0 Mbps), 96.3% DC             | WLAN          | 9.51     | ±0.6                   |
| 10767 | AAC | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 99.9% DC, 1 RB   | 5G NR FR1 TDD | 7.99     | ±0.6                   |
| 10768 | AAC | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.01     | ±0.6                   |
| 10769 | AAC | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.01     | ±0.6                   |
| 10770 | AAC | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.02     | ±0.6                   |
| 10771 | AAC | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.02     | ±0.6                   |
| 10772 | AAC | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB | 5G NR FR1 TDD | 8.03     | ±0.6                   |

Certificate No: EX-3768\_Oct25

Page 17 of 20

EX3DV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                            | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------------|---------------|----------|------------------------|
| 10773 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.03     | ±0.6                   |
| 10774 | AAF | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.02     | ±0.6                   |
| 10775 | AAF | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 8.01     | ±0.6                   |
| 10776 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.20     | ±0.6                   |
| 10777 | AAE | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.30     | ±0.6                   |
| 10778 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10779 | AAE | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.42     | ±0.6                   |
| 10780 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.50     | ±0.6                   |
| 10781 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.58     | ±0.6                   |
| 10782 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.63     | ±0.6                   |
| 10783 | AAE | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 8.31     | ±0.6                   |
| 10784 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.20     | ±0.6                   |
| 10785 | AAE | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.40     | ±0.6                   |
| 10786 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.35     | ±0.6                   |
| 10787 | AAE | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.44     | ±0.6                   |
| 10788 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±0.6                   |
| 10789 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.97     | ±0.6                   |
| 10790 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.99     | ±0.6                   |
| 10791 | AAE | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB       | 5G NR FR1 TDD | 7.93     | ±0.6                   |
| 10792 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.92     | ±0.6                   |
| 10793 | AAE | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.95     | ±0.6                   |
| 10794 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.92     | ±0.6                   |
| 10795 | AAE | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.94     | ±0.6                   |
| 10796 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.92     | ±0.6                   |
| 10797 | AAE | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 8.01     | ±0.6                   |
| 10798 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.89     | ±0.6                   |
| 10799 | AAE | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.93     | ±0.6                   |
| 10800 | AAE | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.68     | ±0.6                   |
| 10802 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.87     | ±0.6                   |
| 10803 | AAE | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB    | 5G NR FR1 TDD | 7.68     | ±0.6                   |
| 10805 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10806 | AAE | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.37     | ±0.6                   |
| 10809 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10810 | AAE | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10812 | AAE | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.35     | ±0.6                   |
| 10817 | AAE | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 8.35     | ±0.6                   |
| 10818 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10819 | AAE | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.33     | ±0.6                   |
| 10820 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.30     | ±0.6                   |
| 10821 | AAE | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 10822 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 10823 | AAE | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.38     | ±0.6                   |
| 10824 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.39     | ±0.6                   |
| 10825 | AAE | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 10827 | AAE | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.52     | ±0.6                   |
| 10828 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.43     | ±0.6                   |
| 10829 | AAE | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB | 5G NR FR1 TDD | 8.40     | ±0.6                   |
| 10830 | AAE | CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.63     | ±0.6                   |
| 10831 | AAE | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.73     | ±0.6                   |
| 10832 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.74     | ±0.6                   |
| 10833 | AAE | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | 5G NR FR1 TDD | 7.70     | ±0.6                   |
| 10834 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.75     | ±0.6                   |
| 10839 | AAE | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.70     | ±0.6                   |
| 10836 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.68     | ±0.6                   |
| 10837 | AAE | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.68     | ±0.6                   |
| 10839 | AAE | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.70     | ±0.6                   |
| 10840 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | 5G NR FR1 TDD | 7.67     | ±0.6                   |
| 10841 | AAE | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB    | 5G NR FR1 TDD | 7.71     | ±0.6                   |
| 10843 | AAE | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.48     | ±0.6                   |
| 10844 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10846 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 10854 | AAE | CP-OFDM, 10.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 10855 | AAE | CP-OFDM, 15.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.36     | ±0.6                   |
| 10856 | AAE | CP-OFDM, 30.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.37     | ±0.6                   |
| 10857 | AAE | CP-OFDM, 35.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.25     | ±0.6                   |
| 10858 | AAE | CP-OFDM, 50.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB  | 5G NR FR1 TDD | 8.26     | ±0.6                   |

Certificate No: EX-3768\_Oct25

Page 18 of 20

EX3DV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                                | Group         | PAR (dB) | Unc <sup>E</sup> $k=2$ |
|-------|-----|----------------------------------------------------------|---------------|----------|------------------------|
| 10858 | AAF | CP-OFDM, 40.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.34     | +9.6                   |
| 10860 | AAF | CP-OFDM, 50.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.41     | +9.6                   |
| 10861 | AAF | CP-OFDM, 60.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.40     | +9.6                   |
| 10863 | AAF | CP-OFDM, 80.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.41     | +9.6                   |
| 10864 | AAF | CP-OFDM, 90.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.37     | +9.6                   |
| 10866 | AAF | CP-OFDM, 100.0 MHz, QPSK, 80 kHz, 100.0% DC, 100% RB     | 5G NR FR1 TDD | 8.41     | +9.6                   |
| 10866 | AAF | DFTs-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB      | 5G NR FR1 TDD | 5.68     | +9.6                   |
| 10868 | AAF | DFTs-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 5.88     | +9.6                   |
| 10869 | AAF | DFTs-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 5.75     | +9.6                   |
| 10870 | AAF | DFTs-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 5.86     | +9.6                   |
| 10871 | AAF | DFTs-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 5.75     | +9.6                   |
| 10872 | AAF | DFTs-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.02     | +9.6                   |
| 10873 | AAF | DFTs-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 6.51     | +9.6                   |
| 10874 | AAF | DFTs-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.53     | +9.6                   |
| 10875 | AAF | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 7.75     | +9.6                   |
| 10876 | AAF | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.39     | +9.6                   |
| 10877 | AAF | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB      | 5G NR FR2 TDD | 7.85     | +9.6                   |
| 10878 | AAF | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB   | 5G NR FR2 TDD | 8.41     | +9.6                   |
| 10879 | AAF | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB      | 5G NR FR2 TDD | 8.12     | +9.6                   |
| 10880 | AAF | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB   | 5G NR FR2 TDD | 8.39     | +9.6                   |
| 10881 | AAF | DFTs-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB      | 5G NR FR2 TDD | 5.75     | +9.6                   |
| 10882 | AAF | DFTs-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB   | 5G NR FR2 TDD | 5.88     | +9.6                   |
| 10883 | AAF | DFTs-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.57     | +9.6                   |
| 10884 | AAF | DFTs-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.53     | +9.6                   |
| 10885 | AAF | DFTs-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.61     | +9.6                   |
| 10886 | AAF | DFTs-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.65     | +9.6                   |
| 10887 | AAF | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 99.9% DC, 1 RB         | 5G NR FR2 TDD | 7.78     | +9.6                   |
| 10888 | AAF | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.85     | +9.6                   |
| 10889 | AAF | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 8.02     | +9.6                   |
| 10890 | AAF | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.40     | +9.6                   |
| 10891 | AAF | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 8.12     | +9.6                   |
| 10892 | AAF | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.41     | +9.6                   |
| 10897 | AAF | DFTs-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB         | 5G NR FR1 TDD | 5.66     | +9.6                   |
| 10899 | AAC | DFTs-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | +9.6                   |
| 10899 | AAB | DFTs-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | +9.6                   |
| 10900 | AAC | DFTs-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.56     | +9.6                   |
| 10901 | AAB | DFTs-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.56     | +9.6                   |
| 10902 | AAC | DFTs-OFDM, 35.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.56     | +9.6                   |
| 10903 | AAD | DFTs-OFDM, 45.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.55     | +9.6                   |
| 10904 | AAC | DFTs-OFDM, 55.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.55     | +9.6                   |
| 10905 | AAD | DFTs-OFDM, 65.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.55     | +9.6                   |
| 10906 | AAD | DFTs-OFDM, 85.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.55     | +9.6                   |
| 10907 | AAF | DFTs-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB      | 5G NR FR1 TDD | 5.75     | +9.6                   |
| 10908 | AAC | DFTs-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.83     | +9.6                   |
| 10909 | AAB | DFTs-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.98     | +9.6                   |
| 10910 | AAC | DFTs-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.83     | +9.6                   |
| 10911 | AAB | DFTs-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | +9.6                   |
| 10912 | AAC | DFTs-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10913 | AAD | DFTs-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10914 | AAC | DFTs-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.85     | +9.6                   |
| 10915 | AAD | DFTs-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.83     | +9.6                   |
| 10916 | AAD | DFTs-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.87     | +9.6                   |
| 10917 | AAD | DFTs-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10918 | AAF | DFTs-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB     | 5G NR FR1 TDD | 5.86     | +9.6                   |
| 10919 | AAC | DFTs-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.86     | +9.6                   |
| 10920 | AAB | DFTs-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.87     | +9.6                   |
| 10921 | AAC | DFTs-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10922 | AAD | DFTs-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.82     | +9.6                   |
| 10923 | AAC | DFTs-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10924 | AAD | DFTs-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10925 | AAC | DFTs-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.85     | +9.6                   |
| 10926 | AAD | DFTs-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | +9.6                   |
| 10927 | AAD | DFTs-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.94     | +9.6                   |
| 10928 | AAD | DFTs-OFDM, 5.0 MHz, QPSK, 15 kHz, 1 RB                   | 5G NR FR1 FDD | 5.52     | +9.6                   |
| 10929 | AAD | DFTs-OFDM, 10.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | +9.6                   |
| 10930 | AAC | DFTs-OFDM, 15.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | +9.6                   |

Certificate No: EX-3768\_Oct25

Page 18 of 20

EXSDV4 - SN:3768

October 20, 2025

| UID   | Rev | Communication System Name                   | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|---------------------------------------------|---------------|----------|------------------------|
| 10931 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10932 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10933 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10934 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10935 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 1 RB    | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10936 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 50% RB   | 5G NR FR1 FDD | 5.80     | ±9.6                   |
| 10937 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.77     | ±9.6                   |
| 10938 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.80     | ±9.6                   |
| 10939 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.80     | ±9.6                   |
| 10940 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.80     | ±9.6                   |
| 10941 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10942 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10943 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 50% RB  | 5G NR FR1 FDD | 5.95     | ±9.6                   |
| 10944 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 100% RB  | 5G NR FR1 FDD | 5.81     | ±9.6                   |
| 10945 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10946 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10947 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10948 | AAC | DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.84     | ±9.6                   |
| 10949 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10950 | AAC | DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10951 | AAD | DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 100% RB | 5G NR FR1 FDD | 5.92     | ±9.6                   |
| 10978 | AAA | BDR, 1.0 MHz, 75.7% DC                      | ULLA          | 1.16     | ±9.6                   |
| 10979 | AAA | HDR4, 2.0 MHz, 25.1% DC                     | ULLA          | 3.58     | ±9.6                   |
| 10980 | AAA | HDR8, 4.0 MHz, 15.5% DC                     | ULLA          | 10.02    | ±9.6                   |
| 10981 | AAA | HDRp4, 2.0 MHz, 59.0% DC                    | ULLA          | 3.19     | ±9.6                   |
| 10982 | AAA | HDRp8, 4.0 MHz, 30.3% DC                    | ULLA          | 3.43     | ±9.6                   |
| 11013 | AAB | EHT320, MCS1 (872.0 Mbps), 100.0% DC        | WLAN          | 8.47     | ±9.6                   |
| 11014 | AAB | EHT320, MCS2 (408.0 Mbps), 100.0% DC        | WLAN          | 8.45     | ±9.6                   |
| 11015 | AAB | EHT320, MCS3 (644.0 Mbps), 100.0% DC        | WLAN          | 8.44     | ±9.6                   |
| 11016 | AAB | EHT320, MCS4 (817.0 Mbps), 100.0% DC        | WLAN          | 8.44     | ±9.6                   |
| 11017 | AAD | EHT320, MCS5 (1099.0 Mbps), 100.0% DC       | WLAN          | 8.41     | ±9.6                   |
| 11018 | AAD | EHT320, MCS6 (1225.0 Mbps), 100.0% DC       | WLAN          | 8.40     | ±9.6                   |
| 11019 | AAB | EHT320, MCS7 (1381.0 Mbps), 100.0% DC       | WLAN          | 8.39     | ±9.6                   |
| 11020 | AAB | EHT320, MCS8 (1603.0 Mbps), 100.0% DC       | WLAN          | 8.27     | ±9.6                   |
| 11021 | AAB | EHT320, MCS9 (1815.0 Mbps), 100.0% DC       | WLAN          | 8.45     | ±9.6                   |
| 11022 | AAB | EHT320, MCS10 (2042.0 Mbps), 100.0% DC      | WLAN          | 8.35     | ±9.6                   |
| 11023 | AAB | EHT320, MCS11 (2260.0 Mbps), 100.0% DC      | WLAN          | 8.09     | ±9.6                   |
| 11024 | AAB | EHT320, MCS12 (2450.0 Mbps), 100.0% DC      | WLAN          | 8.42     | ±9.6                   |
| 11025 | AAB | EHT320, MCS13 (2722.0 Mbps), 100.0% DC      | WLAN          | 8.37     | ±9.6                   |
| 11026 | AAB | EHT320, MCS14 (296.0 Mbps), 100.0% DC       | WLAN          | 8.39     | ±9.6                   |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

**Client** **HCT**  
Gyeonggi-do, Republic of Korea

**Certificate No.** **EX-7655\_Jun25**

**CALIBRATION CERTIFICATE**

**Object** EX3DV4 - SN:7655

**Calibration procedure(s)** QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,  
QA CAL-25.v8  
Calibration procedure for dosimetric E-field probes

**Calibration date** June 03, 2025

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.  
All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .  
Calibration Equipment used (M&E critical for calibration):

| Primary Standards          | ID         | Calibration Date (Certificate No.)     | Sched. Cal. |
|----------------------------|------------|----------------------------------------|-------------|
| Power Sensor R&S NRP-33T   | SN: 100967 | 26-Mar-25 (No. 217-04290)              | Mar-26      |
| N-type mismatch combinator | SN: L1119  | 26-Mar-25 (No. 217-04292)              | Mar-26      |
| OCP DAK-12                 | SN: 1016   | 24-Sept-24 (No. OCP-DAK12-1016_Sep24)  | Sep-25      |
| OCP DAK-3.5                | SN: 1249   | 23-Sept-24 (No. OCP-DAK3.5-1249_Sep24) | Sep-25      |
| Reference Probe EX3DV4     | SN: 7349   | 10-Jan-25 (No. EX3-7349_Jan25)         | Jan-26      |
| DAE4                       | SN: 1301   | 07-Nov-24 (No. DAE4-1301_Nov24)        | Nov-26      |

| Secondary Standards | ID        | Check Date (in house)                            | Sched. Check |
|---------------------|-----------|--------------------------------------------------|--------------|
| ACAP 2020 Setup 1   | SN: L1404 | 30-Sept-24 (No. Report ACAP2020E-Cave 20240930e) | Sep-25       |

|               | Name           | Function              | Signature |
|---------------|----------------|-----------------------|-----------|
| Calibrated by | Joanna Lieshaj | Laboratory Technician |           |
| Approved by   | Sven Kühn      | Technical Manager     |           |

Issued: June 03, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX-7655\_Jun25

Page 1 of 21

|      |      |       |    |       |    |
|------|------|-------|----|-------|----|
| 결    | 합    | 장     | 하  | 일     | 자  |
| 제    | 기    | 지     | 문  |       |    |
| 서명/일 | 01   | 17/25 | 82 | 14/25 |    |
| 일 자  | 2025 | 06    | 10 | 2025  | 06 |

## Calibration Laboratory of Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary

|                        |                                                                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | tissue simulating liquid                                                                                                                       |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                      |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                     |
| DCP                    | diode compression point                                                                                                                        |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                   |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                  |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                           |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | information used in DASY system to align probe sensor X to the robot coordinate system                                                         |

## Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f < 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM<sub>lin</sub><sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

EX3DV4 - SN:7655

June 03, 2025

### Parameters of Probe: EX3DV4 - SN:7655

#### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k = 2) |
|-----------------------------------------------------------|----------|----------|----------|-------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.49     | 0.62     | 0.51     | ±10.1%      |
| DCP (mV) <sup>B</sup>                                     | 107.2    | 107.0    | 107.9    | ±4.7%       |

#### Calibration Results for Modulation Response

| UID   | Communication System Name   |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C     | D<br>dB | VR<br>mV | Max<br>dev. | Max<br>Unc <sup>E</sup><br>k = 2 |
|-------|-----------------------------|---|---------|------------------------------|-------|---------|----------|-------------|----------------------------------|
| 0     | CW                          | X | 0.00    | 0.00                         | 1.00  | 0.00    | 122.2    | ±2.2%       | ±4.7%                            |
|       |                             | Y | 0.00    | 0.00                         | 1.00  |         | 148.8    |             |                                  |
|       |                             | Z | 0.00    | 0.00                         | 1.00  |         | 125.6    |             |                                  |
| 10352 | Pulse Waveform (200Hz, 10%) | X | 1.83    | 62.22                        | 7.49  | 10.00   | 60.0     | ±2.4%       | ±9.6%                            |
|       |                             | Y | 1.45    | 60.24                        | 6.18  |         | 60.0     |             |                                  |
|       |                             | Z | 1.70    | 61.63                        | 7.29  |         | 60.0     |             |                                  |
| 10353 | Pulse Waveform (200Hz, 20%) | X | 0.84    | 60.01                        | 5.32  | 6.99    | 80.0     | ±2.2%       | ±9.6%                            |
|       |                             | Y | 0.80    | 60.00                        | 4.89  |         | 80.0     |             |                                  |
|       |                             | Z | 0.81    | 60.00                        | 5.43  |         | 80.0     |             |                                  |
| 10354 | Pulse Waveform (200Hz, 40%) | X | 22.00   | 76.00                        | 9.00  | 3.98    | 95.0     | ±2.7%       | ±9.6%                            |
|       |                             | Y | 0.13    | 136.03                       | 0.48  |         | 95.0     |             |                                  |
|       |                             | Z | 0.04    | 118.35                       | 0.44  |         | 95.0     |             |                                  |
| 10355 | Pulse Waveform (200Hz, 60%) | X | 11.77   | 153.29                       | 7.79  | 2.22    | 120.0    | ±1.7%       | ±9.6%                            |
|       |                             | Y | 8.37    | 159.23                       | 13.04 |         | 120.0    |             |                                  |
|       |                             | Z | 0.42    | 60.00                        | 2.92  |         | 120.0    |             |                                  |
| 10367 | QPSK Waveform, 1 MHz        | X | 0.52    | 62.56                        | 11.33 | 1.00    | 150.0    | ±4.2%       | ±9.6%                            |
|       |                             | Y | 0.48    | 61.61                        | 11.06 |         | 150.0    |             |                                  |
|       |                             | Z | 0.57    | 63.09                        | 11.40 |         | 150.0    |             |                                  |
| 10368 | QPSK Waveform, 10 MHz       | X | 1.27    | 64.81                        | 13.16 | 0.00    | 150.0    | ±1.2%       | ±9.6%                            |
|       |                             | Y | 1.22    | 64.45                        | 13.00 |         | 150.0    |             |                                  |
|       |                             | Z | 1.31    | 64.89                        | 13.22 |         | 150.0    |             |                                  |
| 10398 | 64-QAM Waveform, 100 kHz    | X | 1.75    | 64.86                        | 15.88 | 3.01    | 150.0    | ±1.0%       | ±9.6%                            |
|       |                             | Y | 1.82    | 63.72                        | 15.53 |         | 150.0    |             |                                  |
|       |                             | Z | 1.75    | 64.90                        | 15.94 |         | 150.0    |             |                                  |
| 10399 | 64-QAM Waveform, 40 MHz     | X | 2.77    | 65.88                        | 14.74 | 0.00    | 150.0    | ±1.9%       | ±9.6%                            |
|       |                             | Y | 2.72    | 65.67                        | 14.67 |         | 150.0    |             |                                  |
|       |                             | Z | 2.83    | 65.98                        | 14.77 |         | 150.0    |             |                                  |
| 10414 | WLAN CCDF, 64-QAM, 40 MHz   | X | 3.77    | 65.69                        | 15.00 | 0.00    | 150.0    | ±3.5%       | ±9.6%                            |
|       |                             | Y | 3.86    | 66.21                        | 15.27 |         | 150.0    |             |                                  |
|       |                             | Z | 3.86    | 65.77                        | 15.06 |         | 150.0    |             |                                  |

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sub>1</sub>-field uncertainty inside TSL (see Page 5).

<sup>B</sup> Linearization parameter uncertainty for maximum specified field strength.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4 - SN:7655

June 03, 2025

### Parameters of Probe: EX3DV4 - SN:7655

#### Sensor Model Parameters

|   | C1<br>IF | C2<br>IF | $\alpha$<br>$V^{-1}$ | T1<br>$ms V^{-2}$ | T2<br>$ms V^{-1}$ | T3<br>ms | T4<br>$V^{-2}$ | T5<br>$V^{-1}$ | T6   |
|---|----------|----------|----------------------|-------------------|-------------------|----------|----------------|----------------|------|
| x | 9.9      | 70.99    | 32.87                | 4.23              | 0.00              | 4.95     | 0.62           | 0.00           | 1.00 |
| y | 9.4      | 68.01    | 33.11                | 2.45              | 0.00              | 4.90     | 0.31           | 0.00           | 1.00 |
| z | 10.7     | 77.02    | 32.92                | 3.62              | 0.00              | 4.95     | 0.54           | 0.00           | 1.00 |

#### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle                               | 80.2°      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

**Note:** Measurement distance from surface can be increased to 3–4 mm for an Area Scan job.

EX3DV4 - SN:7655

June 03, 2025

### Parameters of Probe: EX3DV4 - SN:7655

#### Calibration Parameter Determined in HSL

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 150                  | 52.3                               | 0.76                            | 11.97   | 12.76   | 12.99   | 0.00               | 1.25                    | ±13.3%                   |
| 450                  | 43.5                               | 0.87                            | 11.03   | 11.03   | 11.03   | 0.16               | 1.30                    | ±13.3%                   |
| 750                  | 41.9                               | 0.89                            | 9.40    | 10.04   | 10.19   | 0.39               | 1.27                    | ±11.0%                   |
| 835                  | 41.5                               | 0.90                            | 9.13    | 9.75    | 9.90    | 0.39               | 1.27                    | ±11.0%                   |
| 900                  | 41.5                               | 0.97                            | 8.99    | 9.60    | 9.74    | 0.39               | 1.27                    | ±11.0%                   |
| 1450                 | 40.5                               | 1.20                            | 7.79    | 8.32    | 8.44    | 0.39               | 1.27                    | ±11.0%                   |
| 1750                 | 40.1                               | 1.37                            | 7.67    | 8.20    | 8.32    | 0.38               | 1.27                    | ±11.0%                   |
| 1900                 | 40.0                               | 1.40                            | 7.46    | 7.97    | 8.09    | 0.38               | 1.27                    | ±11.0%                   |
| 2300                 | 39.5                               | 1.67                            | 7.02    | 7.49    | 7.60    | 0.38               | 1.27                    | ±11.0%                   |
| 2450                 | 39.2                               | 1.80                            | 6.85    | 7.31    | 7.42    | 0.38               | 1.27                    | ±11.0%                   |
| 2600                 | 39.0                               | 1.96                            | 6.86    | 7.32    | 7.43    | 0.38               | 1.27                    | ±11.0%                   |
| 4400                 | 36.9                               | 3.84                            | 6.08    | 6.49    | 6.59    | 0.37               | 1.27                    | ±13.1%                   |
| 4600                 | 36.7                               | 4.04                            | 6.00    | 6.40    | 6.50    | 0.37               | 1.27                    | ±13.1%                   |
| 4800                 | 36.4                               | 4.25                            | 6.04    | 6.45    | 6.55    | 0.37               | 1.27                    | ±13.1%                   |
| 4950                 | 36.3                               | 4.40                            | 5.89    | 6.29    | 6.38    | 0.35               | 1.27                    | ±13.1%                   |

<sup>C</sup> Frequency validity above 300 MHz at +100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to +50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 160 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–9 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to +110 MHz.


<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon'$  and  $\sigma$  by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10% if SAR correction is applied.

<sup>G</sup> Alpha/Depth are determined during calibration. SPFAC warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1:2020/1528:2020.

EX3DV4 - SN:7655

June 03, 2025




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

EX3DV4 - SN:7655


June 03, 2025

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



EX3DV4 - SN:7655

June 03, 2025




Uncertainty of Linearity Assessment: 10.6% (k=2)


EX3DV4 - SN-7655

June 03, 2025

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid



EX3DV4 - SN:7655

June 03, 2025

## Appendix: Modulation Calibration Parameters

| UID   | Rev | Communication System Name                          | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|----------------------------------------------------|-----------|----------|------------------------|
| 0     |     | CW                                                 | CW        | 0.00     | ±4.7                   |
| 10010 | CAB | SAR Validation (Square, 100 ms, 10 ms)             | Test      | 10.00    | ±9.8                   |
| 10011 | CAC | UMTS-FDD (WCDMA)                                   | WCDMA     | 2.91     | ±9.8                   |
| 10012 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)           | WLAN      | 1.87     | ±9.8                   |
| 10013 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)      | WLAN      | 9.48     | ±9.8                   |
| 10021 | DAC | GSM-FDD (TDMA, GMSK)                               | GSM       | 9.39     | ±9.8                   |
| 10023 | DAC | GPRS-FDD (TDMA, GMSK, TN 0)                        | GSM       | 9.57     | ±9.8                   |
| 10024 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-1)                      | GSM       | 8.56     | ±9.8                   |
| 10025 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0)                        | GSM       | 12.62    | ±9.8                   |
| 10026 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1)                      | GSM       | 9.55     | ±9.8                   |
| 10027 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-2)                      | GSM       | 4.80     | ±9.8                   |
| 10028 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)                  | GSM       | 3.55     | ±9.8                   |
| 10029 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1-2)                    | GSM       | 7.78     | ±9.8                   |
| 10030 | CAA | IEEE 802.15.1 Bluetooth (GFSK, DH1)                | Bluetooth | 5.30     | ±9.8                   |
| 10031 | CAA | IEEE 802.15.1 Bluetooth (GFSK, DH3)                | Bluetooth | 1.87     | ±9.8                   |
| 10032 | CAA | IEEE 802.15.1 Bluetooth (GFSK, DH5)                | Bluetooth | 1.16     | ±9.8                   |
| 10033 | CAA | IEEE 802.15.1 Bluetooth (PI4-DQPSK, DH1)           | Bluetooth | 7.74     | ±9.8                   |
| 10034 | CAA | IEEE 802.15.1 Bluetooth (PI4-DQPSK, DH3)           | Bluetooth | 4.53     | ±9.8                   |
| 10035 | CAA | IEEE 802.15.1 Bluetooth (PI4-DQPSK, DH5)           | Bluetooth | 3.83     | ±9.8                   |
| 10036 | CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH1)              | Bluetooth | 8.01     | ±9.8                   |
| 10037 | CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH3)              | Bluetooth | 4.77     | ±9.8                   |
| 10038 | CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH5)              | Bluetooth | 4.10     | ±9.8                   |
| 10039 | CAB | CDMA2000 (1xRTT, RC1)                              | CDMA2000  | 4.57     | ±9.8                   |
| 10042 | CAB | IS-54 / IS-136 FDD (TDMA/FDD, PI4-DQPSK, Fullrate) | AMPS      | 7.78     | ±9.8                   |
| 10044 | CAA | IS-61/EIA/TIA-553 FDD (FDMA, FM)                   | AMPS      | 0.00     | ±9.8                   |
| 10048 | CAA | DECT (TDD, TDMA/FDD, GFSK, Full Slot, 24)          | DECT      | 18.80    | ±9.8                   |
| 10049 | CAA | DECT (TDD, TDMA/FDD, GFSK, Double Slot, 12)        | DECT      | 10.79    | ±9.8                   |
| 10056 | CAA | UMTS-TDD (TD-SCDMA, 1.28 Mbps)                     | TD-SCDMA  | 11.01    | ±9.8                   |
| 10058 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)                  | GSM       | 6.52     | ±9.8                   |
| 10059 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)           | WLAN      | 2.12     | ±9.8                   |
| 10060 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)         | WLAN      | 2.83     | ±9.8                   |
| 10061 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)          | WLAN      | 3.60     | ±9.8                   |
| 10062 | CAC | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)           | WLAN      | 8.69     | ±9.8                   |
| 10063 | CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)           | WLAN      | 8.63     | ±9.8                   |
| 10064 | CAC | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)          | WLAN      | 9.08     | ±9.8                   |
| 10065 | CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)          | WLAN      | 9.00     | ±9.8                   |
| 10066 | CAC | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)          | WLAN      | 9.39     | ±9.8                   |
| 10067 | CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)          | WLAN      | 10.12    | ±9.8                   |
| 10068 | CAC | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)          | WLAN      | 10.24    | ±9.8                   |
| 10069 | CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)          | WLAN      | 10.56    | ±9.8                   |
| 10071 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)      | WLAN      | 9.99     | ±9.8                   |
| 10072 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)     | WLAN      | 9.82     | ±9.8                   |
| 10073 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)     | WLAN      | 9.94     | ±9.8                   |
| 10074 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)     | WLAN      | 10.30    | ±9.8                   |
| 10075 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)     | WLAN      | 10.77    | ±9.8                   |
| 10076 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)     | WLAN      | 10.94    | ±9.8                   |
| 10077 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)     | WLAN      | 11.30    | ±9.8                   |
| 10081 | CAB | CDMA2000 (1xRTT, RC3)                              | CDMA2000  | 3.97     | ±9.8                   |
| 10082 | CAB | IS-54 / IS-136 FDD (TDMA/FDD, PI4-DQPSK, Fullrate) | AMPS      | 4.77     | ±9.8                   |
| 10090 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-4)                      | GSM       | 8.56     | ±9.8                   |
| 10097 | CAC | UMTS-FDD (HSDPA)                                   | WCDMA     | 3.38     | ±9.8                   |
| 10098 | CAC | UMTS-FDD (HSUPA, Subslot 2)                        | WCDMA     | 3.96     | ±9.8                   |
| 10099 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-4)                      | GSM       | 9.55     | ±9.8                   |
| 10100 | CAF | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)           | LTE-FDD   | 5.67     | ±9.8                   |
| 10101 | CAF | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)         | LTE-FDD   | 6.42     | ±9.8                   |
| 10102 | CAF | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)         | LTE-FDD   | 6.80     | ±9.8                   |
| 10103 | CAH | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)           | LTE-TDD   | 9.29     | ±9.8                   |
| 10104 | CAH | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)         | LTE-TDD   | 9.87     | ±9.8                   |
| 10105 | CAH | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)         | LTE-TDD   | 10.01    | ±9.8                   |
| 10106 | CAH | LTE-FDD (SC-FDMA, 100% RB, 16 MHz, QPSK)           | LTE-FDD   | 5.80     | ±9.8                   |
| 10109 | CAH | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)         | LTE-FDD   | 6.43     | ±9.8                   |
| 10110 | CAH | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)            | LTE-FDD   | 5.75     | ±9.8                   |
| 10111 | CAH | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)          | LTE-FDD   | 6.44     | ±9.8                   |

Certificate No: EX-7655\_Jun25

Page 10 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                      | Group   | PAR (dB) | Unc <sup>E</sup> $k = 2$ |
|-------|-----|------------------------------------------------|---------|----------|--------------------------|
| 10112 | CAH | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)     | LTE-FDD | 6.59     | +9.5                     |
| 10113 | CAH | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)      | LTE-FDD | 6.62     | +9.5                     |
| 10114 | CAE | IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)  | WLAN    | 8.10     | +9.5                     |
| 10115 | CAE | IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)  | WLAN    | 8.48     | +9.5                     |
| 10116 | CAE | IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM) | WLAN    | 8.15     | +9.5                     |
| 10117 | CAE | IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)       | WLAN    | 8.07     | +9.5                     |
| 10118 | CAE | IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)       | WLAN    | 8.59     | +9.5                     |
| 10119 | CAE | IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)      | WLAN    | 8.13     | +9.5                     |
| 10143 | CAF | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)     | LTE-FDD | 6.48     | +9.5                     |
| 10141 | CAF | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)     | LTE-FDD | 6.53     | +9.5                     |
| 10142 | CAF | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)        | LTE-FDD | 5.73     | +9.5                     |
| 10143 | CAF | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)      | LTE-FDD | 6.35     | +9.5                     |
| 10144 | CAF | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)      | LTE-FDD | 6.65     | +9.5                     |
| 10145 | CAG | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)      | LTE-FDD | 5.76     | +9.5                     |
| 10146 | CAG | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)    | LTE-FDD | 6.41     | +9.5                     |
| 10147 | CAG | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)    | LTE-FDD | 6.72     | +9.5                     |
| 10149 | CAF | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)      | LTE-FDD | 6.42     | +9.5                     |
| 10150 | CAF | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)      | LTE-FDD | 6.60     | +9.5                     |
| 10151 | CAH | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)        | LTE-TDD | 6.28     | +9.5                     |
| 10152 | CAH | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)      | LTE-TDD | 6.92     | +9.5                     |
| 10153 | CAH | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)      | LTE-TDD | 7.05     | +9.5                     |
| 10154 | CAH | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)        | LTE-FDD | 5.75     | +9.5                     |
| 10155 | CAH | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)      | LTE-FDD | 6.43     | +9.5                     |
| 10156 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)         | LTE-FDD | 5.79     | +9.5                     |
| 10157 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)       | LTE-FDD | 6.43     | +9.5                     |
| 10158 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)       | LTE-FDD | 6.62     | +9.5                     |
| 10159 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)       | LTE-FDD | 6.56     | +9.5                     |
| 10160 | CAF | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)         | LTE-FDD | 6.32     | +9.5                     |
| 10161 | CAF | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)      | LTE-FDD | 6.43     | +9.5                     |
| 10162 | CAF | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)      | LTE-FDD | 6.59     | +9.5                     |
| 10166 | CAG | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)       | LTE-FDD | 5.46     | +9.5                     |
| 10167 | CAG | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)     | LTE-FDD | 6.21     | +9.5                     |
| 10168 | CAG | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)     | LTE-FDD | 6.78     | +9.5                     |
| 10169 | CAF | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)          | LTE-FDD | 5.72     | +9.5                     |
| 10170 | CAF | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)        | LTE-FDD | 6.52     | +9.5                     |
| 10171 | AAF | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)        | LTE-FDD | 6.49     | +9.5                     |
| 10172 | CAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)          | LTE-TDD | 6.21     | +9.5                     |
| 10173 | CAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)        | LTE-TDD | 6.48     | +9.5                     |
| 10174 | CAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)        | LTE-TDD | 7.05     | +9.5                     |
| 10175 | CAH | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)          | LTE-FDD | 5.72     | +9.5                     |
| 10176 | CAH | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)        | LTE-FDD | 6.52     | +9.5                     |
| 10177 | CAJ | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)           | LTE-FDD | 5.78     | +9.5                     |
| 10178 | CAH | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)         | LTE-FDD | 6.52     | +9.5                     |
| 10179 | CAH | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)        | LTE-FDD | 6.50     | +9.5                     |
| 10180 | CAH | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)         | LTE-FDD | 6.50     | +9.5                     |
| 10181 | CAF | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)          | LTE-FDD | 5.72     | +9.5                     |
| 10182 | CAF | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)        | LTE-FDD | 6.52     | +9.5                     |
| 10183 | AAE | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)        | LTE-FDD | 6.50     | +9.5                     |
| 10184 | CAH | LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)           | LTE-FDD | 5.73     | +9.5                     |
| 10185 | CAF | LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)         | LTE-FDD | 6.51     | +9.5                     |
| 10186 | AAF | LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)         | LTE-FDD | 6.50     | +9.5                     |
| 10187 | CAG | LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)         | LTE-FDD | 5.73     | +9.5                     |
| 10188 | CAG | LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)       | LTE-FDD | 6.52     | +9.5                     |
| 10189 | AVG | LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)       | LTE-FDD | 6.50     | +9.5                     |
| 10193 | CAE | IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)   | WLAN    | 8.09     | +9.5                     |
| 10194 | CAE | IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)  | WLAN    | 8.12     | +9.5                     |
| 10195 | CAF | IEEE 802.11n (HT Greenfield, 85 Mbps, 64-QAM)  | WLAN    | 8.21     | +9.5                     |
| 10196 | CAE | IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)        | WLAN    | 8.10     | +9.5                     |
| 10197 | CAE | IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)       | WLAN    | 8.13     | +9.5                     |
| 10198 | CAF | IEEE 802.11n (HT Mixed, 85 Mbps, 64-QAM)       | WLAN    | 8.27     | +9.5                     |
| 10219 | CAE | IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)        | WLAN    | 8.03     | +9.5                     |
| 10220 | CAF | IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)     | WLAN    | 8.13     | +9.5                     |
| 10221 | CAE | IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)     | WLAN    | 8.27     | +9.5                     |
| 10222 | CAE | IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)         | WLAN    | 8.06     | +9.5                     |
| 10223 | CAE | IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)       | WLAN    | 8.48     | +9.5                     |
| 10224 | CAF | IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)      | WLAN    | 8.09     | +9.5                     |

Certificate No: EX-7655\_Jun25

Page 11 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                                            | Group    | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|----------------------------------------------------------------------|----------|----------|------------------------|
| 10225 | CAC | UMTS-FDD (HSPA+)                                                     | WCDMA    | 5.37     | ±9.6                   |
| 10226 | CAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)                             | LTE-TDD  | 9.46     | +9.6                   |
| 10227 | CAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)                             | LTE-TDD  | 10.26    | ±9.6                   |
| 10228 | CAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)                               | LTE-TDD  | 9.22     | +9.6                   |
| 10229 | CAE | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)                               | LTE-TDD  | 9.46     | ±9.6                   |
| 10230 | CAE | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)                               | LTE-TDD  | 10.25    | +9.6                   |
| 10231 | CAE | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)                                 | LTE-TDD  | 9.19     | ±9.6                   |
| 10232 | CAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)                               | LTE-TDD  | 9.46     | +9.6                   |
| 10233 | CAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)                               | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)                                 | LTE-TDD  | 9.21     | +9.6                   |
| 10235 | CAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)                              | LTE-TDD  | 9.46     | ±9.6                   |
| 10236 | CAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)                              | LTE-TDD  | 10.25    | +9.6                   |
| 10237 | CAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)                                | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)                              | LTE-TDD  | 9.46     | ±9.6                   |
| 10239 | CAG | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)                              | LTE-TDD  | 10.25    | +9.6                   |
| 10240 | CAG | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)                                | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)                           | LTE-TDD  | 9.62     | +9.6                   |
| 10242 | CAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)                           | LTE-TDD  | 9.86     | ±9.6                   |
| 10243 | CAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)                             | LTE-TDD  | 9.46     | ±9.6                   |
| 10244 | CAE | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)                             | LTE-TDD  | 10.06    | ±9.6                   |
| 10245 | CAH | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)                             | LTE-TDD  | 10.06    | ±9.6                   |
| 10246 | CAE | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)                               | LTE-TDD  | 9.80     | ±9.6                   |
| 10247 | CAH | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)                             | LTE-TDD  | 9.91     | ±9.6                   |
| 10248 | CAH | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)                             | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CAH | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)                               | LTE-TDD  | 9.29     | +9.6                   |
| 10250 | CAH | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)                            | LTE-TDD  | 9.81     | ±9.6                   |
| 10251 | CAH | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)                            | LTE-TDD  | 10.17    | +9.6                   |
| 10252 | CAH | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)                              | LTE-TDD  | 9.24     | ±9.6                   |
| 10253 | CAC | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)                            | LTE-TDD  | 9.90     | +9.6                   |
| 10254 | CAG | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)                            | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAC | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)                              | LTE-TDD  | 9.20     | +9.6                   |
| 10256 | CAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)                          | LTE-TDD  | 9.98     | ±9.6                   |
| 10257 | CAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)                          | LTE-TDD  | 10.08    | +9.6                   |
| 10258 | CAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)                            | LTE-TDD  | 9.54     | ±9.6                   |
| 10259 | CAE | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)                            | LTE-TDD  | 9.98     | +9.6                   |
| 10260 | CAE | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)                            | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)                              | LTE-TDD  | 9.24     | +9.6                   |
| 10262 | CAH | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)                            | LTE-TDD  | 9.83     | ±9.6                   |
| 10263 | CAH | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)                            | LTE-TDD  | 10.16    | ±9.6                   |
| 10264 | CAH | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)                              | LTE-TDD  | 9.23     | ±9.6                   |
| 10265 | CAH | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)                           | LTE-TDD  | 9.92     | +9.6                   |
| 10266 | CAH | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)                           | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CAH | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)                             | LTE-TDD  | 9.50     | ±9.6                   |
| 10268 | CAG | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)                           | LTE-TDD  | 10.06    | ±9.6                   |
| 10269 | CAG | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)                           | LTE-TDD  | 10.13    | +9.6                   |
| 10270 | CAG | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                             | LTE-TDD  | 9.58     | ±9.6                   |
| 10274 | CAC | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel9.4)                             | WCDMA    | 4.87     | ±9.6                   |
| 10275 | CAC | UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel9.4)                             | WCDMA    | 8.98     | +9.6                   |
| 10277 | CAA | PHS (QPSK)                                                           | PHS      | 11.81    | ±9.6                   |
| 10278 | CAA | PHS (QPSK, BW 604 MHz, Roll-off 0.5)                                 | PHS      | 11.81    | +9.6                   |
| 10279 | CAA | PHS (QPSK, BW 884 MHz, Roll-off 0.38)                                | PHS      | 12.18    | ±9.6                   |
| 10290 | AAB | CDMA2000, RC1, SC55, Full Rate                                       | CDMA2000 | 9.91     | +9.6                   |
| 10291 | AAB | CDMA2000, RC3, SC55, Full Rate                                       | CDMA2000 | 9.46     | ±9.6                   |
| 10292 | AAB | CDMA2000, RC3, SC32, Full Rate                                       | CDMA2000 | 9.59     | +9.6                   |
| 10293 | AAB | CDMA2000, RC3, SC3, Full Rate                                        | CDMA2000 | 9.50     | ±9.6                   |
| 10295 | AAB | CDMA2000, RC1, SC3, 1/8th Rate 25 fr                                 | CDMA2000 | 12.49    | +9.6                   |
| 10297 | AAE | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                              | LTE-FDD  | 5.81     | ±9.6                   |
| 10298 | AAE | LTE-FDD (SC-FDMA, 50% RB, 8 MHz, QPSK)                               | LTE-FDD  | 5.72     | ±9.6                   |
| 10299 | AAE | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)                             | LTE-FDD  | 6.39     | +9.6                   |
| 10300 | AAE | LTE-FDD (SC-FDMA, 50% RB, 8 MHz, 64-QAM)                             | LTE-FDD  | 6.60     | ±9.6                   |
| 10301 | AAA | IEEE 802.16e WiMAX (20-18, 5 ms, 10 MHz, QPSK, PUSC)                 | WiMAX    | 12.03    | +9.6                   |
| 10302 | AAA | IEEE 802.16e WiMAX (20-18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols) | WiMAX    | 12.57    | ±9.6                   |
| 10303 | AAA | IEEE 802.16e WiMAX (31-15, 5 ms, 10 MHz, 64QAM, PUSC)                | WiMAX    | 12.52    | +9.6                   |
| 10304 | AAA | IEEE 802.16e WiMAX (20-18, 5 ms, 10 MHz, 64QAM, PUSC)                | WiMAX    | 11.88    | ±9.6                   |
| 10305 | AAA | IEEE 802.16e WiMAX (31-15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)   | WiMAX    | 15.24    | +9.6                   |
| 10306 | AAA | IEEE 802.16e WiMAX (20-18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)   | WiMAX    | 14.67    | ±9.6                   |

Certificate No: EX-7655\_Jun25

Page 12 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                                                       | Group    | PAR (dB) | Unc <sup>E</sup> $k=2$ |
|-------|-----|---------------------------------------------------------------------------------|----------|----------|------------------------|
| 10307 | AAA | IEEE 802.16e WIMAX (20.16, 10 ms, 10 MHz, QPSK, PUSC, 16 symbols)               | WIMAX    | 14.49    | ±9.6                   |
| 10308 | AAA | IEEE 802.16e WIMAX (20.16, 10 ms, 10 MHz, 16QAM, PUSC)                          | WIMAX    | 14.46    | ±9.6                   |
| 10309 | AAA | IEEE 802.16e WIMAX (20.16, 10 ms, 10 MHz, 16QAM, AMC 2x3, 16 symbols)           | WIMAX    | 14.58    | ±9.6                   |
| 10310 | AAA | IEEE 802.16e WIMAX (20.16, 10 ms, 10 MHz, QPSK, AMC 2x3, 16 symbols)            | WIMAX    | 14.57    | ±9.6                   |
| 10311 | AAE | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                                        | LTE-FDD  | 6.06     | ±9.6                   |
| 10313 | AAA | IDEN 1:3                                                                        | IDEN     | 10.51    | ±9.6                   |
| 10314 | AAA | IDEN 1:6                                                                        | IDEN     | 13.48    | ±9.6                   |
| 10315 | AAG | IEEE 802.11a WiFi 2.4 GHz (DSSS, 1 Mbps, 86pc duty cycle)                       | WLAN     | 1.71     | ±9.6                   |
| 10315 | AAB | IEEE 802.11g WiFi 2.4 GHz (ERP OFDM, 6 Mbps, 90pc duty cycle)                   | WLAN     | 8.38     | ±9.6                   |
| 10317 | AAC | IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 98pc duty cycle)                         | WLAN     | 9.38     | ±9.6                   |
| 10352 | AAA | Pulse Waveform (200Hz, 10%)                                                     | Generic  | 10.30    | ±9.6                   |
| 10353 | AAA | Pulse Waveform (200Hz, 20%)                                                     | Generic  | 9.89     | ±9.6                   |
| 10354 | AAA | Pulse Waveform (200Hz, 40%)                                                     | Generic  | 9.88     | ±9.6                   |
| 10355 | AAA | Pulse Waveform (200Hz, 60%)                                                     | Generic  | 2.22     | ±9.6                   |
| 10358 | AAA | Pulse Waveform (200Hz, 80%)                                                     | Generic  | 0.87     | ±9.6                   |
| 10387 | AAA | QPSK Waveform, 1 MHz                                                            | Generic  | 5.10     | ±9.6                   |
| 10388 | AAA | QPSK Waveform, 10 MHz                                                           | Generic  | 5.22     | ±9.6                   |
| 10395 | AAA | 64-QAM Waveform, 100 kHz                                                        | Generic  | 6.27     | ±9.6                   |
| 10399 | AAA | 64-QAM Waveform, 40 MHz                                                         | Generic  | 6.27     | ±9.6                   |
| 10400 | AAF | IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)                            | WLAN     | 8.57     | ±9.6                   |
| 10401 | AAF | IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99pc duty cycle)                            | WLAN     | 8.60     | ±9.6                   |
| 10402 | AAF | IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)                            | WLAN     | 8.53     | ±9.6                   |
| 10403 | AAB | CDMA2000 (1xEV-DO, Rev. 0)                                                      | CDMA2000 | 3.78     | ±9.6                   |
| 10404 | AAB | CDMA2000 (1xEV-DO, Rev. A)                                                      | CDMA2000 | 3.77     | ±9.6                   |
| 10406 | AAB | CDMA2000, R03, S032, SCH0, Full Rate                                            | CDMA2000 | 6.22     | ±9.6                   |
| 10410 | AAH | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4) | LTE-TDD  | 7.82     | ±9.6                   |
| 10414 | AAA | WLAN CCK4, 64-QAM, 40 MHz                                                       | Generic  | 8.54     | ±9.6                   |
| 10415 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)                       | WLAN     | 1.54     | ±9.6                   |
| 10416 | AAA | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)                   | WLAN     | 8.23     | ±9.6                   |
| 10417 | AAI | IEEE 802.11a/n WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)                       | WLAN     | 8.23     | ±9.6                   |
| 10418 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)   | WLAN     | 8.14     | ±9.6                   |
| 10418 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)  | WLAN     | 8.18     | ±9.6                   |
| 10422 | AAO | IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)                                    | WLAN     | 9.32     | ±9.6                   |
| 10423 | AAO | IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)                                 | WLAN     | 9.47     | ±9.6                   |
| 10424 | AAO | IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)                                 | WLAN     | 9.40     | ±9.6                   |
| 10425 | AAO | IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)                                     | WLAN     | 9.41     | ±9.6                   |
| 10426 | AAO | IEEE 802.11n (HT Greenfield, 30 Mbps, 16-QAM)                                   | WLAN     | 9.46     | ±9.6                   |
| 10427 | AAO | IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)                                  | WLAN     | 9.41     | ±9.6                   |
| 10430 | AAE | LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)                                                | LTE-FDD  | 9.38     | ±9.6                   |
| 10431 | AAE | LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)                                               | LTE-FDD  | 9.36     | ±9.6                   |
| 10432 | AAO | LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)                                               | LTE-FDD  | 9.34     | ±9.6                   |
| 10433 | AAO | LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)                                               | LTE-FDD  | 9.34     | ±9.6                   |
| 10434 | AAB | W-CDMA (BS Test Model 1, 64 DPCH)                                               | WCDMA    | 8.60     | ±9.6                   |
| 10435 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10447 | AAE | LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)                                  | LTE-FDD  | 7.56     | ±9.6                   |
| 10448 | AAE | LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)                                 | LTE-FDD  | 7.53     | ±9.6                   |
| 10448 | AAO | LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)                                 | LTE-FDD  | 7.51     | ±9.6                   |
| 10450 | AAO | LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)                                 | LTE-FDD  | 7.49     | ±9.6                   |
| 10451 | AAB | W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)                                 | WCDMA    | 7.53     | ±9.6                   |
| 10453 | AAE | Validation (Square, 10 ms, 1 ms)                                                | Test     | 10.00    | ±9.6                   |
| 10456 | AAO | IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)                           | WLAN     | 8.53     | ±9.6                   |
| 10457 | AAB | UMTS-FDD (DC-HSDPA)                                                             | WCDMA    | 6.92     | ±9.6                   |
| 10458 | AAA | CDMA2000 (1xEV-DO, Rev. B, 2 carriers)                                          | CDMA2000 | 6.55     | ±9.6                   |
| 10459 | AAA | CDMA2000 (1xEV-DO, Rev. B, 3 carriers)                                          | CDMA2000 | 6.25     | ±9.6                   |
| 10460 | AAB | UMTS-FDD (WCDMA, AMR)                                                           | WCDMA    | 2.38     | ±9.6                   |
| 10461 | AAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 7.82     | ±9.6                   |
| 10462 | AAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)               | LTE-TDD  | 8.30     | ±9.6                   |
| 10463 | AAC | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)               | LTE-TDD  | 8.56     | ±9.6                   |
| 10464 | AAO | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10465 | AAO | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10465 | AAO | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10467 | AAG | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10468 | AAG | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.32     | ±9.6                   |
| 10469 | AAG | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.56     | ±9.6                   |
| 10470 | AAG | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10471 | AAG | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                | LTE-TDD  | 8.32     | ±9.6                   |

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                                            | Group   | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|----------------------------------------------------------------------|---------|----------|------------------------|
| 10472 | AAG | LTE-TDD (SC-FDMA, 1 RB, 18 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 9.57     | ±9.6                   |
| 10473 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)       | LTE-TDD | 7.82     | ±9.6                   |
| 10474 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 9.32     | ±9.6                   |
| 10475 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10477 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 9.32     | ±9.6                   |
| 10478 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10479 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10480 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.18     | ±9.6                   |
| 10481 | AAC | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.45     | ±9.6                   |
| 10482 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)      | LTE-TDD | 7.71     | ±9.6                   |
| 10483 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.39     | ±9.6                   |
| 10484 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.47     | ±9.6                   |
| 10485 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)      | LTE-TDD | 7.59     | ±9.6                   |
| 10486 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.38     | ±9.6                   |
| 10487 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.60     | ±9.6                   |
| 10488 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.70     | ±9.6                   |
| 10489 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.31     | ±9.6                   |
| 10490 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10491 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.74     | ±9.6                   |
| 10492 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.41     | ±9.6                   |
| 10493 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.55     | ±9.6                   |
| 10494 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.74     | ±9.6                   |
| 10495 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.37     | ±9.6                   |
| 10496 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10497 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 7.57     | ±9.6                   |
| 10498 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | LTE-TDD | 8.49     | ±9.6                   |
| 10499 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | LTE-TDD | 8.58     | ±9.6                   |
| 10500 | AAC | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.97     | ±9.6                   |
| 10501 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.44     | ±9.6                   |
| 10502 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.52     | ±9.6                   |
| 10503 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.72     | ±9.6                   |
| 10504 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.31     | ±9.6                   |
| 10505 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10506 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10507 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.36     | ±9.6                   |
| 10508 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.55     | ±9.6                   |
| 10509 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.89     | ±9.6                   |
| 10510 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.49     | ±9.6                   |
| 10511 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.51     | ±9.6                   |
| 10512 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10513 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.42     | ±9.6                   |
| 10514 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.45     | ±9.6                   |
| 10515 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)            | WLAN    | 1.56     | ±9.6                   |
| 10516 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)          | WLAN    | 1.57     | ±9.6                   |
| 10517 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)           | WLAN    | 1.56     | ±9.6                   |
| 10518 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)            | WLAN    | 8.28     | ±9.6                   |
| 10519 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)           | WLAN    | 8.39     | ±9.6                   |
| 10520 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)           | WLAN    | 8.12     | ±9.6                   |
| 10521 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)           | WLAN    | 7.97     | ±9.6                   |
| 10522 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)           | WLAN    | 8.45     | ±9.6                   |
| 10523 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)           | WLAN    | 8.08     | ±9.6                   |
| 10524 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)           | WLAN    | 8.27     | ±9.6                   |
| 10525 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)                   | WLAN    | 8.36     | ±9.6                   |
| 10526 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)                   | WLAN    | 8.42     | ±9.6                   |
| 10527 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)                   | WLAN    | 8.21     | ±9.6                   |
| 10528 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)                   | WLAN    | 8.56     | ±9.6                   |
| 10529 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)                   | WLAN    | 8.56     | ±9.6                   |
| 10530 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS5, 99pc duty cycle)                   | WLAN    | 8.43     | ±9.6                   |
| 10531 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)                   | WLAN    | 8.29     | ±9.6                   |
| 10532 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)                   | WLAN    | 8.29     | ±9.6                   |
| 10533 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)                   | WLAN    | 8.53     | ±9.6                   |
| 10534 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)                   | WLAN    | 8.45     | ±9.6                   |
| 10535 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)                   | WLAN    | 8.45     | ±9.6                   |
| 10536 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)                   | WLAN    | 8.52     | ±9.6                   |
| 10537 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)                   | WLAN    | 8.44     | ±9.6                   |
| 10538 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)                   | WLAN    | 8.54     | ±9.6                   |
| 10540 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS5, 99pc duty cycle)                   | WLAN    | 8.39     | ±9.6                   |

FX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                                       | Group | PAR (dB) | Unc <sup>E</sup> k - 2 |
|-------|-----|-----------------------------------------------------------------|-------|----------|------------------------|
| 10541 | AAD | IEEE 802.11ac W/F (40 MHz, MCS7, 86pc duty cycle)               | WLAN  | 8.46     | ±9.6                   |
| 10542 | AAD | IEEE 802.11ac W/F (40 MHz, MCS8, 86pc duty cycle)               | WLAN  | 8.65     | ±9.6                   |
| 10543 | AAD | IEEE 802.11ac W/F (40 MHz, MCS9, 86pc duty cycle)               | WLAN  | 8.65     | ±9.6                   |
| 10544 | AAD | IEEE 802.11ac W/F (80 MHz, MCS0, 86pc duty cycle)               | WLAN  | 8.47     | ±9.6                   |
| 10545 | AAD | IEEE 802.11ac W/F (80 MHz, MCS1, 86pc duty cycle)               | WLAN  | 8.55     | ±9.6                   |
| 10546 | AAD | IEEE 802.11ac W/F (80 MHz, MCS2, 86pc duty cycle)               | WLAN  | 8.35     | ±9.6                   |
| 10547 | AAD | IEEE 802.11ac W/F (80 MHz, MCS3, 86pc duty cycle)               | WLAN  | 8.49     | ±9.6                   |
| 10548 | AAD | IEEE 802.11ac W/F (80 MHz, MCS4, 86pc duty cycle)               | WLAN  | 8.37     | ±9.6                   |
| 10550 | AAD | IEEE 802.11ac W/F (80 MHz, MCS5, 86pc duty cycle)               | WLAN  | 8.39     | ±9.6                   |
| 10551 | AAD | IEEE 802.11ac W/F (80 MHz, MCS7, 86pc duty cycle)               | WLAN  | 8.50     | ±9.6                   |
| 10552 | AAD | IEEE 802.11ac W/F (80 MHz, MCS9, 86pc duty cycle)               | WLAN  | 8.42     | ±9.6                   |
| 10553 | AAD | IEEE 802.11ac W/F (80 MHz, MCS0, 86pc duty cycle)               | WLAN  | 8.45     | ±9.6                   |
| 10554 | AAE | IEEE 802.11ac W/F (160 MHz, MCS0, 86pc duty cycle)              | WLAN  | 8.49     | ±9.6                   |
| 10555 | AAE | IEEE 802.11ac W/F (160 MHz, MCS1, 86pc duty cycle)              | WLAN  | 8.47     | ±9.6                   |
| 10556 | AAE | IEEE 802.11ac W/F (160 MHz, MCS2, 86pc duty cycle)              | WLAN  | 8.50     | ±9.6                   |
| 10557 | AAE | IEEE 802.11ac W/F (160 MHz, MCS3, 86pc duty cycle)              | WLAN  | 8.52     | ±9.6                   |
| 10558 | AAE | IEEE 802.11ac W/F (160 MHz, MCS4, 86pc duty cycle)              | WLAN  | 8.61     | ±9.6                   |
| 10560 | AAE | IEEE 802.11ac W/F (160 MHz, MCS5, 86pc duty cycle)              | WLAN  | 8.73     | ±9.6                   |
| 10561 | AAE | IEEE 802.11ac W/F (160 MHz, MCS7, 86pc duty cycle)              | WLAN  | 8.56     | ±9.6                   |
| 10562 | AAE | IEEE 802.11ac W/F (160 MHz, MCS9, 86pc duty cycle)              | WLAN  | 8.58     | ±9.6                   |
| 10563 | AAE | IEEE 802.11ac W/F (160 MHz, MCS0, 86pc duty cycle)              | WLAN  | 8.77     | ±9.6                   |
| 10564 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 9 Mbps, 86pc duty cycle)  | WLAN  | 8.25     | ±9.6                   |
| 10565 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 12 Mbps, 86pc duty cycle) | WLAN  | 8.45     | ±9.6                   |
| 10566 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 18 Mbps, 86pc duty cycle) | WLAN  | 8.13     | ±9.6                   |
| 10567 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 24 Mbps, 86pc duty cycle) | WLAN  | 8.30     | ±9.6                   |
| 10568 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 36 Mbps, 86pc duty cycle) | WLAN  | 8.37     | ±9.6                   |
| 10569 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 48 Mbps, 86pc duty cycle) | WLAN  | 8.10     | ±9.6                   |
| 10570 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 54 Mbps, 86pc duty cycle) | WLAN  | 8.30     | ±9.6                   |
| 10571 | AAA | IEEE 802.11b W/FI 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)       | WLAN  | 1.95     | ±9.6                   |
| 10572 | AAA | IEEE 802.11b W/FI 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)       | WLAN  | 1.98     | ±9.6                   |
| 10573 | AAA | IEEE 802.11b W/FI 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)     | WLAN  | 1.98     | ±9.6                   |
| 10574 | AAA | IEEE 802.11b W/FI 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)      | WLAN  | 1.98     | ±9.6                   |
| 10575 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 6 Mbps, 80pc duty cycle)  | WLAN  | 8.59     | ±9.6                   |
| 10576 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 9 Mbps, 80pc duty cycle)  | WLAN  | 9.30     | ±9.6                   |
| 10577 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 12 Mbps, 80pc duty cycle) | WLAN  | 8.70     | ±9.6                   |
| 10578 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 18 Mbps, 80pc duty cycle) | WLAN  | 8.49     | ±9.6                   |
| 10579 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 24 Mbps, 80pc duty cycle) | WLAN  | 8.36     | ±9.6                   |
| 10580 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 36 Mbps, 80pc duty cycle) | WLAN  | 8.76     | ±9.6                   |
| 10581 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 48 Mbps, 80pc duty cycle) | WLAN  | 8.35     | ±9.6                   |
| 10582 | AAA | IEEE 802.11g W/FI 2.4 GHz (DSSS-OFDM, 54 Mbps, 80pc duty cycle) | WLAN  | 8.57     | ±9.6                   |
| 10583 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 8 Mbps, 90pc duty cycle)        | WLAN  | 8.59     | ±9.6                   |
| 10584 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)        | WLAN  | 8.50     | ±9.6                   |
| 10585 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)       | WLAN  | 8.70     | ±9.6                   |
| 10586 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)       | WLAN  | 8.49     | ±9.6                   |
| 10587 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)       | WLAN  | 8.36     | ±9.6                   |
| 10588 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)       | WLAN  | 8.76     | ±9.6                   |
| 10589 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)       | WLAN  | 8.35     | ±9.6                   |
| 10590 | AAD | IEEE 802.11ah W/FI 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)       | WLAN  | 8.87     | ±9.6                   |
| 10591 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)          | WLAN  | 8.83     | ±9.6                   |
| 10592 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)          | WLAN  | 8.78     | ±9.6                   |
| 10593 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 90pc duty cycle)          | WLAN  | 8.94     | ±9.6                   |
| 10594 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)          | WLAN  | 8.74     | ±9.6                   |
| 10595 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)          | WLAN  | 8.74     | ±9.6                   |
| 10596 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)          | WLAN  | 8.71     | ±9.6                   |
| 10597 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)          | WLAN  | 8.72     | ±9.6                   |
| 10598 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)          | WLAN  | 8.50     | ±9.6                   |
| 10599 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)          | WLAN  | 8.79     | ±9.6                   |
| 10600 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 90pc duty cycle)          | WLAN  | 8.88     | ±9.6                   |
| 10601 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 90pc duty cycle)          | WLAN  | 8.92     | ±9.6                   |
| 10602 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)          | WLAN  | 8.94     | ±9.6                   |
| 10603 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)          | WLAN  | 9.09     | ±9.6                   |
| 10604 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)          | WLAN  | 9.78     | ±9.6                   |
| 10605 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)          | WLAN  | 8.97     | ±9.6                   |
| 10606 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)          | WLAN  | 8.92     | ±9.6                   |
| 10607 | AAD | IEEE 802.11ac W/FI (20 MHz, MCS0, 86pc duty cycle)              | WLAN  | 8.64     | ±9.6                   |
| 10608 | AAD | IEEE 802.11ac W/FI (20 MHz, MCS1, 86pc duty cycle)              | WLAN  | 8.77     | ±9.6                   |

EX3DV4 - SN:7055

June 03, 2025

| UID   | Rev | Communication System Name                              | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------------------|-----------|----------|------------------------|
| 10609 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.57     | ±9.6                   |
| 10610 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.78     | ±9.6                   |
| 10611 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.70     | ±9.6                   |
| 10612 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.77     | ±9.6                   |
| 10613 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.84     | ±9.6                   |
| 10614 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.59     | ±9.6                   |
| 10615 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10616 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10617 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10618 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.56     | ±9.6                   |
| 10619 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.86     | ±9.6                   |
| 10620 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.87     | ±9.6                   |
| 10621 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.77     | ±9.6                   |
| 10622 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.68     | ±9.6                   |
| 10623 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10624 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.96     | ±9.6                   |
| 10625 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)     | WLAN      | 8.98     | ±9.6                   |
| 10626 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)     | WLAN      | 8.83     | ±9.6                   |
| 10627 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)     | WLAN      | 8.88     | ±9.6                   |
| 10628 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.71     | ±9.6                   |
| 10629 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.85     | ±9.6                   |
| 10630 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.72     | ±9.6                   |
| 10631 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10632 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.74     | ±9.6                   |
| 10633 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.83     | ±9.6                   |
| 10634 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.80     | ±9.6                   |
| 10635 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10636 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)    | WLAN      | 8.83     | ±9.6                   |
| 10637 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)    | WLAN      | 8.79     | ±9.6                   |
| 10638 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)    | WLAN      | 8.88     | ±9.6                   |
| 10639 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)    | WLAN      | 8.85     | ±9.6                   |
| 10640 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)    | WLAN      | 8.99     | ±9.6                   |
| 10641 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)    | WLAN      | 9.08     | ±9.6                   |
| 10642 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)    | WLAN      | 9.06     | ±9.6                   |
| 10643 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)    | WLAN      | 8.89     | ±9.6                   |
| 10644 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)    | WLAN      | 9.05     | ±9.6                   |
| 10645 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)    | WLAN      | 9.11     | ±9.6                   |
| 10646 | AAD | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)  | LTE-TDD   | 11.96    | ±9.6                   |
| 10647 | AAD | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7) | LTE-TDD   | 11.96    | ±9.6                   |
| 10648 | AAA | CDMA2000 (1x Advanced)                                 | CDMA2000  | 3.45     | ±9.6                   |
| 10652 | AAD | LTE-TDD (OFDMA, 8 MHz, E-TM 3.1, Clipping 44%)         | LTE-TDD   | 6.91     | ±9.6                   |
| 10653 | AAD | LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 7.42     | ±9.6                   |
| 10654 | AAD | LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 6.96     | ±9.6                   |
| 10655 | AAD | LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 7.21     | ±9.6                   |
| 10658 | AAB | Pulse Waveform (200Hz, 10%)                            | Test      | 10.30    | ±9.6                   |
| 10659 | AAB | Pulse Waveform (200Hz, 20%)                            | Test      | 8.99     | ±9.6                   |
| 10660 | AAB | Pulse Waveform (200Hz, 40%)                            | Test      | 3.08     | ±9.6                   |
| 10661 | AAB | Pulse Waveform (200Hz, 60%)                            | Test      | 2.22     | ±9.6                   |
| 10662 | AAB | Pulse Waveform (200Hz, 80%)                            | Test      | 0.37     | ±9.6                   |
| 10670 | AAA | Bluetooth Low Energy                                   | Bluetooth | 2.19     | ±9.6                   |
| 10671 | AAC | IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)          | WLAN      | 9.08     | ±9.6                   |
| 10672 | AAC | IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)          | WLAN      | 8.57     | ±9.6                   |
| 10673 | AAC | IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)          | WLAN      | 8.78     | ±9.6                   |
| 10674 | AAC | IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)          | WLAN      | 8.74     | ±9.6                   |
| 10675 | AAC | IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)          | WLAN      | 8.90     | ±9.6                   |
| 10676 | AAC | IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)          | WLAN      | 8.77     | ±9.6                   |
| 10677 | AAC | IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)          | WLAN      | 8.73     | ±9.6                   |
| 10678 | AAC | IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)          | WLAN      | 8.78     | ±9.6                   |
| 10679 | AAC | IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)          | WLAN      | 8.98     | ±9.6                   |
| 10680 | AAC | IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)          | WLAN      | 8.80     | ±9.6                   |
| 10681 | AAC | IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)         | WLAN      | 8.82     | ±9.6                   |
| 10682 | AAC | IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)         | WLAN      | 8.93     | ±9.6                   |
| 10683 | AAC | IEEE 802.11ax (20 MHz, MCS0, 95pc duty cycle)          | WLAN      | 8.42     | ±9.6                   |
| 10684 | AAC | IEEE 802.11ax (20 MHz, MCS1, 95pc duty cycle)          | WLAN      | 8.26     | ±9.6                   |
| 10685 | AAC | IEEE 802.11ax (20 MHz, MCS2, 95pc duty cycle)          | WLAN      | 8.33     | ±9.6                   |
| 10686 | AAC | IEEE 802.11ax (20 MHz, MCS3, 95pc duty cycle)          | WLAN      | 8.28     | ±9.6                   |

Certificate No: EX-7055\_Jun25

Page 16 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                      | Group | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|------------------------------------------------|-------|----------|------------------------|
| 10607 | AAC | IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.45     | ±9.6                   |
| 10608 | AAC | IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10609 | AAC | IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.58     | ±9.6                   |
| 10610 | AAC | IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10611 | AAC | IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.25     | ±9.6                   |
| 10612 | AAC | IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10613 | AAC | IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.25     | ±9.6                   |
| 10614 | AAC | IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.57     | ±9.6                   |
| 10615 | AAC | IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)  | WLAN  | 8.78     | ±9.6                   |
| 10616 | AAC | IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)  | WLAN  | 8.91     | ±9.6                   |
| 10617 | AAC | IEEE 802.11ax (40 MHz, MCS2, 90pc duty cycle)  | WLAN  | 8.61     | ±9.6                   |
| 10618 | AAC | IEEE 802.11ax (40 MHz, MCS3, 90pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10619 | AAC | IEEE 802.11ax (40 MHz, MCS4, 90pc duty cycle)  | WLAN  | 8.82     | ±9.6                   |
| 10700 | AAC | IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)  | WLAN  | 8.73     | ±9.6                   |
| 10701 | AAC | IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)  | WLAN  | 8.85     | ±9.6                   |
| 10702 | AAC | IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)  | WLAN  | 8.70     | ±9.6                   |
| 10703 | AAC | IEEE 802.11ax (40 MHz, MCS8, 90pc duty cycle)  | WLAN  | 8.82     | ±9.6                   |
| 10704 | AAC | IEEE 802.11ax (40 MHz, MCS9, 90pc duty cycle)  | WLAN  | 8.58     | ±9.6                   |
| 10705 | AAC | IEEE 802.11ax (40 MHz, MCS10, 90pc duty cycle) | WLAN  | 8.69     | ±9.6                   |
| 10706 | AAC | IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle) | WLAN  | 8.58     | ±9.6                   |
| 10707 | AAC | IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.32     | ±9.6                   |
| 10708 | AAC | IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.55     | ±9.6                   |
| 10709 | AAC | IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.33     | ±9.6                   |
| 10710 | AAC | IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.28     | ±9.6                   |
| 10711 | AAC | IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.38     | ±9.6                   |
| 10712 | AAC | IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.37     | ±9.6                   |
| 10713 | AAC | IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.33     | ±9.6                   |
| 10714 | AAC | IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)  | WLAN  | 9.28     | ±9.6                   |
| 10715 | AAC | IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.45     | ±9.6                   |
| 10716 | AAC | IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)  | WLAN  | 9.30     | ±9.6                   |
| 10717 | AAC | IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.48     | ±9.6                   |
| 10718 | AAC | IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle) | WLAN  | 9.24     | ±9.6                   |
| 10719 | AAC | IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)  | WLAN  | 8.81     | ±9.6                   |
| 10720 | AAC | IEEE 802.11ax (80 MHz, MCS1, 90pc duty cycle)  | WLAN  | 9.97     | ±9.6                   |
| 10721 | AAC | IEEE 802.11ax (80 MHz, MCS2, 90pc duty cycle)  | WLAN  | 8.76     | ±9.6                   |
| 10722 | AAC | IEEE 802.11ax (80 MHz, MCS3, 90pc duty cycle)  | WLAN  | 9.55     | ±9.6                   |
| 10723 | AAC | IEEE 802.11ax (80 MHz, MCS4, 90pc duty cycle)  | WLAN  | 8.70     | ±9.6                   |
| 10724 | AAC | IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)  | WLAN  | 9.90     | ±9.6                   |
| 10725 | AAC | IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)  | WLAN  | 8.74     | ±9.6                   |
| 10726 | AAC | IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)  | WLAN  | 8.72     | ±9.6                   |
| 10727 | AAC | IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)  | WLAN  | 8.66     | ±9.6                   |
| 10728 | AAC | IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)  | WLAN  | 9.66     | ±9.6                   |
| 10729 | AAC | IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle) | WLAN  | 8.84     | ±9.6                   |
| 10730 | AAC | IEEE 802.11ax (80 MHz, MCS11, 90pc duty cycle) | WLAN  | 8.87     | ±9.6                   |
| 10731 | AAC | IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)  | WLAN  | 9.42     | ±9.6                   |
| 10732 | AAC | IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)  | WLAN  | 9.46     | ±9.6                   |
| 10733 | AAC | IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)  | WLAN  | 9.40     | ±9.6                   |
| 10734 | AAC | IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.25     | ±9.6                   |
| 10735 | AAC | IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)  | WLAN  | 9.33     | ±9.6                   |
| 10736 | AAC | IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.27     | ±9.6                   |
| 10737 | AAC | IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)  | WLAN  | 9.36     | ±9.6                   |
| 10738 | AAC | IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.42     | ±9.6                   |
| 10739 | AAC | IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.29     | ±9.6                   |
| 10740 | AAC | IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.48     | ±9.6                   |
| 10741 | AAC | IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.40     | ±9.6                   |
| 10742 | AAC | IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.43     | ±9.6                   |
| 10743 | AAC | IEEE 802.11ax (160 MHz, MCS0, 90pc duty cycle) | WLAN  | 8.84     | ±9.6                   |
| 10744 | AAC | IEEE 802.11ax (160 MHz, MCS1, 90pc duty cycle) | WLAN  | 8.16     | ±9.6                   |
| 10745 | AAC | IEEE 802.11ax (160 MHz, MCS2, 90pc duty cycle) | WLAN  | 8.53     | ±9.6                   |
| 10746 | AAC | IEEE 802.11ax (160 MHz, MCS3, 90pc duty cycle) | WLAN  | 9.11     | ±9.6                   |
| 10747 | AAC | IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle) | WLAN  | 8.04     | ±9.6                   |
| 10748 | AAC | IEEE 802.11ax (160 MHz, MCS5, 90pc duty cycle) | WLAN  | 8.93     | ±9.6                   |
| 10749 | AAC | IEEE 802.11ax (160 MHz, MCS6, 90pc duty cycle) | WLAN  | 8.80     | ±9.6                   |
| 10750 | AAC | IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle) | WLAN  | 8.79     | ±9.6                   |
| 10751 | AAC | IEEE 802.11ax (160 MHz, MCS8, 90pc duty cycle) | WLAN  | 8.82     | ±9.6                   |
| 10752 | AAC | IEEE 802.11ax (160 MHz, MCS9, 90pc duty cycle) | WLAN  | 8.81     | ±9.6                   |

Certificate No: EX-7655\_Jun25

Page 17 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                       | Group         | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|-------------------------------------------------|---------------|----------|------------------------|
| 10752 | AAC | IEEE 802.11ax (180 MHz, MCS10, 99pc duty cycle) | WLAN          | 8.00     | ±9.6                   |
| 10754 | AAC | IEEE 802.11ax (180 MHz, MCS11, 99pc duty cycle) | WLAN          | 8.54     | ±9.6                   |
| 10755 | AAC | IEEE 802.11ax (180 MHz, MCS0, 99pc duty cycle)  | WLAN          | 8.64     | ±9.6                   |
| 10756 | AAC | IEEE 802.11ax (180 MHz, MCS1, 99pc duty cycle)  | WLAN          | 8.77     | ±9.6                   |
| 10757 | AAC | IEEE 802.11ax (180 MHz, MCS2, 99pc duty cycle)  | WLAN          | 8.77     | ±9.6                   |
| 10758 | AAC | IEEE 802.11ax (180 MHz, MCS3, 99pc duty cycle)  | WLAN          | 8.69     | ±9.6                   |
| 10759 | AAC | IEEE 802.11ax (180 MHz, MCS4, 99pc duty cycle)  | WLAN          | 8.58     | ±9.6                   |
| 10760 | AAC | IEEE 802.11ax (180 MHz, MCS5, 99pc duty cycle)  | WLAN          | 8.49     | ±9.6                   |
| 10761 | AAC | IEEE 802.11ax (180 MHz, MCS6, 99pc duty cycle)  | WLAN          | 8.58     | ±9.6                   |
| 10762 | AAC | IEEE 802.11ax (180 MHz, MCS7, 99pc duty cycle)  | WLAN          | 8.49     | ±9.6                   |
| 10763 | AAC | IEEE 802.11ax (180 MHz, MCS8, 99pc duty cycle)  | WLAN          | 8.53     | ±9.6                   |
| 10764 | AAC | IEEE 802.11ax (180 MHz, MCS8, 99pc duty cycle)  | WLAN          | 8.54     | ±9.6                   |
| 10765 | AAC | IEEE 802.11ax (180 MHz, MCS10, 99pc duty cycle) | WLAN          | 8.54     | ±9.6                   |
| 10766 | AAC | IEEE 802.11ax (180 MHz, MCS11, 99pc duty cycle) | WLAN          | 8.51     | ±9.6                   |
| 10767 | AAG | 5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)      | 5G NR FR1 TDD | 7.99     | ±9.6                   |
| 10768 | AAE | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10769 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10770 | AAE | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.32     | ±9.6                   |
| 10771 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10772 | AAE | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.29     | ±9.6                   |
| 10773 | AAF | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10774 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.6                   |
| 10775 | AAF | 5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)    | 5G NR FR1 TDD | 9.31     | ±9.6                   |
| 10776 | AAE | 5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10777 | AAC | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10778 | AAE | 5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10779 | AAC | 5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10780 | AAE | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10781 | AAF | 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.38     | ±9.6                   |
| 10782 | AAE | 5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.43     | ±9.6                   |
| 10783 | AAC | 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.31     | ±9.6                   |
| 10784 | AAE | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.29     | ±9.6                   |
| 10785 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.40     | ±9.6                   |
| 10786 | AAE | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10787 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.44     | ±9.6                   |
| 10788 | AAE | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10789 | AAF | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.57     | ±9.6                   |
| 10790 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.59     | ±9.6                   |
| 10791 | AAG | 5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 7.83     | ±9.6                   |
| 10792 | AAE | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.92     | ±9.6                   |
| 10793 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.95     | ±9.6                   |
| 10794 | AAE | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10795 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.84     | ±9.6                   |
| 10796 | AAE | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.82     | ±9.6                   |
| 10797 | AAF | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.6                   |
| 10798 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.99     | ±9.6                   |
| 10799 | AAF | 5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10800 | AAF | 5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.89     | ±9.6                   |
| 10802 | AAE | 5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.87     | ±9.6                   |
| 10803 | AAF | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 7.93     | ±9.6                   |
| 10805 | AAE | 5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10806 | AAD | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.37     | ±9.6                   |
| 10809 | AAE | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10810 | AAF | 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10812 | AAF | 5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10817 | AAG | 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.35     | ±9.6                   |
| 10818 | AAE | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.34     | ±9.6                   |
| 10819 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10820 | AAE | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.30     | ±9.6                   |
| 10821 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10822 | AAE | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10823 | AAF | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.36     | ±9.6                   |
| 10824 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.6                   |
| 10825 | AAF | 5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.6                   |
| 10827 | AAF | 5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.42     | ±9.6                   |
| 10829 | AAE | 5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.43     | ±9.6                   |

Certificate No: EX-7655\_Jun25

Page 18 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                            | Group         | PAR (dB) | Unc <sup>F</sup> k = 2 |
|-------|-----|------------------------------------------------------|---------------|----------|------------------------|
| 19829 | AAF | 5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 6.40     | ±0.6                   |
| 19830 | AAE | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.63     | ±0.6                   |
| 19831 | AAE | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.73     | ±0.6                   |
| 19832 | AAE | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.74     | ±0.6                   |
| 19833 | AAE | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.70     | ±0.6                   |
| 19834 | AAE | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.73     | ±0.6                   |
| 19835 | AAE | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.70     | ±0.6                   |
| 19836 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.68     | ±0.6                   |
| 19837 | AAE | 5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.69     | ±0.6                   |
| 19838 | AAE | 5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.70     | ±0.6                   |
| 19840 | AAE | 5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)          | 5G NR FR1 TDD | 7.87     | ±0.6                   |
| 19841 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)         | 5G NR FR1 TDD | 7.71     | ±0.6                   |
| 19843 | AAE | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)        | 5G NR FR1 TDD | 8.49     | ±0.6                   |
| 19844 | AAE | 5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)        | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 19846 | AAE | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)        | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 19854 | AAE | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 19855 | AAE | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.28     | ±0.6                   |
| 19856 | AAE | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.37     | ±0.6                   |
| 19857 | AAE | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.35     | ±0.6                   |
| 19858 | AAE | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.56     | ±0.6                   |
| 19859 | AAE | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.34     | ±0.6                   |
| 19860 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 19861 | AAE | 5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 9.40     | ±0.6                   |
| 19863 | AAE | 5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 19864 | AAE | 5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)       | 5G NR FR1 TDD | 8.37     | ±0.6                   |
| 19865 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)      | 5G NR FR1 TDD | 8.41     | ±0.6                   |
| 19866 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 5.66     | ±0.6                   |
| 19869 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.69     | ±0.6                   |
| 19869 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)     | 5G NR FR2 TDD | 5.75     | ±0.6                   |
| 19870 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)  | 5G NR FR2 TDD | 5.66     | ±0.6                   |
| 19871 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)    | 5G NR FR2 TDD | 5.75     | ±0.6                   |
| 19872 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz) | 5G NR FR2 TDD | 6.62     | ±0.6                   |
| 19873 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)    | 5G NR FR2 TDD | 6.61     | ±0.6                   |
| 19874 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz) | 5G NR FR2 TDD | 6.65     | ±0.6                   |
| 19875 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)        | 5G NR FR2 TDD | 7.78     | ±0.6                   |
| 19876 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)     | 5G NR FR2 TDD | 6.39     | ±0.6                   |
| 19877 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)       | 5G NR FR2 TDD | 7.95     | ±0.6                   |
| 19878 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)    | 5G NR FR2 TDD | 8.41     | ±0.6                   |
| 19879 | AAE | 5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)       | 5G NR FR2 TDD | 8.12     | ±0.6                   |
| 19880 | AAE | 5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)    | 5G NR FR2 TDD | 8.39     | ±0.6                   |
| 19881 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)      | 5G NR FR2 TDD | 5.75     | ±0.6                   |
| 19882 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)   | 5G NR FR2 TDD | 6.95     | ±0.6                   |
| 19883 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)     | 5G NR FR2 TDD | 6.57     | ±0.6                   |
| 19884 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)  | 5G NR FR2 TDD | 6.53     | ±0.6                   |
| 19885 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)     | 5G NR FR2 TDD | 6.51     | ±0.6                   |
| 19886 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)  | 5G NR FR2 TDD | 6.65     | ±0.6                   |
| 19887 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)         | 5G NR FR2 TDD | 7.78     | ±0.6                   |
| 19888 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)      | 5G NR FR2 TDD | 8.35     | ±0.6                   |
| 19889 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)        | 5G NR FR2 TDD | 8.02     | ±0.6                   |
| 19890 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)     | 5G NR FR2 TDD | 8.40     | ±0.6                   |
| 19891 | AAE | 5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)        | 5G NR FR2 TDD | 8.13     | ±0.6                   |
| 19892 | AAE | 5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)     | 5G NR FR2 TDD | 8.41     | ±0.6                   |
| 19897 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)        | 5G NR FR1 TDD | 5.38     | ±0.6                   |
| 19898 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.57     | ±0.6                   |
| 19899 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.57     | ±0.6                   |
| 19900 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.58     | ±0.6                   |
| 19901 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.59     | ±0.6                   |
| 19902 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.58     | ±0.6                   |
| 19903 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.58     | ±0.6                   |
| 19904 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.58     | ±0.6                   |
| 19905 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.58     | ±0.6                   |
| 19906 | AAE | 5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)       | 5G NR FR1 TDD | 5.58     | ±0.6                   |
| 19907 | AAE | 5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 5.78     | ±0.6                   |
| 19908 | AAE | 5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 5.93     | ±0.6                   |
| 19909 | AAE | 5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 5.96     | ±0.6                   |
| 19910 | AAE | 5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 5.93     | ±0.6                   |

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                           | Group         | PAR (dB) | Unc <sup>1</sup> k = 2 |
|-------|-----|-----------------------------------------------------|---------------|----------|------------------------|
| 10911 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.93     | ±9.6                   |
| 10912 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10913 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10914 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.85     | ±9.6                   |
| 10915 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.83     | ±9.6                   |
| 10916 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10917 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.94     | ±9.6                   |
| 10918 | AAE | 5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 5.85     | ±9.6                   |
| 10919 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.86     | ±9.6                   |
| 10920 | AAB | 5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.87     | ±9.6                   |
| 10921 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10922 | AAB | 5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.82     | ±9.6                   |
| 10923 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10924 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10925 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.85     | ±9.6                   |
| 10926 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10927 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 5.84     | ±9.6                   |
| 10928 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)       | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10929 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10930 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.52     | ±9.6                   |
| 10931 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10932 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10933 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10934 | AAC | 5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10935 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)      | 5G NR FR1 FDD | 5.51     | ±9.6                   |
| 10936 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)     | 5G NR FR1 FDD | 5.90     | ±9.6                   |
| 10937 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.77     | ±9.6                   |
| 10938 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.90     | ±9.6                   |
| 10939 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.82     | ±9.6                   |
| 10940 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.89     | ±9.6                   |
| 10941 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10942 | AAC | 5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10943 | AAD | 5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.95     | ±9.6                   |
| 10944 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)    | 5G NR FR1 FDD | 5.81     | ±9.6                   |
| 10945 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.85     | ±9.6                   |
| 10946 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.83     | ±9.6                   |
| 10947 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10948 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10949 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.87     | ±9.6                   |
| 10950 | AAC | 5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.94     | ±9.6                   |
| 10951 | AAD | 5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)   | 5G NR FR1 FDD | 5.98     | ±9.6                   |
| 10952 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)   | 5G NR FR1 FDD | 9.25     | ±9.6                   |
| 10953 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 FDD | 8.15     | ±9.6                   |
| 10954 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 FDD | 9.23     | ±9.6                   |
| 10955 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 FDD | 8.42     | ±9.6                   |
| 10956 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)   | 5G NR FR1 FDD | 9.14     | ±9.6                   |
| 10957 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 FDD | 8.31     | ±9.6                   |
| 10958 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 FDD | 9.31     | ±9.6                   |
| 10959 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 FDD | 8.33     | ±9.6                   |
| 10960 | AAE | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)   | 5G NR FR1 TDD | 9.32     | ±9.6                   |
| 10961 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 TDD | 9.36     | ±9.6                   |
| 10962 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 TDD | 9.40     | ±9.6                   |
| 10963 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)  | 5G NR FR1 TDD | 9.55     | ±9.6                   |
| 10964 | AAE | 5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)   | 5G NR FR1 TDD | 9.29     | ±9.6                   |
| 10965 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 TDD | 9.37     | ±9.6                   |
| 10966 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 TDD | 9.55     | ±9.6                   |
| 10967 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)  | 5G NR FR1 TDD | 9.42     | ±9.6                   |
| 10968 | AAD | 5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.49     | ±9.6                   |
| 10972 | AAC | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)         | 5G NR FR1 TDD | 11.59    | ±9.6                   |
| 10973 | AAD | 5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 9.06     | ±9.6                   |
| 10974 | AAD | 5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)  | 5G NR FR1 TDD | 10.28    | ±9.6                   |
| 10976 | AAA | JLLA BDR                                            | ULLA          | 1.16     | ±9.6                   |
| 10979 | AAA | JLLA HDR4                                           | ULLA          | 9.88     | ±9.6                   |
| 10980 | AAA | JLLA HDR8                                           | ULLA          | 10.32    | ±9.6                   |
| 10981 | AAA | JLLA HDRp4                                          | ULLA          | 9.19     | ±9.6                   |
| 10982 | AAA | JLLA HDRp8                                          | ULLA          | 9.43     | ±9.6                   |

Certificate No: EX-7655\_Jun25

Page 20 of 21

EX3DV4 - SN:7655

June 03, 2025

| UID   | Rev | Communication System Name                          | Group         | PAR (dB) | Unc <sup>F</sup> k = 2 |
|-------|-----|----------------------------------------------------|---------------|----------|------------------------|
| 10983 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz) | 5G NR FR1 TDD | 9.31     | ±9.6                   |
| 10984 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz) | 5G NR FR1 TDD | 9.42     | ±9.6                   |
| 10985 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.54     | ±9.6                   |
| 10986 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.50     | ±9.6                   |
| 10987 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.53     | ±9.6                   |
| 10988 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 9.30     | ±9.6                   |
| 10989 | AAC | 5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 8.33     | ±9.6                   |
| 10990 | AAB | 5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 8.52     | ±9.6                   |
| 11003 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz) | 5G NR FR1 TDD | 10.24    | ±9.6                   |
| 11004 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz) | 5G NR FR1 TDD | 10.73    | ±9.6                   |
| 11005 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.70     | ±9.6                   |
| 11006 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.55     | ±9.6                   |
| 11007 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.48     | ±9.6                   |
| 11008 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz) | 5G NR FR1 FDD | 8.51     | ±9.6                   |
| 11009 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.78     | ±9.6                   |
| 11010 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.95     | ±9.6                   |
| 11011 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.98     | ±9.6                   |
| 11012 | AAA | 5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz) | 5G NR FR1 FDD | 8.58     | ±9.6                   |
| 11018 | AAB | IEEE 802.11be (320 MHz, MCS1, 99% duty cycle)      | WLAN          | 8.47     | ±9.6                   |
| 11014 | AAB | IEEE 802.11be (320 MHz, MCS2, 99% duty cycle)      | WLAN          | 8.45     | ±9.6                   |
| 11015 | AAB | IEEE 802.11be (320 MHz, MCS3, 99% duty cycle)      | WLAN          | 8.44     | ±9.6                   |
| 11016 | AAB | IEEE 802.11be (320 MHz, MCS4, 99% duty cycle)      | WLAN          | 8.44     | ±9.6                   |
| 11017 | AAB | IEEE 802.11be (320 MHz, MCS5, 99% duty cycle)      | WLAN          | 8.41     | ±9.6                   |
| 11018 | AAB | IEEE 802.11be (320 MHz, MCS6, 99% duty cycle)      | WLAN          | 8.40     | ±9.6                   |
| 11019 | AAB | IEEE 802.11be (320 MHz, MCS7, 99% duty cycle)      | WLAN          | 8.29     | ±9.6                   |
| 11020 | AAB | IEEE 802.11be (320 MHz, MCS8, 99% duty cycle)      | WLAN          | 8.27     | ±9.6                   |
| 11021 | AAB | IEEE 802.11be (320 MHz, MCS9, 99% duty cycle)      | WLAN          | 8.46     | ±9.6                   |
| 11022 | AAB | IEEE 802.11be (320 MHz, MCS10, 99% duty cycle)     | WLAN          | 8.36     | ±9.6                   |
| 11023 | AAB | IEEE 802.11be (320 MHz, MCS11, 99% duty cycle)     | WLAN          | 8.09     | ±9.6                   |
| 11024 | AAB | IEEE 802.11be (320 MHz, MCS12, 99% duty cycle)     | WLAN          | 8.42     | ±9.6                   |
| 11025 | AAB | IEEE 802.11be (320 MHz, MCS13, 99% duty cycle)     | WLAN          | 8.37     | ±9.6                   |
| 11026 | AAB | IEEE 802.11be (320 MHz, MCS0, 99% duty cycle)      | WLAN          | 8.39     | ±9.6                   |

<sup>F</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**

Zaugghausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **HCT**  
Gyeonggi-do, Republic of Korea

Certificate No. **EX-7907\_Jan26**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7907**

Calibration procedure(s) **QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,  
QA CAL-25.v9, QA CAL-48.v2  
Calibration procedure for dosimetric E-field probes**

Calibration date **January 23, 2026**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.  
All calibrations have been conducted in the closed laboratory facility; environment temperature (22 ± 3) °C and humidity < 70%.  
Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID         | Calibration Date (Certificate No.)     | Sched. Cal. |
|-----------------------------|------------|----------------------------------------|-------------|
| Power Sensor R&S NRP40T     | SN: 101861 | 29-Apr-25 (No. 2025-001453)            | Apr-26      |
| N-type mismatch combination | SN: L1119  | 26-Mar-25 (No. 217-04292)              | Mar-26      |
| OCP DAK-12                  | SN: 1016   | 16-Sept-25 (No. OCP-DAK12-1016_Sep25)  | Sep-26      |
| OCP DAK-3.5                 | SN: 1249   | 16-Sept-25 (No. OCP-DAK3.5-1249_Sep25) | Sep-26      |
| Reference Probe EX3DV4      | SN: 7349   | 10-Jan-25 (No. EX3-7349_Jan25)         | Jan-26      |
| DAE4                        | SN: 1301   | 22-Jan-26 (No. DAE4-1301_Jan26)        | Jan-27      |

| Secondary Standards | ID        | Check Date (in house)                 | Sched. Check |
|---------------------|-----------|---------------------------------------|--------------|
| ACAP 2020 Setup 1   | SN: L1404 | 01-Oct-25 (No. IHCK_ACAP2020-1_Oct25) | Oct-26       |
| OCP DAK-12          | SN: 1029  | 27-Feb-25 (No. OCP-DAK12-1029_Feb25)  | Feb-26       |
| OCP DAK-3.5         | SN: 1336  | 10-Dec-25 (No. OCP-DAK3.5-1336_Dec25) | Dec-26       |

|                                                                                                                 |                  |                       |                          |
|-----------------------------------------------------------------------------------------------------------------|------------------|-----------------------|--------------------------|
|                                                                                                                 | Name             | Function              | Signature                |
| Calibrated by                                                                                                   | Henrique Almeida | Laboratory Technician | <i>Henrique Almeida</i>  |
| Approved by                                                                                                     | Sven Kohn        | Technical Manager     | <i>Sven Kohn</i>         |
|                                                                                                                 |                  |                       | Issued: January 23, 2026 |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |                  |                       |                          |

Certificate No: EX-7907\_Jan26

Page 1 of 21

|    |            |                    |
|----|------------|--------------------|
| 결  | 담당자        | 확인자                |
| 제  | 7/2/26     | <i>[Signature]</i> |
| 작성 | DL 1/2/26  | 1/2/26             |
| 일자 | 2026.02.05 | 2026.02.25         |

# Calibration Laboratory of Schmid & Partner Engineering AG

Zoughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

## Glossary

|                        |                                                                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | tissue simulating liquid                                                                                                                       |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                      |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                     |
| DCP                    | diode compression point                                                                                                                        |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                   |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                  |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                           |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | information used in DASY system to align probe sensor X to the robot coordinate system                                                         |

## Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865604, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f < 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM( $f$ )<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to  $NORM_{x,y,z} * ConvF$  whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

EX3DV4 - SN:7907

January 23, 2026

### Parameters of Probe: EX3DV4 - SN:7907

#### Basic Calibration Parameters

|                                                    | Sensor X | Sensor Y | Sensor Z | Unc (k = 2)  |
|----------------------------------------------------|----------|----------|----------|--------------|
| Norm ( $\mu\text{W}/(\text{V/m})^2$ ) <sup>A</sup> | 0.63     | 0.65     | 0.64     | $\pm 10.1\%$ |
| DCP (mV) <sup>B</sup>                              | 101.9    | 103.4    | 103.7    | $\pm 4.7\%$  |

#### Calibration Results for Modulation Response

| UID   | Communication System Name      |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C     | D<br>dB | VR<br>mV | Max<br>dev. | Max<br>Unc <sup>E</sup><br>k = 2 |
|-------|--------------------------------|---|---------|------------------------------|-------|---------|----------|-------------|----------------------------------|
| 0     | Continuous Wave                | X | 0.00    | 0.00                         | 1.00  | 0.00    | 127.3    | $\pm 1.6\%$ | $\pm 4.7\%$                      |
|       |                                | Y | 0.00    | 0.00                         | 1.00  |         | 137.2    |             |                                  |
|       |                                | Z | 0.00    | 0.00                         | 1.00  |         | 131.4    |             |                                  |
| 10352 | Pulse (D=10%, T=5 ms)          | X | 0.47    | 70.00                        | 18.76 | 10.00   | 23.0     | $\pm 1.6\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 0.44    | 70.00                        | 18.67 |         | 24.0     |             |                                  |
|       |                                | Z | 0.49    | 70.00                        | 18.74 |         | 24.0     |             |                                  |
| 10353 | Pulse (D=20%, T=5 ms)          | X | 0.44    | 73.01                        | 18.83 | 6.99    | 47.0     | $\pm 1.4\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 0.41    | 73.01                        | 18.72 |         | 47.0     |             |                                  |
|       |                                | Z | 0.46    | 73.01                        | 18.79 |         | 48.0     |             |                                  |
| 10354 | Pulse (D=40%, T=5 ms)          | X | 0.41    | 76.02                        | 18.89 | 3.90    | 93.0     | $\pm 1.2\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 0.38    | 76.02                        | 18.78 |         | 94.0     |             |                                  |
|       |                                | Z | 0.43    | 76.02                        | 18.84 |         | 95.0     |             |                                  |
| 10355 | Pulse (D=60%, T=5 ms)          | X | 0.39    | 77.78                        | 18.93 | 2.22    | 140.0    | $\pm 1.1\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 0.36    | 77.78                        | 18.81 |         | 141.0    |             |                                  |
|       |                                | Z | 0.42    | 77.78                        | 18.87 |         | 143.0    |             |                                  |
| 10387 | Random (BW=1 MHz, MOD=QPSK)    | X | 0.00    | 60.06                        | 20.08 | 0.07    | 110.0    | $\pm 1.7\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 0.00    | 74.90                        | 20.08 |         | 111.0    |             |                                  |
|       |                                | Z | 0.01    | 60.16                        | 19.99 |         | 112.0    |             |                                  |
| 10388 | Random (BW=10 MHz, MOD=QPSK)   | X | 1.81    | 74.78                        | 17.55 | 0.00    | 116.0    | $\pm 2.5\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 1.60    | 74.78                        | 17.64 |         | 118.0    |             |                                  |
|       |                                | Z | 1.76    | 74.78                        | 17.71 |         | 119.0    |             |                                  |
| 10396 | Random (BW=100 kHz, MOD=64QAM) | X | 0.03    | 73.73                        | 22.12 | 1.79    | 61.0     | $\pm 5.0\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 0.08    | 60.75                        | 21.51 |         | 62.0     |             |                                  |
|       |                                | Z | 0.09    | 60.52                        | 21.77 |         | 63.0     |             |                                  |
| 10399 | Random (BW=40 MHz, MOD=64QAM)  | X | 3.97    | 73.73                        | 17.43 | 0.00    | 108.0    | $\pm 3.7\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 3.73    | 73.73                        | 17.48 |         | 110.0    |             |                                  |
|       |                                | Z | 3.86    | 73.73                        | 17.59 |         | 111.0    |             |                                  |
| 10414 | Random (BW=40 MHz, HIGH PAR)   | X | 4.95    | 71.46                        | 17.43 | 0.00    | 60.0     | $\pm 1.7\%$ | $\pm 9.6\%$                      |
|       |                                | Y | 4.61    | 71.46                        | 17.48 |         | 61.0     |             |                                  |
|       |                                | Z | 4.75    | 71.46                        | 17.59 |         | 62.0     |             |                                  |

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$  field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Linearization parameter uncertainty for maximum specified field strength.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4 - SN:7907

January 23, 2026

### Parameters of Probe: EX3DV4 - SN:7907

#### Sensor Model Parameters

|   | C1<br>IF | C2<br>IF | $\alpha$<br>V <sup>-1</sup> | T1<br>ms V <sup>-2</sup> | T2<br>ms V <sup>-1</sup> | T3<br>ms | T4<br>V <sup>-2</sup> | T5<br>V <sup>-1</sup> | T6   |
|---|----------|----------|-----------------------------|--------------------------|--------------------------|----------|-----------------------|-----------------------|------|
| x | 11.5     | 88.25    | 35.52                       | 1.75                     | 0.00                     | 4.90     | 0.21                  | 0.00                  | 1.00 |
| y | 10.5     | 77.89    | 35.19                       | 2.07                     | 0.00                     | 4.90     | 0.17                  | 0.00                  | 1.00 |
| z | 11.2     | 82.66    | 34.92                       | 2.03                     | 0.00                     | 4.90     | 0.18                  | 0.00                  | 1.00 |

#### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle                               | 32.7°      |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 12 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

Note: Measurement distance from surface can be increased to 3-4 mm for an Area Scan job.

EX3DV4 - SN:7907

January 23, 2026

# Parameters of Probe: EX3DV4 - SN:7907

## Calibration Parameter Determined in HSL

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 750                  | 41.9                               | 0.89                            | 9.48    | 9.47    | 9.89    | 0.36               | 1.27                    | ±11.0%                   |
| 835                  | 41.5                               | 0.90                            | 9.01    | 9.02    | 9.42    | 0.36               | 1.27                    | ±11.0%                   |
| 900                  | 41.5                               | 0.97                            | 8.98    | 8.99    | 9.39    | 0.36               | 1.27                    | ±11.0%                   |
| 1640                 | 40.2                               | 1.31                            | 7.64    | 7.64    | 7.90    | 0.36               | 1.27                    | ±11.0%                   |
| 1750                 | 40.1                               | 1.37                            | 7.71    | 7.71    | 8.06    | 0.36               | 1.27                    | ±11.0%                   |
| 1900                 | 40.0                               | 1.40                            | 7.48    | 7.48    | 7.82    | 0.36               | 1.27                    | ±11.0%                   |
| 2300                 | 39.5                               | 1.67                            | 7.30    | 7.30    | 7.63    | 0.36               | 1.27                    | ±11.0%                   |
| 2450                 | 39.2                               | 1.80                            | 6.90    | 6.90    | 7.21    | 0.36               | 1.27                    | ±11.0%                   |
| 2600                 | 39.0                               | 1.96                            | 7.06    | 7.06    | 7.38    | 0.36               | 1.27                    | ±11.0%                   |
| 3300                 | 38.2                               | 2.71                            | 6.23    | 6.23    | 6.51    | 0.36               | 1.27                    | ±13.1%                   |
| 3500                 | 37.9                               | 2.91                            | 6.25    | 6.25    | 6.54    | 0.36               | 1.27                    | ±13.1%                   |
| 3700                 | 37.7                               | 3.12                            | 6.27    | 6.27    | 6.56    | 0.36               | 1.27                    | ±13.1%                   |
| 3900                 | 37.5                               | 3.32                            | 6.40    | 6.40    | 6.69    | 0.36               | 1.27                    | ±13.1%                   |
| 4100                 | 37.2                               | 3.53                            | 6.22    | 6.23    | 6.51    | 0.36               | 1.27                    | ±13.1%                   |
| 5250                 | 35.9                               | 4.71                            | 5.37    | 5.37    | 5.62    | 0.32               | 1.27                    | ±13.1%                   |
| 5600                 | 35.5                               | 5.07                            | 4.91    | 4.92    | 5.14    | 0.28               | 1.27                    | ±13.1%                   |
| 5750                 | 35.4                               | 5.22                            | 5.00    | 5.00    | 5.23    | 0.27               | 1.27                    | ±13.1%                   |
| 5800                 | 35.3                               | 5.27                            | 4.81    | 4.81    | 5.03    | 0.27               | 1.27                    | ±13.1%                   |

<sup>C</sup> Frequency validity above 300 MHz of ±100 MHz only applies for DASY v6.4 and higher (see Page 2), else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is +10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 5 MHz is 4–8 MHz, and ConvF assessed at 15 MHz is 8–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon'$  and  $\sigma$  by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10% if SAR correction is applied.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Non-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.

EX3DV4 - SN:7907

January 23, 2025

## Parameters of Probe: EX3DV4 - SN:7907

### Calibration Parameter Determined in HSL

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 6500                 | 34.5                               | 6.07                            | 5.31    | 5.31    | 5.55    | 0.20               | 1.27                    | ±18.8%                   |

<sup>C</sup> Frequency validity is -500/+700 MHz at 6.5 GHz, +700 MHz at or above 7 GHz, and ±150 MHz at 9.85 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.


<sup>F</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon$  and  $\sigma$  by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±13%.

<sup>G</sup> Alpha/Depth are determined during calibration. SPPLAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz; below ±2% for frequencies between 3–8 GHz; and below ±4% for frequencies between 8–10 GHz at any distance larger than half the probe tip diameter from the boundary.

<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm ConvF. This is equivalent to the uncertainty component with the symbol C<sup>F</sup> in Table 9 of IEC/IEEE 62239-1525:2020.

EX3DV4 - SN:7907



January 23, 2026



EX3DV4 - SN:7907


January 23, 2026

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



EX3DV4 - SN:7907

January 23, 2026




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )


EX3DV4 - SN:7907

January 23, 2026

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid



EX3DV4 - SN:7907

January 23, 2026

## Appendix: Modulation Calibration Parameters

| UID   | Rev | Communication System Name                      | Group     | PAR (dB) | Unc <sup>1</sup> k = 2 |
|-------|-----|------------------------------------------------|-----------|----------|------------------------|
| 0     |     | Continuous Wave                                | CW        | 0.00     | ±4.7                   |
| 10010 | CAD | Pulse (D=10%, T=100 ms)                        | Pest      | 13.00    | ±8.6                   |
| 10011 | CAC | Rel. 99, RMC, QPSK, 5.0 MHz                    | WCDMA     | 2.91     | ±8.6                   |
| 10012 | CAB | DSSS, DQPSK, 1.0 Mbps, 82.5% DC                | WLAN      | 1.87     | ±8.6                   |
| 10013 | CAB | OFDM, BPSK, 5.0 Mbps, 72.1% DC                 | WLAN      | 8.46     | ±8.6                   |
| 10021 | DAC | Voice, GMSK, 1 slot(s)                         | GSM       | 9.39     | ±8.6                   |
| 10023 | DAC | Data, GMSK, 1 slot(s)                          | GSM       | 9.57     | ±8.6                   |
| 10024 | DAC | Data, GMSK, 2 slot(s)                          | GSM       | 8.50     | ±8.6                   |
| 10025 | DAC | Data, 8PSK, 1 slot(s)                          | GSM       | 12.82    | ±8.6                   |
| 10026 | DAC | Data, 8PSK, 2 slot(s)                          | GSM       | 9.55     | ±8.6                   |
| 10027 | DAC | Data, GMSK, 3 slot(s)                          | GSM       | 4.80     | ±8.6                   |
| 10028 | DAC | Data, GMSK, 4 slot(s)                          | GSM       | 3.58     | ±8.6                   |
| 10029 | DAC | Data, 8PSK, 3 slot(s)                          | GSM       | 7.79     | ±8.6                   |
| 10030 | CAA | BR, D11, GFSK                                  | Bluetooth | 5.30     | ±8.6                   |
| 10031 | CAA | BR, D13, GFSK                                  | Bluetooth | 1.87     | ±8.6                   |
| 10032 | CAA | BR, D15, GFSK                                  | Bluetooth | 1.13     | ±8.6                   |
| 10033 | CAA | EDR, D11, pi/4-QPSK                            | Bluetooth | 7.74     | ±8.6                   |
| 10034 | CAA | EDR, D13, pi/4-QPSK                            | Bluetooth | 4.53     | ±8.6                   |
| 10035 | CAA | EDR, D15, pi/4-QPSK                            | Bluetooth | 3.83     | ±8.6                   |
| 10036 | CAA | EDR, D11, 8-PSK                                | Bluetooth | 8.01     | ±8.6                   |
| 10037 | CAA | EDR, D13, 8-PSK                                | Bluetooth | 4.77     | ±8.6                   |
| 10038 | CAA | EDR, D15, 8-PSK                                | Bluetooth | 4.19     | ±8.6                   |
| 10039 | CAB | RC1, 1xRTT                                     | CDMA2000  | 4.57     | ±8.6                   |
| 10048 | CAA | Full Slot, GFSK, 1 slot(s)                     | DECT      | 13.80    | ±8.6                   |
| 10049 | CAA | Double Slot, GFSK, 2 slot(s)                   | DECT      | 10.78    | ±8.6                   |
| 10058 | CAA | TD-SCDMA, QPSK, 1.8 MHz                        | TD-SCDMA  | 11.01    | ±8.6                   |
| 10058 | DAC | Data, 8PSK, 4 slot(s)                          | GSM       | 6.59     | ±8.6                   |
| 10059 | CAB | DSSS, DQPSK, 2.0 Mbps, 87.4% DC                | WLAN      | 2.12     | ±8.6                   |
| 10060 | CAB | HR-DSSS, DQPSK, 5.5 Mbps, 72.7% DC             | WLAN      | 2.83     | ±8.6                   |
| 10061 | CAB | HR-DSSS, DQPSK, 11.0 Mbps, 67.5% DC            | WLAN      | 3.60     | ±8.6                   |
| 10062 | CAE | OFDM, BPSK, 8.0 Mbps, 89.1% DC                 | WLAN      | 8.68     | ±8.6                   |
| 10063 | CAE | OFDM, BPSK, 8.0 Mbps, 85.3% DC                 | WLAN      | 8.63     | ±8.6                   |
| 10064 | CAE | OFDM, QPSK, 12.0 Mbps, 82.0% DC                | WLAN      | 8.68     | ±8.6                   |
| 10065 | CAE | OFDM, QPSK, 18.0 Mbps, 78.0% DC                | WLAN      | 9.00     | ±8.6                   |
| 10066 | CAE | OFDM, 16QAM, 24.0 Mbps, 70.8% DC               | WLAN      | 9.58     | ±8.6                   |
| 10067 | CAE | OFDM, 16QAM, 36.0 Mbps, 62.8% DC               | WLAN      | 10.12    | ±8.6                   |
| 10068 | CAE | OFDM, 64QAM, 48.0 Mbps, 58.8% DC               | WLAN      | 10.24    | ±8.6                   |
| 10069 | CAE | OFDM, 64QAM, 54.0 Mbps, 54.7% DC               | WLAN      | 10.56    | ±8.6                   |
| 10071 | CAB | OFDM, BPSK, 8.0 Mbps, 85.1% DC                 | WLAN      | 9.69     | ±8.6                   |
| 10072 | CAB | OFDM, QPSK, 12.0 Mbps, 80.1% DC                | WLAN      | 9.62     | ±8.6                   |
| 10073 | CAB | OFDM, QPSK, 18.0 Mbps, 53.1% DC                | WLAN      | 9.94     | ±8.6                   |
| 10074 | CAB | OFDM, 16QAM, 24.0 Mbps, 48.5% DC               | WLAN      | 10.36    | ±8.6                   |
| 10075 | CAB | OFDM, 16QAM, 36.0 Mbps, 42.9% DC               | WLAN      | 10.77    | ±8.6                   |
| 10076 | CAB | OFDM, 64QAM, 48.0 Mbps, 38.5% DC               | WLAN      | 10.84    | ±8.6                   |
| 10077 | CAB | OFDM, 64QAM, 54.0 Mbps, 38.5% DC               | WLAN      | 11.00    | ±8.6                   |
| 10081 | CAB | RC3, 1xRTT                                     | CDMA2000  | 3.97     | ±8.6                   |
| 10087 | CAC | Rel. 5 HSPA, QPSK, 5.0 MHz                     | WCDMA     | 3.98     | ±8.6                   |
| 10088 | CAC | Rel. 5 HSPA, Subcar. 2, QPSK, 5.0 MHz          | WCDMA     | 3.98     | ±8.6                   |
| 10100 | CAF | 20.0 MHz, QPSK, 100% RB                        | LTE-FDD   | 5.67     | ±8.6                   |
| 10101 | CAF | 20.0 MHz, 16QAM, 100% RB                       | LTE-FDD   | 6.42     | ±8.6                   |
| 10102 | CAF | 20.0 MHz, 64QAM, 100% RB                       | LTE-FDD   | 6.60     | ±8.6                   |
| 10103 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB  | LTE-TDD   | 9.28     | ±8.6                   |
| 10104 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB | LTE-TDD   | 9.97     | ±8.6                   |
| 10105 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB | LTE-TDD   | 10.01    | ±8.6                   |
| 10106 | CAH | 10.0 MHz, QPSK, 100% RB                        | LTE-FDD   | 5.80     | ±8.6                   |
| 10106 | CAH | 10.0 MHz, 16QAM, 100% RB                       | LTE-FDD   | 6.43     | ±8.6                   |
| 10110 | CAH | 5.0 MHz, QPSK, 100% RB                         | LTE-FDD   | 5.76     | ±8.6                   |
| 10111 | CAH | 5.0 MHz, 16QAM, 100% RB                        | LTE-FDD   | 6.44     | ±8.6                   |
| 10112 | CAH | 10.0 MHz, 64QAM, 100% RB                       | LTE-FDD   | 6.58     | ±8.6                   |
| 10113 | CAH | 5.0 MHz, 64QAM, 100% RB                        | LTE-FDD   | 6.62     | ±8.6                   |
| 10114 | CAE | HT40 Greenfield, MCS0 (13.5 Mbps), 99.7% DC    | WLAN      | 6.10     | ±8.6                   |
| 10115 | CAE | HT40 Greenfield, MCS4 (81.0 Mbps), 99.7% DC    | WLAN      | 6.46     | ±8.6                   |
| 10116 | CAE | HT40 Greenfield, MCS7 (135.0 Mbps), 99.7% DC   | WLAN      | 6.15     | ±8.6                   |

Certificate No: EX-7907\_Jan26

Page 11 of 21

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                     | Group   | PAR (dB) | Unc <sup>1</sup> λ = 2 |
|-------|-----|-----------------------------------------------|---------|----------|------------------------|
| 10117 | CAE | HT40 Mixed, MCS6 (13.5 Mbps), 99.7% DC        | WLAN    | 8.07     | ±0.6                   |
| 10118 | CAE | HT40 Mixed, MCS4 (81.0 Mbps), 99.7% DC        | WLAN    | 8.59     | ±0.6                   |
| 10119 | CAE | HT40 Mixed, MCS7 (135.0 Mbps), 99.7% DC       | WLAN    | 8.73     | ±0.6                   |
| 10140 | CAF | 15.0 MHz, 16QAM, 100% RB                      | LTE-FDD | 6.49     | ±0.6                   |
| 10141 | CAF | 15.0 MHz, 64QAM, 100% RB                      | LTE-FDD | 6.63     | ±0.6                   |
| 10142 | CAF | 3.0 MHz, QPSK, 100% RB                        | LTE-FDD | 5.73     | ±0.6                   |
| 10143 | CAF | 3.0 MHz, 16QAM, 100% RB                       | LTE-FDD | 6.25     | ±0.6                   |
| 10144 | CAF | 3.0 MHz, 64QAM, 100% RB                       | LTE-FDD | 6.65     | ±0.6                   |
| 10145 | CAG | 1.4 MHz, QPSK, 100% RB                        | LTE-FDD | 5.76     | ±0.6                   |
| 10146 | CAG | 1.4 MHz, 16QAM, 100% RB                       | LTE-FDD | 6.47     | ±0.6                   |
| 10147 | CAG | 1.4 MHz, 64QAM, 100% RB                       | LTE-FDD | 6.72     | ±0.6                   |
| 10149 | CAF | 20.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.42     | ±0.6                   |
| 10150 | CAF | 20.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.60     | ±0.6                   |
| 10151 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB  | LTE-TDD | 9.26     | ±0.6                   |
| 10152 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB | LTE-TDD | 9.99     | ±0.6                   |
| 10153 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB | LTE-TDD | 10.06    | ±0.6                   |
| 10154 | CAH | 10.0 MHz, QPSK, 50% RB                        | LTE-FDD | 5.75     | ±0.6                   |
| 10155 | CAH | 10.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 5.43     | ±0.6                   |
| 10156 | CAH | 5.0 MHz, QPSK, 50% RB                         | LTE-FDD | 5.70     | ±0.6                   |
| 10157 | CAH | 5.0 MHz, 16QAM, 50% RB                        | LTE-FDD | 6.49     | ±0.6                   |
| 10158 | CAH | 10.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.62     | ±0.6                   |
| 10159 | CAH | 5.0 MHz, 64QAM, 50% RB                        | LTE-FDD | 6.55     | ±0.6                   |
| 10160 | CAF | 15.0 MHz, QPSK, 50% RB                        | LTE-FDD | 5.82     | ±0.6                   |
| 10161 | CAF | 15.0 MHz, 16QAM, 50% RB                       | LTE-FDD | 6.43     | ±0.6                   |
| 10162 | CAF | 15.0 MHz, 64QAM, 50% RB                       | LTE-FDD | 6.53     | ±0.6                   |
| 10166 | CAG | 1.4 MHz, QPSK, 50% RB                         | LTE-FDD | 5.45     | ±0.6                   |
| 10167 | CAG | 1.4 MHz, 16QAM, 50% RB                        | LTE-FDD | 6.21     | ±0.6                   |
| 10168 | CAG | 1.4 MHz, 64QAM, 50% RB                        | LTE-FDD | 6.70     | ±0.6                   |
| 10169 | CAF | 20.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.73     | ±0.6                   |
| 10170 | CAF | 20.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±0.6                   |
| 10171 | AAF | 20.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.40     | ±0.6                   |
| 10172 | CAH | 20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 8.21     | ±0.6                   |
| 10173 | CAH | 20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB   | LTE-TDD | 9.45     | ±0.6                   |
| 10174 | CAH | 20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB   | LTE-TDD | 10.25    | ±0.6                   |
| 10175 | CAH | 10.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.72     | ±0.6                   |
| 10176 | CAH | 10.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±0.6                   |
| 10177 | CAJ | 5.0 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±0.6                   |
| 10178 | CAH | 5.0 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.52     | ±0.6                   |
| 10179 | CAH | 10.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.53     | ±0.6                   |
| 10180 | CAH | 5.0 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.53     | ±0.6                   |
| 10181 | CAF | 15.0 MHz, QPSK, 1 RB                          | LTE-FDD | 5.72     | ±0.6                   |
| 10182 | CAF | 15.0 MHz, 16QAM, 1 RB                         | LTE-FDD | 6.52     | ±0.6                   |
| 10183 | AAE | 15.0 MHz, 64QAM, 1 RB                         | LTE-FDD | 6.50     | ±0.6                   |
| 10184 | CAF | 3.0 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±0.6                   |
| 10185 | CAF | 3.0 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.51     | ±0.6                   |
| 10186 | AAF | 3.0 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±0.6                   |
| 10187 | CAG | 1.4 MHz, QPSK, 1 RB                           | LTE-FDD | 5.73     | ±0.6                   |
| 10188 | CAG | 1.4 MHz, 16QAM, 1 RB                          | LTE-FDD | 6.52     | ±0.6                   |
| 10189 | AAG | 1.4 MHz, 64QAM, 1 RB                          | LTE-FDD | 6.50     | ±0.6                   |
| 10193 | CAE | HT20 Greenfield, MCS0 (3.5 Mbps), 99.4% DC    | WLAN    | 8.03     | ±0.6                   |
| 10194 | CAE | HT20 Greenfield, MCS4 (39.0 Mbps), 99.5% DC   | WLAN    | 8.72     | ±0.6                   |
| 10195 | CAE | HT20 Greenfield, MCS7 (55.0 Mbps), 99.5% DC   | WLAN    | 8.21     | ±0.6                   |
| 10196 | CAE | HT20 Mixed, MCS0 (3.5 Mbps), 99.4% DC         | WLAN    | 8.10     | ±0.6                   |
| 10197 | CAE | HT20 Mixed, MCS4 (39.0 Mbps), 99.5% DC        | WLAN    | 8.73     | ±0.6                   |
| 10198 | CAE | HT20 Mixed, MCS7 (55.0 Mbps), 99.5% DC        | WLAN    | 8.27     | ±0.6                   |
| 10219 | CAE | HT20 Mixed, MCS0 (3.5 Mbps), 99.3% DC         | WLAN    | 8.03     | ±0.6                   |
| 10220 | CAE | HT20 Mixed, MCS4 (39.0 Mbps), 99.4% DC        | WLAN    | 8.73     | ±0.6                   |
| 10221 | CAE | HT20 Mixed, MCS7 (55.0 Mbps), 99.4% DC        | WLAN    | 8.27     | ±0.6                   |
| 10222 | CAE | HT40 Mixed, MCS0 (3.5 Mbps), 99.7% DC         | WLAN    | 8.06     | ±0.6                   |
| 10223 | CAE | HT40 Mixed, MCS4 (39.0 Mbps), 99.7% DC        | WLAN    | 8.48     | ±0.6                   |
| 10224 | CAE | HT40 Mixed, MCS7 (55.0 Mbps), 99.7% DC        | WLAN    | 8.00     | ±0.6                   |
| 10226 | CAC | Rel. 7 HSPA+, 16QAM, 5.0 MHz                  | WCDMA   | 5.87     | ±0.6                   |
| 10228 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.48     | ±0.6                   |
| 10227 | CAC | 1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 10.26    | ±0.6                   |
| 10228 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB     | LTE-TDD | 9.22     | ±0.6                   |
| 10229 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB    | LTE-TDD | 9.48     | ±0.6                   |

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                                  | Group    | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|------------------------------------------------------------|----------|----------|------------------------|
| 10230 | CAE | 3.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 1 RB                 | LTE-TDD  | 10.25    | ±9.6                   |
| 10231 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB                  | LTE-TDD  | 9.19     | ±9.6                   |
| 10232 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB                 | LTE-TDD  | 9.45     | ±9.6                   |
| 10233 | CAH | 5.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 1 RB                 | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB                  | LTE-TDD  | 9.21     | ±9.6                   |
| 10235 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB                | LTE-TDD  | 9.45     | ±9.6                   |
| 10236 | CAH | 10.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 1 RB                | LTE-TDD  | 10.25    | ±9.6                   |
| 10237 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB                 | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB                | LTE-TDD  | 9.49     | ±9.6                   |
| 10239 | CAG | 15.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 1 RB                | LTE-TDD  | 10.25    | ±9.6                   |
| 10240 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB                 | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 9.82     | ±9.6                   |
| 10242 | CAC | 1.4 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 9.85     | ±9.6                   |
| 10243 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB                | LTE-TDD  | 9.48     | ±9.6                   |
| 10244 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 10.06    | ±9.6                   |
| 10245 | CAE | 3.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 10.06    | ±9.6                   |
| 10246 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB                | LTE-TDD  | 9.26     | ±9.6                   |
| 10247 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 9.87     | ±9.6                   |
| 10248 | CAH | 5.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB                | LTE-TDD  | 9.29     | ±9.6                   |
| 10250 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB              | LTE-TDD  | 9.81     | ±9.6                   |
| 10251 | CAH | 10.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 50% RB              | LTE-TDD  | 10.17    | ±9.6                   |
| 10252 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 9.24     | ±9.6                   |
| 10253 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB              | LTE-TDD  | 9.90     | ±9.6                   |
| 10254 | CAG | 15.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 50% RB              | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB               | LTE-TDD  | 9.20     | ±9.6                   |
| 10256 | CAC | 1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 9.95     | ±9.6                   |
| 10257 | CAC | 1.4 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 10.06    | ±9.6                   |
| 10258 | CAC | 1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB               | LTE-TDD  | 8.34     | ±9.6                   |
| 10259 | CAE | 3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 9.89     | ±9.6                   |
| 10260 | CAE | 3.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE | 3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB               | LTE-TDD  | 9.24     | ±9.6                   |
| 10262 | CAH | 5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 9.93     | ±9.6                   |
| 10263 | CAH | 5.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 10.18    | ±9.6                   |
| 10264 | CAH | 5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB               | LTE-TDD  | 9.29     | ±9.6                   |
| 10265 | CAH | 10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB             | LTE-TDD  | 9.82     | ±9.6                   |
| 10266 | CAH | 10.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 100% RB             | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CAH | 10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 9.30     | ±9.6                   |
| 10268 | CAG | 15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB             | LTE-TDD  | 10.06    | ±9.6                   |
| 10269 | CAG | 15.0 MHz, 84QAM, UL/DL CFG: 1, SSC: 4, 100% RB             | LTE-TDD  | 10.13    | ±9.6                   |
| 10270 | CAG | 15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB              | LTE-TDD  | 9.58     | ±9.6                   |
| 10274 | CAC | Rel. 8 HSURA Subcar 2, beta <sub>0</sub> 0, QPSK, 5.0 MHz  | WCDMA    | 4.87     | ±9.6                   |
| 10275 | CAC | Rel. 8 HSURA Subcar 2, beta <sub>0</sub> 15, QPSK, 5.0 MHz | WCDMA    | 3.86     | ±9.6                   |
| 10280 | AAB | RC1, SO55, Full frame rate, 1xRTT                          | CDMA2000 | 3.81     | ±9.6                   |
| 10281 | AAB | RC3, SO55, Full frame rate, 1xRTT                          | CDMA2000 | 3.46     | ±9.6                   |
| 10282 | AAB | RC3, SO32, Full frame rate, SCH0 disabled, 1xRTT           | CDMA2000 | 3.38     | ±9.6                   |
| 10283 | AAB | RC3, SO3, Full frame rate, 1xRTT                           | CDMA2000 | 3.50     | ±9.6                   |
| 10285 | AAB | RC3, SO3, 1/8 frame rate, 1xRTT                            | CDMA2000 | 12.48    | ±9.6                   |
| 10287 | AAF | 20.0 MHz, QPSK, 50% RB                                     | LTE-FDD  | 5.81     | ±9.6                   |
| 10288 | AAF | 3.0 MHz, QPSK, 50% RB                                      | LTE-FDD  | 5.72     | ±9.6                   |
| 10289 | AAF | 3.0 MHz, 16QAM, 50% RB                                     | LTE-FDD  | 8.39     | ±9.6                   |
| 10290 | AAF | 3.0 MHz, 84QAM, 50% RB                                     | LTE-FDD  | 8.53     | ±9.6                   |
| 10301 | AAA | PUSC, 28:18, QPSK, 5.0 ms, 18 TRAF SYM                     | WMAX     | 12.03    | ±9.6                   |
| 10302 | AAA | PUSC, 28:18, QPSK, 5.0 ms, 18 TRAF SYM                     | WMAX     | 12.57    | ±9.6                   |
| 10303 | AAA | PUSC, 31:15, 84QAM, 5.0 ms, 15 TRAF SYM                    | WMAX     | 12.52    | ±9.6                   |
| 10304 | AAA | PUSC, 28:18, 84QAM, 5.0 ms, 15 TRAF SYM                    | WMAX     | 11.95    | ±9.6                   |
| 10305 | AAA | PUSC, 31:15, 84QAM, 10.0 ms, 15 TRAF SYM                   | WMAX     | 15.24    | ±9.6                   |
| 10306 | AAA | PUSC, 28:18, 84QAM, 10.0 ms, 15 TRAF SYM                   | WMAX     | 14.87    | ±9.6                   |
| 10307 | AAA | PUSC, 28:18, QPSK, 10.0 ms, 18 TRAF SYM                    | WMAX     | 14.49    | ±9.6                   |
| 10308 | AAA | PUSC, 28:18, 16QAM, 10.0 ms, 18 TRAF SYM                   | WMAX     | 14.48    | ±9.6                   |
| 10309 | AAA | AMC 2x3, 28:18, 16QAM, 10.0 ms, 18 TRAF SYM                | WMAX     | 14.59    | ±9.6                   |
| 10310 | AAA | AMC 2x3, 28:18, QPSK, 10.0 ms, 18 TRAF SYM                 | WMAX     | 14.57    | ±9.6                   |
| 10311 | AAE | 15.0 MHz, QPSK, 100% RB                                    | LTE-FDD  | 6.08     | ±9.6                   |
| 10315 | AAB | DSSS, DBPSK, 1.0 Mbps, 99.9% DC                            | WLAN     | 1.71     | ±9.6                   |
| 10316 | AAB | OFDM, BPSK, 6.0 Mbps, 99.9% DC                             | WLAN     | 0.36     | ±9.6                   |
| 10317 | AAE | OFDM, BPSK, 6.0 Mbps, 99.9% DC                             | WLAN     | 0.36     | ±9.6                   |

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                                   | Group    | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|-------------------------------------------------------------|----------|----------|------------------------|
| 10352 | AAA | Pulse (D=10%, T=0 ms)                                       | Generic  | 10.00    | ±0.8                   |
| 10353 | AAA | Pulse (D=20%, T=0 ms)                                       | Generic  | 6.68     | ±0.8                   |
| 10354 | AAA | Pulse (D=10%, T=5 ms)                                       | Generic  | 3.58     | ±0.8                   |
| 10355 | AAA | Pulse (D=60%, T=5 ms)                                       | Generic  | 2.22     | ±0.8                   |
| 10356 | AAA | Pulse (D=60%, T=5 ms)                                       | Generic  | 0.97     | ±0.8                   |
| 10357 | AAA | Random (BW=1 MHz, MOD=QPSK)                                 | Generic  | 5.10     | ±0.8                   |
| 10358 | AAA | Random (BW=10 MHz, MOD=QPSK)                                | Generic  | 5.22     | ±0.8                   |
| 10359 | AAA | Random (BW=100 kHz, MOD=8QAM)                               | Generic  | 8.27     | ±0.8                   |
| 10359 | AAA | Random (BW=40 MHz, MOD=8QAM)                                | Generic  | 8.27     | ±0.8                   |
| 10400 | AAI | V-IT20, MCS5 (52.0 Mbps), 98.0% DC                          | WLAN     | 8.37     | ±0.8                   |
| 10401 | AAI | V-IT40, MCS5 (108.0 Mbps), 98.7% DC                         | WLAN     | 8.60     | ±0.8                   |
| 10402 | AAI | V-IT80, MCS5 (234.3 Mbps), 98.0% DC                         | WLAN     | 8.50     | ±0.8                   |
| 10403 | AAB | Rev. 0, 1xEV-DO                                             | CDMA2000 | 3.78     | ±0.8                   |
| 10404 | AAB | Rev. A, 1xEV-DO                                             | CDMA2000 | 3.77     | ±0.8                   |
| 10405 | AAB | RC3, SC32, Full frame rate, SCH0 enabled, 1xRTT             | CDMA2000 | 5.22     | ±0.8                   |
| 10410 | AAH | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 4, 1 RB                  | LTE-TDD  | 7.82     | ±0.8                   |
| 10414 | AAA | Random (BW=40 MHz, HIGH PAR)                                | Generic  | 8.54     | ±0.8                   |
| 10415 | AAA | DSSS, DBPSK, 1.0 Mbps, 98.8% DC                             | WLAN     | 1.54     | ±0.8                   |
| 10416 | AAA | OFDM, BPSK, 6.0 Mbps, 98.9% DC                              | WLAN     | 8.23     | ±0.8                   |
| 10417 | AAD | OFDM, BPSK, 6.0 Mbps, 98.8% DC                              | WLAN     | 8.23     | ±0.8                   |
| 10418 | AAA | OFDM (LTF), BPSK, 6.0 Mbps, 98.8% DC                        | WLAN     | 8.14     | ±0.8                   |
| 10418 | AAA | OFDM (STF), BPSK, 6.0 Mbps, 98.8% DC                        | WLAN     | 8.16     | ±0.8                   |
| 10422 | AAD | HT20 Greenfield, MCS6 (7.2 Mbps), 98.8% DC                  | WLAN     | 8.22     | ±0.8                   |
| 10423 | AAD | HT20 Greenfield, MCS4 (48.3 Mbps), 98.3% DC                 | WLAN     | 8.47     | ±0.8                   |
| 10424 | AAD | HT20 Greenfield, MCS7 (72.2 Mbps), 98.8% DC                 | WLAN     | 8.40     | ±0.8                   |
| 10425 | AAD | HT40 Greenfield, MCS6 (15.0 Mbps), 98.2% DC                 | WLAN     | 8.41     | ±0.8                   |
| 10426 | AAD | HT40 Greenfield, MCS4 (90.0 Mbps), 98.2% DC                 | WLAN     | 8.45     | ±0.8                   |
| 10427 | AAD | HT40 Greenfield, MCS7 (150.0 Mbps), 98.2% DC                | WLAN     | 8.41     | ±0.8                   |
| 10430 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 8.35     | ±0.8                   |
| 10431 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.38     | ±0.8                   |
| 10432 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±0.8                   |
| 10433 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 8.34     | ±0.8                   |
| 10434 | AAR | BS Test Model 1, 64 QPSK, 64QAM, 5.0 MHz (DL)               | WCDMA    | 8.60     | ±0.8                   |
| 10435 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.87     | ±0.8                   |
| 10447 | AAE | 5.0 MHz, 64-QAM, 100% RB                                    | LTE-FDD  | 7.58     | ±0.8                   |
| 10448 | AAE | 10.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.53     | ±0.8                   |
| 10449 | AAD | 15.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.51     | ±0.8                   |
| 10450 | AAD | 20.0 MHz, 64-QAM, 100% RB                                   | LTE-FDD  | 7.48     | ±0.8                   |
| 10451 | AAR | BS Test Model 1, 64 QPSK, Clipping 44%, 64QAM, 5.0 MHz (DL) | WCDMA    | 7.59     | ±0.8                   |
| 10455 | AAD | V-IT150, MCS5 (58.5 Mbps), 98.0% DC                         | WLAN     | 8.68     | ±0.8                   |
| 10457 | AAB | Rel. 5 DC-HSDPA, QPSK, 10.0 MHz                             | WCDMA    | 8.62     | ±0.8                   |
| 10458 | AAA | Rev. B, 2 carriers, 1xEV-DO                                 | CDMA2000 | 8.56     | ±0.8                   |
| 10459 | AAA | Rev. B, 3 carriers, 1xEV-DO                                 | CDMA2000 | 8.25     | ±0.8                   |
| 10460 | AAB | Rel. 10, AMR, QPSK, 5.0 MHz                                 | WCDMA    | 2.36     | ±0.8                   |
| 10461 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±0.8                   |
| 10462 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.30     | ±0.8                   |
| 10463 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.58     | ±0.8                   |
| 10464 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±0.8                   |
| 10465 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±0.8                   |
| 10466 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.57     | ±0.8                   |
| 10467 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                   | LTE-TDD  | 7.82     | ±0.8                   |
| 10468 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.32     | ±0.8                   |
| 10469 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 8.55     | ±0.8                   |
| 10470 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.82     | ±0.8                   |
| 10471 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±0.8                   |
| 10472 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±0.8                   |
| 10473 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB                  | LTE-TDD  | 7.92     | ±0.8                   |
| 10474 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±0.8                   |
| 10475 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±0.8                   |
| 10477 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.32     | ±0.8                   |
| 10478 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB                 | LTE-TDD  | 8.57     | ±0.8                   |
| 10479 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.74     | ±0.8                   |
| 10480 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.18     | ±0.8                   |
| 10481 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.45     | ±0.8                   |
| 10482 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB                 | LTE-TDD  | 7.71     | ±0.8                   |
| 10483 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB                | LTE-TDD  | 8.38     | ±0.8                   |

Certificate No: EX-7907\_Jan26

Page 14 of 21

EX3DV4 - SN:7907

January 23, 2020

| UID   | Rev | Communication System Name                      | Group   | PAR (dB) | Unc <sup>a</sup> k - 2 |
|-------|-----|------------------------------------------------|---------|----------|------------------------|
| 10484 | AAD | 5.0 MHz, 54QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.47     | ±0.5                   |
| 10485 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB    | LTE-TDD | 7.58     | ±0.5                   |
| 10486 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.38     | ±0.5                   |
| 10487 | AAG | 5.0 MHz, 54QAM, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 8.60     | ±0.5                   |
| 10488 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.70     | ±0.5                   |
| 10489 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.51     | ±0.5                   |
| 10490 | AAG | 10.0 MHz, 54QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | ±0.5                   |
| 10491 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | ±0.5                   |
| 10492 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.41     | ±0.5                   |
| 10493 | AAF | 15.0 MHz, 54QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.55     | ±0.5                   |
| 10494 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB   | LTE-TDD | 7.74     | ±0.5                   |
| 10495 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.37     | ±0.5                   |
| 10496 | AAG | 20.0 MHz, 54QAM, UL/DL CFG: 0, SSC: 7, 50% RB  | LTE-TDD | 8.54     | ±0.5                   |
| 10497 | AAC | 1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.57     | ±0.5                   |
| 10498 | AAC | 1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.40     | ±0.5                   |
| 10499 | AAC | 1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.55     | ±0.5                   |
| 10500 | AAD | 3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.57     | ±0.5                   |
| 10501 | AAD | 3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.44     | ±0.5                   |
| 10502 | AAD | 3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.52     | ±0.5                   |
| 10503 | AAG | 5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB   | LTE-TDD | 7.72     | ±0.5                   |
| 10504 | AAG | 5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.31     | ±0.5                   |
| 10505 | AAG | 5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 8.54     | ±0.5                   |
| 10506 | AAG | 10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | ±0.5                   |
| 10507 | AAG | 10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.35     | ±0.5                   |
| 10508 | AAG | 10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.55     | ±0.5                   |
| 10509 | AAF | 15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.90     | ±0.5                   |
| 10510 | AAF | 15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.40     | ±0.5                   |
| 10511 | AAF | 15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.51     | ±0.5                   |
| 10512 | AAG | 20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB  | LTE-TDD | 7.74     | ±0.5                   |
| 10513 | AAG | 20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.42     | ±0.5                   |
| 10514 | AAG | 20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB | LTE-TDD | 8.45     | ±0.5                   |
| 10515 | AAA | DSSS, DQPSK, 2.0 Mbps, 99.0% DC                | WLAN    | 1.58     | ±0.5                   |
| 10516 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 99.2% DC             | WLAN    | 1.57     | ±0.5                   |
| 10517 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 99.0% DC            | WLAN    | 1.58     | ±0.5                   |
| 10518 | AAD | OFDM, QPSK, 9.0 Mbps, 99.9% DC                 | WLAN    | 5.25     | ±0.5                   |
| 10519 | AAD | OFDM, QPSK, 12.0 Mbps, 99.0% DC                | WLAN    | 5.28     | ±0.5                   |
| 10520 | AAD | OFDM, QPSK, 15.0 Mbps, 99.0% DC                | WLAN    | 5.12     | ±0.5                   |
| 10521 | AAD | OFDM, 16QAM, 24.0 Mbps, 99.0% DC               | WLAN    | 7.57     | ±0.5                   |
| 10522 | AAD | OFDM, 16QAM, 36.0 Mbps, 99.0% DC               | WLAN    | 5.45     | ±0.5                   |
| 10523 | AAD | OFDM, 64QAM, 48.0 Mbps, 99.0% DC               | WLAN    | 5.08     | ±0.5                   |
| 10524 | AAD | OFDM, 64QAM, 54.0 Mbps, 99.0% DC               | WLAN    | 5.27     | ±0.5                   |
| 10525 | AAD | VHT20, MCS0 (6.5 Mbps), 99.0% DC               | WLAN    | 5.36     | ±0.5                   |
| 10526 | AAD | VHT20, MCS1 (13.0 Mbps), 99.0% DC              | WLAN    | 5.42     | ±0.5                   |
| 10527 | AAD | VHT20, MCS2 (19.5 Mbps), 99.0% DC              | WLAN    | 5.21     | ±0.5                   |
| 10528 | AAD | VHT20, MCS3 (26.0 Mbps), 99.0% DC              | WLAN    | 5.36     | ±0.5                   |
| 10529 | AAD | VHT20, MCS4 (33.0 Mbps), 99.0% DC              | WLAN    | 5.38     | ±0.5                   |
| 10531 | AAD | VHT20, MCS6 (58.5 Mbps), 99.0% DC              | WLAN    | 5.43     | ±0.5                   |
| 10532 | AAD | VHT20, MCS7 (65.0 Mbps), 99.0% DC              | WLAN    | 5.25     | ±0.5                   |
| 10533 | AAD | VHT20, MCS8 (78.0 Mbps), 99.0% DC              | WLAN    | 5.33     | ±0.5                   |
| 10534 | AAD | VHT40, MCS0 (13.5 Mbps), 98.8% DC              | WLAN    | 5.45     | ±0.5                   |
| 10535 | AAD | VHT40, MCS1 (27.0 Mbps), 98.8% DC              | WLAN    | 5.45     | ±0.5                   |
| 10536 | AAD | VHT40, MCS2 (40.5 Mbps), 98.8% DC              | WLAN    | 5.32     | ±0.5                   |
| 10537 | AAD | VHT40, MCS3 (54.0 Mbps), 98.7% DC              | WLAN    | 5.44     | ±0.5                   |
| 10538 | AAD | VHT40, MCS4 (67.0 Mbps), 98.8% DC              | WLAN    | 5.54     | ±0.5                   |
| 10540 | AAD | VHT40, MCS6 (121.5 Mbps), 98.3% DC             | WLAN    | 5.30     | ±0.5                   |
| 10541 | AAD | VHT40, MCS7 (135.0 Mbps), 98.2% DC             | WLAN    | 5.45     | ±0.5                   |
| 10542 | AAD | VHT40, MCS8 (162.0 Mbps), 98.1% DC             | WLAN    | 5.55     | ±0.5                   |
| 10543 | AAD | VHT80, MCS0 (100.0 Mbps), 98.0% DC             | WLAN    | 5.55     | ±0.5                   |
| 10544 | AAD | VHT80, MCS1 (200.0 Mbps), 99.0% DC             | WLAN    | 5.47     | ±0.5                   |
| 10545 | AAD | VHT80, MCS2 (300.0 Mbps), 99.0% DC             | WLAN    | 5.55     | ±0.5                   |
| 10546 | AAD | VHT80, MCS3 (400.0 Mbps), 99.0% DC             | WLAN    | 5.35     | ±0.5                   |
| 10547 | AAD | VHT80, MCS4 (500.0 Mbps), 99.0% DC             | WLAN    | 5.49     | ±0.5                   |
| 10548 | AAD | VHT80, MCS5 (600.0 Mbps), 99.0% DC             | WLAN    | 5.37     | ±0.5                   |
| 10550 | AAD | VHT80, MCS6 (800.0 Mbps), 99.0% DC             | WLAN    | 5.35     | ±0.5                   |
| 10551 | AAD | VHT80, MCS7 (1000.0 Mbps), 99.0% DC            | WLAN    | 5.50     | ±0.5                   |
| 10552 | AAD | VHT80, MCS8 (1200.0 Mbps), 99.0% DC            | WLAN    | 5.42     | ±0.5                   |

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name               | Group | PAR (dB) | Unc <sup>F</sup> k = 2 |
|-------|-----|-----------------------------------------|-------|----------|------------------------|
| 10553 | AA0 | VHT90, MCS9 (300.0 Mbps), 99.0% DC      | WLAN  | 8.46     | +9.5                   |
| 10554 | AAE | VHT160, MCS9 (58.5 Mbps), 99.0% DC      | WLAN  | 8.46     | +9.5                   |
| 10555 | AAE | VHT160, MCS1 (117.0 Mbps), 99.0% DC     | WLAN  | 8.47     | +9.5                   |
| 10556 | AAE | VHT160, MCS2 (175.5 Mbps), 99.0% DC     | WLAN  | 8.50     | +9.5                   |
| 10557 | AAE | VHT160, MCS3 (234.0 Mbps), 99.0% DC     | WLAN  | 8.52     | +9.5                   |
| 10558 | AAE | VHT160, MCS4 (351.0 Mbps), 99.0% DC     | WLAN  | 8.51     | +9.5                   |
| 10560 | AAE | VHT160, MCS5 (526.5 Mbps), 99.0% DC     | WLAN  | 8.73     | +9.5                   |
| 10561 | AAE | VHT160, MCS7 (885.0 Mbps), 99.0% DC     | WLAN  | 8.56     | +9.5                   |
| 10562 | AAE | VHT160, MCS8 (102.0 Mbps), 99.0% DC     | WLAN  | 8.59     | +9.5                   |
| 10563 | AAE | VHT160, MCS9 (178.0 Mbps), 99.0% DC     | WLAN  | 8.77     | +9.5                   |
| 10564 | AAA | OFDM, BPSK, 9.0 Mbps, 99.9% DC          | WLAN  | 8.25     | +9.5                   |
| 10565 | AAA | OFDM, QPSK, 12.0 Mbps, 99.0% DC         | WLAN  | 8.45     | +9.5                   |
| 10566 | AAA | OFDM, QPSK, 18.0 Mbps, 99.0% DC         | WLAN  | 8.13     | +9.5                   |
| 10567 | AAA | OFDM, 16QAM, 24.0 Mbps, 99.0% DC        | WLAN  | 8.00     | +9.5                   |
| 10568 | AAA | OFDM, 16QAM, 36.0 Mbps, 99.0% DC        | WLAN  | 8.97     | +9.5                   |
| 10569 | AAA | OFDM, 64QAM, 48.0 Mbps, 99.0% DC        | WLAN  | 8.10     | +9.5                   |
| 10570 | AAA | OFDM, 64QAM, 54.0 Mbps, 99.0% DC        | WLAN  | 8.80     | +9.5                   |
| 10571 | AAA | DSSS, DQPSK, 1.0 Mbps, 90.0% DC         | WLAN  | 1.99     | +9.5                   |
| 10572 | AAA | DSSS, DQPSK, 2.0 Mbps, 90.0% DC         | WLAN  | 1.99     | +9.5                   |
| 10573 | AAA | HR-DSSS, DQPSK, 5.5 Mbps, 90.1% DC      | WLAN  | 1.96     | +9.5                   |
| 10574 | AAA | HR-DSSS, DQPSK, 11.0 Mbps, 90.3% DC     | WLAN  | 1.96     | +9.5                   |
| 10575 | AAA | OFDM, BPSK, 5.0 Mbps, 99.9% DC          | WLAN  | 5.59     | +9.5                   |
| 10576 | AAA | OFDM, BPSK, 9.0 Mbps, 99.9% DC          | WLAN  | 5.60     | +9.5                   |
| 10577 | AAA | OFDM, QPSK, 12.0 Mbps, 90.0% DC         | WLAN  | 5.70     | +9.5                   |
| 10578 | AAA | OFDM, QPSK, 18.0 Mbps, 90.0% DC         | WLAN  | 5.49     | +9.5                   |
| 10579 | AAA | OFDM, 16QAM, 24.0 Mbps, 90.0% DC        | WLAN  | 5.35     | +9.5                   |
| 10580 | AAA | OFDM, 16QAM, 36.0 Mbps, 90.0% DC        | WLAN  | 5.75     | +9.5                   |
| 10581 | AAA | OFDM, 64QAM, 48.0 Mbps, 90.0% DC        | WLAN  | 5.33     | +9.5                   |
| 10582 | AAA | OFDM, 64QAM, 54.0 Mbps, 90.0% DC        | WLAN  | 5.57     | +9.5                   |
| 10583 | AAD | OFDM, BPSK, 5.0 Mbps, 99.9% DC          | WLAN  | 5.59     | +9.5                   |
| 10584 | AAD | OFDM, BPSK, 9.0 Mbps, 99.9% DC          | WLAN  | 5.60     | +9.5                   |
| 10585 | AAD | OFDM, QPSK, 12.0 Mbps, 90.0% DC         | WLAN  | 5.70     | +9.5                   |
| 10586 | AAD | OFDM, QPSK, 18.0 Mbps, 90.0% DC         | WLAN  | 5.49     | +9.5                   |
| 10587 | AAD | OFDM, 16QAM, 24.0 Mbps, 90.0% DC        | WLAN  | 5.35     | +9.5                   |
| 10588 | AAD | OFDM, 16QAM, 36.0 Mbps, 90.0% DC        | WLAN  | 5.76     | +9.5                   |
| 10589 | AAD | OFDM, 64QAM, 48.0 Mbps, 90.0% DC        | WLAN  | 5.35     | +9.5                   |
| 10590 | AAD | OFDM, 64QAM, 54.0 Mbps, 90.0% DC        | WLAN  | 5.67     | +9.5                   |
| 10591 | AAD | HT20 Mixed, MCS9 (6.5 Mbps), 99.9% DC   | WLAN  | 5.63     | +9.5                   |
| 10592 | AAD | HT20 Mixed, MCS1 (13.0 Mbps), 90.0% DC  | WLAN  | 5.79     | +9.5                   |
| 10593 | AAD | HT20 Mixed, MCS2 (19.5 Mbps), 90.0% DC  | WLAN  | 5.64     | +9.5                   |
| 10594 | AAD | HT20 Mixed, MCS3 (26.0 Mbps), 90.0% DC  | WLAN  | 5.74     | +9.5                   |
| 10595 | AAD | HT20 Mixed, MCS4 (39.0 Mbps), 90.0% DC  | WLAN  | 5.74     | +9.5                   |
| 10596 | AAD | HT20 Mixed, MCS5 (52.0 Mbps), 90.0% DC  | WLAN  | 5.71     | +9.5                   |
| 10597 | AAD | HT20 Mixed, MCS6 (68.5 Mbps), 90.0% DC  | WLAN  | 5.72     | +9.5                   |
| 10598 | AAD | HT20 Mixed, MCS7 (85.0 Mbps), 90.0% DC  | WLAN  | 5.50     | +9.5                   |
| 10599 | AAD | HT40 Mixed, MCS0 (13.5 Mbps), 99.9% DC  | WLAN  | 5.79     | +9.5                   |
| 10600 | AAD | HT40 Mixed, MCS1 (27.0 Mbps), 99.7% DC  | WLAN  | 5.85     | +9.5                   |
| 10601 | AAD | HT40 Mixed, MCS2 (40.5 Mbps), 99.6% DC  | WLAN  | 5.92     | +9.5                   |
| 10602 | AAD | HT40 Mixed, MCS3 (54.0 Mbps), 99.4% DC  | WLAN  | 5.94     | +9.5                   |
| 10603 | AAD | HT40 Mixed, MCS4 (81.0 Mbps), 99.2% DC  | WLAN  | 5.93     | +9.5                   |
| 10604 | AAD | HT40 Mixed, MCS5 (108.0 Mbps), 99.9% DC | WLAN  | 5.75     | +9.5                   |
| 10605 | AAD | HT40 Mixed, MCS6 (121.5 Mbps), 99.2% DC | WLAN  | 5.97     | +9.5                   |
| 10606 | AAD | HT40 Mixed, MCS7 (135.0 Mbps), 99.7% DC | WLAN  | 5.92     | +9.5                   |
| 10607 | AAD | VHT20, MCS0 (5.0 Mbps), 99.9% DC        | WLAN  | 5.64     | +9.5                   |
| 10608 | AAD | VHT20, MCS1 (13.0 Mbps), 90.0% DC       | WLAN  | 5.77     | +9.5                   |
| 10609 | AAD | VHT20, MCS2 (19.5 Mbps), 90.0% DC       | WLAN  | 5.67     | +9.5                   |
| 10610 | AAD | VHT20, MCS3 (29.0 Mbps), 90.0% DC       | WLAN  | 5.78     | +9.5                   |
| 10611 | AAD | VHT20, MCS4 (39.0 Mbps), 90.0% DC       | WLAN  | 5.70     | +9.5                   |
| 10612 | AAD | VHT20, MCS5 (52.0 Mbps), 90.0% DC       | WLAN  | 5.77     | +9.5                   |
| 10613 | AAD | VHT20, MCS6 (68.5 Mbps), 90.0% DC       | WLAN  | 5.54     | +9.5                   |
| 10614 | AAD | VHT20, MCS7 (85.0 Mbps), 90.0% DC       | WLAN  | 5.65     | +9.5                   |
| 10615 | AAD | VHT20, MCS8 (78.0 Mbps), 90.0% DC       | WLAN  | 5.82     | +9.5                   |
| 10616 | AAD | VHT40, MCS0 (13.5 Mbps), 99.9% DC       | WLAN  | 5.82     | +9.5                   |
| 10617 | AAD | VHT40, MCS1 (27.0 Mbps), 99.7% DC       | WLAN  | 5.81     | +9.5                   |
| 10618 | AAD | VHT40, MCS2 (40.5 Mbps), 99.6% DC       | WLAN  | 5.58     | +9.5                   |
| 10619 | AAD | VHT40, MCS3 (54.0 Mbps), 99.4% DC       | WLAN  | 5.85     | +9.5                   |

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                   | Group     | PAR (dB) | Unc <sup>®</sup> k = 2 |
|-------|-----|---------------------------------------------|-----------|----------|------------------------|
| 10620 | AAD | VHT40, MCS4 (81.0 Mbps), 88.2% DC           | WLAN      | 8.57     | +9.6                   |
| 10621 | AAD | VHT40, MCS5 (108.0 Mbps), 88.9% DC          | WLAN      | 8.77     | +9.6                   |
| 10622 | AAD | VHT40, MCS6 (121.5 Mbps), 88.0% DC          | WLAN      | 9.58     | +9.6                   |
| 10623 | AAD | VHT40, MCS7 (136.0 Mbps), 88.6% DC          | WLAN      | 9.52     | +9.6                   |
| 10624 | AAD | VHT40, MCS8 (162.0 Mbps), 88.4% DC          | WLAN      | 9.90     | +9.6                   |
| 10625 | AAD | VHT40, MCS9 (180.0 Mbps), 88.2% DC          | WLAN      | 9.90     | +9.6                   |
| 10626 | AAD | VHT80, MCS0 (29.2 Mbps), 90.0% DC           | WLAN      | 8.80     | +9.6                   |
| 10627 | AAD | VHT80, MCS1 (38.5 Mbps), 90.0% DC           | WLAN      | 8.88     | +9.6                   |
| 10628 | AAD | VHT80, MCS2 (57.8 Mbps), 90.0% DC           | WLAN      | 8.71     | +9.6                   |
| 10629 | AAD | VHT80, MCS3 (117.0 Mbps), 90.0% DC          | WLAN      | 8.85     | +9.6                   |
| 10630 | AAD | VHT80, MCS4 (175.5 Mbps), 90.0% DC          | WLAN      | 8.72     | +9.6                   |
| 10631 | AAD | VHT80, MCS5 (234.0 Mbps), 90.0% DC          | WLAN      | 8.81     | +9.6                   |
| 10632 | AAD | VHT80, MCS6 (293.0 Mbps), 90.0% DC          | WLAN      | 8.74     | +9.6                   |
| 10633 | AAD | VHT80, MCS7 (352.5 Mbps), 90.0% DC          | WLAN      | 8.83     | +9.6                   |
| 10634 | AAD | VHT80, MCS8 (411.0 Mbps), 90.0% DC          | WLAN      | 8.80     | +9.6                   |
| 10635 | AAD | VHT80, MCS9 (470.0 Mbps), 90.0% DC          | WLAN      | 8.81     | +9.6                   |
| 10636 | AAE | VHT160, MCS0 (58.5 Mbps), 80.0% DC          | WLAN      | 8.83     | +9.6                   |
| 10637 | AAE | VHT160, MCS1 (117.0 Mbps), 80.0% DC         | WLAN      | 8.79     | +9.6                   |
| 10638 | AAE | VHT160, MCS2 (175.5 Mbps), 80.0% DC         | WLAN      | 8.86     | +9.6                   |
| 10639 | AAE | VHT160, MCS3 (234.0 Mbps), 80.0% DC         | WLAN      | 8.85     | +9.6                   |
| 10640 | AAE | VHT160, MCS4 (351.0 Mbps), 80.0% DC         | WLAN      | 8.96     | +9.6                   |
| 10641 | AAE | VHT160, MCS5 (489.0 Mbps), 80.0% DC         | WLAN      | 9.06     | +9.6                   |
| 10642 | AAE | VHT160, MCS6 (528.5 Mbps), 80.0% DC         | WLAN      | 9.06     | +9.6                   |
| 10643 | AAE | VHT160, MCS7 (585.0 Mbps), 80.0% DC         | WLAN      | 8.89     | +9.6                   |
| 10644 | AAE | VHT160, MCS8 (702.0 Mbps), 80.0% DC         | WLAN      | 9.00     | +9.6                   |
| 10645 | AAE | VHT160, MCS9 (780.0 Mbps), 80.0% DC         | WLAN      | 9.11     | +9.6                   |
| 10646 | AAH | 5.0 MHz, QPSK, L1/31, CFI: 2, SBC: 4, 1 RB  | LTE-TDD   | 11.93    | +9.6                   |
| 10647 | AAG | 20.0 MHz, QPSK, L1/31, CFI: 2, SBC: 7, 1 RB | LTE-TDD   | 11.93    | +9.6                   |
| 10648 | AAA | RCR, SOFS, "xAdvanced"                      | CDMA2000  | 3.45     | +9.6                   |
| 10649 | AAA | LE, "test, QPSK"                            | Bluetooth | 2.19     | +9.6                   |
| 10671 | AAC | ET20, MCS0 (8.8 Mbps), 90.0% DC             | WLAN      | 9.09     | +9.6                   |
| 10672 | AAC | ET20, MCS1 (17.0 Mbps), 90.0% DC            | WLAN      | 8.57     | +9.6                   |
| 10673 | AAC | ET20, MCS2 (28.0 Mbps), 90.0% DC            | WLAN      | 8.79     | +9.6                   |
| 10674 | AAC | ET20, MCS3 (34.0 Mbps), 90.0% DC            | WLAN      | 8.74     | +9.6                   |
| 10675 | AAC | ET20, MCS4 (52.0 Mbps), 90.0% DC            | WLAN      | 8.89     | +9.6                   |
| 10676 | AAC | ET20, MCS5 (68.0 Mbps), 90.0% DC            | WLAN      | 8.77     | +9.6                   |
| 10677 | AAC | ET20, MCS6 (77.0 Mbps), 90.0% DC            | WLAN      | 8.73     | +9.6                   |
| 10678 | AAC | ET20, MCS7 (86.0 Mbps), 90.0% DC            | WLAN      | 8.70     | +9.6                   |
| 10679 | AAC | ET20, MCS8 (103.0 Mbps), 90.0% DC           | WLAN      | 8.88     | +9.6                   |
| 10680 | AAC | ET20, MCS9 (115.0 Mbps), 90.0% DC           | WLAN      | 8.80     | +9.6                   |
| 10681 | AAC | ET20, MCS10 (122.0 Mbps), 90.0% DC          | WLAN      | 8.82     | +9.6                   |
| 10682 | AAC | ET20, MCS11 (135.0 Mbps), 90.0% DC          | WLAN      | 8.83     | +9.6                   |
| 10683 | AAC | ET20, MCS0 (8.8 Mbps), 100.0% DC            | WLAN      | 8.42     | +9.6                   |
| 10684 | AAC | ET20, MCS1 (17.0 Mbps), 100.0% DC           | WLAN      | 8.26     | +9.6                   |
| 10685 | AAC | ET20, MCS2 (28.0 Mbps), 100.0% DC           | WLAN      | 8.33     | +9.6                   |
| 10686 | AAC | ET20, MCS3 (34.0 Mbps), 100.0% DC           | WLAN      | 8.28     | +9.6                   |
| 10687 | AAC | ET20, MCS4 (52.0 Mbps), 100.0% DC           | WLAN      | 8.46     | +9.6                   |
| 10688 | AAC | ET20, MCS5 (68.0 Mbps), 100.0% DC           | WLAN      | 8.28     | +9.6                   |
| 10689 | AAC | ET20, MCS6 (77.0 Mbps), 100.0% DC           | WLAN      | 8.55     | +9.6                   |
| 10690 | AAC | ET20, MCS7 (86.0 Mbps), 100.0% DC           | WLAN      | 8.28     | +9.6                   |
| 10691 | AAC | ET20, MCS8 (103.0 Mbps), 100.0% DC          | WLAN      | 8.25     | +9.6                   |
| 10692 | AAC | ET20, MCS9 (115.0 Mbps), 100.0% DC          | WLAN      | 8.25     | +9.6                   |
| 10693 | AAC | ET20, MCS10 (122.0 Mbps), 100.0% DC         | WLAN      | 8.25     | +9.6                   |
| 10694 | AAC | ET20, MCS11 (135.0 Mbps), 100.0% DC         | WLAN      | 8.57     | +9.6                   |
| 10695 | AAC | ET40, MCS0 (17.2 Mbps), 89.8% DC            | WLAN      | 9.75     | +9.6                   |
| 10696 | AAC | ET40, MCS1 (34.0 Mbps), 89.8% DC            | WLAN      | 9.91     | +9.6                   |
| 10697 | AAC | ET40, MCS2 (52.0 Mbps), 89.7% DC            | WLAN      | 9.31     | +9.6                   |
| 10698 | AAC | ET40, MCS3 (68.0 Mbps), 89.7% DC            | WLAN      | 9.89     | +9.6                   |
| 10699 | AAC | ET40, MCS4 (103.0 Mbps), 89.9% DC           | WLAN      | 10.02    | +9.6                   |
| 10700 | AAC | ET40, MCS5 (138.0 Mbps), 89.8% DC           | WLAN      | 9.73     | +9.6                   |
| 10701 | AAC | ET40, MCS6 (155.0 Mbps), 89.8% DC           | WLAN      | 9.85     | +9.6                   |
| 10702 | AAC | ET40, MCS7 (172.0 Mbps), 89.8% DC           | WLAN      | 9.79     | +9.6                   |
| 10703 | AAC | ET40, MCS8 (207.0 Mbps), 89.8% DC           | WLAN      | 9.82     | +9.6                   |
| 10704 | AAC | ET40, MCS9 (229.0 Mbps), 89.8% DC           | WLAN      | 9.55     | +9.6                   |
| 10705 | AAC | ET40, MCS10 (258.0 Mbps), 89.8% DC          | WLAN      | 9.69     | +9.6                   |
| 10706 | AAC | ET40, MCS11 (267.0 Mbps), 89.8% DC          | WLAN      | 9.86     | +9.6                   |

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                         | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|---------------------------------------------------|---------------|----------|------------------------|
| 10707 | AAC | ET40, MCS0 (17.2 Mbps), 89.8% DC                  | WLAN          | 8.32     | ±9.5                   |
| 10708 | AAC | ET40, MCS1 (34.0 Mbps), 89.7% DC                  | WLAN          | 8.55     | ±9.5                   |
| 10709 | AAC | ET40, MCS2 (52.0 Mbps), 89.7% DC                  | WLAN          | 8.82     | ±9.5                   |
| 10710 | AAC | ET40, MCS3 (69.0 Mbps), 89.7% DC                  | WLAN          | 8.25     | ±9.5                   |
| 10711 | AAC | ET40, MCS4 (103.0 Mbps), 89.8% DC                 | WLAN          | 8.55     | ±9.5                   |
| 10712 | AAC | ET40, MCS5 (138.0 Mbps), 89.8% DC                 | WLAN          | 8.87     | ±9.5                   |
| 10713 | AAC | ET40, MCS6 (155.0 Mbps), 89.8% DC                 | WLAN          | 8.33     | ±9.5                   |
| 10714 | AAC | ET40, MCS7 (172.0 Mbps), 89.8% DC                 | WLAN          | 8.25     | ±9.5                   |
| 10715 | AAC | ET40, MCS8 (207.0 Mbps), 89.8% DC                 | WLAN          | 8.45     | ±9.5                   |
| 10716 | AAC | ET40, MCS9 (229.0 Mbps), 89.8% DC                 | WLAN          | 8.30     | ±9.5                   |
| 10717 | AAC | ET40, MCS10 (256.0 Mbps), 89.8% DC                | WLAN          | 8.48     | ±9.5                   |
| 10718 | AAC | ET40, MCS11 (267.0 Mbps), 89.8% DC                | WLAN          | 8.24     | ±9.5                   |
| 10719 | AAC | ET80, MCS0 (36.0 Mbps), 90.0% DC                  | WLAN          | 8.81     | ±9.5                   |
| 10720 | AAC | ET80, MCS1 (72.1 Mbps), 90.0% DC                  | WLAN          | 8.87     | ±9.5                   |
| 10721 | AAC | ET80, MCS2 (108.1 Mbps), 90.0% DC                 | WLAN          | 8.75     | ±9.5                   |
| 10722 | AAC | ET80, MCS3 (144.1 Mbps), 90.0% DC                 | WLAN          | 8.55     | ±9.5                   |
| 10723 | AAC | ET80, MCS4 (216.2 Mbps), 90.0% DC                 | WLAN          | 8.70     | ±9.5                   |
| 10724 | AAC | ET80, MCS5 (288.2 Mbps), 90.0% DC                 | WLAN          | 8.50     | ±9.5                   |
| 10725 | AAC | ET80, MCS6 (324.4 Mbps), 90.0% DC                 | WLAN          | 8.74     | ±9.5                   |
| 10726 | AAC | ET80, MCS7 (360.3 Mbps), 90.0% DC                 | WLAN          | 8.72     | ±9.5                   |
| 10727 | AAC | ET80, MCS8 (432.4 Mbps), 90.0% DC                 | WLAN          | 8.66     | ±9.5                   |
| 10728 | AAC | ET80, MCS9 (480.4 Mbps), 90.0% DC                 | WLAN          | 8.85     | ±9.5                   |
| 10729 | AAC | ET80, MCS10 (540.4 Mbps), 90.0% DC                | WLAN          | 8.64     | ±9.5                   |
| 10730 | AAC | ET80, MCS11 (720.0 Mbps), 90.0% DC                | WLAN          | 8.67     | ±9.5                   |
| 10731 | AAC | ET80, MCS0 (36.0 Mbps), 100.0% DC                 | WLAN          | 8.42     | ±9.5                   |
| 10732 | AAC | ET80, MCS1 (72.1 Mbps), 100.0% DC                 | WLAN          | 8.45     | ±9.5                   |
| 10733 | AAC | ET80, MCS2 (108.1 Mbps), 100.0% DC                | WLAN          | 8.40     | ±9.5                   |
| 10734 | AAC | ET80, MCS3 (144.1 Mbps), 100.0% DC                | WLAN          | 8.25     | ±9.5                   |
| 10735 | AAC | ET80, MCS4 (216.2 Mbps), 100.0% DC                | WLAN          | 8.33     | ±9.5                   |
| 10736 | AAC | ET80, MCS5 (288.2 Mbps), 100.0% DC                | WLAN          | 8.27     | ±9.5                   |
| 10737 | AAC | ET80, MCS6 (324.4 Mbps), 100.0% DC                | WLAN          | 8.35     | ±9.5                   |
| 10738 | AAC | ET80, MCS7 (360.3 Mbps), 100.0% DC                | WLAN          | 8.42     | ±9.5                   |
| 10739 | AAC | ET80, MCS8 (432.4 Mbps), 100.0% DC                | WLAN          | 8.29     | ±9.5                   |
| 10740 | AAC | ET80, MCS9 (480.4 Mbps), 100.0% DC                | WLAN          | 8.48     | ±9.5                   |
| 10741 | AAC | ET80, MCS10 (540.4 Mbps), 100.0% DC               | WLAN          | 8.40     | ±9.5                   |
| 10742 | AAC | ET80, MCS11 (600.5 Mbps), 100.0% DC               | WLAN          | 8.48     | ±9.5                   |
| 10743 | AAC | ET160, MCS0 (72.0 Mbps), 88.2% DC                 | WLAN          | 8.94     | ±9.5                   |
| 10744 | AAC | ET160, MCS1 (144.0 Mbps), 87.1% DC                | WLAN          | 9.16     | ±9.5                   |
| 10745 | AAC | ET160, MCS2 (216.0 Mbps), 87.4% DC                | WLAN          | 8.98     | ±9.5                   |
| 10746 | AAC | ET160, MCS3 (288.0 Mbps), 87.1% DC                | WLAN          | 9.11     | ±9.5                   |
| 10747 | AAC | ET160, MCS4 (432.0 Mbps), 87.4% DC                | WLAN          | 9.04     | ±9.5                   |
| 10748 | AAC | ET160, MCS5 (576.0 Mbps), 86.8% DC                | WLAN          | 8.93     | ±9.5                   |
| 10749 | AAC | ET160, MCS6 (648.0 Mbps), 86.7% DC                | WLAN          | 8.90     | ±9.5                   |
| 10750 | AAC | ET160, MCS7 (720.0 Mbps), 86.7% DC                | WLAN          | 8.79     | ±9.5                   |
| 10751 | AAC | ET160, MCS8 (866.0 Mbps), 86.3% DC                | WLAN          | 8.82     | ±9.5                   |
| 10752 | AAC | ET160, MCS9 (961.0 Mbps), 86.3% DC                | WLAN          | 8.81     | ±9.5                   |
| 10753 | AAC | ET160, MCS10 (1081.0 Mbps), 86.7% DC              | WLAN          | 8.39     | ±9.5                   |
| 10754 | AAC | ET160, MCS11 (1201.0 Mbps), 86.7% DC              | WLAN          | 8.94     | ±9.5                   |
| 10755 | AAC | ET160, MCS0 (72.0 Mbps), 99.0% DC                 | WLAN          | 8.54     | ±9.5                   |
| 10756 | AAC | ET160, MCS1 (144.0 Mbps), 99.0% DC                | WLAN          | 8.77     | ±9.5                   |
| 10757 | AAC | ET160, MCS2 (216.0 Mbps), 97.1% DC                | WLAN          | 8.77     | ±9.5                   |
| 10758 | AAC | ET160, MCS3 (288.0 Mbps), 96.8% DC                | WLAN          | 8.59     | ±9.5                   |
| 10759 | AAC | ET160, MCS4 (432.0 Mbps), 97.1% DC                | WLAN          | 8.58     | ±9.5                   |
| 10760 | AAC | ET160, MCS5 (576.0 Mbps), 95.9% DC                | WLAN          | 8.49     | ±9.5                   |
| 10761 | AAC | ET160, MCS6 (648.0 Mbps), 95.3% DC                | WLAN          | 8.58     | ±9.5                   |
| 10762 | AAC | ET160, MCS7 (720.0 Mbps), 95.3% DC                | WLAN          | 8.49     | ±9.5                   |
| 10763 | AAC | ET160, MCS8 (866.0 Mbps), 95.3% DC                | WLAN          | 8.53     | ±9.5                   |
| 10764 | AAC | ET160, MCS9 (961.0 Mbps), 95.3% DC                | WLAN          | 8.54     | ±9.5                   |
| 10765 | AAC | ET160, MCS10 (1081.0 Mbps), 95.3% DC              | WLAN          | 8.54     | ±9.5                   |
| 10766 | AAC | ET160, MCS11 (1201.0 Mbps), 95.3% DC              | WLAN          | 8.51     | ±9.5                   |
| 10767 | AAC | CP-OFDM, 5.0 MHz, QPSK, 15 k-hz, 99.9% DC, 1 RB   | SG NR FR1 TDD | 7.55     | ±9.5                   |
| 10768 | AAC | CP-OFDM, 10.0 MHz, QPSK, 15 k-hz, 100.0% DC, 1 RB | SG NR FR1 TDD | 8.01     | ±9.5                   |
| 10769 | AAC | CP-OFDM, 15.0 MHz, QPSK, 15 k-hz, 100.0% DC, 1 RB | SG NR FR1 TDD | 8.01     | ±9.5                   |
| 10770 | AAC | CP-OFDM, 20.0 MHz, QPSK, 15 k-hz, 100.0% DC, 1 RB | SG NR FR1 TDD | 8.02     | ±9.5                   |
| 10771 | AAC | CP-OFDM, 25.0 MHz, QPSK, 15 k-hz, 100.0% DC, 1 RB | SG NR FR1 TDD | 8.02     | ±9.5                   |
| 10772 | AAC | CP-OFDM, 30.0 MHz, QPSK, 15 k-hz, 100.0% DC, 1 RB | SG NR FR1 TDD | 8.23     | ±9.5                   |

Certificate No: EX-7907\_Jan26

Page 18 of 21

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                            | Group         | PAR (dB) | Unc <sup>E</sup> $k = 2$ |
|-------|-----|------------------------------------------------------|---------------|----------|--------------------------|
| 10773 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 8.93     | ±0.6                     |
| 10774 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 8.92     | ±0.6                     |
| 10775 | AAF | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB    | SG NR FR1 TDD | 8.91     | ±0.6                     |
| 10776 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.90     | ±0.6                     |
| 10777 | AAE | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.90     | ±0.6                     |
| 10778 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.94     | ±0.6                     |
| 10779 | AAE | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.45     | ±0.6                     |
| 10780 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.58     | ±0.6                     |
| 10781 | AAE | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.56     | ±0.6                     |
| 10782 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.45     | ±0.6                     |
| 10793 | AAE | CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB   | SG NR FR1 TDD | 8.31     | ±0.6                     |
| 10794 | AAE | CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.29     | ±0.6                     |
| 10795 | AAE | CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.45     | ±0.6                     |
| 10796 | AAE | CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10797 | AAE | CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.44     | ±0.6                     |
| 10798 | AAE | CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.39     | ±0.6                     |
| 10799 | AAF | CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.37     | ±0.6                     |
| 10790 | AAE | CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10791 | AAE | CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB       | SG NR FR1 TDD | 7.83     | ±0.6                     |
| 10792 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB      | SG NR FR1 TDD | 7.82     | ±0.6                     |
| 10793 | AAE | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.85     | ±0.6                     |
| 10794 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.82     | ±0.6                     |
| 10795 | AAE | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.84     | ±0.6                     |
| 10796 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.82     | ±0.6                     |
| 10797 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 8.01     | ±0.6                     |
| 10798 | AAF | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.89     | ±0.6                     |
| 10799 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.93     | ±0.6                     |
| 10800 | AAF | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.89     | ±0.6                     |
| 10801 | AAF | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.87     | ±0.6                     |
| 10802 | AAF | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB    | SG NR FR1 TDD | 7.87     | ±0.6                     |
| 10803 | AAF | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10804 | AAE | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.37     | ±0.6                     |
| 10805 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10806 | AAE | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10807 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10808 | AAE | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10809 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10810 | AAE | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10811 | AAE | CP-OFDM, 70.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10812 | AAE | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10813 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10814 | AAE | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB  | SG NR FR1 TDD | 8.33     | ±0.6                     |
| 10815 | AAE | CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.20     | ±0.6                     |
| 10816 | AAE | CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.41     | ±0.6                     |
| 10817 | AAE | CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.41     | ±0.6                     |
| 10818 | AAE | CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.36     | ±0.6                     |
| 10819 | AAE | CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.36     | ±0.6                     |
| 10820 | AAE | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.36     | ±0.6                     |
| 10821 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.36     | ±0.6                     |
| 10822 | AAE | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.41     | ±0.6                     |
| 10823 | AAE | CP-OFDM, 70.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.42     | ±0.6                     |
| 10824 | AAE | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.42     | ±0.6                     |
| 10825 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB  | SG NR FR1 TDD | 8.40     | ±0.6                     |
| 10826 | AAE | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB | SG NR FR1 TDD | 8.40     | ±0.6                     |
| 10827 | AAE | CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | SG NR FR1 TDD | 7.63     | ±0.6                     |
| 10828 | AAE | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | SG NR FR1 TDD | 7.73     | ±0.6                     |
| 10829 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | SG NR FR1 TDD | 7.74     | ±0.6                     |
| 10830 | AAE | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB      | SG NR FR1 TDD | 7.70     | ±0.6                     |
| 10831 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.73     | ±0.6                     |
| 10832 | AAE | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.70     | ±0.6                     |
| 10833 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.55     | ±0.6                     |
| 10834 | AAE | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.68     | ±0.6                     |
| 10835 | AAE | CP-OFDM, 70.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.78     | ±0.6                     |
| 10836 | AAE | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.87     | ±0.6                     |
| 10837 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB     | SG NR FR1 TDD | 7.71     | ±0.6                     |
| 10838 | AAE | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB    | SG NR FR1 TDD | 7.71     | ±0.6                     |
| 10839 | AAE | CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.49     | ±0.6                     |
| 10840 | AAE | CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10841 | AAE | CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.41     | ±0.6                     |
| 10842 | AAE | CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.34     | ±0.6                     |
| 10843 | AAE | CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.36     | ±0.6                     |
| 10844 | AAE | CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.37     | ±0.6                     |
| 10845 | AAE | CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10846 | AAE | CP-OFDM, 70.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10847 | AAE | CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10848 | AAE | CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB   | SG NR FR1 TDD | 8.35     | ±0.6                     |
| 10849 | AAE | CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB  | SG NR FR1 TDD | 8.35     | ±0.6                     |

EX3DV4 - SN:7907

January 25, 2026

| UID   | Rev | Communication System Name                                 | Group         | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|-----------------------------------------------------------|---------------|----------|------------------------|
| 10550 | AAF | CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.34     | ±0.8                   |
| 10550 | AAE | CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.41     | ±0.8                   |
| 10551 | AAF | CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.40     | ±0.8                   |
| 10553 | AAF | CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.41     | ±0.8                   |
| 10554 | AAE | CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB       | 5G NR FR1 TDD | 8.37     | ±0.8                   |
| 10555 | AAF | CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB      | 5G NR FR1 TDD | 8.41     | ±0.8                   |
| 10555 | AAF | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB      | 5G NR FR1 TDD | 5.89     | ±0.6                   |
| 10558 | AAF | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB   | 5G NR FR1 TDD | 5.89     | ±0.6                   |
| 10560 | AAE | DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 5.75     | ±0.6                   |
| 10570 | AAE | DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 5.88     | ±0.6                   |
| 10571 | AAE | DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 5.75     | ±0.6                   |
| 10572 | AAE | DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.52     | ±0.8                   |
| 10573 | AAE | DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB    | 5G NR FR2 TDD | 6.61     | ±0.8                   |
| 10574 | AAE | DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB | 5G NR FR2 TDD | 6.65     | ±0.8                   |
| 10575 | AAE | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 7.70     | ±0.8                   |
| 10576 | AAE | CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.28     | ±0.8                   |
| 10577 | AAE | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 7.86     | ±0.8                   |
| 10578 | AAE | CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 8.41     | ±0.8                   |
| 10579 | AAE | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB       | 5G NR FR2 TDD | 8.12     | ±0.8                   |
| 10580 | AAE | CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB    | 5G NR FR2 TDD | 9.38     | ±0.8                   |
| 10581 | AAE | DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB      | 5G NR FR2 TDD | 5.75     | ±0.6                   |
| 10582 | AAE | DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB   | 5G NR FR2 TDD | 5.93     | ±0.6                   |
| 10583 | AAE | DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.57     | ±0.6                   |
| 10584 | AAE | DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.53     | ±0.6                   |
| 10585 | AAE | DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB     | 5G NR FR2 TDD | 6.61     | ±0.8                   |
| 10585 | AAE | DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB  | 5G NR FR2 TDD | 6.85     | ±0.8                   |
| 10587 | AAE | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 99.5% DC, 1 RB          | 5G NR FR2 TDD | 7.76     | ±0.8                   |
| 10588 | AAE | CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 99.5% DC, 100% RB       | 5G NR FR2 TDD | 8.95     | ±0.8                   |
| 10589 | AAE | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 8.62     | ±0.8                   |
| 10590 | AAE | CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.40     | ±0.8                   |
| 10591 | AAE | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB        | 5G NR FR2 TDD | 8.13     | ±0.8                   |
| 10592 | AAE | CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB     | 5G NR FR2 TDD | 8.41     | ±0.8                   |
| 10597 | AAC | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.5% DC, 1 RB         | 5G NR FR1 TDD | 5.66     | ±0.6                   |
| 10599 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | ±0.6                   |
| 10599 | AAB | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.67     | ±0.6                   |
| 10600 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10601 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10602 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10603 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10604 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10605 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10606 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB       | 5G NR FR1 TDD | 5.68     | ±0.6                   |
| 10607 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB      | 5G NR FR1 TDD | 5.75     | ±0.6                   |
| 10608 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±0.6                   |
| 10609 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±0.6                   |
| 10610 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±0.6                   |
| 10611 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±0.6                   |
| 10612 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.94     | ±0.6                   |
| 10613 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.94     | ±0.6                   |
| 10614 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.95     | ±0.6                   |
| 10615 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.93     | ±0.6                   |
| 10616 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB     | 5G NR FR1 TDD | 5.97     | ±0.6                   |
| 10617 | AAD | DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB    | 5G NR FR1 TDD | 5.94     | ±0.6                   |
| 10618 | AAE | DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB     | 5G NR FR1 TDD | 5.86     | ±0.6                   |
| 10619 | AAC | DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.86     | ±0.6                   |
| 10620 | AAB | DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.87     | ±0.6                   |
| 10621 | AAC | DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±0.6                   |
| 10622 | AAB | DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.82     | ±0.6                   |
| 10623 | AAC | DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±0.6                   |
| 10624 | AAD | DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±0.6                   |
| 10625 | AAC | DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.95     | ±0.6                   |
| 10626 | AAD | DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.84     | ±0.6                   |
| 10627 | AAD | DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB    | 5G NR FR1 TDD | 5.94     | ±0.6                   |
| 10628 | AAD | DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 1 RB                   | 5G NR FR1 FDD | 5.52     | ±0.6                   |
| 10629 | AAD | DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | ±0.6                   |
| 10630 | AAC | DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 1 RB                  | 5G NR FR1 FDD | 5.52     | ±0.6                   |

EX3DV4 - SN:7907

January 23, 2026

| UID   | Rev | Communication System Name                  | Group         | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|--------------------------------------------|---------------|----------|------------------------|
| 10931 | AAC | DFTs-OFDM, 20.0 MHz, QPSK, 15 kHz, 1 RB    | 53 NR FR1 FDD | 5.51     | ±9.5                   |
| 10932 | AAC | DFTs-OFDM, 25.0 MHz, QPSK, 15 kHz, 1 RB    | 53 NR FR1 FDD | 5.51     | ±9.5                   |
| 10933 | AAC | DFTs-OFDM, 30.0 MHz, QPSK, 15 kHz, 1 RB    | 53 NR FR1 FDD | 5.51     | ±9.5                   |
| 10934 | AAC | DFTs-OFDM, 40.0 MHz, QPSK, 15 kHz, 1 RB    | 53 NR FR1 FDD | 5.51     | ±9.5                   |
| 10935 | AAC | DFTs-OFDM, 50.0 MHz, QPSK, 15 kHz, 1 RB    | 53 NR FR1 FDD | 5.51     | ±9.5                   |
| 10936 | AAD | DFTs-OFDM, 5.0 MHz, QPSK, 15 kHz, 50% RB   | 53 NR FR1 FDD | 5.50     | ±9.5                   |
| 10937 | AAD | DFTs-OFDM, 10.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.77     | ±9.5                   |
| 10938 | AAC | DFTs-OFDM, 15.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.50     | ±9.5                   |
| 10939 | AAC | DFTs-OFDM, 20.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.82     | ±9.5                   |
| 10940 | AAC | DFTs-OFDM, 25.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.89     | ±9.5                   |
| 10941 | AAC | DFTs-OFDM, 30.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.83     | ±9.5                   |
| 10942 | AAC | DFTs-OFDM, 40.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.85     | ±9.5                   |
| 10943 | AAD | DFTs-OFDM, 50.0 MHz, QPSK, 15 kHz, 50% RB  | 53 NR FR1 FDD | 5.85     | ±9.5                   |
| 10944 | AAD | DFTs-OFDM, 5.0 MHz, QPSK, 15 kHz, 100% RB  | 53 NR FR1 FDD | 5.81     | ±9.5                   |
| 10945 | AAD | DFTs-OFDM, 10.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.85     | ±9.5                   |
| 10946 | AAC | DFTs-OFDM, 15.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.83     | ±9.5                   |
| 10947 | AAC | DFTs-OFDM, 20.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.87     | ±9.5                   |
| 10948 | AAC | DFTs-OFDM, 25.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.94     | ±9.5                   |
| 10949 | AAC | DFTs-OFDM, 30.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.87     | ±9.5                   |
| 10950 | AAC | DFTs-OFDM, 40.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.94     | ±9.5                   |
| 10951 | AAD | DFTs-OFDM, 50.0 MHz, QPSK, 15 kHz, 100% RB | 53 NR FR1 FDD | 5.92     | ±9.5                   |
| 10978 | AAA | BCR, 1.0 MHz, 76.7% DC                     | ULLA          | 1.16     | ±9.5                   |
| 10979 | AAA | HDR4, 2.0 MHz, 25.1% DC                    | ULLA          | 5.06     | ±9.5                   |
| 10980 | AAA | HDR8, 4.0 MHz, 16.5% DC                    | ULLA          | 10.32    | ±9.5                   |
| 10981 | AAA | HDR4, 2.0 MHz, 29.0% DC                    | ULLA          | 3.19     | ±9.5                   |
| 10982 | AAA | HDR8, 4.0 MHz, 90.3% DC                    | ULLA          | 3.43     | ±9.5                   |
| 11013 | AAB | EHT320, MCS1 (272.0 Mbps), 100.0% DC       | WLAN          | 9.47     | ±9.5                   |
| 11014 | AAB | EHT320, MCS2 (408.0 Mbps), 100.0% DC       | WLAN          | 9.46     | ±9.5                   |
| 11015 | AAB | EHT320, MCS3 (544.0 Mbps), 100.0% DC       | WLAN          | 9.44     | ±9.5                   |
| 11016 | AAB | EHT320, MCS4 (517.0 Mbps), 100.0% DC       | WLAN          | 9.44     | ±9.5                   |
| 11017 | AAB | EHT320, MCS5 (1069.0 Mbps), 100.0% DC      | WLAN          | 9.41     | ±9.5                   |
| 11018 | AAB | EHT320, MCS6 (1225.0 Mbps), 100.0% DC      | WLAN          | 9.40     | ±9.5                   |
| 11019 | AAB | EHT320, MCS7 (1261.0 Mbps), 100.0% DC      | WLAN          | 9.29     | ±9.5                   |
| 11020 | AAB | EHT320, MCS8 (1633.0 Mbps), 100.0% DC      | WLAN          | 9.27     | ±9.5                   |
| 11021 | AAB | EHT320, MCS9 (1815.0 Mbps), 100.0% DC      | WLAN          | 9.40     | ±9.5                   |
| 11022 | AAB | EHT320, MCS10 (2042.0 Mbps), 100.0% DC     | WLAN          | 9.36     | ±9.5                   |
| 11023 | AAB | EHT320, MCS11 (2209.0 Mbps), 100.0% DC     | WLAN          | 9.09     | ±9.5                   |
| 11024 | AAB | EHT320, MCS12 (2450.0 Mbps), 100.0% DC     | WLAN          | 9.42     | ±9.5                   |
| 11025 | AAB | EHT320, MCS13 (2722.0 Mbps), 100.0% DC     | WLAN          | 9.37     | ±9.5                   |
| 11026 | AAB | EHT320, MCS0 (136.0 Mbps), 100.0% DC       | WLAN          | 9.39     | ±9.5                   |

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **HCT**  
 Gyeonggi-do, Republic of Korea

Certificate No. **EX-7732\_Jun25**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:7732**

Calibration procedure(s) **QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,  
 QA CAL-25.v8**  
**Calibration procedure for dosimetric E-field probes**

Calibration date **June 25, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.  
 All calibrations have been conducted in the closest laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .  
 Calibration Equipment used (M&E critical for calibration)

| Primary Standards           | ID         | Calibration Date (Certificate No.)     | Sched. Cal. |
|-----------------------------|------------|----------------------------------------|-------------|
| Power Sensor R&S NRP-33T    | SN: 100967 | 26-Mar-25 (No. 217-04290)              | Mar-26      |
| N-type mismatch combination | SN: L1119  | 26-Mar-25 (No. 217-04292)              | Mar-26      |
| OCP DAK-12                  | SN: 1016   | 24-Sept-24 (No. OCP-DAK12-1016_Sep24)  | Sep-25      |
| OCP DAK-3.5                 | SN: 1249   | 23-Sept-24 (No. OCP-DAK3.5-1249_Sep24) | Sep-25      |
| Reference Probe EX3DV4      | SN: 7349   | 10-Jan-25 (No. EX3-7349_Jan25)         | Jan-26      |
| DAE4                        | SN: 1301   | 07-Nov-24 (No. DAE4-1301_Nov24)        | Nov-25      |

| Secondary Standards | ID        | Check Date (in house)                            | Sched. Check |
|---------------------|-----------|--------------------------------------------------|--------------|
| ACAP 2020 Setup 1   | SN: L1404 | 30-Sept-24 (No. Report ACAP2020E-Cava_20210830s) | Sep-25       |
| OCP DAK-12          | SN: 1029  | 27-Feb-25 (No. OCP-DAK12-1029_Feb25)             | Feb-26       |
| OCP DAK-3.5         | SN: 1336  | 09-Dec-24 (No. OCP-DAK3.5-1336_Dec24)            | Dec-25       |

|                                                                                                                 |            |                       |                       |
|-----------------------------------------------------------------------------------------------------------------|------------|-----------------------|-----------------------|
|                                                                                                                 | Name       | Function              | Signature             |
| Calibrated by                                                                                                   | Paulo Pina | Laboratory Technician |                       |
| Approved by                                                                                                     | Sven Kjhn  | Technical Manager     |                       |
|                                                                                                                 |            |                       | Issued: June 25, 2025 |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |            |                       |                       |

Certificate No: EX-7732\_Jun25

Page 1 of 21

|       |            |            |
|-------|------------|------------|
| 결     | 담당자        | 확인자        |
| 재     | 김민준        | 김민준        |
| 직위/성명 | DL 178010  | DL 178010  |
| 일 자   | 2025 07-01 | 2025-07-01 |

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
 Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
 The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

## Glossary

|                        |                                                                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                    | Tissue simulating liquid                                                                                                                       |
| NORM <sub>x,y,z</sub>  | sensitivity in free space                                                                                                                      |
| ConvF                  | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                     |
| DCP                    | diode compression point                                                                                                                        |
| CF                     | crest factor (1/duty_cycle) of the RF signal                                                                                                   |
| A, B, C, D             | modulation dependent linearization parameters                                                                                                  |
| Polarization $\varphi$ | $\varphi$ rotation around probe axis                                                                                                           |
| Polarization $\theta$  | $\theta$ rotation around an axis that is in the plane normal to probe axis [at measurement center], i.e., $\theta = 0$ is normal to probe axis |
| Connector Angle        | Information used in DASY system to align probe sensor X to the robot coordinate system                                                         |

## Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

## Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1600$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM<sub>lin</sub>(<sub>x,y,z</sub>) = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy)**: In a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).

EX3DV4 - SN:7732

June 25, 2025

### Parameters of Probe: EX3DV4 - SN:7732

#### Basic Calibration Parameters

|                                       | Sensor X | Sensor Y | Sensor Z | Unc (k = 2) |
|---------------------------------------|----------|----------|----------|-------------|
| Norm ( $\mu W/(V/m)^2$ ) <sup>A</sup> | 0.51     | 0.55     | 0.58     | ±10.1%      |
| DCP (mV) <sup>B</sup>                 | 105.8    | 103.6    | 104.1    | ±4.7%       |

#### Calibration Results for Modulation Response

| UID   | Communication System Name   |   | A<br>dB | B<br>dB/√μV | C     | D<br>dB | VR<br>mV | Max<br>dev. | Max<br>Unc <sup>E</sup><br>k = 2 |
|-------|-----------------------------|---|---------|-------------|-------|---------|----------|-------------|----------------------------------|
| 0     | CW                          | X | 0.00    | 0.00        | 1.00  | 0.00    | 122.4    | ±1.6%       | ±4.7%                            |
|       |                             | Y | 0.00    | 0.00        | 1.00  |         | 134.8    |             |                                  |
|       |                             | Z | 0.00    | 0.00        | 1.00  |         | 131.7    |             |                                  |
| 10352 | Pulse Waveform (200Hz, 10%) | X | 2.00    | 62.00       | 7.00  | 10.00   | 60.0     | ±2.7%       | ±9.6%                            |
|       |                             | Y | 1.56    | 60.96       | 6.75  |         | 60.0     |             |                                  |
|       |                             | Z | 1.38    | 60.00       | 6.04  |         | 60.0     |             |                                  |
| 10353 | Pulse Waveform (200Hz, 20%) | X | 44.00   | 60.00       | 11.00 | 6.99    | 80.0     | ±2.2%       | ±9.6%                            |
|       |                             | Y | 0.77    | 60.00       | 5.12  |         | 80.0     |             |                                  |
|       |                             | Z | 20.00   | 74.00       | 9.00  |         | 80.0     |             |                                  |
| 10354 | Pulse Waveform (200Hz, 40%) | X | 0.08    | 131.59      | 0.26  | 3.98    | 95.0     | ±2.5%       | ±9.6%                            |
|       |                             | Y | 0.30    | 113.00      | 1.81  |         | 95.0     |             |                                  |
|       |                             | Z | 0.33    | 154.92      | 4.19  |         | 95.0     |             |                                  |
| 10355 | Pulse Waveform (200Hz, 60%) | X | 6.69    | 160.00      | 26.75 | 2.22    | 120.0    | ±1.5%       | ±9.6%                            |
|       |                             | Y | 0.00    | 159.97      | 0.03  |         | 120.0    |             |                                  |
|       |                             | Z | 7.78    | 113.50      | 5.09  |         | 120.0    |             |                                  |
| 10387 | QPSK Waveform, 1 MHz        | X | 0.57    | 65.34       | 13.87 | 1.00    | 150.0    | ±3.5%       | ±9.6%                            |
|       |                             | Y | 0.59    | 63.59       | 12.04 |         | 150.0    |             |                                  |
|       |                             | Z | 0.60    | 65.90       | 13.84 |         | 150.0    |             |                                  |
| 10388 | QPSK Waveform, 10 MHz       | X | 1.42    | 67.39       | 14.73 | 0.00    | 150.0    | ±1.2%       | ±9.6%                            |
|       |                             | Y | 1.36    | 65.35       | 13.60 |         | 150.0    |             |                                  |
|       |                             | Z | 1.43    | 67.40       | 14.61 |         | 150.0    |             |                                  |
| 10396 | 64-QAM Waveform, 100 kHz    | X | 1.62    | 63.97       | 15.94 | 3.01    | 150.0    | ±1.1%       | ±9.6%                            |
|       |                             | Y | 1.66    | 64.05       | 15.74 |         | 150.0    |             |                                  |
|       |                             | Z | 1.66    | 64.54       | 16.03 |         | 150.0    |             |                                  |
| 10399 | 64-QAM Waveform, 40 MHz     | X | 2.84    | 66.74       | 15.42 | 0.00    | 150.0    | ±1.6%       | ±9.6%                            |
|       |                             | Y | 2.87    | 66.10       | 14.98 |         | 150.0    |             |                                  |
|       |                             | Z | 2.89    | 66.93       | 15.49 |         | 150.0    |             |                                  |
| 10414 | WLAN CCDF, 64-QAM, 40 MHz   | X | 3.76    | 66.24       | 15.42 | 0.00    | 150.0    | ±2.8%       | ±9.6%                            |
|       |                             | Y | 3.69    | 65.68       | 15.24 |         | 150.0    |             |                                  |
|       |                             | Z | 3.84    | 66.51       | 15.55 |         | 150.0    |             |                                  |

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Page 5).

<sup>B</sup> Linearization parameter uncertainty for maximum specified field strength.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4 - SN:7732

June 25, 2025

### Parameters of Probe: EX3DV4 - SN:7732

#### Sensor Model Parameters

|   | C1<br>IF | C2<br>IF | $\alpha$<br>V <sup>-1</sup> | T1<br>ms V <sup>-2</sup> | T2<br>ms V <sup>-1</sup> | T3<br>ms | T4<br>V <sup>-2</sup> | T5<br>V <sup>-1</sup> | T6   |
|---|----------|----------|-----------------------------|--------------------------|--------------------------|----------|-----------------------|-----------------------|------|
| x | 8.7      | 62.97    | 33.23                       | 1.99                     | 0.00                     | 4.90     | 0.11                  | 0.02                  | 1.00 |
| y | 10.4     | 76.71    | 34.57                       | 2.02                     | 0.00                     | 4.92     | 0.32                  | 0.00                  | 1.00 |
| z | 8.8      | 64.02    | 33.99                       | 1.83                     | 0.00                     | 4.90     | 0.30                  | 0.00                  | 1.00 |

#### Other Probe Parameters

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle                               | -27.6°     |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |

Note: Measurement distance from surface can be increased to 3–4 mm for an Area Scan job.

EX3DV4 - SN:7732

June 25, 2025

## Parameters of Probe: EX3DV4 - SN:7732

### Calibration Parameter Determined in HSL

| f (MHz) <sup>D</sup> | Relative Permittivity <sup>E</sup> | Conductivity <sup>F</sup> (S/m) | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc <sup>H</sup> (k = 2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|--------------------------|
| 750                  | 41.9                               | 0.89                            | 10.06   | 9.54    | 10.08   | 0.35               | 1.27                    | ±11.0%                   |
| 835                  | 41.5                               | 0.90                            | 9.80    | 9.29    | 9.82    | 0.35               | 1.27                    | ±11.0%                   |
| 900                  | 41.5                               | 0.97                            | 9.47    | 8.98    | 9.49    | 0.35               | 1.27                    | ±11.0%                   |
| 1750                 | 40.1                               | 1.37                            | 8.46    | 8.02    | 8.48    | 0.34               | 1.27                    | ±11.0%                   |
| 1900                 | 40.0                               | 1.40                            | 8.19    | 7.77    | 8.21    | 0.34               | 1.27                    | ±11.0%                   |
| 2300                 | 39.5                               | 1.67                            | 7.75    | 7.35    | 7.77    | 0.33               | 1.27                    | ±11.0%                   |
| 2450                 | 39.2                               | 1.80                            | 7.52    | 7.13    | 7.53    | 0.33               | 1.27                    | ±11.0%                   |
| 2600                 | 39.0                               | 1.96                            | 7.71    | 7.31    | 7.73    | 0.33               | 1.27                    | ±11.0%                   |

<sup>D</sup> Frequency validity above 300 MHz of ±100 MHz only applies for DASV v4.4 and higher (see Page 2), else it is restricted to +50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–8 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

<sup>E</sup> The probes are calibrated using tissue simulating liquids (TSL) that deviate for  $\epsilon'$  and  $\sigma$  by less than +5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to +10% if SAR correction is applied.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.


<sup>H</sup> The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1520:2020.

EX3DV4 - SN:7732

June 25, 2025

### Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide:R22)


Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)

EX3DV4 - SN:7732


June 25, 2025

## Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$



EX3DV4 - SN:7732

June 25, 2025




Uncertainty of Linearity Assessment:  $\pm 0.8\%$  ( $k=2$ )

EX3DV4 - SN:7732


June 25, 2025

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi, \theta$ ),  $f=900\text{ MHz}$



EX3DV4 - SN:7732

June 25, 2025

## Appendix: Modulation Calibration Parameters

| UID   | Rev | Communication System Name                          | Group     | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|-----|----------------------------------------------------|-----------|----------|------------------------|
| 0     |     | CW                                                 | CW        | 0.00     | ±4.7                   |
| 10010 | CAB | SAR Validation (Square, 100 ms, 10 ms)             | Test      | 10.00    | ±9.6                   |
| 10011 | CAC | UMTS-FDD (WCDMA)                                   | WCDMA     | 2.91     | ±9.6                   |
| 10012 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)           | WLAN      | 1.87     | ±9.6                   |
| 10013 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)      | WLAN      | 9.48     | ±9.6                   |
| 10021 | DAC | GSM-FDD (TDMA, GMSK)                               | GSM       | 9.39     | ±9.6                   |
| 10023 | DAC | GPRS-FDD (TDMA, GMSK, TN 0)                        | GSM       | 9.57     | ±9.6                   |
| 10024 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-1)                      | GSM       | 6.56     | ±9.6                   |
| 10025 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0)                        | GSM       | 12.82    | ±9.6                   |
| 10026 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1)                      | GSM       | 9.55     | ±9.6                   |
| 10027 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-1-2)                    | GSM       | 4.80     | ±9.6                   |
| 10028 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)                  | GSM       | 3.55     | ±9.6                   |
| 10029 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1-2)                    | GSM       | 7.78     | ±9.6                   |
| 10030 | CAA | IEEE 802.15.1 Bluetooth (3FSK, DH1)                | Bluetooth | 5.30     | ±9.6                   |
| 10031 | CAA | IEEE 802.15.1 Bluetooth (GFSK, DH3)                | Bluetooth | 1.87     | ±9.6                   |
| 10032 | CAA | IEEE 802.15.1 Bluetooth (3FSK, DH5)                | Bluetooth | 1.16     | ±9.6                   |
| 10033 | CAA | IEEE 802.15.1 Bluetooth (PI4-DQPSK, DH1)           | Bluetooth | 7.74     | ±9.6                   |
| 10034 | CAA | IEEE 802.15.1 Bluetooth (PI4-DQPSK, DH3)           | Bluetooth | 4.58     | ±9.6                   |
| 10035 | CAA | IEEE 802.15.1 Bluetooth (PI4-DQPSK, DH5)           | Bluetooth | 3.03     | ±9.6                   |
| 10036 | CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH1)              | Bluetooth | 8.01     | ±9.6                   |
| 10037 | CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH3)              | Bluetooth | 4.77     | ±9.6                   |
| 10038 | CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH5)              | Bluetooth | 4.10     | ±9.6                   |
| 10039 | CAB | CDMA2000 (1xRTT, RC1)                              | CDMA2000  | 4.57     | ±9.6                   |
| 10042 | CAB | IS-54 / IS-136 FDD (TDMA/FDM, PI4-DQPSK, Fullrate) | AMPS      | 7.78     | ±9.6                   |
| 10044 | CAA | IS-95/EIA-TIA-553 FDD (FDMA, FM)                   | AMPS      | 0.00     | ±9.6                   |
| 10046 | CAA | DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)          | DECT      | 13.00    | ±9.6                   |
| 10049 | CAA | DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)        | DECT      | 10.78    | ±9.6                   |
| 10056 | CAA | UMTS-TDD (TD-SCDMA, 1.28 Mbps)                     | TD-SCDMA  | 11.01    | ±9.6                   |
| 10058 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)                  | GSM       | 6.52     | ±9.6                   |
| 10060 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)           | WLAN      | 2.12     | ±9.6                   |
| 10060 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)         | WLAN      | 2.88     | ±9.6                   |
| 10061 | CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)          | WLAN      | 3.60     | ±9.6                   |
| 10062 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 6 Mbps)            | WLAN      | 9.68     | ±9.6                   |
| 10063 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 9 Mbps)            | WLAN      | 9.63     | ±9.6                   |
| 10064 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 12 Mbps)           | WLAN      | 9.09     | ±9.6                   |
| 10065 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 18 Mbps)           | WLAN      | 9.00     | ±9.6                   |
| 10066 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 24 Mbps)           | WLAN      | 9.58     | ±9.6                   |
| 10067 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 36 Mbps)           | WLAN      | 10.12    | ±9.6                   |
| 10068 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 48 Mbps)           | WLAN      | 10.24    | ±9.6                   |
| 10069 | CAE | IEEE 802.11ah WiFi 5 GHz (OFDM, 54 Mbps)           | WLAN      | 10.50    | ±9.6                   |
| 10071 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)      | WLAN      | 8.83     | ±9.6                   |
| 10072 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)     | WLAN      | 9.02     | ±9.6                   |
| 10073 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)     | WLAN      | 9.94     | ±9.6                   |
| 10074 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)     | WLAN      | 10.30    | ±9.6                   |
| 10075 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)     | WLAN      | 10.77    | ±9.6                   |
| 10076 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)     | WLAN      | 10.94    | ±9.6                   |
| 10077 | CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)     | WLAN      | 11.00    | ±9.6                   |
| 10081 | CAB | CDMA2000 (1xRTT, RC3)                              | CDMA2000  | 2.97     | ±9.6                   |
| 10082 | CAB | IS-54 / IS-136 FDD (TDMA/FDM, PI4-DQPSK, Fullrate) | AMPS      | 4.77     | ±9.6                   |
| 10086 | DAC | GPRS-FDD (TDMA, GMSK, TN 0-4)                      | GSM       | 6.56     | ±9.6                   |
| 10087 | CAC | UMTS-FDD (HSPA)                                    | WCDMA     | 3.98     | ±9.6                   |
| 10088 | CAC | UMTS-FDD (HSPA, Suspend 2)                         | WCDMA     | 3.98     | ±9.6                   |
| 10089 | DAC | EDGE-FDD (TDMA, 8PSK, TN 0-4)                      | GSM       | 9.55     | ±9.6                   |
| 10100 | CAF | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)           | LTE-FDD   | 5.67     | ±9.6                   |
| 10101 | CAF | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)         | LTE-FDD   | 6.42     | ±9.6                   |
| 10102 | CAF | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)         | LTE-FDD   | 6.60     | ±9.6                   |
| 10103 | CAH | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)           | LTE-TDD   | 5.29     | ±9.6                   |
| 10104 | CAH | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)         | LTE-TDD   | 5.97     | ±9.6                   |
| 10105 | CAH | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)         | LTE-TDD   | 6.01     | ±9.6                   |
| 10106 | CAH | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)           | LTE-FDD   | 5.80     | ±9.6                   |
| 10109 | CAH | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)         | LTE-FDD   | 6.43     | ±9.6                   |
| 10110 | CAH | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)            | LTE-FDD   | 5.75     | ±9.6                   |
| 10111 | CAH | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)          | LTE-FDD   | 6.44     | ±9.6                   |

Certificate No: EX-7732\_Jun25

Page 10 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev | Communication System Name                      | Group   | PAR [dB] | Unc <sup>F</sup> k = 2 |
|-------|-----|------------------------------------------------|---------|----------|------------------------|
| 10112 | CAH | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)     | LTE-FDD | 5.58     | ±9.6                   |
| 10113 | CAH | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)      | LTE-FDD | 5.52     | ±9.6                   |
| 10114 | CAE | IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)  | WLAN    | 5.10     | ±9.6                   |
| 10115 | CAE | IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)  | WLAN    | 5.46     | ±9.6                   |
| 10116 | CAE | IEEE 802.11n (HT Greenfield, 126 Mbps, 64-QAM) | WLAN    | 5.15     | ±9.6                   |
| 10117 | CAE | IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)       | WLAN    | 5.07     | ±9.6                   |
| 10118 | CAE | IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)       | WLAN    | 5.58     | ±9.6                   |
| 10119 | CAE | IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)      | WLAN    | 5.12     | ±9.6                   |
| 10140 | CAF | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)     | LTE-FDD | 5.49     | ±9.6                   |
| 10141 | CAF | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)     | LTE-FDD | 5.53     | ±9.6                   |
| 10142 | CAF | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)        | LTE-FDD | 5.73     | ±9.6                   |
| 10143 | CAF | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)      | LTE-FDD | 5.35     | ±9.6                   |
| 10144 | CAF | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)      | LTE-FDD | 5.65     | ±9.6                   |
| 10145 | CAG | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)      | LTE-FDD | 5.76     | ±9.6                   |
| 10146 | CAG | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)    | LTE-FDD | 5.41     | ±9.6                   |
| 10147 | CAG | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)    | LTE-FDD | 5.72     | ±9.6                   |
| 10148 | CAF | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)      | LTE-FDD | 5.42     | ±9.6                   |
| 10150 | CAF | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)      | LTE-FDD | 5.60     | ±9.6                   |
| 10151 | CAH | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)        | LTE-TDD | 9.29     | ±9.6                   |
| 10152 | CAH | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)      | LTE-TDD | 9.92     | ±9.6                   |
| 10153 | CAH | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)      | LTE-TDD | 10.05    | ±9.6                   |
| 10154 | CAH | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)        | LTE-FDD | 5.75     | ±9.6                   |
| 10155 | CAH | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)      | LTE-FDD | 5.43     | ±9.6                   |
| 10156 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)         | LTE-FDD | 5.79     | ±9.6                   |
| 10157 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)       | LTE-FDD | 5.49     | ±9.6                   |
| 10158 | CAH | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)      | LTE-FDD | 5.82     | ±9.6                   |
| 10159 | CAH | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)       | LTE-FDD | 5.58     | ±9.6                   |
| 10160 | CAF | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)        | LTE-FDD | 5.82     | ±9.6                   |
| 10161 | CAF | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)      | LTE-FDD | 5.43     | ±9.6                   |
| 10162 | CAF | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)      | LTE-FDD | 5.59     | ±9.6                   |
| 10166 | CAG | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)       | LTE-FDD | 5.46     | ±9.6                   |
| 10167 | CAG | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)     | LTE-FDD | 5.21     | ±9.6                   |
| 10168 | CAG | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)     | LTE-FDD | 5.79     | ±9.6                   |
| 10169 | CAF | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)          | LTE-FDD | 5.73     | ±9.6                   |
| 10170 | CAF | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)        | LTE-FDD | 5.52     | ±9.6                   |
| 10171 | AAF | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)        | LTE-FDD | 5.49     | ±9.6                   |
| 10172 | CAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)          | LTE-TDD | 9.21     | ±9.6                   |
| 10173 | CAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)        | LTE-TDD | 9.46     | ±9.6                   |
| 10174 | CAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)        | LTE-TDD | 10.25    | ±9.6                   |
| 10175 | CAH | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)          | LTE-FDD | 5.72     | ±9.6                   |
| 10176 | CAH | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)        | LTE-FDD | 5.52     | ±9.6                   |
| 10177 | CAJ | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)           | LTE-FDD | 5.73     | ±9.6                   |
| 10178 | CAH | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)         | LTE-FDD | 5.52     | ±9.6                   |
| 10179 | CAH | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)        | LTE-FDD | 5.50     | ±9.6                   |
| 10180 | CAH | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)         | LTE-FDD | 5.50     | ±9.6                   |
| 10181 | CAF | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)          | LTE-FDD | 5.72     | ±9.6                   |
| 10182 | CAF | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)        | LTE-FDD | 5.52     | ±9.6                   |
| 10183 | AAF | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)        | LTE-FDD | 5.50     | ±9.6                   |
| 10184 | CAF | LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)           | LTE-FDD | 5.73     | ±9.6                   |
| 10185 | CAF | LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)         | LTE-FDD | 5.51     | ±9.6                   |
| 10186 | AAF | LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)         | LTE-FDD | 5.50     | ±9.6                   |
| 10187 | CAG | LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)         | LTE-FDD | 5.73     | ±9.6                   |
| 10188 | CAG | LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)       | LTE-FDD | 5.52     | ±9.6                   |
| 10189 | AAG | LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)       | LTE-FDD | 5.50     | ±9.6                   |
| 10193 | CAC | IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)   | WLAN    | 5.09     | ±9.6                   |
| 10194 | CAE | IEEE 802.11n (HT Greenfield, 30 Mbps, 16-QAM)  | WLAN    | 5.12     | ±9.6                   |
| 10195 | CAE | IEEE 802.11n (HT Greenfield, 60 Mbps, 64-QAM)  | WLAN    | 5.21     | ±9.6                   |
| 10196 | CAE | IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)        | WLAN    | 5.10     | ±9.6                   |
| 10197 | CAE | IEEE 802.11n (HT Mixed, 30 Mbps, 16-QAM)       | WLAN    | 5.13     | ±9.6                   |
| 10198 | CAE | IEEE 802.11n (HT Mixed, 60 Mbps, 64-QAM)       | WLAN    | 5.27     | ±9.6                   |
| 10219 | CAE | IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)        | WLAN    | 5.03     | ±9.6                   |
| 10220 | CAE | IEEE 802.11n (HT Mixed, 43.2 Mbps, 16-QAM)     | WLAN    | 5.13     | ±9.6                   |
| 10221 | CAF | IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)     | WLAN    | 5.27     | ±9.6                   |
| 10222 | CAE | IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)         | WLAN    | 5.05     | ±9.6                   |
| 10223 | CAE | IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)       | WLAN    | 5.48     | ±9.6                   |
| 10224 | CAE | IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)      | WLAN    | 5.05     | ±9.6                   |

Certificate No: EX-7732\_Jun25

Page 11 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev  | Communication System Name                                            | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|------|----------------------------------------------------------------------|----------|----------|------------------------|
| 10225 | CAC  | UMTS-FDD (HSPA+)                                                     | WCDMA    | 5.87     | ±9.6                   |
| 10226 | CAC  | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)                             | LTE-TDD  | 5.49     | ±9.6                   |
| 10227 | CAC  | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)                             | LTE-TDD  | 10.26    | ±9.6                   |
| 10228 | CAC  | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)                               | LTE-TDD  | 9.22     | ±9.6                   |
| 10229 | CAE  | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)                               | LTE-TDD  | 6.46     | ±9.6                   |
| 10230 | CAE  | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)                               | LTE-TDD  | 10.25    | ±9.6                   |
| 10231 | CAE  | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)                                 | LTE-TDD  | 6.19     | ±9.6                   |
| 10232 | CAH  | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)                               | LTE-TDD  | 5.43     | ±9.6                   |
| 10233 | CAH  | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)                               | LTE-TDD  | 10.25    | ±9.6                   |
| 10234 | CAH  | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)                                 | LTE-TDD  | 9.21     | ±9.6                   |
| 10235 | CAH  | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)                              | LTE-TDD  | 9.25     | ±9.6                   |
| 10236 | CAH  | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)                              | LTE-TDD  | 10.25    | ±9.6                   |
| 10237 | CAH  | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)                                | LTE-TDD  | 9.21     | ±9.6                   |
| 10238 | CAG  | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)                              | LTE-TDD  | 9.48     | ±9.6                   |
| 10239 | CAG  | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)                              | LTE-TDD  | 10.25    | ±9.6                   |
| 10240 | CAG  | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)                                | LTE-TDD  | 9.21     | ±9.6                   |
| 10241 | CAC  | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)                           | LTE-TDD  | 9.92     | ±9.6                   |
| 10242 | CAC  | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)                           | LTE-TDD  | 9.86     | ±9.6                   |
| 10243 | CAC  | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)                             | LTE-TDD  | 9.46     | ±9.6                   |
| 10244 | CAE  | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)                             | LTE-TDD  | 10.06    | ±9.6                   |
| 10245 | CAE  | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)                             | LTE-TDD  | 10.06    | ±9.6                   |
| 10246 | CAE  | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)                               | LTE-TDD  | 9.30     | ±9.6                   |
| 10247 | CA-I | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)                             | LTE-TDD  | 9.81     | ±9.6                   |
| 10248 | CA-I | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)                             | LTE-TDD  | 10.09    | ±9.6                   |
| 10249 | CA-I | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)                               | LTE-TDD  | 9.29     | ±9.6                   |
| 10250 | CA-I | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)                            | LTE-TDD  | 8.61     | ±9.6                   |
| 10251 | CA-I | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)                            | LTE-TDD  | 10.17    | ±9.6                   |
| 10252 | CA-I | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)                              | LTE-TDD  | 8.24     | ±9.6                   |
| 10253 | CAG  | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)                            | LTE-TDD  | 9.90     | ±9.6                   |
| 10254 | CAG  | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)                            | LTE-TDD  | 10.14    | ±9.6                   |
| 10255 | CAG  | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)                              | LTE-TDD  | 8.20     | ±9.6                   |
| 10256 | CAC  | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)                          | LTE-TDD  | 9.96     | ±9.6                   |
| 10257 | CAC  | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)                          | LTE-TDD  | 10.08    | ±9.6                   |
| 10258 | CAC  | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)                            | LTE-TDD  | 9.34     | ±9.6                   |
| 10259 | CAE  | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)                            | LTE-TDD  | 9.98     | ±9.6                   |
| 10260 | CAE  | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)                            | LTE-TDD  | 9.97     | ±9.6                   |
| 10261 | CAE  | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)                              | LTE-TDD  | 9.24     | ±9.6                   |
| 10262 | CA-I | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)                            | LTE-TDD  | 9.83     | ±9.6                   |
| 10263 | CA-I | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)                            | LTE-TDD  | 10.16    | ±9.6                   |
| 10264 | CA-I | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)                              | LTE-TDD  | 9.23     | ±9.6                   |
| 10265 | CA-I | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)                           | LTE-TDD  | 9.92     | ±9.6                   |
| 10266 | CA-I | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)                           | LTE-TDD  | 10.07    | ±9.6                   |
| 10267 | CA-I | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)                             | LTE-TDD  | 9.30     | ±9.6                   |
| 10268 | CAG  | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)                           | LTE-TDD  | 10.06    | ±9.6                   |
| 10269 | CAG  | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)                           | LTE-TDD  | 10.13    | ±9.6                   |
| 10270 | CAG  | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                             | LTE-TDD  | 9.59     | ±9.6                   |
| 10274 | CAC  | UMTS-FDD (HSPA, Subtest 5, 3GPP Rel8.10)                             | WCDMA    | 4.87     | ±9.6                   |
| 10275 | CAC  | UMTS-FDD (HSPA, Subtest 5, 3GPP Rel8.4)                              | WCDMA    | 3.96     | ±9.6                   |
| 10277 | CAA  | PHS (QPSK)                                                           | PHS      | 11.81    | ±9.6                   |
| 10278 | CAA  | PHS (QPSK, BW 864MHz, Roll-off 0.5)                                  | PHS      | 11.81    | ±9.6                   |
| 10279 | CAA  | PHS (QPSK, BW 864MHz, Roll-off 0.35)                                 | PHS      | 12.18    | ±9.6                   |
| 10290 | AAB  | CDMA2000, RC1, SC95, Full Rate                                       | CDMA2000 | 3.91     | ±9.6                   |
| 10291 | AAB  | CDMA2000, RC3, SC95, Full Rate                                       | CDMA2000 | 3.48     | ±9.6                   |
| 10292 | AAB  | CDMA2000, RC3, SC92, Full Rate                                       | CDMA2000 | 3.39     | ±9.6                   |
| 10293 | AAB  | CDMA2000, RC3, SC9, Full Rate                                        | CDMA2000 | 3.50     | ±9.6                   |
| 10295 | AAB  | CDMA2000, RC1, SC9, 1/8th Rate 25 Ir                                 | CDMA2000 | 12.49    | ±9.6                   |
| 10297 | AAE  | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)                              | LTE-FDD  | 5.81     | ±9.6                   |
| 10298 | AAE  | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)                               | LTE-FDD  | 5.72     | ±9.6                   |
| 10299 | AAE  | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)                             | LTE-FDD  | 6.39     | ±9.6                   |
| 10300 | AAE  | LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)                             | LTE-FDD  | 8.80     | ±9.6                   |
| 10301 | AAA  | IEEE 802.11a WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)                 | WiMAX    | 12.18    | ±9.6                   |
| 10302 | AAA  | IEEE 802.11a WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols) | WiMAX    | 12.57    | ±9.6                   |
| 10303 | AAA  | IEEE 802.11a WiMAX (31:15, 5 ms, 10 MHz, 64QAM, PUSC)                | WiMAX    | 12.52    | ±9.6                   |
| 10304 | AAA  | IEEE 802.11a WiMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)                | WiMAX    | 11.86    | ±9.6                   |
| 10305 | AAA  | IEEE 802.11a WiMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)   | WiMAX    | 15.24    | ±9.6                   |
| 10306 | AAA  | IEEE 802.11a WiMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)   | WiMAX    | 14.67    | ±9.6                   |

Certificate No: EX-7732 Jun25

Page 12 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev  | Communication System Name                                                       | Group    | PAR (dB) | Unc <sup>E</sup> k = 2 |
|-------|------|---------------------------------------------------------------------------------|----------|----------|------------------------|
| 10307 | AAA  | IEEE 802.16e WiMAX (29.18, 10 ms, 10 MHz, QPSK, PUSC, 16 symbols)               | WiMAX    | 14.49    | ±9.6                   |
| 10308 | AAA  | IEEE 802.16e WiMAX (29.18, 10 ms, 10 MHz, 16QAM, PUSC)                          | WiMAX    | 14.48    | ±9.6                   |
| 10309 | AAA  | IEEE 802.16e WiMAX (29.18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 16 symbols)           | WiMAX    | 14.58    | ±9.6                   |
| 10310 | AAA  | IEEE 802.16e WiMAX (29.18, 10 ms, 10 MHz, QPSK, AMC 2x3, 16 symbols)            | WiMAX    | 14.57    | ±9.6                   |
| 10311 | AAE  | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)                                        | LTE-FDD  | 8.08     | ±9.6                   |
| 10313 | AAA  | IDEN 1.3                                                                        | IDEN     | 10.51    | ±9.6                   |
| 10314 | AAA  | IDEN 1.6                                                                        | IDEN     | 13.48    | ±9.6                   |
| 10315 | AAD  | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99% duty cycle)                        | WLAN     | 1.71     | ±9.6                   |
| 10316 | AAB  | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99% duty cycle)                    | WLAN     | 8.38     | ±9.6                   |
| 10317 | A/LE | IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 99% duty cycle)                          | WLAN     | 8.38     | ±9.6                   |
| 10352 | AAA  | Pulse Waveform (200Hz, 10%)                                                     | Generic  | 10.00    | ±9.6                   |
| 10353 | AAA  | Pulse Waveform (200Hz, 20%)                                                     | Generic  | 8.89     | ±9.6                   |
| 10354 | AAA  | Pulse Waveform (200Hz, 40%)                                                     | Generic  | 3.88     | ±9.6                   |
| 10355 | AAA  | Pulse Waveform (200Hz, 60%)                                                     | Generic  | 2.28     | ±9.6                   |
| 10356 | AAA  | Pulse Waveform (200Hz, 80%)                                                     | Generic  | 0.67     | ±9.6                   |
| 10387 | AAA  | QPSK Waveform, 1 MHz                                                            | Generic  | 5.10     | ±9.6                   |
| 10388 | AAA  | QPSK Waveform, 10 MHz                                                           | Generic  | 5.22     | ±9.6                   |
| 10389 | AAA  | 64-QAM Waveform, 100 kHz                                                        | Generic  | 6.27     | ±9.6                   |
| 10389 | AAA  | 64-QAM Waveform, 40 MHz                                                         | Generic  | 6.27     | ±9.6                   |
| 10400 | AAF  | IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99% duty cycle)                             | WLAN     | 8.57     | ±9.6                   |
| 10401 | AAF  | IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99% duty cycle)                             | WLAN     | 8.60     | ±9.6                   |
| 10402 | AAF  | IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99% duty cycle)                             | WLAN     | 8.63     | ±9.6                   |
| 10403 | AAB  | CDMA2000 (1xEV-DO, Rev. 3)                                                      | CDMA2000 | 3.76     | ±9.6                   |
| 10404 | AAB  | CDMA2000 (1xEV-DO, Rev. A)                                                      | CDMA2000 | 3.77     | ±9.6                   |
| 10406 | AAB  | CDMA2000, HCS, SS32, SCH0, Full Rate                                            | CDMA2000 | 5.22     | ±9.6                   |
| 10410 | AAH  | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Cont=4) | LTE-TDD  | 7.82     | ±9.6                   |
| 10414 | AAA  | WLAN CCK, 64 QAM, 40 MHz                                                        | Generic  | 8.54     | ±9.6                   |
| 10415 | AAA  | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99% duty cycle)                        | WLAN     | 1.54     | ±9.6                   |
| 10416 | AAA  | IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99% duty cycle)                    | WLAN     | 8.23     | ±9.6                   |
| 10417 | AAD  | IEEE 802.11a/n WiFi 5 GHz (OFDM, 6 Mbps, 99% duty cycle)                        | WLAN     | 8.23     | ±9.6                   |
| 10419 | AAA  | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99% duty cycle, Long preamble)    | WLAN     | 8.14     | ±9.6                   |
| 10419 | AAA  | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99% duty cycle, Short preamble)   | WLAN     | 8.19     | ±9.6                   |
| 10422 | AAD  | IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)                                    | WLAN     | 8.32     | ±9.6                   |
| 10423 | AAC  | IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)                                 | WLAN     | 8.47     | ±9.6                   |
| 10424 | AAD  | IEEE 802.11n (HT Greenfield, 72.8 Mbps, 64-QAM)                                 | WLAN     | 8.40     | ±9.6                   |
| 10425 | AAD  | IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)                                     | WLAN     | 8.41     | ±9.6                   |
| 10426 | AAD  | IEEE 802.11n (HT Greenfield, 30 Mbps, 16-QAM)                                   | WLAN     | 8.45     | ±9.6                   |
| 10427 | AAD  | IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)                                  | WLAN     | 8.41     | ±9.6                   |
| 10430 | AAE  | LTE-FDD (CDMA, 5 MHz, E-TM 3.1)                                                 | LTE-FDD  | 8.29     | ±9.6                   |
| 10431 | AAF  | LTE-FDD (CDMA, 10 MHz, E-TM 3.1)                                                | LTE-FDD  | 8.38     | ±9.6                   |
| 10432 | AAD  | LTE-FDD (CDMA, 15 MHz, E-TM 3.1)                                                | LTE-FDD  | 8.34     | ±9.6                   |
| 10433 | AAC  | LTE-FDD (CDMA, 20 MHz, E-TM 3.1)                                                | LTE-FDD  | 8.34     | ±9.6                   |
| 10434 | AAB  | WCDMA (BS Test Model 1, 84 DPCCH)                                               | WCDMA    | 8.88     | ±9.6                   |
| 10435 | AAG  | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10447 | AAE  | LTE-FDD (CDMA, 5 MHz, E-TM 3.1, Clipping 44%)                                   | LTE-FDD  | 7.58     | ±9.6                   |
| 10448 | AAE  | LTE-FDD (CDMA, 10 MHz, E-TM 3.1, Clipping 44%)                                  | LTE-FDD  | 7.53     | ±9.6                   |
| 10449 | AAE  | LTE-FDD (CDMA, 15 MHz, E-TM 3.1, Clipping 44%)                                  | LTE-FDD  | 7.51     | ±9.6                   |
| 10450 | AAE  | LTE-FDD (CDMA, 20 MHz, E-TM 3.1, Clipping 44%)                                  | LTE-FDD  | 7.49     | ±9.6                   |
| 10451 | AAB  | WCDMA (BS Test Model 1, 84 DPCCH, Clipping 44%)                                 | WCDMA    | 7.59     | ±9.6                   |
| 10453 | AAE  | Validation (Square, 10 ms, 1 ms)                                                | Test     | 10.00    | ±9.6                   |
| 10458 | AAD  | IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99% duty cycle)                            | WLAN     | 8.69     | ±9.6                   |
| 10457 | AAB  | UMTS-FDD (DC-HSDPA)                                                             | WCDMA    | 8.82     | ±9.6                   |
| 10458 | AAA  | CDMA2000 (1xEV-DO, Rev. B, 2 carriers)                                          | CDMA2000 | 8.55     | ±9.6                   |
| 10459 | AAA  | CDMA2000 (1xEV-DO, Rev. B, 3 carriers)                                          | CDMA2000 | 8.25     | ±9.6                   |
| 10460 | AAB  | UMTS-FDD (WCDMA, AMR)                                                           | WCDMA    | 2.39     | ±9.6                   |
| 10461 | AAC  | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 7.82     | ±9.6                   |
| 10462 | AAC  | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)               | LTE-TDD  | 8.30     | ±9.6                   |
| 10463 | AAC  | LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)               | LTE-TDD  | 8.58     | ±9.6                   |
| 10464 | AAD  | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10465 | AAD  | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.39     | ±9.6                   |
| 10466 | AAD  | LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 8.57     | ±9.6                   |
| 10467 | AAG  | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                   | LTE-TDD  | 7.82     | ±9.6                   |
| 10468 | AAG  | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 9.32     | ±9.6                   |
| 10469 | AAG  | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)                 | LTE-TDD  | 9.56     | ±9.6                   |
| 10470 | AAG  | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)                  | LTE-TDD  | 7.82     | ±9.6                   |
| 10471 | AAG  | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)                | LTE-TDD  | 9.32     | ±9.6                   |

Certificate No: EX-7732\_Jun25

Page 13 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev | Communication System Name                                            | Group   | PAR (dB) | Unc <sup>F</sup> k = 2 |
|-------|-----|----------------------------------------------------------------------|---------|----------|------------------------|
| 10472 | AAG | LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10473 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)       | LTE-TDD | 7.92     | ±9.6                   |
| 10474 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.37     | ±9.6                   |
| 10475 | AAF | LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10477 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.32     | ±9.6                   |
| 10478 | AAG | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 8.57     | ±9.6                   |
| 10479 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10480 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.18     | ±9.6                   |
| 10481 | AAC | LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.45     | ±9.6                   |
| 10482 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)      | LTE-TDD | 7.71     | ±9.6                   |
| 10483 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.39     | ±9.6                   |
| 10484 | AAD | LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.47     | ±9.6                   |
| 10485 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)      | LTE-TDD | 7.59     | ±9.6                   |
| 10486 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.58     | ±9.6                   |
| 10487 | AAG | LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 8.60     | ±9.6                   |
| 10488 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.70     | ±9.6                   |
| 10489 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.51     | ±9.6                   |
| 10490 | AAG | LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10491 | AAG | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.74     | ±9.6                   |
| 10492 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.41     | ±9.6                   |
| 10493 | AAF | LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.55     | ±9.6                   |
| 10494 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.74     | ±9.6                   |
| 10495 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.37     | ±9.6                   |
| 10496 | AAG | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10497 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 7.57     | ±9.6                   |
| 10498 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9) | LTE-TDD | 8.48     | ±9.6                   |
| 10499 | AAC | LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9) | LTE-TDD | 8.88     | ±9.6                   |
| 10500 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.87     | ±9.6                   |
| 10501 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.44     | ±9.6                   |
| 10502 | AAD | LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.52     | ±9.6                   |
| 10503 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)     | LTE-TDD | 7.72     | ±9.6                   |
| 10504 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.31     | ±9.6                   |
| 10505 | AAG | LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)   | LTE-TDD | 8.54     | ±9.6                   |
| 10506 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10507 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.36     | ±9.6                   |
| 10508 | AAG | LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.55     | ±9.6                   |
| 10509 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.99     | ±9.6                   |
| 10510 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.49     | ±9.6                   |
| 10511 | AAF | LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.51     | ±9.6                   |
| 10512 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)    | LTE-TDD | 7.74     | ±9.6                   |
| 10513 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.42     | ±9.6                   |
| 10514 | AAG | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)  | LTE-TDD | 8.45     | ±9.6                   |
| 10515 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)            | WLAN    | 1.58     | ±9.6                   |
| 10516 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)          | WLAN    | 1.57     | ±9.6                   |
| 10517 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)           | WLAN    | 1.58     | ±9.6                   |
| 10518 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)            | WLAN    | 8.23     | ±9.6                   |
| 10519 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)           | WLAN    | 8.30     | ±9.6                   |
| 10520 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)           | WLAN    | 8.12     | ±9.6                   |
| 10521 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)           | WLAN    | 7.97     | ±9.6                   |
| 10522 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)           | WLAN    | 8.45     | ±9.6                   |
| 10523 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)           | WLAN    | 8.08     | ±9.6                   |
| 10524 | AAD | IEEE 802.11a/n WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)           | WLAN    | 8.27     | ±9.6                   |
| 10525 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)                   | WLAN    | 8.36     | ±9.6                   |
| 10526 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)                   | WLAN    | 8.42     | ±9.6                   |
| 10527 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)                   | WLAN    | 8.21     | ±9.6                   |
| 10528 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)                   | WLAN    | 8.35     | ±9.6                   |
| 10529 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)                   | WLAN    | 8.36     | ±9.6                   |
| 10531 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)                   | WLAN    | 8.43     | ±9.6                   |
| 10532 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)                   | WLAN    | 8.29     | ±9.6                   |
| 10533 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)                   | WLAN    | 8.38     | ±9.6                   |
| 10534 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)                   | WLAN    | 8.45     | ±9.6                   |
| 10535 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)                   | WLAN    | 8.45     | ±9.6                   |
| 10536 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)                   | WLAN    | 8.32     | ±9.6                   |
| 10537 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)                   | WLAN    | 8.44     | ±9.6                   |
| 10538 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)                   | WLAN    | 8.54     | ±9.6                   |
| 10540 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)                   | WLAN    | 8.38     | ±9.6                   |

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev | Communication System Name                                       | Group | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|-----------------------------------------------------------------|-------|----------|------------------------|
| 10541 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)              | WLAN  | 8.46     | ±0.6                   |
| 10542 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)              | WLAN  | 8.65     | ±0.6                   |
| 10543 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)              | WLAN  | 8.65     | ±0.6                   |
| 10544 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)              | WLAN  | 8.47     | ±0.6                   |
| 10545 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS1, 99pc duty cycle)              | WLAN  | 8.55     | ±0.6                   |
| 10546 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)              | WLAN  | 8.35     | ±0.6                   |
| 10547 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)              | WLAN  | 8.49     | ±0.6                   |
| 10548 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)              | WLAN  | 8.37     | ±0.6                   |
| 10549 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS5, 99pc duty cycle)              | WLAN  | 8.38     | ±0.6                   |
| 10550 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)              | WLAN  | 8.50     | ±0.6                   |
| 10551 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)              | WLAN  | 8.42     | ±0.6                   |
| 10552 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)              | WLAN  | 8.45     | ±0.6                   |
| 10553 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)              | WLAN  | 8.40     | ±0.6                   |
| 10554 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)             | WLAN  | 8.47     | ±0.6                   |
| 10555 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)             | WLAN  | 8.50     | ±0.6                   |
| 10556 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)             | WLAN  | 8.52     | ±0.6                   |
| 10557 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)             | WLAN  | 8.61     | ±0.6                   |
| 10558 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS4, 99pc duty cycle)             | WLAN  | 8.73     | ±0.6                   |
| 10559 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS5, 99pc duty cycle)             | WLAN  | 8.56     | ±0.6                   |
| 10560 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)             | WLAN  | 8.60     | ±0.6                   |
| 10561 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)             | WLAN  | 8.77     | ±0.6                   |
| 10562 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS8, 99pc duty cycle)             | WLAN  | 8.25     | ±0.6                   |
| 10563 | AAE | IEEE 802.11ac WiFi (160 MHz, MCS9, 99pc duty cycle)             | WLAN  | 8.43     | ±0.6                   |
| 10564 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)  | WLAN  | 8.13     | ±0.6                   |
| 10565 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle) | WLAN  | 8.00     | ±0.6                   |
| 10566 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle) | WLAN  | 8.07     | ±0.6                   |
| 10567 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle) | WLAN  | 8.10     | ±0.6                   |
| 10568 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle) | WLAN  | 8.30     | ±0.6                   |
| 10569 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle) | WLAN  | 1.98     | ±0.6                   |
| 10570 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle) | WLAN  | 1.99     | ±0.6                   |
| 10571 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)       | WLAN  | 1.98     | ±0.6                   |
| 10572 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)       | WLAN  | 1.98     | ±0.6                   |
| 10573 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)     | WLAN  | 1.98     | ±0.6                   |
| 10574 | AAA | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)      | WLAN  | 1.98     | ±0.6                   |
| 10575 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle)  | WLAN  | 8.30     | ±0.6                   |
| 10576 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)  | WLAN  | 8.36     | ±0.6                   |
| 10577 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle) | WLAN  | 8.48     | ±0.6                   |
| 10578 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle) | WLAN  | 8.36     | ±0.6                   |
| 10579 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle) | WLAN  | 8.78     | ±0.6                   |
| 10580 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle) | WLAN  | 8.35     | ±0.6                   |
| 10581 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle) | WLAN  | 8.57     | ±0.6                   |
| 10582 | AAA | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle) | WLAN  | 8.59     | ±0.6                   |
| 10583 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 8 Mbps, 99pc duty cycle)        | WLAN  | 8.70     | ±0.6                   |
| 10584 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)        | WLAN  | 8.48     | ±0.6                   |
| 10585 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)       | WLAN  | 8.36     | ±0.6                   |
| 10586 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)       | WLAN  | 8.78     | ±0.6                   |
| 10587 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)       | WLAN  | 8.35     | ±0.6                   |
| 10588 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)       | WLAN  | 8.67     | ±0.6                   |
| 10589 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)       | WLAN  | 8.83     | ±0.6                   |
| 10590 | AAD | IEEE 802.11ah WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)       | WLAN  | 8.79     | ±0.6                   |
| 10591 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 99pc duty cycle)          | WLAN  | 8.78     | ±0.6                   |
| 10592 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 99pc duty cycle)          | WLAN  | 8.84     | ±0.6                   |
| 10593 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 99pc duty cycle)          | WLAN  | 8.74     | ±0.6                   |
| 10594 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 99pc duty cycle)          | WLAN  | 8.74     | ±0.6                   |
| 10595 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 99pc duty cycle)          | WLAN  | 8.71     | ±0.6                   |
| 10596 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 99pc duty cycle)          | WLAN  | 8.72     | ±0.6                   |
| 10597 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 99pc duty cycle)          | WLAN  | 8.50     | ±0.6                   |
| 10598 | AAD | IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 99pc duty cycle)          | WLAN  | 8.79     | ±0.6                   |
| 10599 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 99pc duty cycle)          | WLAN  | 8.80     | ±0.6                   |
| 10600 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 99pc duty cycle)          | WLAN  | 8.82     | ±0.6                   |
| 10601 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 99pc duty cycle)          | WLAN  | 8.94     | ±0.6                   |
| 10602 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 99pc duty cycle)          | WLAN  | 8.93     | ±0.6                   |
| 10603 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 99pc duty cycle)          | WLAN  | 8.76     | ±0.6                   |
| 10604 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 99pc duty cycle)          | WLAN  | 8.97     | ±0.6                   |
| 10605 | AAD | IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 99pc duty cycle)          | WLAN  | 8.82     | ±0.6                   |
| 10606 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)              | WLAN  | 8.64     | ±0.6                   |
| 10607 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)              | WLAN  | 8.77     | ±0.6                   |

Certificate No: EX-7732\_Jun25

Page 15 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev | Communication System Name                              | Group     | PAR (dB) | Unc <sup>F</sup> k = 2 |
|-------|-----|--------------------------------------------------------|-----------|----------|------------------------|
| 10609 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.57     | ±9.6                   |
| 10610 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.78     | ±9.6                   |
| 10611 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.70     | ±9.6                   |
| 10612 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.77     | ±9.6                   |
| 10613 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.94     | ±9.6                   |
| 10614 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.59     | ±9.6                   |
| 10615 | AAD | IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10616 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10617 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10618 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.58     | ±9.6                   |
| 10619 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.88     | ±9.6                   |
| 10620 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.87     | ±9.6                   |
| 10621 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.77     | ±9.6                   |
| 10622 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.89     | ±9.6                   |
| 10623 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.82     | ±9.6                   |
| 10624 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.96     | ±9.6                   |
| 10625 | AAD | IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)     | WLAN      | 8.98     | ±9.6                   |
| 10626 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)     | WLAN      | 8.93     | ±9.6                   |
| 10627 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)     | WLAN      | 8.88     | ±9.6                   |
| 10628 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)     | WLAN      | 8.71     | ±9.6                   |
| 10629 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)     | WLAN      | 8.85     | ±9.6                   |
| 10630 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)     | WLAN      | 8.72     | ±9.6                   |
| 10631 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10632 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)     | WLAN      | 8.74     | ±9.6                   |
| 10633 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)     | WLAN      | 8.83     | ±9.6                   |
| 10634 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)     | WLAN      | 8.80     | ±9.6                   |
| 10635 | AAD | IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)     | WLAN      | 8.81     | ±9.6                   |
| 10636 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)    | WLAN      | 8.83     | ±9.6                   |
| 10637 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)    | WLAN      | 8.79     | ±9.6                   |
| 10638 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)    | WLAN      | 8.86     | ±9.6                   |
| 10639 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)    | WLAN      | 8.85     | ±9.6                   |
| 10640 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)    | WLAN      | 8.86     | ±9.6                   |
| 10641 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)    | WLAN      | 8.06     | ±9.6                   |
| 10642 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)    | WLAN      | 8.06     | ±9.6                   |
| 10643 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)    | WLAN      | 8.69     | ±9.6                   |
| 10644 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)    | WLAN      | 8.05     | ±9.6                   |
| 10645 | AAD | IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)    | WLAN      | 8.11     | ±9.6                   |
| 10646 | AAH | LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe-2,7)  | LTE-TDD   | 11.86    | ±9.6                   |
| 10647 | AAH | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe-2,7) | LTE-TDD   | 11.86    | ±9.6                   |
| 10648 | AAA | CDMA2000 (1x Advanced)                                 | CDMA2000  | 3.45     | ±9.6                   |
| 10652 | AAH | LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)         | LTE-TDD   | 8.91     | ±9.6                   |
| 10653 | AAH | LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 7.42     | ±9.6                   |
| 10654 | AAH | LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 8.86     | ±9.6                   |
| 10655 | AAH | LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)        | LTE-TDD   | 7.21     | ±9.6                   |
| 10658 | AAH | Pulse Waveform (200Hz, 10%)                            | Test      | 10.00    | ±9.6                   |
| 10659 | AAH | Pulse Waveform (200Hz, 20%)                            | Test      | 8.59     | ±9.6                   |
| 10660 | AAH | Pulse Waveform (200Hz, 40%)                            | Test      | 3.96     | ±9.6                   |
| 10661 | AAH | Pulse Waveform (200Hz, 60%)                            | Test      | 2.22     | ±9.6                   |
| 10662 | AAH | Pulse Waveform (200Hz, 80%)                            | Test      | 0.97     | ±9.6                   |
| 10670 | AAA | Bluetooth Low Energy                                   | Bluetooth | 2.19     | ±9.6                   |
| 10671 | AAC | IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)          | WLAN      | 8.09     | ±9.6                   |
| 10672 | AAC | IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)          | WLAN      | 8.57     | ±9.6                   |
| 10673 | AAC | IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)          | WLAN      | 8.78     | ±9.6                   |
| 10674 | AAC | IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)          | WLAN      | 8.74     | ±9.6                   |
| 10675 | AAC | IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)          | WLAN      | 8.90     | ±9.6                   |
| 10676 | AAC | IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)          | WLAN      | 8.77     | ±9.6                   |
| 10677 | AAC | IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)          | WLAN      | 8.73     | ±9.6                   |
| 10678 | AAC | IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)          | WLAN      | 8.78     | ±9.6                   |
| 10679 | AAC | IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)          | WLAN      | 8.69     | ±9.6                   |
| 10680 | AAC | IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)          | WLAN      | 8.80     | ±9.6                   |
| 10681 | AAC | IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)         | WLAN      | 8.62     | ±9.6                   |
| 10682 | AAC | IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)         | WLAN      | 8.83     | ±9.6                   |
| 10683 | AAC | IEEE 802.11ax (20 MHz, MCS0, 99pc duty cycle)          | WLAN      | 8.42     | ±9.6                   |
| 10684 | AAC | IEEE 802.11ax (20 MHz, MCS1, 99pc duty cycle)          | WLAN      | 8.26     | ±9.6                   |
| 10685 | AAC | IEEE 802.11ax (20 MHz, MCS2, 99pc duty cycle)          | WLAN      | 8.33     | ±9.6                   |
| 10686 | AAC | IEEE 802.11ax (20 MHz, MCS3, 99pc duty cycle)          | WLAN      | 8.28     | ±9.6                   |

Certificate No: EX-7732\_Jun25

Page 16 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev | Communication System Name                      | Group | PAR (dB) | Unc <sup>k</sup> k = 2 |
|-------|-----|------------------------------------------------|-------|----------|------------------------|
| 10687 | AAC | IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.45     | ±9.8                   |
| 10688 | AAC | IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.29     | ±9.8                   |
| 10689 | AAC | IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.55     | ±9.8                   |
| 10690 | AAC | IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.29     | ±9.8                   |
| 10691 | AAC | IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.25     | ±9.8                   |
| 10692 | AAC | IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.29     | ±9.8                   |
| 10693 | AAC | IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.25     | ±9.8                   |
| 10694 | AAC | IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.57     | ±9.8                   |
| 10695 | AAC | IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.78     | ±9.8                   |
| 10696 | AAC | IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.91     | ±9.8                   |
| 10697 | AAC | IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.61     | ±9.8                   |
| 10698 | AAC | IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.89     | ±9.8                   |
| 10699 | AAC | IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.82     | ±9.8                   |
| 10700 | AAC | IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.73     | ±9.8                   |
| 10701 | AAC | IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.89     | ±9.8                   |
| 10702 | AAC | IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.70     | ±9.8                   |
| 10703 | AAC | IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.82     | ±9.8                   |
| 10704 | AAC | IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.58     | ±9.8                   |
| 10705 | AAC | IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.89     | ±9.8                   |
| 10706 | AAC | IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.86     | ±9.8                   |
| 10707 | AAC | IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.32     | ±9.8                   |
| 10708 | AAC | IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.55     | ±9.8                   |
| 10709 | AAC | IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.39     | ±9.8                   |
| 10710 | AAC | IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.29     | ±9.8                   |
| 10711 | AAC | IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.39     | ±9.8                   |
| 10712 | AAC | IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.67     | ±9.8                   |
| 10713 | AAC | IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.39     | ±9.8                   |
| 10714 | AAC | IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)  | WLAN  | 9.28     | ±9.8                   |
| 10715 | AAC | IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.46     | ±9.8                   |
| 10716 | AAC | IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)  | WLAN  | 9.30     | ±9.8                   |
| 10717 | AAC | IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.48     | ±9.8                   |
| 10718 | AAC | IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle) | WLAN  | 9.24     | ±9.8                   |
| 10719 | AAC | IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.81     | ±9.8                   |
| 10720 | AAC | IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.67     | ±9.8                   |
| 10721 | AAC | IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.76     | ±9.8                   |
| 10722 | AAC | IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.65     | ±9.8                   |
| 10723 | AAC | IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.70     | ±9.8                   |
| 10724 | AAC | IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.90     | ±9.8                   |
| 10725 | AAC | IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.74     | ±9.8                   |
| 10726 | AAC | IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.72     | ±9.8                   |
| 10727 | AAC | IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.88     | ±9.8                   |
| 10728 | AAC | IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.65     | ±9.8                   |
| 10729 | AAC | IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.64     | ±9.8                   |
| 10730 | AAC | IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.67     | ±9.8                   |
| 10731 | AAC | IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)  | WLAN  | 8.42     | ±9.8                   |
| 10732 | AAC | IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)  | WLAN  | 8.46     | ±9.8                   |
| 10733 | AAC | IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)  | WLAN  | 8.49     | ±9.8                   |
| 10734 | AAC | IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)  | WLAN  | 8.25     | ±9.8                   |
| 10735 | AAC | IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)  | WLAN  | 8.33     | ±9.8                   |
| 10736 | AAC | IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)  | WLAN  | 8.27     | ±9.8                   |
| 10737 | AAC | IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)  | WLAN  | 8.36     | ±9.8                   |
| 10738 | AAC | IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)  | WLAN  | 8.42     | ±9.8                   |
| 10739 | AAC | IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)  | WLAN  | 8.29     | ±9.8                   |
| 10740 | AAC | IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)  | WLAN  | 8.48     | ±9.8                   |
| 10741 | AAC | IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle) | WLAN  | 8.40     | ±9.8                   |
| 10742 | AAC | IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle) | WLAN  | 8.43     | ±9.8                   |
| 10743 | AAC | IEEE 802.11ax (160 MHz, MCS0, 99pc duty cycle) | WLAN  | 8.94     | ±9.8                   |
| 10744 | AAC | IEEE 802.11ax (160 MHz, MCS1, 99pc duty cycle) | WLAN  | 9.16     | ±9.8                   |
| 10745 | AAC | IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle) | WLAN  | 8.93     | ±9.8                   |
| 10746 | AAC | IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle) | WLAN  | 9.11     | ±9.8                   |
| 10747 | AAC | IEEE 802.11ax (160 MHz, MCS4, 99pc duty cycle) | WLAN  | 9.04     | ±9.8                   |
| 10748 | AAC | IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle) | WLAN  | 8.93     | ±9.8                   |
| 10749 | AAC | IEEE 802.11ax (160 MHz, MCS6, 99pc duty cycle) | WLAN  | 8.90     | ±9.8                   |
| 10750 | AAC | IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle) | WLAN  | 9.79     | ±9.8                   |
| 10751 | AAC | IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle) | WLAN  | 8.82     | ±9.8                   |
| 10752 | AAC | IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle) | WLAN  | 9.01     | ±9.8                   |

Certificate No: EX-7732\_Jun25

Page 17 of 21

EX3DV4 - SN:7732

June 25, 2025

| UID   | Rev | Communication System Name                       | Group         | PAR (dB) | Unc <sup>1</sup> k = 2 |
|-------|-----|-------------------------------------------------|---------------|----------|------------------------|
| 10753 | AAC | IEEE 802.11ax (160 MHz, MCS10, 80pc duty cycle) | WLAN          | 9.05     | ±9.5                   |
| 10754 | AAC | IEEE 802.11ax (160 MHz, MCS11, 80pc duty cycle) | WLAN          | 8.84     | ±9.5                   |
| 10755 | AAC | IEEE 802.11ax (160 MHz, MCS3, 88pc duty cycle)  | WLAN          | 8.84     | ±9.5                   |
| 10756 | AAC | IEEE 802.11ax (160 MHz, MCS1, 88pc duty cycle)  | WLAN          | 8.77     | ±9.5                   |
| 10757 | AAC | IEEE 802.11ax (160 MHz, MCS2, 88pc duty cycle)  | WLAN          | 8.77     | ±9.5                   |
| 10758 | AAC | IEEE 802.11ax (160 MHz, MCS3, 88pc duty cycle)  | WLAN          | 8.69     | ±9.5                   |
| 10759 | AAC | IEEE 802.11ax (160 MHz, MCS4, 88pc duty cycle)  | WLAN          | 8.58     | ±9.5                   |
| 10760 | AAC | IEEE 802.11ax (160 MHz, MCS5, 88pc duty cycle)  | WLAN          | 8.48     | ±9.5                   |
| 10761 | AAC | IEEE 802.11ax (160 MHz, MCS6, 88pc duty cycle)  | WLAN          | 8.58     | ±9.5                   |
| 10762 | AAC | IEEE 802.11ax (160 MHz, MCS7, 88pc duty cycle)  | WLAN          | 8.49     | ±9.5                   |
| 10763 | AAC | IEEE 802.11ax (160 MHz, MCS8, 88pc duty cycle)  | WLAN          | 8.53     | ±9.5                   |
| 10764 | AAC | IEEE 802.11ax (160 MHz, MCS3, 88pc duty cycle)  | WLAN          | 8.54     | ±9.5                   |
| 10765 | AAC | IEEE 802.11ax (160 MHz, MCS10, 88pc duty cycle) | WLAN          | 8.54     | ±9.5                   |
| 10766 | AAC | IEEE 802.11ax (160 MHz, MCS11, 88pc duty cycle) | WLAN          | 8.51     | ±9.5                   |
| 10767 | AAG | 5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)      | 5G NR FR1 TDD | 7.99     | ±9.5                   |
| 10768 | AAG | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.5                   |
| 10769 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.5                   |
| 10770 | AAG | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.5                   |
| 10771 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.5                   |
| 10772 | AAG | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.23     | ±9.5                   |
| 10773 | AAG | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.03     | ±9.5                   |
| 10774 | AAG | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)     | 5G NR FR1 TDD | 8.02     | ±9.5                   |
| 10775 | AAG | 5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)    | 5G NR FR1 TDD | 8.31     | ±9.5                   |
| 10776 | AAG | 5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.30     | ±9.5                   |
| 10777 | AAG | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.30     | ±9.5                   |
| 10778 | AAG | 5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.5                   |
| 10779 | AAG | 5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.42     | ±9.5                   |
| 10780 | AAG | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.39     | ±9.5                   |
| 10781 | AAG | 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.38     | ±9.5                   |
| 10782 | AAG | 5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.43     | ±9.5                   |
| 10783 | AAG | 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)   | 5G NR FR1 TDD | 8.31     | ±9.5                   |
| 10784 | AAG | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.29     | ±9.5                   |
| 10785 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.40     | ±9.5                   |
| 10786 | AAG | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.35     | ±9.5                   |
| 10787 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.44     | ±9.5                   |
| 10788 | AAG | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.5                   |
| 10789 | AAG | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.37     | ±9.5                   |
| 10790 | AAG | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)  | 5G NR FR1 TDD | 8.39     | ±9.5                   |
| 10791 | AAG | 5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)      | 5G NR FR1 TDD | 7.89     | ±9.5                   |
| 10792 | AAG | 5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.92     | ±9.5                   |
| 10793 | AAD | 5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.95     | ±9.5                   |
| 10794 | AAG | 5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.92     | ±9.5                   |
| 10795 | AAD | 5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.84     | ±9.5                   |
| 10796 | AAG | 5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.82     | ±9.5                   |
| 10797 | AAG | 5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 8.01     | ±9.5                   |
| 10798 | AAG | 5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.89     | ±9.5                   |
| 10799 | AAG | 5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.93     | ±9.5                   |
| 10800 | AAG | 5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.88     | ±9.5                   |
| 10801 | AAH | 5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.88     | ±9.5                   |
| 10802 | AAG | 5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)     | 5G NR FR1 TDD | 7.87     | ±9.5                   |
| 10803 | AAH | 5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)    | 5G NR FR1 TDD | 7.58     | ±9.5                   |
| 10805 | AAG | 5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.5                   |
| 10806 | AAD | 5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.57     | ±9.5                   |
| 10809 | AAG | 5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.5                   |
| 10810 | AAG | 5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.34     | ±9.5                   |
| 10812 | AAG | 5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.35     | ±9.5                   |
| 10817 | AAG | 5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)   | 5G NR FR1 TDD | 8.35     | ±9.5                   |
| 10818 | AAG | 5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.34     | ±9.5                   |
| 10819 | AAD | 5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.33     | ±9.5                   |
| 10820 | AAG | 5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.35     | ±9.5                   |
| 10821 | AAD | 5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.5                   |
| 10822 | AAG | 5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.5                   |
| 10823 | AAG | 5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.36     | ±9.5                   |
| 10824 | AAG | 5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.35     | ±9.5                   |
| 10825 | AAG | 5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.41     | ±9.5                   |
| 10827 | AAG | 5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.42     | ±9.5                   |
| 10828 | AAG | 5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)  | 5G NR FR1 TDD | 8.43     | ±9.5                   |

Certificate No: EX-7732\_Jun25

Page 18 of 21