

TEST REPORT

FCC PART 25 SCS Test for SM-A276U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2604-FC038-R1

DATE OF ISSUE
May 20, 2026

Tested by
Jae Ryang Do



Technical Manager
Kwon Jeong



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO



HCT CO., LTD.

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2604-FC038-R1

DATE OF ISSUE

May 20, 2026

Additional Model

SM-A276U1, SM-S276V

Applicant

SAMSUNG Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-A276U

Date of Test

March 11, 2026 ~ April 22, 2026

FCC ID

A3LSMA276U

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

Test Standard Used

FCC 47 CFR PART 25

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 24, 2026	Initial Release
1	May 20, 2026	Deleted the test report number(HCT-RF-2604-FC020) on page 7

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
2. INTRODUCTION	6
2.1. DESCRIPTION OF EUT	6
2.2. MEASURING INSTRUMENT CALIBRATION	6
2.3. TEST FACILITY	6
2.4. EQUIPMENT	6
3. SUPPLEMENTAL COVERAGE FROM SPACE (SCS)	7

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§ 25
EUT Type:	Mobile Phone
Model(s):	SM-A276U
Additional Model(s)	SM-A276U1, SM-S276V

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea.

Detailed description of test facility was submitted to the Commission and accepted dated February 26, 2026 (Registration Number: KR0032).

2.4. EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to ANSI/USEMCSC C63.2-2023, "American National Standard for Specifications of Electromagnetic Interference and Field Strength Measuring Instrumentation in the Frequency Range 9 kHz to 40 GHz".

3. SUPPLEMENTAL COVERAGE FROM SPACE (SCS)

Under section § 25.109 (f) of the FCC rules Space and SCS earth stations providing SCS are subject to technical rules in parts 2, 22, 24, and 27 of this chapter based on the operating frequency band.

Section § 25.204 (g) specifies that earth stations providing SCS pursuant to § § 25.125 and 25.115 shall comply with the power requirements and out-of-band emission limits corresponding to devices operating in parts 22, 24, or 27 of this chapter (e.g., § 22.913, § 24.232, § 27.50), as required for their operating frequencies. We have clarified through KDB inquiry that the technical requirements from Part 90R should be applied for SCS operations in the 700 MHz Public Safety Band.

The table below identifies the SCS frequencies available for use and, for each band, the applicable FCC Part 22, 24, 27, and 90R technical requirements, the air interfaces supported by the device for SCS use and, in the final column, the reference to the test report containing the relevant test data showing compliance with the technical requirements.

The bands available for SCS and the bands supported by the devices in the scope of this report are:

Band	Frequency		Part 22/24/27 Rule parts	3GPP Band	Supported	Reference to test report showing compliance with § 25.204 (g) for power requirements and out-of- band emission limits
	DL (MHz)	UL (MHz)				
600 MHz:	614-652	663-698	27.5 (c) 27.50 (c) 27.53 (g)	B71/ n71	Yes	B71: HCT-RF-2604-FC025 n71: HCT-RF-2604-FC033
700 MHz: 698 –769 MHz 775 –799 MHz 805 –806 MHz	729 – 746	699 –716	27.5 (c) 27.50 (c) 27.53 (g)	B12	Yes	HCT-RF-2604-FC015
	746 – 756	777 – 787	27.5 (b) 27.50 (b) 27.53 (f)	B13	Yes	HCT-RF-2604-FC016
	758 - 769	788 - 799	90R	B14	Yes	HCT-RF-2604-FC017
	805-806 MHz				No	-
800 MHz:	869 - 894	824-849	22H	WCDMA B5 B5/ n5 B26	Yes	WCDMA B5: HCT-RF-2604-FC013 B5: HCT-RF-2604-FC019 n5: HCT-RF-2604-FC026 B26: HCT-RF-2604-FC019
Broadband PCS:	1930 - 1995	1850-1915	24E	WCDMA B2 B2/ n2 B25/ n25	Yes	WCDMA B2: HCT-RF-2604-FC013 B2: HCT-RF-2604-FC018 N2: HCT-RF-2604-FC027 B25: HCT-RF-2604-FC018 N25: HCT-RF-2604-FC027

Note 1: Test reports are for the reference model FCC ID A3LSMA276U.