

TEST REPORT

FCC LTE B66(4) Test for SM-A276U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2604-FC024

DATE OF ISSUE
April 23, 2026

Tested by
Jae Ryang Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
BongJai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2604-FC024

DATE OF ISSUE

April 23, 2026

Additional Model

SM-A276U1, SM-S276V

Applicant**SAMSUNG Electronics Co., Ltd.**

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-A276U

Date of Test

March 11, 2026 ~ April 22, 2026

FCC ID

A3LSMA276U

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

Test Standard Used

FCC Rule Part: §27

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 23, 2026	Initial Release

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	6
1.1. MAXIMUM OUTPUT POWER	7
2. INTRODUCTION	9
2.1. DESCRIPTION OF EUT	9
2.2. MEASURING INSTRUMENT CALIBRATION	9
2.3. TEST FACILITY	9
2.4. EQUIPMENT	9
3. DESCRIPTION OF TESTS	10
3.1 TEST PROCEDURE	10
3.2 RADIATED POWER	11
3.3 RADIATED SPURIOUS EMISSIONS	12
3.4 PEAK- TO- AVERAGE RATIO	13
3.5 OCCUPIED BANDWIDTH.	14
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	15
3.7 BAND EDGE	16
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	18
3.9 WORST CASE(RADIATED TEST)	19
3.10 WORST CASE(CONDUCTED TEST)	20
4. LIST OF TEST EQUIPMENT	21
5. MEASUREMENT UNCERTAINTY	22
6. SUMMARY OF TEST RESULTS	23
7. SAMPLE CALCULATION	24
8. TEST DATA(Main 1 ANT)	26
8.1 EQUIVALENT ISOTROPIC RADIATED POWER	26
8.2 RADIATED SPURIOUS EMISSIONS	29
8.3 PEAK-TO-AVERAGE RATIO	30
8.4 OCCUPIED BANDWIDTH	31
8.5 CONDUCTED SPURIOUS EMISSIONS	32
8.6 BAND EDGE	32
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	33
9. TEST DATA(Sub 2-2 ANT)	51
9.1 EQUIVALENT ISOTROPIC RADIATED POWER	51
9.2 RADIATED SPURIOUS EMISSIONS	54
9.3 PEAK-TO-AVERAGE RATIO	55
9.4 OCCUPIED BANDWIDTH	56
9.5 CONDUCTED SPURIOUS EMISSIONS	57
9.6 BAND EDGE	57
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	58
10. TEST PLOTS(Main 1 ANT)	76
10.1 PEAK-TO-AVERAGE RATIO	77
10.2 OCCUPIED BANDWIDTH	101
10.3 CONDUCTED SPURIOUS EMISSIONS	125
10.4 BAND EDGE	161
11. TEST PLOTS(Sub 2-2 ANT)	197
11.1 PEAK-TO-AVERAGE RATIO	198
11.2 OCCUPIED BANDWIDTH	222

11.3 CONDUCTED SPURIOUS EMISSIONS	246
11.4 BAND EDGE	282
12. ANNEX A_ TEST SETUP PHOTO.....	318

MEASUREMENT REPORT

1. GENERAL INFORMATION

Model(s):	SM-A276U
Additional Model(s)	SM-A276U1, SM-S276V
Tx Frequency:	1710.7 MHz – 1779.3 MHz (LTE – Band 66/4 (1.4 MHz)) 1711.5 MHz – 1778.5 MHz (LTE – Band 66/4 (3 MHz)) 1712.5 MHz – 1777.5 MHz (LTE – Band 66/4 (5 MHz)) 1715.0 MHz – 1775.0 MHz (LTE – Band 66/4 (10 MHz)) 1717.5 MHz – 1772.5 MHz (LTE – Band 66/4 (15 MHz)) 1720.0 MHz – 1770.0 MHz (LTE – Band 66/4 (20 MHz))
Serial number:	Radiated : R37L300TJ6D Conducted : 9aece160ab127ece
Antenna Information	Please refer to the Antenna Specification document.

1.1. MAXIMUM OUTPUT POWER

Main 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band66/4 (1.4)	1710.7 – 1779.3	1M10G7D	QPSK	0.182	22.60
		1M10W7D	16-QAM	0.153	21.84
		1M10W7D	64-QAM	0.122	20.88
		1M10W7D	256-QAM	0.060	17.79
LTE – Band66/4 (3)	1711.5 – 1778.5	2M71G7D	QPSK	0.185	22.68
		2M71W7D	16-QAM	0.156	21.94
		2M71W7D	64-QAM	0.124	20.92
		2M71W7D	256-QAM	0.059	17.74
LTE – Band66/4 (5)	1712.5 – 1777.5	4M52G7D	QPSK	0.185	22.67
		4M52W7D	16-QAM	0.160	22.04
		4M52W7D	64-QAM	0.124	20.95
		4M53W7D	256-QAM	0.061	17.82
LTE – Band66/4 (10)	1715.0 – 1775.0	9M01G7D	QPSK	0.182	22.60
		9M01W7D	16-QAM	0.153	21.85
		9M01W7D	64-QAM	0.119	20.76
		8M98W7D	256-QAM	0.059	17.68
LTE – Band66/4 (15)	1717.5 – 1772.5	13M5G7D	QPSK	0.173	22.37
		13M4W7D	16-QAM	0.145	21.60
		13M5W7D	64-QAM	0.112	20.49
		13M5W7D	256-QAM	0.054	17.34
LTE – Band66/4 (20)	1720.0 – 1770.0	18M0G7D	QPSK	0.178	22.50
		17M9W7D	16-QAM	0.145	21.61
		17M9W7D	64-QAM	0.114	20.57
		17M9W7D	256-QAM	0.057	17.59

Sub 2-2 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band66/4 (1.4)	1710.7 – 1779.3	1M10G7D	QPSK	0.147	21.68
		1M10W7D	16-QAM	0.127	21.03
		1M10W7D	64-QAM	0.098	19.92
		1M10W7D	256-QAM	0.048	16.78
LTE – Band66/4 (3)	1711.5 – 1778.5	2M71G7D	QPSK	0.148	21.71
		2M71W7D	16-QAM	0.124	20.94
		2M71W7D	64-QAM	0.096	19.84
		2M72W7D	256-QAM	0.048	16.84
LTE – Band66/4 (5)	1712.5 – 1777.5	4M53G7D	QPSK	0.149	21.72
		4M53W7D	16-QAM	0.126	21.02
		4M52W7D	64-QAM	0.099	19.95
		4M52W7D	256-QAM	0.048	16.80
LTE – Band66/4 (10)	1715.0 – 1775.0	9M02G7D	QPSK	0.144	21.58
		9M02W7D	16-QAM	0.120	20.79
		9M00W7D	64-QAM	0.094	19.75
		9M03W7D	256-QAM	0.048	16.84
LTE – Band66/4 (15)	1717.5 – 1772.5	13M5G7D	QPSK	0.138	21.39
		13M5W7D	16-QAM	0.115	20.59
		13M5W7D	64-QAM	0.091	19.59
		13M5W7D	256-QAM	0.045	16.55
LTE – Band66/4 (20)	1720.0 – 1770.0	18M0G7D	QPSK	0.135	21.31
		18M0W7D	16-QAM	0.116	20.65
		18M0W7D	64-QAM	0.091	19.57
		18M0W7D	256-QAM	0.046	16.64

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea.

Detailed description of test facility was submitted to the Commission and accepted dated February 26, 2026 (Registration Number: KR0032).

2.4. EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to ANSI/USEMCSC C63.2-2023, "American National Standard for Specifications of Electromagnetic Interference and Field Strength Measuring Instrumentation in the Frequency Range 9 kHz to 40 GHz".

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- KDB 971168 D01 v03r01 - Section 5.2.4 - ANSI C63.26-2015 - Section 5.2.1 & 5.2.4.2
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $>$ 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. No. of sweep points $> 2 \times$ span / RBW
4. Detector = Peak
5. Trace mode = Max Hold
6. The trace was allowed to stabilize
7. Test channel : Low/ Middle/ High
8. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning. The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.
The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup


Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

Test Notes

1. This test was performed using the spectrum analyzer's CCDF function.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq$ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep = 1001

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time > (Number of Points) $\times$ (Symbol Period)
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels(low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz/ RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 3 MHz(Main 1 ANT), 5 MHz(Sub 2-2 ANT))
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- LTE Band 66 (1710 – 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz) and they have the same Tune-up power. Therefore, test data provided in this report covers Band 4 as well as Band 66.
- SM-A276U & additional models were tested and the worst case results are reported.
(Worst case : SM-A276U)

[Main 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		X

[Sub 2-2 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
 - LTE Band 66 (1710 – 1780 MHz) overlaps the entire frequency range of LTE Band 4 (1710 - 1755 MHz) and they have the same Tune-up power. Therefore, test data provided in this report covers Band 4 as well as Band 66.
 - SM-A276U & additional models were tested and the worst case results are reported.
- (Worst case : SM-A276U)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	input 1 + 1.2G HPF+LNA	HCT CO., LTD.	F1L1	12/17/2026	Annual
RF Switching System	input 1 + 3.3 G HPF+LNA	HCT CO., LTD.	F1L2	12/17/2026	Annual
RF Switching System	input 1 + LNA	HCT CO., LTD.	F1L4	12/17/2026	Annual
RF Switching System	Input 2 + 6G HPF + LNA	HCT CO., LTD.	F1L7	12/17/2026	Annual
Broadband LNA	CBL18265035	CERNEX	22966	10/21/2026	Annual
Broadband LNA	CBL26405040	CERNEX	25956	02/09/2027	Annual
Power Splitter	11667B	Hewlett Packard	5001	04/01/2027	Annual
DC Power Supply	E3632A	Agilent	MY40010147	07/29/2026	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/05/2028	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/04/2027	Annual
Horn Antenna	BBHA 9120D	Schwarzbeck	147	08/07/2027	Biennial
Horn Antenna	BBHA 9120D	Schwarzbeck	9120D-1298	08/27/2027	Biennial
Horn Antenna	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna	BBHA 9170	Schwarzbeck	BBHA9170124	03/23/2027	Biennial
MXA SIGNAL ANALYZER	N9020A	Agilent	MY52090906	04/08/2027	Annual
20dB ATTENUATOR	8493C	HP	15233	12/10/2026	Annual
Spectrum Analyzer	FSV40	ROHDE & SCHWARZ	100931	07/28/2026	Annual
Wireless Communications Set	E5515C	Agilent	MY48360800	07/29/2026	Annual
Loop Antenna	FMZB1513	Schwarzbeck	1513-333	06/23/2027	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	00895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	SCHWARZBECK MESS-ELEKTRONIK	01135	08/19/2026	Biennial
Radio Communication Analyzer	MT8821C	Anritsu	6262094331	11/24/2026	Annual
Radio Communication Test Station	MT8000A	Anritsu	6272613402	08/18/2026	Annual
SIGNAL GENERATOR	SMB100A	ROHDE & SCHWARZ	177633	07/22/2026	Annual
Signal Analyzer	N9030B	KEYSIGHT	MY55480167	05/14/2026	Annual
SIGNAL ANALYZER	FSW67	ROHDE & SCHWARZ	101736	05/27/2026	Annual
Automation Software	FCC 2G/3G/4G Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC NR Conducted	HCT CO., LTD	-	-	-
Automation Software	FCC LTE Radiated	HCT CO., LTD	-	-	-
Automation Software	FCC NR Radiated	HCT CO., LTD	-	-	-

Note:

- Equipment whose calibration due date was updated during the test period was not used between the previous due date and the update. All reported measurements were performed using equipment within valid calibration.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of ANSI C63.5-2017.

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)

Parameter	Expanded Uncertainty ($\pm$ kHz)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.11 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.73 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.54 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.80 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.86 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.44 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

-. The decision rule applies 'simple acceptance'

6.1 Test Condition : Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§2.1051, §27.53(h)	$< 43 + 10\log_{10} (P[\text{Watts}])$ at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§2.1046	N/A	PASS Note1
Peak- to- Average Ratio	§27.50(d)(5)	$< 13 \text{ dB}$	PASS
Frequency stability / variation of ambient temperature	§2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. Refer to the SAR report.

6.2 Test Condition : Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§27.50(d)(4)	$< 1 \text{ Watts max. EIRP}$	PASS
Radiated Spurious and Harmonic Emissions	§2.1053, §27.53(h)	$< 43 + 10\log_{10} (P[\text{Watts}])$ for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 1 ANT)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1710.7	LTE B66/B4 (1.4 MHz)	QPSK	-20.38	13.16	10.04	2.06	H	<1.00	0.130	21.14	1	3
		16-QAM	-21.00	12.54	10.04	2.06	H		0.113	20.52		
		64-QAM	-22.14	11.40	10.04	2.06	H		0.087	19.38		
		256-QAM	-25.38	8.16	10.04	2.06	H		0.041	16.14		
1745		QPSK	-19.71	13.79	10.18	2.07	H		0.155	21.90	1	0
		16-QAM	-20.51	12.99	10.18	2.07	H		0.129	21.10		
		64-QAM	-21.70	11.80	10.18	2.07	H		0.098	19.91		
		256-QAM	-24.66	8.84	10.18	2.07	H		0.050	16.95		
1779.3		QPSK	-19.24	14.43	10.26	2.09	H		0.182	22.60	1	3
		16-QAM	-20.00	13.67	10.26	2.09	H		0.153	21.84		
		64-QAM	-20.96	12.71	10.26	2.09	H		0.122	20.88		
		256-QAM	-24.05	9.62	10.26	2.09	H		0.060	17.79		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1711.5	LTE B66/B4 (3 MHz)	QPSK	-20.33	13.21	10.04	2.06	H	<1.00	0.132	21.19	1	0
		16-QAM	-21.16	12.38	10.04	2.06	H		0.109	20.36		
		64-QAM	-22.06	11.48	10.04	2.06	H		0.088	19.46		
		256-QAM	-25.24	8.30	10.04	2.06	H		0.042	16.28		
1745		QPSK	-19.79	13.71	10.18	2.07	H		0.152	21.82	1	14
		16-QAM	-20.50	13.00	10.18	2.07	H		0.129	21.11		
		64-QAM	-21.58	11.92	10.18	2.07	H		0.101	20.03		
		256-QAM	-24.60	8.90	10.18	2.07	H		0.050	17.01		
1778.5		QPSK	-19.16	14.51	10.26	2.09	H		0.185	22.68	1	8
		16-QAM	-19.90	13.77	10.26	2.09	H		0.156	21.94		
		64-QAM	-20.92	12.75	10.26	2.09	H		0.124	20.92		
		256-QAM	-24.10	9.57	10.26	2.09	H		0.059	17.74		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1712.5	LTE B66/B4 (5 MHz)	QPSK	-20.31	13.22	10.06	2.06	H	<1.00	0.132	21.22	1	0
		16-QAM	-21.22	12.31	10.06	2.06	H		0.107	20.31		
		64-QAM	-22.23	11.30	10.06	2.06	H		0.085	19.30		
		256-QAM	-25.31	8.22	10.06	2.06	H		0.042	16.22		
1745		QPSK	-19.66	13.84	10.18	2.07	H		0.157	21.95	1	24
		16-QAM	-20.43	13.07	10.18	2.07	H		0.131	21.18		
		64-QAM	-21.51	11.99	10.18	2.07	H		0.102	20.10		
		256-QAM	-24.56	8.94	10.18	2.07	H		0.051	17.05		
1777.5		QPSK	-19.17	14.50	10.26	2.09	H		0.185	22.67	1	13
		16-QAM	-19.80	13.87	10.26	2.09	H		0.160	22.04		
		64-QAM	-20.89	12.78	10.26	2.09	H		0.124	20.95		
		256-QAM	-24.02	9.65	10.26	2.09	H		0.061	17.82		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1715	LTE B66/B4 (10 MHz)	QPSK	-20.38	13.15	10.06	2.06	H	<1.00	0.130	21.15	1	0
		16-QAM	-21.06	12.47	10.06	2.06	H		0.111	20.47		
		64-QAM	-22.13	11.40	10.06	2.06	H		0.087	19.40		
		256-QAM	-25.13	8.40	10.06	2.06	H		0.044	16.40		
1745		QPSK	-19.73	13.77	10.18	2.07	H		0.154	21.88	1	49
		16-QAM	-20.30	13.20	10.18	2.07	H		0.135	21.31		
		64-QAM	-21.43	12.07	10.18	2.07	H		0.104	20.18		
		256-QAM	-24.46	9.04	10.18	2.07	H		0.052	17.15		
1775		QPSK	-19.22	14.44	10.25	2.09	H		0.182	22.60	1	49
		16-QAM	-19.97	13.69	10.25	2.09	H		0.153	21.85		
		64-QAM	-21.06	12.60	10.25	2.09	H		0.119	20.76		
		256-QAM	-24.14	9.52	10.25	2.09	H		0.059	17.68		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1717.5	LTE B66/B4 (15 MHz)	QPSK	-20.41	13.11	10.08	2.06	H	<1.00	0.130	21.13	1	0
		16-QAM	-21.22	12.30	10.08	2.06	H		0.108	20.32		
		64-QAM	-22.35	11.17	10.08	2.06	H		0.083	19.19		
		256-QAM	-25.36	8.16	10.08	2.06	H		0.041	16.18		
1745		QPSK	-19.70	13.80	10.18	2.07	H		0.155	21.91	1	74
		16-QAM	-20.53	12.97	10.18	2.07	H		0.128	21.08		
		64-QAM	-21.44	12.06	10.18	2.07	H		0.104	20.17		
		256-QAM	-24.56	8.94	10.18	2.07	H		0.051	17.05		
1772.5		QPSK	-19.45	14.21	10.25	2.09	H		0.173	22.37	1	38
		16-QAM	-20.22	13.44	10.25	2.09	H		0.145	21.60		
		64-QAM	-21.33	12.33	10.25	2.09	H		0.112	20.49		
		256-QAM	-24.48	9.18	10.25	2.09	H		0.054	17.34		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1720	LTE B66/B4 (20 MHz)	QPSK	-20.30	13.22	10.08	2.06	H	<1.00	0.133	21.24	1	0
		16-QAM	-21.16	12.36	10.08	2.06	H		0.109	20.38		
		64-QAM	-22.32	11.20	10.08	2.06	H		0.084	19.22		
		256-QAM	-25.39	8.13	10.08	2.06	H		0.041	16.15		
1745		QPSK	-19.56	13.94	10.18	2.07	H		0.160	22.05	1	99
		16-QAM	-20.43	13.07	10.18	2.07	H		0.131	21.18		
		64-QAM	-21.51	11.99	10.18	2.07	H		0.102	20.10		
		256-QAM	-24.65	8.85	10.18	2.07	H		0.050	16.96		
1770		QPSK	-19.31	14.35	10.24	2.09	H		0.178	22.50	1	99
		16-QAM	-20.20	13.46	10.24	2.09	H		0.145	21.61		
		64-QAM	-21.24	12.42	10.24	2.09	H		0.114	20.57		
		256-QAM	-24.22	9.44	10.24	2.09	H		0.057	17.59		

8.2 RADIATED SPURIOUS EMISSIONS

■ MODE: LTE B66(4)
 ■ MODULATION SIGNAL: 3 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: -13 dBm

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
131987 (1711.5)	3 423.00	-42.68	12.43	-61.40	2.99	V	-51.96	1	0
		-42.83		-61.55		H	-52.11		
	5 134.50	-43.48	12.33	-56.38	3.81	V	-47.86		
		-43.54		-56.44		H	-47.92		
	6 846.00	-41.43	11.91	-48.99	4.35	V	-41.43		
		-39.94		-47.50		H	-39.94		
132322 (1745.0)	3 490.00	-43.53	12.34	-61.71	3.04	V	-52.41	1	14
		-43.05		-61.23		H	-51.93		
	5 235.00	-42.81	12.84	-55.45	3.78	V	-46.39		
		-42.45		-55.09		H	-46.03		
	6 980.00	-39.84	11.40	-46.31	4.48	V	-39.39		
		-41.24		-47.71		H	-40.79		
132657 (1778.5)	3 557.00	-43.65	12.34	-61.11	3.09	V	-51.86	1	8
		-42.79		-60.25		H	-51.00		
	5 335.50	-44.05	13.09	-57.65	3.79	V	-48.35		
		-43.22		-56.82		H	-47.52		
	7 114.00	-41.85	10.85	-46.55	4.47	V	-40.17		
		-41.34		-46.04		H	-39.66		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)	Limit (dB)
LTE B66/4	1.4 MHz	1745.0	QPSK	6	0	5.51	13.00
			16-QAM			6.30	
			64-QAM			6.78	
			256-QAM			7.05	
	3 MHz		QPSK	15		5.41	
			16-QAM			6.31	
			64-QAM			6.74	
			256-QAM			6.96	
	5 MHz		QPSK	25		5.46	
			16-QAM			6.30	
			64-QAM			6.71	
			256-QAM			6.93	
	10 MHz		QPSK	50		5.54	
			16-QAM			6.30	
			64-QAM			6.69	
			256-QAM			6.92	
	15 MHz		QPSK	75		5.46	
			16-QAM			6.30	
			64-QAM			6.70	
			256-QAM			6.88	
	20 MHz		QPSK	100		5.37	
			16-QAM			6.29	
			64-QAM			6.69	
			256-QAM			6.87	

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
LTE B66/4	1.4 MHz	1745.0	QPSK	6	0	1.1009
			16-QAM			1.1030
			64-QAM			1.0994
			256-QAM			1.0990
	3 MHz		QPSK	15		2.7128
			16-QAM			2.7132
			64-QAM			2.7105
			256-QAM			2.7114
	5 MHz		QPSK	25		4.5226
			16-QAM			4.5175
			64-QAM			4.5235
			256-QAM			4.5260
	10 MHz		QPSK	50		9.0047
			16-QAM			9.0100
			64-QAM			9.0114
			256-QAM			8.9843
	15 MHz		QPSK	75		13.463
			16-QAM			13.444
			64-QAM			13.464
			256-QAM			13.447
	20 MHz		QPSK	100		17.968
			16-QAM			17.917
			64-QAM			17.922
			256-QAM			17.855

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
LTE B66/4	1.4	1710.70	2.5823	27.976	-62.428	-34.452	-13.00
		1745.00	3.6990	27.976	-61.948	-33.972	
		1779.30	3.7089	27.976	-62.082	-34.106	
	3	1711.50	3.7388	27.976	-62.324	-34.348	
		1745.00	3.6890	27.976	-61.234	-33.258	
		1778.50	3.7388	27.976	-62.005	-34.029	
	5	1712.50	3.7189	27.976	-62.289	-34.313	
		1745.00	5.7727	28.591	-62.112	-33.521	
		1777.50	3.7189	27.976	-61.593	-33.617	
	10	1715.00	3.6990	27.976	-62.061	-34.085	
		1745.00	6.3111	28.591	-61.690	-33.099	
		1775.00	3.6890	27.976	-62.230	-34.254	
	15	1717.50	3.7089	27.976	-61.678	-33.702	
		1745.00	3.7289	27.976	-61.021	-33.045	
		1772.50	3.6691	27.976	-62.036	-34.060	
	20	1720.00	2.7020	27.976	-61.759	-33.783	
		1745.00	3.6790	27.976	-61.814	-33.838	
		1770.00	7.2184	28.591	-61.312	-32.721	

Note:

1. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Section 10.4.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1710,700,000 Hz</u>
CHANNEL:	<u>131979 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.880	+20(Ref)	1710 700 001	0.0	0.000 000	0.000
100 %		-30	1710 700 005	3.8	0.000 000	0.002
100 %		-20	1710 700 004	2.2	0.000 000	0.001
100 %		-10	1710 700 004	2.7	0.000 000	0.002
100 %		0	1710 699 999	-2.2	0.000 000	-0.001
100 %		+10	1710 700 004	2.8	0.000 000	0.002
100 %		+30	1710 700 004	2.2	0.000 000	0.001
100 %		+40	1710 700 003	2.0	0.000 000	0.001
100 %		+50	1710 700 000	-1.6	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1710 700 005	3.5	0.000 000	0.002




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1711,500,000 Hz</u>
CHANNEL:	<u>131987 (3 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1711 500 005	0.0	0.000 000	0.000
100 %		-30	1711 500 001	-3.8	0.000 000	-0.002
100 %		-20	1711 500 001	-3.3	0.000 000	-0.002
100 %		-10	1711 500 010	4.9	0.000 000	0.003
100 %		0	1711 500 007	2.4	0.000 000	0.001
100 %		+10	1711 500 002	-3.0	0.000 000	-0.002
100 %		+30	1711 499 999	-5.3	0.000 000	-0.003
100 %		+40	1711 500 007	2.8	0.000 000	0.002
100 %		+50	1711 500 002	-3.1	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1711 500 001	-4.1	0.000 000	-0.002




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1712,500,000 Hz</u>
CHANNEL:	<u>131997 (5 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1712 500 005	0.0	0.000 000	0.000
100 %		-30	1712 500 008	2.9	0.000 000	0.002
100 %		-20	1712 500 008	2.5	0.000 000	0.001
100 %		-10	1712 500 008	2.1	0.000 000	0.001
100 %		0	1712 500 003	-2.9	0.000 000	-0.002
100 %		+10	1712 500 008	2.3	0.000 000	0.001
100 %		+30	1712 500 008	2.5	0.000 000	0.001
100 %		+40	1712 500 008	2.5	0.000 000	0.001
100 %		+50	1712 500 010	4.3	0.000 000	0.003
Batt. Endpoint	3.300	+20	1712 500 003	-2.3	0.000 000	-0.001




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1715,000,000 Hz
 ■ CHANNEL: 132022 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1714 999 997	0.0	0.000 000	0.000
100 %		-30	1714 999 995	-1.6	0.000 000	-0.001
100 %		-20	1714 999 996	-1.3	0.000 000	-0.001
100 %		-10	1714 999 999	2.6	0.000 000	0.002
100 %		0	1714 999 995	-1.8	0.000 000	-0.001
100 %		+10	1714 999 995	-2.2	0.000 000	-0.001
100 %		+30	1714 999 999	1.7	0.000 000	0.001
100 %		+40	1714 999 995	-2.1	0.000 000	-0.001
100 %		+50	1714 999 995	-2.2	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1714 999 994	-2.8	0.000 000	-0.002




☐ MODE: LTE B66/4
☐ OPERATING FREQUENCY: 1717,500,000 Hz
☐ CHANNEL: 132047 (15 MHz)
☐ REFERENCE VOLTAGE: 3.880 VDC
☐ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1717 499 998	0.0	0.000 000	0.000
100 %		-30	1717 499 995	-2.4	0.000 000	-0.001
100 %		-20	1717 499 994	-3.2	0.000 000	-0.002
100 %		-10	1717 499 994	-3.6	0.000 000	-0.002
100 %		0	1717 499 994	-3.3	0.000 000	-0.002
100 %		+10	1717 499 993	-4.5	0.000 000	-0.003
100 %		+30	1717 499 994	-3.2	0.000 000	-0.002
100 %		+40	1717 499 995	-2.6	0.000 000	-0.002
100 %		+50	1717 499 995	-2.6	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1717 499 996	-1.7	0.000 000	-0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1720,000,000 Hz</u>
CHANNEL:	<u>132072 (20 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1719 999 998	0.0	0.000 000	0.000
100 %		-30	1719 999 999	1.5	0.000 000	0.001
100 %		-20	1719 999 995	-2.5	0.000 000	-0.001
100 %		-10	1719 999 996	-1.8	0.000 000	-0.001
100 %		0	1719 999 995	-2.8	0.000 000	-0.002
100 %		+10	1719 999 995	-2.9	0.000 000	-0.002
100 %		+30	1719 999 996	-2.0	0.000 000	-0.001
100 %		+40	1719 999 995	-2.6	0.000 000	-0.002
100 %		+50	1719 999 994	-3.6	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1719 999 996	-1.9	0.000 000	-0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1745,000,000 Hz</u>
CHANNEL:	<u>132322 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 003	0.0	0.000 000	0.000
100 %		-30	1745 000 000	-2.6	0.000 000	-0.001
100 %		-20	1745 000 005	1.8	0.000 000	0.001
100 %		-10	1745 000 008	5.7	0.000 000	0.003
100 %		0	1745 000 005	2.2	0.000 000	0.001
100 %		+10	1744 999 997	-5.4	0.000 000	-0.003
100 %		+30	1745 000 006	2.9	0.000 000	0.002
100 %		+40	1745 000 006	3.4	0.000 000	0.002
100 %		+50	1745 000 006	3.5	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 004	1.4	0.000 000	0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1745,000,000 Hz</u>
CHANNEL:	<u>132322 (3 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 003	0.0	0.000 000	0.000
100 %		-30	1744 999 999	-3.1	0.000 000	-0.002
100 %		-20	1745 000 001	-2.0	0.000 000	-0.001
100 %		-10	1745 000 006	3.3	0.000 000	0.002
100 %		0	1745 000 005	2.3	0.000 000	0.001
100 %		+10	1745 000 006	3.4	0.000 000	0.002
100 %		+30	1745 000 007	4.7	0.000 000	0.003
100 %		+40	1745 000 010	7.0	0.000 000	0.004
100 %		+50	1745 000 005	2.4	0.000 000	0.001
Batt. Endpoint	3.300	+20	1745 000 007	4.3	0.000 000	0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 132322 (5 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 005	0.0	0.000 000	0.000
100 %		-30	1745 000 008	3.4	0.000 000	0.002
100 %		-20	1745 000 003	-2.2	0.000 000	-0.001
100 %		-10	1745 000 009	3.9	0.000 000	0.002
100 %		0	1745 000 007	2.4	0.000 000	0.001
100 %		+10	1745 000 001	-3.4	0.000 000	-0.002
100 %		+30	1745 000 007	2.6	0.000 000	0.001
100 %		+40	1745 000 008	3.0	0.000 000	0.002
100 %		+50	1745 000 008	3.6	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 001	-3.7	0.000 000	-0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 132322 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1744 999 997	0.0	0.000 000	0.000
100 %		-30	1745 000 001	3.8	0.000 000	0.002
100 %		-20	1744 999 994	-2.6	0.000 000	-0.001
100 %		-10	1745 000 001	4.5	0.000 000	0.003
100 %		0	1744 999 993	-4.3	0.000 000	-0.002
100 %		+10	1744 999 993	-3.4	0.000 000	-0.002
100 %		+30	1745 000 001	4.3	0.000 000	0.002
100 %		+40	1745 000 003	5.7	0.000 000	0.003
100 %		+50	1744 999 993	-4.0	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1744 999 994	-3.1	0.000 000	-0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 132322 (15 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1744 999 997	0.0	0.000 000	0.000
100 %		-30	1744 999 994	-3.5	0.000 000	-0.002
100 %		-20	1744 999 993	-4.0	0.000 000	-0.002
100 %		-10	1744 999 993	-3.8	0.000 000	-0.002
100 %		0	1744 999 991	-6.1	0.000 000	-0.003
100 %		+10	1745 000 000	2.6	0.000 000	0.001
100 %		+30	1744 999 994	-3.7	0.000 000	-0.002
100 %		+40	1744 999 992	-5.1	0.000 000	-0.003
100 %		+50	1744 999 993	-4.3	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1744 999 993	-4.2	0.000 000	-0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 132322 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 003	0.0	0.000 000	0.000
100 %		-30	1745 000 000	-3.0	0.000 000	-0.002
100 %		-20	1744 999 998	-4.8	0.000 000	-0.003
100 %		-10	1745 000 000	-3.7	0.000 000	-0.002
100 %		0	1745 000 005	1.4	0.000 000	0.001
100 %		+10	1744 999 998	-5.6	0.000 000	-0.003
100 %		+30	1744 999 999	-4.7	0.000 000	-0.003
100 %		+40	1745 000 000	-3.3	0.000 000	-0.002
100 %		+50	1745 000 001	-2.0	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1744 999 999	-4.3	0.000 000	-0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1779,300,000 Hz
 ■ CHANNEL: 132665 (1.4 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1779 299 996	0.0	0.000 000	0.000
100 %		-30	1779 299 998	2.0	0.000 000	0.001
100 %		-20	1779 299 994	-2.3	0.000 000	-0.001
100 %		-10	1779 299 999	3.1	0.000 000	0.002
100 %		0	1779 299 998	1.7	0.000 000	0.001
100 %		+10	1779 299 994	-2.7	0.000 000	-0.002
100 %		+30	1779 299 999	2.4	0.000 000	0.001
100 %		+40	1779 299 994	-2.3	0.000 000	-0.001
100 %		+50	1779 299 999	2.3	0.000 000	0.001
Batt. Endpoint	3.300	+20	1779 300 001	4.7	0.000 000	0.003




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1778,500,000 Hz</u>
CHANNEL:	<u>132657 (3 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1778 499 990	0.0	0.000 000	0.000
100 %		-30	1778 499 984	-6.5	0.000 000	-0.004
100 %		-20	1778 499 984	-5.9	0.000 000	-0.003
100 %		-10	1778 499 980	-10.2	-0.000 001	-0.006
100 %		0	1778 499 984	-6.8	0.000 000	-0.004
100 %		+10	1778 499 994	3.4	0.000 000	0.002
100 %		+30	1778 499 982	-8.7	0.000 000	-0.005
100 %		+40	1778 499 997	6.5	0.000 000	0.004
100 %		+50	1778 499 999	9.0	0.000 001	0.005
Batt. Endpoint	3.300	+20	1778 499 999	8.5	0.000 000	0.005




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1777,500,000 Hz</u>
CHANNEL:	<u>132647 (5 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1777 499 998	0.0	0.000 000	0.000
100 %		-30	1777 499 999	1.6	0.000 000	0.001
100 %		-20	1777 500 001	2.8	0.000 000	0.002
100 %		-10	1777 499 996	-2.2	0.000 000	-0.001
100 %		0	1777 499 993	-4.5	0.000 000	-0.003
100 %		+10	1777 499 996	-2.2	0.000 000	-0.001
100 %		+30	1777 499 995	-2.6	0.000 000	-0.001
100 %		+40	1777 499 995	-2.7	0.000 000	-0.002
100 %		+50	1777 500 001	2.9	0.000 000	0.002
Batt. Endpoint	3.300	+20	1777 500 000	1.7	0.000 000	0.001




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1775,000,000 Hz
 ■ CHANNEL: 132622 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1774 999 998	0.0	0.000 000	0.000
100 %		-30	1775 000 000	2.3	0.000 000	0.001
100 %		-20	1774 999 995	-3.1	0.000 000	-0.002
100 %		-10	1774 999 996	-2.1	0.000 000	-0.001
100 %		0	1774 999 996	-2.5	0.000 000	-0.001
100 %		+10	1774 999 995	-3.1	0.000 000	-0.002
100 %		+30	1774 999 995	-3.0	0.000 000	-0.002
100 %		+40	1774 999 996	-2.2	0.000 000	-0.001
100 %		+50	1774 999 995	-3.0	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1774 999 995	-2.9	0.000 000	-0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1772,500,000 Hz
 ■ CHANNEL: 132597 (15 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1772 499 995	0.0	0.000 000	0.000
100 %		-30	1772 499 988	-7.0	0.000 000	-0.004
100 %		-20	1772 499 988	-7.4	0.000 000	-0.004
100 %		-10	1772 499 989	-6.3	0.000 000	-0.004
100 %		0	1772 499 989	-6.4	0.000 000	-0.004
100 %		+10	1772 499 991	-4.4	0.000 000	-0.002
100 %		+30	1772 499 989	-6.2	0.000 000	-0.003
100 %		+40	1772 499 988	-6.7	0.000 000	-0.004
100 %		+50	1772 499 989	-6.0	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1772 499 987	-8.2	0.000 000	-0.005



☐ MODE: LTE B66/4
☐ OPERATING FREQUENCY: 1770,000,000 Hz
☐ CHANNEL: 132572 (20 MHz)
☐ REFERENCE VOLTAGE: 3.880 VDC
☐ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1769 999 994	0.0	0.000 000	0.000
100 %		-30	1769 999 988	-6.3	0.000 000	-0.004
100 %		-20	1769 999 987	-7.0	0.000 000	-0.004
100 %		-10	1769 999 988	-6.1	0.000 000	-0.003
100 %		0	1769 999 987	-7.6	0.000 000	-0.004
100 %		+10	1769 999 987	-7.2	0.000 000	-0.004
100 %		+30	1769 999 988	-6.6	0.000 000	-0.004
100 %		+40	1769 999 988	-5.9	0.000 000	-0.003
100 %		+50	1769 999 987	-7.2	0.000 000	-0.004
Batt. Endpoint	3.300	+20	1769 999 985	-8.8	0.000 000	-0.005



9. TEST DATA(Sub 2-2 ANT)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1710.7	LTE B66/B4 (1.4 MHz)	QPSK	-20.99	12.55	10.04	2.06	H	<1.00	0.113	20.53	1	3
		16-QAM	-21.75	11.79	10.04	2.06	H		0.095	19.77		
		64-QAM	-22.88	10.66	10.04	2.06	H		0.073	18.64		
		256-QAM	-25.82	7.72	10.04	2.06	H		0.037	15.70		
1745		QPSK	-20.74	12.76	10.18	2.07	H		0.122	20.87	1	3
		16-QAM	-21.42	12.08	10.18	2.07	H		0.104	20.19		
		64-QAM	-22.57	10.93	10.18	2.07	H		0.080	19.04		
		256-QAM	-25.64	7.86	10.18	2.07	H		0.040	15.97		
1779.3		QPSK	-20.16	13.51	10.26	2.09	H		0.147	21.68	1	3
		16-QAM	-20.81	12.86	10.26	2.09	H		0.127	21.03		
		64-QAM	-21.92	11.75	10.26	2.09	H		0.098	19.92		
		256-QAM	-25.06	8.61	10.26	2.09	H		0.048	16.78		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1711.5	LTE B66/B4 (3 MHz)	QPSK	-21.17	12.37	10.04	2.06	H	<1.00	0.108	20.35	1	0
		16-QAM	-21.87	11.67	10.04	2.06	H		0.092	19.65		
		64-QAM	-22.89	10.65	10.04	2.06	H		0.073	18.63		
		256-QAM	-25.96	7.58	10.04	2.06	H		0.036	15.56		
1745		QPSK	-20.77	12.73	10.18	2.07	H		0.121	20.84	1	14
		16-QAM	-21.47	12.03	10.18	2.07	H		0.103	20.14		
		64-QAM	-22.56	10.94	10.18	2.07	H		0.080	19.05		
		256-QAM	-25.70	7.80	10.18	2.07	H		0.039	15.91		
1778.5		QPSK	-20.13	13.54	10.26	2.09	H		0.148	21.71	1	8
		16-QAM	-20.90	12.77	10.26	2.09	H		0.124	20.94		
		64-QAM	-22.00	11.67	10.26	2.09	H		0.096	19.84		
		256-QAM	-25.00	8.67	10.26	2.09	H		0.048	16.84		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1712.5	LTE B66/B4 (5 MHz)	QPSK	-21.07	12.46	10.06	2.06	H	<1.00	0.111	20.46	1	13
		16-QAM	-21.88	11.65	10.06	2.06	H		0.092	19.65		
		64-QAM	-23.06	10.47	10.06	2.06	H		0.070	18.47		
		256-QAM	-26.16	7.37	10.06	2.06	H		0.034	15.37		
1745		QPSK	-20.78	12.72	10.18	2.07	H		0.121	20.83	1	24
		16-QAM	-21.55	11.95	10.18	2.07	H		0.101	20.06		
		64-QAM	-22.62	10.88	10.18	2.07	H		0.079	18.99		
		256-QAM	-25.70	7.80	10.18	2.07	H		0.039	15.91		
1777.5		QPSK	-20.12	13.55	10.26	2.09	H		0.149	21.72	1	13
		16-QAM	-20.82	12.85	10.26	2.09	H		0.126	21.02		
		64-QAM	-21.89	11.78	10.26	2.09	H		0.099	19.95		
		256-QAM	-25.04	8.63	10.26	2.09	H		0.048	16.80		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1715	LTE B66/B4 (10 MHz)	QPSK	-21.31	12.22	10.06	2.06	H	<1.00	0.105	20.22	1	49
		16-QAM	-22.02	11.51	10.06	2.06	H		0.089	19.51		
		64-QAM	-22.98	10.55	10.06	2.06	H		0.072	18.55		
		256-QAM	-26.24	7.29	10.06	2.06	H		0.034	15.29		
1745		QPSK	-20.69	12.81	10.18	2.07	H		0.124	20.92	1	49
		16-QAM	-21.35	12.15	10.18	2.07	H		0.106	20.26		
		64-QAM	-22.52	10.98	10.18	2.07	H		0.081	19.09		
		256-QAM	-25.48	8.02	10.18	2.07	H		0.041	16.13		
1775		QPSK	-20.24	13.42	10.25	2.09	H		0.144	21.58	1	25
		16-QAM	-21.03	12.63	10.25	2.09	H		0.120	20.79		
		64-QAM	-22.07	11.59	10.25	2.09	H		0.094	19.75		
		256-QAM	-24.98	8.68	10.25	2.09	H		0.048	16.84		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1717.5	LTE B66/B4 (15 MHz)	QPSK	-21.31	12.21	10.08	2.06	H	<1.00	0.105	20.23	1	0
		16-QAM	-22.20	11.32	10.08	2.06	H		0.086	19.34		
		64-QAM	-23.13	10.39	10.08	2.06	H		0.069	18.41		
		256-QAM	-26.16	7.36	10.08	2.06	H		0.035	15.38		
1745		QPSK	-20.58	12.92	10.18	2.07	H		0.127	21.03	1	74
		16-QAM	-21.49	12.01	10.18	2.07	H		0.103	20.12		
		64-QAM	-22.46	11.04	10.18	2.07	H		0.082	19.15		
		256-QAM	-25.58	7.92	10.18	2.07	H		0.040	16.03		
1772.5		QPSK	-20.43	13.23	10.25	2.09	H		0.138	21.39	1	74
		16-QAM	-21.23	12.43	10.25	2.09	H		0.115	20.59		
		64-QAM	-22.23	11.43	10.25	2.09	H		0.091	19.59		
		256-QAM	-25.27	8.39	10.25	2.09	H		0.045	16.55		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1720	LTE B66/B4 (20 MHz)	QPSK	-21.32	12.20	10.08	2.06	H	<1.00	0.105	20.22	1	0
		16-QAM	-22.05	11.47	10.08	2.06	H		0.089	19.49		
		64-QAM	-23.23	10.29	10.08	2.06	H		0.068	18.31		
		256-QAM	-26.10	7.42	10.08	2.06	H		0.035	15.44		
1745		QPSK	-20.59	12.91	10.18	2.07	H		0.126	21.02	1	99
		16-QAM	-21.41	12.09	10.18	2.07	H		0.105	20.20		
		64-QAM	-22.48	11.02	10.18	2.07	H		0.082	19.13		
		256-QAM	-25.60	7.90	10.18	2.07	H		0.040	16.01		
1770		QPSK	-20.50	13.16	10.24	2.09	H		0.135	21.31	1	99
		16-QAM	-21.16	12.50	10.24	2.09	H		0.116	20.65		
		64-QAM	-22.24	11.42	10.24	2.09	H		0.091	19.57		
		256-QAM	-25.17	8.49	10.24	2.09	H		0.046	16.64		

9.2 RADIATED SPURIOUS EMISSIONS

MODE:	<u>LTE B66(4)</u>
MODULATION SIGNAL:	<u>5 MHz QPSK</u>
DISTANCE:	<u>3 meters</u>
LIMIT:	<u>-13 dBm</u>

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
131997 (1712.5)	3 425.00	-43.01	12.43	-61.73	2.99	V	-52.29	1	13
		-42.77		-61.49		H	-52.05		
	5 137.50	-42.73	12.35	-55.71	3.80	V	-47.16		
		-43.58		-56.56		H	-48.01		
	6 850.00	-43.77	11.90	-51.37	4.36	V	-43.83		
		-43.67		-51.27		H	-43.73		
132322 (1745.0)	3 490.00	-42.43	12.34	-60.61	3.04	V	-51.31	1	24
		-42.25		-60.43		H	-51.13		
	5 235.00	-43.08	12.84	-55.72	3.78	V	-46.66		
		-43.63		-56.27		H	-47.21		
	6 980.00	-43.46	11.40	-49.93	4.48	V	-43.01		
		-43.60		-50.07		H	-43.15		
132647 (1777.5)	3 555.00	-42.58	12.34	-60.04	3.09	V	-50.79	1	13
		-42.25		-59.71		H	-50.46		
	5 332.50	-43.50	13.09	-57.10	3.79	V	-47.80		
		-43.44		-57.04		H	-47.74		
	7 110.00	-44.39	10.86	-49.03	4.48	V	-42.65		
		-43.71		-48.35		H	-41.97		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)	Limit (dB)
LTE B66/4	1.4 MHz	1745.0	QPSK	6	0	5.39	13.00
			16-QAM			6.16	
			64-QAM			6.58	
			256-QAM			6.86	
	3 MHz		QPSK	15		5.35	
			16-QAM			6.21	
			64-QAM			6.62	
			256-QAM			6.85	
	5 MHz		QPSK	25		5.41	
			16-QAM			6.24	
			64-QAM			6.61	
			256-QAM			6.83	
	10 MHz		QPSK	50		5.51	
			16-QAM			6.28	
			64-QAM			6.62	
			256-QAM			6.81	
	15 MHz		QPSK	75		5.52	
			16-QAM			6.27	
			64-QAM			6.63	
			256-QAM			6.84	
	20 MHz		QPSK	100		5.48	
			16-QAM			6.29	
			64-QAM			6.65	
			256-QAM			6.83	

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
LTE B66/4	1.4 MHz	1745.0	QPSK	6	0	1.1013
			16-QAM			1.1031
			64-QAM			1.1004
			256-QAM			1.1023
	3 MHz		QPSK	15		2.7133
			16-QAM			2.7084
			64-QAM			2.7101
			256-QAM			2.7195
	5 MHz		QPSK	25		4.5265
			16-QAM			4.5293
			64-QAM			4.5180
			256-QAM			4.5200
	10 MHz		QPSK	50		9.0226
			16-QAM			9.0239
			64-QAM			9.0022
			256-QAM			9.0250
	15 MHz		QPSK	75		13.516
			16-QAM			13.494
			64-QAM			13.496
			256-QAM			13.531
	20 MHz		QPSK	100		18.036
			16-QAM			18.025
			64-QAM			18.010
			256-QAM			17.995

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
LTE B66/4	1.4	1710.70	6.2812	28.591	-61.130	-32.539	-13.00
		1745.00	6.5404	28.591	-62.079	-33.488	
		1779.30	6.5604	28.591	-62.010	-33.419	
	3	1711.50	3.0808	27.976	-62.183	-34.207	
		1745.00	4.6262	27.976	-62.398	-34.422	
		1778.50	3.6890	27.976	-61.525	-33.549	
	5	1712.50	3.6990	27.976	-61.687	-33.711	
		1745.00	5.6531	28.591	-62.322	-33.731	
		1777.50	5.3440	28.591	-61.919	-33.328	
	10	1715.00	6.2812	28.591	-61.816	-33.225	
		1745.00	6.2413	28.591	-61.262	-32.671	
		1775.00	3.6890	27.976	-62.210	-34.234	
	15	1717.50	3.7488	27.976	-61.794	-33.818	
		1745.00	3.0310	27.976	-62.037	-34.061	
		1772.50	6.8794	28.591	-61.593	-33.002	
	20	1720.00	6.5903	28.591	-62.191	-33.600	
		1745.00	5.6331	28.591	-61.566	-32.975	
		1770.00	3.6990	27.976	-61.763	-33.787	

Note:

1. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
3. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


9.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Section 11.4.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


- MODE: LTE B66/4
- OPERATING FREQUENCY: 1710,700,000 Hz
- CHANNEL: 131979 (1.4 MHz)
- REFERENCE VOLTAGE: 3.880 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1710 700 003	0.0	0.000 000	0.000
100 %		-30	1710 700 004	1.3	0.000 000	0.001
100 %		-20	1710 700 007	4.0	0.000 000	0.002
100 %		-10	1710 700 006	3.0	0.000 000	0.002
100 %		0	1710 700 001	-1.8	0.000 000	-0.001
100 %		+10	1710 700 005	2.7	0.000 000	0.002
100 %		+30	1710 700 005	2.6	0.000 000	0.002
100 %		+40	1710 700 005	2.6	0.000 000	0.002
100 %		+50	1710 700 007	4.6	0.000 000	0.003
Batt. Endpoint	3.300	+20	1710 700 005	2.6	0.000 000	0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1711,500,000 Hz
 ■ CHANNEL: 131987 (3 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1711 499 997	0.0	0.000 000	0.000
100 %		-30	1711 499 993	-3.4	0.000 000	-0.002
100 %		-20	1711 499 992	-4.4	0.000 000	-0.003
100 %		-10	1711 499 993	-3.6	0.000 000	-0.002
100 %		0	1711 499 993	-3.6	0.000 000	-0.002
100 %		+10	1711 499 993	-3.7	0.000 000	-0.002
100 %		+30	1711 499 991	-5.4	0.000 000	-0.003
100 %		+40	1711 499 993	-4.2	0.000 000	-0.002
100 %		+50	1711 499 993	-3.3	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1711 499 993	-3.9	0.000 000	-0.002




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1712,500,000 Hz</u>
CHANNEL:	<u>131997 (5 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1712 499 998	0.0	0.000 000	0.000
100 %		-30	1712 500 000	2.0	0.000 000	0.001
100 %		-20	1712 500 001	3.3	0.000 000	0.002
100 %		-10	1712 499 996	-1.9	0.000 000	-0.001
100 %		0	1712 499 995	-3.2	0.000 000	-0.002
100 %		+10	1712 499 995	-3.1	0.000 000	-0.002
100 %		+30	1712 499 996	-2.5	0.000 000	-0.001
100 %		+40	1712 499 996	-2.3	0.000 000	-0.001
100 %		+50	1712 500 002	3.8	0.000 000	0.002
Batt. Endpoint	3.300	+20	1712 499 996	-1.8	0.000 000	-0.001




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1715,000,000 Hz
 ■ CHANNEL: 132022 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1714 999 998	0.0	0.000 000	0.000
100 %		-30	1714 999 995	-2.7	0.000 000	-0.002
100 %		-20	1714 999 999	1.4	0.000 000	0.001
100 %		-10	1714 999 995	-2.3	0.000 000	-0.001
100 %		0	1714 999 994	-3.1	0.000 000	-0.002
100 %		+10	1714 999 999	1.2	0.000 000	0.001
100 %		+30	1714 999 995	-2.9	0.000 000	-0.002
100 %		+40	1714 999 999	1.9	0.000 000	0.001
100 %		+50	1714 999 995	-2.9	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1714 999 995	-2.1	0.000 000	-0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1717,500,000 Hz</u>
CHANNEL:	<u>132047 (15 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1717 499 997	0.0	0.000 000	0.000
100 %		-30	1717 499 994	-2.3	0.000 000	-0.001
100 %		-20	1717 499 993	-3.5	0.000 000	-0.002
100 %		-10	1717 499 995	-1.8	0.000 000	-0.001
100 %		0	1717 499 994	-2.6	0.000 000	-0.002
100 %		+10	1717 499 995	-1.7	0.000 000	-0.001
100 %		+30	1717 499 994	-2.6	0.000 000	-0.002
100 %		+40	1717 499 993	-4.0	0.000 000	-0.002
100 %		+50	1717 499 994	-2.6	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1717 499 995	-1.8	0.000 000	-0.001




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1720,000,000 Hz
 ■ CHANNEL: 132072 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1719 999 996	0.0	0.000 000	0.000
100 %		-30	1719 999 993	-3.3	0.000 000	-0.002
100 %		-20	1719 999 992	-3.8	0.000 000	-0.002
100 %		-10	1719 999 993	-2.5	0.000 000	-0.001
100 %		0	1719 999 993	-3.2	0.000 000	-0.002
100 %		+10	1719 999 993	-3.3	0.000 000	-0.002
100 %		+30	1719 999 992	-4.0	0.000 000	-0.002
100 %		+40	1719 999 992	-3.5	0.000 000	-0.002
100 %		+50	1719 999 994	-1.8	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1719 999 995	-1.3	0.000 000	-0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1745,000,000 Hz</u>
CHANNEL:	<u>132322 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 002	0.0	0.000 000	0.000
100 %		-30	1744 999 999	-2.8	0.000 000	-0.002
100 %		-20	1745 000 004	1.8	0.000 000	0.001
100 %		-10	1745 000 006	4.0	0.000 000	0.002
100 %		0	1745 000 004	2.3	0.000 000	0.001
100 %		+10	1745 000 005	3.3	0.000 000	0.002
100 %		+30	1745 000 005	2.6	0.000 000	0.001
100 %		+40	1745 000 004	1.4	0.000 000	0.001
100 %		+50	1745 000 005	3.2	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 000	-1.7	0.000 000	-0.001




☐ MODE: LTE B66/4
☐ OPERATING FREQUENCY: 1745,000,000 Hz
☐ CHANNEL: 132322 (3 MHz)
☐ REFERENCE VOLTAGE: 3.880 VDC
☐ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 004	0.0	0.000 000	0.000
100 %		-30	1745 000 006	1.8	0.000 000	0.001
100 %		-20	1745 000 007	3.6	0.000 000	0.002
100 %		-10	1745 000 010	6.4	0.000 000	0.004
100 %		0	1745 000 008	3.9	0.000 000	0.002
100 %		+10	1745 000 006	2.3	0.000 000	0.001
100 %		+30	1745 000 001	-2.7	0.000 000	-0.002
100 %		+40	1745 000 009	5.3	0.000 000	0.003
100 %		+50	1745 000 008	4.1	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 007	3.0	0.000 000	0.002




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1745,000,000 Hz</u>
CHANNEL:	<u>132322 (5 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 002	0.0	0.000 000	0.000
100 %		-30	1744 999 999	-2.9	0.000 000	-0.002
100 %		-20	1745 000 005	2.2	0.000 000	0.001
100 %		-10	1745 000 006	4.0	0.000 000	0.002
100 %		0	1745 000 004	1.8	0.000 000	0.001
100 %		+10	1745 000 006	3.4	0.000 000	0.002
100 %		+30	1745 000 001	-1.7	0.000 000	-0.001
100 %		+40	1745 000 005	2.7	0.000 000	0.002
100 %		+50	1745 000 005	3.0	0.000 000	0.002
Batt. Endpoint	3.300	+20	1745 000 006	4.1	0.000 000	0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 132322 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1744 999 998	0.0	0.000 000	0.000
100 %		-30	1744 999 994	-3.6	0.000 000	-0.002
100 %		-20	1744 999 994	-4.2	0.000 000	-0.002
100 %		-10	1744 999 995	-3.2	0.000 000	-0.002
100 %		0	1744 999 999	1.5	0.000 000	0.001
100 %		+10	1744 999 993	-4.8	0.000 000	-0.003
100 %		+30	1744 999 996	-2.0	0.000 000	-0.001
100 %		+40	1745 000 000	2.3	0.000 000	0.001
100 %		+50	1744 999 993	-4.5	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1744 999 995	-2.9	0.000 000	-0.002




■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1745,000,000 Hz
 ■ CHANNEL: 132322 (15 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1745 000 003	0.0	0.000 000	0.000
100 %		-30	1745 000 001	-1.7	0.000 000	-0.001
100 %		-20	1744 999 999	-3.7	0.000 000	-0.002
100 %		-10	1744 999 998	-4.7	0.000 000	-0.003
100 %		0	1745 000 006	3.1	0.000 000	0.002
100 %		+10	1745 000 000	-2.5	0.000 000	-0.001
100 %		+30	1745 000 001	-1.8	0.000 000	-0.001
100 %		+40	1745 000 000	-2.3	0.000 000	-0.001
100 %		+50	1745 000 000	-2.7	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1744 999 999	-3.4	0.000 000	-0.002




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1745,000,000 Hz</u>
CHANNEL:	<u>132322 (20 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1744 999 997	0.0	0.000 000	0.000
100 %		-30	1744 999 993	-3.9	0.000 000	-0.002
100 %		-20	1744 999 994	-2.4	0.000 000	-0.001
100 %		-10	1744 999 995	-1.3	0.000 000	-0.001
100 %		0	1744 999 993	-4.1	0.000 000	-0.002
100 %		+10	1744 999 995	-1.8	0.000 000	-0.001
100 %		+30	1744 999 994	-2.5	0.000 000	-0.001
100 %		+40	1744 999 998	1.5	0.000 000	0.001
100 %		+50	1744 999 994	-2.6	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1744 999 995	-1.4	0.000 000	-0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1779,300,000 Hz</u>
CHANNEL:	<u>132665 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1779 300 003	0.0	0.000 000	0.000
100 %		-30	1779 300 004	1.7	0.000 000	0.001
100 %		-20	1779 300 000	-2.2	0.000 000	-0.001
100 %		-10	1779 300 001	-1.6	0.000 000	-0.001
100 %		0	1779 300 000	-2.5	0.000 000	-0.001
100 %		+10	1779 300 007	4.8	0.000 000	0.003
100 %		+30	1779 300 005	2.2	0.000 000	0.001
100 %		+40	1779 300 000	-2.5	0.000 000	-0.001
100 %		+50	1779 300 006	3.3	0.000 000	0.002
Batt. Endpoint	3.300	+20	1779 300 005	2.3	0.000 000	0.001




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1778,500,000 Hz</u>
CHANNEL:	<u>132657 (3 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1778 499 994	0.0	0.000 000	0.000
100 %		-30	1778 500 004	9.9	0.000 001	0.006
100 %		-20	1778 500 004	10.7	0.000 001	0.006
100 %		-10	1778 499 987	-7.0	0.000 000	-0.004
100 %		0	1778 500 003	8.9	0.000 001	0.005
100 %		+10	1778 499 998	4.7	0.000 000	0.003
100 %		+30	1778 500 003	9.5	0.000 001	0.005
100 %		+40	1778 499 988	-5.5	0.000 000	-0.003
100 %		+50	1778 500 001	7.1	0.000 000	0.004
Batt. Endpoint	3.300	+20	1778 500 001	7.2	0.000 000	0.004




☐ MODE: LTE B66/4
☐ OPERATING FREQUENCY: 1777,500,000 Hz
☐ CHANNEL: 132647 (5 MHz)
☐ REFERENCE VOLTAGE: 3.880 VDC
☐ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1777 499 996	0.0	0.000 000	0.000
100 %		-30	1777 499 998	1.6	0.000 000	0.001
100 %		-20	1777 499 994	-2.4	0.000 000	-0.001
100 %		-10	1777 499 994	-2.0	0.000 000	-0.001
100 %		0	1777 499 994	-2.5	0.000 000	-0.001
100 %		+10	1777 499 994	-2.5	0.000 000	-0.001
100 %		+30	1777 500 000	3.4	0.000 000	0.002
100 %		+40	1777 499 993	-3.3	0.000 000	-0.002
100 %		+50	1777 499 998	1.7	0.000 000	0.001
Batt. Endpoint	3.300	+20	1777 499 993	-2.8	0.000 000	-0.002




MODE:	<u>LTE B66/4</u>
OPERATING FREQUENCY:	<u>1775,000,000 Hz</u>
CHANNEL:	<u>132622 (10 MHz)</u>
REFERENCE VOLTAGE:	<u>3.880 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1774 999 995	0.0	0.000 000	0.000
100 %		-30	1774 999 997	1.8	0.000 000	0.001
100 %		-20	1774 999 993	-1.8	0.000 000	-0.001
100 %		-10	1774 999 993	-1.7	0.000 000	-0.001
100 %		0	1774 999 992	-2.8	0.000 000	-0.002
100 %		+10	1774 999 994	-1.5	0.000 000	-0.001
100 %		+30	1774 999 993	-1.7	0.000 000	-0.001
100 %		+40	1774 999 993	-2.0	0.000 000	-0.001
100 %		+50	1774 999 993	-2.0	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1774 999 993	-2.2	0.000 000	-0.001




☐ MODE: LTE B66/4
☐ OPERATING FREQUENCY: 1772,500,000 Hz
☐ CHANNEL: 132597 (15 MHz)
☐ REFERENCE VOLTAGE: 3.880 VDC
☐ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1772 499 995	0.0	0.000 000	0.000
100 %		-30	1772 499 988	-6.9	0.000 000	-0.004
100 %		-20	1772 499 987	-8.0	0.000 000	-0.005
100 %		-10	1772 499 989	-5.7	0.000 000	-0.003
100 %		0	1772 499 990	-4.9	0.000 000	-0.003
100 %		+10	1772 499 988	-7.1	0.000 000	-0.004
100 %		+30	1772 499 989	-6.1	0.000 000	-0.003
100 %		+40	1772 499 989	-5.4	0.000 000	-0.003
100 %		+50	1772 499 989	-5.4	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1772 499 988	-6.2	0.000 000	-0.003



■ MODE: LTE B66/4
 ■ OPERATING FREQUENCY: 1770,000,000 Hz
 ■ CHANNEL: 132572 (20 MHz)
 ■ REFERENCE VOLTAGE: 3.880 VDC
 ■ DEVIATION LIMIT: Emission must remain in band


Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.880	+20(Ref)	1769 999 993	0.0	0.000 000	0.000
100 %		-30	1769 999 988	-5.1	0.000 000	-0.003
100 %		-20	1769 999 986	-7.1	0.000 000	-0.004
100 %		-10	1769 999 987	-6.0	0.000 000	-0.003
100 %		0	1769 999 986	-6.9	0.000 000	-0.004
100 %		+10	1769 999 988	-5.1	0.000 000	-0.003
100 %		+30	1769 999 987	-5.5	0.000 000	-0.003
100 %		+40	1769 999 985	-7.7	0.000 000	-0.004
100 %		+50	1769 999 988	-5.3	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1769 999 988	-5.3	0.000 000	-0.003




10. TEST PLOTS(Main 1 ANT)

10.1 PEAK-TO-AVERAGE RATIO


LTE B66(4)_1.4 M_PAR_Mid_QPSK_FullRB




LTE B66(4)_1.4 M_PAR_Mid_16QAM_FullRB




LTE B66(4)_1.4 M_PAR_Mid_64QAM_FullRB




LTE B66(4)_1.4 M_PAR_Mid_256QAM_FullRB




LTE B66(4)_3 M_PAR_Mid_QPSK_FullRB




LTE B66(4)_3 M_PAR_Mid_16QAM_FullRB




LTE B66(4)_3 M_PAR_Mid_64QAM_FullRB




LTE B66(4)_3 M_PAR_Mid_256QAM_FullRB




LTE B66(4)_5 M_PAR_Mid_QPSK_FullRB




LTE B66(4)_5 M_PAR_Mid_16QAM_FullRB




LTE B66(4)_5 M_PAR_Mid_64QAM_FullRB




LTE B66(4)_5 M_PAR_Mid_256QAM_FullRB




LTE B66(4)_10 M_PAR_Mid_QPSK_FullRB




LTE B66(4)_10 M_PAR_Mid_16QAM_FullRB




LTE B66(4)_10 M_PAR_Mid_64QAM_FullRB




LTE B66(4)_10 M_PAR_Mid_256QAM_FullRB




LTE B66(4)_15 M_PAR_Mid_QPSK_FullRB




LTE B66(4)_15 M_PAR_Mid_16QAM_FullRB




LTE B66(4)_15 M_PAR_Mid_64QAM_FullRB




LTE B66(4)_15 M_PAR_Mid_256QAM_FullRB




LTE B66(4)_20 M_PAR_Mid_QPSK_FullRB




LTE B66(4)_20 M_PAR_Mid_16QAM_FullRB



LTE B66(4)_20 M_PAR_Mid_64QAM_FullRB




LTE B66(4)_20 M_PAR_Mid_256QAM_FullRB




10.2 OCCUPIED BANDWIDTH


LTE B66(4)_1.4 M_OBW_Mid_QPSK_FullRB




LTE B66(4)_1.4 M_OBW_Mid_16QAM_FullRB




LTE B66(4)_1.4 M_OBW_Mid_64QAM_FullRB




LTE B66(4)_1.4 M_OBW_Mid_256QAM_FullRB




LTE B66(4)_3 M_OBW_Mid_QPSK_FullRB




LTE B66(4)_3 M_OBW_Mid_16QAM_FullRB




LTE B66(4)_3 M_OBW_Mid_64QAM_FullRB




LTE B66(4)_3 M_OBW_Mid_256QAM_FullRB




LTE B66(4)_5 M_OBW_Mid_QPSK_FullRB




LTE B66(4)_5 M_OBW_Mid_16QAM_FullRB




LTE B66(4)_5 M_OBW_Mid_64QAM_FullRB




LTE B66(4)_5 M_OBW_Mid_256QAM_FullRB




LTE B66(4)_10 M_OBW_Mid_QPSK_FullRB




LTE B66(4)_10 M_OBW_Mid_16QAM_FullRB




LTE B66(4)_10 M_OBW_Mid_64QAM_FullRB




LTE B66(4)_10 M_OBW_Mid_256QAM_FullRB




LTE B66(4)_15 M_OBW_Mid_QPSK_FullRB




LTE B66(4)_15 M_OBW_Mid_16QAM_FullRB




LTE B66(4)_15 M_OBW_Mid_64QAM_FullRB




LTE B66(4)_15 M_OBW_Mid_256QAM_FullRB




LTE B66(4)_20 M_OBW_Mid_QPSK_FullRB




LTE B66(4)_20 M_OBW_Mid_16QAM_FullRB



LTE B66(4)_20 M_OBW_Mid_64QAM_FullRB




LTE B66(4)_20 M_OBW_Mid_256QAM_FullRB




10.3 CONDUCTED SPURIOUS EMISSIONS


LTE B66(4)_1.4 M_Conducted Spurious Emissions(30 M-10 G)_Low_QPSK_1RB




LTE B66(4)_1.4 M_Conducted Spurious Emissions(30 M-10 G)_Mid_QPSK_1RB




LTE B66(4)_1.4 M_Conducted Spurious Emissions(30 M-10 G)_High_QPSK_1RB




LTE B66(4)_3 M_Conducted Spurious Emissions(30 M-10 G)_Low_QPSK_1RB




LTE B66(4)_3 M_Conducted Spurious Emissions(30 M-10 G)_Mid_QPSK_1RB




LTE B66(4)_3 M_Conducted Spurious Emissions(30 M-10 G)_High_QPSK_1RB



LTE B66(4)_5 M_Conducted Spurious Emissions(30 M-10 G)_Low_QPSK_1RB



LTE B66(4)_5 M_Conducted Spurious Emissions(30 M-10 G)_Mid_QPSK_1RB



LTE B66(4)_5 M_Conducted Spurious Emissions(30 M-10 G)_High_QPSK_1RB

