



CERTIFICATION TEST REPORT

Report Number. : 12678272-E8V3

Applicant : Samsung Electronics Co., Ltd.
129 Samsung-Ro, Yeongtong-Gu,
Suwon-Si, Gyeonggi-Do, 16677, Korea

Model : SM-A305FN/DS

FCC ID : A3LSMA305FN

EUT Description : GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac and
NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:
February 20, 2019

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538 U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2/11/2019	Initial Issue	
V2	2/15/2019	Updated Cover Page, Section 1, 2, and 5.1	Steven Tran
V2	2/15/2019	Updated Cover Page, Section 1, 2, and 5.1	Steven Tran

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY.....	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM FIELD STRENGTH.....	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. SOFTWARE AND FIRMWARE.....	7
5.5. WORST-CASE CONFIGURATION AND MODE.....	7
5.6. DESCRIPTION OF TEST SETUP.....	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. OCCUPIED BANDWIDTH	11
7.1. Type A (CE Mode)	12
7.2. Type B (CE Mode)	15
7.3. Type F (CE Mode)	18
8. RADIATED EMISSION TEST RESULTS.....	20
8.1. LIMITS AND PROCEDURE	20
8.2. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)	22
8.3. TX SPURIOUS EMISSION 30 TO 1000 MHz	25
9. FREQUENCY STABILITY	27
10. AC MAINS LINE CONDUCTED EMISSIONS	29
11. SETUP PHOTOS	32

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Samsung Electronics Co., Ltd.
129 Samsung-Ro, Yeongtong-Gu,
Suwon-Si, Gyeonggi-Do, 16677, Korea

EUT DESCRIPTION: GSM/WCDMA/LTE phone with BT, DTS/UNII a/b/g/n/ac and NFC

MODEL: SM-A305FN/DS

SERIAL NUMBER: R38KC08WHJE (Conducted)
R38KC08WJSN, R38KC08WKGY (Radiated)

DATE TESTED: January 24 – 31, 2019

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Dan Corona
Operations Leader
Consumer Technology Division
UL Verification Services Inc.

Reviewed By:



Steven Tran
Project Engineer
Consumer Technology Division
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR 47 Part 2, and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, and 47658 Kato Road, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street	47658 Kato Rd
☐ Chamber A (ISED:2324B-1)	☐ Chamber D (ISED:22541-1)	☐ Chamber I (ISED:2324A-5)
☒ Chamber B (ISED:2324B-2)	☐ Chamber E (ISED:22541-2)	☐ Chamber J (ISED:2324A-6)
☐ Chamber C (ISED:2324B-3)	☐ Chamber F (ISED:22541-3)	☐ Chamber K (ISED:2324A-1)
	☐ Chamber G (ISED:22541-4)	☐ Chamber L (ISED:2324A-3)
	☐ Chamber H (ISED:22541-5)	

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers above are covered under Industry Canada company address and respective code

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)
 $36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$

MAINS CONDUCTED EMISSIONS

Where relevant, the following sample calculation is provided:

Final Voltage (dBuV) = Measured Voltage (dBuV) + Cable Loss (dB) + Limiter Factor (dB) + LISN Insertion Loss.
 $36.5 \text{ dBuV} + 0 \text{ dB} + 10.1 \text{ dB} + 0 \text{ dB} = 46.6 \text{ dBuV}$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE phone with BT,DTS/UNII a/b/g/n/ac, and NFC. The model SM-A305FN/DS was used for final testing and is representative of the test results in this report.

5.2. MAXIMUM FIELD STRENGTH

The testing was performed at 3 meters. The transmitter maximum E-field at 30 meter distance was 19.46 dBuV/m, which was converted from the 3 meter data.

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes the loop antenna.

5.4. SOFTWARE AND FIRMWARE

The test utility software used during testing was A305FN.001.

5.5. WORST-CASE CONFIGURATION AND MODE

The fundamental of the EUT was investigated under three orthogonal orientations X (Flatbed), Y (Landscape), and Z (Portrait). The Y (Landscape) orientation was determined to be the worst-case orientation.

Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788

NOTE: The EUT pre-scanned in three NFC type A, B & F. The worst type is A, and data rate of 106kbps was recorded to this report.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung	EP-TA50EWE	DW3J719AS/A-E	N/A
Earphone	Samsung	N/A	N/A	N/A

I/O CABLES (CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	RF	Shielded	0.2	To PSA
2	USB	1	USB	Un-shielded	1	EUT to AC Mains


I/O CABLES (RADIATED AND CONDUCTED EMISSIONS)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	USB	1	USB	Shielded	1	N/A
2	earphone	1	3.5mm	Un-shielded	1	N/A

TEST SETUP

The EUT is a stand alone. Test software exercised the radio card.

RADIATED AND AC LINE CONDUCTED EMISSIONS SETUP DIAGRAM



TEST SETUP

For radiated tests: EUT has support equipment. The test software exercises the radio.

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST					
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences Corp.	JB3	T407	05/10/2019	05/10/2018
Amplifier, 9kHz to 1GHz, 32dB	Sonoma Instrument	310	170649	11/01/2019	11/01/2018
EMI Reciever	Rohde & Schwarz	ESR	T1436	02/21/2019	02/21/2018
Antenna, Passive Loop 9KHz to 1MHz	ELETRO METRICS	EM-6871	PRE0179465	05/22/2019	05/22/2018
Antenna, Passive Loop 9KHz to 1MHz	ELETRO METRICS	EM-6872	PRE0179467	05/22/2019	05/22/2018
L.I.S.N.	FCC INC.	FCC LISN 50/250	T1310	06/15/2019	06/15/2018
L.I.S.N.	FCC INC.	FCC LISN 50/250	T24	03/06/2019	03/06/2018
Temp Chamber	Thermotron Industries	SE-600-10-10	T80	05/01/2019	11/01/2018
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T339	09/11/2019	09/11/2018
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1454	01/25/20	01/25/2019

Test Software List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Ver 9.5, June 22, 2018
Antenna Port Software	UL	UL RF	Ver 9.0, Oct 31, 2018
AC Line Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015

Note: * indicates automation software version used in the compliance certification testing

7. OCCUPIED BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 10kHz. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

Note: Because the measured signal is CW or CW-like adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW

RESULTS

99% and 20dB BW

Type A (CE Mode)

Mode Kbps	Frequency (MHz)	99% Bandwidth (KHz)	20dB Bandwidth (KHz)
424	13.56	21.149	24.96
212	13.56	21.161	24.94
106	13.56	21.173	24.99

TYPE B


Mode Kbps	Frequency (MHz)	99% Bandwidth (KHz)	20dB Bandwidth (KHz)
424	13.56	21.132	24.92
212	13.56	21.144	24.95
106	13.56	21.155	24.92

TYPE F


Mode Kbps	Frequency (MHz)	99% Bandwidth (KHz)	20dB Bandwidth (KHz)
424	13.56	21.152	25.00
212	13.56	21.124	24.93

7.1. Type A (CE Mode)


424Kbps



212Kbps




106Kbps




7.2. Type B (CE Mode)


424Kbps



212Kbps




106Kbps




7.3. Type F (CE Mode)

424Kbps



212Kbps



8. RADIATED EMISSION TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMIT

§15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the field strength from uV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (uV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE

ANSI C63.10, 2013

The EUT is an intentional radiator that incorporates a digital device, the highest fundamental frequency generated or used in the device is 13.56 MHz; therefore, the frequency range was investigated from 0.15 MHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater.

2D antenna use - For below 30MHz testing, investigation was done on three antenna orientations (parallel, perpendicular, and ground-parallel), parallel and perpendicular are the worst orientations, therefore testing was performed on these two orientations only.

KDB 414788 OATS and Chamber Correlation Justification

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

Open field site (OFS) and chamber correlation testing had been performed and chamber measured test result is the worst case test result.


RESULTS

8.2. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 - 30 MHz)

Type A (CE Mode), 106Kbps

DATA

FUNDAMENTAL EMISSION MASK (11.56 – 15.56 MHz)



NOTE: All data rate Field Strength was investigated and Type A, 106k found to have the highest Field Strength results and represents as the worst case data rate.


Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna (dB/m)	Cbl (dB)	Dist Corr 30m	Corrected Reading dB(uVolts/meter)	FCC 15.225 Limit	PK Margin (dB)	Azimuth (Degs)	Polarity
8	12.97939	31.12	Pk	10.7	.5	-40	2.32	29.54	-27.22	0-360	Face-Off
1	13.033	24.21	Pk	10.7	.5	-40	-4.59	29.54	-34.13	0-360	Face-On
9	13.28916	31.15	Pk	10.7	.5	-40	2.35	40.51	-38.16	0-360	Face-Off
2	13.30975	24.96	Pk	10.7	.5	-40	-3.84	40.51	-44.35	0-360	Face-On
3	13.49188	24.06	Pk	10.7	.5	-40	-4.74	50.5	-55.24	0-360	Face-On
10	13.52833	30.39	Pk	10.6	.5	-40	1.49	50.5	-49.01	0-360	Face-Off
11	*13.55822	44.48	Pk	10.6	.5	-40	15.58	84	-68.42	0-360	Face-Off
4	*13.55975	48.36	Pk	10.6	.5	-40	19.46	84	-64.54	0-360	Face-On
12	13.59404	30.2	Pk	10.6	.5	-40	1.3	50.5	-49.2	0-360	Face-Off
5	13.66663	32.58	Pk	10.6	.5	-40	3.68	50.5	-46.82	0-360	Face-On
6	13.77175	30.31	Pk	10.6	.5	-40	1.41	40.51	-39.1	0-360	Face-On
13	13.95212	29.14	Pk	10.6	.5	-40	.24	40.51	-40.27	0-360	Face-Off
7	14.22825	22.2	Pk	10.6	.5	-40	-6.7	29.54	-36.24	0-360	Face-On
14	14.48663	28.89	Pk	10.6	.5	-40	-.01	29.54	-29.55	0-360	Face-Off

* - Indicates fundamental frequency

Pk - Peak detector

SPURIOUS EMISSIONS (0.09 – 30MHz)



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna (dB/m)	Cables (dB)	Dist Corr 300m	Corrected Reading (dBuVolts)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Avg Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
2	.07684	37.59	Pk	11.4	0	-80	-31.01	49.87	-80.88	29.87	-60.88	-	-	-	-	0-360
1	.07717	38.59	Pk	11.4	0	-80	-30.01	49.84	-79.85	29.84	-59.85	-	-	-	-	0-360
4	.25497	45.37	Pk	10.9	.1	-80	-23.63	-	-	-	-	39.48	-63.11	19.48	-43.11	0-360
3	.2955	42.06	Pk	10.9	.1	-80	-26.94	-	-	-	-	38.2	-65.14	18.2	-45.14	0-360

Pk - Peak detector



Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Loop Antenna (dB/m)	Cables (dB)	Dist Corr (dB) 40Log	Corrected Reading (dBuVolts)	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
5	.69657	35.76	Pk	11	.1	-40	6.86	30.75	-23.89	0-360
6	1.55081	27.57	Pk	11.4	.2	-40	-8.3	23.82	-24.65	0-360
8	27.31812	17.82	Pk	10	.7	-40	-11.48	29.5	-40.98	0-360
7	28.07949	12.9	Pk	9.9	.7	-40	-16.5	29.5	-46	0-360

Pk - Peak detector

8.3. TX SPURIOUS EMISSION 30 TO 1000 MHz

Type A (CE Mode), 106Kbps

DATA



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	AF T407 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBUV/m)	QPk Limit (dBUV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	30.9778	31.7	Pk	24.1	-31.4	24.4	40	-15.6	0-360	101	H
2	65.3797	49.46	Pk	12	-31	30.46	40	-9.54	99	100	V
	65.3797	46.91	Qp	12	-31	27.91	40	-12.09	99	100	V
4	91.7685	51.41	Pk	12.1	-30.7	32.81	43.52	-10.71	0-360	100	V
3	92.5337	48.5	Pk	12.2	-30.7	30	43.52	-13.52	0-360	200	H
5	450.9326	34.84	Pk	20.9	-29.1	26.64	46.02	-19.38	0-360	100	H
6	640.3572	31.39	Pk	23.9	-28.6	26.69	46.02	-19.33	0-360	101	V

* - indicates frequency in CFR47 Pt 15 Restricted Band

Pk - Peak detector

Qp - Quasi-Peak detector

9. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

TEST PROCEDURE

ANSI C63.10-2013 Clause 6.8

RESULTS

No non-compliance noted.

Type A (CE Mode), 106Kbps

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply	Envir. Temp	Frequency Deviation Measured with Time Elapse								
(Vdc)	(°C)	Startup (MHz)	Delta (ppm)	@ 2 mins (MHz)	Delta (ppm)	@ 5 mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.80	50	13.5600078	-0.280	13.5600077	-0.276	13.5600077	-0.272	13.5600075	-0.261	± 100
3.80	40	13.5600061	-0.155	13.5600065	-0.185	13.5600068	-0.208	13.5600070	-0.224	± 100
3.80	30	13.5600044	-0.029	13.5600046	-0.045	13.5600048	-0.056	13.5600050	-0.077	± 100
3.80	20	13.5600040	0.000	13.5600045	-0.039	13.5600042	-0.018	13.5600043	-0.025	± 100
3.80	10	13.5600053	-0.096	13.5600051	-0.081	13.5600051	-0.081	13.5600050	-0.076	± 100
3.80	0	13.5600056	-0.120	13.5600056	-0.117	13.5600055	-0.114	13.5600054	-0.106	± 100
3.80	-10	13.5600029	0.081	13.5600034	0.041	13.5600040	0.003	13.5600054	-0.101	± 100
3.23	20	13.5600046	-0.042	13.5600046	-0.042	13.5600046	-0.042	13.5600046	-0.044	± 100
4.37	20	13.5600045	-0.039	13.5600045	-0.039	13.5600045	-0.040	13.5600046	-0.044	± 100

10. AC MAINS LINE CONDUCTED EMISSIONS

LIMITS

§15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Notes:
1. The lower limit shall apply at the transition frequencies
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

TEST PROCEDURE


ANSI C63.10:2013

RESULTS

No non-compliance noted:

Type A (CE Mode), 106Kbps

LINE 1 RESULTS



Worst Emission


Range 1: Line-L1 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L1	LC Cables C1&C3	Limiter (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR) Margin (dB)
1	.17025	34.09	Qp	0	0	10.1	44.19	64.95	-20.76	-	-
2	.17025	18.59	Ca	0	0	10.1	28.69	-	-	54.95	-26.26
3	.6855	24.19	Qp	0	0	10.1	34.29	56	-21.71	-	-
4	.6855	15.53	Ca	0	0	10.1	25.63	-	-	46	-20.37
5	4.08975	20.27	Qp	0	.1	10.1	30.47	56	-25.53	-	-
6	4.08975	12.57	Ca	0	.1	10.1	22.77	-	-	46	-23.23
7	8.826	18.05	Qp	0	.2	10.2	28.45	60	-31.55	-	-
8	8.83725	11.37	Ca	0	.2	10.2	21.77	-	-	50	-28.23
9	13.56	29.84	Qp	.1	.2	10.2	40.34	60	-19.66	-	-
10	13.56	27.12	Ca	.1	.2	10.2	37.62	-	-	50	-12.38
11	27.12075	2.61	Qp	.1	.4	10.5	13.61	60	-46.39	-	-
12	27.12075	-2.14	Ca	.1	.4	10.5	8.86	-	-	50	-41.14

Qp - Quasi-Peak detector

Ca - CISPR average detection

Note: Markers 9 and 10 are the 13.56MHz NFC Fundamental

LINE 2 RESULTS



Worst Emission

Range 2: Line-L2 .15 - 30MHz											
Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	LISN L2	LC Cables C2&C3	Limit (dB)	Corrected Reading dBuV	CFR 47 Part 15 Class B QP	QP Margin (dB)	CFR 47 Part 15 Class B Avg	Av(CISPR) Margin (dB)
13	.17025	34.26	Qp	0	0	10.1	44.36	64.95	-20.59	-	-
14	.17025	20.58	Ca	0	0	10.1	30.68	-	-	54.95	-24.27
15	.6855	26.04	Qp	0	0	10.1	36.14	56	-19.86	-	-
16	.6855	24.72	Ca	0	0	10.1	34.82	-	-	46	-11.18
17	4.05375	25.3	Qp	0	.1	10.1	35.5	56	-20.5	-	-
18	4.05375	18.76	Ca	0	.1	10.1	28.96	-	-	46	-17.04
19	8.79	22.99	Qp	0	.2	10.2	33.39	60	-26.61	-	-
20	8.78775	15.61	Ca	0	.2	10.2	26.01	-	-	50	-23.99
21	13.56	34.16	Qp	.1	.2	10.2	44.66	60	-15.34	-	-
22	13.56	30.07	Ca	.1	.2	10.2	40.57	-	-	50	-9.43
23	27.12075	3.55	Qp	.1	.4	10.5	14.55	60	-45.45	-	-
24	27.12075	-2.14	Ca	.1	.4	10.5	8.86	-	-	50	-41.14

Qp - Quasi-Peak detector

Ca - CISPR average detection

Note: Markers 21 and 22 are the 13.56MHz NFC Fundamental