

CERTIFICATION TEST REPORT

Report Number. : S-4791547056-E10V2

Applicant : SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Model : SM-A366U, SM-A366U1, SM-S366V

FCC ID : A3LSMA366U

EUT Description : GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax
and NFC

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C

Date Of Issue:

2025-01-09

Prepared by:

UL KOREA LTD.

26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL KOREA LTD. Suwon Laboratory

218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea

TEL: (031) 337-9902

FAX: (031) 213-5433

Revision History

Rev.	Issue Date	Revisions	Presented By
V1	2024-12-31	Initial issue	David Jung
V2	2025-01-09	Updated to address TCB's question	David Jung

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	6
4.3. MEASUREMENT UNCERTAINTY	6
4.4. DECISION RULE	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT	7
5.2. MAXIMUM E-FIELD STRENGTH	7
5.3. WORST-CASE CONFIGURATION AND MODE	7
5.4. DESCRIPTION OF TEST SETUP	8
6. TEST AND MEASUREMENT EQUIPMENT	9
7. 20dB BANDWIDTH	10
8. RADIATED EMISSION TEST RESULTS	11
8.1. LIMITS AND PROCEDURE	11
8.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS [EUT with passive TAG mode]	13
8.1.2. SPURIOUS EMISSION 0.009 TO 30 MHz [EUT with passive TAG mode]	14
8.1.3. TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT with passive TAG mode]	15
8.1.4. FUNDAMENTAL AND SPURIOUS EMISSIONS) [EUT without passive TAG mode]	16
8.1.5. SPURIOUS EMISSION 0.09 TO 30 MHz [EUT without passive TAG mode]	17
8.1.6. TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT without passive TAG mode]	18
9. AC MAINS LINE CONDUCTED EMISSIONS	19
10. FREQUENCY STABILITY	24

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax and NFC.

MODEL NUMBER: SM-A366U, SM-A366U1, SM-S366V

SERIAL NUMBER: R3CXA0QK8QE, R3CXA0QK7YK (CONDUCTION);
R3CXA0QK7SP, R3CXA0QK8WP (RADIATION)

DATE TESTED: 2024-11-13 – 2024-12-31

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
47 CFR Part 15 Subpart C	Complies

UL KOREA LTD. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL KOREA LTD. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL KOREA LTD. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL KOREA LTD. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL KOREA LTD. By:



Seokhwan Hong
Suwon Lab Engineer
UL KOREA LTD.

Tested By:



David Jung
Suwon Lab Engineer
UL KOREA LTD.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC 47 CFR Part 2.
2. FCC 47 CFR Part 15.
3. ANSI C63.10-2020.
4. KDB 414788 D01 Radiated Test Site v01r01

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☐	Chamber 1(3m semi-anechoic chamber)
☒	Chamber 2(3m semi-anechoic chamber)
☒	Chamber 3(3m semi-anechoic chamber)
☐	Chamber 4(3m Full-anechoic chamber)
☐	Chamber 5(3m Full-anechoic chamber)

UL KOREA LTD. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) +
Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

Corrected Reading (dBuV) = Meter Reading (dBuV) + External Cable (dB) +
Cableloss (dB)

46.62 dBuV + 9.8 dB + 0.1 dB = 56.52 dBuV

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Occupied Bandwidth	0.04 %
Frequency Stability	5.3×10^{-8} Hz
Conducted Disturbance, 0.15 to 30 MHz	2.79 dB
Radiated Disturbance, 9 kHz to 30 MHz	1.69 dB
Radiated Disturbance, 30 MHz to 1 GHz	3.92 dB

Uncertainty figures are valid to a confidence level of 95%.

4.4. DECISION RULE

Decision rule for statement(s) of conformity is based on Clause 4.4.3 in IEC Guide 115:2023.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE/5G NR Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax and NFC. This test report addresses the DXX (NFC) operational mode.

Representative model	Difference	Derivative model
		SM-A366U1, SM-S366V
SM-A366U	Hardware	Same
	Software	The UI has changed according to Service Provider

The model SM-A366U was used for final testing and is representative of the test results in this report.

5.2. MAXIMUM E-FIELD STRENGTH

The testing was performed at 3 meter. The transmitter maximum E-field at 30m distance is 11.49 dBuV/m which convert from 3 meter data.

5.3. WORST-CASE CONFIGURATION AND MODE

The NFC function was tested at its' fundamental and only operational frequency of 13.56 MHz.

Worst case of antenna axis:

NFC with tag mode	NFC without tag mode
Z	Z

The fundamental level of the EUT was investigated each type and bitrate. All test was performed worst case condition.

- ISO/IEC 14443-A(Type A) and bit rate 106 kbps

Radiated(fundamental level and spurious emissions) tests were performed both without reading a passive tag condition[test mode] and with reading a passive tag condition.

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB 9163	845	2026-07-30
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB 9163	749	2026-08-12
Preamplifier, 1000 MHz	Sonoma	310N	341282	2025-07-22
Preamplifier, 1000 MHz	Sonoma	310N	351741	2025-07-22
Spectrum Analyzer, 7 GHz	Agilent / HP	N9010A	MY54200580	2025-07-23
Spectrum Analyzer, 44 GHz	KEYSIGHT	N9030A	MY54170614	2025-07-24
EMI Test Receive, 3 GHz	R&S	ESR 3	101832	2025-07-22
DC Power Supply	Agilent / HP	E3640A	MY54226395	2025-07-24
Temperature Chamber	ESPEC	SH-642	93001109	2025-07-23
LISN	R&S	ENV216	101836	2025-07-22
LISN	R&S	ENV216	101837	2025-07-22
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2E	100900	2025-07-25
UL Software				
Description	Manufacturer	Model	Version	
Radiated software	UL	UL EMC	Ver 9.5	
AC Line Conducted software	UL	UL EMC	Ver 9.5	

7. 20dB BANDWIDTH

LIMITS

§15.215

(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated

§15.225

Operation within the band 13.110 – 14.010MHz

TEST PROCEDURE

The spectrum analyzer connected receive antenna and the EUT placed on near the receive antenna. The RBW is set to 1-5% of emission BW. The VBW is set to 3 times the RBW. The sweep time is coupled.

RESULTS

Frequency [MHz]	20 dB Bandwidth [kHz]
13.56	440

20dB Bandwidth Plot



8. RADIATED EMISSION TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMIT

§15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (µV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the field strength from µV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (µV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE


ANSI C63.10-2020

The EUT is an intentional radiator that incorporates a digital device. The highest fundamental frequency generated or used in the device is 13.56 MHz. The frequency range was investigated from 0.15 MHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater (1000MHz)

RESULTS

No non-compliance noted:

8.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS [EUT with passive TAG mode]



Trace Markers Face on

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Dist Corr 30m[dB]	Cable Loss[dB]	Corrected Reading (dBuV/m)	FCC 15.225 Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	12.98775	11.57	Pk	20.1	-40	.5	-7.83	29.54	-37.37	0-360
2	13.34775	12.07	Pk	20.1	-40	.5	-7.33	40.51	-47.84	0-360
3	13.45275	15.94	Pk	20.1	-40	.5	-3.46	50.5	-53.96	0-360
**4	13.56	29.34	Pk	20.1	-40	.5	9.94	84	-74.06	0-360
5	13.63725	11.8	Pk	20.1	-40	.6	-7.5	50.5	-58	0-360
6	13.77325	12.43	Pk	20.1	-40	.6	-6.87	40.51	-47.38	0-360
7	14.08275	10.99	Pk	20.1	-40	.6	-8.31	29.54	-37.85	0-360

Face off

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Dist Corr 30m[dB]	Cable Loss[dB]	Corrected Reading (dBuV/m)	FCC 15.225 Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
8	12.93625	11.7	Pk	20.1	-40	.5	-7.7	29.54	-37.24	0-360
9	13.324	11.07	Pk	20.1	-40	.5	-8.33	40.51	-48.84	0-360
10	13.44525	12.53	Pk	20.1	-40	.5	-6.87	50.5	-57.37	0-360
**11	13.56	26.63	Pk	20.1	-40	.5	7.23	84	-76.77	0-360
12	13.6245	10.55	Pk	20.1	-40	.6	-8.75	50.5	-59.25	0-360
13	13.75275	10.37	Pk	20.1	-40	.6	-8.93	40.51	-49.44	0-360
14	14.08875	10.79	Pk	20.1	-40	.6	-8.51	29.54	-38.05	0-360

Pk - Peak detector


**Fundamental

Note 1 : Although these tests were performed other than open filed test site, adequate comparison measurements were confirmed against 30 m open are test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.2. SPURIOUS EMISSION 0.009 TO 30 MHz [EUT with passive TAG mode]



Trace Markers

[Face on]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Cable Loss [dB]	Dist Corr 30m[dB]	Corrected Reading (dBuV/m)	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	.65705	22.05	Pk	19.9	.1	-40	2.05	31.26	-29.21	0-360
2	1.05878	17.65	Pk	19.9	.2	-40	-2.25	27.13	-29.38	0-360
3	1.60492	16.38	Pk	20	.2	-40	-3.42	23.52	-26.94	0-360
4	2.54383	18.82	Pk	20.1	.3	-40	-.78	29.5	-30.28	0-360
5	2.9868	18.51	Pk	20.1	.3	-40	-1.09	29.5	-30.59	0-360
6	3.54288	16.78	Pk	20.1	.3	-40	-2.82	29.5	-32.32	0-360
**7	13.56165	28.88	Pk	20	.5	-40	9.38	29.5	-20.12	0-360

[Face off]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Cable Loss [dB]	Dist Corr 30m[dB]	Corrected Reading (dBuV/m)	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
8	.71405	21.17	Pk	19.9	.1	-40	1.17	30.54	-29.37	0-360
9	1.02823	18.66	Pk	19.9	.2	-40	-1.24	27.38	-28.62	0-360
10	1.57156	18.39	Pk	20	.2	-40	-1.41	23.71	-25.12	0-360
11	2.5344	18.03	Pk	20.1	.3	-40	-1.57	29.5	-31.07	0-360
12	2.9868	18.29	Pk	20.1	.3	-40	-1.31	29.5	-30.81	0-360
13	3.4769	17.84	Pk	20.1	.3	-40	-1.76	29.5	-31.26	0-360
**14	13.56165	27.56	Pk	20	.5	-40	8.06	29.5	-21.44	0-360

Pk - Peak detector

**Fundamental


Note 1: The data for marker number 7 and 14 are the fundamental signal.

Please refer to section 8.1.1 about the fundamental level.

Frequency range 0.009MHz ~ 0.490MHz, only noise floor level and more than 20dB margin.

Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.3. TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT with passive TAG mode]




Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna 845 Factor (dB/m)	Below 1G Path Loss (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	49.305	37.48	PK	20	-31.8	25.68	40	-14.32	0-360	300	H
3	90.2432	44.46	PK	16.2	-31.4	29.26	43.52	-14.26	0-360	200	H
5	546.9663	38.66	PK	23.6	-29.6	32.66	46.02	-13.36	0-360	200	H
2	35.8206	47.36	PK	17.3	-31.9	32.76	40	-7.24	0-360	100	V
4	194.529	41.13	PK	16.9	-30.7	27.33	43.52	-16.19	0-360	100	V
6	551.9138	40.46	PK	23.6	-29.6	34.46	46.02	-11.56	0-360	200	V

* - indicates frequency in 47 CFR Pt 15 / IC RSS-Restricted Band
Pk - Peak detector

8.1.4. FUNDAMENTAL AND SPURIOUS EMISSIONS) [EUT without passive TAG mode]



Trace Markers Face on

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Dist Corr 30m[dB]	Cable Loss[dB]	Corrected Reading (dBuV/m)	FCC 15.225 Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	12.9845	10.2	Pk	20.1	-40	.5	-9.2	29.54	-38.74	0-360
2	13.345	16.84	Pk	20.1	-40	.5	-2.56	40.51	-43.07	0-360
3	13.4555	19.95	Pk	20.1	-40	.5	.55	50.5	-49.95	0-360
**4	13.5615	30.89	Pk	20.1	-40	.5	11.49	84	-72.51	0-360
5	13.67	20.03	Pk	20.1	-40	.6	.73	50.5	-49.77	0-360
6	13.77325	16.77	Pk	20.1	-40	.6	-2.53	40.51	-43.04	0-360
7	14.94025	12.14	Pk	20.1	-40	.6	-7.16	29.54	-36.7	0-360

Face off

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Dist Corr 30m[dB]	Cable Loss[dB]	Corrected Reading (dBuV/m)	FCC 15.225 Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
8	12.91925	10.38	Pk	20.1	-40	.5	-9.02	29.54	-38.56	0-360
9	13.34825	15.7	Pk	20.1	-40	.5	-3.7	40.51	-44.21	0-360
10	13.455	17.14	Pk	20.1	-40	.5	-2.26	50.5	-52.76	0-360
**11	13.562	27.57	Pk	20.1	-40	.5	8.17	84	-75.83	0-360
12	13.66575	16.95	Pk	20.1	-40	.6	-2.35	50.5	-52.85	0-360
13	13.773	14.55	Pk	20.1	-40	.6	-4.75	40.51	-45.26	0-360
14	14.581	11.16	Pk	20.1	-40	.6	-8.14	29.54	-37.68	0-360

Pk - Peak detector


**Fundamental

Note 1: Although these tests were performed other than open filed test site, adequate comparison measurements were confirmed against 30 m open are test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.5. SPURIOUS EMISSION 0.09 TO 30 MHz [EUT without passive TAG mode]



Trace Markers

[Face on]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Cable Loss [dB]	Dist Corr 30m[dB]	Corrected Reading (dBuV/m)	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
1	.70869	18.18	Pk	19.9	.1	-40	-1.82	30.6	-32.42	0-360
2	1.12331	15.94	Pk	19.9	.2	-40	-3.96	26.61	-30.57	0-360
3	1.61932	16.08	Pk	20	.2	-40	-3.72	23.45	-27.17	0-360
4	2.52498	18.54	Pk	20.1	.3	-40	-1.06	29.5	-30.56	0-360
5	2.92083	17.69	Pk	20.1	.3	-40	-1.91	29.5	-31.41	0-360
6	3.42035	17.43	Pk	20.1	.3	-40	-2.17	29.5	-31.67	0-360
**7	13.56165	31.08	Pk	20	.5	-40	11.58	29.5	-17.92	0-360

[Face off]

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna Correction Factor(dB/m)	Cable Loss [dB]	Dist Corr 30m[dB]	Corrected Reading (dBuV/m)	QP Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)
8	.68897	20.6	Pk	19.9	.1	-40	.6	30.85	-30.25	0-360
9	1.09002	17.58	Pk	19.9	.2	-40	-2.32	26.87	-29.19	0-360
10	1.56502	18.41	Pk	20	.2	-40	-1.39	23.74	-25.13	0-360
11	2.52498	17.38	Pk	20.1	.3	-40	-2.22	29.5	-31.72	0-360
12	3.04335	18.92	Pk	20.1	.3	-40	-.68	29.5	-30.18	0-360
13	3.38265	18.8	Pk	20.1	.3	-40	-.8	29.5	-30.3	0-360
**14	13.56165	27.92	Pk	20	.5	-40	8.42	29.5	-21.08	0-360

Pk - Peak detector


**Fundamental

Note 1: The data for marker number 7 and 14 are the fundamental signal. Please refer to section 8.1.4 about the fundamental level. Frequency range 0.009MHz ~ 0.490MHz, only noise floor level and more than 20dB margin.


Note 2: Radiated test were investigated with three receiving antenna axes: Face-on, Face-off and horizontal (parallel to the ground plane) and the worse orientations of Face-on and Face-off were set for final test.

8.1.6. TX SPURIOUS EMISSION 30 TO 1000 MHz [EUT without passive TAG mode]

HORIZONTAL



VERTICAL



Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Antenna_845 Factor(dB/m)	Below_1G_Path Loss(dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	48.2379	37.61	PK	20	-31.8	25.81	40	-14.19	0-360	100	H
3	100.0412	40.01	PK	17.7	-31.4	26.31	43.52	-17.21	0-360	200	H
5	603.4261	39.15	PK	25.1	-29.5	34.75	46.02	-11.27	0-360	200	H
2	36.3057	47.06	PK	17.5	-31.9	32.66	40	-7.34	0-360	100	V
4	* 170.2765	41.17	PK	14.4	-30.9	24.67	43.52	-18.85	0-360	100	V
6	597.3145	39.41	PK	25	-29.4	35.01	46.02	-11.01	0-360	100	V

Pk - Peak detector

9. AC MAINS LINE CONDUCTED EMISSIONS

LIMITS

§15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
Notes: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.		

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.


Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

No non-compliance noted:

WORST EMISSIONS(non-Terminated)

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_L1 [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
1	.159	50.37	Pk	9.7	.1	60.17	65.52	-5.35	-	-
2	.159	37.79	Av	9.7	.1	47.59	-	-	55.52	-7.93
3	.24	40.71	Pk	9.6	.1	50.41	62.1	-11.69	-	-
4	.24	25.68	Av	9.6	.1	35.38	-	-	52.1	-16.72
5	.324	35.86	Pk	9.6	.1	45.56	59.6	-14.04	-	-
6	.324	17.11	Av	9.6	.1	26.81	-	-	49.6	-22.79
7	.39	33.65	Pk	9.7	.1	43.45	58.06	-14.61	-	-
8	.39	16.86	Av	9.7	.1	26.66	-	-	48.06	-21.4
9	.696	32.44	Pk	9.7	.1	42.24	56	-13.76	-	-
10	.699	12.33	Av	9.7	.1	22.13	-	-	46	-23.87
11	13.56	35.82	Pk	9.7	.3	45.82	60	-14.18	-	-
12	13.56	34.3	Av	9.7	.3	44.3	-	-	50	-5.7

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Range 1: Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101836_L1 [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
.15825	44.42	Qp	9.7	.1	54.22	65.56	-11.34	-	-
13.5593	34.53	Qp	9.7	.3	44.53	60	-15.47	-	-

Qp - Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz


Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_N [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
13	.156	47.47	Pk	9.7	.1	57.27	65.67	-8.4	-	-
14	.156	30.34	Av	9.7	.1	40.14	-	-	55.67	-15.53
15	.243	37.14	Pk	9.6	.1	46.84	61.99	-15.15	-	-
16	.243	22.19	Av	9.6	.1	31.89	-	-	51.99	-20.1
17	.309	34.32	Pk	9.6	.1	44.02	60	-15.98	-	-
18	.309	18.29	Av	9.6	.1	27.99	-	-	50	-22.01
19	.411	30.61	Pk	9.7	.1	40.41	57.63	-17.22	-	-
20	.411	13.29	Av	9.7	.1	23.09	-	-	47.63	-24.54
21	1.446	32.04	Pk	9.6	.1	41.74	56	-14.26	-	-
22	1.446	9.47	Av	9.6	.1	19.17	-	-	46	-26.83
23	13.56	37.86	Pk	9.6	.3	47.76	60	-12.24	-	-
24	13.56	34.01	Av	9.6	.3	43.91	-	-	50	-6.09

Pk - Peak detector

Av - Average detection

WORST EMISSIONS(Terminated)

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Range 1: Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_L1 [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
1	.156	53.95	Pk	9.7	.1	63.75	65.67	-1.92	-	-
2	.156	40.93	Av	9.7	.1	50.73	-	-	55.67	-4.94
3	.24	44.69	Pk	9.6	.1	54.39	62.1	-7.71	-	-
4	.237	27.39	Av	9.6	.1	37.09	-	-	52.2	-15.11
5	.309	39.37	Pk	9.6	.1	49.07	60	-10.93	-	-
6	.309	23.43	Av	9.6	.1	33.13	-	-	50	-16.87
7	.417	36.38	Pk	9.7	.1	46.18	57.51	-11.33	-	-
8	.417	18.14	Av	9.7	.1	27.94	-	-	47.51	-19.57
9	.483	33.79	Pk	9.8	.1	43.69	56.29	-12.6	-	-
10	.501	16.12	Av	9.8	.1	26.02	-	-	46	-19.98
11	21.927	41.86	Pk	9.7	.3	51.86	60	-8.14	-	-
12	21.192	26.96	Av	9.7	.3	36.96	-	-	50	-13.04

Pk - Peak detector

Av - Average detection


Quasi-Peak Emissions

Range 1: Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101836_L1 [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
.15615	45.06	Qp	9.7	.1	54.86	65.67	-10.81	-	-
.23925	36.07	Qp	9.6	.1	45.77	62.12	-16.35	-	-
21.9263	31.78	Qp	9.7	.3	41.78	60	-18.22	-	-

Qp - Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Range 2: Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101836_N [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
13	.153	51.97	Pk	9.7	.1	61.77	65.84	-4.07	-	-
14	.153	36.87	Av	9.7	.1	46.67	-	-	55.84	-9.17
15	.234	42.32	Pk	9.6	.1	52.02	62.31	-10.29	-	-
16	.24	27.68	Av	9.6	.1	37.38	-	-	52.1	-14.72
17	.312	38	Pk	9.6	.1	47.7	59.92	-12.22	-	-
18	.306	20.78	Av	9.6	.1	30.48	-	-	50.08	-19.6
19	.417	35.03	Pk	9.7	.1	44.83	57.51	-12.68	-	-
20	.414	13.07	Av	9.7	.1	22.87	-	-	47.57	-24.7
21	.462	34.36	Pk	9.7	.1	44.16	56.66	-12.5	-	-
22	.462	14.91	Av	9.7	.1	24.71	-	-	46.66	-21.95
23	21.132	34.96	Pk	9.7	.3	44.96	60	-15.04	-	-
24	21.144	24.79	Av	9.7	.3	34.79	-	-	50	-15.21

Pk - Peak detector

Av - Average detection

Quasi-Peak Emissions

Range 2: Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101836_N [dB]	Cable Loss [dB]	Corrected Reading [dBuV]	FCC 15 Class B QP [dBuV]	Margin (dB)	FCC 15 Class B AV [dBuV]	Margin (dB)
.15375	44.99	Qp	9.7	.1	54.79	65.79	-11	-	-

Qp - Quasi-Peak detector

10. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

TEST PROCEDURE

ANSI C63.10 §6.8

RESULTS

Test Date	2024-12-26
Test Engineer	33535

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply (Vdc)	Envir. Temp (°C)	Frequency Deviation Measured with Time Elapse								
		Start up (MHz)	Delta (ppm)	@ 2mins (MHz)	Delta (ppm)	@ 5mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.88	50	13.559955262	-3.021	13.559953952	-3.118	13.559952744	-3.207	13.559951740	-3.281	100
3.88	40	13.559957789	-2.835	13.559957048	-2.889	13.559957349	-2.867	13.559957345	-2.867	100
3.88	30	13.559980536	-1.157	13.559978154	-1.333	13.559978692	-1.293	13.559978255	-1.325	100
3.88	20	13.559996228	0.000	13.559995538	-0.051	13.560002113	0.434	13.560001666	0.401	100
3.88	10	13.560023118	1.983	13.560023361	2.001	13.560027344	2.295	13.560028487	2.379	100
3.88	0	13.560053896	4.253	13.560054194	4.275	13.560054949	4.330	13.560055016	4.335	100
3.88	-10	13.560060994	4.776	13.560060925	4.771	13.560060893	4.769	13.560061308	4.799	100
3.88	-20	13.560044441	3.556	13.560044845	3.585	13.560052385	4.141	13.560052634	4.160	100
3.88	-30	13.560001108	0.360	13.560015101	1.392	13.560015210	1.400	13.560015201	1.399	100

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz										
Power Supply (Vdc)	Envir. Temp (°C)	Frequency Deviation Measured with Time Elapse								
		Start up (MHz)	Delta (ppm)	@ 2mins (MHz)	Delta (ppm)	@ 5mins (MHz)	Delta (ppm)	@ 10 mins (MHz)	Delta (ppm)	Limit (ppm)
3.70	20	13.560001525	0.391	13.560001425	0.383	13.560003525	0.147	13.560001415	-0.008	100
3.88	20	13.559996228	0.000	13.559995538	-0.051	13.560002113	0.043	13.560001666	0.010	100
4.45	20	13.559998352	0.157	13.559998962	0.202	13.559999141	-0.176	13.559998362	-0.233	100

No non-compliance noted.

END OF TEST REPORT