



SAR EVALUATION REPORT

Applicant Name:

Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

Date of Testing:

09/15/14 - 09/23/14

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

OY1409081825.A3L

FCC ID:

A3LSMA500M

APPLICANT:

SAMSUNG ELECTRONICS, CO. LTD.

DUT Type:

Portable Handset

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093

Model(s):

SM-A500M, SM-A500M/DS

Equipment Class	Band & Mode	Tx Frequency	SAR		
			1 gm Head (W/kg)	1 gm Body-Worn (W/kg)	1 gm Hotspot (W/kg)
PCE	GSM/GPRS/EDGE 850	824.20 - 848.80 MHz	0.24	0.42	0.41
PCE	GSM/GPRS/EDGE 1900	1850.20 - 1909.80 MHz	0.20	0.40	0.59
PCE	UMTS 850	826.40 - 846.60 MHz	0.22	0.35	0.35
PCE	UMTS 1900	1852.4 - 1907.6 MHz	0.28	0.69	1.06
PCE	LTE Band 17	706.5 - 713.5 MHz	< 0.1	0.13	0.13
PCE	LTE Band 5 (Cell)	824.7 - 848.3 MHz	0.20	0.31	0.31
PCE	LTE Band 4 (AWS)	1710.7 - 1754.3 MHz	0.30	0.52	0.71
PCE	LTE Band 2 (PCS)	1850.7 - 1909.3 MHz	0.26	0.64	0.97
DTS	2.4 GHz WLAN	2412 - 2462 MHz	0.10	< 0.1	< 0.1
DTS	5.8 GHz WLAN	5745 - 5825 MHz	< 0.1	< 0.1	
NII	5.2 GHz WLAN	5180 - 5240 MHz	< 0.1	< 0.1	
NII	5.3 GHz WLAN	5260 - 5320 MHz	0.15	< 0.1	
NII	5.5 GHz WLAN	5500 - 5700 MHz	0.16	< 0.1	
DSS/DTS	Bluetooth	2402 - 2480 MHz	N/A		
Simultaneous SAR per KDB 690783 D01v01r03:			0.46	1.07	1.06

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.


Randy Ortanez
President



The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 1 of 66	

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	LTE INFORMATION	9
3	INTRODUCTION	10
4	DOSIMETRIC ASSESSMENT	11
5	DEFINITION OF REFERENCE POINTS	12
6	TEST CONFIGURATION POSITIONS FOR HANDSETS	13
7	RF EXPOSURE LIMITS	16
8	FCC MEASUREMENT PROCEDURES.....	17
9	RF CONDUCTED POWERS.....	22
10	SYSTEM VERIFICATION.....	45
11	SAR DATA SUMMARY	47
12	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	56
13	SAR MEASUREMENT VARIABILITY	60
14	EQUIPMENT LIST	61
15	MEASUREMENT UNCERTAINTIES	62
16	CONCLUSION.....	64
17	REFERENCES	65
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: SAR TEST SETUP PHOTOGRAPHS		

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 2 of 66	

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 17	Voice/Data	706.5 - 713.5 MHz
LTE Band 5 (Cell)	Voice/Data	824.7 - 848.3 MHz
LTE Band 4 (AWS)	Voice/Data	1710.7 - 1754.3 MHz
LTE Band 2 (PCS)	Voice/Data	1850.7 - 1909.3 MHz
2.4 GHz WLAN	Data	2412 - 2462 MHz
5.8 GHz WLAN	Data	5745 - 5825 MHz
5.2 GHz WLAN	Data	5180 - 5240 MHz
5.3 GHz WLAN	Data	5260 - 5320 MHz
5.5 GHz WLAN	Data	5500 - 5700 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
ANT+	Data	2402 - 2480 MHz

1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 TX Slot	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots	1 TX Slots	2 TX Slots	3 TX Slots	4 TX Slots
GSM/GPRS/EDGE 850	Maximum	32.5	32.5	28.5	27.0	25.5	27.5	26.0	25.0	23.5
	Nominal	32.0	32.0	28.0	26.5	25.0	27.0	25.5	24.5	23.0
GSM/GPRS/EDGE 1900	Maximum	29.5	29.5	25.5	23.5	22.5	27.0	25.0	23.5	22.5
	Nominal	29.0	29.0	25.0	23.0	22.0	26.5	24.5	23.0	22.0

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 3 of 66


Mode / Band		Modulated Average (dBm)			
		3GPP WCDMA Rel 99	3GPP HSDPA Rel 5	3GPP HSUPA Rel 6	3GPP DC-HSDPA Rel 8
UMTS Band 5 (850 MHz)	Maximum	23.0	23.0	23.0	22.5
	Nominal	22.5	22.5	22.5	22.0
UMTS Band 2 (1900 MHz)	Maximum	22.5	22.5	22.5	22.0
	Nominal	22.0	22.0	22.0	21.5

Mode / Band		Modulated Average (dBm)
LTE Band 17	Maximum	23.5
	Nominal	23.0
LTE Band 5	Maximum	23.0
	Nominal	22.5
LTE Band 4	Maximum	23.0
	Nominal	22.5
LTE Band 2	Maximum	22.5
	Nominal	22.0

Mode / Band		Modulated Average (dBm)
IEEE 802.11b (2.4 GHz)	Maximum	17.5
	Nominal	17.0
IEEE 802.11g (2.4 GHz)	Maximum	13.5
	Nominal	13.0
IEEE 802.11n (2.4 GHz)	Maximum	12.5
	Nominal	12.0
IEEE 802.11a (5 GHz)	Maximum	11.5
	Nominal	11.0
IEEE 802.11n (5 GHz)	Maximum	10.5
	Nominal	10.0
Bluetooth	Maximum	12.5
	Nominal	12.0
Bluetooth LE	Maximum	4.0
	Nominal	3.5

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 4 of 66	

1.3 DUT Antenna Locations



Note: Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC Filing.

Figure 1-1
DUT Antenna Locations

Table 1-1
Sides for SAR Testing

Sides for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
GPRS 850	Yes	Yes	No	Yes	No	Yes
GPRS 1900	Yes	Yes	No	Yes	No	Yes
UMTS 850	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Yes	Yes	No	Yes	No	Yes
LTE Band 17	Yes	Yes	No	Yes	No	Yes
LTE Band 5 (Cell)	Yes	Yes	No	Yes	No	Yes
LTE Band 4 (AWS)	Yes	Yes	No	Yes	No	Yes
LTE Band 2 (PCS)	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN	Yes	Yes	Yes	No	Yes	No

Note: Particular DUT edges were not required to be evaluated for Wireless Router and/or Extremity SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2 and FCC KDB Publication 648474 D04 Handset SAR v01r01 guidance, page 2. When the wireless router mode is enabled, all 5 GHz bands are disabled. Therefore 5 GHz WIFI is not considered in this section.

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 5 of 66	

1.4 Near Field Communications (NFC) Antenna

This DUT has NFC operations. The NFC antenna is integrated into the back of the device for this model. Therefore, all SAR tests were performed with the device which already incorporates the NFC antenna.




Figure 1-2
NFC Antenna Locations

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-3 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Figure 1-3
Simultaneous Transmission Paths

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT	 SAMSUNG	Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 6 of 66

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Head	Body-Worn Accessory	Wireless Router	Notes
1	GSM voice + 2.4 GHz Wi-Fi	Yes	Yes	N/A	
2	GSM voice + 5 GHz Wi-Fi	Yes	Yes	N/A	
3	GSM voice + 2.4 GHz Bluetooth	N/A	Yes	N/A	
4	UMTS + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
5	UMTS + 5 GHz Wi-Fi	Yes	Yes	N/A	
6	UMTS + 2.4 GHz Bluetooth	N/A	Yes	N/A	
7	LTE + 2.4 GHz Wi-Fi	Yes	Yes	Yes	
8	LTE + 5 GHz Wi-Fi	Yes	Yes	N/A	
9	LTE + 2.4 GHz Bluetooth	N/A	Yes	N/A	
10	GPRS/EDGE + 2.4 GHz Wi-Fi	N/A	N/A	Yes	
11	GPRS/EDGE + 5 GHz Wi-Fi	N/A	N/A	N/A	

- 2.4 GHz WLAN, 5 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
- All licensed modes share the same antenna path and cannot transmit simultaneously.
- When wireless router mode is enabled, all 5GHz bands are disabled.
- Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, no simultaneous transmission scenarios involving WIFI direct are specified above.
- When the user utilizes multiple services in UMTS 3G mode it uses multi-Radio Access Bearer or multi-RAB. The power control is based on a physical control channel (Dedicated Physical Control Channel [DPCCH]) and power control will be adjusted to meet the needs of both services. Therefore, the UMTS+WLAN scenario also represents the UMTS Voice/DATA + WLAN Hotspot scenario.

1.6 SAR Test Exclusions Applied

(A) WIFI/BT

Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; $[(18/10) * \sqrt{2.480}] = 2.8 < 3.0$. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

This device supports 20 MHz and 40 MHz Bandwidths for IEEE 802.11n for 5 GHz WIFI only. IEEE 802.11n was not evaluated for SAR since the average output power of 20 MHz and 40 MHz bandwidths was not more than 0.25 dB higher than the average output power of IEEE 802.11a.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 7 of 66

(B) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v02.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

1.7 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

1.8 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v02, D02v02r02, D03v01, D05v02r03, D06v01r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)
- October 2013 TCB Workshop Notes (GPRS Testing Considerations)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

	Head Serial Number	Body-Worn Serial Number	Hotspot Serial Number
GSM/GPRS/EDGE 850	PCT5	PCT5	PCT5
GSM/GPRS/EDGE 1900	PCT5	PCT5	PCT5
UMTS 850	PCT5	PCT5	PCT5
UMTS 1900	PCT5	PCT5	PCT5
LTE Band 17	PCT4	PCT4	PCT4
LTE Band 5 (Cell)	PCT4	PCT4	PCT4
LTE Band 4 (AWS)	PCT4	PCT4	PCT4
LTE Band 2 (PCS)	PCT4	PCT4	PCT4
2.4 GHz WLAN	PCT6	PCT6	PCT6
5 GHz WLAN	PCT4	PCT6	-

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 8 of 66	

2

LTE INFORMATION

LTE Information			
FCC ID	A3LSMA500M		
Form Factor	Portable Handset		
Frequency Range of each LTE transmission band	LTE Band 17 (706.5 - 713.5 MHz)		
	LTE Band 5 (Cell) (824.7 - 848.3 MHz)		
	LTE Band 4 (AWS) (1710.7 - 1754.3 MHz)		
	LTE Band 2 (PCS) (1850.7 - 1909.3 MHz)		
Channel Bandwidths	LTE Band 17: 5 MHz, 10 MHz		
	LTE Band 5 (Cell): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers and Frequencies (MHz)	Low	Mid	High
LTE Band 17: 5 MHz	706.5 (23755)	710 (23790)	713.5 (23825)
LTE Band 17: 10 MHz	709 (23780)	710 (23790)	711 (23800)
LTE Band 5 (Cell): 1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
LTE Band 5 (Cell): 3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
LTE Band 5 (Cell): 5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
LTE Band 5 (Cell): 10 MHz	829 (20450)	836.5 (20525)	844 (20600)
LTE Band 4 (AWS): 1.4 MHz	1710.7 (19957)	1732.5 (20175)	1754.3 (20393)
LTE Band 4 (AWS): 3 MHz	1711.5 (19965)	1732.5 (20175)	1753.5 (20385)
LTE Band 4 (AWS): 5 MHz	1712.5 (19975)	1732.5 (20175)	1752.5 (20375)
LTE Band 4 (AWS): 10 MHz	1715 (20000)	1732.5 (20175)	1750 (20350)
LTE Band 4 (AWS): 15 MHz	1717.5 (20025)	1732.5 (20175)	1747.5 (20325)
LTE Band 4 (AWS): 20 MHz	1720 (20050)	1732.5 (20175)	1745 (20300)
LTE Band 2 (PCS): 1.4 MHz	1850.7 (18607)	1880 (18900)	1909.3 (19193)
LTE Band 2 (PCS): 3 MHz	1851.5 (18615)	1880 (18900)	1908.5 (19185)
LTE Band 2 (PCS): 5 MHz	1852.5 (18625)	1880 (18900)	1907.5 (19175)
LTE Band 2 (PCS): 10 MHz	1855 (18650)	1880 (18900)	1905 (19150)
LTE Band 2 (PCS): 15 MHz	1857.5 (18675)	1880 (18900)	1902.5 (19125)
LTE Band 2 (PCS): 20 MHz	1860 (18700)	1880 (18900)	1900 (19100)
UE Category	4		
Modulations Supported in UL	QPSK, 16QAM		
LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided)	YES		
A-MPR (Additional MPR) disabled for SAR Testing?	YES		

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 9 of 66	

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

Equation 3-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 10 of 66

4

DOSIMETRIC ASSESSMENT

4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 4-1
Sample SAR Area Scan

Table 4-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid $\Delta z_{\text{zoom}}(n)$	Graded Grid		
				$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMA500M		SAR EVALUATION REPORT			Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset			Page 11 of 66

5

DEFINITION OF REFERENCE POINTS

5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 5-1
Close-Up Side view
of ERP

5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 5-3). The acoustic output was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 5-2
Front, back and side view of SAM Twin Phantom




Figure 5-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 12 of 66

6

TEST CONFIGURATION POSITIONS FOR HANDSETS

6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 6-1 Front, Side and Top View of Cheek Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

6.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 13 of 66




Figure 6-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 6-3 Side view w/ relevant markings

6.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




Figure 6-4 Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.5 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 14 of 66

the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

6.6 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 15 of 66

7 RF EXPOSURE LIMITS

7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 7-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 16 of 66

Power measurements were performed using a base station simulator under digital average power.

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

8.3 SAR Measurement Conditions for UMTS

8.3.1 Output Power Verification

Maximum output power is measured on the High, Middle and Low channels for each applicable transmission band according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121 (release 5), using the appropriate RMC with TPC (transmit power control) set to all "1s" or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.3.2 Head SAR Measurements for Handsets

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than 0.25 dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that resulted in the highest SAR for that RF channel in the 12.2 kbps RMC mode.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 17 of 66

8.3.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all “1s”.

8.3.4 SAR Measurements for Handsets with Rel 5 HSDPA

Body SAR for HSDPA is not required for handsets with HSDPA capabilities when the maximum average output power of each RF channel with HSDPA active is less than 0.25 dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration measured in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that resulted in the highest SAR in 12.2 kbps RMC mode for that RF channel.

The H-set used in FRC for HSDPA should be configured according to the UE category of a test device. The number of HS-DSCH/HSPDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the applicable H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the FRC for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 2 ms to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors of $\beta_c=9$ and $\beta_d=15$, and power offset parameters of $\Delta_{ACK} = \Delta_{NACK} = 5$ and $\Delta_{CQI}=2$ is used. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the FRC.

Sub-Test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{HS} = \beta_{HS}/\beta_c = 30/15 \Leftrightarrow \beta_{HS} = 30/15 * \beta_c$.
Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 8$ ($A_{HS} = 30/15$) with $\beta_{HS} = 30/15 * \beta_c$, and $\Delta_{CQI} = 7$ ($A_{HS} = 24/15$) with $\beta_{HS} = 24/15 * \beta_c$.
Note 3: CM = 1 for $\beta_c/\beta_d=12/15$, $\beta_{HS}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Figure 8-1
Table C.10.1.4 of TS 234.121-1

8.3.5 SAR Measurements for Handsets with Rel 6 HSUPA

Body SAR for HSUPA is not required when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25 dB higher than as measured without HSUPA/HSDPA using 12.2 kbps RMC and maximum SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit. Otherwise SAR is measured on the maximum output channel for the body exposure configuration produced highest SAR in 12.2 kbps RMC for that RF channel, using the additional procedures under “Release 6 HSPA data devices”

Head SAR for VOIP operations under HSPA is not required when maximum average output of each RF channel with HSPA is less than 0.25 dB higher than as measured using 12.2 kbps RMC. Otherwise SAR is measured using same HSPA configuration as used for body SAR.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 18 of 66

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	$\beta_{1e}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11/15 ⁽³⁾	15/15 ⁽³⁾	64	11/15 ⁽³⁾	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 ⁽⁴⁾	15/15 ⁽⁴⁾	64	15/15 ⁽⁴⁾	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{1e} = \beta_{1e}/\beta_c = 30/15 \Leftrightarrow \beta_{1e} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{1e}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1.g.

Note 6: β_{ed} can not be set directly; it is set by Absolute Grant Value.

8.3.6 SAR Measurement Conditions for DC-HSDPA

SAR test exclusion for DC-HSDPA devices is determined by power measurements according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to qualify for SAR test exclusion. DC-HSDPA uplink maximum output power measurements using the four Rel. 5 HSDPA subtests in Table C.10.1.4 of TS 234.121-1 is required.

When the maximum average output power of each RF channel with DC-HSDPA active is $\leq 1/4$ dB higher than that measured using 12.2 kbps RMC, or the maximum reported SAR for 12.2 kbps RMC is $\leq 75\%$ of the SAR limit, SAR evaluation for DC-HSDPA is not required.

8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 19 of 66	

8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

- a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
- c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.

8.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g/n transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

8.5.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

For 5 GHz, the highest average RF output power channel across the default test channels at the lowest data rate was selected for SAR evaluation in 802.11a. When the adjacent channels are higher in power than the default channels, these "required channels" were considered instead of the default

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 20 of 66

channels for SAR testing. 802.11n modes and higher data rates for 802.11a/n were evaluated only if the respective mode was higher than 0.25 dB or more than the 802.11a mode.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.

FCC ID: A3LSMA500M	 SAR EVALUATION REPORT 		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 21 of 66

9 RF CONDUCTED POWERS

9.1 GSM Conducted Powers

		Maximum Burst-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	32.34	32.35	28.12	26.83	25.04	27.17	25.88	23.09	23.20
	190	32.29	32.21	28.13	27.00	25.18	27.23	25.82	23.14	23.19
	251	32.24	32.10	28.09	26.99	25.08	27.12	25.86	23.00	23.00
GSM 1900	512	29.18	29.18	25.31	23.29	22.22	25.99	24.71	21.66	21.68
	661	29.06	29.07	25.29	23.34	22.24	26.09	24.72	21.66	21.78
	810	29.15	29.10	25.28	23.36	22.26	26.13	25.00	21.99	21.89
		Calculated Maximum Frame-Averaged Output Power								
		Voice	GPRS/EDGE Data (GMSK)				EDGE Data (8-PSK)			
Band	Channel	GSM [dBm] CS (1 Slot)	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	GPRS [dBm] 3 Tx Slot	GPRS [dBm] 4 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot	EDGE [dBm] 3 Tx Slot	EDGE [dBm] 4 Tx Slot
GSM 850	128	23.31	23.32	22.10	22.57	22.03	18.14	19.86	18.83	20.19
	190	23.26	23.18	22.11	22.74	22.17	18.20	19.80	18.88	20.18
	251	23.21	23.07	22.07	22.73	22.07	18.09	19.84	18.74	19.99
GSM 1900	512	20.15	20.15	19.29	19.03	19.21	16.96	18.69	17.40	18.67
	661	20.03	20.04	19.27	19.08	19.23	17.06	18.70	17.40	18.77
	810	20.12	20.07	19.26	19.10	19.25	17.10	18.98	17.73	18.88
GSM 850	Frame	22.97	22.97	21.98	22.24	21.99	17.97	19.48	20.24	19.99
GSM 1900	Avg.Targets:	19.97	19.97	18.98	18.74	18.99	17.47	18.48	18.74	18.99

Note:

- Both burst-averaged and calculated frame-averaged powers are included. Frame-averaged power was calculated from the measured burst-averaged power by converting the slot powers into linear units and calculating the energy over 8 timeslots.
- The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
- GPRS/EDGE (GMSK) output powers were measured with coding scheme setting of 1 (CS1) on the base station simulator. CS1 was configured to measure GPRS output power measurements and SAR to ensure GMSK modulation in the signal. Our Investigation has shown that CS1 - CS4 settings do not have any impact on the output levels or modulation in the GPRS modes.
- EDGE (8-PSK) output powers were measured with MCS7 on the base station simulator. MCS7 coding scheme was used to measure the output powers for EDGE since investigation has shown that choosing MCS7 coding scheme will ensure 8-PSK modulation. It has been shown that MCS levels that produce 8PSK modulation do not have an impact on output power.

GSM Class: B
GPRS Multislot class: 33 (Max 4 Tx uplink slots)
EDGE Multislot class: 33 (Max 4 Tx uplink slots)
DTM Multislot Class: N/A




Figure 9-1
Power Measurement Setup

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 22 of 66	

9.2 UMTS Conducted Powers

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			3GPP MPR [dB]
			4132	4183	4233	9262	9400	9538	
99	WCDMA	12.2 kbps RMC	22.97	22.94	22.95	22.27	22.15	22.21	-
99		12.2 kbps AMR	23.00	22.90	22.93	22.30	22.23	22.18	-
6	HSDPA	Subtest 1	21.69	21.49	21.31	21.00	20.98	21.04	0
6		Subtest 2	21.66	21.52	21.44	20.98	21.00	21.13	0
6		Subtest 3	21.17	20.99	20.84	20.53	20.60	20.58	0.5
6		Subtest 4	21.21	20.97	20.80	20.50	20.45	20.65	0.5
6	HSUPA	Subtest 1	21.06	21.00	21.04	21.12	21.06	21.14	0
6		Subtest 2	20.55	20.66	20.40	20.04	20.02	20.11	2
6		Subtest 3	20.39	20.46	20.27	19.50	20.05	20.20	1
6		Subtest 4	20.65	21.17	20.82	20.57	20.64	20.58	2
6		Subtest 5	21.18	21.11	21.00	20.52	20.69	20.76	0
8	DC-HSDPA	Subtest 1	21.56	21.78	21.76	20.76	20.65	21.06	0
8		Subtest 2	21.58	21.69	21.69	20.78	20.36	20.79	0
8		Subtest 3	21.42	21.41	21.12	20.19	20.22	20.62	0.5
8		Subtest 4	21.42	21.19	21.29	20.29	20.33	20.55	0.5

UMTS SAR was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

DC-HSDPA considerations

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12 (QPSK) was confirmed to be used during DC-HSDPA measurements
- Measured maximum output powers for DC-HSDPA were not greater than 1/4 dB higher than the WCDMA 12.2 kbps RMC maximum output, as a result, SAR is not required for DC-HSDPA
- The DUT supports UE category 24 for HSDPA

It is expected by the manufacturer that MPR for some HSPA subtests may be up to 2 dB more than specified by 3GPP, but also as low as 0 dB according to the chipset implementation in this model.




Figure 9-2
Power Measurement Setup

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 23 of 66	

9.3 LTE Conducted Powers

9.3.1 LTE Band 17

Table 9-1
LTE Band 17 Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	710.0	23790	10	QPSK	1	0	23.37	0	0
	710.0	23790	10	QPSK	1	25	22.97	0	0
	710.0	23790	10	QPSK	1	49	22.89	0	0
	710.0	23790	10	QPSK	25	0	22.15	0-1	1
	710.0	23790	10	QPSK	25	12	22.12	0-1	1
	710.0	23790	10	QPSK	25	25	21.85	0-1	1
	710.0	23790	10	QPSK	50	0	21.91	0-1	1
	710.0	23790	10	16QAM	1	0	22.32	0-1	1
	710.0	23790	10	16QAM	1	25	22.12	0-1	1
	710.0	23790	10	16QAM	1	49	21.83	0-1	1
	710.0	23790	10	16QAM	25	0	21.17	0-2	2
	710.0	23790	10	16QAM	25	12	21.04	0-2	2
	710.0	23790	10	16QAM	25	25	20.83	0-2	2
	710.0	23790	10	16QAM	50	0	20.89	0-2	2

Note: LTE Band 17 at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

Table 9-2
LTE Band 17 Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	710.0	23790	5	QPSK	1	0	22.67	0	0
	710.0	23790	5	QPSK	1	12	22.55	0	0
	710.0	23790	5	QPSK	1	24	22.40	0	0
	710.0	23790	5	QPSK	12	0	21.52	0-1	1
	710.0	23790	5	QPSK	12	6	21.83	0-1	1
	710.0	23790	5	QPSK	12	13	21.87	0-1	1
	710.0	23790	5	QPSK	25	0	21.77	0-1	1
	710.0	23790	5	16-QAM	1	0	21.87	0-1	1
	710.0	23790	5	16-QAM	1	12	21.38	0-1	1
	710.0	23790	5	16-QAM	1	24	22.04	0-1	1
	710.0	23790	5	16-QAM	12	0	21.24	0-2	2
	710.0	23790	5	16-QAM	12	6	20.73	0-2	2
	710.0	23790	5	16-QAM	12	13	20.85	0-2	2
	710.0	23790	5	16-QAM	25	0	20.79	0-2	2

Note: LTE Band 17 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 24 of 66

9.3.2

LTE Band 5 (Cell)

Table 9-3
LTE Band 5 (Cell) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	836.5	20525	10	QPSK	1	0	22.91	0	0
	836.5	20525	10	QPSK	1	25	22.69	0	0
	836.5	20525	10	QPSK	1	49	22.33	0	0
	836.5	20525	10	QPSK	25	0	21.73	0-1	1
	836.5	20525	10	QPSK	25	12	21.60	0-1	1
	836.5	20525	10	QPSK	25	25	21.46	0-1	1
	836.5	20525	10	QPSK	50	0	21.47	0-1	1
	836.5	20525	10	16QAM	1	0	22.00	0-1	1
	836.5	20525	10	16QAM	1	25	21.87	0-1	1
	836.5	20525	10	16QAM	1	49	21.39	0-1	1
	836.5	20525	10	16QAM	25	0	20.74	0-2	2
	836.5	20525	10	16QAM	25	12	20.61	0-2	2
	836.5	20525	10	16QAM	25	25	20.51	0-2	2
	836.5	20525	10	16QAM	50	0	20.49	0-2	2

Note: LTE Band 5 (Cell) at 10 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 25 of 66

Table 9-4
LTE Band 5 (Cell) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	826.5	20425	5	QPSK	1	0	22.38	0	0
	826.5	20425	5	QPSK	1	12	22.27	0	0
	826.5	20425	5	QPSK	1	24	22.27	0	0
	826.5	20425	5	QPSK	12	0	21.23	0-1	1
	826.5	20425	5	QPSK	12	6	21.24	0-1	1
	826.5	20425	5	QPSK	12	13	21.25	0-1	1
	826.5	20425	5	QPSK	25	0	21.18	0-1	1
	826.5	20425	5	16-QAM	1	0	21.48	0-1	1
	826.5	20425	5	16-QAM	1	12	21.31	0-1	1
	826.5	20425	5	16-QAM	1	24	21.26	0-1	1
	826.5	20425	5	16-QAM	12	0	20.28	0-2	2
	826.5	20425	5	16-QAM	12	6	20.34	0-2	2
	826.5	20425	5	16-QAM	12	13	20.21	0-2	2
	826.5	20425	5	16-QAM	25	0	20.19	0-2	2
Mid	836.5	20525	5	QPSK	1	0	22.27	0	0
	836.5	20525	5	QPSK	1	12	22.45	0	0
	836.5	20525	5	QPSK	1	24	22.01	0	0
	836.5	20525	5	QPSK	12	0	21.32	0-1	1
	836.5	20525	5	QPSK	12	6	21.37	0-1	1
	836.5	20525	5	QPSK	12	13	21.33	0-1	1
	836.5	20525	5	QPSK	25	0	21.28	0-1	1
	836.5	20525	5	16-QAM	1	0	21.60	0-1	1
	836.5	20525	5	16-QAM	1	12	21.81	0-1	1
	836.5	20525	5	16-QAM	1	24	21.58	0-1	1
	836.5	20525	5	16-QAM	12	0	20.50	0-2	2
	836.5	20525	5	16-QAM	12	6	20.46	0-2	2
	836.5	20525	5	16-QAM	12	13	20.37	0-2	2
	836.5	20525	5	16-QAM	25	0	20.22	0-2	2
High	846.5	20625	5	QPSK	1	0	22.43	0	0
	846.5	20625	5	QPSK	1	12	22.31	0	0
	846.5	20625	5	QPSK	1	24	22.27	0	0
	846.5	20625	5	QPSK	12	0	21.25	0-1	1
	846.5	20625	5	QPSK	12	6	21.34	0-1	1
	846.5	20625	5	QPSK	12	13	21.26	0-1	1
	846.5	20625	5	QPSK	25	0	21.33	0-1	1
	846.5	20625	5	16-QAM	1	0	21.46	0-1	1
	846.5	20625	5	16-QAM	1	12	21.26	0-1	1
	846.5	20625	5	16-QAM	1	24	21.40	0-1	1
	846.5	20625	5	16-QAM	12	0	20.42	0-2	2
	846.5	20625	5	16-QAM	12	6	20.42	0-2	2
	846.5	20625	5	16-QAM	12	13	20.29	0-2	2
	846.5	20625	5	16-QAM	25	0	20.33	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 26 of 66

Table 9-5
LTE Band 5 (Cell) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	825.5	20415	3	QPSK	1	0	22.43	0	0
	825.5	20415	3	QPSK	1	7	22.30	0	0
	825.5	20415	3	QPSK	1	14	22.26	0	0
	825.5	20415	3	QPSK	8	0	21.28	0-1	1
	825.5	20415	3	QPSK	8	4	21.32	0-1	1
	825.5	20415	3	QPSK	8	7	21.27	0-1	1
	825.5	20415	3	QPSK	15	0	21.30	0-1	1
	825.5	20415	3	16-QAM	1	0	21.40	0-1	1
	825.5	20415	3	16-QAM	1	7	21.27	0-1	1
	825.5	20415	3	16-QAM	1	14	21.30	0-1	1
	825.5	20415	3	16-QAM	8	0	20.23	0-2	2
	825.5	20415	3	16-QAM	8	4	20.24	0-2	2
	825.5	20415	3	16-QAM	8	7	20.27	0-2	2
	825.5	20415	3	16-QAM	15	0	20.33	0-2	2
Mid	836.5	20525	3	QPSK	1	0	22.45	0	0
	836.5	20525	3	QPSK	1	7	22.36	0	0
	836.5	20525	3	QPSK	1	14	22.25	0	0
	836.5	20525	3	QPSK	8	0	21.28	0-1	1
	836.5	20525	3	QPSK	8	4	21.33	0-1	1
	836.5	20525	3	QPSK	8	7	21.25	0-1	1
	836.5	20525	3	QPSK	15	0	21.29	0-1	1
	836.5	20525	3	16-QAM	1	0	21.43	0-1	1
	836.5	20525	3	16-QAM	1	7	21.33	0-1	1
	836.5	20525	3	16-QAM	1	14	21.37	0-1	1
	836.5	20525	3	16-QAM	8	0	20.22	0-2	2
	836.5	20525	3	16-QAM	8	4	20.23	0-2	2
	836.5	20525	3	16-QAM	8	7	20.21	0-2	2
	836.5	20525	3	16-QAM	15	0	20.34	0-2	2
High	847.5	20635	3	QPSK	1	0	22.34	0	0
	847.5	20635	3	QPSK	1	7	22.27	0	0
	847.5	20635	3	QPSK	1	14	22.32	0	0
	847.5	20635	3	QPSK	8	0	21.32	0-1	1
	847.5	20635	3	QPSK	8	4	21.30	0-1	1
	847.5	20635	3	QPSK	8	7	21.34	0-1	1
	847.5	20635	3	QPSK	15	0	21.27	0-1	1
	847.5	20635	3	16-QAM	1	0	21.45	0-1	1
	847.5	20635	3	16-QAM	1	7	21.31	0-1	1
	847.5	20635	3	16-QAM	1	14	21.07	0-1	1
	847.5	20635	3	16-QAM	8	0	20.25	0-2	2
	847.5	20635	3	16-QAM	8	4	20.23	0-2	2
	847.5	20635	3	16-QAM	8	7	20.19	0-2	2
	847.5	20635	3	16-QAM	15	0	20.25	0-2	2

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 27 of 66	

Table 9-6
LTE Band 5 (Cell) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	824.7	20407	1.4	QPSK	1	0	22.64	0	0
	824.7	20407	1.4	QPSK	1	2	22.55	0	0
	824.7	20407	1.4	QPSK	1	5	22.48	0	0
	824.7	20407	1.4	QPSK	3	0	22.72	0	0
	824.7	20407	1.4	QPSK	3	2	22.65	0	0
	824.7	20407	1.4	QPSK	3	3	22.62	0	0
	824.7	20407	1.4	QPSK	6	0	21.62	0-1	1
	824.7	20407	1.4	16-QAM	1	0	21.34	0-1	1
	824.7	20407	1.4	16-QAM	1	2	21.34	0-1	1
	824.7	20407	1.4	16-QAM	1	5	21.27	0-1	1
	824.7	20407	1.4	16-QAM	3	0	21.67	0-1	1
	824.7	20407	1.4	16-QAM	3	2	21.63	0-1	1
	824.7	20407	1.4	16-QAM	3	3	21.69	0-1	1
	824.7	20407	1.4	16-QAM	6	0	20.48	0-2	2
Mid	836.5	20525	1.4	QPSK	1	0	22.39	0	0
	836.5	20525	1.4	QPSK	1	2	22.43	0	0
	836.5	20525	1.4	QPSK	1	5	22.32	0	0
	836.5	20525	1.4	QPSK	3	0	22.36	0	0
	836.5	20525	1.4	QPSK	3	2	22.37	0	0
	836.5	20525	1.4	QPSK	3	3	22.31	0	0
	836.5	20525	1.4	QPSK	6	0	21.38	0-1	1
	836.5	20525	1.4	16-QAM	1	0	21.34	0-1	1
	836.5	20525	1.4	16-QAM	1	2	21.41	0-1	1
	836.5	20525	1.4	16-QAM	1	5	21.39	0-1	1
	836.5	20525	1.4	16-QAM	3	0	21.47	0-1	1
	836.5	20525	1.4	16-QAM	3	2	21.38	0-1	1
	836.5	20525	1.4	16-QAM	3	3	21.26	0-1	1
	836.5	20525	1.4	16-QAM	6	0	20.31	0-2	2
High	848.3	20643	1.4	QPSK	1	0	22.64	0	0
	848.3	20643	1.4	QPSK	1	2	22.61	0	0
	848.3	20643	1.4	QPSK	1	5	22.69	0	0
	848.3	20643	1.4	QPSK	3	0	22.65	0	0
	848.3	20643	1.4	QPSK	3	2	22.65	0	0
	848.3	20643	1.4	QPSK	3	3	22.70	0	0
	848.3	20643	1.4	QPSK	6	0	21.65	0-1	1
	848.3	20643	1.4	16-QAM	1	0	21.45	0-1	1
	848.3	20643	1.4	16-QAM	1	2	21.41	0-1	1
	848.3	20643	1.4	16-QAM	1	5	21.50	0-1	1
	848.3	20643	1.4	16-QAM	3	0	21.62	0-1	1
	848.3	20643	1.4	16-QAM	3	2	21.61	0-1	1
	848.3	20643	1.4	16-QAM	3	3	21.63	0-1	1
	848.3	20643	1.4	16-QAM	6	0	20.54	0-2	2

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 28 of 66	

9.3.3

LTE Band 4 (AWS)

Table 9-7

LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Mid	1732.5	20175	20	QPSK	1	0	23.00	0	0
	1732.5	20175	20	QPSK	1	50	22.59	0	0
	1732.5	20175	20	QPSK	1	99	22.65	0	0
	1732.5	20175	20	QPSK	50	0	21.63	0-1	1
	1732.5	20175	20	QPSK	50	25	21.43	0-1	1
	1732.5	20175	20	QPSK	50	50	21.50	0-1	1
	1732.5	20175	20	QPSK	100	0	21.50	0-1	1
	1732.5	20175	20	16QAM	1	0	22.00	0-1	1
	1732.5	20175	20	16QAM	1	50	21.56	0-1	1
	1732.5	20175	20	16QAM	1	99	21.60	0-1	1
	1732.5	20175	20	16QAM	50	0	20.67	0-2	2
	1732.5	20175	20	16QAM	50	25	20.55	0-2	2
	1732.5	20175	20	16QAM	50	50	20.59	0-2	2
	1732.5	20175	20	16QAM	100	0	20.45	0-2	2

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 29 of 66

Table 9-8
LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1717.5	20025	15	QPSK	1	0	22.70	0	0
	1717.5	20025	15	QPSK	1	36	22.80	0	0
	1717.5	20025	15	QPSK	1	74	22.78	0	0
	1717.5	20025	15	QPSK	36	0	21.60	0-1	1
	1717.5	20025	15	QPSK	36	18	21.71	0-1	1
	1717.5	20025	15	QPSK	36	37	21.64	0-1	1
	1717.5	20025	15	QPSK	75	0	21.65	0-1	1
	1717.5	20025	15	16QAM	1	0	21.69	0-1	1
	1717.5	20025	15	16QAM	1	36	21.75	0-1	1
	1717.5	20025	15	16QAM	1	74	21.78	0-1	1
	1717.5	20025	15	16QAM	36	0	20.68	0-2	2
	1717.5	20025	15	16QAM	36	18	20.66	0-2	2
	1717.5	20025	15	16QAM	36	37	20.72	0-2	2
Mid	1732.5	20175	15	QPSK	1	0	22.75	0	0
	1732.5	20175	15	QPSK	1	36	22.71	0	0
	1732.5	20175	15	QPSK	1	74	22.65	0	0
	1732.5	20175	15	QPSK	36	0	21.65	0-1	1
	1732.5	20175	15	QPSK	36	18	21.65	0-1	1
	1732.5	20175	15	QPSK	36	37	21.60	0-1	1
	1732.5	20175	15	QPSK	75	0	21.56	0-1	1
	1732.5	20175	15	16QAM	1	0	21.84	0-1	1
	1732.5	20175	15	16QAM	1	36	21.78	0-1	1
	1732.5	20175	15	16QAM	1	74	21.64	0-1	1
	1732.5	20175	15	16QAM	36	0	20.73	0-2	2
	1732.5	20175	15	16QAM	36	18	20.71	0-2	2
	1732.5	20175	15	16QAM	36	37	20.58	0-2	2
	1732.5	20175	15	16QAM	75	0	20.62	0-2	2
High	1747.5	20325	15	QPSK	1	0	22.71	0	0
	1747.5	20325	15	QPSK	1	36	22.58	0	0
	1747.5	20325	15	QPSK	1	74	22.60	0	0
	1747.5	20325	15	QPSK	36	0	21.52	0-1	1
	1747.5	20325	15	QPSK	36	18	21.49	0-1	1
	1747.5	20325	15	QPSK	36	37	21.45	0-1	1
	1747.5	20325	15	QPSK	75	0	21.42	0-1	1
	1747.5	20325	15	16QAM	1	0	21.58	0-1	1
	1747.5	20325	15	16QAM	1	36	21.44	0-1	1
	1747.5	20325	15	16QAM	1	74	21.48	0-1	1
	1747.5	20325	15	16QAM	36	0	20.50	0-2	2
	1747.5	20325	15	16QAM	36	18	20.61	0-2	2
	1747.5	20325	15	16QAM	36	37	20.53	0-2	2
	1747.5	20325	15	16QAM	75	0	20.47	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 30 of 66	

Table 9-9
LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1715	20000	10	QPSK	1	0	22.66	0	0
	1715	20000	10	QPSK	1	25	22.87	0	0
	1715	20000	10	QPSK	1	49	22.50	0	0
	1715	20000	10	QPSK	25	0	21.55	0-1	1
	1715	20000	10	QPSK	25	12	21.71	0-1	1
	1715	20000	10	QPSK	25	25	21.63	0-1	1
	1715	20000	10	QPSK	50	0	21.59	0-1	1
	1715	20000	10	16QAM	1	0	21.63	0-1	1
	1715	20000	10	16QAM	1	25	21.84	0-1	1
	1715	20000	10	16QAM	1	49	21.74	0-1	1
	1715	20000	10	16QAM	25	0	20.62	0-2	2
	1715	20000	10	16QAM	25	12	20.69	0-2	2
	1715	20000	10	16QAM	25	25	20.63	0-2	2
	1715	20000	10	16QAM	50	0	20.66	0-2	2
Mid	1732.5	20175	10	QPSK	1	0	22.79	0	0
	1732.5	20175	10	QPSK	1	25	22.64	0	0
	1732.5	20175	10	QPSK	1	49	22.93	0	0
	1732.5	20175	10	QPSK	25	0	21.70	0-1	1
	1732.5	20175	10	QPSK	25	12	21.65	0-1	1
	1732.5	20175	10	QPSK	25	25	21.61	0-1	1
	1732.5	20175	10	QPSK	50	0	21.62	0-1	1
	1732.5	20175	10	16QAM	1	0	21.90	0-1	1
	1732.5	20175	10	16QAM	1	25	21.69	0-1	1
	1732.5	20175	10	16QAM	1	49	21.68	0-1	1
	1732.5	20175	10	16QAM	25	0	20.79	0-2	2
	1732.5	20175	10	16QAM	25	12	20.68	0-2	2
	1732.5	20175	10	16QAM	25	25	20.67	0-2	2
	1732.5	20175	10	16QAM	50	0	20.71	0-2	2
High	1750	20350	10	QPSK	1	0	22.64	0	0
	1750	20350	10	QPSK	1	25	22.55	0	0
	1750	20350	10	QPSK	1	49	22.41	0	0
	1750	20350	10	QPSK	25	0	21.53	0-1	1
	1750	20350	10	QPSK	25	12	21.48	0-1	1
	1750	20350	10	QPSK	25	25	21.46	0-1	1
	1750	20350	10	QPSK	50	0	21.39	0-1	1
	1750	20350	10	16QAM	1	0	21.44	0-1	1
	1750	20350	10	16QAM	1	25	21.57	0-1	1
	1750	20350	10	16QAM	1	49	21.45	0-1	1
	1750	20350	10	16QAM	25	0	20.64	0-2	2
	1750	20350	10	16QAM	25	12	20.62	0-2	2
	1750	20350	10	16QAM	25	25	20.50	0-2	2
	1750	20350	10	16QAM	50	0	20.42	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 31 of 66	

Table 9-10
LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1712.5	19975	5	QPSK	1	0	22.91	0	0
	1712.5	19975	5	QPSK	1	12	22.75	0	0
	1712.5	19975	5	QPSK	1	24	22.50	0	0
	1712.5	19975	5	QPSK	12	0	21.53	0-1	1
	1712.5	19975	5	QPSK	12	6	21.49	0-1	1
	1712.5	19975	5	QPSK	12	13	21.53	0-1	1
	1712.5	19975	5	QPSK	25	0	21.53	0-1	1
	1712.5	19975	5	16-QAM	1	0	21.79	0-1	1
	1712.5	19975	5	16-QAM	1	12	21.62	0-1	1
	1712.5	19975	5	16-QAM	1	24	21.70	0-1	1
	1712.5	19975	5	16-QAM	12	0	20.56	0-2	2
	1712.5	19975	5	16-QAM	12	6	20.53	0-2	2
	1712.5	19975	5	16-QAM	12	13	20.64	0-2	2
Mid	1732.5	20175	5	QPSK	1	0	22.82	0	0
	1732.5	20175	5	QPSK	1	12	22.74	0	0
	1732.5	20175	5	QPSK	1	24	22.84	0	0
	1732.5	20175	5	QPSK	12	0	21.64	0-1	1
	1732.5	20175	5	QPSK	12	6	21.66	0-1	1
	1732.5	20175	5	QPSK	12	13	21.59	0-1	1
	1732.5	20175	5	QPSK	25	0	21.59	0-1	1
	1732.5	20175	5	16-QAM	1	0	21.98	0-1	1
	1732.5	20175	5	16-QAM	1	12	21.65	0-1	1
	1732.5	20175	5	16-QAM	1	24	21.67	0-1	1
	1732.5	20175	5	16-QAM	12	0	20.59	0-2	2
	1732.5	20175	5	16-QAM	12	6	20.70	0-2	2
	1732.5	20175	5	16-QAM	12	13	20.61	0-2	2
	1732.5	20175	5	16-QAM	25	0	20.67	0-2	2
High	1752.5	20375	5	QPSK	1	0	22.78	0	0
	1752.5	20375	5	QPSK	1	12	22.81	0	0
	1752.5	20375	5	QPSK	1	24	22.56	0	0
	1752.5	20375	5	QPSK	12	0	21.59	0-1	1
	1752.5	20375	5	QPSK	12	6	21.66	0-1	1
	1752.5	20375	5	QPSK	12	13	21.58	0-1	1
	1752.5	20375	5	QPSK	25	0	21.53	0-1	1
	1752.5	20375	5	16-QAM	1	0	21.92	0-1	1
	1752.5	20375	5	16-QAM	1	12	21.74	0-1	1
	1752.5	20375	5	16-QAM	1	24	21.63	0-1	1
	1752.5	20375	5	16-QAM	12	0	20.53	0-2	2
	1752.5	20375	5	16-QAM	12	6	20.73	0-2	2
	1752.5	20375	5	16-QAM	12	13	20.52	0-2	2
	1752.5	20375	5	16-QAM	25	0	20.58	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 32 of 66

Table 9-11
LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1711.5	19965	3	QPSK	1	0	22.87	0	0
	1711.5	19965	3	QPSK	1	7	22.82	0	0
	1711.5	19965	3	QPSK	1	14	22.22	0	0
	1711.5	19965	3	QPSK	8	0	21.48	0-1	1
	1711.5	19965	3	QPSK	8	4	21.49	0-1	1
	1711.5	19965	3	QPSK	8	7	21.52	0-1	1
	1711.5	19965	3	QPSK	15	0	21.47	0-1	1
	1711.5	19965	3	16-QAM	1	0	21.73	0-1	1
	1711.5	19965	3	16-QAM	1	7	21.71	0-1	1
	1711.5	19965	3	16-QAM	1	14	21.66	0-1	1
	1711.5	19965	3	16-QAM	8	0	20.50	0-2	2
	1711.5	19965	3	16-QAM	8	4	20.56	0-2	2
	1711.5	19965	3	16-QAM	8	7	20.55	0-2	2
Mid	1732.5	20175	3	QPSK	1	0	22.86	0	0
	1732.5	20175	3	QPSK	1	7	22.67	0	0
	1732.5	20175	3	QPSK	1	14	23.00	0	0
	1732.5	20175	3	QPSK	8	0	21.69	0-1	1
	1732.5	20175	3	QPSK	8	4	21.66	0-1	1
	1732.5	20175	3	QPSK	8	7	21.60	0-1	1
	1732.5	20175	3	QPSK	15	0	21.65	0-1	1
	1732.5	20175	3	16-QAM	1	0	22.00	0-1	1
	1732.5	20175	3	16-QAM	1	7	21.56	0-1	1
	1732.5	20175	3	16-QAM	1	14	21.71	0-1	1
	1732.5	20175	3	16-QAM	8	0	20.65	0-2	2
	1732.5	20175	3	16-QAM	8	4	20.67	0-2	2
	1732.5	20175	3	16-QAM	8	7	20.70	0-2	2
	1732.5	20175	3	16-QAM	15	0	20.76	0-2	2
High	1753.5	20385	3	QPSK	1	0	22.71	0	0
	1753.5	20385	3	QPSK	1	7	22.78	0	0
	1753.5	20385	3	QPSK	1	14	22.37	0	0
	1753.5	20385	3	QPSK	8	0	21.60	0-1	1
	1753.5	20385	3	QPSK	8	4	21.65	0-1	1
	1753.5	20385	3	QPSK	8	7	21.59	0-1	1
	1753.5	20385	3	QPSK	15	0	21.50	0-1	1
	1753.5	20385	3	16-QAM	1	0	21.78	0-1	1
	1753.5	20385	3	16-QAM	1	7	21.87	0-1	1
	1753.5	20385	3	16-QAM	1	14	21.60	0-1	1
	1753.5	20385	3	16-QAM	8	0	20.67	0-2	2
	1753.5	20385	3	16-QAM	8	4	20.74	0-2	2
	1753.5	20385	3	16-QAM	8	7	20.49	0-2	2
	1753.5	20385	3	16-QAM	15	0	20.53	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 33 of 66	

Table 9-12
LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1710.7	19957	1.4	QPSK	1	0	22.94	0	0
	1710.7	19957	1.4	QPSK	1	2	22.84	0	0
	1710.7	19957	1.4	QPSK	1	5	22.64	0	0
	1710.7	19957	1.4	QPSK	3	0	22.61	0	0
	1710.7	19957	1.4	QPSK	3	2	22.81	0	0
	1710.7	19957	1.4	QPSK	3	3	22.42	0	0
	1710.7	19957	1.4	QPSK	6	0	21.14	0-1	1
	1710.7	19957	1.4	16-QAM	1	0	21.66	0-1	1
	1710.7	19957	1.4	16-QAM	1	2	21.88	0-1	1
	1710.7	19957	1.4	16-QAM	1	5	21.52	0-1	1
	1710.7	19957	1.4	16-QAM	3	0	21.20	0-1	1
	1710.7	19957	1.4	16-QAM	3	2	21.32	0-1	1
	1710.7	19957	1.4	16-QAM	3	3	21.30	0-1	1
Mid	1710.7	19957	1.4	16-QAM	6	0	20.69	0-2	2
	1732.5	20175	1.4	QPSK	1	0	22.92	0	0
	1732.5	20175	1.4	QPSK	1	2	22.54	0	0
	1732.5	20175	1.4	QPSK	1	5	22.32	0	0
	1732.5	20175	1.4	QPSK	3	0	22.58	0	0
	1732.5	20175	1.4	QPSK	3	2	22.78	0	0
	1732.5	20175	1.4	QPSK	3	3	22.40	0	0
	1732.5	20175	1.4	QPSK	6	0	21.50	0-1	1
	1732.5	20175	1.4	16-QAM	1	0	21.24	0-1	1
	1732.5	20175	1.4	16-QAM	1	2	21.32	0-1	1
	1732.5	20175	1.4	16-QAM	1	5	21.62	0-1	1
	1732.5	20175	1.4	16-QAM	3	0	21.45	0-1	1
	1732.5	20175	1.4	16-QAM	3	2	21.54	0-1	1
	1732.5	20175	1.4	16-QAM	3	3	21.60	0-1	1
High	1732.5	20175	1.4	16-QAM	6	0	20.72	0-2	2
	1754.3	20393	1.4	QPSK	1	0	22.62	0	0
	1754.3	20393	1.4	QPSK	1	2	22.76	0	0
	1754.3	20393	1.4	QPSK	1	5	22.04	0	0
	1754.3	20393	1.4	QPSK	3	0	22.40	0	0
	1754.3	20393	1.4	QPSK	3	2	22.15	0	0
	1754.3	20393	1.4	QPSK	3	3	22.38	0	0
	1754.3	20393	1.4	QPSK	6	0	21.20	0-1	1
	1754.3	20393	1.4	16-QAM	1	0	21.76	0-1	1
	1754.3	20393	1.4	16-QAM	1	2	21.49	0-1	1
	1754.3	20393	1.4	16-QAM	1	5	21.40	0-1	1
	1754.3	20393	1.4	16-QAM	3	0	21.54	0-1	1
	1754.3	20393	1.4	16-QAM	3	2	21.68	0-1	1
	1754.3	20393	1.4	16-QAM	3	3	21.38	0-1	1
	1754.3	20393	1.4	16-QAM	6	0	20.76	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 34 of 66

9.3.4

LTE Band 2 (PCS)

Table 9-13
LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1860	18700	20	QPSK	1	0	21.50	0	0
	1860	18700	20	QPSK	1	50	21.55	0	0
	1860	18700	20	QPSK	1	99	21.66	0	0
	1860	18700	20	QPSK	50	0	20.60	0-1	1
	1860	18700	20	QPSK	50	25	20.56	0-1	1
	1860	18700	20	QPSK	50	50	20.52	0-1	1
	1860	18700	20	QPSK	100	0	20.53	0-1	1
	1860	18700	20	16QAM	1	0	20.90	0-1	1
	1860	18700	20	16QAM	1	50	20.80	0-1	1
	1860	18700	20	16QAM	1	99	20.73	0-1	1
	1860	18700	20	16QAM	50	0	19.90	0-2	2
	1860	18700	20	16QAM	50	25	19.56	0-2	2
	1860	18700	20	16QAM	50	50	19.57	0-2	2
	1860	18700	20	16QAM	100	0	19.51	0-2	2
Mid	1880.0	18900	20	QPSK	1	0	21.51	0	0
	1880.0	18900	20	QPSK	1	50	21.66	0	0
	1880.0	18900	20	QPSK	1	99	21.68	0	0
	1880.0	18900	20	QPSK	50	0	20.57	0-1	1
	1880.0	18900	20	QPSK	50	25	20.55	0-1	1
	1880.0	18900	20	QPSK	50	50	20.50	0-1	1
	1880.0	18900	20	QPSK	100	0	20.54	0-1	1
	1880.0	18900	20	16QAM	1	0	20.88	0-1	1
	1880.0	18900	20	16QAM	1	50	20.82	0-1	1
	1880.0	18900	20	16QAM	1	99	20.54	0-1	1
	1880.0	18900	20	16QAM	50	0	19.81	0-2	2
	1880.0	18900	20	16QAM	50	25	19.57	0-2	2
	1880.0	18900	20	16QAM	50	50	19.50	0-2	2
	1880.0	18900	20	16QAM	100	0	19.55	0-2	2
High	1900	19100	20	QPSK	1	0	21.69	0	0
	1900	19100	20	QPSK	1	50	21.67	0	0
	1900	19100	20	QPSK	1	99	21.68	0	0
	1900	19100	20	QPSK	50	0	20.65	0-1	1
	1900	19100	20	QPSK	50	25	20.64	0-1	1
	1900	19100	20	QPSK	50	50	20.58	0-1	1
	1900	19100	20	QPSK	100	0	20.62	0-1	1
	1900	19100	20	16QAM	1	0	21.00	0-1	1
	1900	19100	20	16QAM	1	50	20.87	0-1	1
	1900	19100	20	16QAM	1	99	20.85	0-1	1
	1900	19100	20	16QAM	50	0	19.97	0-2	2
	1900	19100	20	16QAM	50	25	19.68	0-2	2
	1900	19100	20	16QAM	50	50	19.75	0-2	2
	1900	19100	20	16QAM	100	0	19.63	0-2	2

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 35 of 66

Table 9-14
LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1857.5	18675	15	QPSK	1	0	21.66	0	0
	1857.5	18675	15	QPSK	1	36	21.81	0	0
	1857.5	18675	15	QPSK	1	74	21.70	0	0
	1857.5	18675	15	QPSK	36	0	20.76	0-1	1
	1857.5	18675	15	QPSK	36	18	20.75	0-1	1
	1857.5	18675	15	QPSK	36	37	20.70	0-1	1
	1857.5	18675	15	QPSK	75	0	20.68	0-1	1
	1857.5	18675	15	16QAM	1	0	20.78	0-1	1
	1857.5	18675	15	16QAM	1	36	20.86	0-1	1
	1857.5	18675	15	16QAM	1	74	20.72	0-1	1
	1857.5	18675	15	16QAM	36	0	19.82	0-2	2
	1857.5	18675	15	16QAM	36	18	19.82	0-2	2
Mid	1857.5	18675	15	16QAM	36	37	19.77	0-2	2
	1857.5	18675	15	16QAM	75	0	19.80	0-2	2
	1880.0	18900	15	QPSK	1	0	21.64	0	0
	1880.0	18900	15	QPSK	1	36	21.73	0	0
	1880.0	18900	15	QPSK	1	74	21.83	0	0
	1880.0	18900	15	QPSK	36	0	20.85	0-1	1
	1880.0	18900	15	QPSK	36	18	20.82	0-1	1
	1880.0	18900	15	QPSK	36	37	20.78	0-1	1
	1880.0	18900	15	QPSK	75	0	20.85	0-1	1
	1880.0	18900	15	16QAM	1	0	20.86	0-1	1
	1880.0	18900	15	16QAM	1	36	20.86	0-1	1
	1880.0	18900	15	16QAM	1	74	21.03	0-1	1
High	1880.0	18900	15	16QAM	36	0	19.85	0-2	2
	1880.0	18900	15	16QAM	36	18	19.83	0-2	2
	1880.0	18900	15	16QAM	36	37	19.90	0-2	2
	1880.0	18900	15	16QAM	75	0	19.75	0-2	2
	1902.5	19125	15	QPSK	1	0	21.94	0	0
	1902.5	19125	15	QPSK	1	36	22.04	0	0
	1902.5	19125	15	QPSK	1	74	22.09	0	0
	1902.5	19125	15	QPSK	36	0	20.87	0-1	1
	1902.5	19125	15	QPSK	36	18	20.97	0-1	1
	1902.5	19125	15	QPSK	36	37	21.01	0-1	1
	1902.5	19125	15	QPSK	75	0	20.78	0-1	1
	1902.5	19125	15	16QAM	1	0	20.83	0-1	1
	1902.5	19125	15	16QAM	1	36	20.95	0-1	1
	1902.5	19125	15	16QAM	1	74	20.99	0-1	1
	1902.5	19125	15	16QAM	36	0	19.96	0-2	2
	1902.5	19125	15	16QAM	36	18	20.05	0-2	2
	1902.5	19125	15	16QAM	36	37	20.08	0-2	2
	1902.5	19125	15	16QAM	75	0	19.95	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 36 of 66	

Table 9-15
LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1855	18650	10	QPSK	1	0	21.72	0	0
	1855	18650	10	QPSK	1	25	21.78	0	0
	1855	18650	10	QPSK	1	49	21.73	0	0
	1855	18650	10	QPSK	25	0	20.85	0-1	1
	1855	18650	10	QPSK	25	12	20.77	0-1	1
	1855	18650	10	QPSK	25	25	20.83	0-1	1
	1855	18650	10	QPSK	50	0	20.63	0-1	1
	1855	18650	10	16QAM	1	0	20.76	0-1	1
	1855	18650	10	16QAM	1	25	20.85	0-1	1
	1855	18650	10	16QAM	1	49	20.76	0-1	1
	1855	18650	10	16QAM	25	0	19.91	0-2	2
	1855	18650	10	16QAM	25	12	19.86	0-2	2
	1855	18650	10	16QAM	25	25	19.93	0-2	2
	1855	18650	10	16QAM	50	0	19.73	0-2	2
Mid	1880.0	18900	10	QPSK	1	0	21.72	0	0
	1880.0	18900	10	QPSK	1	25	21.65	0	0
	1880.0	18900	10	QPSK	1	49	21.85	0	0
	1880.0	18900	10	QPSK	25	0	20.83	0-1	1
	1880.0	18900	10	QPSK	25	12	20.76	0-1	1
	1880.0	18900	10	QPSK	25	25	20.83	0-1	1
	1880.0	18900	10	QPSK	50	0	20.69	0-1	1
	1880.0	18900	10	16QAM	1	0	20.84	0-1	1
	1880.0	18900	10	16QAM	1	25	20.91	0-1	1
	1880.0	18900	10	16QAM	1	49	20.96	0-1	1
	1880.0	18900	10	16QAM	25	0	19.92	0-2	2
	1880.0	18900	10	16QAM	25	12	19.91	0-2	2
	1880.0	18900	10	16QAM	25	25	19.86	0-2	2
	1880.0	18900	10	16QAM	50	0	19.82	0-2	2
High	1905	19150	10	QPSK	1	0	21.90	0	0
	1905	19150	10	QPSK	1	25	21.89	0	0
	1905	19150	10	QPSK	1	49	21.97	0	0
	1905	19150	10	QPSK	25	0	20.92	0-1	1
	1905	19150	10	QPSK	25	12	20.93	0-1	1
	1905	19150	10	QPSK	25	25	20.98	0-1	1
	1905	19150	10	QPSK	50	0	20.91	0-1	1
	1905	19150	10	16QAM	1	0	20.88	0-1	1
	1905	19150	10	16QAM	1	25	20.83	0-1	1
	1905	19150	10	16QAM	1	49	20.88	0-1	1
	1905	19150	10	16QAM	25	0	20.10	0-2	2
	1905	19150	10	16QAM	25	12	20.13	0-2	2
	1905	19150	10	16QAM	25	25	20.17	0-2	2
	1905	19150	10	16QAM	50	0	20.08	0-2	2

FCC ID: A3LSMA500M	 	SAR EVALUATION REPORT	Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 37 of 66

Table 9-16
LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1852.5	18625	5	QPSK	1	0	21.77	0	0
	1852.5	18625	5	QPSK	1	12	21.79	0	0
	1852.5	18625	5	QPSK	1	24	21.86	0	0
	1852.5	18625	5	QPSK	12	0	20.78	0-1	1
	1852.5	18625	5	QPSK	12	6	20.80	0-1	1
	1852.5	18625	5	QPSK	12	13	20.81	0-1	1
	1852.5	18625	5	QPSK	25	0	20.76	0-1	1
	1852.5	18625	5	16-QAM	1	0	20.85	0-1	1
	1852.5	18625	5	16-QAM	1	12	20.93	0-1	1
	1852.5	18625	5	16-QAM	1	24	21.03	0-1	1
	1852.5	18625	5	16-QAM	12	0	19.93	0-2	2
	1852.5	18625	5	16-QAM	12	6	19.86	0-2	2
	1852.5	18625	5	16-QAM	12	13	19.91	0-2	2
	1852.5	18625	5	16-QAM	25	0	19.86	0-2	2
Mid	1880.0	18900	5	QPSK	1	0	21.67	0	0
	1880.0	18900	5	QPSK	1	12	21.68	0	0
	1880.0	18900	5	QPSK	1	24	21.72	0	0
	1880.0	18900	5	QPSK	12	0	20.84	0-1	1
	1880.0	18900	5	QPSK	12	6	20.85	0-1	1
	1880.0	18900	5	QPSK	12	13	20.81	0-1	1
	1880.0	18900	5	QPSK	25	0	20.81	0-1	1
	1880.0	18900	5	16-QAM	1	0	20.60	0-1	1
	1880.0	18900	5	16-QAM	1	12	20.72	0-1	1
	1880.0	18900	5	16-QAM	1	24	20.79	0-1	1
	1880.0	18900	5	16-QAM	12	0	19.89	0-2	2
	1880.0	18900	5	16-QAM	12	6	19.87	0-2	2
	1880.0	18900	5	16-QAM	12	13	19.92	0-2	2
	1880.0	18900	5	16-QAM	25	0	19.90	0-2	2
High	1907.5	19175	5	QPSK	1	0	22.07	0	0
	1907.5	19175	5	QPSK	1	12	22.05	0	0
	1907.5	19175	5	QPSK	1	24	22.11	0	0
	1907.5	19175	5	QPSK	12	0	21.09	0-1	1
	1907.5	19175	5	QPSK	12	6	21.02	0-1	1
	1907.5	19175	5	QPSK	12	13	21.07	0-1	1
	1907.5	19175	5	QPSK	25	0	21.03	0-1	1
	1907.5	19175	5	16-QAM	1	0	20.98	0-1	1
	1907.5	19175	5	16-QAM	1	12	20.97	0-1	1
	1907.5	19175	5	16-QAM	1	24	21.06	0-1	1
	1907.5	19175	5	16-QAM	12	0	20.20	0-2	2
	1907.5	19175	5	16-QAM	12	6	20.14	0-2	2
	1907.5	19175	5	16-QAM	12	13	20.17	0-2	2
	1907.5	19175	5	16-QAM	25	0	20.12	0-2	2

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 38 of 66	

Table 9-17
LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1851.5	18615	3	QPSK	1	0	21.75	0	0
	1851.5	18615	3	QPSK	1	7	21.75	0	0
	1851.5	18615	3	QPSK	1	14	21.77	0	0
	1851.5	18615	3	QPSK	8	0	20.81	0-1	1
	1851.5	18615	3	QPSK	8	4	20.79	0-1	1
	1851.5	18615	3	QPSK	8	7	20.80	0-1	1
	1851.5	18615	3	QPSK	15	0	20.85	0-1	1
	1851.5	18615	3	16-QAM	1	0	20.82	0-1	1
	1851.5	18615	3	16-QAM	1	7	20.74	0-1	1
	1851.5	18615	3	16-QAM	1	14	20.76	0-1	1
	1851.5	18615	3	16-QAM	8	0	19.82	0-2	2
	1851.5	18615	3	16-QAM	8	4	19.84	0-2	2
	1851.5	18615	3	16-QAM	8	7	19.80	0-2	2
	1851.5	18615	3	16-QAM	15	0	19.86	0-2	2
Mid	1880.0	18900	3	QPSK	1	0	21.77	0	0
	1880.0	18900	3	QPSK	1	7	21.71	0	0
	1880.0	18900	3	QPSK	1	14	21.75	0	0
	1880.0	18900	3	QPSK	8	0	20.82	0-1	1
	1880.0	18900	3	QPSK	8	4	20.79	0-1	1
	1880.0	18900	3	QPSK	8	7	20.81	0-1	1
	1880.0	18900	3	QPSK	15	0	20.81	0-1	1
	1880.0	18900	3	16-QAM	1	0	20.94	0-1	1
	1880.0	18900	3	16-QAM	1	7	20.86	0-1	1
	1880.0	18900	3	16-QAM	1	14	20.91	0-1	1
	1880.0	18900	3	16-QAM	8	0	19.94	0-2	2
	1880.0	18900	3	16-QAM	8	4	19.98	0-2	2
	1880.0	18900	3	16-QAM	8	7	20.04	0-2	2
	1880.0	18900	3	16-QAM	15	0	19.90	0-2	2
High	1908.5	19185	3	QPSK	1	0	21.88	0	0
	1908.5	19185	3	QPSK	1	7	21.96	0	0
	1908.5	19185	3	QPSK	1	14	22.02	0	0
	1908.5	19185	3	QPSK	8	0	21.09	0-1	1
	1908.5	19185	3	QPSK	8	4	21.10	0-1	1
	1908.5	19185	3	QPSK	8	7	21.15	0-1	1
	1908.5	19185	3	QPSK	15	0	21.12	0-1	1
	1908.5	19185	3	16-QAM	1	0	20.83	0-1	1
	1908.5	19185	3	16-QAM	1	7	20.85	0-1	1
	1908.5	19185	3	16-QAM	1	14	20.91	0-1	1
	1908.5	19185	3	16-QAM	8	0	20.23	0-2	2
	1908.5	19185	3	16-QAM	8	4	20.22	0-2	2
	1908.5	19185	3	16-QAM	8	7	20.26	0-2	2
	1908.5	19185	3	16-QAM	15	0	20.19	0-2	2

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 39 of 66

Table 9-18
LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
Low	1850.7	18607	1.4	QPSK	1	0	21.68	0	0
	1850.7	18607	1.4	QPSK	1	2	21.72	0	0
	1850.7	18607	1.4	QPSK	1	5	21.73	0	0
	1850.7	18607	1.4	QPSK	3	0	21.70	0	0
	1850.7	18607	1.4	QPSK	3	2	21.79	0	0
	1850.7	18607	1.4	QPSK	3	3	21.78	0	0
	1850.7	18607	1.4	QPSK	6	0	20.85	0-1	1
	1850.7	18607	1.4	16-QAM	1	0	20.73	0-1	1
	1850.7	18607	1.4	16-QAM	1	2	20.69	0-1	1
	1850.7	18607	1.4	16-QAM	1	5	20.77	0-1	1
	1850.7	18607	1.4	16-QAM	3	0	20.71	0-1	1
	1850.7	18607	1.4	16-QAM	3	2	20.72	0-1	1
	1850.7	18607	1.4	16-QAM	3	3	20.70	0-1	1
	1850.7	18607	1.4	16-QAM	6	0	19.72	0-2	2
Mid	1880.0	18900	1.4	QPSK	1	0	21.85	0	0
	1880.0	18900	1.4	QPSK	1	2	21.78	0	0
	1880.0	18900	1.4	QPSK	1	5	21.84	0	0
	1880.0	18900	1.4	QPSK	3	0	21.77	0	0
	1880.0	18900	1.4	QPSK	3	2	21.75	0	0
	1880.0	18900	1.4	QPSK	3	3	21.77	0	0
	1880.0	18900	1.4	QPSK	6	0	20.86	0-1	1
	1880.0	18900	1.4	16-QAM	1	0	20.79	0-1	1
	1880.0	18900	1.4	16-QAM	1	2	20.77	0-1	1
	1880.0	18900	1.4	16-QAM	1	5	20.78	0-1	1
	1880.0	18900	1.4	16-QAM	3	0	20.91	0-1	1
	1880.0	18900	1.4	16-QAM	3	2	20.95	0-1	1
	1880.0	18900	1.4	16-QAM	3	3	21.00	0-1	1
	1880.0	18900	1.4	16-QAM	6	0	19.88	0-2	2
High	1909.3	19193	1.4	QPSK	1	0	21.97	0	0
	1909.3	19193	1.4	QPSK	1	2	22.01	0	0
	1909.3	19193	1.4	QPSK	1	5	22.05	0	0
	1909.3	19193	1.4	QPSK	3	0	22.00	0	0
	1909.3	19193	1.4	QPSK	3	2	22.00	0	0
	1909.3	19193	1.4	QPSK	3	3	22.05	0	0
	1909.3	19193	1.4	QPSK	6	0	21.14	0-1	1
	1909.3	19193	1.4	16-QAM	1	0	20.91	0-1	1
	1909.3	19193	1.4	16-QAM	1	2	20.90	0-1	1
	1909.3	19193	1.4	16-QAM	1	5	20.92	0-1	1
	1909.3	19193	1.4	16-QAM	3	0	21.05	0-1	1
	1909.3	19193	1.4	16-QAM	3	2	21.02	0-1	1
	1909.3	19193	1.4	16-QAM	3	3	21.07	0-1	1
	1909.3	19193	1.4	16-QAM	6	0	20.21	0-2	2

FCC ID: A3LSMA500M	 	SAR EVALUATION REPORT	Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 40 of 66

9.4 WLAN Conducted Powers

Table 9-19
IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1*	16.68	16.48	16.90	16.78
802.11b	2437	6*	16.90	16.77	17.08	17.02
802.11b	2462	11*	17.45	17.23	17.46	17.41

Table 9-20
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	12.75	12.45	12.41	12.81	12.62	12.50	12.48	12.82
802.11g	2437	6	12.78	12.52	12.42	12.83	12.64	12.59	12.55	12.80
802.11g	2462	11	13.17	12.88	12.79	13.23	13.00	12.93	12.86	13.23

Table 9-21
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	802.11n (2.4GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	2412	1	11.67	11.99	11.62	11.78	11.49	11.49	11.64	11.58
802.11n	2437	6	11.84	12.12	11.79	11.94	11.65	11.64	11.84	11.77
802.11n	2462	11	12.38	12.42	12.35	12.48	12.18	12.12	12.38	12.33

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 41 of 66

Table 9-22
IEEE 802.11a Average RF Power

Mode	Freq [MHz]	Channel	802.11a Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11a	5180	36*	10.82	10.63	10.85	10.82	10.79	10.67	10.78	10.85
802.11a	5200	40	10.64	10.51	10.63	10.61	10.60	10.54	10.63	10.68
802.11a	5220	44	10.63	10.48	10.72	10.62	10.66	10.45	10.58	10.70
802.11a	5240	48*	10.54	10.36	10.60	10.52	10.55	10.31	10.44	10.55
802.11a	5260	52*	10.58	10.43	10.37	10.34	10.41	10.32	10.35	10.38
802.11a	5280	56	10.37	10.26	10.35	10.39	10.34	10.31	10.38	10.40
802.11a	5300	60	10.47	10.35	10.28	10.30	10.31	10.37	10.31	10.36
802.11a	5320	64*	10.60	10.42	10.40	10.34	10.37	10.28	10.34	10.44
802.11a	5500	100	10.72	10.71	10.76	10.34	10.53	10.57	10.55	10.51
802.11a	5520	104*	10.78	10.69	10.84	10.40	10.64	10.66	10.55	10.58
802.11a	5540	108	10.91	10.92	10.94	10.44	10.73	10.71	10.72	10.65
802.11a	5560	112	11.30	11.29	11.33	10.92	11.08	11.18	11.16	11.04
802.11a	5580	116*	10.93	10.88	10.93	10.55	10.69	10.75	10.67	10.74
802.11a	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5660	132	11.33	11.32	11.40	11.01	11.17	11.19	11.22	11.19
802.11a	5680	136*	10.45	10.42	10.57	10.48	10.39	10.37	10.28	10.28
802.11a	5700	140	10.53	10.48	10.63	10.19	10.31	10.45	10.32	10.35
802.11a	5745	149*	10.51	10.49	10.45	10.62	10.49	10.48	10.52	10.59
802.11a	5765	153	10.55	10.51	10.52	10.63	10.52	10.57	10.59	10.68
802.11a	5785	157*	11.14	11.11	11.03	11.28	11.09	11.20	11.17	11.27
802.11a	5805	161	11.10	11.00	10.97	11.23	11.08	11.18	11.15	11.10
802.11a	5825	165*	10.68	10.70	10.68	10.74	10.63	10.60	10.70	10.76

Per FCC KDB Publication 443999 and RSS-210 A9.2(3), transmission on channels which overlap the 5600-5650 MHz is prohibited as a client. This device does not transmit any beacons or initiate any transmissions in 5.3 and 5.5 GHz Band.

(*) – indicates default channels per KDB Publication 248227 D01v01r02. When the adjacent channels are higher in power then the default channels, these “required channels” are considered for SAR testing instead of the default channels.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 42 of 66	

Table 9-23
IEEE 802.11n Average RF Power – 20 MHz Bandwidth

Mode	Freq [MHz]	Channel	20MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13	19.5	26	39	52	58.5	65
802.11n	5180	36	10.37	10.29	10.47	10.33	10.49	10.48	10.31	10.43
802.11n	5200	40	9.61	9.59	9.70	9.54	9.78	9.70	9.55	9.72
802.11n	5220	44	9.42	9.35	9.55	9.40	9.53	9.58	9.44	9.49
802.11n	5240	48	10.35	10.21	10.46	10.34	10.43	10.46	10.29	10.37
802.11n	5260	52	10.28	10.29	10.27	10.28	10.24	10.24	10.17	10.14
802.11n	5280	56	10.24	10.23	10.30	10.25	10.21	10.25	10.20	10.18
802.11n	5300	60	10.33	10.37	10.28	10.34	10.25	10.34	10.27	10.15
802.11n	5320	64	10.47	10.45	10.40	10.48	10.41	10.45	10.39	10.36
802.11n	5500	100	9.75	9.70	9.64	9.79	9.75	9.86	9.69	9.79
802.11n	5520	104	10.03	10.02	9.96	10.10	10.01	10.19	9.97	10.09
802.11n	5540	108	10.25	10.19	10.08	10.25	10.26	10.31	10.18	10.38
802.11n	5560	112	10.47	10.39	10.27	10.30	10.46	10.40	10.42	10.35
802.11n	5580	116	10.00	9.96	9.90	10.04	10.02	10.06	9.96	10.13
802.11n	5600	120	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5620	124	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5640	128	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5660	132	9.81	9.74	9.70	9.89	9.76	9.88	9.75	9.82
802.11n	5680	136	9.85	9.77	9.82	9.91	9.82	9.92	9.72	9.88
802.11n	5700	140	9.92	9.86	9.78	10.04	9.87	10.04	9.92	10.04
802.11n	5745	149	10.23	10.42	10.41	10.34	10.39	10.44	10.30	10.41
802.11n	5765	153	10.36	10.40	10.49	10.43	10.42	10.32	10.36	10.37
802.11n	5785	157	10.44	10.49	10.47	10.43	10.49	10.46	10.42	10.46
802.11n	5805	161	10.35	10.42	10.46	10.45	10.41	10.45	10.49	10.48
802.11n	5825	165	10.39	10.45	10.43	10.40	10.48	10.47	10.41	10.40

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 43 of 66

Table 9-24
IEEE 802.11n Average RF Power – 40 MHz Bandwidth

Mode	Freq [MHz]	Channel	40MHz BW 802.11n (5GHz) Conducted Power [dBm]							
			Data Rate [Mbps]							
			13.5	27	40.5	54	81	108	121.5	135
802.11n	5190	38	10.33	10.34	10.48	10.45	10.43	10.44	10.44	10.40
802.11n	5230	46	10.46	10.49	10.45	10.46	10.41	10.49	10.39	10.47
802.11n	5270	54	9.46	9.55	9.56	9.57	9.44	9.60	9.49	9.56
802.11n	5310	62	9.82	9.95	9.91	9.87	9.85	9.93	9.84	9.96
802.11n	5510	102	9.86	9.84	9.85	9.86	9.85	9.60	9.79	9.80
802.11n	5550	110	10.37	10.38	10.32	10.46	10.38	10.11	10.32	10.38
802.11n	5590	118	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5630	126	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5670	134	9.98	9.93	9.93	9.96	9.96	9.67	9.91	9.95
802.11n	5755	151	10.27	10.28	10.34	10.33	10.33	10.38	10.40	10.48
802.11n	5795	159	10.34	10.32	10.35	10.40	10.36	10.44	10.46	10.44

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For 2.4 GHz operations, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- For 5 GHz operations, highest average RF output power channel for the lowest data rate for IEEE 802.11a were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.




Figure 9-3
Power Measurement Setup

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 44 of 66

10 SYSTEM VERIFICATION

10.1 Tissue Verification

Table 10-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
9/18/2014	750H	22.6	710	0.873	40.911	0.890	42.149	-1.91%	-2.94%
			725	0.886	40.700	0.891	42.071	-0.56%	-3.26%
			740	0.899	40.444	0.893	41.994	0.67%	-3.69%
			755	0.910	40.227	0.894	41.916	1.79%	-4.03%
9/15/2014	835H	22.5	820	0.911	41.766	0.899	41.578	1.33%	0.45%
			835	0.925	41.591	0.900	41.500	2.78%	0.22%
			850	0.939	41.408	0.916	41.500	2.51%	-0.22%
9/17/2014	1750H	22.8	1710	1.318	39.693	1.348	40.142	-2.23%	-1.12%
			1750	1.357	39.498	1.371	40.079	-1.02%	-1.45%
			1790	1.397	39.314	1.394	40.016	0.22%	-1.75%
9/15/2014	1900H	22.8	1850	1.362	40.187	1.400	40.000	-2.71%	0.47%
			1880	1.394	40.036	1.400	40.000	-0.43%	0.09%
			1910	1.427	39.931	1.400	40.000	1.93%	-0.17%
9/22/2014	1900H	22.3	1850	1.394	39.468	1.400	40.000	-0.43%	-1.33%
			1880	1.423	39.372	1.400	40.000	1.64%	-1.57%
			1910	1.454	39.210	1.400	40.000	3.86%	-1.98%
9/15/2014	2450H	23.4	2401	1.756	39.846	1.756	39.287	0.00%	1.42%
			2450	1.815	39.696	1.800	39.200	0.83%	1.27%
			2499	1.866	39.504	1.853	39.138	0.70%	0.94%
			5180	4.528	36.119	4.635	36.009	-2.31%	0.31%
9/18/2014	5200H-5800H	23.1	5200	4.541	36.087	4.655	35.986	-2.45%	0.28%
			5300	4.635	35.984	4.758	35.871	-2.59%	0.32%
			5320	4.656	35.914	4.778	35.849	-2.55%	0.18%
			5600	4.955	35.553	5.065	35.529	-2.17%	0.07%
			5660	5.004	35.530	5.127	35.460	-2.40%	0.20%
			5785	5.126	35.418	5.255	35.317	-2.45%	0.29%
			5800	5.130	35.336	5.270	35.300	-2.66%	0.10%
09/17/2014	750B	22.4	710	0.936	54.206	0.960	55.687	-2.50%	-2.66%
			725	0.949	54.067	0.961	55.629	-1.25%	-2.81%
			740	0.962	53.869	0.963	55.570	-0.10%	-3.06%
			755	0.976	53.716	0.964	55.512	1.24%	-3.24%
09/15/2014	835B	22.5	820	0.992	53.401	0.969	55.258	2.37%	-3.36%
			835	1.007	53.246	0.970	55.200	3.81%	-3.54%
			850	1.022	53.060	0.988	55.154	3.44%	-3.80%
09/15/2014	1750B	22.2	1710	1.436	52.451	1.463	53.537	-1.85%	-2.03%
			1750	1.479	52.229	1.488	53.432	-0.60%	-2.25%
			1790	1.526	52.112	1.514	53.326	0.79%	-2.28%
09/15/2014	1900B	22.1	1850	1.488	51.542	1.520	53.300	-2.11%	-3.30%
			1880	1.523	51.404	1.520	53.300	0.20%	-3.56%
			1910	1.561	51.316	1.520	53.300	2.70%	-3.72%
09/23/2014	1900B	23.7	1850	1.468	50.986	1.520	53.300	-3.42%	-4.34%
			1880	1.502	50.892	1.520	53.300	-1.18%	-4.52%
			1910	1.539	50.799	1.520	53.300	1.25%	-4.69%
09/15/2014	2450B	22.4	2401	1.974	51.281	1.903	52.765	3.73%	-2.81%
			2450	2.046	51.116	1.950	52.700	4.92%	-3.01%
			2499	2.111	50.911	2.019	52.638	4.56%	-3.28%
			5180	5.321	47.728	5.276	49.041	0.85%	-2.68%
09/15/2014	5200B-5800B	22.5	5200	5.345	47.648	5.299	49.014	0.87%	-2.79%
			5300	5.491	47.379	5.416	48.879	1.38%	-3.07%
			5320	5.528	47.303	5.439	48.851	1.64%	-3.17%
			5600	5.957	46.603	5.766	48.471	3.31%	-3.85%
			5660	6.033	46.479	5.837	48.390	3.36%	-3.95%
			5785	6.233	46.199	5.982	48.220	4.20%	-4.19%
			5800	6.242	46.136	6.000	48.200	4.03%	-4.28%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 45 of 66	

10.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

Table 10-2
System Verification Results

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Dipole SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
D	750	HEAD	09/18/2014	24.3	23.6	0.100	1003	3263	0.860	8.370	8.600	2.75%
D	835	HEAD	09/15/2014	23.4	22.5	0.100	4d119	3263	0.961	9.220	9.610	4.23%
G	1750	HEAD	09/17/2014	24.0	23.0	0.100	1008	3258	3.430	36.900	34.300	-7.05%
K	1900	HEAD	09/15/2014	23.4	22.8	0.100	5d141	3287	4.110	40.100	41.100	2.49%
K	1900	HEAD	09/22/2014	23.0	22.5	0.100	5d141	3287	4.260	40.100	42.600	6.23%
G	2450	HEAD	09/15/2014	24.4	23.6	0.100	797	3258	5.360	51.800	53.600	3.47%
E	5200	HEAD	09/18/2014	24.2	23.1	0.100	1057	3914	7.270	78.000	72.700	-6.79%
E	5300	HEAD	09/18/2014	24.2	23.1	0.100	1057	3914	7.860	83.000	78.600	-5.30%
E	5600	HEAD	09/18/2014	24.2	23.2	0.100	1057	3914	7.770	83.500	77.700	-6.95%
E	5800	HEAD	09/18/2014	24.2	23.2	0.100	1057	3914	7.300	79.300	73.000	-7.94%
I	750	BODY	09/17/2014	23.9	22.4	0.100	1003	3209	0.920	8.770	9.200	4.90%
D	835	BODY	09/15/2014	22.4	22.5	0.100	4d119	3263	0.960	9.340	9.600	2.78%
H	1750	BODY	09/15/2014	22.1	22.2	0.100	1008	3319	3.810	37.600	38.100	1.33%
K	1900	BODY	09/15/2014	23.4	22.2	0.100	5d141	3287	4.320	40.600	43.200	6.40%
K	1900	BODY	09/23/2014	23.8	23.7	0.100	5d141	3287	3.960	40.600	39.600	-2.46%
G	2450	BODY	09/15/2014	20.8	22.4	0.100	797	3258	5.290	49.400	52.900	7.09%
I	5200	BODY	09/15/2014	23.2	22.5	0.100	1057	3589	7.790	75.300	77.900	3.45%
I	5300	BODY	09/15/2014	23.2	22.5	0.100	1057	3589	8.030	77.400	80.300	3.75%
I	5600	BODY	09/15/2014	23.2	22.5	0.100	1057	3589	7.570	80.200	75.700	-5.61%
I	5800	BODY	09/15/2014	23.2	22.5	0.100	1057	3589	7.440	74.300	74.400	0.13%




Figure 10-1
System Verification Setup Diagram



Figure 10-2
System Verification Setup Photo

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 46 of 66

11 SAR DATA SUMMARY

11.1 Standalone Head SAR Data

Table 11-1
GSM 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.5	32.29	0.07	Right	Cheek	PCT5	1:8.3	0.230	1.050	0.242	A1
836.60	190	GSM 850	GSM	32.5	32.29	0.02	Right	Tilt	PCT5	1:8.3	0.134	1.050	0.141	
836.60	190	GSM 850	GSM	32.5	32.29	0.07	Left	Cheek	PCT5	1:8.3	0.181	1.050	0.190	
836.60	190	GSM 850	GSM	32.5	32.29	0.03	Left	Tilt	PCT5	1:8.3	0.131	1.050	0.138	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-2
GSM 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	661	GSM 1900	GSM	29.5	29.06	0.17	Right	Cheek	PCT5	1:8.3	0.133	1.107	0.147	
1880.00	661	GSM 1900	GSM	29.5	29.06	0.19	Right	Tilt	PCT5	1:8.3	0.077	1.107	0.085	
1880.00	661	GSM 1900	GSM	29.5	29.06	-0.15	Left	Cheek	PCT5	1:8.3	0.179	1.107	0.198	A2
1880.00	661	GSM 1900	GSM	29.5	29.06	-0.12	Left	Tilt	PCT5	1:8.3	0.027	1.107	0.030	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

Table 11-3
UMTS 850 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
836.60	4183	UMTS 850	RMC	23.0	22.94	0.07	Right	Cheek	PCT5	1:1	0.219	1.014	0.222	A3
836.60	4183	UMTS 850	RMC	23.0	22.94	0.03	Right	Tilt	PCT5	1:1	0.133	1.014	0.135	
836.60	4183	UMTS 850	RMC	23.0	22.94	0.07	Left	Cheek	PCT5	1:1	0.161	1.014	0.163	
836.60	4183	UMTS 850	RMC	23.0	22.94	-0.05	Left	Tilt	PCT5	1:1	0.119	1.014	0.121	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram						

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 47 of 66

Table 11-4
UMTS 1900 Head SAR

MEASUREMENT RESULTS														
FREQUENCY		Mode/Band	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.										(W/kg)		(W/kg)	
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.00	Right	Cheek	PCT5	1:1	0.215	1.084	0.233	
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.08	Right	Tilt	PCT5	1:1	0.119	1.084	0.129	
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.10	Left	Cheek	PCT5	1:1	0.259	1.084	0.281	A4
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.11	Left	Tilt	PCT5	1:1	0.042	1.084	0.046	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-5
LTE Band 17 Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	0.12	0	Right	Cheek	QPSK	1	0	PCT4	1:1	0.053	1.030	0.055	A5
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	0.18	1	Right	Cheek	QPSK	25	0	PCT4	1:1	0.042	1.084	0.046	
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	0.19	0	Right	Tilt	QPSK	1	0	PCT4	1:1	0.039	1.030	0.040	
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	0.16	1	Right	Tilt	QPSK	25	0	PCT4	1:1	0.032	1.084	0.035	
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	0.17	0	Left	Cheek	QPSK	1	0	PCT4	1:1	0.053	1.030	0.055	
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	0.12	1	Left	Cheek	QPSK	25	0	PCT4	1:1	0.040	1.084	0.043	
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	0.21	0	Left	Tilt	QPSK	1	0	PCT4	1:1	0.034	1.030	0.035	
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	0.20	1	Left	Tilt	QPSK	25	0	PCT4	1:1	0.026	1.084	0.028	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-6
LTE Band 5 (Cell) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.00	0	Right	Cheek	QPSK	1	0	PCT4	1:1	0.199	1.021	0.203	A6
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	0.05	1	Right	Cheek	QPSK	25	0	PCT4	1:1	0.153	1.064	0.163	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.06	0	Right	Tilt	QPSK	1	0	PCT4	1:1	0.137	1.021	0.140	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	0.11	1	Right	Tilt	QPSK	25	0	PCT4	1:1	0.104	1.064	0.111	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.02	0	Left	Cheek	QPSK	1	0	PCT4	1:1	0.171	1.021	0.175	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	0.03	1	Left	Cheek	QPSK	25	0	PCT4	1:1	0.130	1.064	0.138	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.00	0	Left	Tilt	QPSK	1	0	PCT4	1:1	0.121	1.021	0.124	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	0.04	1	Left	Tilt	QPSK	25	0	PCT4	1:1	0.093	1.064	0.099	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 48 of 66

Table 11-7
LTE Band 4 (AWS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)	(W/kg)			
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	0.11	0	Right	Cheek	QPSK	1	0	PCT4	1:1	0.260	1.000	0.260	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	-0.01	1	Right	Cheek	QPSK	50	0	PCT4	1:1	0.193	1.089	0.210	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	-0.01	0	Right	Tilt	QPSK	1	0	PCT4	1:1	0.063	1.000	0.063	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	0.17	1	Right	Tilt	QPSK	50	0	PCT4	1:1	0.053	1.089	0.058	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	0.00	0	Left	Cheek	QPSK	1	0	PCT4	1:1	0.299	1.000	0.299	A7
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	0.00	1	Left	Cheek	QPSK	50	0	PCT4	1:1	0.207	1.089	0.225	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	0.01	0	Left	Tilt	QPSK	1	0	PCT4	1:1	0.123	1.000	0.123	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	0.08	1	Left	Tilt	QPSK	50	0	PCT4	1:1	0.097	1.089	0.106	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-8
LTE Band 2 (PCS) Head SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Side	Test Position	Modulation	RB Size	RB Offset	Device Serial Number	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)	(W/kg)			
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	-0.02	0	Right	Cheek	QPSK	1	0	PCT4	1:1	0.174	1.205	0.210	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	0.01	1	Right	Cheek	QPSK	50	0	PCT4	1:1	0.133	1.216	0.162	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	-0.16	0	Right	Tilt	QPSK	1	0	PCT4	1:1	0.072	1.205	0.087	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	0.02	1	Right	Tilt	QPSK	50	0	PCT4	1:1	0.059	1.216	0.072	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	0.04	0	Left	Cheek	QPSK	1	0	PCT4	1:1	0.214	1.205	0.258	A8
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	-0.02	1	Left	Cheek	QPSK	50	0	PCT4	1:1	0.167	1.216	0.203	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	-0.16	0	Left	Tilt	QPSK	1	0	PCT4	1:1	0.054	1.205	0.065	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	0.00	1	Left	Tilt	QPSK	50	0	PCT4	1:1	0.041	1.216	0.050	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population										Head 1.6 W/kg (mW/g) averaged over 1 gram									

Table 11-9
DTS Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.12	Right	Cheek	PCT6	1	1:1	0.053	1.012	0.054	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.12	Right	Tilt	PCT6	1	1:1	0.044	1.012	0.045	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.19	Left	Cheek	PCT6	1	1:1	0.099	1.012	0.100	A9
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.12	Left	Tilt	PCT6	1	1:1	0.077	1.012	0.078	
5785	157	IEEE 802.11a	OFDM	11.5	11.14	-0.20	Right	Cheek	PCT4	6	1:1	0.018	1.086	0.020	
5785	157	IEEE 802.11a	OFDM	11.5	11.14	0.00	Right	Tilt	PCT4	6	1:1	0.011	1.086	0.012	
5785	157	IEEE 802.11a	OFDM	11.5	11.14	-0.05	Left	Cheek	PCT4	6	1:1	0.050	1.086	0.054	A10
5785	157	IEEE 802.11a	OFDM	11.5	11.14	0.21	Left	Tilt	PCT4	6	1:1	0.033	1.086	0.036	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 49 of 66

Table 11-10
NII Head SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Device Serial Number	Data Rate (Mbps)	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
5180	36	IEEE 802.11a	OFDM	11.5	10.82	0.19	Right	Cheek	PCT4	6	1:1	0.024	1.169	0.028	
5180	36	IEEE 802.11a	OFDM	11.5	10.82	0.13	Right	Tilt	PCT4	6	1:1	0.013	1.169	0.015	
5180	36	IEEE 802.11a	OFDM	11.5	10.82	0.18	Left	Cheek	PCT4	6	1:1	0.058	1.169	0.068	
5180	36	IEEE 802.11a	OFDM	11.5	10.82	0.06	Left	Tilt	PCT4	6	1:1	0.047	1.169	0.055	
5320	64	IEEE 802.11a	OFDM	11.5	10.60	0.12	Right	Cheek	PCT4	6	1:1	0.049	1.230	0.060	
5320	64	IEEE 802.11a	OFDM	11.5	10.60	0.20	Right	Tilt	PCT4	6	1:1	0.035	1.230	0.043	
5320	64	IEEE 802.11a	OFDM	11.5	10.60	-0.04	Left	Cheek	PCT4	6	1:1	0.119	1.230	0.146	
5320	64	IEEE 802.11a	OFDM	11.5	10.60	-0.16	Left	Tilt	PCT4	6	1:1	0.037	1.230	0.046	
5660	132	IEEE 802.11a	OFDM	11.5	11.33	0.13	Right	Cheek	PCT4	6	1:1	0.057	1.040	0.059	
5660	132	IEEE 802.11a	OFDM	11.5	11.33	0.08	Right	Tilt	PCT4	6	1:1	0.041	1.040	0.043	
5660	132	IEEE 802.11a	OFDM	11.5	11.33	0.15	Left	Cheek	PCT4	6	1:1	0.154	1.040	0.160	A11
5660	132	IEEE 802.11a	OFDM	11.5	11.33	0.07	Left	Tilt	PCT4	6	1:1	0.112	1.040	0.116	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Head 1.6 W/kg (mW/g) averaged over 1 gram							

11.2 Standalone Body-Worn SAR Data

Table 11-11
GSM/UMTS Body-Worn SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of Time Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GSM	32.5	32.29	-0.01	10 mm	PCT5	1	1:8.3	back	0.398	1.050	0.418	A12
1880.00	661	GSM 1900	GSM	29.5	29.06	0.03	10 mm	PCT5	1	1:8.3	back	0.359	1.107	0.397	A14
836.60	4183	UMTS 850	RMC	23.0	22.94	-0.03	10 mm	PCT5	N/A	1:1	back	0.341	1.014	0.346	A16
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.04	10 mm	PCT5	N/A	1:1	back	0.639	1.084	0.693	A17
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram							

Table 11-12
LTE Body-Worn SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g) (W/kg)	Plot #	
MHz	Ch.														(W/kg)				
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	-0.07	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.123	1.030	0.127	A19
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	-0.14	1	PCT4	QPSK	25	0	10 mm	back	1:1	0.084	1.084	0.091	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.00	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.302	1.021	0.308	A20
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	-0.01	1	PCT4	QPSK	25	0	10 mm	back	1:1	0.238	1.064	0.253	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	-0.02	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.519	1.000	0.519	A21
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	0.03	1	PCT4	QPSK	50	0	10 mm	back	1:1	0.393	1.089	0.428	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	0.03	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.534	1.205	0.643	A23
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	-0.02	1	PCT4	QPSK	50	0	10 mm	back	1:1	0.422	1.216	0.513	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak										Body 1.6 W/kg (mW/g) averaged over 1 gram									
Uncontrolled Exposure/General Population																			

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 50 of 66

Table 11-13
DTS Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.11	10 mm	PCT6	1	back	1:1	0.027	1.012	0.027	A25
5785	157	IEEE 802.11a	OFDM	11.5	11.14	-0.06	10 mm	PCT6	6	back	1:1	0.004	1.086	0.004	A26
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Table 11-14
NII Body-Worn SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
5180	36	IEEE 802.11a	OFDM	11.5	10.82	-0.09	10 mm	PCT6	6	back	1:1	0.006	1.169	0.007	
5320	64	IEEE 802.11a	OFDM	11.5	10.60	-0.14	10 mm	PCT6	6	back	1:1	0.014	1.230	0.017	
5660	132	IEEE 802.11a	OFDM	11.5	11.33	0.06	10 mm	PCT6	6	back	1:1	0.015	1.040	0.016	A27
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 51 of 66

11.1 Standalone Wireless Router SAR Data

Table 11-15
GPRS/UMTS Hotspot SAR Data

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	# of GPRS Slots	Duty Cycle	Side	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
836.60	190	GSM 850	GPRS	32.5	32.21	0.02	10 mm	PCT5	1	1:8.3	back	0.380	1.069	0.406	A13
836.60	190	GSM 850	GPRS	32.5	32.21	0.08	10 mm	PCT5	1	1:8.3	front	0.326	1.069	0.348	
836.60	190	GSM 850	GPRS	32.5	32.21	0.02	10 mm	PCT5	1	1:8.3	bottom	0.154	1.069	0.165	
836.60	190	GSM 850	GPRS	32.5	32.21	0.03	10 mm	PCT5	1	1:8.3	left	0.273	1.069	0.292	
1880.00	661	GSM 1900	GPRS	29.5	29.07	0.02	10 mm	PCT5	1	1:8.3	back	0.342	1.104	0.378	
1880.00	661	GSM 1900	GPRS	29.5	29.07	0.03	10 mm	PCT5	1	1:8.3	front	0.336	1.104	0.371	
1880.00	661	GSM 1900	GPRS	29.5	29.07	-0.11	10 mm	PCT5	1	1:8.3	bottom	0.533	1.104	0.588	A15
1880.00	661	GSM 1900	GPRS	29.5	29.07	0.06	10 mm	PCT5	1	1:8.3	left	0.163	1.104	0.180	
836.60	4183	UMTS 850	RMC	23.0	22.94	-0.03	10 mm	PCT5	N/A	1:1	back	0.341	1.014	0.346	A16
836.60	4183	UMTS 850	RMC	23.0	22.94	0.01	10 mm	PCT5	N/A	1:1	front	0.306	1.014	0.310	
836.60	4183	UMTS 850	RMC	23.0	22.94	0.09	10 mm	PCT5	N/A	1:1	bottom	0.135	1.014	0.137	
836.60	4183	UMTS 850	RMC	23.0	22.94	0.01	10 mm	PCT5	N/A	1:1	left	0.292	1.014	0.296	
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.04	10 mm	PCT5	N/A	1:1	back	0.639	1.084	0.693	
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.12	10 mm	PCT5	N/A	1:1	front	0.670	1.084	0.726	
1852.40	9262	UMTS 1900	RMC	22.5	22.27	0.00	10 mm	PCT5	N/A	1:1	bottom	0.851	1.054	0.897	
1880.00	9400	UMTS 1900	RMC	22.5	22.15	0.00	10 mm	PCT5	N/A	1:1	bottom	0.963	1.084	1.044	
1907.60	9538	UMTS 1900	RMC	22.5	22.21	0.00	10 mm	PCT5	N/A	1:1	bottom	0.992	1.069	1.060	A18
1880.00	9400	UMTS 1900	RMC	22.5	22.15	-0.03	10 mm	PCT5	N/A	1:1	left	0.294	1.084	0.319	
1907.60	9538	UMTS 1900	RMC	22.5	22.21	-0.03	10 mm	PCT5	N/A	1:1	bottom	0.938	1.069	1.003	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

Blue highlighted entries represent variability measurement data

Table 11-16
LTE Band 17 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	-0.07	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.123	1.030	0.127	A19
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	-0.14	1	PCT4	QPSK	25	0	10 mm	back	1:1	0.084	1.084	0.091	
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	-0.01	0	PCT4	QPSK	1	0	10 mm	front	1:1	0.118	1.030	0.122	
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	-0.03	1	PCT4	QPSK	25	0	10 mm	front	1:1	0.090	1.084	0.098	
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	0.13	0	PCT4	QPSK	1	0	10 mm	bottom	1:1	0.032	1.030	0.033	
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	0.04	1	PCT4	QPSK	25	0	10 mm	bottom	1:1	0.024	1.084	0.026	
710.00	23790	Mid	LTE Band 17	10	23.5	23.37	0.07	0	PCT4	QPSK	1	0	10 mm	left	1:1	0.085	1.030	0.088	
710.00	23790	Mid	LTE Band 17	10	22.5	22.15	-0.03	1	PCT4	QPSK	25	0	10 mm	left	1:1	0.063	1.084	0.068	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram											

FCC ID: A3LSMA500M			SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 52 of 66	

Table 11-17
LTE Band 5 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.00	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.302	1.021	0.308	A20
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	-0.01	1	PCT4	QPSK	25	0	10 mm	back	1:1	0.238	1.064	0.253	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.06	0	PCT4	QPSK	1	0	10 mm	front	1:1	0.289	1.021	0.295	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	-0.03	1	PCT4	QPSK	25	0	10 mm	front	1:1	0.232	1.064	0.247	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	-0.04	0	PCT4	QPSK	1	0	10 mm	bottom	1:1	0.125	1.021	0.128	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	0.03	1	PCT4	QPSK	25	0	10 mm	bottom	1:1	0.102	1.064	0.109	
836.50	20525	Mid	LTE Band 5 (Cell)	10	23.0	22.91	0.09	0	PCT4	QPSK	1	0	10 mm	left	1:1	0.246	1.021	0.251	
836.50	20525	Mid	LTE Band 5 (Cell)	10	22.0	21.73	-0.07	1	PCT4	QPSK	25	0	10 mm	left	1:1	0.206	1.064	0.219	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Table 11-18
LTE Band 4 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	-0.02	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.519	1.000	0.519	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	0.03	1	PCT4	QPSK	50	0	10 mm	back	1:1	0.393	1.089	0.428	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	0.00	0	PCT4	QPSK	1	0	10 mm	front	1:1	0.524	1.000	0.524	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	-0.03	1	PCT4	QPSK	50	0	10 mm	front	1:1	0.398	1.089	0.433	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	-0.09	0	PCT4	QPSK	1	0	10 mm	bottom	1:1	0.709	1.000	0.709	A22
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	0.00	1	PCT4	QPSK	50	0	10 mm	bottom	1:1	0.517	1.089	0.563	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	23.0	23.00	0.01	0	PCT4	QPSK	1	0	10 mm	left	1:1	0.182	1.000	0.182	
1732.50	20175	Mid	LTE Band 4 (AWS)	20	22.0	21.63	-0.06	1	PCT4	QPSK	50	0	10 mm	left	1:1	0.137	1.089	0.149	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

Table 11-19
LTE Band 2 Hotspot SAR

MEASUREMENT RESULTS																			
FREQUENCY		Mode	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	MPR [dB]	Device Serial Number	Modulation	RB Size	RB Offset	Spacing	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #	
MHz	Ch.														(W/kg)		(W/kg)		
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	0.03	0	PCT4	QPSK	1	0	10 mm	back	1:1	0.534	1.205	0.643	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	-0.02	1	PCT4	QPSK	50	0	10 mm	back	1:1	0.422	1.216	0.513	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	-0.01	0	PCT4	QPSK	1	0	10 mm	front	1:1	0.555	1.205	0.669	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	0.03	1	PCT4	QPSK	50	0	10 mm	front	1:1	0.436	1.216	0.530	
1860.00	18700	Low	LTE Band 2 (PCS)	20	22.5	21.66	-0.06	0	PCT4	QPSK	1	99	10 mm	bottom	1:1	0.686	1.213	0.832	
1880.00	18900	Mid	LTE Band 2 (PCS)	20	22.5	21.68	0.01	0	PCT4	QPSK	1	99	10 mm	bottom	1:1	0.765	1.208	0.924	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	-0.06	0	PCT4	QPSK	1	0	10 mm	bottom	1:1	0.808	1.205	0.974	A24
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	-0.02	1	PCT4	QPSK	50	0	10 mm	bottom	1:1	0.638	1.216	0.776	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.62	0.02	1	PCT4	QPSK	100	0	10 mm	bottom	1:1	0.644	1.225	0.789	
1900.00	19100	High	LTE Band 2 (PCS)	20	22.5	21.69	0.07	0	PCT4	QPSK	1	0	10 mm	left	1:1	0.283	1.205	0.341	
1900.00	19100	High	LTE Band 2 (PCS)	20	21.5	20.65	0.03	1	PCT4	QPSK	50	0	10 mm	left	1:1	0.208	1.216	0.253	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body											
Spatial Peak								1.6 W/kg (mW/g)											
Uncontrolled Exposure/General Population								averaged over 1 gram											

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 53 of 66

Table 11-20
WLAN Hotspot SAR

MEASUREMENT RESULTS															
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle	SAR (1g)	Scaling Factor	Scaled SAR (1g)	Plot #
MHz	Ch.											(W/kg)		(W/kg)	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.11	10 mm	PCT6	1	back	1:1	0.027	1.012	0.027	A25
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.15	10 mm	PCT6	1	front	1:1	0.015	1.012	0.015	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.02	10 mm	PCT6	1	top	1:1	0.010	1.012	0.010	
2462	11	IEEE 802.11b	DSSS	17.5	17.45	0.02	10 mm	PCT6	1	right	1:1	0.003	1.012	0.003	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram								

11.2 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003, and FCC KDB Publication 447498 D01v05.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
- Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
- Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.
- Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
- During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

GSM Test Notes:

- Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
- Justification for reduced test configurations per KDB Publication 941225 D03v01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.
- Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 54 of 66	

UMTS Notes:

1. UMTS mode in was tested under RMC 12.2 kbps with HSPA Inactive per KDB Publication 941225 D01v02. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.
2. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is $> \frac{1}{2}$ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.4.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

WLAN Notes:

1. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 5 GHz WIFI operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11a. Other IEEE 802.11 modes (including 802.11n 20 MHz and 40 MHz bandwidths) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11a mode.
3. When Hotspot is enabled, all 5 GHz bands are disabled. Therefore no 5 GHz WIFI Wireless Router SAR Data was required.
4. WIFI transmission was verified using an uncalibrated spectrum analyzer.
5. When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is < 1.6 W/kg and the reported 1g averaged SAR is < 0.8 W/kg, SAR testing on other default channels was not required.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 55 of 66	

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

Table 12-1
Estimated SAR

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR (Body)
	[MHz]	[dBm]	[mm]	[W/kg]
Bluetooth	2480	12.50	10	0.378

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 56 of 66	

12.3 Head SAR Simultaneous Transmission Analysis

Table 12-2
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.242	0.054	0.296	Head SAR	Right Cheek	0.147	0.054	0.201
	Right Tilt	0.141	0.045	0.186		Right Tilt	0.085	0.045	0.130
	Left Cheek	0.190	0.100	0.290		Left Cheek	0.198	0.100	0.298
	Left Tilt	0.138	0.078	0.216		Left Tilt	0.030	0.078	0.108
Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.222	0.054	0.276	Head SAR	Right Cheek	0.233	0.054	0.287
	Right Tilt	0.135	0.045	0.180		Right Tilt	0.129	0.045	0.174
	Left Cheek	0.163	0.100	0.263		Left Cheek	0.281	0.100	0.381
	Left Tilt	0.121	0.078	0.199		Left Tilt	0.046	0.078	0.124
Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.055	0.054	0.109	Head SAR	Right Cheek	0.203	0.054	0.257
	Right Tilt	0.040	0.045	0.085		Right Tilt	0.140	0.045	0.185
	Left Cheek	0.055	0.100	0.155		Left Cheek	0.175	0.100	0.275
	Left Tilt	0.035	0.078	0.113		Left Tilt	0.124	0.078	0.202
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.260	0.054	0.314	Head SAR	Right Cheek	0.210	0.054	0.264
	Right Tilt	0.063	0.045	0.108		Right Tilt	0.087	0.045	0.132
	Left Cheek	0.299	0.100	0.399		Left Cheek	0.258	0.100	0.358
	Left Tilt	0.123	0.078	0.201		Left Tilt	0.065	0.078	0.143

Table 12-3
Simultaneous Transmission Scenario with 5 GHz WLAN (Held to Ear)

Simult Tx	Configuration	GSM 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GSM 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.242	0.060	0.302	Head SAR	Right Cheek	0.147	0.060	0.207
	Right Tilt	0.141	0.043	0.184		Right Tilt	0.085	0.043	0.128
	Left Cheek	0.190	0.160	0.350		Left Cheek	0.198	0.160	0.358
	Left Tilt	0.138	0.116	0.254		Left Tilt	0.030	0.116	0.146
Simult Tx	Configuration	UMTS 850 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.222	0.060	0.282	Head SAR	Right Cheek	0.233	0.060	0.293
	Right Tilt	0.135	0.043	0.178		Right Tilt	0.129	0.043	0.172
	Left Cheek	0.163	0.160	0.323		Left Cheek	0.281	0.160	0.441
	Left Tilt	0.121	0.116	0.237		Left Tilt	0.046	0.116	0.162

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 57 of 66	

Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.055	0.060	0.115	Head SAR	Right Cheek	0.203	0.060	0.263
	Right Tilt	0.040	0.043	0.083		Right Tilt	0.140	0.043	0.183
	Left Cheek	0.055	0.160	0.215		Left Cheek	0.175	0.160	0.335
	Left Tilt	0.035	0.116	0.151		Left Tilt	0.124	0.116	0.240
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.260	0.060	0.320	Head SAR	Right Cheek	0.210	0.060	0.270
	Right Tilt	0.063	0.043	0.106		Right Tilt	0.087	0.043	0.130
	Left Cheek	0.299	0.160	0.459		Left Cheek	0.258	0.160	0.418
	Left Tilt	0.123	0.116	0.239		Left Tilt	0.065	0.116	0.181

12.4 Body-Worn Simultaneous Transmission Analysis

Table 12-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.418	0.027	0.445
Back Side	GSM 1900	0.397	0.027	0.424
Back Side	UMTS 850	0.346	0.027	0.373
Back Side	UMTS 1900	0.693	0.027	0.720
Back Side	LTE Band 17	0.127	0.027	0.154
Back Side	LTE Band 5 (Cell)	0.308	0.027	0.335
Back Side	LTE Band 4 (AWS)	0.519	0.027	0.546
Back Side	LTE Band 2 (PCS)	0.643	0.027	0.670

Table 12-5
Simultaneous Transmission Scenario with 5 GHz WLAN (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	5 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.418	0.017	0.435
Back Side	GSM 1900	0.397	0.017	0.414
Back Side	UMTS 850	0.346	0.017	0.363
Back Side	UMTS 1900	0.693	0.017	0.710
Back Side	LTE Band 17	0.127	0.017	0.144
Back Side	LTE Band 5 (Cell)	0.308	0.017	0.325
Back Side	LTE Band 4 (AWS)	0.519	0.017	0.536
Back Side	LTE Band 2 (PCS)	0.643	0.017	0.660

Table 12-6
Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)

Configuration	Mode	2G/3G/4G SAR (W/kg)	Bluetooth SAR (W/kg)	Σ SAR (W/kg)
Back Side	GSM 850	0.418	0.378	0.796
Back Side	GSM 1900	0.397	0.378	0.775
Back Side	UMTS 850	0.346	0.378	0.724
Back Side	UMTS 1900	0.693	0.378	1.071
Back Side	LTE Band 17	0.127	0.378	0.505
Back Side	LTE Band 5 (Cell)	0.308	0.378	0.686
Back Side	LTE Band 4 (AWS)	0.519	0.378	0.897
Back Side	LTE Band 2 (PCS)	0.643	0.378	1.021

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 58 of 66	

12.5 Hotspot SAR Simultaneous Transmission Analysis

Table 12-7
Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)

Simult Tx	Configuration	GPRS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	GPRS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.406	0.027	0.433	Body SAR	Back	0.378	0.027	0.405
	Front	0.348	0.015	0.363		Front	0.371	0.015	0.386
	Top	-	0.010	0.010		Top	-	0.010	0.010
	Bottom	0.165	-	0.165		Bottom	0.588	-	0.588
	Right	-	0.003	0.003		Right	-	0.003	0.003
	Left	0.292	-	0.292		Left	0.180	-	0.180
Simult Tx	Configuration	UMTS 850 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	UMTS 1900 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.346	0.027	0.373	Body SAR	Back	0.693	0.027	0.720
	Front	0.310	0.015	0.325		Front	0.726	0.015	0.741
	Top	-	0.010	0.010		Top	-	0.010	0.010
	Bottom	0.137	-	0.137		Bottom	1.060	-	1.060
	Right	-	0.003	0.003		Right	-	0.003	0.003
	Left	0.296	-	0.296		Left	0.319	-	0.319
Simult Tx	Configuration	LTE Band 17 SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 5 (Cell) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.127	0.027	0.154	Body SAR	Back	0.308	0.027	0.335
	Front	0.122	0.015	0.137		Front	0.295	0.015	0.310
	Top	-	0.010	0.010		Top	-	0.010	0.010
	Bottom	0.033	-	0.033		Bottom	0.128	-	0.128
	Right	-	0.003	0.003		Right	-	0.003	0.003
	Left	0.088	-	0.088		Left	0.251	-	0.251
Simult Tx	Configuration	LTE Band 4 (AWS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	LTE Band 2 (PCS) SAR (W/kg)	2.4 GHz WLAN SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.519	0.027	0.546	Body SAR	Back	0.643	0.027	0.670
	Front	0.524	0.015	0.539		Front	0.669	0.015	0.684
	Top	-	0.010	0.010		Top	-	0.010	0.010
	Bottom	0.709	-	0.709		Bottom	0.974	-	0.974
	Right	-	0.003	0.003		Right	-	0.003	0.003
	Left	0.182	-	0.182		Left	0.341	-	0.341

12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 59 of 66	

13 SAR MEASUREMENT VARIABILITY

13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 13-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS													
Band	FREQUENCY		Mode	Service	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.					(W/kg)	(W/kg)		(W/kg)		(W/kg)	
1900	1907.60	9538	UMTS 1900	RMC	bottom	10 mm	0.992	0.938	1.06	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram							

13.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.

FCC ID: A3LSMA500M	 PCTEST ENGINEERING LABORATORY, INC.	SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 60 of 66	

14 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E5515C	Wireless Communications Test Set	9/24/2012	Biennial	9/24/2014	G843163447
Agilent	8753ES	S-Parameter Network Analyzer	10/29/2013	Annual	10/29/2014	US39170122
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/15/2014	Annual	4/15/2015	MY45470194
Agilent	8648D	(9kHz-4GHz) Signal Generator	4/15/2014	Annual	4/15/2015	3629U00687
Agilent	E4438C	ESG Vector Signal Generator	4/15/2014	Annual	4/15/2015	MY45091346
Agilent	E4438C	ESG Vector Signal Generator	4/25/2014	Annual	4/25/2015	MY42082385
Agilent	8753ES	S-Parameter Network Analyzer	5/22/2014	Annual	5/22/2015	US39170118
Agilent	8594A	(9kHz-2.9GHz) Spectrum Analyzer	N/A	N/A	N/A	3051A00187
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433978
Anritsu	MA2481A	Power Sensor	10/30/2013	Annual	10/30/2014	5605
Anritsu	ML2495A	Power Meter	10/31/2013	Annual	10/31/2014	1039008
Anritsu	MT8820C	Radio Communication Analyzer	12/12/2013	Annual	12/12/2014	6200901190
Anritsu	MA2411B	Pulse Power Sensor	2/3/2014	Annual	2/3/2015	1339018
Anritsu	ML2469A	Power Meter	3/14/2014	Annual	3/14/2015	1306009
Anritsu	MA2411B	Pulse Power Sensor	3/25/2014	Annual	3/25/2015	1207470
Anritsu	MA24106A	USB Power Sensor	5/15/2014	Annual	5/15/2015	1244524
Anritsu	MA24106A	USB Power Sensor	5/15/2014	Annual	5/15/2015	1244512
COMTECH	AR85729-5/5759B	Solid State Amplifier	CBT	N/A	CBT	M3W1A00-1002
COMTECH	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	61220-416	Long-Stem Thermometer	4/29/2014	Biennial	4/29/2016	111331323
Control Company	36934-158	Wall-Mounted Thermometer	4/29/2014	Biennial	4/29/2016	122014488
Fisher Scientific	S97611	Thermometer	4/12/2013	Biennial	4/12/2015	130219304
Fisher Scientific	15-077-960	Digital Thermometer	12/4/2013	Biennial	12/4/2015	130764558
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/30/2013	Annual	10/30/2014	1833460
Gigatronics	8651A	Universal Power Meter	10/30/2013	Annual	10/30/2014	8650319
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mitutoyo	CD-6"CSX	Digital Caliper	5/8/2014	Biennial	5/8/2016	13264165
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	NRVD	Dual Channel Power Meter	10/12/2012	Biennial	10/12/2014	101695
Rohde & Schwarz	NRV-232	Peak Power Sensor	10/12/2012	Biennial	10/12/2014	836019/013
Rohde & Schwarz	CMW500	Radio Communication Tester	10/18/2013	Annual	10/18/2014	100976
Rohde & Schwarz	SME06	Signal Generator	10/30/2013	Annual	10/30/2014	832026
Rohde & Schwarz	NRVS	Single Channel Power Meter	10/31/2013	Annual	10/31/2014	835360/0079
Rohde & Schwarz	CMU200	Base Station Simulator	6/6/2014	Annual	6/6/2015	109892
Seekonk	NC-100	Torque Wrench	3/18/2014	Biennial	3/18/2016	22313
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/18/2014	Biennial	3/18/2016	N/A
SPEAG	EX3DV4	SAR Probe	10/23/2013	Annual	10/23/2014	3914
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/19/2013	Annual	11/19/2014	1333
SPEAG	DAE4	Dasy Data Acquisition Electronics	11/19/2013	Annual	11/19/2014	1408
SPEAG	ES3DV3	SAR Probe	11/20/2013	Annual	11/20/2014	3287
SPEAG	D750V3	750 MHz Dipole	1/20/2014	Annual	1/20/2015	1003
SPEAG	D2450V2	2450 MHz SAR Dipole	1/21/2014	Annual	1/21/2015	797
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/27/2014	Annual	1/27/2015	1057
SPEAG	EX3DV4	SAR Probe	1/29/2014	Annual	1/29/2015	3589
SPEAG	ES3DV3	SAR Probe	2/25/2014	Annual	2/25/2015	3258
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/26/2014	Annual	2/26/2015	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2014	Annual	3/17/2015	1334
SPEAG	ES3DV3	SAR Probe	3/19/2014	Annual	3/19/2015	3209
SPEAG	D835V2	835 MHz SAR Dipole	4/7/2014	Annual	4/7/2015	40119
SPEAG	D1900V2	1900 MHz SAR Dipole	4/9/2014	Annual	4/9/2015	50141
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/11/2014	Annual	4/11/2015	1368
SPEAG	ES3DV3	SAR Probe	4/17/2014	Annual	4/17/2015	3319
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/6/2014	Annual	5/6/2015	1070
SPEAG	D1765V2	1765 MHz SAR Dipole	5/7/2014	Annual	5/7/2015	1008
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/14/2014	Annual	5/14/2015	859
SPEAG	ES3DV3	SAR Probe	5/15/2014	Annual	5/15/2015	3263
Tektronix	RSA6114A	Real Time Spectrum Analyzer	4/16/2014	Annual	4/16/2015	8010177

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

2. Each equipment item was used solely within its respective calibration period.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 61 of 66

15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.2	23.5

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 62 of 66

Applicable for frequencies up to 6 GHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset	Page 63 of 66	

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 64 of 66

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 65 of 66

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: A3LSMA500M		SAR EVALUATION REPORT		Reviewed by: Quality Manager
Document S/N: OY1409081825.A3L	Test Dates: 09/15/14 - 09/23/14	DUT Type: Portable Handset		Page 66 of 66

APPENDIX A: SAR TEST DATA

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.571$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Right Head, Cheek, Mid.ch


Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (6x6x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 16.01 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.290 W/kg

SAR(1 g) = 0.230 W/kg



0 dB = 0.252 W/kg = -5.99 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, GSM1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Head Medium parameters used:

$$f = 1880 \text{ MHz}; \sigma = 1.423 \text{ S/m}; \epsilon_r = 39.372; \rho = 1000 \text{ kg/m}^3$$

Phantom section: Left Section

Test Date: 09-22-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(5.08, 5.08, 5.08); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Left Head, Cheek, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.14 V/m; Power Drift = -0.15 dB

Peak SAR (extrapolated) = 0.267 W/kg

SAR(1 g) = 0.179 W/kg



0 dB = 0.211 W/kg = -6.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.571$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Right Head, Cheek, Mid.ch


Area Scan (9x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 15.45 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.219 W/kg



0 dB = 0.241 W/kg = -6.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used:

$$f = 1880 \text{ MHz}; \sigma = 1.423 \text{ S/m}; \epsilon_r = 39.372; \rho = 1000 \text{ kg/m}^3$$

Phantom section: Left Section

Test Date: 09-22-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(5.08, 5.08, 5.08); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Left Head, Cheek, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 13.51 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.385 W/kg

SAR(1 g) = 0.259 W/kg



0 dB = 0.303 W/kg = -5.19 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used:

$f = 710 \text{ MHz}$; $\sigma = 0.873 \text{ S/m}$; $\epsilon_r = 40.911$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 09-18-2014; Ambient Temp: 24.3°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3263; ConvF(6.42, 6.42, 6.42); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 17, Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.272 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.0660 W/kg

SAR(1 g) = 0.053 W/kg



0 dB = 0.0578 W/kg = -12.38 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 5 (Cell.); Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 0.926 \text{ S/m}$; $\epsilon_r = 41.573$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Right Head, Cheek, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.82 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.256 W/kg

SAR(1 g) = 0.199 W/kg



0 dB = 0.216 W/kg = -6.66 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.34 \text{ S/m}$; $\epsilon_r = 39.583$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 09-17-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(5.19, 5.19, 5.19); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset**


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.95 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.457 W/kg

SAR(1 g) = 0.299 W/kg



0 dB = 0.346 W/kg = -4.61 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.416 \text{ S/m}$; $\epsilon_r = 39.966$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.8°C

Probe: ES3DV3 - SN3287; ConvF(5.08, 5.08, 5.08); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, High.ch,
QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset**


Area Scan (9x15x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 14.08 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.326 W/kg

SAR(1 g) = 0.214 W/kg



0 dB = 0.255 W/kg = -5.93 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT6

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 1.827 \text{ S/m}$; $\epsilon_r = 39.649$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 09-15-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Left Head, Cheek, Ch 11, 1 Mbps


Area Scan (10x16x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$

Zoom Scan (8x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.791 V/m; Power Drift = 0.19 dB

Peak SAR (extrapolated) = 0.265 W/kg

SAR(1 g) = 0.099 W/kg



0 dB = 0.141 W/kg = -8.51 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, IEEE 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5785 \text{ MHz}$; $\sigma = 5.126 \text{ S/m}$; $\epsilon_r = 35.418$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 09-18-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.8 GHz, Left Head, Cheek, Ch 157, 6 Mbps


Area Scan (13x19x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Reference Value = 3.706 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.297 W/kg

SAR(1 g) = 0.050 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, IEEE 802.11a; Frequency: 5660 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5660 \text{ MHz}$; $\sigma = 5.004 \text{ S/m}$; $\epsilon_r = 35.53$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

Test Date: 09-18-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3914; ConvF(4.37, 4.37, 4.37); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.5-5.7 GHz, Left Head, Cheek, Ch 132, 6 Mbps


Area Scan (13x19x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 5.860 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 0.744 W/kg

SAR(1 g) = 0.154 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, GSM; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.009 \text{ S/m}$; $\epsilon_r = 53.226$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.16, 6.16, 6.16); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 850, Body SAR, Back side, Mid.ch


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.75 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.569 W/kg

SAR(1 g) = 0.398 W/kg



0 dB = 0.445 W/kg = -3.52 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, GSM GPRS; 1 Tx slot; Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.009 \text{ S/m}$; $\epsilon_r = 53.226$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.16, 6.16, 6.16); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 850, Body SAR, Back side, Mid.ch, 1 Tx Slots


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (6x6x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.17 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.536 W/kg

SAR(1 g) = 0.380 W/kg



0 dB = 0.428 W/kg = -3.69 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, GSM; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.502 \text{ S/m}$; $\epsilon_r = 50.892$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-23-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GSM 1900, Body SAR, Back Side, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.23 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.570 W/kg

SAR(1 g) = 0.359 W/kg



0 dB = 0.422 W/kg = -3.75 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, GSM GPRS; 1 Tx slot; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.502 \text{ S/m}$; $\epsilon_r = 50.892$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-23-2014; Ambient Temp: 23.8°C; Tissue Temp: 23.7°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: GPRS 1900, Body SAR, Bottom Edge, Mid.ch, 1 Tx Slot


Area Scan (11x9x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 20.25 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.879 W/kg

SAR(1 g) = 0.533 W/kg



0 dB = 0.654 W/kg = -1.84 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, UMTS; Frequency: 836.6 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.6 \text{ MHz}$; $\sigma = 1.009 \text{ S/m}$; $\epsilon_r = 53.226$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.16, 6.16, 6.16); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 850, Body SAR, Back side, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.06 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 0.474 W/kg

SAR(1 g) = 0.341 W/kg



0 dB = 0.380 W/kg = -4.20 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, UMTS; Frequency: 1880 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used:

$f = 1880 \text{ MHz}$; $\sigma = 1.523 \text{ S/m}$; $\epsilon_r = 51.404$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Back Side, Mid.ch


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.67 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.639 W/kg



0 dB = 0.774 W/kg = -1.11 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT5

Communication System: UID 0, UMTS, Frequency: 1907.6 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated):

$f = 1907.6 \text{ MHz}$; $\sigma = 1.558 \text{ S/m}$; $\epsilon_r = 51.323$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: UMTS 1900, Body SAR, Bottom Edge, High.ch


Area Scan (11x8x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 26.55 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 0.992 W/kg



0 dB = 1.19 W/kg = 0.76 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 17; Frequency: 710 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used:

$f = 710 \text{ MHz}$; $\sigma = 0.936 \text{ S/m}$; $\epsilon_r = 54.206$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-17-2014; Ambient Temp: 23.9°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3209; ConvF(6.16, 6.16, 6.16); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 17, Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (9x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.85 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.161 W/kg

SAR(1 g) = 0.123 W/kg



0 dB = 0.137 W/kg = -8.63 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used (interpolated):

$f = 836.5 \text{ MHz}$; $\sigma = 1.009 \text{ S/m}$; $\epsilon_r = 53.227$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.16, 6.16, 6.16); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 5 (Cell.), Body SAR, Back side, Mid.ch,
10 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x12x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.88 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 0.416 W/kg

SAR(1 g) = 0.302 W/kg



0 dB = 0.337 W/kg = -4.72 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.46 \text{ S/m}$; $\epsilon_r = 52.326$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(4.85, 4.85, 4.85); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,

20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 20.19 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.777 W/kg

SAR(1 g) = 0.519 W/kg



0 dB = 0.617 W/kg = -2.10 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used (interpolated):

$f = 1732.5 \text{ MHz}$; $\sigma = 1.46 \text{ S/m}$; $\epsilon_r = 52.326$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(4.85, 4.85, 4.85); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 4 (AWS), Body SAR, Bottom Edge, Mid.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (13x7x1): Measurement grid: dx=5mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 23.62 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 1.12 W/kg

SAR(1 g) = 0.709 W/kg



0 dB = 0.857 W/kg = -0.67 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.548 \text{ S/m}$; $\epsilon_r = 51.345$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Back Side, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.81 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.884 W/kg

SAR(1 g) = 0.534 W/kg



0 dB = 0.639 W/kg = -1.94 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT4

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.548 \text{ S/m}$; $\epsilon_r = 51.345$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Mode: LTE Band 2 (PCS), Body SAR, Bottom Edge, High.ch,
20 MHz Bandwidth, QPSK, 1 RB, 0 RB Offset**


Area Scan (11x8x1): Measurement grid: $dx=5\text{mm}$, $dy=15\text{mm}$

Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.80 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.808 W/kg



0 dB = 0.994 W/kg = -0.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT6

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used (interpolated):

$f = 2462 \text{ MHz}$; $\sigma = 2.062 \text{ S/m}$; $\epsilon_r = 51.066$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 20.8°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Back Side


Area Scan (10x16x1): Measurement grid: dx=12mm, dy=12mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.625 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0570 W/kg

SAR(1 g) = 0.027 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT6

Communication System: UID 0, IEEE 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5785 \text{ MHz}$; $\sigma = 6.233 \text{ S/m}$; $\epsilon_r = 46.199$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3589; ConvF(3.97, 3.97, 3.97); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.8 GHz, Body SAR, Ch 157, 6 Mbps, Back Side


Area Scan (17x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 1.271 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 0.0690 W/kg

SAR(1 g) = 0.00355 W/kg



PCTEST ENGINEERING LABORATORY, INC.

DUT: A3LSMA500M; Type: Portable Handset; Serial: PCT6

Communication System: UID 0, IEEE 802.11a; Frequency: 5660 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5660 \text{ MHz}$; $\sigma = 6.033 \text{ S/m}$; $\epsilon_r = 46.479$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3589; ConvF(3.81, 3.81, 3.81); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Mode: IEEE 802.11a, 5.5-5.7 GHz, Body SAR, Ch 132, 6 Mbps, Back Side


Area Scan (17x22x1): Measurement grid: dx=10mm, dy=10mm

Zoom Scan (9x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Reference Value = 1.221 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 0.108 W/kg

SAR(1 g) = 0.015 W/kg



APPENDIX B: SYSTEM VERIFICATION

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Head Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.906 \text{ S/m}$; $\epsilon_r = 40.299$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 09-18-2014; Ambient Temp: 24.3°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3263; ConvF(6.42, 6.42, 6.42); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.31 W/kg

SAR(1 g) = 0.860 W/kg

Deviation: 2.75%



0 dB = 1.01 W/kg = 0.04 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Head Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 0.925 \text{ S/m}$; $\epsilon_r = 41.591$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.23, 6.23, 6.23); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 Left; Type: QD000P40CD; Serial: TP: 1687

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.45 W/kg

SAR(1 g) = 0.961 W/kg

Deviation: 4.23%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Head Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.357 \text{ S/m}$; $\epsilon_r = 39.498$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-17-2014; Ambient Temp: 24.0°C; Tissue Temp: 23.0°C

Probe: ES3DV3 - SN3258; ConvF(5.19, 5.19, 5.19); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.27 W/kg

SAR(1 g) = 3.43 W/kg

Deviation: -7.05%



0 dB = 4.29 W/kg = 6.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Head Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.444 \text{ S/m}$; $\epsilon_r = 39.264$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-22-2014; Ambient Temp: 23.0°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3287; ConvF(5.08, 5.08, 5.08); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1797

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.63 W/kg

SAR(1 g) = 4.26 W/kg

Deviation: 6.23%



0 dB = 5.40 W/kg = 7.32 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Head Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 1.815 \text{ S/m}$; $\epsilon_r = 39.696$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 24.4°C; Tissue Temp: 23.6°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: SAM Front; Type: SAM; Serial: 1686

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: dx=12mm, dy=12mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 5.36 W/kg

Deviation: 3.47%



0 dB = 6.97 W/kg = 8.43 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 4.541 \text{ S/m}$; $\epsilon_r = 36.087$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-18-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.1°C

Probe: EX3DV4 - SN3914; ConvF(4.99, 4.99, 4.99); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5200 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 31.3 W/kg

SAR(1 g) = 7.27 W/kg

Deviation: -6.79%



0 dB = 18.2 W/kg = 12.60 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 4.635 \text{ S/m}$; $\epsilon_r = 35.984$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-18-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.1°C

Probe: EX3DV4 - SN3914; ConvF(4.82, 4.82, 4.82); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.2 W/kg

SAR(1 g) = 7.86 W/kg

Deviation: -5.30%



0 dB = 20.1 W/kg = 13.03 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 4.955 \text{ S/m}$; $\epsilon_r = 35.553$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-18-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3914; ConvF(4.37, 4.37, 4.37); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x7x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 34.3 W/kg

SAR(1 g) = 7.77 W/kg

Deviation: -6.95%



0 dB = 19.0 W/kg = 12.79 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Head Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 5.13 \text{ S/m}$; $\epsilon_r = 35.336$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.0 cm

Test Date: 09-18-2014; Ambient Temp: 24.2°C; Tissue Temp: 23.2°C

Probe: EX3DV4 - SN3914; ConvF(4.52, 4.52, 4.52); Calibrated: 10/23/2013;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1333; Calibrated: 11/19/2013

Phantom: SAM V5.0 Right; Type: QD000P40CD; Serial: 1647

Measurement SW: DASY52, Version 52.8 (8);SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x7x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 33.9 W/kg

SAR(1 g) = 7.30 W/kg

Deviation: -7.94%



0 dB = 18.0 W/kg = 12.55 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: SAR Dipole 750 MHz; Type: D750V3; Serial: 1003

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium: 750 Body Medium parameters used (interpolated):

$f = 750 \text{ MHz}$; $\sigma = 0.971 \text{ S/m}$; $\epsilon_r = 53.767$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 09-17-2014; Ambient Temp: 23.9°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3209; ConvF(6.16, 6.16, 6.16); Calibrated: 3/19/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM front; Type: QD000P40CD; Serial: TP:1759

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

750 MHz System Verification

Area Scan (7x15x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.33 W/kg

SAR(1 g) = 0.920 W/kg

Deviation: 4.90%



0 dB = 1.07 W/kg = 0.29 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d119

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: 835 Body Medium parameters used:

$f = 835 \text{ MHz}$; $\sigma = 1.007 \text{ S/m}$; $\epsilon_r = 53.246$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.5 cm

Test Date: 09-15-2014; Ambient Temp: 22.4°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3263; ConvF(6.16, 6.16, 6.16); Calibrated: 5/15/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn859; Calibrated: 5/14/2014

Phantom: SAM v5.0 front; Type: QD000P40CD; Serial: TP-1646

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

835 MHz System Verification

Area Scan (7x14x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 1.42 W/kg

SAR(1 g) = 0.960 W/kg

Deviation: 2.78%



0 dB = 1.12 W/kg = 0.49 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1750 MHz; Type: D1765V2; Serial: 1008

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium: 1750 Body Medium parameters used:

$f = 1750 \text{ MHz}$; $\sigma = 1.479 \text{ S/m}$; $\epsilon_r = 52.229$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 22.1°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3319; ConvF(4.85, 4.85, 4.85); Calibrated: 4/17/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1368; Calibrated: 4/11/2014

Phantom: SAM; Type: QD000P40CD; Serial: TP:1758

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1750 MHz System Verification

Area Scan (7x9x1): Measurement grid: dx=15mm, dy=15mm


Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 6.62 W/kg

SAR(1 g) = 3.81 W/kg

Deviation: 1.33%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d141

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: 1900 Body Medium parameters used (interpolated):

$f = 1900 \text{ MHz}$; $\sigma = 1.548 \text{ S/m}$; $\epsilon_r = 51.345$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.4°C; Tissue Temp: 22.2°C

Probe: ES3DV3 - SN3287; ConvF(4.67, 4.67, 4.67); Calibrated: 11/20/2013;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1408; Calibrated: 11/19/2013

Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1229

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

1900 MHz System Verification

Area Scan (7x10x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$


Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 7.75 W/kg

SAR(1 g) = 4.32 W/kg

Deviation: 6.40%



0 dB = 5.42 W/kg = 7.34 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 797

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Body Medium parameters used:

$f = 2450 \text{ MHz}$; $\sigma = 2.046 \text{ S/m}$; $\epsilon_r = 51.116$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 20.8°C; Tissue Temp: 22.4°C

Probe: ES3DV3 - SN3258; ConvF(4.14, 4.14, 4.14); Calibrated: 2/25/2014;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn665; Calibrated: 2/26/2014

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1158

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

2450 MHz System Verification

Area Scan (8x9x1): Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 11.0 W/kg

SAR(1 g) = 5.29 W/kg

Deviation: 7.09%



0 dB = 6.92 W/kg = 8.40 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5200 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5200 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5200 \text{ MHz}$; $\sigma = 5.345 \text{ S/m}$; $\epsilon_r = 47.648$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3589; ConvF(4.19, 4.19, 4.19); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5200 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (9x9x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 33.8 W/kg

SAR(1 g) = 7.79 W/kg

Deviation: 3.45%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5300 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5300 \text{ MHz}$; $\sigma = 5.491 \text{ S/m}$; $\epsilon_r = 47.379$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3589; ConvF(3.98, 3.98, 3.98); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5300 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 35.6 W/kg

SAR(1 g) = 8.03 W/kg

Deviation: 3.75%



0 dB = 20.8 W/kg = 13.18 dBW/kg

PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5600 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5600 \text{ MHz}$; $\sigma = 5.957 \text{ S/m}$; $\epsilon_r = 46.603$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3589; ConvF(3.81, 3.81, 3.81); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5600 MHz System Verification

Area Scan (7x8x1): Measurement grid: dx=10mm, dy=10mm


Zoom Scan (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 39.5 W/kg

SAR(1 g) = 7.57 W/kg

Deviation: -5.61%



PCTEST ENGINEERING LABORATORY, INC.

DUT: Dipole 5800 MHz; Type: D5GHzV2; Serial: 1057

Communication System: UID 0, CW; Frequency: 5800 MHz; Duty Cycle: 1:1

Medium: 5 GHz Body Medium parameters used:

$f = 5800 \text{ MHz}$; $\sigma = 6.242 \text{ S/m}$; $\epsilon_r = 46.136$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section ; Space: 1.0 cm

Test Date: 09-15-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: EX3DV4 - SN3589; ConvF(3.97, 3.97, 3.97); Calibrated: 1/29/2014;

Sensor-Surface: 1.4mm (Mechanical Surface Detection)

Electronics: DAE4 Sn1334; Calibrated: 3/17/2014

Phantom: SAM Right; Type: SAM; Serial: 1757

Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

5800 MHz System Verification

Area Scan (7x8x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$


Zoom Scan (8x8x7)/Cube 0: Measurement grid: $dx=4\text{mm}$, $dy=4\text{mm}$, $dz=1.4\text{mm}$; Graded Ratio: 1.4

Input Power: 20 dBm (100 mW)

Peak SAR (extrapolated) = 38.4 W/kg

SAR(1 g) = 7.44 W/kg

Deviation: 0.13%



0 dB = 20.3 W/kg = 13.07 dBW/kg