


FCC SAR Test Report

APPLICANT : Samsung Electronics Co., Ltd.
EQUIPMENT : Mobile phone
BRAND NAME : SAMSUNG
MODEL NAME : SM-A500YZ
FCC ID : A3LSMA500YZ
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003

We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



Testing Laboratory
2353

SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C.



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Standard	5
4. Equipment Under Test (EUT)	6
4.1 General Information	6
4.2 Maximum Tune-up Limit	7
5. RF Exposure Limits	8
5.1 Uncontrolled Environment	8
5.2 Controlled Environment	8
6. Specific Absorption Rate (SAR)	9
6.1 Introduction	9
6.2 SAR Definition	9
7. System Description and Setup	10
8. Measurement Procedures	11
8.1 Spatial Peak SAR Evaluation	11
8.2 Power Reference Measurement	12
8.3 Area Scan	12
8.4 Zoom Scan	13
8.5 Volume Scan Procedures	13
8.6 Power Drift Monitoring	13
9. Test Equipment List	14
10. System Verification	15
10.1 Tissue Verification	15
10.2 System Performance Check Results	17
11. RF Exposure Positions	18
11.1 Ear and handset reference point	18
11.2 Definition of the cheek position	19
11.3 Definition of the tilt position	20
11.4 Body Worn Accessory	21
11.5 Wireless Router	21
12. Conducted RF Output Power (Unit: dBm)	22
13. Antenna Location	31
14. SAR Test Results	33
14.1 Head SAR	33
14.2 Hotspot SAR	35
14.3 Body Worn Accessory SAR	37
15. Simultaneous Transmission Analysis	38
15.1 Head Exposure Conditions	39
15.2 Hotspot Exposure Conditions	41
15.3 Body-Worn Accessory Exposure Conditions	44
16. Uncertainty Assessment	45
17. References	48
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. SAR System Validation	
Appendix E. Test Setup Photos	



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA482502	Rev. 01	Initial issue of report	Oct. 20, 2014

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Samsung Electronics Co., Ltd., Mobile phone, SM-A500YZ** are as follows.

Equipment Class	Frequency Band	Highest SAR Summary				
		Head 1g SAR (W/kg)	Wireless Router 1g SAR (W/kg) (Gap 1cm)	Body-worn 1g SAR (W/kg) (Gap 1cm)	Highest Simultaneous Transmission Head 1g SAR (W/kg)	Highest Simultaneous Transmission Body 1g SAR (W/kg)
PCE	GSM850	0.37	0.95	0.95	0.50	0.99
	GSM1900	0.25	0.64	0.55		
	WCDMA Band V	0.19	0.54	0.54		
	WCDMA Band II	0.27	0.79	0.79		
DTS	WLAN 2.4GHz	0.22	< 0.10	< 0.10	0.50	0.99
NII	WLAN 5.2GHz	0.17		< 0.10	0.47	0.97
	WLAN 5.3GHz	0.20		< 0.10		
	WLAN 5.5GHz	< 0.10		< 0.10		
	WLAN 5.8GHz	< 0.10	< 0.10	< 0.10		
DSS	Bluetooth	0.12	< 0.10	< 0.10	0.42	0.97
Date of Testing:		Sep. 22, 2014 ~ Oct. 06, 2014				

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	No. 101, Complex Building C, Guanlong Village, Xili Town, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755-8637-9589 FAX: +86-755-8637-9595

Applicant	
Company Name	Samsung Electronics Co., Ltd.
Address	No.9 WeiWu Rd, Micro Electronic Industrial Park, Jingang Highway, Xiqing District, Tianjin, China

Manufacturer	
Company Name	Samsung Electronics Co., Ltd.
Address	256, 6th Road Zhongkai, Chenjiang Town Huizhou City, Guangdong Province, China

3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r02
- FCC KDB 248227 D01 SAR meas for 802 11abg v01r02
- FCC KDB 941225 D01 SAR test for 3G devices v02
- FCC KDB 941225 D02 HSPA and 1x Advanced v02r02
- FCC KDB 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- FCC KDB 941225 D06 Hotspot Mode SAR v01r01

4. Equipment Under Test (EUT)

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile phone
Brand Name	SAMSUNG
Model Name	SM-A500YZ
FCC ID	A3LSMA500YZ
IMEI Code	356150060002980
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	• GSM/GPRS/EGPRS • RMC/AMR 12.2Kbps • HSDPA • HSUPA • DC-HSDPA • WLAN 2.4GHz 802.11b/g/n HT20 • WLAN 5GHz 802.11a/n HT20/HT40 • Bluetooth v3.0+EDR, Bluetooth v4.0 LE
HW Version	REV1.0
SW Version	A500YZ.001
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: 1. WLAN operation in 5600 MHz ~ 5650 MHz is notched and 802.11n-HT40 is not supported in 2.4GHz WLAN. 2. This device 2.4GHz WLAN supports hotspot operation, and 2.4GHz / 5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.2GHz / 5.3GHz / 5.5GHz supports WiFi Direct (GC only). 3. This device supported VoIP in GPRS, EGPRS and WCDMA (e.g. 3rd party VoIP). 4. This device supports GRPS/EGPRS mode up to multi-slot class33 and does not support DTM operation. 5. The HSPA+ does not support 16QAM uplink.	

4.2 Maximum Tune-up Limit

Mode	Burst Average Power (dBm)	
	GSM850	GSM1900
GSM (GMSK, 1 Tx slot)	33.5	30.5
GPRS (GMSK, 1 Tx slot)	33.5	30.5
GPRS (GMSK, 2 Tx slots)	30.5	28.5
GPRS (GMSK, 3 Tx slots)	29.5	26.5
GPRS (GMSK, 4 Tx slots)	28.0	25.5
EDGE (8PSK, 1 Tx slot)	28.0	26.0
EDGE (8PSK, 2 Tx slots)	28.0	26.0
EDGE (8PSK, 3 Tx slots)	25.5	24.5
EDGE (8PSK, 4 Tx slots)	25.5	24.5

Mode	Average Power (dBm)	
	WCDMA Band V	WCDMA Band II
RMC/AMR 12.2Kbps	23.0	22.5
HSDPA	22.0	22.5
DC-HSDPA	22.0	22.5
HSUPA	22.0	22.5

Mode			Maximum Average Power (dBm)
2.4GHz	802.11b		16.0
	802.11g		14.0
	802.11n-HT20		12.5
5GHz	802.11a	5.2GHz	12.5
		5.3GHz	13.0
		5.5GHz	11.5
		5.8GHz	13.5
	802.11n-HT20	5.2GHz	12.5
		5.3GHz	12.5
		5.5GHz	11.5
		5.8GHz	12.5
	802.11n-HT40	5.2GHz	11.5
		5.3GHz	11.5
		5.5GHz	10.5
		5.8GHz	11.0
Bluetooth v3.0+EDR			12.5
Bluetooth v4.0 LE			3.5



5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)


$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.



7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
Measurement Areas	Left Hand, Right Hand, Flat Phantom



Photo of SAM Phantom

- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 18, 2011	Nov. 17, 2014
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2011	Nov. 20, 2014
SPEAG	2450MHz System Validation Kit	D2450V2	908	Mar. 26, 2013	Mar. 25, 2015
SPEAG	5000MHz System Validation Kit	D5GHzV2	1128	Jul. 22, 2014	Jul. 21, 2015
SPEAG	Data Acquisition Electronics	DAE4	910	Jul. 22, 2014	Jul. 21, 2015
SPEAG	Data Acquisition Electronics	DAE4	1210	May 19, 2014	May 18, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3819	Nov. 27, 2013	Nov. 26, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3857	May 23, 2014	May 22, 2015
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1670	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1671	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1477	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Agilent	Wireless Communication Test Set	E5515C	MY50267224	Oct. 10, 2013	Oct. 09, 2014
Agilent	Wireless Communication Test Set	E5515E	MY53211040	Jun. 12, 2014	Jun. 11, 2015
Anritsu	Bluetooth Base Station	MT8852B-042	1336001	Jul. 17, 2014	Jul. 16, 2015
R&S	Network Analyzer	ZVB8	100106	Nov. 07, 2013	Nov. 06, 2014
Speag	Dielectric Assessment Kit	DAK-3.5	1032	NCR	NCR
Anritsu	Power Meter	ML2495A	1218010	Mar. 03, 2014	Mar. 02, 2015
Anritsu	Power Sensor	MA2411B	1207253	Mar. 03, 2014	Mar. 02, 2015
ARRA	Power Divider	A3200-2	N/A	NA	NA
R&S	Spectrum Analyzer	FSP30	101362	Oct. 10, 2013	Oct. 09, 2014
Agilent	Dual Directional Coupler	778D	50422	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note1	
PE	Attenuator 2	PE7005-10	N/A	Note1	
PE	Attenuator 3	PE7005- 3	N/A	Note1	
AR	Power Amplifier	5S1G4M2	0328767	Note1	
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	Note1	
Mini-Circuits	Power Amplifier	ZHL-42W+	13440021344	Note1	

General Note:

- Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
- Referring to KDB 865664 D01v01r03, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
- The justification data of dipole D835V2, SN: 4d091, D1900V2, SN: 5d118 and D2450V2, SN: 908 can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

10. System Verification

10.1 Tissue Verification

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm; For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which are show as followings.



Photo of Liquid Height for Head SAR



Photo of Liquid Height for Body SAR

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	22.6	0.910	42.910	0.90	41.50	1.11	3.40	±5	Sep. 22, 2014
1900	Head	22.8	1.419	40.346	1.40	40.00	1.36	0.86	±5	Sep. 23, 2014
2450	Head	22.7	1.878	40.464	1.80	39.20	4.33	3.22	±5	Sep. 23, 2014
5200	Head	22.6	4.811	35.43	4.66	36.00	3.24	-1.58	±5	Oct. 05, 2014
5300	Head	22.6	4.917	35.291	4.76	35.90	3.30	-1.70	±5	Oct. 05, 2014
5600	Head	22.6	5.183	34.839	5.07	35.50	2.23	-1.86	±5	Oct. 05, 2014
5800	Head	22.6	5.42	34.321	5.27	35.30	2.85	-2.77	±5	Oct. 05, 2014
835	Body	22.7	1.000	54.086	0.97	55.20	3.09	-2.02	±5	Sep. 22, 2014
1900	Body	22.8	1.542	53.532	1.52	53.30	1.45	0.44	±5	Sep. 23, 2014
2450	Body	22.7	1.992	52.302	1.95	52.70	2.15	-0.76	±5	Sep. 24, 2014
5200	Body	22.8	5.297	49.185	5.30	49.00	-0.06	0.38	±5	Oct. 06, 2014
5300	Body	22.8	5.439	48.992	5.42	48.90	0.35	0.19	±5	Oct. 06, 2014
5600	Body	22.8	5.872	48.306	5.77	48.50	1.77	-0.40	±5	Oct. 06, 2014
5800	Body	22.8	6.127	47.784	6.00	48.20	2.12	-0.86	±5	Oct. 06, 2014

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured SAR (W/kg)	Targeted SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
Sep. 22, 2014	835	Head	250	4d091	3819	910	2.20	9.40	8.8	-6.38
Sep. 23, 2014	1900	Head	250	5d118	3819	910	10.10	40.30	40.4	0.25
Sep. 23, 2014	2450	Head	250	908	3819	910	12.60	54.00	50.4	-6.67
Oct. 05, 2014	5200	Head	100	1128	3857	1210	8.29	79.8	82.9	3.88
Oct. 05, 2014	5300	Head	100	1128	3857	1210	8.32	81.6	83.2	1.96
Oct. 05, 2014	5600	Head	100	1128	3857	1210	8.78	84	87.8	4.52
Oct. 05, 2014	5800	Head	100	1128	3857	1210	8.36	78.9	83.6	5.96
Sep. 22, 2014	835	Body	250	4d091	3819	910	2.27	9.42	9.08	-3.61
Sep. 23, 2014	1900	Body	250	5d118	3819	910	10.40	41.80	41.6	-0.48
Sep. 24, 2014	2450	Body	250	908	3819	910	13.20	50.40	52.8	4.76
Oct. 06, 2014	5200	Body	100	1128	3857	1210	7.25	76.20	72.5	-4.86
Oct. 06, 2014	5300	Body	100	1128	3857	1210	7.36	77.70	73.6	-5.28
Oct. 06, 2014	5600	Body	100	1128	3857	1210	7.66	81.50	76.6	-6.01
Oct. 06, 2014	5800	Body	100	1128	3857	1210	7.06	75.90	70.6	-6.98




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2. The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB 648474 D04v01r02, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v05r02 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

11.5 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC HDB Publication 941225 D06v01r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05r02 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

1. Per KDB 447498 D01v05r02, the maximum output power channel is used for SAR testing and for further SAR test reduction.
2. According to October 2013TCB Workshop, for GSM / GPRS / EGPRS, the number of time slots to test for SAR should correspond to the highest source-based time-averaged maximum output power configuration, Considering the possibility of e.g. 3rd party VoIP operation for head and body-worn SAR testing, the EUT was set in GPRS (3Tx slots) for GSM850 band and GPRS (2Tx slots) for GSM1900 band due to their highest frame-average power.
3. For hotspot mode SAR testing, GPRS / EDGE should be evaluated, therefore the EUT was set in GPRS (3Tx slots) for GSM850 band and GPRS (2Tx slots) for GSM1900 band due to their highest frame-average power.

Band GSM850	Burst Average Power (dBm)			Tune-up	Frame-Average Power (dBm)			Tune-up
Tx Channel	128	189	251	Limit	128	189	251	Limit
Frequency (MHz)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8	(dBm)
GSM (GMSK, 1 Tx slot)	31.97	31.99	31.92	33.5	22.97	22.99	22.92	24.5
GPRS (GMSK, 1 Tx slot) – CS1	31.96	31.98	31.91	33.5	22.96	22.98	22.91	24.5
GPRS (GMSK, 2 Tx slots) – CS1	30.07	30.10	29.90	30.5	24.07	24.10	23.90	24.5
GPRS (GMSK, 3 Tx slots) – CS1	28.73	28.88	28.58	29.5	24.47	24.62	24.32	25.24
GPRS (GMSK, 4 Tx slots) – CS1	27.01	27.03	26.82	28.0	24.01	24.03	23.82	25.0
EDGE (8PSK, 1 Tx slot) – MCS5	27.83	26.83	26.69	28.0	18.83	17.83	17.69	19.0
EDGE (8PSK, 2 Tx slots) – MCS5	27.74	26.82	26.60	28.0	21.74	20.82	20.60	22.0
EDGE (8PSK, 3 Tx slots) – MCS5	25.48	24.37	24.07	25.5	21.22	20.11	19.81	21.24
EDGE (8PSK, 4 Tx slots) – MCS5	25.43	24.31	23.96	25.5	22.43	21.31	20.96	22.5
Band GSM1900	Burst Average Power (dBm)			Tune-up	Frame-Average Power (dBm)			Tune-up
Tx Channel	512	661	810	Limit	512	661	810	Limit
Frequency (MHz)	1850.2	1880	1909.8	(dBm)	1850.2	1880	1909.8	(dBm)
GSM (GMSK, 1 Tx slot)	29.13	29.00	28.99	30.5	20.13	20.00	19.99	21.5
GPRS (GMSK, 1 Tx slot) – CS1	29.09	28.98	28.96	30.5	20.09	19.98	19.96	21.5
GPRS (GMSK, 2 Tx slots) – CS1	27.29	26.88	26.82	28.5	21.29	20.88	20.82	22.5
GPRS (GMSK, 3 Tx slots) – CS1	25.29	24.86	24.83	26.5	21.03	20.60	20.57	22.24
GPRS (GMSK, 4 Tx slots) – CS1	24.02	23.82	23.60	25.5	21.02	20.82	20.60	22.5
EDGE (8PSK, 1 Tx slot) – MCS5	25.73	24.33	24.32	26.0	16.73	15.33	15.32	17.0
EDGE (8PSK, 2 Tx slots) – MCS5	25.78	24.31	24.32	26.0	19.78	18.31	18.32	20.0
EDGE (8PSK, 3 Tx slots) – MCS5	24.29	22.76	22.63	24.5	20.03	18.50	18.37	20.24
EDGE (8PSK, 4 Tx slots) – MCS5	24.20	22.75	22.61	24.5	21.20	19.75	19.61	21.5

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCl
 - viii. Confirm that E-TFCl is equal to the target E-TFCl of 75 for sub-test 1, and other subtest's E-TFCl
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCl
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: $\Delta_{ACK}, \Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{HS} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{HS}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Factor to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

Setup Configuration



<WCDMA Conducted Power>

General Note:

1. SAR testing in AMR configuration is not required when the maximum average output of each RF channel for AMR 12.2Kbps is less than 0.25dB higher than that measured in RMC 12.2Kbps
2. Per KDB 941225 D02v02r02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA/DC-HSDPA output power is < 0.25dB higher than RMC, or reported SAR with RMC 12.2kbps setting is $\leq 1.2\text{W/kg}$, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded.
3. MPR values are maximum power reduction allowed, so measured power reduction would always be $\leq 3\text{GPP MPR}$ values. In all cases, the HSPA output power never exceeds the maximum power of Rel. 99.

Band			WCDMA Band V				WCDMA Band II			
Tx Channel			4132	4182	4233	Tune-up Limit (dBm)	9262	9400	9538	Tune-up Limit (dBm)
Frequency (MHz)			826.4	836.4	846.6		1852.4	1880	1907.6	
MPR (dB)	3GPP Rel 99	AMR 12.2Kbps	22.01	22.02	21.98	23.0	21.92	21.89	22.07	22.5
	3GPP Rel 99	RMC 12.2Kbps	22.05	22.04	22.00		21.93	21.90	22.09	
0	3GPP Rel 6	HSDPA Subtest-1	21.51	21.57	21.54	22.0	21.42	21.42	21.41	22.5
0	3GPP Rel 6	HSDPA Subtest-2	21.57	21.71	21.69		21.42	21.57	21.53	
0.5	3GPP Rel 6	HSDPA Subtest-3	21.12	21.20	21.16		20.90	21.04	21.01	
0.5	3GPP Rel 6	HSDPA Subtest-4	21.09	21.19	21.16		20.89	21.03	21.01	
0	3GPP Rel 8	DC-HSDPA Subtest-1	21.44	21.43	21.40	22.0	21.52	21.55	21.62	22.5
0	3GPP Rel 8	DC-HSDPA Subtest-2	21.56	21.52	21.46		21.49	21.56	21.64	
0.5	3GPP Rel 8	DC-HSDPA Subtest-3	21.04	21.02	21.00		21.10	21.11	21.23	
0.5	3GPP Rel 8	DC-HSDPA Subtest-4	21.02	21.01	20.98		21.08	21.04	21.12	
0	3GPP Rel 6	HSUPA Subtest-1	20.76	21.42	21.27	22.0	21.37	21.25	21.60	22.5
2	3GPP Rel 6	HSUPA Subtest-2	20.20	20.07	20.45		20.51	20.56	20.68	
1	3GPP Rel 6	HSUPA Subtest-3	20.19	20.18	20.33		20.56	20.58	20.65	
2	3GPP Rel 6	HSUPA Subtest-4	20.34	20.54	20.92		20.64	20.52	20.72	
0	3GPP Rel 6	HSUPA Subtest-5	21.60	21.60	21.80		21.40	21.50	21.50	



<WLAN Conducted Power>

General Note:

1. For 2.4GHz WLAN SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were selected for SAR evaluation. 802.11g/n HT20 were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of 802.11b mode.
2. For 5GHz WLAN SAR testing, highest average RF output power channel for the lowest data rate for 802.11a were selected for SAR evaluation. 802.11n HT20/n HT40 were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of 802.11a mode.

<2.4GHz WLAN>

WLAN 2.4GHz 802.11b Average Power (dBm)							Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate				
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps	
CH 01	2412	15.48	CH 01	15.39	15.41	15.36	16.0
CH 06	2437	15.17					
CH 11	2462	15.39					

WLAN 2.4GHz 802.11g Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
CH 01	2412	13.35	CH 01	13.24	13.24	13.30	13.29	13.31	13.29	13.31	14.0
CH 06	2437	12.24									
CH 11	2462	12.83									

WLAN 2.4GHz 802.11n HT20 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
		MCS0									
CH 01	2412	11.61	CH 01	11.54	11.57	11.50	11.58	11.55	11.58	11.57	12.5
CH 06	2437	10.50									
CH 11	2462	11.04									



<5GHz WLAN>

WLAN 5GHz 802.11a Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
CH 36	5180	12.20	CH 48	12.28	12.30	12.24	12.21	12.22	12.27	12.32	12.5
CH 40	5200	11.89									
CH 44	5220	12.27									
CH 48	5240	12.37									
CH 52	5260	12.48	CH 64	12.81	12.79	12.70	12.71	12.72	12.72	12.82	13.0
CH 56	5280	12.31									
CH 60	5300	12.11									
CH 64	5320	12.86									
CH 100	5500	11.07	CH 100	10.93	10.93	10.94	10.87	10.92	10.89	10.98	11.5
CH 104	5520	10.61									
CH 108	5540	10.09									
CH 112	5560	10.79									
CH 116	5580	10.70									
CH 132	5660	10.35									
CH 136	5680	10.30									
CH 140	5700	10.61									
CH 149	5745	13.05	CH 149	13.02	13.02	12.98	12.93	12.96	12.97	13.03	13.5
CH 153	5765	12.51									
CH 157	5785	12.81									
CH 161	5805	12.27									
CH 165	5825	12.61									



WLAN 5GHz 802.11n HT20 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	Data Rate MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
CH 36	5180	11.74	CH 48	11.92	11.70	11.81	11.84	11.89	11.85	11.94	12.5
CH 40	5200	11.50									
CH 44	5220	11.88									
CH 48	5240	12.00									
CH 52	5260	12.10	CH 64	12.24	12.02	12.15	12.15	12.20	12.27	12.24	12.5
CH 56	5280	11.91									
CH 60	5300	11.77									
CH 64	5320	12.30									
CH 100	5500	10.57	CH 116	10.60	10.33	10.50	10.47	10.54	10.59	10.61	11.5
CH 104	5520	10.13									
CH 108	5540	10.00									
CH 112	5560	10.27									
CH 116	5580	10.67									
CH 132	5660	10.36									
CH 136	5680	10.28									
CH 140	5700	10.49									
CH 149	5745	12.24	CH 149	12.21	11.96	12.11	12.12	12.16	12.18	12.22	12.5
CH 153	5765	11.98									
CH 157	5785	11.97									
CH 161	5805	11.72									
CH 165	5825	11.76									

WLAN 5GHz 802.11n HT40 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	Data Rate MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
CH 38	5190	10.20	CH 46	10.11	10.09	10.14	10.13	10.21	10.18	10.15	11.5
CH 46	5230	10.35									
CH 54	5270	10.61	CH 62	10.56	10.48	10.55	10.55	10.66	10.57	10.56	11.5
CH 62	5310	10.71									
CH 102	5510	9.10	CH 102	8.92	8.81	8.92	8.91	9.00	8.94	8.89	10.5
CH 110	5550	9.07									
CH 134	5670	9.06									
CH 151	5755	10.68	CH 151	10.44	10.42	10.47	10.46	10.57	10.48	10.51	11.0
CH 159	5795	10.47									


**<Bluetooth Conducted Power>****General Note:**

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The duty factor is selected theoretical 83.3% perform Bluetooth SAR testing.

Bluetooth Burst Average Power (dBm)_DH5					Tune up Limit (dBm)
Channel	Frequency (MHz)	v3.0+EDR			
		1Mbps	2Mbps	3Mbps	
CH 00	2402	12.17	10.25	10.26	12.5
CH 39	2441	12.31	10.47	10.50	
CH 78	2480	12.18	10.26	10.25	

Channel	Frequency (MHz)	Bluetooth Burst Average power (dBm)	Tune up Limit (dBm)
		v4.0 LE	
CH 00	2402	3.19	3.5
CH 19	2440	3.49	
CH 39	2480	3.20	

13. Antenna Location



Top Side
Right Side
Left Side

Bottom Side
Back View

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	120mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	125mm	≤ 25mm	54mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

Referring to KDB 941225 D06 v01r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

14. SAR Test Results

General Note:

- Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- Per KDB 447498 D01v05r02, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
- According to October 2013TCB Workshop, for GSM / GPRS / EGPRS, the number of time slots to test for SAR should correspond to the highest source-based time-averaged maximum output power configuration, Considering the possibility of e.g. 3rd party VoIP operation for head and body-worn SAR testing, the EUT was set in GPRS (3Tx slots) for GSM850 band and GPRS (2Tx slots) for GSM1900 band due to their highest frame-average power.
- For hotspot mode SAR testing, GPRS / EDGE should be evaluated, therefore the EUT was set in GPRS (3Tx slots) for GSM850 band and GPRS (2Tx slots) for GSM1900 band due to their highest frame-average power.
- Per KDB 941225 D02v02r02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA/DC-HSDPA output power is < 0.25dB higher than RMC, or reported SAR with RMC 12.2kbps setting is ≤ 1.2W/kg, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded.
- This device 2.4GHz WLAN supports hotspot operation, and 2.4GHz / 5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.2GHz / 5.3GHz / 5.5GHz supports WiFi Direct (GC only).
- Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
- Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8W/kg.

14.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
#01	GSM850	GPRS (3 Tx slots)	Right Cheek	189	836.4	28.88	29.50	1.153	0.03	0.318	0.367
	GSM850	GPRS (3 Tx slots)	Right Tilted	189	836.4	28.88	29.50	1.153	0.08	0.139	0.160
	GSM850	GPRS (3 Tx slots)	Left Cheek	189	836.4	28.88	29.50	1.153	0.06	0.196	0.226
	GSM850	GPRS (3 Tx slots)	Left Tilted	189	836.4	28.88	29.50	1.153	-0.04	0.136	0.157
	GSM1900	GPRS (2 Tx slots)	Right Cheek	512	1850.2	27.29	28.50	1.321	0.03	0.137	0.181
	GSM1900	GPRS (2 Tx slots)	Right Tilted	512	1850.2	27.29	28.50	1.321	0.03	0.048	0.063
#02	GSM1900	GPRS (2 Tx slots)	Left Cheek	512	1850.2	27.29	28.50	1.321	0.08	0.191	0.252
	GSM1900	GPRS (2 Tx slots)	Left Tilted	512	1850.2	27.29	28.50	1.321	0.01	0.148	0.196

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2K	Right Cheek	4132	826.4	22.05	23.00	1.245	0.05	0.107	0.133
	WCDMA Band V	RMC 12.2K	Right Tilted	4132	826.4	22.05	23.00	1.245	0.01	0.035	0.044
#03	WCDMA Band V	RMC 12.2K	Left Cheek	4132	826.4	22.05	23.00	1.245	0.12	0.154	0.192
	WCDMA Band V	RMC 12.2K	Left Tilted	4132	826.4	22.05	23.00	1.245	0.09	0.092	0.114
	WCDMA Band II	RMC 12.2K	Right Cheek	9538	1907.6	22.09	22.50	1.099	0.12	0.227	0.249
	WCDMA Band II	RMC 12.2K	Right Tilted	9538	1907.6	22.09	22.50	1.099	0.09	0.061	0.067
#04	WCDMA Band II	RMC 12.2K	Left Cheek	9538	1907.6	22.09	22.50	1.099	-0.06	0.247	0.271
	WCDMA Band II	RMC 12.2K	Left Tilted	9538	1907.6	22.09	22.50	1.099	0.04	0.232	0.255

<DTS WLAN SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b 1Mbps	Right Cheek	1	2412	15.48	16.00	1.127	0.1	0.114	0.128
	WLAN 2.4GHz	802.11b 1Mbps	Right Tilted	1	2412	15.48	16.00	1.127	0.05	0.112	0.126
#05	WLAN 2.4GHz	802.11b 1Mbps	Left Cheek	1	2412	15.48	16.00	1.127	0.05	0.197	0.222
	WLAN 2.4GHz	802.11b 1Mbps	Left Tilted	1	2412	15.48	16.00	1.127	0.06	0.157	0.177

<DSS Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	39	2441	12.31	12.50	1.044	0.08	0.055	0.057
	Bluetooth	1Mbps	Right Tilted	39	2441	12.31	12.50	1.044	0.08	0.047	0.049
#06	Bluetooth	1Mbps	Left Cheek	39	2441	12.31	12.50	1.044	0.02	0.117	0.122
	Bluetooth	1Mbps	Left Tilted	39	2441	12.31	12.50	1.044	0.02	0.068	0.071

<NII WLAN SAR>

Plot No.	Band	Mode	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 5.2GHz	802.11a 6Mbps	Right Cheek	48	5240	12.37	12.50	1.030	0.07	0.056	0.058
	WLAN 5.2GHz	802.11a 6Mbps	Right Tilted	48	5240	12.37	12.50	1.030	0.052	0.055	0.057
#07	WLAN 5.2GHz	802.11a 6Mbps	Left Cheek	48	5240	12.37	12.50	1.030	0.05	0.169	0.174
	WLAN 5.2GHz	802.11a 6Mbps	Left Tilted	48	5240	12.37	12.50	1.030	0.03	0.081	0.083
	WLAN 5.3GHz	802.11a 6Mbps	Right Cheek	64	5320	12.86	13.00	1.032	0.038	0.076	0.078
	WLAN 5.3GHz	802.11a 6Mbps	Right Tilted	64	5320	12.86	13.00	1.032	0.14	0.059	0.061
#08	WLAN 5.3GHz	802.11a 6Mbps	Left Cheek	64	5320	12.86	13.00	1.032	0.07	0.189	0.195
	WLAN 5.3GHz	802.11a 6Mbps	Left Tilted	64	5320	12.86	13.00	1.032	0.06	0.118	0.122
	WLAN 5.5GHz	802.11a 6Mbps	Right Cheek	100	5500	11.07	11.5	1.103	0.086	0.026	0.029
	WLAN 5.5GHz	802.11a 6Mbps	Right Tilted	100	5500	11.07	11.5	1.103	0.07	0.014	0.015
#09	WLAN 5.5GHz	802.11a 6Mbps	Left Cheek	100	5500	11.07	11.5	1.103	0.053	0.056	0.062
	WLAN 5.5GHz	802.11a 6Mbps	Left Tilted	100	5500	11.07	11.5	1.103	0.07	0.038	0.042
	WLAN 5.8GHz	802.11a 6Mbps	Right Cheek	149	5745	13.05	13.50	1.108	0.13	0.011	0.012
	WLAN 5.8GHz	802.11a 6Mbps	Right Tilted	149	5745	13.05	13.50	1.108	0.085	0.00844	0.009
#10	WLAN 5.8GHz	802.11a 6Mbps	Left Cheek	149	5745	13.05	13.50	1.108	-0.066	0.016	0.018
	WLAN 5.8GHz	802.11a 6Mbps	Left Tilted	149	5745	13.05	13.50	1.108	0.01	0.00819	0.009

14.2 Hotspot SAR

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	120mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	125mm	≤ 25mm	54mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

Referring to KDB 941225 D06 v01r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (3 Tx slots)	Front	1	189	836.4	28.88	29.50	1.153	0.07	0.465	0.536
	GSM850	GPRS (3 Tx slots)	Back	1	189	836.4	28.88	29.50	1.153	0.08	0.706	0.814
	GSM850	GPRS (3 Tx slots)	Left Side	1	189	836.4	28.88	29.50	1.153	0.05	0.263	0.303
	GSM850	GPRS (3 Tx slots)	Right Side	1	189	836.4	28.88	29.50	1.153	0.06	0.521	0.601
	GSM850	GPRS (3 Tx slots)	Bottom Side	1	189	836.4	28.88	29.50	1.153	0.07	0.282	0.325
	GSM850	GPRS (3 Tx slots)	Back	1	128	824.2	28.73	29.50	1.194	0.06	0.659	0.787
#11	GSM850	GPRS (3 Tx slots)	Back	1	251	848.8	28.58	29.50	1.236	0.02	0.772	0.954
	GSM1900	GPRS (2 Tx slots)	Front	1	512	1850.2	27.29	28.50	1.321	0.05	0.405	0.535
	GSM1900	GPRS (2 Tx slots)	Back	1	512	1850.2	27.29	28.50	1.321	0.03	0.417	0.551
	GSM1900	GPRS (2 Tx slots)	Left Side	1	512	1850.2	27.29	28.50	1.321	0.03	0.127	0.168
	GSM1900	GPRS (2 Tx slots)	Right Side	1	512	1850.2	27.29	28.50	1.321	0.1	0.090	0.119
#12	GSM1900	GPRS (2 Tx slots)	Bottom Side	1	512	1850.2	27.29	28.50	1.321	-0.07	0.481	0.636

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2K	Front	1	4132	826.4	22.05	23.00	1.245	0.08	0.313	0.390
#13	WCDMA Band V	RMC 12.2K	Back	1	4132	826.4	22.05	23.00	1.245	0.03	0.434	0.540
	WCDMA Band V	RMC 12.2K	Left Side	1	4132	826.4	22.05	23.00	1.245	0.05	0.229	0.285
	WCDMA Band V	RMC 12.2K	Right Side	1	4132	826.4	22.05	23.00	1.245	-0.02	0.341	0.424
	WCDMA Band V	RMC 12.2K	Bottom Side	1	4132	826.4	22.05	23.00	1.245	0.08	0.198	0.246
	WCDMA Band II	RMC12.2K	Front	1	9538	1907.6	22.09	22.50	1.099	0.03	0.709	0.779
#14	WCDMA Band II	RMC12.2K	Back	1	9538	1907.6	22.09	22.50	1.099	-0.05	0.718	0.789
	WCDMA Band II	RMC12.2K	Left Side	1	9538	1907.6	22.09	22.50	1.099	0.04	0.149	0.164
	WCDMA Band II	RMC12.2K	Right Side	1	9538	1907.6	22.09	22.50	1.099	0.06	0.124	0.136
	WCDMA Band II	RMC12.2K	Bottom Side	1	9538	1907.6	22.09	22.50	1.099	0.02	0.550	0.604

<DTS WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b 1Mbps	Front	1	1	2412	15.48	16.00	1.127	0.03	0.027	0.030
#15	WLAN 2.4GHz	802.11b 1Mbps	Back	1	1	2412	15.48	16.00	1.127	0.05	0.032	0.036
	WLAN 2.4GHz	802.11b 1Mbps	Right Side	1	1	2412	15.48	16.00	1.127	0.01	0.00853	0.010
	WLAN 2.4GHz	802.11b 1Mbps	Top Side	1	1	2412	15.48	16.00	1.127	0.01	0.027	0.030

<DSS Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	1	39	2441	12.31	12.50	1.044	0.09	0.014	0.015
#16	Bluetooth	1Mbps	Back	1	39	2441	12.31	12.50	1.044	0.02	0.017	0.018
	Bluetooth	1Mbps	Right Side	1	39	2441	12.31	12.50	1.044	0.01	0.00335	0.003
	Bluetooth	1Mbps	Top Side	1	39	2441	12.31	12.50	1.044	0.01	0.012	0.013

<NII WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 5.8GHz	802.11a 6Mbps	Front	1	149	5745	13.05	13.50	1.108	0.12	0.00485	0.005
#17	WLAN 5.8GHz	802.11a 6Mbps	Back	1	149	5745	13.05	13.50	1.108	0.13	0.010	0.011
	WLAN 5.8GHz	802.11a 6Mbps	Right side	1	149	5745	13.05	13.50	1.108	-0.018	0.0058	0.006
	WLAN 5.8GHz	802.11a 6Mbps	Top side	1	149	5745	13.05	13.50	1.108	-0.057	0.00785	0.009

14.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (3 Tx slots)	Front	1	189	836.4	28.88	29.50	1.153	0.07	0.465	0.536
	GSM850	GPRS (3 Tx slots)	Back	1	189	836.4	28.88	29.50	1.153	0.08	0.706	0.814
	GSM850	GPRS (3 Tx slots)	Back	1	128	824.2	28.73	29.50	1.194	0.06	0.659	0.787
#11	GSM850	GPRS (3 Tx slots)	Back	1	251	848.8	28.58	29.50	1.236	0.02	0.772	0.954
	GSM1900	GPRS (2 Tx slots)	Front	1	512	1850.2	27.29	28.50	1.321	0.05	0.405	0.535
#18	GSM1900	GPRS (2 Tx slots)	Back	1	512	1850.2	27.29	28.50	1.321	0.03	0.417	0.551

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA Band V	RMC 12.2K	Front	1	4132	826.4	22.05	23.00	1.245	0.08	0.313	0.390
#13	WCDMA Band V	RMC 12.2K	Back	1	4132	826.4	22.05	23.00	1.245	0.03	0.434	0.540
	WCDMA Band II	RMC12.2K	Front	1	9538	1907.6	22.09	22.50	1.099	0.03	0.709	0.779
#14	WCDMA Band II	RMC12.2K	Back	1	9538	1907.6	22.09	22.50	1.099	-0.05	0.718	0.789

<DTS WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN 2.4GHz	802.11b 1Mbps	Front	1	1	2412	15.48	16.00	1.127	0.03	0.027	0.030
#15	WLAN 2.4GHz	802.11b 1Mbps	Back	1	1	2412	15.48	16.00	1.127	0.05	0.032	0.036

<DSS Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	1	39	2441	12.31	12.50	1.044	0.09	0.014	0.015
#16	Bluetooth	1Mbps	Back	1	39	2441	12.31	12.50	1.044	0.02	0.017	0.018

<NII WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
#19	WLAN 5.2GHz	802.11a 6Mbps	Front	1	48	5240	12.37	12.50	1.030	0.087	0.023	0.024
	WLAN 5.2GHz	802.11a 6Mbps	Back	1	48	5240	12.37	12.50	1.030	0.08	0.012	0.012
#20	WLAN 5.3GHz	802.11a 6Mbps	Front	1	64	5320	12.86	13.00	1.032	-0.078	0.017	0.018
	WLAN 5.3GHz	802.11a 6Mbps	Back	1	64	5320	12.86	13.00	1.032	-0.079	0.0092	0.009
#21	WLAN 5.5GHz	802.11a 6Mbps	Front	1	100	5500	11.07	11.5	1.103	-0.06	0.00969	0.011
	WLAN 5.5GHz	802.11a 6Mbps	Back	1	100	5500	11.07	11.5	1.103	-0.03	0.00846	0.009
	WLAN 5.8GHz	802.11a 6Mbps	Front	1	149	5745	13.05	13.50	1.108	0.12	0.00485	0.005
#17	WLAN 5.8GHz	802.11a 6Mbps	Back	1	149	5745	13.05	13.50	1.108	0.13	0.010	0.011

15. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Head	Body-worn	Hotspot	Note
1.	GSM(voice) + WLAN 2.4GHz(data)	Yes	Yes		
2.	WCDMA(voice) + WLAN 2.4GHz(data)	Yes	Yes		
3.	GSM(voice) + WLAN 5GHz(data)	Yes	Yes		
4.	WCDMA(voice) + WLAN 5GHz(data)	Yes	Yes		
5.	GSM(voice) + Bluetooth(data)	Yes	Yes		
6.	WCDMA(voice) + Bluetooth(data)	Yes	Yes		
7.	GPRS/EDGE(data) + WLAN 2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
8.	WCDMA(data) + WLAN 2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
9.	GPRS/EDGE(data) + WLAN 5.8GHz(data)	Yes	Yes	Yes	WiFi Direct (GC/GO)
10.	WCDMA(data) + WLAN 5.8GHz(data)	Yes	Yes	Yes	WiFi Direct (GC/GO)
11.	GPRS/EDGE(data) + WLAN 5.2/5.3/5.5GHz(data)	Yes	Yes		WiFi Direct (GC only)
12.	WCDMA(data) + WLAN 5.2/5.3/5.5GHz(data)	Yes	Yes		WiFi Direct (GC only)
13.	GPRS/EDGE(data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
14.	WCDMA(data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering

General Note:

- This device supported VoIP in GPRS, EGPRS and WCDMA (e.g. 3rd party VoIP).
- This device 2.4GHz WLAN supports hotspot operation, and 2.4GHz / 5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.2GHz / 5.3GHz / 5.5GHz supports WiFi Direct (GC only).
- WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
- EUT will choose either GSM or WCDMA according to the network signal condition; therefore, they will not operate simultaneously at any moment.
- The reported SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation $< 1.6\text{W/kg}$.
 - $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\min. \text{separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.
- The worst case WLAN reported SAR for each configuration was used for SAR summation, therefore, the following summations represent the absolute worst cases for simultaneous transmission with WLAN.

15.1 Head Exposure Conditions

<WWAN PCE + WLAN DTS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN DTS Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Right Cheek	0.367	0.128	0.50
		Right Tilted	0.160	0.126	0.29
		Left Cheek	0.226	0.222	0.45
		Left Tilted	0.157	0.177	0.33
	GSM1900	Right Cheek	0.181	0.128	0.31
		Right Tilted	0.063	0.126	0.19
		Left Cheek	0.252	0.222	0.47
		Left Tilted	0.196	0.177	0.37
WCDMA	Band V	Right Cheek	0.133	0.128	0.26
		Right Tilted	0.044	0.126	0.17
		Left Cheek	0.192	0.222	0.41
		Left Tilted	0.114	0.177	0.29
	Band II	Right Cheek	0.249	0.128	0.38
		Right Tilted	0.067	0.126	0.19
		Left Cheek	0.271	0.222	0.49
		Left Tilted	0.255	0.177	0.43

<WWAN PCE + WLAN NII>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN NII Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Right Cheek	0.367	0.078	0.45
		Right Tilted	0.160	0.061	0.22
		Left Cheek	0.226	0.195	0.42
		Left Tilted	0.157	0.122	0.28
	GSM1900	Right Cheek	0.181	0.078	0.26
		Right Tilted	0.063	0.061	0.12
		Left Cheek	0.252	0.195	0.45
		Left Tilted	0.196	0.122	0.32
WCDMA	Band V	Right Cheek	0.133	0.078	0.21
		Right Tilted	0.044	0.061	0.11
		Left Cheek	0.192	0.195	0.39
		Left Tilted	0.114	0.122	0.24
	Band II	Right Cheek	0.249	0.078	0.33
		Right Tilted	0.067	0.061	0.13
		Left Cheek	0.271	0.195	0.47
		Left Tilted	0.255	0.122	0.38

<WWAN PCE + Bluetooth DSS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	Bluetooth DSS Max. Bluetooth SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Right Cheek	0.367	0.057	0.42
		Right Tilted	0.160	0.049	0.21
		Left Cheek	0.226	0.122	0.35
		Left Tilted	0.157	0.071	0.23
	GSM1900	Right Cheek	0.181	0.057	0.24
		Right Tilted	0.063	0.049	0.11
		Left Cheek	0.252	0.122	0.37
		Left Tilted	0.196	0.071	0.27
WCDMA	Band V	Right Cheek	0.133	0.057	0.19
		Right Tilted	0.044	0.049	0.09
		Left Cheek	0.192	0.122	0.31
		Left Tilted	0.114	0.071	0.19
	Band II	Right Cheek	0.249	0.057	0.31
		Right Tilted	0.067	0.049	0.12
		Left Cheek	0.271	0.122	0.39
		Left Tilted	0.255	0.071	0.33

15.2 Hotspot Exposure Conditions
<WWAN PCE + WLAN DTS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN DTS Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.536	0.030	0.57
		Back	0.954	0.036	0.99
		Left side	0.303		0.30
		Right side	0.601	0.010	0.61
		Top side		0.030	0.03
		Bottom side	0.325		0.33
	GSM1900	Front	0.535	0.030	0.57
		Back	0.551	0.036	0.59
		Left side	0.168		0.17
		Right side	0.119	0.010	0.13
		Top side		0.030	0.03
		Bottom side	0.636		0.64
WCDMA	Band V	Front	0.390	0.030	0.42
		Back	0.540	0.036	0.58
		Left side	0.285		0.29
		Right side	0.424	0.010	0.43
		Top side		0.030	0.03
		Bottom side	0.246		0.25
	Band II	Front	0.779	0.030	0.81
		Back	0.789	0.036	0.83
		Left side	0.164		0.16
		Right side	0.136	0.010	0.15
		Top side		0.030	0.03
		Bottom side	0.604		0.60

<WWAN PCE + WLAN NII>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN NII Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.536	0.005	0.54
		Back	0.954	0.011	0.97
		Left side	0.303		0.30
		Right side	0.601	0.006	0.61
		Top side		0.009	0.01
		Bottom side	0.325		0.33
	GSM1900	Front	0.535	0.005	0.54
		Back	0.551	0.011	0.56
		Left side	0.168		0.17
		Right side	0.119	0.006	0.13
		Top side		0.009	0.01
		Bottom side	0.636		0.64
WCDMA	Band V	Front	0.390	0.005	0.40
		Back	0.540	0.011	0.55
		Left side	0.285		0.29
		Right side	0.424	0.006	0.43
		Top side		0.009	0.01
		Bottom side	0.246		0.25
	Band II	Front	0.779	0.005	0.78
		Back	0.789	0.011	0.80
		Left side	0.164		0.16
		Right side	0.136	0.006	0.14
		Top side		0.009	0.01
		Bottom side	0.604		0.60

<WWAN PCE + Bluetooth DSS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	Bluetooth DSS Max. Bluetooth SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.536	0.015	0.55
		Back	0.954	0.018	0.97
		Left side	0.303		0.30
		Right side	0.601	0.003	0.60
		Top side		0.013	0.01
		Bottom side	0.325		0.33
	GSM1900	Front	0.535	0.015	0.55
		Back	0.551	0.018	0.57
		Left side	0.168		0.17
		Right side	0.119	0.003	0.12
		Top side		0.013	0.01
		Bottom side	0.636		0.64
WCDMA	Band V	Front	0.390	0.015	0.41
		Back	0.540	0.018	0.56
		Left side	0.285		0.29
		Right side	0.424	0.003	0.43
		Top side		0.013	0.01
		Bottom side	0.246		0.25
	Band II	Front	0.779	0.015	0.79
		Back	0.789	0.018	0.81
		Left side	0.164		0.16
		Right side	0.136	0.003	0.14
		Top side		0.013	0.01
		Bottom side	0.604		0.60

15.3 Body-Worn Accessory Exposure Conditions

<WWAN PCE + WLAN DTS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN DTS Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.536	0.030	0.57
		Back	0.954	0.036	0.99
	GSM1900	Front	0.535	0.030	0.57
		Back	0.551	0.036	0.59
WCDMA	Band V	Front	0.390	0.030	0.42
		Back	0.540	0.036	0.58
	Band II	Front	0.779	0.030	0.81
		Back	0.789	0.036	0.83

<WWAN PCE + WLAN NII>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	WLAN NII Max. WLAN SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.536	0.024	0.56
		Back	0.954	0.012	0.97
	GSM1900	Front	0.535	0.024	0.56
		Back	0.551	0.012	0.56
WCDMA	Band V	Front	0.390	0.024	0.41
		Back	0.540	0.012	0.55
	Band II	Front	0.779	0.024	0.80
		Back	0.789	0.012	0.80

<WWAN PCE + Bluetooth DSS>

WWAN Band		Exposure Position	WWAN PCE Max. WWAN SAR (W/kg)	Bluetooth DSS Max. Bluetooth SAR (W/kg)	Summed SAR (W/kg)
GSM	GSM850	Front	0.536	0.015	0.55
		Back	0.954	0.018	0.97
	GSM1900	Front	0.535	0.015	0.55
		Back	0.551	0.018	0.57
WCDMA	Band V	Front	0.390	0.015	0.41
		Back	0.540	0.018	0.56
	Band II	Front	0.779	0.015	0.79
		Back	0.789	0.018	0.81

Test Engineer : Luke Lu

16. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/ κ ^(b)	1/ $\sqrt{3}$	1/ $\sqrt{6}$	1/ $\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) κ is the coverage factor

Table 16.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %


Table 16.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.55	Normal	1	1	1	± 6.55 %	± 6.55 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Probe Positioning	9.9	Rectangular	√3	1	1	± 5.7 %	± 5.7 %
Max. SAR Eval.	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 12.8 %	± 12.6 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 25.6 %	± 25.2 %

Table 16.3. Uncertainty Budget for frequency range 3 GHz to 6 GHz


17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r03 "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014.
- [6] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations", May 2013
- [7] FCC KDB 447498 D01 v05r02 General RF Exposure Guidance "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014.
- [8] FCC KDB 648474 D04 v01r01r02, "SAR Evaluation Considerations for Wireless Handsets", Dec 2013
- [9] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [10] FCC KDB 941225 D01 v02, "SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA", October 2007
- [11] FCC KDB 941225 D02 v02r02, "SAR Guidance for HSPA, HSPA+, DC-HSDPA and 1x-Advanced", May 2013.
- [12] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008
- [13] FCC KDB 941225 D06 v01r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", May 2013




Appendix A. Plots of System Performance Check

The plots are shown as follows.



Appendix B. Plots of High SAR Measurement

The plots are shown as follows.



Appendix C. DASY Calibration Certificate

The DASY calibration certificates are shown as follows.