



TEST REPORT

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR19-SEF0188 Page (1) of (21)						
1. Client - Name : Samsung Electronics Co., Ltd. - Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea - Date of Receipt : 2019-10-07 2. Use of Report : - 3. Name of Product and Model : Mobile phone / SM-A515F/DS 4. Manufacturer and Country of Origin : SAMSUNG ELECTRONICS VIETNAM CO.,LTD. / Vietnam 5. Date of Test : 2019-11-11 to 2019-11-12 6. Test method used : ANSI C63.4:2014, Class B 7. FCC ID : A3LSMA515F 8. Test Results : Refer to the test result in the test report							
<table border="1"> <tr> <td data-bbox="197 1464 357 1632" rowspan="2">Affirmation</td> <td data-bbox="357 1464 877 1576"> Tested by  </td> <td data-bbox="877 1464 1401 1576"> Technical Manager  </td> </tr> <tr> <td data-bbox="357 1576 877 1632"> Name : Jinwon Kim (Signature) </td> <td data-bbox="877 1576 1401 1632"> Name : Gunsu Park (Signature) </td> </tr> </table>			Affirmation	Tested by 	Technical Manager 	Name : Jinwon Kim (Signature)	Name : Gunsu Park (Signature)
Affirmation	Tested by 	Technical Manager 					
	Name : Jinwon Kim (Signature)	Name : Gunsu Park (Signature)					
2019-11-13 KCTL Inc. As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.							

Contents

1. Applicant information	4
2. Laboratory information.....	5
3. Test system configuration.....	6
3.1 Operation environment.....	6
3.2 Measurement Uncertainty	7
4. Description of EUT	9
4.1 General information.....	9
4.2 Product description.....	10
4.3 Auxiliary equipments	10
4.4 Test configuration	11
4.5 Operating conditions	12
5. Summary of test results	13
5.1 Summary of EMI emission test results.....	13
6. Test results	14
6.1 Conducted Emissions.....	14
6.2 Radiated Emission	17

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR19-SEF0188 Page (4) of (21)	
---	--	---

1. Applicant information

Applicant: Samsung Electronics Co., Ltd.
Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si,
 Gyeonggi-do, 16677, Rep. of Korea
E-mail: yongil89.heo@samsung.com
Contact name: Yongil Heo

Manufacturer: SAMSUNG ELECTRONICS VIETNAM CO.,LTD.
Address: Kcn Yen Binh1, huyen pho Yen Tinh Thai Nguyen Vietnam

KCTL

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SEF0188

Page (5) of (21)

KCTL

2. Laboratory information

Address

KCTL Inc. (Suwon Lab.)

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Telephone Number: 82 31 285 0894

Facsimile Number: 82 505 299 8311

FCC Site Designation No: KR0040

VCCI Registration No.: R-20080, G-20078, C-20059, T-20056

Industry Canada Registration No. : 8035A

KOLAS NO.: KT231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber 10 m (RE)	23.8 °C / 23.4 °C	39.2 % R.H./ 38.7 % R.H.	-
Shielded room(CE)	24.6 °C	40.1 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted Emission measurement (Confidence level about 95 %, $k = 2$)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz:	3.66 dB
	150 kHz ~ 30 MHz:	3.26 dB
Shielded Room (CE#2)	9 kHz ~ 150 kHz:	3.48 dB
	150 kHz ~ 30 MHz:	3.06 dB
Radiated Emission measurement (Confidence level about 95 %, $k = 2$)		
10 m Chamber (4F)	30 MHz ~ 300 MHz	3 m: 5.32 dB
		10 m: 5.32 dB
	300 MHz ~ 1 000 MHz	3 m: 5.46 dB
		10 m: 5.34 dB
	1 GHz ~ 6 GHz	3 m: 6.32 dB
	6 GHz ~ 18 GHz	3 m: 6.66 dB
10 m Chamber (2F)	30 MHz ~ 300 MHz	3 m: 4.98 dB
		10 m: 4.96 dB
	300 MHz ~ 1 000 MHz	3 m: 5.14 dB
		10 m: 5.00 dB
	1 GHz ~ 6 GHz	3 m: 6.34 dB
	6 GHz ~ 18 GHz	3 m: 6.68 dB
3 m Chamber (3F)	30 MHz ~ 300 MHz	3 m: 4.90 dB
	300 MHz ~ 1 000 MHz	3 m: 5.06 dB
	1 GHz ~ 6 GHz	3 m: 6.70 dB
	6 GHz ~ 18 GHz	3 m: 6.60 dB

3.3 Measurement Program

These test items were performed by software programs;

Test item	Measurement Program		Used
Conducted Emission	EP5CE_V 5.4.0(TOYO)		☒
Radiated Emission	2F	EP5RE_V 4.6.0(TOYO)	☒
	4F	EP5RE_V 5.11.10(TOYO)	

KCTL

4. Description of EUT

4.1 General information

Declared Hardware Version	REV1.0
Declared Software Version	A515F.001
IMEI No	352332110063360/01
Operating Band(s)	GSM 850/1900 WCDMA FDD 1/2/4/5/8 LTE FDD 1/2/3/4/5/7/8/12/13/17/20/26/28/66 LTE TDD 38/40/41
Testing Band(s)	GSM 850 WCDMA FDD 5 LTE FDD 5/12/13/17/26


4.2 Product description

Type of product	Mobile phone
Model name (Basic)	SM-A515F/DS
Model name (Variant)	SM-A515F
Difference	SIM Tray difference
Serial no	-
Testing voltage	120 V, 60 Hz
Input/Output rating	Adapter (EP-TA200) Input: AC 100 - 240 V, 50-60 Hz, 0.5 A Output: DC 9.0 V, 1.67 A or DC 5.0 V, 2.0 A Battery: DC 3.4 V
Internal clock frequency	Above 108 MHz
RF Frequency	5 825 MHz
Note	-

4.3 Auxiliary equipments

Type	Model / Part #	S/N	Manufacturer
Adapter(EUT)	EP-TA200	R37M6AS5E41DK3	SAMSUNG
Battery(EUT)	EB-BA515ABY	-	SAMSUNG
USB Cable(EUT)	EP-DR140ABE	-	SAMSUNG
Earphone(EUT)	EHS61ASFBE	-	SAMSUNG
USIM Card	-	-	-
Micro SD Card	-	-	-
Radio Communication Tester	CMU200	108667	R&S
Wideband Radio Communication Tester	CMW500	141780	R&S
Spiral ANT	PSA-75301R/170	406827-0001	COBHAM

4.4 Test configuration



	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT	Power	Adapter(EUT)	USB	0.9	Shield
2		USIM	USIM Card	-	Direct	-
3		Micro SD	Micro SD Card	-	Direct	-
4		Earphone	Earphone(EUT)	-	1.5	Unshield
5	Adapter (EUT)	Power	AC Main	-	Direct	-
6	Wideband Radio Communication Tester or Radio Communication Tester	RF	Spiral ANT	-	3.0	Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
Test #1	Charging(w/TA) + Cellular receiver(GSM850_Center frequency)

Note 1. All cellular RX bands operating below 1 GHz, including GSM, WCDMA and LTE have been investigated with low/mid/high channels and test results are not significantly different.

Note 2. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that Z orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in Z orientation

KCTL

5. Summary of test results

5.1 Summary of EMI emission test results

Applied	Test items	Test method	Result
☒	Conducted Emission	ANSI C63.4:2014, Class B FCC Part 15 Subpart B	Pass
☒	Radiated Emission	ANSI C63.4:2014, Class B FCC Part 15 Subpart B	Pass

KCTL

6. Test results

6.1 Conducted Emissions

Test specification	ANSI C63.4:2014, Class B FCC Part 15 Subpart B		
Testing voltage	120 V, 60 Hz		
Test facility	Shielded room (CE#1)		
Date	2019-11-11		
Temperature (°C)	24.6 °C	Humidity (% R.H.)	40.1 % R.H.
Remarks	Pass		

6.1.1 Limits of conducted emissions measurement

Frequency [MHz]	Class A (dB(μ V))		Class B (dB(μ V))	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79	66	66 ~ 56 ¹⁾	56 ~ 46 ¹⁾
0.5 ~ 5	73	60	56	46
5 ~ 30	73	60	60	50

¹⁾ The limit decreases linearly with the logarithm of frequency

6.1.2 Measurement procedure

The measurements were performed in a shielded room. EUT was setup as shown in photograph and placed on a non-metallic table height of 0.8 m above the reference ground plane. The rear of table was located 0.4 m to the vertical conducted plane. EUT was power through the LISN, which was bonded to the ground plane. The LISN power was filtered. Each EUT power lead, except ground (safety) lead was individually connected through a LISN to input power source. EUT signal cables that hung closer than 0.4 m to the Horizontal metal ground 0.3 m ~ 0.4 m long. The power cord was bundles in the center. All peripheral equipment was powered from a sub LISN. The LISN and ISN were positioned 0.8 m from the EUT. Peak and Average detection were used in preliminary testing and Quasi-peak and Average detections were used at final measurement.

6.1.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
EMI TEST RECEIVER	ESCI	100001	R&S	2020.08.22	☒
TWO-LINE V-NETWORK	ENV216	101358	R&S	2020.10.02	☒
TWO-LINE V-NETWORK	ENV216	101352	R&S	2020.04.05	☐
Wideband Radio Communication Tester	CMW500	141780	R&S	2020.04.18	☒
Radio Communication Tester	CMU200	108667	R&S	2020.01.04	☒

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SEF0188
Page (16) of (21)



6.1.4 Conducted emissions measurement result

AC Main



Final Result

--- N_A Phase ---									
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	QP CAV
1	0.18629	29.1	12.3	10.3	39.4	22.6	64.1	54.1	24.7 31.5
2	0.27462	27.2	10.7	10.0	37.2	20.7	61.0	51.0	23.8 30.3
3	0.54822	20.9	8.8	10.2	31.1	19.0	56.0	46.0	24.9 27.0
4	4.54408	16.2	7.9	10.3	26.5	18.2	56.0	46.0	29.5 27.8
5	9.46741	19.6	11.8	10.6	30.2	22.4	60.0	50.0	29.8 27.6
6	13.36178	18.0	8.1	10.8	28.8	18.9	60.0	50.0	31.2 31.1

--- L1_A Phase ---									
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	QP CAV
1	0.17447	28.5	12.6	10.4	38.9	23.0	64.7	54.7	25.8 31.7
2	0.21732	27.8	11.3	10.1	37.9	21.4	62.9	52.9	25.0 31.5
3	0.50141	21.6	7.3	10.2	31.8	17.5	56.0	46.0	24.2 28.5
4	4.48395	18.3	10.9	10.3	28.6	21.2	56.0	46.0	27.4 24.8
5	9.59977	18.8	10.4	10.7	29.5	21.1	60.0	50.0	30.5 28.9
6	13.02896	18.2	11.1	10.9	29.1	22.0	60.0	50.0	30.9 28.0

6.2 Radiated Emission

Test specification		ANSI C63.4:2014, Class B FCC Part 15 Subpart B		
Testing voltage		120 V, 60 Hz		
Test facility		10 m Chamber (4F)		
Test distance		3 m		
Date		2019-11-12		
30 MHz ~ 1000 MHz	Temperature (°C)	23.8 °C	Humidity (% R.H.)	39.2 % R.H.
1 GHz ~ 30 GHz		23.4 °C		38.7 % R.H.
Remarks		Pass		

6.2.1 Limits of radiated emission measurement

Frequency [MHz]	Class A (dB(μ V/m)) @ 10 m	Class B (dB(μ V/m)) @ 3 m
30-88	39	40
88-216	43.5	43.5
216-960	46.4	46
Above 960	49.5	54

Note- Alternative standard: CISPR, Pub. 22

6.2.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane.

Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.2.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
EMI TEST RECEIVER	ESR7	101078	R&S	2020.08.22	☒
Bilog Antenna	CBL 6112D	37876	TESEQ	2020.07.20	☒
AMPLIFIER	310N	293004	SONOMA	2020.08.22	☒
ATTENUATOR	8491B	MY39270292	AGILENT	-	☒
Antenna Mast	MA4640-XP-ET	-	Innco Systems	-	☒
Turn Table	TT 3.0-3t	-	MATURO	-	☒
AMPLIFIER	JS44-18004000-33-8P	2000996	L-3Narda-MITEQ	2020.01.28	☒
Horn antenna	3116	00086635	ETS-LINDGREN	2020.05.09	☒
DOUBLE RIDGED HORN ANTENNA	3117-PA	00161083	ETS-LINDGREN	2020.09.18	☒
Spectrum Analyzer	FSV40	100988	R&S	2020.01.04	☒
Wideband Radio Communication Tester	CMW500	141780	R&S	2020.04.18	☒
Radio Communication Tester	CMU200	108667	R&S	2020.01.04	☒

6.2.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 6 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G = Amplifier Gain

6 dB Att = 6 dB Attenuator

If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 6 dB, A.G 35 dB

The result is $30 + 12 + 5 + 6 - 35 = 18 \text{ dB } (\mu\text{V/m})$

Bilog Antenna and ATTENUATOR (6 dB) were calibrated together.

AV = CAV : Abbreviation of CISPR Average

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SEF0188
Page (19) of (21)

KCTL

6.2.5 Radiated emission measurement result

30 MHz ~ 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	37.154	V	31.7	-8.6	23.1	40.0	16.9	105.0	166.0
2	44.550	V	33.2	-12.4	20.8	40.0	19.2	120.0	127.0
3	65.890	H	32.4	-16.5	15.9	40.0	24.1	100.0	13.0
4	74.256	V	32.3	-16.0	16.3	40.0	23.7	290.0	259.0
5	132.941	V	25.5	-9.4	16.1	43.5	27.4	215.0	163.0
6	478.019	H	22.6	0.5	23.1	46.0	22.9	397.0	9.0
7	621.821	V	21.0	3.7	24.7	46.0	21.3	179.0	91.0
8	900.333	H	20.3	9.1	29.4	46.0	16.6	109.0	317.0


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SEF0188
Page (20) of (21)

KCTL

1 GHz ~ 18 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	10556.030	H	43.7	32.0	0.8	44.5	32.8	74.0	54.0	29.5	21.2	249.0	349.0
2	11601.860	H	47.2	35.5	0.3	47.5	35.8	74.0	54.0	26.5	18.2	152.0	40.0
3	12061.590	V	45.5	33.9	0.5	46.0	34.4	74.0	54.0	28.0	19.6	152.0	65.0
4	14864.260	V	46.0	34.2	2.0	48.0	36.2	74.0	54.0	26.0	17.8	239.0	264.0
5	15775.100	H	44.6	32.9	3.3	47.9	36.2	74.0	54.0	26.1	17.8	200.0	265.0
6	17807.390	V	38.5	26.9	8.7	47.2	35.6	74.0	54.0	26.8	18.4	100.1	190.0

KCTL


KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SEF0188
Page (21) of (21)



18 GHz ~ 30 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]
1	24922.550	V	41.5	26.5	9.4	50.9	35.9	74.0	54.0	23.1	18.1	118.0	171.0
2	25394.170	V	40.8	30.1	10.5	51.3	40.6	74.0	54.0	22.7	13.4	189.0	144.0
3	25948.000	H	38.6	22.4	12.2	50.8	34.6	74.0	54.0	23.2	19.4	379.0	219.0
4	26701.640	H	40.9	25.8	12.2	53.1	38.0	74.0	54.0	20.9	16.0	396.0	94.0
5	27026.850	H	40.2	24.7	11.8	52.0	36.5	74.0	54.0	22.0	17.5	228.0	112.0
6	27626.880	V	38.2	23.8	13.2	51.4	37.0	74.0	54.0	22.6	17.0	110.0	239.0



This test report shall not be reproduced, except in full, without the written approval.