

**MEASUREMENT REPORT**
GSM / GPRS / EDGE / WCDMA**Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

9/26-10/26/2017

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1709250255-02.A3L

FCC ID:

A3LSMA530N

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-A530N

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

22 & 24

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 1 of 59

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location.....	4
1.3	Test Facility / Accreditations.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	Equipment Description	5
2.2	Device Capabilities.....	5
2.3	Test Configuration	5
2.4	EMI Suppression Device(s)/Modifications	5
3.0	DESCRIPTION OF TESTS	6
3.1	Evaluation Procedure	6
3.2	Cellular - Base Frequency Blocks	6
3.3	Cellular - Mobile Frequency Blocks	6
3.4	PCS - Base Frequency Blocks	6
3.5	PCS - Mobile Frequency Blocks.....	7
3.6	Radiated Measurements	7
4.0	MEASUREMENT UNCERTAINTY	8
5.0	TEST EQUIPMENT CALIBRATION DATA	9
6.0	SAMPLE CALCULATIONS	10
7.0	TEST RESULTS.....	11
7.1	Summary.....	11
7.2	Occupied Bandwidth	12
7.3	Spurious and Harmonic Emissions at Antenna Terminal	15
7.4	Band Edge Emissions at Antenna Terminal	31
7.5	Peak-Average Ratio	37
7.6	Radiated Power (ERP/EIRP).....	40
7.7	Radiated Spurious Emissions Measurements	44
7.8	Frequency Stability / Temperature Variation	52
8.0	CONCLUSION.....	59

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 2 of 59



MEASUREMENT REPORT

GSM / GPRS / EDGE / WCDMA



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)	
WCDMA850	22H	826.4 - 846.6	0.057	17.59	0.094	19.74	4M16F9W
GPRS1900	24E	1850.2 - 1909.8			0.863	29.36	248KGXW
EDGE1900	24E	1850.2 - 1909.8			0.243	23.85	246KG7W
WCDMA1900	24E	1852.4 - 1907.6			0.236	23.72	4M15F9W

EUT Overview

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 3 of 59

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 4 of 59

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA530N**. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

Test Device Serial No.: 18736, 18801, 18785

2.2 Device Capabilities

This device contains the following capabilities:

1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 5 of 59

3.0 DESCRIPTION OF TESTS


3.1 Evaluation Procedure

The measurement procedures described in the “Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards” (ANSI/TIA-603-E-2016) and “Measurement Guidance for Certification of Licensed Digital Transmitters” (KDB 971168 D01 v03) were used in the measurement of the EUT.

Deviation from Measurement Procedure.....None

3.2 Cellular - Base Frequency Blocks

§22.905



BLOCK 1: 869 – 880 MHz (A* Low + A)


BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.3 Cellular - Mobile Frequency Blocks

§22.905



BLOCK 1: 824 – 835 MHz (A* Low + A)


BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

3.4 PCS - Base Frequency Blocks

§24.229



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)

BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)


BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 6 of 59

3.5 PCS - Mobile Frequency Blocks

§24.229



3.6 Radiated Measurements

§2.1053 §22.913(a.2) §22.917(a) §24.232(c) §24.238(a)

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high Styrodur Plastic Test Table is placed on top of the turntable. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d [\text{dBm}] = P_g [\text{dBm}] - \text{cable loss} [\text{dB}] + \text{antenna gain} [\text{dBd/dBi}]$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g [\text{dBm}] - \text{cable loss} [\text{dB}]$.

Radiated power and radiated spurious emission levels are investigated with the receive antenna horizontally and vertically polarized per ANSI/TIA-603-E-2016.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 7 of 59

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 8 of 59

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx1	Licensed Transmitter Cable Set	1/6/2017	Annual	1/6/2018	LTx1
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/21/2017	Annual	6/21/2018	RE1
Agilent	N9030A	PXA Signal Analyzer (44GHz)	3/27/2017	Annual	3/27/2018	MY52350166
COM-Power	AL-130R	Active Loop Antenna	6/5/2017	Annual	6/5/2018	121085
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	6/21/2017	Annual	6/21/2018	441119
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/23/2016	Biennial	8/23/2018	135427
Espec	ESX-2CA	Environmental Chamber	4/11/2017	Annual	4/11/2018	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	4/26/2016	Biennial	4/26/2018	128337
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/24/2017	Annual	3/24/2018	11401010036
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	CMU200	Base Station Simulator	4/11/2017	Annual	4/11/2018	836371/0079
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/31/2017	Annual	7/31/2018	100348
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102135
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102133
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Rx	3/30/2016	Biennial	3/30/2018	9105-2404
Schwarzbeck	UHA 9105	Dipole Antenna (400 - 1GHz) Tx	3/30/2016	Biennial	3/30/2018	9105-2403
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 5-1. Test Equipment

Notes:

Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMA530N	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset	Page 9 of 59

6.0 SAMPLE CALCULATIONS

GPRS Emission Designator

Emission Designator = 250KGXW

GPRS BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250 kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data)

Spurious Radiated Emission

Example: Spurious emission at 3700.40 MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.50 dBm so this harmonic was 25.50 dBm - (-24.80) = 50.3 dBc.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 10 of 59

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA530N
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): GSM / GPRS / EDGE / WCDMA

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 22.917(a) 24.238(a)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Conducted Band Edge / Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions		PASS	Sections 7.3, 7.4
24.232(d)	RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	RSS-132(5.4) RSS-133(4.1) RSS-139(4.1)	Transmitter Conducted Output Power	N/A		PASS	RF Exposure Report
2.1055 22.355 24.235	RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24)		PASS	Section 7.8
22.913(a.2)	RSS-132(5.4)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 7.6
24.232(c)	RSS-133(6.4)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 7.6
2.1053 22.917(a) 24.238(a)	RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)	Radiated Spurious Emissions	$> 43 + \log_{10}(P[\text{Watts}])$ for all out-of-band emissions		PASS	Section 7.7

Table 7-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "2G/3G Automation," Version 3.9.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 11 of 59

7.2 Occupied Bandwidth

§2.1049 RSS-Gen (4.6.1) RSS-133(2.3) RSS-139(2.3)

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-1. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 12 of 59




Plot 7-1. Occupied Bandwidth Plot (PCS GPRS Mode)




Plot 7-2. Occupied Bandwidth Plot (EDGE1900 Mode)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 13 of 59



Plot 7-3. Occupied Bandwidth Plot (Cellular WCDMA Mode)



Plot 7-4. Occupied Bandwidth Plot (PCS WCDMA Mode)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 14 of 59

7.3 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{[Watts]})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03 – Section 6.0

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 10GHz for Cell, 20GHz for AWS, 20GHz for PCS (separated into at least two plots per channel)
2. Detector = RMS
3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
4. Sweep time = auto couple
5. The trace was allowed to stabilize
6. Please see test notes below for RBW and VBW settings

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-2. Test Instrument & Measurement Setup

Test Notes


Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 1MHz, and 100 kHz or greater for Part 22 and RSS-132 measurements below 1GHz. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 15 of 59

PCS GPRS Mode




Plot 7-5. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-6. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 16 of 59




Plot 7-7. Conducted Spurious Plot (PCS GPRS Mode - Low Channel)




Plot 7-8. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 17 of 59




Plot 7-9. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)




Plot 7-10. Conducted Spurious Plot (PCS GPRS Mode - Mid Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 18 of 59



Plot 7-11. Conducted Spurious Plot (PCS GPRS Mode - High Channel)




Plot 7-12. Conducted Spurious Plot (PCS GPRS Mode - High Channel)


FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 19 of 59

FCC ID: A3LSMA530N	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset	Page 20 of 59

Cellular WCDMA Mode




Plot 7-14. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-15. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 21 of 59




Plot 7-16. Conducted Spurious Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-17. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 22 of 59




Plot 7-18. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)




Plot 7-19. Conducted Spurious Plot (Cellular WCDMA Mode - Mid Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 23 of 59




Plot 7-20. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)



Plot 7-21. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)


FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 24 of 59




Plot 7-22. Conducted Spurious Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 25 of 59

PCS WCDMA Mode




Plot 7-23. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-24. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 26 of 59




Plot 7-25. Conducted Spurious Plot (PCS WCDMA Mode - Low Channel)




Plot 7-26. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 27 of 59



Plot 7-27. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)




Plot 7-28. Conducted Spurious Plot (PCS WCDMA Mode - Mid Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 28 of 59




Plot 7-29. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)



Plot 7-30. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 29 of 59



Plot 7-31. Conducted Spurious Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 30 of 59

7.4 Band Edge Emissions at Antenna Terminal

§2.1051 §22.917(a) §24.238(a) RSS-132(5.5) RSS-133(6.5) RSS-139(6.6)

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P_{\text{Watts}})$, where P is the transmitter power in Watts.

Test Procedure Used

KDB 971168 D01 v03 – Section 6.0

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW $\geq$ 1% of the emission bandwidth
4. VBW $\geq$ 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq$ 2 x Span/RBW
7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-3. Test Instrument & Measurement Setup

Test Notes


Per 22.917(b) 24.238(b) and RSS-132(5.5) RSS-133(6.5) RSS-139(6.5) in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 31 of 59

PCS GPRS Mode




Plot 7-32. Band Edge Plot (PCS GPRS Mode - Low Channel)




Plot 7-33. 4MHz Span Plot (PCS GPRS Mode - Low Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 32 of 59



Plot 7-34. Band Edge Plot (PCS GPRS Mode - High Channel)



Plot 7-35. 4MHz Span Plot (PCS GPRS Mode - High Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 33 of 59

Cellular WCDMA Mode



Plot 7-36. Band Edge Plot (Cellular WCDMA Mode - Low Channel)




Plot 7-37. Band Edge Plot (Cellular WCDMA Mode - High Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 34 of 59

PCS WCDMA Mode



Plot 7-38. Band Edge Plot (PCS WCDMA Mode - Low Channel)




Plot 7-39. 4MHz Span Plot (PCS WCDMA Mode - Low Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 35 of 59



Plot 7-40. Band Edge Plot (PCS WCDMA Mode - High Channel)



Plot 7-41. 4MHz Span Plot (PCS WCDMA Mode - High Channel)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 36 of 59

7.5 Peak-Average Ratio

§24.232(d) RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)

Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

Test Procedure Used

KDB 971168 D01 v03 – Section 5.7.1

Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 37 of 59




Plot 7-42. Peak-Average Ratio Plot (PCS GPRS Mode)



Plot 7-43. Peak-Average Ratio Plot (EDGE1900 Mode)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 38 of 59



Plot 7-44. Peak-Average Ratio Plot (PCS WCDMA Mode)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 39 of 59

7.6 Radiated Power (ERP/EIRP)

§22.913(a)(2) 24.232(c) RSS-132(5.4) RSS-133(6.4) RSS-139(6.5)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically and horizontally polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03 – Section 5.2.1

ANSI/TIA-603-E-2016 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
5. No. of sweep points $\geq 2 \times$ span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto". Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 40 of 59

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Radiated Test Setup <1GHz




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 41 of 59

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 42 of 59

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	ERP [dBm]	ERP [Watts]	ERP Limit [dBm]	Margin [dB]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
826.40	WCDMA850	H	150	287	17.44	1.50	16.79	0.048	38.45	-21.66	18.94	0.078	40.61	-21.67
836.60	WCDMA850	H	150	288	17.96	1.50	17.31	0.054	38.45	-21.14	19.46	0.088	40.61	-21.15
846.60	WCDMA850	H	150	293	18.24	1.50	17.59	0.057	38.45	-20.86	19.74	0.094	40.61	-20.87
846.60	WCDMA850	V	150	350	17.51	1.50	16.86	0.049	38.45	-21.59	19.01	0.080	40.61	-21.60

Table 7-2. ERP/EIRP (Cellular WCDMA)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1850.20	GPRS1900	V	150	37	23.20	4.79	27.98	0.629	33.01	-5.03
1880.00	GPRS1900	V	150	41	23.26	4.84	28.10	0.646	33.01	-4.91
1909.80	GPRS1900	V	150	42	24.50	4.86	29.36	0.863	33.01	-3.65
1909.80	GPRS1900	H	150	352	23.67	4.68	28.36	0.685	33.01	-4.66
1909.80	EDGE1900	V	150	41	18.99	4.86	23.85	0.243	33.01	-9.16

Table 7-3. EIRP (PCS GPRS)

Frequency [MHz]	Mode	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Substitute Level [dBm]	Ant. Gain [dBi]	EIRP [dBm]	EIRP [Watts]	EIRP Limit [dBm]	Margin [dB]
1852.40	WCDMA1900	H	150	351	18.66	4.81	23.47	0.222	33.01	-9.54
1880.00	WCDMA1900	H	150	349	17.39	4.74	22.13	0.163	33.01	-10.88
1907.60	WCDMA1900	H	150	350	19.04	4.68	23.72	0.236	33.01	-9.29
1907.60	WCDMA1900	V	150	269	16.54	4.86	21.40	0.138	33.01	-11.61

Table 7-4. EIRP (PCS WCDMA)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset	Page 43 of 59	

7.7 Radiated Spurious Emissions Measurements

§2.1053 §22.917(a) 24.238(a) RSS-132(5.5) RSS-133(5.5) RSS-139(6.6)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-E-2016 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

Test Procedures Used

KDB 971168 D01 v03 – Section 5.8

ANSI/TIA-603-E-2016 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $\geq 2 \times$ span / RBW
5. Detector = RMS
6. Trace mode = Average (Max Hold for pulsed emissions)
7. The trace was allowed to stabilize

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 44 of 59

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup

Test Notes

- 1) This device employs GSM, GPRS, and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GPRS mode while transmitting with one slot active.
- 2) This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA, and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1."
- 3) This unit was tested with its standard battery.
- 4) The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case setup is reported in the tables below.
- 5) The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported.
- 6) Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
- 7) The "-" shown in the following RSE tables are used to denote a noise floor measurement.

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 45 of 59

Cellular WCDMA Mode

OPERATING FREQUENCY: 826.40 MHz
 CHANNEL: 4132
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1652.80	H	131	207	-53.63	8.85	-44.79	-31.8
2479.20	H	117	110	-72.23	9.69	-62.54	-49.5
3305.60	H	-	-	-69.50	9.53	-59.97	-47.0

Table 7-5. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 4183
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1673.20	H	128	181	-51.72	8.85	-42.88	-29.9
2509.80	H	256	158	-72.04	9.78	-62.27	-49.3
3346.40	H	-	-	-69.77	9.67	-60.11	-47.1

Table 7-6. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 46 of 59

OPERATING FREQUENCY: 846.60 MHz
 CHANNEL: 4233
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
1693.20	H	110	220	-52.05	8.85	-43.20	-30.2
2539.80	H	-	-	-73.03	9.75	-63.28	-50.3
3386.40	H	-	-	-69.36	9.80	-59.57	-46.6

Table 7-7. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 47 of 59

PCS GPRS Mode

OPERATING FREQUENCY: 1850.20 MHz
CHANNEL: 512
MODULATION SIGNAL: GPRS (GMSK)
DISTANCE: 3 meters
LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3700.40	H	157	4	-62.87	9.53	-53.34	-40.3
5550.60	H	113	361	-60.11	11.01	-49.10	-36.1
7400.80	H	144	312	-47.53	10.94	-36.59	-23.6
9251.00	H	117	7	-53.51	11.52	-41.99	-29.0
11101.20	H	135	2	-55.71	12.81	-42.90	-29.9
12951.40	H	-	-	-55.29	13.37	-41.91	-28.9

Table 7-8. Radiated Spurious Data (PCS GPRS Mode – Ch. 512)

OPERATING FREQUENCY: 1880.00 MHz
CHANNEL: 661
MODULATION SIGNAL: GPRS (GMSK)
DISTANCE: 3 meters
LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	191	339	-61.26	9.39	-51.88	-38.9
5640.00	H	130	355	-61.67	11.22	-50.45	-37.4
7520.00	H	140	297	-48.72	11.10	-37.62	-24.6
9400.00	H	130	18	-54.80	11.54	-43.26	-30.3
11280.00	H	129	1	-54.21	12.76	-41.44	-28.4
13160.00	H	-	-	-53.72	13.05	-40.67	-27.7

Table 7-9. Radiated Spurious Data (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 48 of 59

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MODULATION SIGNAL: GPRS (GMSK)
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3819.60	H	-	-	-66.52	9.32	-57.20	-44.2
5729.40	H	-	-	-64.58	11.37	-53.21	-40.2
7639.20	H	139	344	-48.68	11.33	-37.35	-24.3
9549.00	H	134	10	-52.28	11.78	-40.50	-27.5
11458.80	H	123	255	-55.22	12.69	-42.53	-29.5
13368.60	H	-	-	-52.66	12.64	-40.02	-27.0

Table 7-10. Radiated Spurious Data (PCS GPRS Mode – Ch. 810)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 49 of 59

PCS WCDMA Mode

OPERATING FREQUENCY: 1852.40 MHz
 CHANNEL: 9262
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3704.80	H	173	308	-64.72	9.72	-55.00	-42.0
5557.20	H	150	37	-61.14	10.99	-50.16	-37.2
7409.60	H	160	46	-55.19	10.79	-44.40	-31.4
9262.00	H	123	348	-63.31	12.28	-51.03	-38.0
11114.40	H	146	8	-62.02	12.95	-49.07	-36.1
12966.80	H	-	-	-60.95	12.70	-48.25	-35.2

Table 7-11. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 9400
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3760.00	H	178	304	-66.26	9.50	-56.76	-43.8
5640.00	H	146	328	-64.30	11.16	-53.14	-40.1
7520.00	H	160	50	-58.51	11.03	-47.48	-34.5
9400.00	H	-	-	-62.82	12.19	-50.63	-37.6
11280.00	H	146	26	-62.70	13.15	-49.55	-36.5
13160.00	H	-	-	-60.76	12.88	-47.88	-34.9

Table 7-12. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 50 of 59

OPERATING FREQUENCY: 1907.60 MHz
 CHANNEL: 9538
 MODULATION SIGNAL: WCDMA
 DISTANCE: 3 meters
 LIMIT: -13 dBm

Frequency [MHz]	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Level at Antenna Terminals [dBm]	Substitute Antenna Gain [dBi]	Spurious Emission Level [dBm]	Margin [dB]
3815.20	H	154	300	-65.08	9.30	-55.78	-42.8
5722.80	H	141	327	-60.46	11.33	-49.13	-36.1
7630.40	H	169	358	-59.71	11.26	-48.45	-35.5
9538.00	H	137	59	-62.70	12.23	-50.47	-37.5
11445.60	H	-	-	-63.19	13.26	-49.93	-36.9

Table 7-13. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 51 of 59

7.8 Frequency Stability / Temperature Variation

§2.1055 §22.355 §24.235 RSS-132(5.3) RSS-133(6.3) RSS-139(6.4)

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-E-2016. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, RSS-132 and RSS-133, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 and RSS-139, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-E-2016

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Test Setup

The EUT was connected via an RF cable to a spectrum analyzer with the EUT placed inside an environmental chamber.

Test Notes

None

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 52 of 59

Frequency Stability / Temperature Variation

§2.1055 §22.355 RSS-132(5.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 4183

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	836,599,919	-81	-0.0000097
100 %		- 30	836,600,070	70	0.0000084
100 %		- 20	836,600,093	93	0.0000111
100 %		- 10	836,599,990	-10	-0.0000012
100 %		0	836,599,809	-191	-0.0000228
100 %		+ 10	836,599,926	-74	-0.0000088
100 %		+ 20	836,599,798	-202	-0.0000241
100 %		+ 30	836,600,071	71	0.0000085
100 %		+ 40	836,600,190	190	0.0000227
100 %		+ 50	836,599,945	-55	-0.0000066
BATT. ENDPOINT	3.45	+ 20	836,599,813	-187	-0.0000224

Table 7-14. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 53 of 59

Frequency Stability / Temperature Variation
§2.1055 §22.355 RSS-132(5.3)




Figure 7-8. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 54 of 59

Frequency Stability / Temperature Variation

§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,131	131	0.0000070
100 %		- 30	1,880,000,186	186	0.0000099
100 %		- 20	1,880,000,240	240	0.0000128
100 %		- 10	1,879,999,888	-112	-0.0000060
100 %		0	1,879,999,972	-28	-0.0000015
100 %		+ 10	1,880,000,115	115	0.0000061
100 %		+ 20	1,880,000,031	31	0.0000016
100 %		+ 30	1,879,999,953	-47	-0.0000025
100 %		+ 40	1,879,999,956	-44	-0.0000023
100 %		+ 50	1,880,000,044	44	0.0000023
BATT. ENDPOINT	3.45	+ 20	1,879,999,651	-349	-0.0000186

Table 7-15. Frequency Stability Data (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 55 of 59

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)




Figure 7-9. Frequency Stability Graph (PCS GPRS Mode – Ch. 661)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 56 of 59

Frequency Stability / Temperature Variation

§2.1055 §24.235 RSS-133(6.4)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 9400

REFERENCE VOLTAGE: 3.85 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.85	+ 20 (Ref)	1,880,000,074	74	0.0000039
100 %		- 30	1,879,999,725	-275	-0.0000146
100 %		- 20	1,879,999,954	-46	-0.0000024
100 %		- 10	1,880,000,055	55	0.0000029
100 %		0	1,879,999,893	-107	-0.0000057
100 %		+ 10	1,880,000,094	94	0.0000050
100 %		+ 20	1,879,999,994	-6	-0.0000003
100 %		+ 30	1,880,000,015	15	0.0000008
100 %		+ 40	1,880,000,196	196	0.0000104
100 %		+ 50	1,879,999,536	-464	-0.0000247
BATT. ENDPOINT	3.45	+ 20	1,879,999,851	-149	-0.0000079

Table 7-16. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 57 of 59

Frequency Stability / Temperature Variation
§2.1055 §24.235 RSS-133(6.4)




Figure 7-10. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)

FCC ID: A3LSMA530N	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 58 of 59

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA530N** complies with all the requirements of Part 22 & 24 of the FCC Rules.

FCC ID: A3LSMA530N		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1709250255-02.A3L	Test Dates: 9/26-10/26/2017	EUT Type: Portable Handset		Page 59 of 59