



MEASUREMENT REPORT

FCC PART 15.407 / ISSED RSS-247 UNII 802.11a/n/ac

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

9/26 – 10/26, 12/11/2017

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1711240303-06-R1.A3L

FCC ID:

A3LSMA530W

IC:

649E-SMA530W

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model/HVIN:

SM-A530W

EUT Type:

Portable Handset

Frequency Range:

5180 – 5825MHz

FCC Classification:

Unlicensed National Information Infrastructure (UNII)

FCC Rule Part(s):

Part 15 Subpart E (15.407)

ISED Specification:

RSS-247 Issue 2


Test Procedure(s):

ANSI C63.10-2013, KDB 789033 D02 v02r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 789033 D02 v02r01. Test results reported herein relate only to the item(s) tested.

The revised Test Report (S/N: 1M1711240303-06-R1.A3L) supersedes and replaces the previously issued test report (S/N: 1M1711240303-06.A3L) on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President




FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION)		 Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 1 of 90


TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	PCTEST Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Test Configuration	6
2.4	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions	8
3.4	Environmental Conditions	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS	12
7.1	Summary	12
7.2	26dB Bandwidth Measurement – 802.11a/n/ac	13
7.3	6dB Bandwidth Measurement – 802.11a/n/ac	30
7.4	UNII Output Power Measurement – 802.11a/n/ac	36
7.5	Maximum Power Spectral Density – 802.11a/n/ac	38
7.6	Radiated Spurious Emission Measurements – Above 1GHz	60
7.7.1	Radiated Spurious Emission Measurements	63
7.7.2	Radiated Band Edge Measurements (20MHz BW)	74
7.7.3	Radiated Band Edge Measurements (40MHz BW)	75
7.7.4	Radiated Band Edge Measurements (80MHz BW)	78
7.7	Radiated Spurious Emissions Measurements – Below 1GHz	80
7.8	Line-Conducted Test Data	84
8.0	CONCLUSION	90

FCC ID: A3LSMA530W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 2 of 90	



MEASUREMENT REPORT



UNII Band	Channel Bandwidth (MHz)	Tx Frequency (MHz)	Conducted Power	
			Max. Power (mW)	Max. Power (dBm)
1	20	5180 - 5240	23.933	13.79
2A		5260 - 5320	24.717	13.93
2C		5500 - 5580	21.878	13.40
2C		5660 - 5720	22.856	13.59
3		5745 - 5825	24.889	13.96
1	40	5190 - 5230	22.909	13.60
2A		5270 - 5310	22.803	13.58
2C		5510 - 5550	21.827	13.39
2C		5670 - 5710	22.909	13.60
3		5755 - 5795	25.003	13.98
1	80	5210	5.070	7.05
2A		5290	3.055	4.85
2C		5530	5.395	7.32
2C		5690	17.498	12.43
3		5775	16.749	12.24

EUT Overview

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 3 of 90

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 4 of 90

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA530W**. The test data contained in this report pertains only to the emissions due to the EUT's UNII transmitter.

Test Device Serial No.: 18793, 18751, 18769, 18801, 39099, 76233, 07349

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
:	:	:	:	:	:	:	:
42	5210	56	5280	116	5580	157	5785
:	:	:	:	:	:	:	:
48	5240	64	5320	144	5720	165	5825

Table 2-1. 802.11a / 802.11n / 802.11ac (20MHz) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
:	:	:	:	:	:	:	:
46	5230	62	5310	110	5550	159	5795
				:	:		
				142	5710		

Table 2-2. 802.11n / 802.11ac (40MHz BW) Frequency / Channel Operations

Band 1		Band 2A		Band 2C		Band 3	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
				:	:		
				138	5690		

Table 2-3. 802.11ac (80MHz BW) Frequency / Channel Operations

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 5 of 90

Notes:

- 5GHz NII operation is possible in 20MHz, and 40MHz, and 80MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section B)2)b) of ANSI C63.10-2013 and KDB 789033 D02 v02r01. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Maximum Achievable Duty Cycles		
802.11 Mode/Band		Duty Cycle [%]
		ANT1
5GHz	a	98.9
	n (HT20)	98.8
	ac (HT20)	98.8
	n (HT40)	96.3
	ac (HT40)	98.2
	ac (HT80)	97.3

Table 2-4. Measured Duty Cycles

Data Rate(s) Tested: 6, 9, 12, 18, 24, 36, 48, 54Mbps (802.11a)
 6.5/7.2, 13/14.4, 19.5/21.7, 26/28.9, 39/43.3, 52/57.8, 58.5/65, 65/72.2 (n – 20MHz)
 13.5/15, 27/30, 40.5/45, 54/60, 81/90, 108/120, 121.5/135, 135/150 (n – 40MHz BW)
 29.3/32.5, 58.5/65, 87.8/97.5, 117/130, 175.5/195, 234/260, 263.3/292.5, 292.5/325, 351/390, 390/433.3 (ac – 80MHz BW)

2.3 Test Configuration

The EUT was tested per the guidance of KDB 789033 D02 v02r01. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, and 7.5 for antenna port conducted emissions test setups.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 6 of 90

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 789033 D02 v02r01 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.8. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 7 of 90

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 8 of 90

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 9 of 90

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMA530W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 10 of 90

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	6/21/2017	Annual	6/21/2018	RE1
-	WL25-1	Conducted Cable Set (25GHz)	6/14/2017	Annual	6/14/2018	WL25-1
Agilent	N9030A	PXA Signal Analyzer (26.5GHz)	8/28/2017	Annual	8/28/2018	MY49432391
Agilent	N9038A	MXE EMI Receiver	4/26/2017	Annual	4/26/2018	MY51210133
Anritsu	MA2411B	Pulse Power Sensor	10/22/2017	Annual	10/22/2018	846215
Anritsu	ML2495A	Power Meter	10/22/2017	Annual	10/22/2018	941001
COM-Power	AL-130R	Active Loop Antenna	6/5/2017	Annual	6/5/2018	121085
Emco	3115	Horn Antenna (1-18GHz)	3/10/2016	Biennial	3/10/2018	9704-5182
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/23/2016	Biennial	8/23/2018	135427
EMCO	3160-10	Small Horn (26.5 - 40GHz)	8/23/2016	Biennial	8/23/2018	130993
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	12/27/2016	Biennial	12/27/2018	114451
Huber+Suhner	Sucoflex 102A	40GHz Radiated Cable	5/19/2017	Annual	5/19/2018	251425001
Pasternack	NMLC-1	Line Conducted Emissions Cable (NM)	5/31/2017	Annual	5/31/2018	NMLC-1
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	4/19/2017	Annual	4/19/2018	100342
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/31/2017	Annual	7/31/2018	100348
Rohde & Schwarz	FSW67	Signal / Spectrum Analyzer	8/11/2017	Annual	8/11/2018	103200
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102134
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	7/3/2017	Annual	7/3/2018	102133
Rohde & Schwarz	TS-PR8	Preamplifier-Antenna SYS; 30MHz-8GHz	10/19/2017	Annual	10/19/2018	102324
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/7/2017	Annual	3/7/2018	100071
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	5/11/2017	Annual	5/11/2018	100040
Rohde & Schwarz	TS-PR40	26.5-40 GHz Pre-Amplifier	5/11/2017	Annual	5/11/2018	100037
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 11 of 90

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA530W
 FCC Classification: Unlicensed National Information Infrastructure (UNII)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
N/A	RSS-Gen [6.6]	26dB Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
15.407(e)	RSS-Gen [6.6]	6dB Bandwidth	>500kHz(5725-5850MHz)		PASS	Section 7.3
15.407 (a.1.iv), (a.2), (a.3)	RSS-247 [6.2]	Maximum Conducted Output Power	Maximum conducted powers must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.4
15.407 (a.1.iv), (a.2), (a.3)	RSS-247 [6.2]	Maximum Power Spectral Density	Maximum power spectral density must meet the limits detailed in 15.407 (a) (RSS-247 [6.2])		PASS	Section 7.5
15.407(h)	RSS-247 [6.3]	Dynamic Frequency Selection	See DFS Test Report		PASS	See DFS Test Report
15.407(b.1), (2), (3), (4)	RSS-247 [6.2]	Undesirable Emissions	Undesirable emissions must meet the limits detailed in 15.407(b) (RSS-247 [6.2])	RADIATED	PASS	Section 7.6
15.205, 15.407(b.1), (4), (5), (6)	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])		PASS	Section 7.6, 7.7
15.407	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 (RSS-Gen [8.8]) limits	LINE CONDUCTED	PASS	Section 7.8

Table 7-1. Summary of Test Results

Notes:

- 1) All channels, modes, and modulations/data rates were investigated among all UNII bands. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "UNII Automation," Version 4.5.
- 5) For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "Chamber Automation," Version 1.1.5.

FCC ID: A3LSMA530W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 12 of 90	

7.2 26dB Bandwidth Measurement – 802.11a/n/ac RSS-Gen [6.2]

Test Overview and Limit

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

The 26dB bandwidth is used to determine the conducted power limits.

Test Procedure Used

ANSI C63.10-2013 – Section 12.4
KDB 789033 D02 v02r01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 26$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 13 of 90


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 26dB Bandwidth [MHz]
Band 1	5180	36	a	6	22.84
	5200	40	a	6	24.44
	5240	48	a	6	22.77
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	29.25
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	28.93
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	28.96
	5190	38	n (40MHz)	13.5/15 (MCS0)	41.44
	5230	46	n (40MHz)	13.5/15 (MCS0)	42.04
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	88.38
Band 2A	5260	52	a	6	22.90
	5280	56	a	6	21.19
	5320	64	a	6	21.61
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	26.94
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	27.22
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	28.01
	5270	54	n (40MHz)	13.5/15 (MCS0)	42.67
	5310	62	n (40MHz)	13.5/15 (MCS0)	41.92
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	96.63
Band 2C	5500	100	a	6	22.61
	5580	116	a	6	20.74
	5720	144	a	6	23.92
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	26.85
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	23.91
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	25.87
	5510	102	n (40MHz)	13.5/15 (MCS0)	43.26
	5550	110	n (40MHz)	13.5/15 (MCS0)	42.17
	5710	142	n (40MHz)	13.5/15 (MCS0)	53.91
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	89.09
	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	84.43

Table 7-2. Conducted Bandwidth Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 14 of 90




Plot 7-1. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 36)




Plot 7-2. 26dB Bandwidth Plot (802.11a (UNII Band 1) – Ch. 40)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 15 of 90




Plot 7-3. 26dB Bandwidth Plot (802.11a (UNII Band 1) - Ch. 48)




Plot 7-4. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) - Ch. 36)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 - 10/26, 12/11/2017	EUT Type: Portable Handset		Page 16 of 90




Plot 7-5. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)




Plot 7-6. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 17 of 90




Plot 7-7. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)




Plot 7-8. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 18 of 90




Plot 7-9. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)




Plot 7-10. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 52)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 19 of 90




Plot 7-11. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 56)




Plot 7-12. 26dB Bandwidth Plot (802.11a (UNII Band 2A) – Ch. 64)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 20 of 90




Plot 7-13. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)




Plot 7-14. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 21 of 90




Plot 7-15. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)




Plot 7-16. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 22 of 90




Plot 7-17. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)




Plot 7-18. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 23 of 90




Plot 7-19. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 100)




Plot 7-20. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 116)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 24 of 90




Plot 7-21. 26dB Bandwidth Plot (802.11a (UNII Band 2C) – Ch. 144)




Plot 7-22. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 25 of 90




Plot 7-23. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 116)




Plot 7-24. 26dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 26 of 90




Plot 7-25. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)




Plot 7-26. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 27 of 90




Plot 7-27. 26dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)



Plot 7-28. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 28 of 90



Plot 7-29. 26dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 29 of 90

7.3 6dB Bandwidth Measurement – 802.11a/n/ac

§15.407 (e); RSS-Gen [6.2]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 6dB bandwidth.

In the 5.725 – 5.850GHz band, the 6dB bandwidth must be ≥ 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 6.9.2
KDB 789033 D02 v02r01 – Section C

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes

None.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 30 of 90

6 dB Bandwidth Measurements


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured 6dB Bandwidth [MHz]
Band 3	5745	149	a	6	16.48
	5785	157	a	6	16.45
	5825	165	a	6	16.37
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	17.37
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	17.55
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	18.69
	5755	151	n (40MHz)	13.5/15 (MCS0)	35.16
	5795	159	n (40MHz)	13.5/15 (MCS0)	32.83
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	75.52

Table 7-3. Conducted Bandwidth Measurements




Plot 7-30. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 149)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 31 of 90




Plot 7-31. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 7-32. 6dB Bandwidth Plot (802.11a (UNII Band 3) – Ch. 165)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 32 of 90



Plot 7-33. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-34. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 33 of 90




Plot 7-35. 6dB Bandwidth Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 7-36. 6dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 34 of 90



Plot 7-37. 6dB Bandwidth Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 7-38. 6dB Bandwidth Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 35 of 90	

7.4 UNII Output Power Measurement – 802.11a/n/ac

§15.407(a.1.iv) §15.407(a.2) §15.407(a.3); RSS-247 [6.2]

Test Overview and Limits

A transmitter antenna terminal of the EUT is connected to the input of an RF pulse power sensor. Measurement is made using a broadband average power meter while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies.

In the 5.15 – 5.25GHz band, the maximum permissible conducted output power is 250mW (23.98dBm) and the maximum permissible e.i.r.p for ISED is 200mW (23.01dBm)

In the 5.25 – 5.35GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(21.19) = 24.26\text{dBm}$ and the maximum permissible e.i.r.p for ISED operation is 1 Watt.

In the 5.47 – 5.725GHz band, the maximum permissible conducted output power is the lesser of 250mW (23.98dBm) and $11 \text{ dBm} + 10\log_{10}(26\text{dB BW}) = 11 \text{ dBm} + 10\log_{10}(20.74) = 24.17\text{dBm}$ and the maximum permissible e.i.r.p for ISED operation is 1 Watt.

In the 5.725 – 5.850GHz band, the maximum permissible conducted output power is 1W (30dBm).

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.3.2 Method PM-G

KDB 789033 D02 v02r01 – Section E3)b) Method PM-G

Test Settings

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 36 of 90

Freq [MHz]	Channel	Detector	Ant. Gain [dBi]	5GHz (20MHz) Conducted Power [dBm]				Max Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Max e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				IEEE Transmission Mode							
				802.11a	802.11n	802.11ac	EIRP				
5180	36	AVG	-5.80	12.79	12.55	12.51	6.99	23.98	-11.19	23.01	-16.02
5200	40	AVG	-5.80	13.12	13.11	13.79	7.99	23.98	-10.86	23.01	-15.02
5220	44	AVG	-5.80	13.18	13.09	13.63	7.83	23.98	-10.80	23.01	-15.18
5240	48	AVG	-5.80	13.28	13.10	13.51	7.71	23.98	-10.70	23.01	-15.30
5260	52	AVG	-5.80	13.26	13.12	13.53	7.73	23.98	-10.72	30.00	-22.27
5280	56	AVG	-5.80	13.22	13.09	13.54	7.74	23.98	-10.76	30.00	-22.26
5300	60	AVG	-6.10	13.60	13.61	13.87	7.77	23.98	-10.37	30.00	-22.23
5320	64	AVG	-6.10	13.44	13.45	13.93	7.83	23.98	-10.53	30.00	-22.17
5500	100	AVG	-5.60	13.06	13.40	13.24	7.80	23.98	-10.58	30.00	-22.20
5580	116	AVG	-6.00	13.36	13.27	13.31	7.36	23.98	-10.62	30.00	-22.64
5660	132	AVG	-6.00	13.59	13.51	13.42	7.59	23.98	-10.39	30.00	-22.41
5720	144	AVG	-6.60	13.54	12.72	12.92	6.94	23.98	-10.44	30.00	-23.06
5745	149	AVG	-6.60	13.20	13.92	13.05	7.32	30.00	-16.08	-	-
5785	157	AVG	-6.60	13.61	13.96	12.95	7.36	30.00	-16.04	-	-
5825	165	AVG	-7.10	13.28	13.78	13.09	6.68	30.00	-16.22	-	-

Table 7-4. 20MHz BW (UNII) Maximum Conducted Output Power

Freq [MHz]	Channel	Detector	Ant. Gain [dBi]	5GHz (40MHz) Conducted Power [dBm]			Max Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Max e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				IEEE Transmission Mode						
				802.11n	802.11ac	EIRP				
5190	38	AVG	-5.80	8.05	8.13	2.33	23.98	-15.93	23.01	-20.68
5230	46	AVG	-6.10	13.60	13.42	7.50	23.98	-10.38	23.01	-15.51
5270	54	AVG	-6.10	13.58	13.35	7.48	23.98	-10.40	30.00	-22.52
5310	62	AVG	-6.10	6.62	7.30	1.20	23.98	-17.36	30.00	-28.80
5510	102	AVG	-5.60	11.81	11.92	6.32	23.98	-12.17	30.00	-23.68
5550	110	AVG	-6.00	13.39	13.31	7.39	23.98	-10.59	30.00	-22.61
5670	134	AVG	-6.00	13.28	13.21	7.28	23.98	-10.70	30.00	-22.72
5710	142	AVG	-6.60	13.48	13.60	7.00	23.98	-10.50	30.00	-23.00
5755	151	AVG	-6.60	13.82	13.80	7.22	30.00	-16.18	-	-
5795	159	AVG	-7.10	13.98	13.67	6.88	30.00	-16.02	-	-

Table 7-5. 40MHz BW (UNII) Maximum Conducted Output Power

Freq [MHz]	Channel	Detector	Ant. Gain [dBi]	5GHz (80MHz) Conducted Power [dBm]		Max Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Max e.i.r.p Limit [dBm]	e.i.r.p Margin [dB]
				IEEE Transmission Mode					
				802.11ac	EIRP				
5210	42	AVG	-5.80	7.05	1.25	23.98	-16.93	23.01	-21.76
5290	58	AVG	-6.10	4.85	-1.25	23.98	-19.13	30.00	-31.25
5530	106	AVG	-6.00	7.32	1.32	23.98	-16.66	30.00	-28.68
5690	138	AVG	-6.60	12.43	5.83	23.98	-11.55	30.00	-24.17
5775	155	AVG	-7.10	12.24	5.14	30.00	-17.76	-	-

Table 7-6. 80MHz BW (UNII) Maximum Conducted Output Power

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 37 of 90

7.5 Maximum Power Spectral Density – 802.11a/n/ac §15.407(a.1.iv) §15.407(a.2) §15.407(a.3); RSS-247 [6.2]

Test Overview and Limit

The spectrum analyzer was connected to the antenna terminal while the EUT was operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. Method SA-1, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, was used to measure the power spectral density.

In the 5.15 – 5.25GHz, 5.25 – 5.35GHz, 5.47 – 5.725GHz bands, the maximum permissible power spectral density is 11dBm/MHz.

In the 5.725 – 5.850GHz band, the maximum permissible power spectral density is 30dBm/500kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 12.3.2.2
KDB 789033 D02 v02r01 – Section F

Test Settings

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire emission bandwidth of the signal
3. RBW = 1MHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span/RBW})$
6. Sweep time = auto
7. Detector = power averaging (RMS)
8. Trigger was set to free run for all modes
9. Trace was averaged over 100 sweeps
10. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 38 of 90


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Power Density [dBm/MHz]	Margin [dB]
Band 1	5180	36	a	6	2.47	11.0	-8.53
	5200	40	a	6	2.71	11.0	-8.29
	5240	48	a	6	2.65	11.0	-8.35
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	2.25	11.0	-8.75
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	2.22	11.0	-8.78
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	2.08	11.0	-8.92
	5190	38	n (40MHz)	13.5/15 (MCS0)	-3.05	11.0	-14.05
	5230	46	n (40MHz)	13.5/15 (MCS0)	-3.03	11.0	-14.03
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-5.00	11.0	-16.00
Band 2A	5260	52	a	6	2.33	11.0	-8.67
	5280	56	a	6	2.19	11.0	-8.81
	5320	64	a	6	2.16	11.0	-8.84
	5260	52	n (20MHz)	6.5/7.2 (MCS0)	2.18	11.0	-8.82
	5280	56	n (20MHz)	6.5/7.2 (MCS0)	2.49	11.0	-8.51
	5320	64	n (20MHz)	6.5/7.2 (MCS0)	1.90	11.0	-9.10
	5270	54	n (40MHz)	13.5/15 (MCS0)	-2.81	11.0	-13.81
	5310	62	n (40MHz)	13.5/15 (MCS0)	-2.37	11.0	-13.37
	5290	58	ac (80MHz)	29.3/32.5 (MCS0)	-4.98	11.0	-15.98
Band 2C	5500	100	a	6	2.20	11.0	-8.80
	5580	116	a	6	0.64	11.0	-10.36
	5720	144	a	6	2.39	11.0	-8.61
	5500	100	n (20MHz)	6.5/7.2 (MCS0)	1.98	11.0	-9.02
	5580	116	n (20MHz)	6.5/7.2 (MCS0)	0.46	11.0	-10.54
	5720	144	n (20MHz)	6.5/7.2 (MCS0)	2.21	11.0	-8.79
	5510	102	n (40MHz)	13.5/15 (MCS0)	-2.68	11.0	-13.68
	5550	110	n (40MHz)	13.5/15 (MCS0)	-2.55	11.0	-13.55
	5710	142	n (40MHz)	13.5/15 (MCS0)	-2.48	11.0	-13.48
	5530	106	ac (80MHz)	29.3/32.5 (MCS0)	-6.51	11.0	-17.51
	5690	138	ac (80MHz)	29.3/32.5 (MCS0)	-9.16	11.0	-20.16

Table 7-7. Bands 1, 2A, 2C Conducted Power Spectral Density Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 39 of 90


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Antenna Gain [dBi]	e.i.r.p. Power Density [dBm/MHz]	ISED Max e.i.r.p. Power Density [dBm/MHz]	Margin [dB]
Band 1	5180	36	a	6	2.47	-5.8	-3.3	10.0	-13.33
	5200	40	a	6	2.71	-5.8	-3.1	10.0	-13.09
	5240	48	a	6	2.65	-5.8	-3.1	10.0	-13.15
	5180	36	n (20MHz)	6.5/7.2 (MCS0)	2.25	-5.8	-3.5	10.0	-13.55
	5200	40	n (20MHz)	6.5/7.2 (MCS0)	2.22	-5.8	-3.6	10.0	-13.58
	5240	48	n (20MHz)	6.5/7.2 (MCS0)	2.08	-6.1	-4.0	10.0	-14.02
	5190	38	n (40MHz)	13.5/15 (MCS0)	-3.05	-5.8	-8.8	10.0	-18.85
	5230	46	n (40MHz)	13.5/15 (MCS0)	-3.03	-5.8	-8.8	10.0	-18.83
	5210	42	ac (80MHz)	29.3/32.5 (MCS0)	-5.00	-5.8	-10.8	10.0	-20.80

Table 7-8. Bands 1 e.i.r.p. Conducted Power Spectral Density Measurements




Plot 7-39. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 36)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 40 of 90




Plot 7-40. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 40)




Plot 7-41. Power Spectral Density Plot (802.11a (UNII Band 1) – Ch. 48)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 41 of 90




Plot 7-42. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 36)




Plot 7-43. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 40)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 42 of 90




Plot 7-44. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 1) – Ch. 48)




Plot 7-45. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 38)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 43 of 90




Plot 7-46. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 1) – Ch. 46)




Plot 7-47. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 1) – Ch. 42)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 44 of 90




Plot 7-48. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 52)




Plot 7-49. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 56)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 45 of 90




Plot 7-50. Power Spectral Density Plot (802.11a (UNII Band 2A) – Ch. 64)




Plot 7-51. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 52)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 46 of 90




Plot 7-52. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 56)




Plot 7-53. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2A) – Ch. 64)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 47 of 90




Plot 7-54. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 54)




Plot 7-55. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2A) – Ch. 62)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 48 of 90




Plot 7-56. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2A) – Ch. 58)




Plot 7-57. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 100)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 49 of 90




Plot 7-58. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 116)




Plot 7-59. Power Spectral Density Plot (802.11a (UNII Band 2C) – Ch. 144)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 50 of 90




Plot 7-60. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 100)




Plot 7-61. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 116)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 51 of 90




Plot 7-62. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 2C) – Ch. 144)




Plot 7-63. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 102)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 52 of 90




Plot 7-64. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 110)




Plot 7-65. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 2C) – Ch. 142)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 53 of 90



Plot 7-66. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 106)




Plot 7-67. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 2C) – Ch. 138)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 54 of 90


	Frequency [MHz]	Channel No.	802.11 Mode	Data Rate [Mbps]	Measured Power Density [dBm]	Max Permissible Power Density [dBm/500kHz]	Margin [dB]
Band 3	5745	149	a	6	-0.50	30.0	-30.50
	5785	157	a	6	-0.57	30.0	-30.57
	5825	165	a	6	-0.31	30.0	-30.31
	5745	149	n (20MHz)	6.5/7.2 (MCS0)	-0.89	30.0	-30.89
	5785	157	n (20MHz)	6.5/7.2 (MCS0)	-0.85	30.0	-30.85
	5825	165	n (20MHz)	6.5/7.2 (MCS0)	-0.69	30.0	-30.69
	5755	151	n (40MHz)	13.5/15 (MCS0)	-5.26	30.0	-35.26
	5795	159	n (40MHz)	13.5/15 (MCS0)	-5.53	30.0	-35.53
	5775	155	ac (80MHz)	29.3/32.5 (MCS0)	-4.83	30.0	-34.83

Table 7-9. Band 3 Conducted Power Spectral Density Measurements




Plot 7-68. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 149)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 55 of 90




Plot 7-69. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 157)




Plot 7-70. Power Spectral Density Plot (802.11a (UNII Band 3) – Ch. 165)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 56 of 90




Plot 7-71. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 149)




Plot 7-72. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 157)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 57 of 90




Plot 7-73. Power Spectral Density Plot (20MHz BW 802.11n (UNII Band 3) – Ch. 165)




Plot 7-74. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 151)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 58 of 90



Plot 7-75. Power Spectral Density Plot (40MHz BW 802.11n (UNII Band 3) – Ch. 159)



Plot 7-76. Power Spectral Density Plot (80MHz BW 802.11ac (UNII Band 3) – Ch. 155)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 59 of 90

7.6 Radiated Spurious Emission Measurements – Above 1GHz

§15.407(b) §15.205 §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10-2013 and KDB 789033 D02 v02r01, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11n (20MHz BW), 802.11n (40MHz BW), and 802.11ac (80MHz)), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

For transmitters operating in the 5.15-5.25 GHz and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-10 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-10. Radiated Limits

Test Procedures Used

ANSI C63.10-2013 – Sections 12.7.7.2, 12.7.6, 12.7.5

KDB 789033 D02 v02r01 – Section G

Test Settings

Average Measurements above 1GHz (Method AD)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Averaging type = power (RMS)
7. Sweep time = auto couple
8. Trace was averaged over 100 sweeps

FCC ID: A3LSMA530W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 60 of 90

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = 120kHz
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 61 of 90

Test Notes

1. All emissions that lie in the restricted bands (denoted by a * next to the frequency) specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-10.
2. All spurious emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-10. All spurious emissions that do not lie in a restricted band are subject to a peak limit of -27dBm/MHz. At a distance of 3 meters, the field strength limit in dBμV/m can be determined by adding a "conversion" factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dBμV/m.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.

Sample Calculations

Determining Spurious Emissions Levels


- o Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- o $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- o $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset


- o The amplitude offset shown in the radiated restricted band edge plots in Section 0 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 62 of 90


7.7.1 Radiated Spurious Emission Measurements



Plot 7-77. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. H)




Plot 7-78. Radiated Spurious Plot above 1GHz (802.11a – U1 Ch. 40, Ant. Pol. V)




Plot 7-79. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. H)


FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 63 of 90



Plot 7-80. Radiated Spurious Plot above 1GHz (802.11a – U2A Ch. 56, Ant. Pol. V)




Plot 7-81. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 116, Ant. Pol. H)




Plot 7-82. Radiated Spurious Plot above 1GHz (802.11a – U2C Ch. 116, Ant. Pol. V)

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 64 of 90




Plot 7-83. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)




Plot 7-84. Radiated Spurious Plot above 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 65 of 90

Radiated Spurious Emissions Measurements (Above 18GHz)




Plot 7-85. Radiated Spurious Plot 18GHz - 26.5GHz (802.11a – Ant. Pol. H)




Plot 7-86. Radiated Spurious Plot above 18GHz - 26.5GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 66 of 90

Radiated Spurious Emissions Measurements (Above 18GHz)



Plot 7-87. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a – Ant. Pol. H)



Plot 7-88. Radiated Spurious Plot above 26.5GHz - 40GHz (802.11a – Ant. Pol. V)

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 67 of 90

Radiated Spurious Emission Measurements

§15.407(b) §15.205 & §15.209; RSS-Gen [8.9]

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5180MHz
Channel: 36

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10360.00	Peak	H	100	253	-61.20	12.13	-9.54	48.39	68.20	-19.81
* 15540.00	Average	H	100	179	-72.18	14.49	-9.54	39.77	53.98	-14.21
* 15540.00	Peak	H	100	179	-60.85	14.49	-9.54	51.10	73.98	-22.88
* 20720.00	Average	H	100	184	-70.76	7.94	-9.54	34.64	53.98	-19.34
* 20720.00	Peak	H	100	184	-59.54	7.94	-9.54	45.86	73.98	-28.12
25900.00	Peak	H	-	-	-57.34	8.46	-9.54	48.58	68.20	-19.62

Table 7-11. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5200MHz
Channel: 40

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10400.00	Peak	H	100	115	-64.91	12.12	-9.54	44.67	68.20	-23.53
* 15600.00	Average	H	100	48	-72.80	14.31	-9.54	38.97	53.98	-15.01
* 15600.00	Peak	H	100	48	-62.38	14.31	-9.54	49.39	73.98	-24.59
* 20800.00	Average	H	100	187	-70.26	7.95	-9.54	35.15	53.98	-18.83
* 20800.00	Peak	H	100	187	-59.31	7.95	-9.54	46.10	73.98	-27.88
26000.00	Peak	H	-	-	-58.06	8.60	-9.54	48.00	68.20	-20.20

Table 7-12. Radiated Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 68 of 90

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5240MHz
Channel: 48

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10480.00	Peak	H	100	101	-62.12	12.09	-9.54	47.43	68.20	-20.77
* 15720.00	Average	H	100	331	-71.41	14.02	-9.54	40.07	53.98	-13.91
* 15720.00	Peak	H	100	331	-60.63	14.02	-9.54	50.85	73.98	-23.13
* 20960.00	Average	H	100	182	-71.04	7.91	-9.54	34.33	53.98	-19.65
* 20960.00	Peak	H	100	182	-60.03	7.91	-9.54	45.34	73.98	-28.64
26200.00	Peak	H	-	-	-56.68	8.62	-9.54	49.40	68.20	-18.80

Table 7-13. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5260MHz
Channel: 52

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10520.00	Peak	H	100	100	-62.29	12.16	-9.54	47.33	68.20	-20.87
* 15780.00	Average	H	100	345	-71.06	14.03	-9.54	40.43	53.98	-13.55
* 15780.00	Peak	H	100	345	-59.92	14.03	-9.54	51.57	73.98	-22.41
* 21040.00	Average	H	100	186	-70.67	7.92	-9.54	34.71	53.98	-19.27
* 21040.00	Peak	H	100	186	-59.88	7.92	-9.54	45.50	73.98	-28.48
26300.00	Peak	H	-	-	-55.69	8.73	-9.54	50.50	68.20	-17.70

Table 7-14. Radiated Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 69 of 90

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5280MHz
Channel: 56

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
10560.00	Peak	H	100	356	-62.31	12.04	-9.54	47.19	68.20	-21.01
* 15840.00	Average	H	100	51	-71.52	14.25	-9.54	40.18	53.98	-13.80
* 15840.00	Peak	H	100	51	-60.60	14.25	-9.54	51.10	73.98	-22.88
* 21120.00	Average	H	100	141	-70.54	7.96	-9.54	34.88	53.98	-19.10
* 21120.00	Peak	H	100	141	-59.78	7.96	-9.54	45.64	73.98	-28.34
26400.00	Peak	H	-	-	-56.58	8.94	-9.54	49.82	68.20	-18.38

Table 7-15. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5320MHz
Channel: 64

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 10640.00	Average	H	100	351	-73.24	12.06	-9.54	36.28	53.98	-17.70
* 10640.00	Peak	H	100	351	-62.27	12.06	-9.54	47.25	73.98	-26.73
* 15960.00	Average	H	100	328	-71.19	14.55	-9.54	40.82	53.98	-13.16
* 15960.00	Peak	H	100	328	-59.70	14.55	-9.54	52.31	73.98	-21.67
* 21280.00	Average	H	100	141	-70.05	8.04	-9.54	35.45	53.98	-18.53
* 21280.00	Peak	H	100	141	-59.17	8.04	-9.54	46.33	73.98	-27.65
26600.00	Peak	H	-	-	-48.40	-8.30	-9.54	40.75	68.20	-27.45

Table 7-16. Radiated Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 70 of 90

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5500MHz
Channel: 100

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11000.00	Average	H	100	355	-74.00	12.87	-9.54	36.33	53.98	-17.65
* 11000.00	Peak	H	100	355	-62.17	12.87	-9.54	48.16	73.98	-25.82
16500.00	Peak	H	-	-	-59.85	16.61	-9.54	54.22	68.20	-13.98
22000.00	Peak	H	-	-	-57.76	8.43	-9.54	48.12	68.20	-20.08
27500.00	Peak	H	-	-	-47.78	-8.80	-9.54	40.88	68.20	-27.32

Table 7-17. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5800MHz
Channel: 116

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11600.00	Average	H	100	75	-72.13	12.64	-9.54	37.97	53.98	-16.01
* 11600.00	Peak	H	100	75	-61.45	12.64	-9.54	48.65	73.98	-25.33
17400.00	Peak	H	-	-	-60.08	16.21	-9.54	53.59	68.20	-14.61
* 23200.00	Average	H	-	-	-70.20	8.08	-9.54	35.34	53.98	-18.64
* 23200.00	Peak	H	-	-	-59.35	8.08	-9.54	46.19	73.98	-27.79
29000.00	Peak	H	-	-	-47.39	-9.08	-9.54	40.99	68.20	-27.21

Table 7-18. Radiated Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 71 of 90

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 Meter
 Operating Frequency: 5720MHz
 Channel: 144

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11440.00	Average	H	100	51	-72.71	12.47	-9.54	37.22	53.98	-16.76
* 11440.00	Peak	H	100	51	-62.02	12.47	-9.54	47.91	73.98	-26.07
17160.00	Peak	H	-	-	-59.59	18.06	-9.54	55.93	68.20	-12.27
* 22880.00	Average	H	-	-	-71.33	8.37	-9.54	34.50	53.98	-19.48
* 22880.00	Peak	H	-	-	-59.89	8.37	-9.54	45.94	73.98	-28.04
28600.00	Peak	H	-	-	-46.84	-8.95	-9.54	41.67	68.20	-26.53

Table 7-19. Radiated Measurements

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6 Mbps
 Distance of Measurements: 1 Meter
 Operating Frequency: 5745MHz
 Channel: 149

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11490.00	Average	H	100	51	-72.89	12.43	-9.54	37.00	53.98	-16.98
* 11490.00	Peak	H	100	51	-61.77	12.43	-9.54	48.12	73.98	-25.86
17235.00	Peak	H	-	-	-60.13	18.61	-9.54	55.94	68.20	-12.26
* 22980.00	Average	H	-	-	-71.27	8.16	-9.54	34.35	53.98	-19.63
* 22980.00	Peak	H	-	-	-60.33	8.16	-9.54	45.29	73.98	-28.69
28725.00	Peak	H	-	-	-46.59	-9.24	-9.54	41.63	68.20	-26.57

Table 7-20. Radiated Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 72 of 90

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5785MHz
Channel: 157

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11570.00	Average	H	100	326	-72.87	12.54	-9.54	37.13	53.98	-16.85
* 11570.00	Peak	H	100	326	-61.81	12.54	-9.54	48.19	73.98	-25.79
17355.00	Peak	H	-	-	-60.26	18.73	-9.54	55.93	68.20	-12.27
23140.00	Peak	H	-	-	-58.67	8.37	-9.54	47.16	68.20	-21.04
28925.00	Peak	H	100	160	-47.28	-9.65	-9.54	40.53	68.20	-27.67

Table 7-21. Radiated Measurements

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6 Mbps
Distance of Measurements: 1 Meter
Operating Frequency: 5825MHz
Channel: 165

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
* 11650.00	Average	H	-	-	-73.12	12.99	-9.54	37.32	53.98	-16.66
* 11650.00	Peak	H	-	-	-61.45	12.99	-9.54	48.99	73.98	-24.99
17475.00	Peak	H	-	-	-58.62	19.25	-9.54	58.08	68.20	-10.12
23300.00	Peak	H	-	-	-58.16	8.50	-9.54	47.79	68.20	-20.41
29125.00	Peak	H	-	-	-47.13	-9.87	-9.54	40.46	68.20	-27.74


Table 7-22. Radiated Measurements

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 73 of 90


7.7.2 Radiated Band Edge Measurements (20MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]; RSS-Gen [8.9]

Worst Case Mode:	802.11a (20MHz)
Worst Case Transfer Rate:	6 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	5180MHz
Channel:	36




Plot 7-89. Radiated Lower Band Edge Plot (Average – UNII Band 1)




Plot 7-90. Radiated Lower Band Edge Plot (Peak – UNII Band 1)

Worst Case Mode:	802.11a (20MHz)
Worst Case Transfer Rate:	6 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	5320MHz
Channel:	64




Plot 7-91. Radiated Upper Band Edge Plot (Average – UNII Band 2A)




Plot 7-92. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 74 of 90

Worst Case Mode:	802.11a (20MHz)
Worst Case Transfer Rate:	6 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	5500MHz
Channel:	100




Plot 7-93. Radiated Lower Band Edge Plot (Average – UNII Band 2C)



Plot 7-94. Radiated Lower Band Edge Plot (Peak – UNII Band 2C)

Worst Case Mode:	802.11a (20MHz)
Worst Case Transfer Rate:	6 Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	5825MHz
Channel:	165



Plot 7-95. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

Note:


Per KDB 789033 Section II (G)(3)(d)(ii), integration was used to determine compliance with out-of band emission limits. Integration method was performed across the first 1 MHz band outside the authorized band of operation which was found to be the worst case emission at the band edge.

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 75 of 90

7.7.3 Radiated Band Edge Measurements (40MHz BW)

§15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11n (40MHz)
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5190MHz
Channel:	38




Plot 7-96. Radiated Lower Band Edge Plot (Average – UNII Band 1)




Plot 7-97. Radiated Lower Band Edge Plot (Peak – UNII Band 1)

Worst Case Mode:	802.11n (40MHz)
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5310MHz
Channel:	62



Plot 7-98. Radiated Upper Band Edge Plot (Average – UNII Band 2A)




Plot 7-99. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)

Note:


Per KDB 789033 Section II (G)(3)(d)(ii), integration was used to determine compliance with out-of band emission limits. Integration method was performed across the first 1 MHz band outside the authorized band of operation which was found to be the worst case emission at the band edge.

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 76 of 90

Worst Case Mode: 802.11n (40MHz)
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5510MHz
Channel: 102




Plot 7-100. Radiated Lower Band Edge Plot (Average – UNII Band 2C)



Plot 7-101. Radiated Lower Band Edge Plot (Peak – UNII Band 2C)

Worst Case Mode: 802.11n (40MHz)
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5795MHz
Channel: 159



Plot 7-102. Radiated Upper Band Edge Plot (Peak – UNII Band 3)

Note:


Per KDB 789033 Section II (G)(3)(d)(ii), integration was used to determine compliance with out-of band emission limits. Integration method was performed across the first 1 MHz band outside the authorized band of operation which was found to be the worst case emission at the band edge.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 77 of 90


7.7.4 Radiated Band Edge Measurements (80MHz BW)

\$15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

Worst Case Mode:	802.11ac (80MHz)
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




Plot 7-103. Radiated Lower Band Edge Plot (Average – UNII Band 1)



Plot 7-104. Radiated Lower Band Edge Plot (Peak – UNII Band 1)

Worst Case Mode:	802.11ac (80MHz)
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58




Plot 7-105. Radiated Upper Band Edge Plot (Average – UNII Band 2A)




Plot 7-106. Radiated Upper Band Edge Plot (Peak – UNII Band 2A)

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 78 of 90

Worst Case Mode: 802.11ac (80MHz)
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5530MHz
Channel: 106




**Plot 7-107. Radiated Lower Band Edge Plot
(Average – UNII Band 2C)**



**Plot 7-108. Radiated Lower Band Edge Plot (Peak –
UNII Band 2C)**

Worst Case Mode: 802.11ac (80MHz)
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5775MHz
Channel: 155



**Plot 7-109. Radiated Upper Band Edge Plot (Peak –
UNII Band 3)**

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 79 of 90

7.7 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-23 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-23. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA530W		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 80 of 90

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 81 of 90


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-23.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 82 of 90

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-110. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. H)



Plot 7-111. Radiated Spurious Plot below 1GHz (802.11a – U3 Ch. 157, Ant. Pol. V)

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 83 of 90

7.8 Line-Conducted Test Data

§15.407; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-24. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 84 of 90

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMA530W	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 85 of 90




Plot 7-112. Line Conducted Plot with 802.11a UNII Band 1 (L1)




Plot 7-113. Line Conducted Plot with 802.11a UNII Band 1 (N)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 86 of 90




Plot 7-114. Line Conducted Plot with 802.11a UNII Band 2A (L1)




Plot 7-115. Line Conducted Plot with 802.11a UNII Band 2A (N)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 87 of 90




Plot 7-116. Line Conducted Plot with 802.11a UNII Band 2C (L1)




Plot 7-117. Line Conducted Plot with 802.11a UNII Band 2C (N)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 88 of 90



Plot 7-118. Line Conducted Plot with 802.11a UNII Band 3 (L1)



Plot 7-119. Line Conducted Plot with 802.11a UNII Band 3 (N)

FCC ID: A3LSMA530W	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset		Page 89 of 90

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA530W** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: A3LSMA530W	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1711240303-06-R1.A3L	Test Dates: 9/26 – 10/26, 12/11/2017	EUT Type: Portable Handset	Page 90 of 90

© 2017 PCTEST Engineering Laboratory, Inc.

V 7.0 9/22/2017

All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST Engineering Laboratory, Inc. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.