



ELEMENT MATERIALS TECHNOLOGY,

Columbia MD

(formerly PCTEST)

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

MEASUREMENT REPORT

FCC Part 15.247 Bluetooth (Low Energy)

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

10/29/2025-12/18/2025

Test Report Issue Date:

1/14/2026

Test Site/Location:

Element Lab., Columbia, MD, USA

Test Report Serial No.:

1M2510280091-13.A3L

FCC ID:

A3LSMA576B

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-A576B/DS

Additional Model(s):

SM-A576B

EUT Type:

Portable Handset

Max. RF Output Power:

59.993 mW (17.78 dBm) Peak Conducted

Frequency Range:

2402 – 2480MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

FCC Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023, KDB 987594 D02 v03

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10:2020. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez
Executive Vice President



FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 1 of 66

© 2026 ELEMENT

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without written permission from Element. If you have any questions about this or have an inquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

V11.3 5/14/2025

TEST REPORT REVISION HISTORY

Rev. No.	Description	Issue Date	Revised By
-	Initial Release	1/14/2026	WKR0000005883

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 2 of 66

TABLE OF CONTENTS

1.0	INTRODUCTION	4
1.1	Scope	4
1.2	Element Test Location	4
1.3	Test Facility / Accreditations	4
2.0	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	6
2.4	Test Configuration	6
2.5	Software and Firmware	6
2.6	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions	8
3.4	Environmental Conditions	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS	14
7.1	Summary	14
7.2	6dB Bandwidth Measurement – Bluetooth (LE)	15
7.3	Output Power Measurement – Bluetooth (LE)	23
7.4	Power Spectral Density – Bluetooth (LE)	31
7.5	Conducted Emissions at the Band Edge	39
7.6	Conducted Spurious Emissions	44
7.7	Radiated Spurious Emission Measurements	49
7.8	Radiated Restricted Band Edge Measurements	56
7.9	Radiated Spurious Emissions Measurements – Below 1GHz	57
7.10	Line-Conducted Test Data	61
8.0	CONCLUSION	64
9.0	APPENDIX A – Data referencing spot-checks	65

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 3 of 66

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Test Location

Measurements were conducted at the Element laboratory(ies) indicated in Section 1.3 below. All measurement facilities are compliant with the test site requirements specified in ANSI C63.4:2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered test laboratory with the site description on file with ISED (Wireless Test Lab number 2451B) and FCC (Designation Number US1113).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 4 of 66

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA576B**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

The authorization for this device utilize data referencing from FCC ID: A3LSMA576U as permitted per KDB 484596 D01 v03. Data referencing data test results are included in Appendix A of this report.

Test Device Serial No.: 0545M, 0107M, 0554M

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-band 5G NR (FR1), 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHz and 6GHz), Bluetooth (1x, EDR, LE), NFC

Ch.	Frequency (MHz)
37	2402
:	:
17	2440
:	:
39	2480

Table 2-1. Frequency / Channel Operations – 125/500kbps & 1Mbps

Ch.	Frequency (MHz)
0	2404
:	:
17	2440
:	:
36	2478

Table 2-2. Frequency / Channel Operations – 2Mbps

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 5 of 66

2.3 Antenna Description

The manufacturer provided the antenna gains which can affect the validity of test results used for determination of compliance. The following antenna gains are used in this device per the "Unlicensed Band Antenna Gain" document provided by the client. This document is also included in the filing as a public exhibit.

Frequency [GHz]	Antenna-1 Gain (dBi)
2.4	-4.65

Table 2-3. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 79 different channels in the 2400 – 2483.5MHz band.

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10:2020. ANSI C63.10:2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report. The worst orientation was found to be Y-orientation (landscape).

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB cable with wire charger
- EUT powered by host PC via USB cable with wire charger

2.5 Software and Firmware

The test was conducted with software/firmware version A576U1UEU0AYK3 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 6 of 66

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10:2020) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that those cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 7 of 66

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4:2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4:2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 8 of 66

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 9 of 66

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10:2020. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

Table 5-1. Measurement Uncertainty Budget

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 10 of 66

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurement antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	MD 1M 40	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	MD 1M 40
-	AP1-002	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	AP1-002
-	AP2-001	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	AP2-001
-	AP2-002	EMC Cable and Switch System	2/25/2025	Annual	2/25/2026	AP2-002
-	ETS-001	EMC Cable and Switch System	12/11/2024	Annual	12/11/2025	ETS-001
-	ETS-002	EMC Cable and Switch System	12/11/2024	Annual	12/11/2025	ETS-002
-	WL25-1	Conducted Cable Set (25GHz)	2/25/2025	Annual	2/25/2026	WL25-1
-	WL25-2	Conducted Cable Set (25GHz)	2/25/2025	Annual	2/25/2026	WL25-2
-	WL40-1	Conducted Cable Set (40GHz)	2/25/2025	Annual	2/25/2026	WL40-1
Agilent	N9038A	MXE EMI Receiver	11/10/2025	Annual	11/10/2026	MY51210133
Anritsu	MA24408A	POWER SENSOR	2/11/2025	Annual	2/11/2026	12776
EMCO	3115	Horn Antenna (1-18GHz)	9/6/2024	Biennial	9/6/2026	9704-5182
Espec	ESX-2CA	Environmental Chamber	11/20/2024	Biennial	11/20/2026	17620
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	6/4/2025	Biennial	6/4/2027	125518
ETS-Lindgren	3164-05	Quad Ridge Horn (Small) 2 - 18GHz	6/4/2025	Biennial	6/4/2027	208255
ETS-Lindgren	3816/2NM	Line Impedance Stabilization Network	4/21/2025	Biennial	4/21/2027	114451
Keysight Technologies	N9030A	PXA Signal Analyzer (44GHz)	6/6/2025	Annual	6/6/2026	MY52350166
Keysight Technologies	N9020A	MXA Signal Analyzer	6/4/2025	Annual	6/4/2026	MY54500644
Keysight Technologies	N9030A	PXA Signal Analyzer	11/3/2025	Annual	11/3/2026	MY54490576
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	3/25/2025	Annual	3/25/2026	NMLC-2
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/25/2025	Annual	3/25/2026	101716
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	10/16/2024	Annual	12/31/2025	100342
Rohde & Schwarz	ENV216	Two-Line V-Network	3/21/2025	Biennial	3/21/2027	101380
Rohde & Schwarz	180-422-KF	Horn (18 - 40GHz)	10/9/2024	Biennial	10/9/2026	U157403-01
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	9/11/2024	Biennial	9/11/2026	A051107
Sunol	JB6	Bi-Log Antenna (30M - 5GHz)	3/24/2025	Biennial	3/24/2027	A082816

Table 6-1. Test Equipment Calibration Table

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

Equipment listed with "N/A" under calibration information was not used to make calibrated measurements.

Component	Serial Number
MegaPhase Cable TM26-S1S1-36	18160103 003
Pasternack 6dB Attenuator PE7005-6	N/A

Table 6-2. WL25-1 Conducted Cable Set Components

Component	Serial Number
MiniCircuits Cable CBL-2FT-SMSM+	77743
MCL 6dB Attenuator BW-S6W2+	1314

Table 6-3. WL25-2 Conducted Cable Set Components

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 11 of 66

Component	Serial Number
MegaPhase Cable TM40K1K1-36	18160102 001
MCL 10dB Attenuator BW-K10 2W44+	1902

Table 6-4. WL40-1 Conducted Cable Set Components

Component	Serial Number
Pasternack Cable RG214/U	111815
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001

Table 6-5. ETS-001 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase (CAGE 1GVT4) Cable GR18-N5N5-24	14042714 001
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	20502201 001
Rohde & Schwarz SF Unit	102134
Minicircuits Cable CBL=0.5M-NMNM+	15440

Table 6-6. ETS-002 EMC Cable and Switch System Components

Component	Serial Number
Sucoflex 106A Cable	501992
MegaPhase Cable N29-N1N1-324	20335606 001
Rohde & Schwarz SF Unit	102133
MiniCircuits Cable CBL-2FT-SMSM+	77745
MegaPhase Cable 10511-1	15034701 001
MiniCircuits Switch RC 2SPDT-A18	11703270 041
Sucoflex 104 Cable	320259/4
Sucoflex 104 Cable	321999/4
Sucoflex 104 Cable	321995/4

Table 6-7. AP1-002 EMC Cable and Switch System Components

Component	Serial Number
Flex Cable	P2A-0001
Micro-Coax Utilifex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Chamber Passthrough	CP4/X12
Micro-Coax Utilifex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Micro-Coax Utilifex Cable UFB142A-0-0629-5GU200 MFR 6463	232069-001
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181

Table 6-8. AP2-001 EMC Cable and Switch System Components

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 12 of 66

Component	Serial Number
MiniCircuits Cable CBL-0.5M-SMNM+	47261
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-001
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-002
MegaPhase (CAGE 1GVT4) Cable NC29-N1N1-324	19046401 001
Megaphase (CAGE 1GVT4) Flex Cable 10511-1	15044701-006
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-002
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-004
Micro-Coax Utilflex Cable UFB142A-0-0629-5GU200 MFR 64639	232069-001
Rohde & Schwarz SF Unit	102138
Rohde & Schwarz OSP130 Open Switch and Control Unit	101181
Micro-Coax Utilflex Cable UFB311A-Q-3346-50U50U MFR 64639	231978-003
Micro-Coax Utilflex Cable UFB311A-1-0629-50U50U MFR 64639	231986-003
Rohde & Schwarz TS-PR8 Pre-Amplifier	102335

Table 6-9. AP2-002 EMC Cable and Switch System Components

Component	Serial Number
MegaPhase Cable TM40-K1K1-30	20233002-004
UTIPLEX Cable	64639 232063-001
Rohde & Schwarz Pre-amp RS-PR1840 18G-40G	9037.7670.02

Table 6-10. MD 1M 18-40 EMC Cable and Switch System Components

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 13 of 66

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA576B
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Data Referencing
15.247(a)(2)	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2	Yes
15.247(b)(3)	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3	Yes
15.247(e)	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4	Yes
15.247(d)	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6	Yes
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.8, 7.9	Yes
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.10	No

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Bluetooth LE Automation,” Version 3.6.
5. For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element “Chamber Automation,” Version 1.3.1.
6. Data was referenced from model SM-A576U1 for the certification of SM-A576B/DS. See Section 9.0 for spotcheck results.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 14 of 66

7.2 6dB Bandwidth Measurement – Bluetooth (LE)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10:2020 – Section 11.8.2 Option 2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 15 of 66


Frequency [MHz]	Data Rate	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2402	125 kbps	37	LE	686.6	500	Pass
2440	125 kbps	17	LE	686.8	500	Pass
2480	125 kbps	39	LE	682.9	500	Pass
2402	500 kbps	37	LE	686.4	500	Pass
2440	500 kbps	17	LE	705.3	500	Pass
2480	500 kbps	39	LE	668.2	500	Pass
2402	1 Mbps	37	LE	671.7	500	Pass
2440	1 Mbps	17	LE	656.0	500	Pass
2480	1 Mbps	39	LE	673.6	500	Pass
2404	2 Mbps	0	LE	1236.2	500	Pass
2440	2 Mbps	17	LE	1233.9	500	Pass
2478	2 Mbps	36	LE	1244.0	500	Pass

Table 7-2. Conducted Bandwidth Measurements

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 16 of 66




Plot 7-1. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 37)



Plot 7-2. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 17 of 66



Plot 7-3. 6dB Bandwidth Plot (Bluetooth (LE), 125kbps – Ch. 39)



Plot 7-4. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 37)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 18 of 66



Plot 7-5. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 17)



Plot 7-6. 6dB Bandwidth Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 19 of 66



Plot 7-7. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-8. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 20 of 66




Plot 7-9. 6dB Bandwidth Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-10. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 21 of 66



Plot 7-11. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-12. 6dB Bandwidth Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 22 of 66

7.3 Output Power Measurement – Bluetooth (LE)

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt and the e.i.r.p. shall not exceed 4 W per RSS-247

Test Procedure Used

ANSI C63.10:2020 – Section 11.9.1.1

Test Settings

1. RBW = 3MHz
2. VBW = 50MHz
3. Span $\geq 3 \times$ RBW
4. Sweep = auto couple
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 23 of 66


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Peak Conducted Power		Ant. Gain [dBi]	EIRP [dBm]	Limit [dBm]	Margin [dB]
				[dBm]	[mW]				
2402	125 kbps	37	LE	12.21	16.634	-4.65	7.56	36.02	-28.46
2440	125 kbps	17	LE	12.01	15.885	-4.65	7.36	36.02	-28.66
2480	125 kbps	39	LE	12.01	15.874	-4.65	7.36	36.02	-28.66
2402	500 kbps	37	LE	12.25	16.769	-4.65	7.60	36.02	-28.43
2440	500 kbps	17	LE	12.00	15.849	-4.65	7.35	36.02	-28.67
2480	500 kbps	39	LE	12.02	15.929	-4.65	7.37	36.02	-28.65
2402	1 Mbps	37	LE	17.42	55.208	-4.65	12.77	36.02	-23.25
2440	1 Mbps	17	LE	17.43	55.284	-4.65	12.78	36.02	-23.24
2480	1 Mbps	39	LE	17.33	54.051	-4.65	12.68	36.02	-23.34
2404	2 Mbps	0	LE	17.78	59.993	-4.65	13.13	36.02	-22.89
2440	2 Mbps	17	LE	17.45	55.642	-4.65	12.80	36.02	-23.22
2478	2 Mbps	36	LE	17.37	54.513	-4.65	12.72	36.02	-23.31

Table 7-3. Conducted Output Power Measurements (Bluetooth (LE))

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 24 of 66




Plot 7-13. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 37)




Plot 7-14. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 25 of 66




Plot 7-15. Peak Power Plot (Bluetooth (LE), 125kbps – Ch. 39)




Plot 7-16. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 37)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 26 of 66




Plot 7-17. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 17)




Plot 7-18. Peak Power Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 27 of 66




Plot 7-19. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-20. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 28 of 66




Plot 7-21. Peak Power Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-22. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 29 of 66



Plot 7-23. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-24. Peak Power Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 30 of 66

7.4 Power Spectral Density – Bluetooth (LE)

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10:2020 – Section 11.10.2 Method PKPSD

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 31 of 66


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm / 3kHz]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2402	125 kbps	37	LE	5.99	8.0	-2.01
2440	125 kbps	17	LE	5.81	8.0	-2.19
2480	125 kbps	39	LE	5.84	8.0	-2.16
2402	500 kbps	37	LE	5.66	8.0	-2.34
2440	500 kbps	17	LE	5.72	8.0	-2.28
2480	500 kbps	39	LE	5.65	8.0	-2.35
2402	1 Mbps	37	LE	1.79	8.0	-6.21
2440	1 Mbps	17	LE	1.91	8.0	-6.09
2480	1 Mbps	39	LE	1.90	8.0	-6.10
2404	2 Mbps	0	LE	-1.74	8.0	-9.74
2440	2 Mbps	17	LE	-1.50	8.0	-9.50
2478	2 Mbps	36	LE	-1.97	8.0	-9.97

Table 7-4. Conducted Power Density Measurements

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 32 of 66




Plot 7-25. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 37)




Plot 7-26. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 33 of 66




Plot 7-27. Power Spectral Density Plot (Bluetooth (LE), 125kbps – Ch. 39)




Plot 7-28. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 37)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 34 of 66




Plot 7-29. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 17)




Plot 7-30. Power Spectral Density Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 35 of 66




Plot 7-31. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-32. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 36 of 66




Plot 7-33. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-34. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 37 of 66



Plot 7-35. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-36. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 38 of 66

7.5 Conducted Emissions at the Band Edge

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 39 of 66




Plot 7-37. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 37)




Plot 7-38. Band Edge Plot (Bluetooth (LE), 125kbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 40 of 66




Plot 7-39. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 37)




Plot 7-40. Band Edge Plot (Bluetooth (LE), 500kbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 41 of 66




Plot 7-41. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-42. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 42 of 66



Plot 7-43. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0)



Plot 7-44. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 43 of 66

7.6 Conducted Spurious Emissions

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11.3 of ANSI C63.10:2020.

Test Procedure Used

ANSI C63.10:2020 – Section 11.11.3

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 44 of 66


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 45 of 66




Plot 7-45. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-46. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 37)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 46 of 66




Plot 7-47. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 17)




Plot 7-48. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 47 of 66



Plot 7-49. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39)



Plot 7-50. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 48 of 66

7.7 Radiated Spurious Emission Measurements

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-5 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-5. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 – Section 6.6.4.3

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3kHz > 1/T
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to run for at least 50 times (1/duty cycle) traces

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 49 of 66

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-6 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-6. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Radiated Test Setup >1GHz

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 50 of 66

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of ANSI C63.10:2020 Section 11.12.2 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-5.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Average measurements were recorded using a VBW of 3kHz, per Section 4.1.4.2.3 of ANSI C63.10:2020, since 1/T is equal to just under 3kHz. This method was used because the EUT could not be configured to operate with a duty cycle > 98%. Both average and peak measurements were made using a peak detector
7. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
8. No significant radiated band edge emissions were found in the 2310 – 2390MHz restricted band.
9. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
10. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $[\text{dB}\mu\text{V/m}] = \text{Analyzer Level} [\text{dBm}] + 107 + \text{AFCL} [\text{dB/m}]$
- $\text{AFCL} [\text{dB/m}] = \text{Antenna Factor} [\text{dB/m}] + \text{Cable Loss} [\text{dB}]$
- $\text{Margin} [\text{dB}] = \text{Field Strength Level} [\text{dB}\mu\text{V/m}] - \text{Limit} [\text{dB}\mu\text{V/m}]$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain


FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 51 of 66

Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247(d)



Plot 7-51. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 37)




Plot 7-52. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 17)



Plot 7-53. Radiated Spurious Plot above 1GHz (Bluetooth (LE) – Ch. 39)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 52 of 66



Plot 7-54. Radiated Spurious Plot above 18GHz (Bluetooth (LE) – Ch. 17)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 53 of 66



Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Bluetooth Mode: LE – 125kbps
Distance of Measurements: 3 Meters
Operating Frequency: 2402MHz
Channel: 37

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4804.00	Avg	V	137	279	-77.69	6.31	35.62	53.98	-18.36
4804.00	Peak	V	137	279	-66.51	6.31	46.80	73.98	-27.18
12010.00	Avg	V	-	-	-81.80	18.49	43.69	53.98	-10.29
12010.00	Peak	V	-	-	-70.67	18.49	54.82	73.98	-19.16

Table 7-7. Radiated Measurements @ 3 meters

Bluetooth Mode: LE – 125kbps
Distance of Measurements: 3 Meters
Operating Frequency: 2440MHz
Channel: 17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
4880.00	Avg	V	137	274	-76.27	6.63	37.36	53.98	-16.62
4880.00	Peak	V	137	274	-65.01	6.63	48.62	73.98	-25.36
7320.00	Avg	V	134	288	-74.43	12.51	45.08	53.98	-8.90
7320.00	Peak	V	134	288	-63.76	12.51	55.75	73.98	-18.23
12200.00	Avg	V	-	-	-81.11	19.20	45.09	53.98	-8.89
12200.00	Peak	V	-	-	-70.52	19.20	55.68	73.98	-18.30

Table 7-8. Radiated Measurements @ 3 meters

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 54 of 66

Bluetooth Mode: LE – 125kbps
Distance of Measurements: 3 Meters
Operating Frequency: 2480MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	V	130	263	-77.83	6.99	36.16	53.98	-17.82
4960.00	Peak	V	130	263	-66.72	6.99	47.27	73.98	-26.71
7440.00	Avg	V	127	227	-73.09	12.70	46.61	53.98	-7.37
7440.00	Peak	V	127	227	-62.77	12.70	56.93	73.98	-17.05
12400.00	Avg	V	-	-	-81.53	19.50	44.97	53.98	-9.01
12400.00	Peak	V	-	-	-71.13	19.50	55.37	73.98	-18.61

Table 7-9. Radiated Measurements @ 3 meters

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 55 of 66


7.8 Radiated Restricted Band Edge Measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.


The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Bluetooth Mode:	LE – 2Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2478MHz
Channel:	36



Plot 7-55. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-56. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 56 of 66

7.9 Radiated Spurious Emissions Measurements – Below 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-10 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μ V/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-10. Radiated Limits

Test Procedures Used

ANSI C63.10:2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 57 of 66

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30Mhz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 58 of 66


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-10.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 59 of 66

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-57. Radiated Spurious Plot below 1GHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
75.00	Quasi-Peak	V	-	-	-91.97	14.79	29.82	40.00	-10.18
475.00	Quasi-Peak	V	-	-	-91.03	25.50	41.47	46.02	-4.55

Table 7-11. Radiated Spurious Emissions Below 1GHz

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 60 of 66

7.10 Line-Conducted Test Data

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-12. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 61 of 66

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 62 of 66



Plot 7-58. Line Conducted Plot with Bluetooth LE (L1)



Plot 7-59. Line Conducted Plot with Bluetooth LE (N)

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 63 of 66

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMA576B** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules. The data referenced from **FCC ID: A3LSMA576U** (Model SM-A576U1) included in this report have been reviewed and are deemed acceptable to support the compliance of **FCC ID: A3LSMA576B**.

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 64 of 66

9.0 APPENDIX A – DATA REFERENCING SPOT-CHECKS


The spot-check data presented in this section was measured on the variant model following the guidance of the FCC's Data Referencing guidance in KDB 484596 D01 v03. Each spot-check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device. For the worst-case RSE data, the measurement is determined by an actual emission and not by noise floor.

All test cases were performed to verify the variant EUT is still in compliance with the spot-checked results to the reference device and was performed using the guidance of ANSI C63.10-2020.

Notes

- Each spot check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.

Conducted Spot-Checks – SM-A576B/DS



Plot 9-1. Conducted Output Power Measurements (Spot-check)


FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset	Page 65 of 66

Radiated Spot-Checks – SM-A576B/DS

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7440.00	Avg	V	314	331	-72.78	15.34	49.56	53.98	-4.42

Table 9-1. RSE Measurements (Spot-check)

Bluetooth Mode: LE – 2Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2478MHz
Channel: 36



Plot 9-2. Radiated Restricted Upper Band Edge Measurement (Average) – Ant 1

FCC Rules	Test Item	Test Case	Units	Limit	Reference Model: SM-A576U1	Variant Model: SM-A576B/DS	Deviation (dB)	Max Deviation (dB)	Pass/Fail
15.247(b)(3)	Conducted Output Power	2M - CH0 - PEAK	dBm	N/A	17.78	17.14	-0.64	1	PASS
15.209	Radiated Spurious Emissions	Ch.39 - Average - 7440 MHz	dBμV/m	53.98	46.61	49.56	2.95	3	PASS
15.209	Radiated Band Edge Emissions	Ch.36 - Average	dBμV/m	53.98	46.67	43.90	-2.77	3	PASS

Table 9-2. Summary of Spot-checks

- END OF TEST REPORT -

FCC ID: A3LSMA576B	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Technical Manager
Test Report S/N: 1M2510280091-13.A3L	Test Dates: 10/29/2025-12/18/2025	EUT Type: Portable Handset		Page 66 of 66