



HEARING AID COMPATIBILITY

Applicant Name:
Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 16677, Korea

Date of Testing:
11/17/2025 – 12/05/2025
Test Site/Location:
Element Washington DC LLC,
Columbia, MD, USA
Test Report Serial No.:
1M2510280090-25.A3L
Date of Issue:
12/10/2025

FCC ID: A3LSMA576U

APPLICANT: SAMSUNG ELECTRONICS CO., LTD.

Scope of Test: RF Emissions Testing
Application Type: Certification
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2019
285076 D01 HAC Guidance v06r02
285076 D02 T-Coil testing for CMRS IP v04
DUT Type: Portable Handset
Model: SM-A576U1
Test Device Serial No.: Pre-Production Sample [S/N: 0103M]

HAC Compliance: PASS

This wireless portable device has been shown to be hearing-aid compatible as specified in ANSI/IEEE Std. C63.19-2019 and has been tested in accordance with the specified measurement procedures. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. Test results reported herein relate only to the item(s) tested. North America bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


RJ Ortanez
Executive Vice President



FCC ID: A3LSMA576U		HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 1 of 58

TEST REPORT REVISION HISTORY

Rev. No.	Report S/N	Description	Issue Date
A	1M2510280090-25.A3L	Initial Release	12/23/2025
B	1M2510280090-25.A3L	Editorial Changes	12/31/2025
C	1M2510280090-25.A3L	Editorial Changes	1/6/2026
D	1M2510280090-25.A3L	Editorial Changes	1/7/2026
E	1M2510280090-25.A3L	Revision Table Added	1/7/2026

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 2 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

TABLE OF CONTENTS

1.	INTRODUCTION	4
2.	DUT DESCRIPTION.....	5
3.	ANSI/IEEE C63.19-2019 PERFORMANCE REQUIREMENTS	7
4.	RF SYSTEM SPECIFICATIONS	8
5.	TEST PROCEDURE	13
6.	CONDUCTED POWER CONFIGURATIONS AND TARGETS	14
7.	JUSTIFICATION OF HELD TO EAR MODES TESTED	53
8.	EQUIPMENT LIST.....	54
9.	MEASUREMENT UNCERTAINTY	55
10.	CONCLUSION.....	56
11.	REFERENCES	57

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 3 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index
- Volume Control, receive volume control performance
- Volume Control, receive distortion and noise performance
- Volume Control, receive acoustic frequency response performance

The hearing aid may be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid *in-vitu*

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 4 of 58

2. DUT DESCRIPTION

FCC ID: A3LSMA576U
Manufacturer: Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 16677, Korea
Model: SM-A576U1
Serial Number: 0103M
Antenna Configurations: Internal Antenna
DUT Type: Portable Handset

I. LTE/NR Band Selection

This device supports LTE/NR capabilities with overlapping transmission frequency ranges. When the supported frequency range of a band falls completely within a band with a larger transmission frequency range, both bands have the same target power (or the band with the larger transmission frequency range has a higher target power), and both bands share the same transmission path and signal characteristics, hearing-aid compatibility compliance was only assessed for the band with the larger transmission frequency range. However, overlapping LTE bands which are anchor bands for dual connectivity (EN-DC) scenarios between LTE and NR were evaluated as independent LTE bands.

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 5 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

**Table 2-1
HAC Air Interfaces**

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service
GSM	850	VO	No ¹	Yes: WIFI or BT	CMRS Voice
	1900				
	GPRS/EDGE	VD	No ¹	Yes: WIFI or BT	Google Meet
UMTS	850	VD	No ¹	Yes: WIFI or BT	CMRS Voice
	1700				
	1900				
	HSPA	VD	No ¹	Yes: WIFI or BT	Google Meet
LTE (FDD)	680 (B71)	VD	No ¹	Yes: NR, WIFI or BT	VoLTE, Google Meet
	700 (B12)				
	780 (B13)				
	790 (B14)				
	850 (B5)				
	850 (B26)				
	1700 (B4)				
	1700 (B66)				
	1900 (B2)				
	1900 (B25)				
	2300 (B30)				
	2500 (B7)				
LTE (TDD)	2600 (B38)	VD	No ¹	Yes: NR, WIFI or BT	VoLTE, Google Meet
	2600 (B41)				
	3600 (B48)				
NR (FDD)	680 (n71)	VD	No ¹	Yes: LTE, WIFI or BT	VoNR, Google Meet
	850 (n5)				
	1700 (n70)				
	1700 (n66)				
	1900 (n2)				
	1900 (n25)				
NR (TDD)	2300 (n30)	VD	No ¹	Yes: LTE, WIFI or BT	VoNR, Google Meet
	2600 (n41)				
	3500 (n77, DoD)				
	3500 (n78, DoD)				
	3600 (n48)				
	3750 (n78)				
WIFI	3800 (n77)	VD	No ¹	Yes: GSM, UMTS, LTE, or NR	VoWIFI, Google Meet
	2450				
	5200 (U-NII 1)				
	5300 (U-NII 2A)				
	5500 (U-NII 2C)				
	5800 (U-NII 3)				
	5900 (U-NII 4)				
	6175 (U-NII 5)				
	6475 (U-NII 6)				
	6700 (U-NII 7)				
7000 (U-NII 8)					
BT	2450	DT	No	Yes: GSM, UMTS, LTE, or NR	N/A
Type Transport VO = Voice Only DT = Digital Data - Not intended for Voice Services VD = CMRS and/or IP Voice over Data Transport			Notes: 1. Evaluated for WD RF peak power level requirements. 2. NR FR2 bands are currently outside the scope of ANSI C63.19 and FCC HAC regulations therefore they were not evaluated. 3. WIFI U-NII band 5 was evaluated for operations which are entirely below 6GHz. Operations partially or entirely above 6GHz were not evaluated due to equipment limitations and being outside of the current scope of ANSI C63.19 and FCC HAC regulations. 4. WIFI U-NII bands 6 through 8 were not evaluated due to being outside of the current scope of ANSI C63.19 and FCC HAC regulations.		

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 6 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

3. ANSI/IEEE C63.19-2019 PERFORMANCE REQUIREMENTS

I. WD EMISSIONS Requirements

The ANSI Standard provides guidance on measuring the potential for wireless device (WD) RF emissions to cause audio frequency interference in a hearing aid. When the performance requirements of the Standard below are met, the WD demonstrates compliance to emission requirements for operation in close proximity with a hearing aid. The WD may demonstrate compliance by meeting any of the four requirements listed below for each of its operating bands.

Frequency Range (MHz)	RF _{AIPL} (dBm)
<960	29
960-2000	26
>2000	25

Table 3-1
WD RF audio interference power level requirements

Frequency Range (MHz)	RF _{Peak Power} (dBm)
<960	35
960-2000	32
>2000	31

Table 3-2
WD RF peak power level requirements

Frequency Range (MHz)	RF _{AIL} (dB(V/m))
<960	39
960-2000	36
>2000	35

Table 3-3
WD RF audio interference level requirements

Frequency Range (MHz)	RF _{Peak} (dB(V/m))
<960	29
960-2000	26
>2000	25

Table 3-4
WD RF peak near-field level requirements

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 7 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

4. RF SYSTEM SPECIFICATIONS

Description of test system for measurement of near-field RF audio interference level

EF3DV3 E-Field Probe Description

Construction:	One dipole parallel, two dipoles normal to probe axis Built-in shielding against static charges
Calibration:	In air from 30 MHz to 6.0 GHz (absolute accuracy $\pm 5.1\%$, $k=2$)
Frequency:	30 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.2 dB in air (rotation around probe axis) ± 0.4 dB in air (rotation normal to probe axis)
Dynamic Range	2 V/m to > 1000 V/m (M3 or better device readings fall well below diode compression point)
Linearity:	± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 4.0 mm (Body: 12 mm) Distance from probe tip to dipole centers: 1.5 mm





Figure 4-1
E-field Free-space
Probe

Probe Tip Description

HAC field measurements take place in the close near field with high gradients. Increasing the measuring distance from the source will generally decrease the measured field values (in case of the validation dipole approx. 10% per mm).

The electric field probes have an irregular internal geometry because it is physically not possible to have the 3 orthogonal sensors situated with the same center. The effect of the different sensor centers is accounted for in the HAC uncertainty budget ("sensor displacement").

Connector Plan



The antistatic shielding inside the probe is connected to the probe connector case.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 8 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Instrumentation Chain

Equation 1


Conversion of Connector Voltage u_i to E-Field E_i

$$E_i = \sqrt{\frac{u_i + (u_i^2 \cdot CF)/(DCP)}{Norm_i \cdot ConvF}}$$

whereby

E_i : electric field in V/m
 u_i : voltage of channel i at the connector in μV
 $Norm_i$: sensitivity of channel i in $\mu V/(V/m)^2$
 $ConvF$: enhancement factor in liquid ($ConvF=1$ for Air)
 DCP : diode compression point in μV
 CF : signal crest factor (peak power/average power)

Conditions of Calibration



Please note:

- a lower input impedance of the amplifier will result in different sensitivity factors $Norm_i$ and DCP
- larger bias currents will cause higher offset

Probe Response to Frequency

The E-field sensors have inherently a very flat frequency response. They are calibrated with a number of frequencies resulting in a common calibration factor, with the frequency behavior documented in the calibration certificate (See also below).

Frequency Response of E-Field

(TEM-Cell: if110 EXX, Waveguide R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Figure 4-2 E-Field Probe Frequency Response

FCC ID: A3LSMA576U	element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 9 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

SPEAG Robotic System

E-field measurements are performed using the DASY6 automated dosimetric assessment system. The DASY6 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Intel CORE i7 computer, near-field probe, probe alignment sensor, and the HAC phantom. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF).



Figure 4-3
SPEAG Robotic System

System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the computer with operating system and RF Measurement Software DASY6 v1.2.4 (with HAC Extension), A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 10 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

System Electronics

The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.




Figure 4-4
SPEAG Robotic System Diagram

DASY6 Instrumentation Chain

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

- with
- V_i

U_i

cf

dcp_i

= compensated signal of channel i

= input signal of channel i

= crest factor of exciting field

= diode compression point

(i = x, y, z)

(i = x, y, z)

(DASY parameter)

(DASY parameter)

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 11 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

From the compensated input signals the primary field data for each channel can be evaluated:

$$E - \text{fieldprobes : } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

with V_i = compensated signal of channel i (i = x, y, z)
 $Norm_i$ = sensor sensitivity of channel i (i = x, y, z)
 $\mu V/(V/m)^2$ for E-field Probes
 $ConvF$ = sensitivity enhancement in solution
 E_i = electric field strength of channel i in V/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

The measurement/integration time per point, as specified by the system manufacturer is >500ms.

The signal response time is evaluated as the time required by the system to reach 90% of the expected final value after an on/off switch of the power source with an integration time of 500ms and a probe response time of <5 ms. In the current implementation, DASY6 waits longer than 100ms after having reached the grid point before starting a measurement, i.e., the response time uncertainty is negligible.

If the device under test does not emit a CW signal, the integration time applied to measure the electric field at a specific point may introduce additional uncertainties due to the discretization. The tolerances for the different systems had the worst-case of 2.6%.

Environmental Conditions

Environmental conditions such as temperature and relative humidity are monitored to ensure there are no impacts on system specifications. Proper voltage and power line frequency conditions are maintained with three phase power sources. Environmental noise and reflections are monitored through system checks.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 12 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

5. TEST PROCEDURE

I. PEAK POWER LEVEL EVALUATION

To demonstrate hearing aid compliance with the ANSI standard C63.19-2019, an evaluation was performed using the peak power level requirements detailed in Table 3-2. Conducted power measurements were performed to verify maximum target power levels for all relevant operating bands/modes. An evaluation of each applicable air interface was performed to ensure compliance for each band.

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 13 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

6. CONDUCTED POWER CONFIGURATIONS AND TARGETS

I. Procedures Used to Establish RF Signal for HAC Testing

The handset was configured to transmit the required air interface in a shielded chamber. Measurements were taken with a fully charged battery.

II. HAC Target Powers

All applicable modes supported by the device have their held-to-ear conducted power targets listed below and were used for the individual mode evaluations in Section 7. All conducted power targets have a tolerance of +1.0dB and -1.5dB unless otherwise noted. For WIFI modes, the overall maximum power amongst all bands per IEEE standards is listed.

III. RF Conducted Power Measurement Setup and Conditions

Output Power Verification

Maximum output power is verified for all applicable test channels for all air interfaces which require HAC compliance. See Table 6-1 for air interface specific settings of transmit power parameters.

Table 6-1
Power Control Parameters and Settings by Air Interface

Air Interface:	Parameter Name:	Parameter Set To:
GSM	PCL	GSM850: "5"; GSM1900: "0"
UMTS	TPC	"All 1's"
LTE	TPC	"Max Power"
NR	PLS	"Max Power"
WIFI	PLS	Mfr Specified

The general setup for conducted powers included in Tables 6-11 to 6-77 is shown in Figure 6-1 below. The power measurement equipment could be a base station simulator, signal analyzer, or power meter depending on the applicable air interface.




Figure 6-1
Power Measurement Setup

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 14 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

IV. GSM Target Powers

Table 6-2
GSM Conducted Power Targets

Band	Modulated Average Output Power (in dBm)	
	Voice	Data
GSM/EDGE 850	33.0	27.0
GSM/EDGE 1900	30.0	27.0

V. UMTS Target Powers

Table 6-3
UMTS Conducted Power Targets

Band	Modulated Average Output Power (in dBm)	
	3GPP WCDMA Rel 99	3GPP HSUPA Rel 6
UMTS V	24.0	22.0
UMTS IV	23.5	22.0
UMTS II	23.5	22.0

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 15 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

VI. LTE FDD Target Powers

Table 6-4
LTE FDD Conducted Power Targets

LTE Band 71	24.0
LTE Band 12	24.5
LTE Band 13	24.0
LTE Band 14	24.0
LTE Band 5	24.0
LTE Band 26	24.0
LTE Band 4	23.5
LTE Band 66	23.5
LTE Band 2	23.5
LTE Band 25	23.5
LTE Band 30	23.0
LTE Band 7	23.5

VII. LTE TDD Target Powers

Table 6-5
LTE TDD Conducted Power Targets

Band	Modulated Average Output Power (in dBm)
LTE Band 38	23.0
LTE Band 41 PC3	23.0
LTE Band 48	23.5

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 16 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

VIII. NR FDD Target Powers

Table 6-6
NR FDD Conducted Power Targets

Band	Modulated Average Output Power (in dBm)
NR Band n71	24.0
NR Band n5	24.0
NR Band n70	23.5
NR Band n66	23.5
NR Band n2	23.5
NR Band n25	23.5
NR Band n30	22.5

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 17 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

IX. NR TDD Target Powers

Table 6-7
NR TDD Conducted Power Targets

Band	Modulated Average Output Power (in dBm)
NR Band n41 PC2	25.5
NR Band n48	22.0
NR Band n77 PC2	26.0
NR Band n78	26.0

X. WIFI Target Powers

Table 6-8
IEEE 802.11a/b/g/n/ac/ax Reduced Average RF Power Targets

Band	Modulated Average Output Power (in dBm)
WLAN - 2.4GHz	20.0
WLAN - 5GHz	18.0

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 18 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

XI. Conducted Power Measurements

Table 6-9
GSM850 Conducted Powers – Ant A

Band	Channel	GSM [dBm] CS (1 Slot)	EDGE [dBm] 1 Tx Slot
GSM 850	128	33.44	27.01
	190	33.56	27.33
	251	33.48	27.42

Table 6-10
GSM850 Conducted Powers – Ant E

Band	Channel	GSM [dBm] CS (1 Slot)	EDGE [dBm] 1 Tx Slot
GSM 850	128	26.30	26.17
	190	26.58	26.54
	251	26.53	26.79

Table 6-11
GSM1900 Conducted Powers – Ant A

Band	Channel	GSM [dBm] CS (1 Slot)	EDGE [dBm] 1 Tx Slot
GSM 1900	512	29.60	24.93
	661	29.87	24.95
	810	30.20	25.63

Table 6-12
UMTS Conducted Powers – Ant A

Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			AWS Band [dBm]			PCS Band [dBm]		
		4132	4183	4233	1312	1412	1513	9262	9400	9538
WCDMA	12.2 kbps RMC	24.35	24.37	24.33	23.37	22.83	23.32	20.32	20.15	20.24
	12.2 kbps AMR	24.30	24.34	24.20	23.20	22.91	23.36	20.34	20.17	20.24
HSUPA	Subtest 1	22.19	22.28	22.23	21.73	21.66	20.84	18.53	18.56	18.55

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 19 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-13
UMTS Conducted Powers – Ant E

Mode	3GPP 34.121 Subtest	Cellular Band [dBm]		
		4132	4183	4233
WCDMA	12.2 kbps RMC	20.79	20.95	20.87
	12.2 kbps AMR	20.77	20.91	20.80
HSUPA	Subtest 1	18.40	18.53	18.51

Table 6-14
LTE Band 71 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	133222	673.0	1 / 99	23.93
		133297	680.5	1 / 99	24.13
		133372	688.0	1 / 99	24.03
	16-QAM	133372	688.0	1 / 99	23.26
15 MHz	QPSK	133197	670.5	1 / 74	23.99
		133297	680.5	1 / 74	24.08
		133397	690.5	1 / 74	24.17
	16-QAM	133397	690.5	1 / 37	23.40
10 MHz	QPSK	133172	668.0	1 / 49	24.03
		133297	680.5	1 / 49	24.06
		133422	693.0	1 / 0	24.04
	16-QAM	133422	693.0	1 / 25	23.59
5 MHz	QPSK	133147	665.5	1 / 24	24.01
		133297	680.5	1 / 12	24.08
		133447	695.5	1 / 24	24.27
	16-QAM	133447	695.5	1 / 24	23.50

Table 6-15
LTE Band 71 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	133222	673.0	1 / 99	23.28
		133297	680.5	1 / 99	23.49
		133372	688.0	1 / 99	23.60
	16-QAM	133222	673.0	1 / 99	22.58
15 MHz	QPSK	133197	670.5	1 / 74	23.37
		133297	680.5	1 / 74	23.50
		133397	690.5	1 / 0	23.43
	16-QAM	133197	670.5	1 / 37	22.68
10 MHz	QPSK	133172	668.0	1 / 49	23.45
		133297	680.5	1 / 49	23.38
		133422	693.0	1 / 0	23.50
	16-QAM	133172	668.0	1 / 49	22.43
5 MHz	QPSK	133147	665.5	1 / 12	23.23
		133297	680.5	1 / 24	23.18
		133447	695.5	1 / 24	23.57
	16-QAM	133147	665.5	1 / 0	22.42

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 20 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-16
LTE Band 12 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	23060	704.0	1 / 0	24.96
		23095	707.5	1 / 0	24.88
		23130	711.0	1 / 0	24.91
	16-QAM	23130	711.0	1 / 0	24.22
5 MHz	QPSK	23035	701.5	1 / 24	24.91
		23095	707.5	1 / 0	24.94
		23155	713.5	1 / 0	24.84
	16-QAM	23155	713.5	1 / 0	24.44
3 MHz	QPSK	23025	700.5	1 / 0	24.89
		23095	707.5	1 / 0	24.88
		23165	714.5	1 / 7	24.80
	16-QAM	23095	707.5	1 / 7	24.44
1.4 MHz	QPSK	23017	699.7	1 / 5	24.86
		23095	707.5	1 / 0	24.93
		23173	715.3	1 / 0	24.38
	16-QAM	23095	707.5	1 / 0	24.26

Table 6-17
LTE Band 12 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	23060	704.0	1 / 49	24.45
		23095	707.5	1 / 0	24.40
		23130	711.0	1 / 0	24.33
	16-QAM	23060	704.0	1 / 49	23.66
		23095	707.5	1 / 25	23.65
		23130	711.0	1 / 0	23.44
5 MHz	QPSK	23035	701.5	1 / 12	24.34
		23095	707.5	1 / 0	24.39
		23155	713.5	1 / 0	24.30
	16-QAM	23035	701.5	1 / 0	23.90
		23095	707.5	1 / 12	23.76
		23155	713.5	1 / 12	23.85
3 MHz	QPSK	23025	700.5	1 / 0	24.36
		23095	707.5	1 / 14	24.38
		23165	714.5	1 / 0	24.39
	16-QAM	23025	700.5	1 / 7	23.75
		23095	707.5	1 / 7	23.81
		23165	714.5	1 / 0	23.65
1.4 MHz	QPSK	23017	699.7	1 / 0	24.42
		23095	707.5	1 / 5	24.33
		23173	715.3	1 / 0	24.14
	16-QAM	23017	699.7	1 / 0	23.69
		23095	707.5	1 / 0	23.77
		23173	715.3	1 / 0	23.56

FCC ID: A3LSMA576U		HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 21 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-18
LTE Band 13 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	23230	782.0	1 / 49	24.51
	16-QAM	23230	782.0	1 / 25	23.60
5 MHz	QPSK	23205	779.5	1 / 24	24.55
		23230	782.0	1 / 24	24.46
		23255	784.5	1 / 12	24.46
	16-QAM	23230	782.0	1 / 12	23.84

Table 6-19
LTE Band 13 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	23230	782.0	1 / 49	23.25
	16-QAM	23230	782.0	1 / 49	22.27
5 MHz	QPSK	23205	779.5	1 / 24	23.29
		23230	782.0	1 / 12	23.25
		23255	784.5	1 / 0	23.20
	16-QAM	23205	779.5	1 / 24	22.33

Table 6-20
LTE Band 14 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	23330	793.0	1 / 0	24.68
	16-QAM	23330	793.0	1 / 0	23.82
5 MHz	QPSK	23305	790.5	1 / 0	24.65
		23330	793.0	1 / 24	24.48
		23355	795.5	1 / 12	24.61
	16-QAM	23330	793.0	1 / 24	23.94

Table 6-21
LTE Band 14 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	23330	793.0	1 / 25	23.38
	16-QAM	23330	793.0	1 / 25	22.43
5 MHz	QPSK	23305	790.5	1 / 0	23.34
		23330	793.0	1 / 12	23.23
		23355	795.5	1 / 0	23.27
	16-QAM	23355	795.5	1 / 0	22.61

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 22 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-22
LTE Band 26/5 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
15 MHz (Band 26)	QPSK	26865	831.5	1 / 74	24.46
		26915	836.5	1 / 74	24.46
		26965	841.5	1 / 0	24.49
	16QAM	26865	831.5	1 / 74	23.46
		26915	836.5	1 / 74	23.40
		26965	841.5	1 / 0	23.38
10 MHz	QPSK	26840	829.0	1 / 49	24.50
		26915	836.5	1 / 25	24.74
		26990	844.0	1 / 25	24.60
	16QAM	26840	829.0	1 / 49	23.61
		26915	836.5	1 / 25	23.61
		26990	844.0	1 / 25	23.78
5 MHz	QPSK	26815	826.5	1 / 24	24.41
		26915	836.5	1 / 0	24.51
		27015	846.5	1 / 0	24.78
	16QAM	26815	826.5	1 / 24	23.30
		26915	836.5	1 / 0	23.51
		27015	846.5	1 / 0	23.49
3 MHz	QPSK	26805	825.5	1 / 0	24.25
		26915	836.5	1 / 0	24.58
		27025	847.5	1 / 7	24.48
	16QAM	26805	825.5	1 / 14	23.35
		26915	836.5	1 / 0	23.42
		27025	847.5	1 / 7	23.47
1.4 MHz	QPSK	26797	824.7	1 / 3	24.34
		26915	836.5	1 / 3	24.65
		27033	848.3	1 / 3	24.47
	16QAM	26797	824.7	1 / 3	23.28
		26915	836.5	1 / 3	23.36
		27033	848.3	1 / 3	23.76

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 23 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-23
LTE Band 26/5 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
15 MHz (Band 26)	QPSK	26865	831.5	1 / 74	24.21
		26915	836.5	1 / 74	24.11
		26965	841.5	1 / 0	23.88
	16QAM	26865	831.5	1 / 74	22.97
		26915	836.5	1 / 74	23.03
		26965	841.5	1 / 0	22.91
10 MHz	QPSK	26840	829.0	1 / 49	23.92
		26915	836.5	1 / 25	23.92
		26990	844.0	1 / 0	23.96
	16QAM	26840	829.0	1 / 49	22.90
		26915	836.5	1 / 25	23.09
		26990	844.0	1 / 0	23.02
5 MHz	QPSK	26815	826.5	1 / 0	23.82
		26915	836.5	1 / 24	23.91
		27015	846.5	1 / 0	23.96
	16QAM	26815	826.5	1 / 0	22.92
		26915	836.5	1 / 24	23.05
		27015	846.5	1 / 0	23.31
3 MHz	QPSK	26805	825.5	1 / 14	23.82
		26915	836.5	1 / 0	23.76
		27025	847.5	1 / 0	23.75
	16QAM	26805	825.5	1 / 14	22.78
		26915	836.5	1 / 0	23.03
		27025	847.5	1 / 0	22.80
1.4 MHz	QPSK	26797	824.7	1 / 5	23.74
		26915	836.5	1 / 3	23.95
		27033	848.3	1 / 3	23.79
	16QAM	26797	824.7	1 / 5	22.79
		26915	836.5	1 / 3	23.16
		27033	848.3	1 / 3	22.89

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 24 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-24
LTE Band 66/4 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	132072	1720.0	1 / 99	23.53
		132322	1745.0	1 / 99	23.71
		132572	1770.0	1 / 50	23.72
	16-QAM	132322	1745.0	1 / 0	22.86
15 MHz	QPSK	132047	1717.5	1 / 74	23.51
		132322	1745.0	1 / 37	23.75
		132597	1772.5	1 / 0	23.65
	16-QAM	132322	1745.0	1 / 74	22.97
10 MHz	QPSK	132022	1715.0	1 / 49	23.59
		132322	1745.0	1 / 49	23.76
		132622	1775.0	1 / 0	23.86
	16-QAM	132322	1745.0	1 / 25	22.99
5 MHz	QPSK	131997	1712.5	1 / 24	23.51
		132322	1745.0	1 / 24	23.80
		132647	1777.5	1 / 24	23.72
	16-QAM	132322	1745.0	1 / 24	23.15
3 MHz	QPSK	131987	1711.5	1 / 14	23.46
		132322	1745.0	1 / 14	23.86
		132657	1778.5	1 / 14	23.74
	16-QAM	132322	1745.0	1 / 7	23.22
1.4 MHz	QPSK	131979	1710.7	1 / 3	23.28
		132322	1745.0	1 / 3	23.71
		132665	1779.3	1 / 0	23.64
	16-QAM	132322	1745.0	1 / 5	23.05

Table 6-25
LTE Band 66/4 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	132072	1720.0	1 / 99	23.22
		132322	1745.0	1 / 99	23.09
		132572	1770.0	1 / 0	23.16
	16-QAM	132322	1745.0	1 / 99	22.35
15 MHz	QPSK	132047	1717.5	1 / 74	23.37
		132322	1745.0	1 / 37	23.18
		132597	1772.5	1 / 37	22.95
	16-QAM	132322	1745.0	1 / 37	22.52
10 MHz	QPSK	132022	1715.0	1 / 49	23.38
		132322	1745.0	1 / 49	23.07
		132622	1775.0	1 / 0	22.73
	16-QAM	132322	1745.0	1 / 49	22.40
5 MHz	QPSK	131997	1712.5	1 / 24	23.23
		132322	1745.0	1 / 12	23.27
		132647	1777.5	1 / 24	22.80
	16-QAM	132322	1745.0	1 / 24	22.57
3 MHz	QPSK	131987	1711.5	1 / 14	23.37
		132322	1745.0	1 / 0	23.20
		132657	1778.5	1 / 14	22.78
	16-QAM	132322	1745.0	1 / 14	22.45
1.4 MHz	QPSK	131979	1710.7	1 / 5	23.22
		132322	1745.0	1 / 0	23.18
		132665	1779.3	1 / 0	22.56
	16-QAM	132322	1745.0	1 / 5	22.42

FCC ID: A3LSMA576U		HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 25 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-26
LTE Band 25/2 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	26140	1860.0	1 / 99	23.75
		26365	1882.5	1 / 50	23.64
		26590	1905.0	1 / 0	23.69
	16-QAM	26140	1860.0	1 / 50	22.90
15 MHz	QPSK	26115	1857.5	1 / 37	23.77
		26365	1882.5	1 / 74	23.64
		26615	1907.5	1 / 0	23.75
	16-QAM	26115	1857.5	1 / 37	23.02
10 MHz	QPSK	26090	1855.0	1 / 49	23.70
		26365	1882.5	1 / 0	23.68
		26640	1910.0	1 / 49	23.69
	16-QAM	26090	1855.0	1 / 49	23.00
5 MHz	QPSK	26065	1852.5	1 / 24	23.65
		26365	1882.5	1 / 24	23.79
		26665	1912.5	1 / 0	23.73
	16-QAM	26065	1852.5	1 / 0	23.21
3 MHz	QPSK	26055	1851.5	1 / 7	23.67
		26365	1882.5	1 / 7	23.87
		26675	1913.5	1 / 14	23.72
	16-QAM	26055	1851.5	1 / 0	23.05
1.4 MHz	QPSK	26047	1850.7	1 / 5	23.64
		26365	1882.5	1 / 3	23.70
		26683	1914.3	1 / 3	23.62
	16-QAM	26365	1882.5	1 / 5	23.05

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 26 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-27
LTE Band 25/2 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	26140	1860.0	1 / 99	23.23
		26365	1882.5	1 / 50	23.36
		26590	1905.0	1 / 0	23.52
	16-QAM	26140	1860.0	1 / 50	22.54
		26365	1882.5	1 / 0	22.68
		26590	1905.0	1 / 0	22.26
15 MHz	QPSK	26115	1857.5	1 / 37	23.37
		26365	1882.5	1 / 37	23.52
		26615	1907.5	1 / 0	23.31
	16-QAM	26115	1857.5	1 / 0	22.62
		26365	1882.5	1 / 37	22.71
		26615	1907.5	1 / 0	22.40
10 MHz	QPSK	26090	1855.0	1 / 49	23.23
		26365	1882.5	1 / 49	23.47
		26640	1910.0	1 / 49	23.20
	16-QAM	26090	1855.0	1 / 49	22.57
		26365	1882.5	1 / 49	22.67
		26640	1910.0	1 / 49	22.44
5 MHz	QPSK	26065	1852.5	1 / 24	23.31
		26365	1882.5	1 / 0	23.54
		26665	1912.5	1 / 0	23.29
	16-QAM	26065	1852.5	1 / 24	22.63
		26365	1882.5	1 / 12	22.89
		26665	1912.5	1 / 12	22.53
3 MHz	QPSK	26055	1851.5	1 / 7	23.33
		26365	1882.5	1 / 7	23.40
		26675	1913.5	1 / 14	23.17
	16-QAM	26055	1851.5	1 / 0	22.32
		26365	1882.5	1 / 0	22.83
		26675	1913.5	1 / 7	22.37
1.4 MHz	QPSK	26047	1850.7	1 / 5	23.12
		26365	1882.5	1 / 0	23.52
		26683	1914.3	1 / 5	23.27
	16-QAM	26047	1850.7	1 / 3	22.22
		26365	1882.5	1 / 0	22.61
		26683	1914.3	1 / 3	22.27

Table 6-28
LTE Band 30 Conducted Powers – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	27710	2310.0	1 / 49	23.68
	16-QAM	27710	2310.0	1 / 49	22.40
5 MHz	QPSK	27685	2307.5	1 / 0	23.57
		27710	2310.0	1 / 24	23.48
		27735	2312.5	1 / 0	23.35
	16-QAM	27685	2307.5	1 / 0	22.62

FCC ID: A3LSMA576U		HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 27 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-29
LTE Band 30 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	QPSK	27710	2310.0	1 / 49	22.02
	16-QAM	27710	2310.0	1 / 49	21.31
5 MHz	QPSK	27685	2307.5	1 / 12	22.31
		27710	2310.0	1 / 0	22.26
		27735	2312.5	1 / 12	22.09
	16-QAM	27685	2307.5	1 / 12	21.45
		27710	2310.0	1 / 0	21.77
		27735	2312.5	1 / 12	21.76

Table 6-30
LTE Band 7 Conducted Powers – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	20850	2510.0	1 / 50	23.42
		21100	2535.0	1 / 0	23.15
		21350	2560.0	1 / 0	23.25
	16-QAM	20850	2510.0	1 / 50	22.90
		21100	2535.0	1 / 50	22.62
		21350	2560.0	1 / 0	22.59
15 MHz	QPSK	20825	2507.5	1 / 37	23.52
		21100	2535.0	1 / 37	23.26
		21375	2562.5	1 / 37	23.16
	16-QAM	20825	2507.5	1 / 37	22.91
		21100	2535.0	1 / 37	22.74
		21375	2562.5	1 / 37	22.48
10 MHz	QPSK	20800	2505.0	1 / 49	23.28
		21100	2535.0	1 / 0	23.04
		21400	2565.0	1 / 0	23.00
	16-QAM	20800	2505.0	1 / 49	22.68
		21100	2535.0	1 / 49	22.39
		21400	2565.0	1 / 0	22.63
5 MHz	QPSK	20775	2502.5	1 / 24	22.76
		21100	2535.0	1 / 0	23.23
		21425	2567.5	1 / 12	23.04
	16-QAM	20775	2502.5	1 / 24	22.18
		21100	2535.0	1 / 12	22.67
		21425	2567.5	1 / 12	22.57

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 28 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-31
LTE Band 7 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	20850	2510.0	1 / 50	23.17
		21100	2535.0	1 / 0	23.05
		21350	2560.0	1 / 0	23.05
	16-QAM	20850	2510.0	1 / 99	22.37
		21100	2535.0	1 / 99	22.43
		21350	2560.0	1 / 0	22.36
15 MHz	QPSK	20825	2507.5	1 / 74	23.01
		21100	2535.0	1 / 0	22.42
		21375	2562.5	1 / 74	22.71
	16-QAM	20825	2507.5	1 / 74	22.34
		21100	2535.0	1 / 37	21.88
		21375	2562.5	1 / 37	22.18
10 MHz	QPSK	20800	2505.0	1 / 0	23.06
		21100	2535.0	1 / 0	22.71
		21400	2565.0	1 / 0	22.73
	16-QAM	20800	2505.0	1 / 0	22.57
		21100	2535.0	1 / 49	22.26
		21400	2565.0	1 / 25	22.18
5 MHz	QPSK	20775	2502.5	1 / 0	23.12
		21100	2535.0	1 / 0	22.82
		21425	2567.5	1 / 12	22.74
	16-QAM	20775	2502.5	1 / 0	22.52
		21100	2535.0	1 / 12	22.46
		21425	2567.5	1 / 0	22.19

Table 6-32
LTE Band 41/38 Power Class 3 Conducted Powers – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	39750	2506.0	1 / 0	23.99
		40620	2593.0	1 / 0	23.29
		41490	2680.0	1 / 99	23.28
	16-QAM	39750	2506.0	1 / 0	22.01
		40620	2593.0	1 / 0	21.33
		41490	2680.0	1 / 99	21.35
15 MHz	QPSK	39725	2503.5	1 / 0	24.00
		40620	2593.0	1 / 0	23.31
		41515	2682.5	1 / 74	23.28
	16-QAM	39725	2503.5	1 / 0	22.04
		40620	2593.0	1 / 0	21.39
		41515	2682.5	1 / 74	21.29
10 MHz	QPSK	39700	2501.0	1 / 0	23.98
		40620	2593.0	1 / 0	23.33
		41540	2685.0	1 / 0	23.31
	16-QAM	39700	2501.0	1 / 0	22.02
		40620	2593.0	1 / 0	21.38
		41540	2685.0	1 / 0	21.32
5 MHz	QPSK	39675	2498.5	1 / 24	23.97
		40620	2593.0	1 / 24	23.38
		41565	2687.5	1 / 0	23.29
	16-QAM	39675	2498.5	1 / 24	21.99
		40620	2593.0	1 / 24	21.40
		41565	2687.5	1 / 0	21.36

FCC ID: A3LSMA576U		HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 29 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-33
LTE Band 41/38 Power Class 3 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	39750	2506.0	1 / 0	22.89
		40620	2593.0	1 / 99	23.13
		41490	2680.0	1 / 0	23.15
	16-QAM	39750	2506.0	1 / 0	22.08
		40620	2593.0	1 / 99	22.16
		41490	2680.0	1 / 0	22.19
15 MHz	QPSK	39725	2503.5	1 / 0	23.02
		40620	2593.0	1 / 74	23.19
		41515	2682.5	1 / 37	23.03
	16-QAM	39725	2503.5	1 / 0	22.03
		40620	2593.0	1 / 74	22.10
		41515	2682.5	1 / 37	22.28
10 MHz	QPSK	39700	2501.0	1 / 0	23.02
		40620	2593.0	1 / 49	23.09
		41540	2685.0	1 / 0	23.18
	16-QAM	39700	2501.0	1 / 0	22.02
		40620	2593.0	1 / 49	22.25
		41540	2685.0	1 / 0	22.14
5 MHz	QPSK	39675	2498.5	1 / 0	23.00
		40620	2593.0	1 / 24	23.09
		41565	2687.5	1 / 0	23.13
	16-QAM	39675	2498.5	1 / 0	22.00
		40620	2593.0	1 / 24	22.14
		41565	2687.5	1 / 0	22.23

Table 6-34
LTE Band 48 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	QPSK	55340	3560.0	1 / 49	23.88
		55990	3625.0	1 / 49	24.01
		56640	3690.0	1 / 49	23.74
	16-QAM	55340	3560.0	1 / 49	22.47
		55990	3625.0	1 / 49	22.66
		56640	3690.0	1 / 49	22.25
15 MHz	QPSK	55315	3557.5	1 / 19	23.58
		55990	3625.0	1 / 19	23.80
		56665	3692.5	1 / 36	23.52
	16-QAM	55315	3557.5	1 / 19	22.30
		55990	3625.0	1 / 19	21.14
		56665	3692.5	1 / 36	22.35
10 MHz	QPSK	55290	3555.0	1 / 22	23.83
		55990	3625.0	1 / 22	24.13
		56690	3695.0	1 / 1	24.06
	16-QAM	55290	3555.0	1 / 22	21.48
		55990	3625.0	1 / 22	22.19
		56690	3695.0	1 / 1	22.56
5 MHz	QPSK	55265	3552.5	1 / 5	23.85
		55990	3625.0	1 / 1	23.94
		56715	3697.5	1 / 5	23.67
	16-QAM	55265	3552.5	1 / 5	21.16
		55990	3625.0	1 / 1	21.82
		56715	3697.5	1 / 5	22.09

FCC ID: A3LSMA576U		HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 30 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-35
NR Band 71 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	$\pi/2$ BPSK	134600	673.0	1 / 53	24.28
		136100	680.5	1 / 104	24.49
		137600	688.0	1 / 53	24.68
	QPSK	134600	673.0	1 / 53	24.17
		136100	680.5	1 / 104	24.46
		137600	688.0	1 / 53	24.54
	16-QAM	137600	688.0	1 / 53	23.67
15 MHz	$\pi/2$ BPSK	134100	670.5	1 / 39	24.51
		136100	680.5	1 / 39	24.43
		138100	690.5	1 / 39	24.75
	QPSK	134100	670.5	1 / 39	24.52
		136100	680.5	1 / 39	24.47
		138100	690.5	1 / 39	24.73
	16-QAM	138100	690.5	1 / 39	23.61
10 MHz	$\pi/2$ BPSK	133600	668.0	1 / 26	24.43
		136100	680.5	1 / 26	24.48
		138600	693.0	1 / 26	24.72
	QPSK	133600	668.0	1 / 26	24.37
		136100	680.5	1 / 26	24.41
		138600	693.0	1 / 26	24.65
	16-QAM	138600	693.0	1 / 26	23.65
5 MHz	$\pi/2$ BPSK	133100	665.5	1 / 12	24.48
		136100	680.5	1 / 12	24.51
		139100	695.5	1 / 12	24.73
	QPSK	133100	665.5	1 / 12	24.40
		136100	680.5	1 / 12	24.51
		139100	695.5	1 / 12	24.73
	16-QAM	139100	695.5	1 / 12	23.70

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 31 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-36
NR Band 71 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	$\pi/2$ BPSK	134600	673.0	1 / 53	23.78
		136100	680.5	1 / 1	23.64
		137600	688.0	1 / 53	23.55
	QPSK	134600	673.0	1 / 53	23.69
		136100	680.5	1 / 1	23.63
		137600	688.0	1 / 1	23.41
	16-QAM	137600	688.0	1 / 53	22.45
15 MHz	$\pi/2$ BPSK	134100	670.5	1 / 39	23.89
		136100	680.5	1 / 1	23.58
		138100	690.5	1 / 39	23.45
	QPSK	134100	670.5	1 / 39	23.88
		136100	680.5	1 / 1	23.57
		138100	690.5	1 / 39	23.46
	16-QAM	138100	690.5	1 / 1	22.38
10 MHz	$\pi/2$ BPSK	133600	668.0	1 / 26	24.04
		136100	680.5	1 / 26	23.57
		138600	693.0	1 / 26	23.35
	QPSK	133600	668.0	1 / 26	23.95
		136100	680.5	1 / 1	23.54
		138600	693.0	1 / 26	23.36
	16-QAM	138600	693.0	1 / 1	22.34
5 MHz	$\pi/2$ BPSK	133100	665.5	1 / 1	23.99
		136100	680.5	1 / 12	23.59
		139100	695.5	1 / 12	23.36
	QPSK	133100	665.5	1 / 23	23.92
		136100	680.5	1 / 12	23.48
		139100	695.5	1 / 12	23.42
	16-QAM	139100	695.5	1 / 12	22.33

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 32 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-37
NR Band 5 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	$\pi/2$ BPSK	166800	834.0	1 / 104	24.42
		167300	836.5	1 / 104	24.42
		167800	839.0	1 / 104	24.72
	QPSK	166800	834.0	1 / 104	24.55
		167300	836.5	1 / 104	24.74
		167800	839.0	1 / 104	24.74
	16-QAM	166800	834.0	1 / 104	23.33
		167300	836.5	1 / 104	23.86
		167800	839.0	1 / 104	23.83
15 MHz	$\pi/2$ BPSK	166300	831.5	1 / 77	24.71
		167300	836.5	1 / 77	24.63
		168300	841.5	1 / 77	24.60
	QPSK	166300	831.5	1 / 77	24.62
		167300	836.5	1 / 77	24.69
		168300	841.5	1 / 77	24.44
	16-QAM	166300	831.5	1 / 77	23.75
		167300	836.5	1 / 77	23.69
		168300	841.5	1 / 77	23.78
10 MHz	$\pi/2$ BPSK	165800	829.0	1 / 50	24.51
		167300	836.5	1 / 50	24.57
		168800	844.0	1 / 26	24.62
	QPSK	165800	829.0	1 / 50	24.41
		167300	836.5	1 / 50	24.69
		168800	844.0	1 / 26	24.62
	16-QAM	165800	829.0	1 / 50	23.56
		167300	836.5	1 / 50	23.37
		168800	844.0	1 / 26	23.75
5 MHz	$\pi/2$ BPSK	165300	826.5	1 / 12	24.43
		167300	836.5	1 / 12	24.54
		169300	846.5	1 / 12	24.86
	QPSK	165300	826.5	1 / 12	24.52
		167300	836.5	1 / 12	24.71
		169300	846.5	1 / 12	24.96
	16-QAM	165300	826.5	1 / 12	23.55
		167300	836.5	1 / 12	23.71
		169300	846.5	1 / 12	23.85

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 33 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-38
NR Band 5 Conducted Powers – Ant E

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
20 MHz	$\pi/2$ BPSK	166800	834.0	1 / 104	23.79
		167300	836.5	1 / 104	23.74
		167800	839.0	1 / 104	23.75
	QPSK	166800	834.0	1 / 104	23.75
		167300	836.5	1 / 104	23.70
		167800	839.0	1 / 104	23.72
	16-QAM	166800	834.0	1 / 104	22.65
		167300	836.5	1 / 104	22.94
		167800	839.0	1 / 104	22.82
15 MHz	$\pi/2$ BPSK	166300	831.5	1 / 77	23.76
		167300	836.5	1 / 77	23.82
		168300	841.5	1 / 39	23.78
	QPSK	166300	831.5	1 / 77	23.77
		167300	836.5	1 / 77	23.88
		168300	841.5	1 / 39	23.80
	16-QAM	166300	831.5	1 / 77	22.87
		167300	836.5	1 / 77	22.89
		168300	841.5	1 / 39	22.84
10 MHz	$\pi/2$ BPSK	165800	829.0	1 / 50	23.67
		167300	836.5	1 / 26	23.79
		168800	844.0	1 / 26	23.76
	QPSK	165800	829.0	1 / 50	23.76
		167300	836.5	1 / 26	23.60
		168800	844.0	1 / 26	23.76
	16-QAM	165800	829.0	1 / 50	22.70
		167300	836.5	1 / 26	22.74
		168800	844.0	1 / 26	22.58
5 MHz	$\pi/2$ BPSK	165300	826.5	1 / 12	23.60
		167300	836.5	1 / 12	23.89
		169300	846.5	1 / 12	23.85
	QPSK	165300	826.5	1 / 12	23.56
		167300	836.5	1 / 12	23.94
		169300	846.5	1 / 12	23.98
	16-QAM	165300	826.5	1 / 12	22.62
		167300	836.5	1 / 12	22.77
		169300	846.5	1 / 12	22.86

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 34 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-39
NR Band 70 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
15 MHz	$\pi/2$ BPSK	340500	1702.5	1 / 39	23.81
	QPSK	340500	1702.5	1 / 1	23.52
	16-QAM	340500	1702.5	1 / 39	22.50
10 MHz	$\pi/2$ BPSK	340000	1700.0	1 / 1	23.84
		340500	1702.5	1 / 26	23.90
		341000	1705.0	1 / 26	23.93
	QPSK	340000	1700.0	1 / 1	23.58
		340500	1702.5	1 / 26	23.53
		341000	1705.0	1 / 1	23.60
	16-QAM	340000	1700.0	1 / 1	22.63
5 MHz	$\pi/2$ BPSK	339500	1697.5	1 / 12	23.99
		340500	1702.5	1 / 12	23.87
		341500	1707.5	1 / 12	23.97
	QPSK	339500	1697.5	1 / 12	23.75
		340500	1702.5	1 / 12	23.51
		341500	1707.5	1 / 12	23.63
	16-QAM	339500	1697.5	1 / 12	22.72

Table 6-40
NR Band 70 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
15 MHz	$\pi/2$ BPSK	340500	1702.5	1 / 39	23.87
	QPSK	340500	1702.5	1 / 39	23.51
	16-QAM	340500	1702.5	1 / 39	22.55
10 MHz	$\pi/2$ BPSK	340000	1700.0	1 / 26	23.72
		340500	1702.5	1 / 26	23.89
		341000	1705.0	1 / 26	23.98
	QPSK	340000	1700.0	1 / 50	23.56
		340500	1702.5	1 / 26	23.57
		341000	1705.0	1 / 26	23.65
	16-QAM	341000	1705.0	1 / 26	22.74
5 MHz	$\pi/2$ BPSK	339500	1697.5	1 / 12	23.84
		340500	1702.5	1 / 12	23.89
		341500	1707.5	1 / 12	23.93
	QPSK	339500	1697.5	1 / 12	23.70
		340500	1702.5	1 / 23	23.56
		341500	1707.5	1 / 12	23.72
	16-QAM	339500	1697.5	1 / 12	22.69

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 35 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-41
NR Band 66 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	346000	1730.0	1 / 108	23.54
		349000	1745.0	1 / 214	23.16
		352000	1760.0	1 / 214	23.69
	QPSK	346000	1730.0	1 / 1	23.51
		349000	1745.0	1 / 214	23.25
		352000	1760.0	1 / 108	23.53
	16-QAM	352000	1760.0	1 / 214	22.79
30 MHz	$\pi/2$ BPSK	345000	1725.0	1 / 80	23.55
		349000	1745.0	1 / 80	23.40
		353000	1765.0	1 / 80	23.62
	QPSK	345000	1725.0	1 / 1	23.51
		349000	1745.0	1 / 158	23.17
		353000	1765.0	1 / 80	23.58
	16-QAM	345000	1725.0	1 / 80	22.57
25 MHz	$\pi/2$ BPSK	344500	1722.5	1 / 1	23.58
		349000	1745.0	1 / 131	23.06
		353500	1767.5	1 / 66	23.59
	QPSK	344500	1722.5	1 / 1	23.61
		349000	1745.0	1 / 131	22.99
		353500	1767.5	1 / 66	23.51
	16-QAM	344500	1722.5	1 / 1	22.65
20 MHz	$\pi/2$ BPSK	344000	1720.0	1 / 1	23.65
		349000	1745.0	1 / 104	23.50
		354000	1770.0	1 / 53	23.67
	QPSK	344000	1720.0	1 / 1	23.66
		349000	1745.0	1 / 104	23.50
		354000	1770.0	1 / 53	23.63
	16-QAM	344000	1720.0	1 / 53	22.72
15 MHz	$\pi/2$ BPSK	343500	1717.5	1 / 1	23.68
		349000	1745.0	1 / 77	23.50
		354500	1772.5	1 / 39	23.71
	QPSK	343500	1717.5	1 / 1	23.56
		349000	1745.0	1 / 77	23.50
		354500	1772.5	1 / 39	23.65
	16-QAM	343500	1717.5	1 / 1	22.78
10 MHz	$\pi/2$ BPSK	343000	1715.0	1 / 1	23.81
		349000	1745.0	1 / 50	23.46
		355000	1775.0	1 / 26	23.94
	QPSK	343000	1715.0	1 / 1	23.85
		349000	1745.0	1 / 50	23.46
		355000	1775.0	1 / 26	23.77
	16-QAM	343000	1715.0	1 / 26	22.92
5 MHz	$\pi/2$ BPSK	342500	1712.5	1 / 12	23.89
		349000	1745.0	1 / 12	23.50
		355500	1777.5	1 / 12	23.98
	QPSK	342500	1712.5	1 / 12	23.84
		349000	1745.0	1 / 12	23.53
		355500	1777.5	1 / 12	23.95
	16-QAM	342500	1712.5	1 / 12	22.89

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 36 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-42
NR Band 66 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	346000	1730.0	1 / 108	23.38
		349000	1745.0	1 / 1	22.90
		352000	1760.0	1 / 108	23.17
	QPSK	346000	1730.0	1 / 108	23.22
		349000	1745.0	1 / 108	23.09
		352000	1760.0	1 / 108	23.04
	16-QAM	352000	1760.0	1 / 108	22.07
30 MHz	$\pi/2$ BPSK	345000	1725.0	1 / 80	23.37
		349000	1745.0	1 / 80	23.24
		353000	1765.0	1 / 80	23.07
	QPSK	345000	1725.0	1 / 80	23.27
		349000	1745.0	1 / 1	23.16
		353000	1765.0	1 / 1	23.06
	16-QAM	353000	1765.0	1 / 80	22.10
25 MHz	$\pi/2$ BPSK	344500	1722.5	1 / 66	23.35
		349000	1745.0	1 / 66	23.20
		353500	1767.5	1 / 66	23.04
	QPSK	344500	1722.5	1 / 66	23.16
		349000	1745.0	1 / 66	23.26
		353500	1767.5	1 / 1	22.99
	16-QAM	353500	1767.5	1 / 66	22.08
20 MHz	$\pi/2$ BPSK	344000	1720.0	1 / 53	23.30
		349000	1745.0	1 / 53	23.18
		354000	1770.0	1 / 53	22.96
	QPSK	344000	1720.0	1 / 53	23.18
		349000	1745.0	1 / 1	23.14
		354000	1770.0	1 / 1	22.91
	16-QAM	354000	1770.0	1 / 1	21.97
15 MHz	$\pi/2$ BPSK	343500	1717.5	1 / 39	23.31
		349000	1745.0	1 / 39	23.24
		354500	1772.5	1 / 39	22.85
	QPSK	343500	1717.5	1 / 39	23.26
		349000	1745.0	1 / 39	23.26
		354500	1772.5	1 / 1	22.82
	16-QAM	354500	1772.5	1 / 1	21.86
10 MHz	$\pi/2$ BPSK	343000	1715.0	1 / 26	23.37
		349000	1745.0	1 / 26	23.18
		355000	1775.0	1 / 26	22.97
	QPSK	343000	1715.0	1 / 26	23.28
		349000	1745.0	1 / 1	23.10
		355000	1775.0	1 / 1	22.87
	16-QAM	355000	1775.0	1 / 26	21.96
5 MHz	$\pi/2$ BPSK	342500	1712.5	1 / 12	23.14
		349000	1745.0	1 / 12	23.22
		355500	1777.5	1 / 12	22.89
	QPSK	342500	1712.5	1 / 12	23.23
		349000	1745.0	1 / 12	23.25
		355500	1777.5	1 / 12	22.88
	16-QAM	355500	1777.5	1 / 12	21.77

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 37 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-43
NR Band 25/2 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	374000	1870.0	1 / 108	24.37
		376500	1882.5	1 / 108	24.13
		379000	1895.0	1 / 108	24.18
	QPSK	374000	1870.0	1 / 108	24.29
		376500	1882.5	1 / 108	24.13
		379000	1895.0	1 / 108	24.15
	16-QAM	374000	1870.0	1 / 108	23.30
30 MHz	$\pi/2$ BPSK	372000	1865.0	1 / 80	24.33
		376500	1882.5	1 / 80	24.33
		381000	1900.0	1 / 80	24.28
	QPSK	372000	1865.0	1 / 80	24.35
		376500	1882.5	1 / 80	24.33
		381000	1900.0	1 / 80	24.28
	16-QAM	381000	1900.0	1 / 80	23.30
25 MHz	$\pi/2$ BPSK	372000	1862.5	1 / 66	24.38
		376500	1882.5	1 / 66	24.46
		381000	1902.5	1 / 66	24.31
	QPSK	372000	1862.5	1 / 66	24.37
		376500	1882.5	1 / 66	24.41
		381000	1902.5	1 / 66	24.30
	16-QAM	381000	1902.5	1 / 66	23.25
20 MHz	$\pi/2$ BPSK	372000	1860.0	1 / 53	24.41
		376500	1882.5	1 / 53	24.35
		381000	1905.0	1 / 53	24.40
	QPSK	372000	1860.0	1 / 53	24.35
		376500	1882.5	1 / 53	24.32
		381000	1905.0	1 / 53	24.41
	16-QAM	372000	1860.0	1 / 53	23.46
15 MHz	$\pi/2$ BPSK	371500	1857.5	1 / 39	24.46
		376500	1882.5	1 / 39	24.41
		381500	1907.5	1 / 77	24.27
	QPSK	371500	1857.5	1 / 39	24.46
		376500	1882.5	1 / 39	24.42
		381500	1907.5	1 / 77	24.24
	16-QAM	371500	1857.5	1 / 39	23.39
10 MHz	$\pi/2$ BPSK	371000	1855.0	1 / 26	24.40
		376500	1882.5	1 / 26	24.35
		382000	1910.0	1 / 26	24.44
	QPSK	371000	1855.0	1 / 26	24.32
		376500	1882.5	1 / 26	24.29
		382000	1910.0	1 / 26	24.38
	16-QAM	382000	1910.0	1 / 26	23.39
5 MHz	$\pi/2$ BPSK	370500	1852.5	1 / 12	24.40
		376500	1882.5	1 / 12	24.38
		382500	1912.5	1 / 12	24.46
	QPSK	370500	1852.5	1 / 12	24.35
		376500	1882.5	1 / 12	24.37
		382500	1912.5	1 / 12	24.45
	16-QAM	382500	1912.5	1 / 12	23.28

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 38 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-44
NR Band 25/2 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	374000	1870.0	1 / 108	23.76
		376500	1882.5	1 / 108	23.85
		379000	1895.0	1 / 108	23.93
	QPSK	374000	1870.0	1 / 108	23.60
		376500	1882.5	1 / 108	23.78
		379000	1895.0	1 / 108	23.92
	16-QAM	374000	1870.0	1 / 108	22.59
		376500	1882.5	1 / 108	22.82
		379000	1895.0	1 / 108	22.87
30 MHz	$\pi/2$ BPSK	372000	1865.0	1 / 158	23.68
		376500	1882.5	1 / 80	23.87
		381000	1900.0	1 / 80	23.96
	QPSK	372000	1865.0	1 / 158	23.56
		376500	1882.5	1 / 80	23.82
		381000	1900.0	1 / 80	23.92
	16-QAM	372000	1865.0	1 / 158	22.75
		376500	1882.5	1 / 80	22.88
		381000	1900.0	1 / 80	22.90
25 MHz	$\pi/2$ BPSK	372000	1862.5	1 / 66	23.71
		376500	1882.5	1 / 66	23.95
		381000	1902.5	1 / 66	23.96
	QPSK	372000	1862.5	1 / 66	23.64
		376500	1882.5	1 / 66	23.89
		381000	1902.5	1 / 66	23.92
	16-QAM	372000	1862.5	1 / 66	22.72
		376500	1882.5	1 / 66	22.89
		381000	1902.5	1 / 66	23.08
20 MHz	$\pi/2$ BPSK	372000	1860.0	1 / 104	23.73
		376500	1882.5	1 / 53	23.88
		381000	1905.0	1 / 104	23.96
	QPSK	372000	1860.0	1 / 104	23.53
		376500	1882.5	1 / 53	23.85
		381000	1905.0	1 / 104	23.93
	16-QAM	372000	1860.0	1 / 104	22.56
		376500	1882.5	1 / 53	22.91
		381000	1905.0	1 / 104	22.98
15 MHz	$\pi/2$ BPSK	371500	1857.5	1 / 77	23.58
		376500	1882.5	1 / 77	23.94
		381500	1907.5	1 / 77	23.97
	QPSK	371500	1857.5	1 / 77	23.54
		376500	1882.5	1 / 77	23.93
		381500	1907.5	1 / 77	23.93
	16-QAM	371500	1857.5	1 / 77	22.62
		376500	1882.5	1 / 77	22.91
		381500	1907.5	1 / 77	23.02
10 MHz	$\pi/2$ BPSK	371000	1855.0	1 / 26	23.84
		376500	1882.5	1 / 26	23.95
		382000	1910.0	1 / 26	23.98
	QPSK	371000	1855.0	1 / 26	23.76
		376500	1882.5	1 / 26	23.94
		382000	1910.0	1 / 26	23.97
	16-QAM	371000	1855.0	1 / 26	22.57
		376500	1882.5	1 / 26	22.98
		382000	1910.0	1 / 26	23.33
5 MHz	$\pi/2$ BPSK	370500	1852.5	1 / 12	23.94
		376500	1882.5	1 / 12	23.92
		382500	1912.5	1 / 12	23.99
	QPSK	370500	1852.5	1 / 12	23.84
		376500	1882.5	1 / 12	23.87
		382500	1912.5	1 / 12	23.97
	16-QAM	370500	1852.5	1 / 12	22.74
		376500	1882.5	1 / 12	23.17
		382500	1912.5	1 / 12	23.25

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 39 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-45
NR Band 30 Conducted Powers – Ant A

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	$\pi/2$ BPSK	27710	2310.0	1 / 1	23.50
	QPSK	27710	2310.0	1 / 1	23.37
	16-QAM	27710	2310.0	1 / 1	22.20
5 MHz	$\pi/2$ BPSK	27685	2307.5	1 / 1	23.14
		27710	2310.0	1 / 12	23.18
		27735	2312.5	1 / 23	23.29
	QPSK	27685	2307.5	1 / 1	23.09
		27710	2310.0	1 / 12	23.19
		27735	2312.5	1 / 23	23.15
	16-QAM	27685	2307.5	1 / 1	22.16
		27710	2310.0	1 / 12	21.96
		27735	2312.5	1 / 23	22.12

Table 6-46
NR Band 30 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
10 MHz	$\pi/2$ BPSK	27710	2310.0	1 / 1	21.72
	QPSK	27710	2310.0	1 / 1	21.69
	16-QAM	27710	2310.0	1 / 1	20.59
5 MHz	$\pi/2$ BPSK	27685	2307.5	1 / 1	21.88
		27710	2310.0	1 / 1	21.81
		27735	2312.5	1 / 12	21.63
	QPSK	27685	2307.5	1 / 1	21.63
		27710	2310.0	1 / 1	21.59
		27735	2312.5	1 / 12	21.46
	16-QAM	27685	2307.5	1 / 1	20.63
		27710	2310.0	1 / 1	20.45
		27735	2312.5	1 / 12	20.30

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 40 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-47
NR Band 41 Power Class 3 Conducted Powers (100MHz through 50MHz) – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
100 MHz	$\pi/2$ BPSK	509202	2546.01	1 / 1	23.82
		518598	2592.99	1 / 136	23.75
		528000	2640.00	1 / 136	23.75
	QPSK	509202	2546.01	1 / 1	23.97
		518598	2592.99	1 / 136	23.91
		528000	2640.00	1 / 136	23.70
	16-QAM	509202	2546.01	1 / 1	22.69
		518598	2592.99	1 / 136	22.49
		528000	2640.00	1 / 136	22.41
90 MHz	$\pi/2$ BPSK	508200	2541.00	1 / 122	23.84
		518598	2592.99	1 / 122	23.74
		528996	2644.98	1 / 122	23.76
	QPSK	508200	2541.00	1 / 1	23.91
		518598	2592.99	1 / 122	23.90
		528996	2644.98	1 / 122	23.89
	16-QAM	508200	2541.00	1 / 1	22.61
		518598	2592.99	1 / 122	22.50
		528996	2644.98	1 / 122	22.57
80 MHz	$\pi/2$ BPSK	507204	2536.02	1 / 1	23.82
		518598	2592.99	1 / 108	23.76
		529998	2649.99	1 / 108	23.79
	QPSK	507204	2536.02	1 / 1	23.93
		518598	2592.99	1 / 108	23.86
		529998	2649.99	1 / 108	23.90
	16-QAM	507204	2536.02	1 / 1	22.71
		518598	2592.99	1 / 108	22.51
		529998	2649.99	1 / 108	22.54
70 MHz	$\pi/2$ BPSK	506202	2531.01	1 / 1	23.80
		518598	2592.99	1 / 94	23.75
		531000	2655.00	1 / 94	23.92
	QPSK	506202	2531.01	1 / 1	23.92
		518598	2592.99	1 / 94	23.86
		531000	2655.00	1 / 94	23.90
	16-QAM	506202	2531.01	1 / 1	22.63
		518598	2592.99	1 / 94	22.49
		531000	2655.00	1 / 94	22.49
60 MHz	$\pi/2$ BPSK	505200	2526.00	1 / 1	23.76
		518598	2592.99	1 / 81	23.78
		531996	2659.98	1 / 81	23.87
	QPSK	505200	2526.00	1 / 1	23.93
		518598	2592.99	1 / 81	23.99
		531996	2659.98	1 / 81	23.81
	16-QAM	505200	2526.00	1 / 1	22.64
		518598	2592.99	1 / 81	22.57
		531996	2659.98	1 / 81	22.67
50 MHz	$\pi/2$ BPSK	504204	2521.02	1 / 66	23.91
		518598	2592.99	1 / 66	23.71
		532998	2664.99	1 / 66	23.92
	QPSK	504204	2521.02	1 / 1	23.98
		518598	2592.99	1 / 66	23.88
		532998	2664.99	1 / 66	23.90
	16-QAM	504204	2521.02	1 / 1	22.64
		518598	2592.99	1 / 66	22.46
		532998	2664.99	1 / 66	22.69

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 41 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-48
NR Band 41 Power Class 3 Conducted Powers (40MHz through 10MHz) – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	503202	2516.01	1 / 53	23.70
		518598	2592.99	1 / 53	23.86
		534000	2670.00	1 / 53	23.94
	QPSK	503202	2516.01	1 / 53	23.72
		518598	2592.99	1 / 53	23.92
		534000	2670.00	1 / 53	23.88
	16-QAM	503202	2516.01	1 / 53	22.46
		518598	2592.99	1 / 53	22.60
		534000	2670.00	1 / 53	22.61
30 MHz	$\pi/2$ BPSK	502200	2511.00	1 / 39	23.74
		518598	2592.99	1 / 39	23.85
		534996	2674.98	1 / 39	23.86
	QPSK	502200	2511.00	1 / 76	23.78
		518598	2592.99	1 / 39	23.93
		534996	2674.98	1 / 39	23.97
	16-QAM	502200	2511.00	1 / 39	22.63
		518598	2592.99	1 / 39	22.59
		534996	2674.98	1 / 39	22.68
20 MHz	$\pi/2$ BPSK	501204	2506.02	1 / 49	23.69
		518598	2592.99	1 / 25	23.73
		535998	2679.99	1 / 1	23.73
	QPSK	501204	2506.02	1 / 49	23.74
		518598	2592.99	1 / 25	23.88
		535998	2679.99	1 / 1	23.89
	16-QAM	501204	2506.02	1 / 25	22.56
		518598	2592.99	1 / 25	22.50
		535998	2679.99	1 / 1	22.52
15 MHz	$\pi/2$ BPSK	500706	2503.50	1 / 19	23.65
		518598	2592.99	1 / 19	23.81
		536449	2682.50	1 / 1	23.68
	QPSK	500706	2503.50	1 / 19	23.68
		518598	2592.99	1 / 19	23.98
		536449	2682.50	1 / 1	23.83
	16-QAM	500706	2503.50	1 / 19	22.88
		518598	2592.99	1 / 19	22.56
		536449	2682.50	1 / 1	22.47
10 MHz	$\pi/2$ BPSK	500208	2501.00	1 / 22	23.79
		518598	2592.99	1 / 12	23.83
		537000	2685.00	1 / 1	23.53
	QPSK	500208	2501.00	1 / 22	23.84
		518598	2592.99	1 / 12	23.99
		537000	2685.00	1 / 1	23.69
	16-QAM	500208	2501.00	1 / 12	22.82
		518598	2592.99	1 / 12	22.58
		537000	2685.00	1 / 1	22.35

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 42 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-49
NR Band 41 Power Class 2 Conducted Powers (100MHz through 50MHz) – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
100 MHz	$\pi/2$ BPSK	509202	2546.01	1 / 271	26.35
		518598	2592.99	1 / 136	26.33
		528000	2640.00	1 / 1	26.30
	QPSK	509202	2546.01	1 / 271	26.37
		518598	2592.99	1 / 136	26.29
		528000	2640.00	1 / 1	26.32
	16-QAM	509202	2546.01	1 / 271	26.02
90 MHz	$\pi/2$ BPSK	508200	2541.00	1 / 243	26.14
		518598	2592.99	1 / 122	26.32
		528996	2644.98	1 / 1	26.37
	QPSK	508200	2541.00	1 / 243	26.15
		518598	2592.99	1 / 122	26.29
		528996	2644.98	1 / 1	26.37
	16-QAM	508200	2541.00	1 / 243	25.82
80 MHz	$\pi/2$ BPSK	507204	2536.02	1 / 215	25.76
		518598	2592.99	1 / 108	26.32
		529998	2649.99	1 / 1	26.34
	QPSK	507204	2536.02	1 / 215	25.78
		518598	2592.99	1 / 108	26.30
		529998	2649.99	1 / 1	26.40
	16-QAM	518598	2592.99	1 / 108	25.94
70 MHz	$\pi/2$ BPSK	506202	2531.01	1 / 187	25.64
		518598	2592.99	1 / 94	26.33
		531000	2655.00	1 / 1	26.16
	QPSK	506202	2531.01	1 / 187	25.64
		518598	2592.99	1 / 94	26.30
		531000	2655.00	1 / 1	26.18
	16-QAM	518598	2592.99	1 / 94	25.92
60 MHz	$\pi/2$ BPSK	505200	2526.00	1 / 160	25.45
		518598	2592.99	1 / 81	26.37
		531996	2659.98	1 / 1	25.88
	QPSK	505200	2526.00	1 / 160	25.45
		518598	2592.99	1 / 81	26.34
		531996	2659.98	1 / 1	25.90
	16-QAM	518598	2592.99	1 / 81	25.99
50 MHz	$\pi/2$ BPSK	504204	2521.02	1 / 131	25.38
		518598	2592.99	1 / 66	26.30
		532998	2664.99	1 / 1	25.66
	QPSK	504204	2521.02	1 / 131	25.41
		518598	2592.99	1 / 131	26.29
		532998	2664.99	1 / 1	25.67
	16-QAM	518598	2592.99	1 / 131	25.94

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 43 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-50
NR Band 41 Power Class 2 Conducted Powers (40MHz through 10MHz) – Ant B

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	503202	2516.01	1 / 104	25.23
		518598	2592.99	1 / 53	26.33
		534000	2670.00	1 / 1	25.54
	QPSK	503202	2516.01	1 / 104	25.24
		518598	2592.99	1 / 104	26.34
		534000	2670.00	1 / 1	25.53
	16-QAM	518598	2592.99	1 / 104	25.95
30 MHz	$\pi/2$ BPSK	502200	2511.00	1 / 76	25.21
		518598	2592.99	1 / 76	26.38
		534996	2674.98	1 / 1	25.41
	QPSK	502200	2511.00	1 / 76	25.22
		518598	2592.99	1 / 76	26.38
		534996	2674.98	1 / 1	25.43
	16-QAM	518598	2592.99	1 / 76	25.97
20 MHz	$\pi/2$ BPSK	501204	2506.02	1 / 25	25.13
		518598	2592.99	1 / 49	26.38
		535998	2679.99	1 / 1	25.30
	QPSK	501204	2506.02	1 / 1	25.07
		518598	2592.99	1 / 49	26.39
		535998	2679.99	1 / 1	25.32
	16-QAM	518598	2592.99	1 / 49	26.05
15 MHz	$\pi/2$ BPSK	500706	2503.50	1 / 19	25.17
		518598	2592.99	1 / 36	26.36
		536449	2682.50	1 / 1	25.22
	QPSK	500706	2503.50	1 / 36	25.14
		518598	2592.99	1 / 36	26.36
		536449	2682.50	1 / 1	25.23
	16-QAM	518598	2592.99	1 / 36	25.98
10 MHz	$\pi/2$ BPSK	500208	2501.00	24 / 0	25.11
		518598	2592.99	1 / 22	26.35
		537000	2685.00	1 / 1	25.07
	QPSK	500208	2501.00	1 / 22	25.12
		518598	2592.99	1 / 22	26.35
		537000	2685.00	1 / 1	25.08
	16-QAM	518598	2592.99	1 / 22	26.01

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 44 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-51
NR Band 48 Conducted Powers – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	TT/2 BPSK	638000	3570.0	1 / 53	22.60
		641666	3625.0	1 / 1	22.34
		645332	3680.0	1 / 53	22.34
	QPSK	638000	3570.0	1 / 53	22.58
		641666	3625.0	1 / 1	22.33
		645332	3680.0	1 / 53	22.28
	16-QAM	638000	3570.0	1 / 53	21.13
		641666	3625.0	1 / 1	21.35
		645332	3680.0	1 / 53	21.98
30 MHz	TT/2 BPSK	637666	3565.0	1 / 1	22.49
		641666	3625.0	1 / 1	22.38
		645666	3685.0	1 / 39	22.38
	QPSK	637666	3565.0	1 / 1	22.58
		641666	3625.0	1 / 1	22.23
		645666	3685.0	1 / 39	22.25
	16-QAM	637666	3565.0	1 / 1	21.68
		641666	3625.0	1 / 1	21.31
		645666	3685.0	1 / 39	21.35
20 MHz	TT/2 BPSK	637334	3560.0	1 / 1	21.56
		641666	3625.0	1 / 25	22.35
		646000	3690.0	1 / 25	22.43
	QPSK	637334	3560.0	1 / 49	21.46
		641666	3625.0	1 / 25	22.58
		646000	3690.0	1 / 25	22.45
	16-QAM	637334	3560.0	1 / 49	20.35
		641666	3625.0	1 / 25	21.93
		646000	3690.0	1 / 25	21.89
15 MHz	TT/2 BPSK	637166	3557.5	1 / 1	21.56
		641666	3625.0	1 / 19	22.34
		646166	3692.5	1 / 19	22.45
	QPSK	637166	3557.5	1 / 1	21.63
		641666	3625.0	1 / 19	22.13
		646166	3692.5	1 / 19	22.21
	16-QAM	637166	3557.5	1 / 1	20.73
		641666	3625.0	1 / 19	21.75
		646166	3692.5	1 / 19	21.79
10 MHz	TT/2 BPSK	637000	3555.0	1 / 12	21.41
		641666	3625.0	1 / 12	22.03
		646332	3695.0	1 / 12	21.53
	QPSK	637000	3555.0	1 / 12	21.32
		641666	3625.0	1 / 12	21.46
		646332	3695.0	1 / 12	21.32
	16-QAM	637000	3555.0	1 / 12	21.26
		641666	3625.0	1 / 12	21.13
		646332	3695.0	1 / 12	21.12

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 45 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-52
NR Band 77 Power Class 2 Conducted Powers (100MHz through 50MHz) – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
100 MHz	$\pi/2$ BPSK	650000	3750.00	1 / 1	24.83
		656000	3840.00	1 / 271	25.77
		662000	3930.00	1 / 136	25.86
	QPSK	650000	3750.00	1 / 1	24.81
		656000	3840.00	1 / 271	25.75
		662000	3930.00	1 / 136	25.96
	16-QAM	650000	3750.00	1 / 1	23.96
		656000	3840.00	1 / 271	24.91
		662000	3930.00	1 / 136	25.05
90 MHz	$\pi/2$ BPSK	649668	3745.02	1 / 1	24.86
		656000	3840.00	1 / 243	25.75
		662332	3934.98	1 / 122	26.03
	QPSK	649668	3745.02	1 / 1	24.85
		656000	3840.00	1 / 243	25.75
		662332	3934.98	1 / 122	25.97
	16-QAM	649668	3745.02	1 / 1	23.98
		656000	3840.00	1 / 243	24.90
		662332	3934.98	1 / 122	25.07
80 MHz	$\pi/2$ BPSK	649334	3740.01	1 / 1	24.84
		656000	3840.00	1 / 215	25.72
		662666	3939.99	1 / 108	25.86
	QPSK	649334	3740.01	1 / 1	24.84
		656000	3840.00	1 / 215	25.71
		662666	3939.99	1 / 108	25.79
	16-QAM	649334	3740.01	1 / 1	23.96
		656000	3840.00	1 / 215	24.86
		662666	3939.99	1 / 108	24.96
70 MHz	$\pi/2$ BPSK	649000	3735.00	1 / 1	24.85
		656000	3840.00	1 / 187	25.69
		663000	3945.00	1 / 1	25.77
	QPSK	649000	3735.00	1 / 1	24.86
		656000	3840.00	1 / 187	25.68
		663000	3945.00	1 / 94	25.82
	16-QAM	649000	3735.00	1 / 1	23.99
		656000	3840.00	1 / 187	24.82
		663000	3945.00	1 / 94	24.91
60 MHz	$\pi/2$ BPSK	648668	3730.02	1 / 1	24.89
		656000	3840.00	1 / 160	25.64
		663332	3949.98	1 / 81	25.75
	QPSK	648668	3730.02	1 / 1	24.89
		656000	3840.00	1 / 160	25.66
		663332	3949.98	1 / 81	25.78
	16-QAM	648668	3730.02	1 / 1	24.01
		656000	3840.00	1 / 160	24.80
		663332	3949.98	1 / 81	24.93
50 MHz	$\pi/2$ BPSK	648334	3725.01	1 / 1	25.01
		656000	3840.00	1 / 131	25.67
		663666	3954.99	1 / 66	25.94
	QPSK	648334	3725.01	1 / 1	25.02
		656000	3840.00	1 / 131	25.68
		663666	3954.99	1 / 1	25.89
	16-QAM	648334	3725.01	1 / 1	24.14
		656000	3840.00	1 / 131	24.81
		663666	3954.99	1 / 1	25.04

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset	Page 46 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-53
NR Band 77 Power Class 2 Conducted Powers (40MHz through 10MHz) – Ant F

Bandwidth	Modulation	Channel	Frequency [MHz]	RB Size/Offset	Conducted Power [dBm]
40 MHz	$\pi/2$ BPSK	648000	3720.00	1 / 1	25.02
		656000	3840.00	1 / 104	25.55
		664000	3960.00	1 / 53	25.76
	QPSK	648000	3720.00	1 / 1	25.03
		656000	3840.00	1 / 104	25.57
		664000	3960.00	1 / 1	25.78
	16-QAM	648000	3720.00	1 / 53	24.19
		656000	3840.00	1 / 104	24.71
		664000	3960.00	1 / 1	24.91
30 MHz	$\pi/2$ BPSK	647668	3715.02	1 / 39	24.97
		656000	3840.00	1 / 76	25.50
		664332	3964.98	1 / 39	25.81
	QPSK	647668	3715.02	1 / 39	24.93
		656000	3840.00	1 / 76	25.52
		664332	3964.98	1 / 39	25.79
	16-QAM	647668	3715.02	1 / 1	24.04
		656000	3840.00	1 / 76	24.65
		664332	3964.98	1 / 1	24.88
25 MHz	$\pi/2$ BPSK	647500	3712.50	1 / 32	25.03
		656000	3840.00	1 / 63	25.46
		664500	3967.50	1 / 32	25.63
	QPSK	647500	3712.50	1 / 32	25.08
		656000	3840.00	1 / 63	25.48
		664500	3967.50	1 / 32	25.68
	16-QAM	647500	3712.50	1 / 32	24.21
		656000	3840.00	1 / 63	24.63
		664500	3967.50	1 / 1	24.77
20 MHz	$\pi/2$ BPSK	647334	3710.01	1 / 25	25.06
		656000	3840.00	1 / 49	25.44
		664666	3969.99	1 / 25	25.73
	QPSK	647334	3710.01	1 / 25	25.02
		656000	3840.00	1 / 49	25.47
		664666	3969.99	1 / 49	25.67
	16-QAM	647334	3710.01	1 / 25	24.17
		656000	3840.00	1 / 49	24.60
		664666	3969.99	1 / 49	24.81
15 MHz	$\pi/2$ BPSK	647168	3707.52	1 / 19	25.05
		656000	3840.00	1 / 19	25.43
		664832	3972.48	1 / 19	25.76
	QPSK	647168	3707.52	1 / 19	24.98
		656000	3840.00	1 / 36	25.43
		664832	3972.48	1 / 19	25.69
	16-QAM	647168	3707.52	1 / 19	24.22
		656000	3840.00	1 / 36	24.55
		664832	3972.48	1 / 19	24.94
10 MHz	$\pi/2$ BPSK	647000	3705.00	1 / 12	24.96
		656000	3840.00	1 / 12	25.43
		664332	3975.00	1 / 12	25.66
	QPSK	647000	3705.00	1 / 12	24.93
		656000	3840.00	1 / 12	25.40
		664332	3975.00	1 / 12	25.63
	16-QAM	647000	3705.00	1 / 12	24.18
		656000	3840.00	1 / 22	24.54
		664332	3975.00	1 / 12	24.79

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 47 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-54
2.4GHz 802.11b WLAN Conducted Powers

Freq [MHz]	Channel	Conducted Power [dBm]
2412	1	20.17
2437	6	20.53
2462	11	20.14

Table 6-55
2.4GHz 802.11g WLAN Conducted Powers

Freq [MHz]	Channel	Conducted Power [dBm]
2412	1	18.76
2437	6	19.13
2462	11	19.09

Table 6-56
2.4GHz 802.11n WLAN Conducted Powers

Freq [MHz]	Channel	Conducted Power [dBm]
2412	1	18.67
2437	6	18.92
2462	11	19.17

Table 6-57
2.4GHz 802.11ax SU WLAN Conducted Powers

2.4GHz WIFI (20MHz 802.11ax)		
Freq [MHz]	Channel	Conducted Power [dBm]
2412	1	18.60
2437	6	19.05
2462	11	19.01

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 48 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-58
5GHz 20MHz BW 802.11a WLAN Conducted Powers

5GHz WIFI (20MHz 802.11a MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5180	36	13.85	15.25	17.62
	5200	40	14.30	16.08	18.29
	5220	44	14.65	16.99	18.99
	5240	48	14.63	15.55	18.12
UNII-2A	5260	52	13.80	16.15	18.14
	5280	56	14.05	15.80	18.02
	5300	60	13.60	16.03	17.99
	5320	64	13.60	15.20	17.48
UNII-2C	5500	100	14.48	16.15	18.40
	5600	120	14.58	16.75	18.81
	5620	124	14.15	16.45	18.46
	5720	144	14.15	16.35	18.40
UNII-3	5745	149	14.55	15.55	18.09
	5785	157	14.40	15.80	18.17
	5825	165	14.55	16.20	18.46
UNII-4	5845	169	14.30	16.25	18.39
	5865	173	13.85	16.20	18.19
	5885	177	13.50	15.80	17.81

Table 6-59
5GHz 20MHz BW 802.11n WLAN Conducted Powers

5GHz WIFI (20MHz 802.11n MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5180	36	13.60	14.75	17.22
	5200	40	14.35	16.00	18.26
	5220	44	14.55	15.70	18.17
	5240	48	14.40	15.40	17.94
UNII-2A	5260	52	13.80	16.50	18.37
	5280	56	14.23	16.30	18.40
	5300	60	14.30	16.10	18.30
	5320	64	13.55	15.20	17.46
UNII-2C	5500	100	14.90	16.80	18.96
	5620	124	14.55	16.65	18.74
	5720	144	14.69	16.50	18.70
UNII-3	5745	149	14.90	16.20	18.61
	5785	157	14.58	16.50	18.65
	5825	165	14.50	16.50	18.62
UNII-4	5845	169	14.40	16.55	18.62
	5865	173	13.75	16.20	18.16
	5885	177	13.95	16.25	18.26

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 49 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-60
5GHz 20MHz BW 802.11ac WLAN Conducted Powers

5GHz WIFI (20MHz 802.11ac MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5180	36	13.30	14.50	16.95
	5200	40	14.10	15.90	18.10
	5220	44	14.50	16.00	18.32
	5240	48	14.40	15.40	17.94
UNII-2A	5260	52	13.40	16.10	17.97
	5280	56	14.00	15.95	18.09
	5300	60	14.00	16.00	18.12
	5320	64	13.00	14.60	16.88
UNII-2C	5500	100	14.79	16.20	18.56
	5600	120	14.50	16.70	18.75
	5620	124	14.30	16.15	18.33
	5720	144	14.40	16.35	18.49
UNII-3	5745	149	14.99	15.90	18.48
	5785	157	14.00	15.80	18.00
	5825	165	14.55	16.25	18.49
	5845	169	14.20	15.95	18.17
UNII-4	5865	173	14.10	16.20	18.29
	5885	177	13.55	15.90	17.89

Table 6-61
5GHz 20MHz BW 802.11ax SU WLAN Conducted Powers

5GHz WIFI (20MHz 802.11ax MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5180	36	13.75	14.99	17.42
	5200	40	14.40	15.70	18.11
	5220	44	14.69	16.85	18.91
	5240	48	14.05	15.35	17.76
UNII-2A	5260	52	13.85	16.20	18.19
	5280	56	13.65	15.95	17.96
	5300	60	14.00	15.50	17.82
	5320	64	13.35	15.15	17.35
UNII-2C	5500	100	14.60	16.25	18.51
	5600	120	14.50	16.60	18.69
	5620	124	14.40	16.55	18.62
	5720	144	14.55	15.90	18.29
UNII-3	5745	149	14.69	16.20	18.52
	5785	157	14.10	16.30	18.35
	5825	165	14.65	15.90	18.33
	5845	169	14.20	16.20	18.32
UNII-4	5865	173	13.75	15.95	18.00
	5885	177	13.90	15.80	17.96

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 50 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-62
5GHz 40MHz BW 802.11n WLAN Conducted Powers
5GHz WIFI (40MHz 802.11n MIMO)

Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5190	38	10.50	11.60	14.10
	5230	46	13.30	14.70	17.07
UNII-2A	5270	54	12.85	15.05	17.10
	5310	62	11.15	13.20	15.31
UNII-2C	5510	102	12.80	14.65	16.83
	5590	118	13.30	15.50	17.55
	5630	126	13.40	15.30	17.46
	5710	142	13.10	15.25	17.32
UNII-3	5755	151	13.30	15.20	17.36
	5795	159	13.00	15.10	17.19
UNII-4	5835	167	13.30	15.40	17.49
	5875	175	12.80	15.00	17.05

Table 6-63
5GHz 40MHz BW 802.11ac WLAN Conducted Powers
5GHz WIFI (40MHz 802.11ac MIMO)

Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5190	38	10.25	11.15	13.73
	5230	46	12.80	14.30	16.62
UNII-2A	5270	54	12.70	15.15	17.11
	5310	62	11.35	12.88	15.19
UNII-2C	5510	102	12.95	14.25	16.66
	5590	118	13.35	15.10	17.32
	5630	126	13.00	15.10	17.19
	5710	142	13.25	15.00	17.22
UNII-3	5755	151	13.20	15.00	17.20
	5795	159	12.90	15.05	17.12
UNII-4	5835	167	12.60	14.95	16.94
	5875	175	12.70	14.95	16.98

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 51 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Table 6-64

5GHz 40MHz BW 802.11ax SU WLAN Conducted Powers

5GHz WIFI (40MHz 802.11ax MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5190	38	10.45	12.15	14.39
	5230	46	13.15	14.90	17.12
UNII-2A	5270	54	12.70	14.70	16.82
	5310	62	11.30	13.15	15.33
UNII-2C	5510	102	12.60	14.45	16.63
	5590	118	13.20	15.30	17.39
	5630	126	13.20	14.50	16.91
	5710	142	13.15	15.15	17.27
UNII-3	5755	151	13.30	15.10	17.30
	5795	159	13.25	15.10	17.28
UNII-4	5835	167	12.90	14.80	16.96
	5875	175	12.75	14.55	16.75

Table 6-65

5GHz 80MHz BW 802.11ac WLAN Conducted Powers

5GHz WIFI (80MHz 802.11ac MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5210	42	9.20	11.85	13.73
UNII-2A	5290	58	9.60	11.43	13.62
UNII-2C	5530	106	9.60	11.20	13.48
	5610	122	10.08	12.43	14.42
	5690	138	10.06	11.64	13.93
UNII-3	5775	155	10.12	11.77	14.03
UNII-4	5855	171	10.08	12.12	14.23

Table 6-66

5GHz 80MHz BW 802.11ax SU WLAN Conducted Powers

5GHz WIFI (80MHz 802.11ax MIMO)					
Band	Freq [MHz]	Channel	Avg. Conducted Powers [dBm]		
			ANT1	ANT2	MIMO
UNII-1	5210	42	10.25	12.10	14.28
UNII-2A	5290	58	9.55	11.55	13.67
UNII-2C	5530	106	10.10	11.40	13.81
	5610	122	10.14	12.12	14.25
	5690	138	9.88	11.64	13.86
UNII-3	5775	155	9.78	11.82	13.93
UNII-4	5855	171	10.18	11.98	14.18

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 52 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

7. JUSTIFICATION OF HELD TO EAR MODES TESTED

I. Analysis of RF Air Interface Technologies

An analysis was performed, following the guidance of §4.7 of the ANSI standard, of the RF air interface technologies being evaluated. For this analysis, the stated peak power levels were verified to be within the requirements detailed in Table 3-2.

II. Individual Mode Evaluations

Table 7-1
Peak power levels of individual air interfaces evaluated for emission compliance

Air Interface	Peak Power** [dBm]	Peak Power Level Margin [dB]	Emission Compliance
GSM - GSM850	34.00	1.00	PASS
GSM - GSM1900	31.00	1.00	PASS
GSM - EDGE850	28.00	7.00	PASS
GSM - EDGE1900	26.00	6.00	PASS
UMTS - RMC	25.00	10.00	PASS
UMTS - AMR	24.50	10.50	PASS
UMTS - HSPA	24.50	10.50	PASS
LTE FDD	25.00	10.00	PASS
LTE TDD - Band 41 (PC3)	24.00	7.00	PASS
LTE TDD - Band 48	24.50	6.50	PASS
NR FDD	25.00	10.00	PASS
NR TDD - n41 PC2	26.50	4.50	PASS
NR TDD - n48	23.00	8.00	PASS
NR TDD - n77 PC2	27.00	4.00	PASS
WIFI - 2.4GHz	21.00	10.00	PASS
WIFI - 5GHz	19.00	12.00	PASS
Simultaneous 2.4GHz and 5GHz WIFI Operations*	23.10	7.90	PASS

* Note: This value is calculated as the linear sum of the worst-case power for each band and antenna combination while in simultaneous 2.4GHz and 5GHz operation. This calculation is conservative and for use in this investigation only.

**Note: The peak power level represents the maximum allowable limit, set at +1 dB above the specified conducted power target.

III. WD RF Peak power level conclusions

Per ANSI C63.19-2019, all applicable air interfaces demonstrate compliance to the peak power requirements shown in Table 3-2 of this report.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 53 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

8. EQUIPMENT LIST

Table 8-1
Equipment List

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Keysight Technologies	N9020A	MXA Signal Analyzer	5/7/2025	Annual	5/7/2026	US46470561
Amplifier Research	15S1G6	Amplifier	N/A	CBT*	N/A	433978
Anritsu	MA24106A	USB Power Sensor	5/29/2025	Annual	6/29/2026	1349511
Control Company	4040	Digital Thermometer	10/15/2024	Biennial	10/15/2026	240763496
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	N/A	CBT*	N/A	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	N/A	CBT*	N/A	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	N/A	CBT*	N/A	1226
Pasternack	PE2237-20	Bidirectional Coupler	N/A	CBT*	N/A	N/A
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	7/9/2025	Annual	7/9/2026	166462
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	8/14/2025	Biennial	8/14/2026	164948
Anritsu	MT8000A	Radio Communication Test Station	6/4/2025	Annual	6/4/2026	6261914237
Seekonk	NC-100	Torque Wrench (8" lb)	5/29/2025	Biennial	5/29/2027	N/A

Calibration traceable to the National Institute of Standards and Technology (NIST).

***Note: CBT (Calibrated Before Testing).** Prior to testing, the measurement paths containing a cable, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 54 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

9. MEASUREMENT UNCERTAINTY

Table 9-1
Uncertainty Estimation Table

Wireless Communications Device Near-Field Measurement Uncertainty Estimation							
Uncertainty Component	Data (dB)	Data Type	Prob. Dist.	Divisor	Ci (E)	Unc. (dB)	Notes/Comments
Measurement System							
RF System Reflections	0.50	Tolerance	N	1.00	1	0.50	* Refl. < -20 dB
Field Probe Calibration	0.21	Tolerance	N	1.00	1	0.21	
Field Probe Isotropy	0.01	Tolerance	N	1.00	1	0.01	
Field Probe Frequency Response	0.135	Tolerance	N	1.00	1	0.14	
Field Probe Linearity	0.013	Tolerance	N	1.00	1	0.01	
Modulation Interference Factor	0.20	Tolerance	R	1.73	1	0.12	Applicable for M-rating testing
Boundary Effects	0.105	Accuracy	R	1.73	1	0.06	*
Probe Positioning Accuracy	0.20	Accuracy	R	1.73	1	0.12	*
Probe Positioner	0.050	Accuracy	R	1.73	1	0.03	*
Extrapolation/Interpolation	0.045	Tolerance	R	1.73	1	0.03	*
Resolution to 2mm error	0.21	Tolerance	N	1.00	1	0.21	
System Detection Limit	0.05	Tolerance	R	1.73	1	0.03	*
Readout Electronics	0.015	Tolerance	N	1.00	1	0.02	*
Integration Time	0.11	Tolerance	R	1.73	1	0.06	*
Response Time	0.033	Tolerance	R	1.73	1	0.02	*
Phantom Thickness	0.10	Tolerance	R	1.73	1	0.06	*
System Repeatability (Field x 2=power)	0.17	Tolerance	N	1.00	1	0.17	*
Test Sample Related							
Device Positioning Vertical	0.2	Tolerance	R	1.73	1	0.12	*
Device Positioning Lateral	0.045	Tolerance	R	1.73	1	0.03	*
Device Holder and Phantom	0.1	Tolerance	R	1.73	1	0.06	*
Power Drift	0.21	Tolerance	R	1.73	1	0.12	
Combined Standard Uncertainty (k=1)						0.66	16.3%
Expanded Uncertainty [95% confidence]						1.31	32.6%
Expanded Uncertainty [95% confidence] on Field						0.66	16.3%

Notes:

1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297. All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.
2. * Uncertainty specifications from Schmidt & Partner Engineering AG (not site specific)

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid immunity tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: A3LSMA576U	 element	HAC (RF EMISSIONS) TEST REPORT		Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset		Page 55 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

10. CONCLUSION

The measurements indicate that the referenced wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19-2019 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 56 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

11. REFERENCES

1. ANSI C63.19-2019, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, August 2019
2. FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v06r02," September 19, 2022
3. FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v04," February 23, 2022
4. FCC Public Notice DA 06-1215, *Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard*, June 6, 2006
5. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
6. Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
7. Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
8. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices," IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
9. Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
10. Byrne, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
11. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells," U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
13. Decker, W. F., Crawford, M. L., and Wilson, W. A., "Construction of a Large Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Feb. 1979.
14. EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
15. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 57 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

16. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
17. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
18. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
19. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
20. Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
21. Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
25. Ma, M. A., Sreenivashiah, I. , and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: A3LSMA576U	 HAC (RF EMISSIONS) TEST REPORT	Approved by: Technical Manager
Filename: 1M2510280090-25.A3L	Test Dates: 11/17/2025 – 12/05/2025	DUT Type: Portable Handset
		Page 58 of 58

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.