

SAR TEST REPORT

Applicant Name:

SAMSUNG Electronics Co., Ltd.
129, Samsung-ro, Yeongtong-gu, Suwon-Si,
Gyeonggi-do, 16677 Rep. of Korea

Date of Issue: 08. 10, 2017

Test Report No.: HCT-A-1707-F001-1

Test Site: HCT CO., LTD.

FCC ID:

A3LSMC7100

Equipment Type:

Model Name:

Additional FCC Model(s):

Mobile Phone

SM-C7100

SM-C7108

Testing has been carried out in accordance with:

FCC 47 CFR §2.1093

ANSI/ IEEE C95.1 – 1992

IEEE 1528-2013

Date of Test:

06/23/2017 ~ 07/10/2017,

07/22/2017 ~ 07/27/2017, 08/09/2017

This device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in FCC KDB procedures and had been tested in accordance with the measurement procedures specified in FCC KDB procedures.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested By



In-Ho, Park
Test Engineer
SAR Team
Certification Division

Reviewed By



Yun-Jeang Heo
Technical Manager
SAR Team
Certification Division

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

DOCUMENT REVISION HISTORY

Rev.	DATE	DESCRIPTION
HCT-A-1707-F001	08. 03, 2017	First Approval Report
HCT-A-1707-F001-1	08. 10, 2017	TYPO were Page 89, 114 Sec.9.3 were revised Attachment 5 were revised. Plots 34,35 and 36 were removed.

Table of Contents

1. ATTESTATION OF TEST RESULT OF DEVICE UNDER TEST	4
2. DEVICE UNDER TEST DESCRIPTION.....	5
3. INTRODUCTION	1 8
4. DESCRIPTION OF TEST EQUIPMENT	1 9
5. SAR MEASUREMENT PROCEDURE.....	2 0
6. DESCRIPTION OF TEST POSITION.....	2 2
7. ANSI/ IEEE C95.1 - 1992 RF EXPOSURE LIMITS	2 5
8. FCC SAR GENERAL MEASUREMENT PROCEDURES	2 6
9. OUTPUT POWER SPECIFICATIONS	3 2
10. SYSTEM VERIFICATION.....	9 0
11. SAR TEST DATA SUMMARY	9 4
12. SIMULTANEOUS SAR ANALYSIS	1 1 0
13. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY	1 1 4
14. MEASUREMENT UNCERTAINTY	1 1 5
15. SAR TEST EQUIPMENT	1 1 6
16. CONCLUSION.....	1 1 7
17. REFERENCES	1 1 8
Attachment 1. – SAR Test Plots	1 2 0
Attachment 2. – Dipole Verification Plots.....	1 6 0
Attachment 3. – Probe Calibration Data	1 7 8
Attachment 4. – Dipole Calibration Data	2 5 6
Attachment 5. – The Verification of Power reduction	2 9 0
Attachment 6. – SAR Tissue Characterization.....	2 9 6
Attachment 7. – SAR SYSTEM VALIDATION	2 9 7
Attachment 8. – DUT Antenna Information and SAR Test SETUP PHOTOGRAPHS	

1. ATTESTATION OF TEST RESULT OF DEVICE UNDER TEST

Test Laboratory	
Company Name:	HCT Co., LTD
Address	74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of Korea
Telephone	+82 31 645 6300
Fax.	+82 31 645 6401

Attestation of SAR test result						
Applicant Name:	SAMSUNG Electronics Co., Ltd.					
FCC ID:	A3LSMC7100					
Model:	SM-C7100					
Additional FCC Model(s):	SM-C7108					
EUT Type:	Mobile Phone					
Application Type:	Certification					
The Highest Reported SAR						
Band	Tx. Frequency	Equipment Class	Reported SAR (W/kg)			
			1g Head	1g Body-Worn	1g Hotspot	10g Extremity
	(MHz)		(W/Kg)	(W/Kg)	(W/Kg)	(W/kg)
GSM/GPRS/EDGE 850	824.2 ~ 848.8	PCE	0.98	0.51	0.86	N/A
GSM/GPRS/EDGE 1900	1 850.2 ~1 909.8	PCE	1.04	0.16	0.36	N/A
UMTS 850	826.4 ~ 846.6	PCE	0.96	0.49	0.99	N/A
UMTS 1900	1 852.4 ~ 1 907.6	PCE	0.86	0.15	0.50	N/A
LTE 5 (Cell)	824.7 ~ 848.3	PCE	0.93	0.41	1.05	N/A
LTE Band 7	2 502.5 ~ 2 567.5	PCE	1.00	0.30	0.64	N/A
LTE TDD Band 41	2 557.5 ~ 2 652.5	PCE	0.69	0.13	0.36	N/A
802.11b	2 412 ~ 2 462	DTS	0.53	<0.1	0.19	N/A
Bluetooth	2 402 ~ 2 480	DSS/DTS	0.19	N/A	N/A	N/A
Simultaneous SAR per KDB 690783 D01v01r03			1.18	0.66	1.28	N/A
Date(s) of Tests:	06/23/2017 ~ 07/10/2017, 07/22/2017 ~ 07/27/2017, 08/09/2017					

2. DEVICE UNDER TEST DESCRIPTION

2.1 DUT specification

Device Wireless specification overview						
Band & Mode		Operating Mode		Tx Frequency		
GSM/GPRS/EDGE 850		Voice / Data		824.2 – 848.8 MHz		
GSM/GPRS/EDGE 1900		Voice / Data		1 850.2 – 1 909.8 MHz		
UMTS 850		Voice / Data		826.4 – 846.6 MHz		
UMTS 1900		Voice / Data		1 852.4 – 1 907.6 MHz		
LTE Band 5 (Cell)		Voice / Data		824.7 – 848.3 MHz		
LTE Band 7		Voice / Data		2 502.5 – 2 567.5 MHz		
LTE TDD Band 38		Voice / Data		2 572.5 ~ 2 617.5 MHz		
LTE TDD Band 41		Voice / Data		2 557.5 ~ 2 652.5 MHz		
2.4 GHz WLAN		Data		2 412 – 2 462 MHz		
Bluetooth		Data		2 402 – 2 480 MHz		
Device Description						
Device Dimension:		Overall (Length x Width): 152.4 mm x 74.7 mm Overall Diagonal: 161.2 mm Display Diagonal: 140 mm				
Back Cover:		Normal Battery cover				
Battery Options:		Standard (Lithium-Ion Polymer)				
		Battery Model Name: EB-BJ731ABE				
		Manufacturer: SDI				
Hardware Version:		REV0.1				
Software Version :		C7100.001				
Device Serial Numbers		Antenna	Mode		Serial Number	
		Antenna 1, Antenna 2	GSM850, GSM1900, W850, W1900, LTE 5 Head/Body		358348080052773	
			LTE7, LTE41 Head/Body		358348080052807	
		Antenna 3	LTE5, GSM850, W850, Body		359771080051413	
			GSM1900, W1900 Body		359771080048997	
			LTE7, LTE 41 Head/Body LTE5, GSM850, W850, GSM1900, W1900 Head		359772080051577	
		Bluetooth, WLAN 2.4GHz			358348080052765	
		Several samples with identical hardware were used to SAR testing. The manufacturer has confirmed that the devices tested have the same physical, mechanical and thermal characteristics are within operational tolerances expected for production units.				

2.1.1 Power Reduction for SAR

This device utilize power reduction mechanisms for SAR compliance for the Licensed transmitter Main Ant 3 and the WLAN transmitter for Held-to ear exposure conditions as outlined in section 2.5. The Held-to-ear exposure conditions were evaluated at reduced Power according to the head SAR positions described in IEEE1528-2013

The reduced powers for the power reduction mechanism were conformed via conducted power measurements at the RF port (see sec 9, Attachment 5).Detailed descriptions of the mechanisms are included in the operational description.

2.2 DUT Wireless mode

Wireless Modulation	Band	Operating Mode		Duty Cycle
GSM	850 1900	Voice(GMSK) GPRS (GMSK) EGPRS (8PSK)	GPRS/ EDGE Multi-Slot Class: Class 12– 4 Up, 4 Down Mode class B	GSM Voice: 12.5% GPRS 1 Slot: 12.5% 2 Slots : 25% 3 Slots : 37.5% 4 Slots : 50%
WCDMA (UMTS)	Band 5 Band 2	UMTS Rel.99 (Voice / DATA) HSDPA (Cat.24) HSUPA (Cat.6) HSPA+ (Rel 8, DC-HSDPA, Uplink QPSK Only)		100 %
LTE Band	5 (Cell)	Voice / Data (QPSK, 16QAM)		100 % (FDD)
	7	Voice / Data (QPSK, 16QAM)		100 % (FDD)
	38	Voice / Data (QPSK, 16QAM)		63.33 % (TDD)
	41	Voice / Data (QPSK, 16QAM)		63.33 % (TDD)
2.4 GHz WLAN		Data	802.11b, 802.11g, 802.11n (HT20)	98.82 %
Bluetooth		Data		76.6 % (DH5)
Bluetooth LE 4.2		Data	4.2 LE	N/A

2.3 LTE information

Item.		Description		
Frequency Range	LTE Band 5 (Cell)	824.7 MHz ~ 848.3 MHz		
	LTE Band 7	2 502.5 MHz ~ 2 567.5 MHz		
	LTE TDD Band 38	2 572.5 MHz ~ 2 617.5 MHz		
	LTE TDD Band 41	2 557.5 MHz ~ 2 652.5 MHz		
Channel Bandwidths	LTE Band 5 (Cell)	1.4 MHz, 3 MHz, 5 MHz, 10 MHz		
	LTE Band 7	5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE TDD Band 38	5 MHz, 10 MHz, 15 MHz, 20 MHz		
	LTE TDD Band 41	5 MHz, 10 MHz, 15 MHz, 20 MHz		
Channel Numbers & Freq.(MHz)		Low	Mid	High
LTE Band 5 (Cell)	1.4 MHz	824.7 (20407)	836.5 (20525)	848.3 (20643)
	3 MHz	825.5 (20415)	836.5 (20525)	847.5 (20635)
	5 MHz	826.5 (20425)	836.5 (20525)	846.5 (20625)
	10 MHz	829.0 (20450)	836.5 (20525)	844.0 (20600)
LTE Band 7	5 MHz	2 502.5 (20775)	2 535.0 (21100)	2 567.5 (21425)
	10 MHz	2 505.0 (20800)	2 535.0 (21100)	2 565.0 (21400)
	15 MHz	2 507.5 (20825)	2 535.0 (21100)	2 562.5 (21375)
	20 MHz	2 510.0 (20850)	2 535.0 (21100)	2 560.0 (21350)
LTE Band 38	5 MHz	2 572.5 (37775)	2 595.0 (38000)	2 617.5 (38225)
	10 MHz	2 575.0 (37800)	2 595.0 (38000)	2 615.0 (38200)
	15 MHz	2 577.5 (37825)	2 595.0 (38000)	2 612.5 (38175)
	20 MHz	2 580.0 (37850)	2 595.0 (38000)	2 610.0 (38150)
LTE Band 41	5 MHz	2 557.5 (40265)	2 605.0 (40740)	2 652.5 (41215)
	10 MHz	2 560.0 (40290)	2 605.0 (40740)	2 650.0 (41190)
	15 MHz	2 562.5 (40315)	2 605.0 (40740)	2 647.5 (41165)
	20 MHz	2 565.0 (40340)	2 605.0 (40740)	2 645.0 (41140)

Item.	Description
UE Category	LTE Rel. 10, Category 5 uplink
Modulations Supported in UL	QPSK, 16QAM,64QAM
LTE voice/data requirements	Voice/ DATA
	VOLTE is supported. LTE Head SAR is also evaluated.
LTE MPR options	The EUT incorporates MPR as per 3GPP TS 36.101 sec. 6.2.3 ~ 6.2.5
	The MPR is permanently built-in by design as a mandatory.
	A-MPR is not implemented in the DUT.
	During the LTE Power reduction , The MPR parameter is set to zero
Description of the LTE Transmitter & antenna	This model has two Tx. paths.
	One is for Main Ant1 ,Main Ant2 and Main Ant3 (GSM and WCDMA and LTE) operate in a switched condition only. These cannot transmit simultaneously.
	The other is for BT & WLAN. It cannot transmit simultaneously.
LTE Carrier Aggregation	This device only supports downlink intra continuous Carrier Aggregation.
LTE Carrier Aggregation Possible Combinations	CA_41C (intra- Contiguous Carrier aggregation in downlink)
	LTE Rel10 Checklist document includes all the possible carrier aggregation combinations.
LTE Release 10 Additional Information	This device does not support full CA feature on 3GPP Release 10. It supports a maximum of 2 carriers in the downlink. All uplink communications are identical to the Release 8 specifications. Uplink communications are done on the PCC. The following LTE release 10 features are not supported: Replay, HetNet, Enhanced MIMO, eICI, WIFI offloading, MDH, eMBHA, Cross-Carrier Scheduling, Enhanced SC-FDMA.
Description of the test equipment, software, etc.	LTE SAR Testing was performed using a CMW500/ MT8820C. UE transmits with maximum output power during SAR testing.

2.4 Test Methodology and Procedures

The tests documented in this report were performed in accordance with IEEE Standard 1528-2013 and the following published KDB procedures.

- FCC KDB Publication 941225 D01 3G SAR Procedures v03r01
- FCC KDB Publication 941225 D06 Hot Spot SAR v02r01
- FCC KDB Publication 941225 D05 SAR for LTE Devices v02r05
- FCC KDB Publication 941225 D05A LTE Rel.10 KDB Inquiry sheet v01r02
- FCC KDB Publication 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB Publication 447498 D01 General SAR Guidance v06
- FCC KDB Publication 648474 D04 Handset SAR v01r03
- FCC KDB Publication 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- FCC KDB Publication 865664 D02 SAR Reporting v01r02
- October 2013 TCB Workshop Notes (GPRS testing criteria)
- April 2015 TCB Workshop Notes (Simultaneous transmission summation clarified)

2.5 Nominal and Maximum Output Power Specifications

This device operates using the following maximum output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB publication 447498 D01v06.

2.5.1 Maximum PCE Output Power (Main Ant.1and Main Ant.2 and Main Ant.3)

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 Tx Slot	1 Tx Slot	2 Tx Slot	3 Tx Slot	4 Tx Slot	1 Tx Slot	2 Tx Slot	3 Tx Slot	4 Tx Slot
GSM/GPRS/EDGE 850	Maximum	32.5	32.5	29.5	28.0	26.5	26.5	26.0	24.0	22.5
	Nominal	32.0	32.0	29.0	27.5	26.0	26.0	25.5	23.5	22.0
GSM/GPRS/EDGE 1900	Maximum	30.5	30.5	27.7	26.5	24.7	26.5	25.5	23.5	22.0
	Nominal	30.0	30.0	27.2	26.0	24.2	26.0	25.0	23.0	21.5

Mode / Band		3GPP WCDMA	3GPP HSDPA	3GPP HSUPA	DC-HSDPA
		(dBm)	(dBm)	(dBm)	(dBm)
UMTS Band 5 (850 MHz)	Maximum	23.0	21.5	22.5	21.5
	Nominal	22.5	21.0	22	21.0
UMTS Band 2 (1900 MHz)	Maximum	21.0	19.5	20.5	19.5
	Nominal	20.5	19.0	20.0	19.0

Mode / Band		Modulated Average (dBm)
LTE Band 5 (Cell)	Maximum	22.5
	Nominal	22.0
LTE Band 7	Maximum	22.5
	Nominal	22.0
LTE Band 38	Maximum	22.5
	Nominal	22.0
LTE Band 41	Maximum	22.5
	Nominal	22.0

2.5.2 Reduced PCE Power Main Ant 3(Held to ear)

Mode / Band		Voice (dBm)	Burst Average GMSK (dBm)				Burst Average 8-PSK (dBm)			
		1 Tx Slot	1 Tx Slot	2 Tx Slot	3 Tx Slot	4 Tx Slot	1 Tx Slot	2 Tx Slot	3 Tx Slot	4 Tx Slot
GSM/GPRS/EDGE 850	Maximum	30.2	30.2	26.5	24.7	23.0	25.5	24.5	22.5	21.5
	Nominal	29.7	29.7	26.0	24.2	22.5	25.0	24.0	22.0	21.0
GSM/GPRS/EDGE 1900	Maximum	28.5	28.5	25.0	23.0	21.0	25.0	24.0	22.0	20.5
	Nominal	28.0	28.0	24.5	22.5	20.5	24.5	23.5	21.5	20.0

Mode / Band		3GPP WCDMA (dBm)	3GPP HSDPA (dBm)	3GPP HSUPA (dBm)	DC-HSDPA (dBm)
		(dBm)	(dBm)	(dBm)	(dBm)
UMTS Band 5 (850 MHz)	Maximum	20.7	19.5	20.5	19.5
	Nominal	20.2	19.0	20	19.0
UMTS Band 2 (1900 MHz)	Maximum	18.7	17.5	18.5	17.5
	Nominal	18.2	17.0	18	17.0

Mode / Band		Modulated Average (dBm)
LTE Band 5 (Cell)	Maximum	20.5
	Nominal	20.0
LTE Band 7	Maximum	17.5
	Nominal	17.0
LTE Band 38	Maximum	18.7
	Nominal	18.2
LTE Band 41	Maximum	18.7
	Nominal	18.2

2.5.3 Maximum WLAN/BT Power

Mode/Band			Modulated Average (dBm)				
	Sensor		a	b	g	n	ac
2.4 GHz WIFI	Inactive	Maximum		17.5	14.5	12.5	
		Nominal		17.0	14.0	12.0	

Mode / Band		Modulated Average (dBm)	
Bluetooth	Maximum	10.5	
	Nominal	10.0	
Bluetooth LE	Maximum	8.0	
	Nominal	7.5	

2.5.4 Reduced WLAN Ant (Held to ear)

Mode/Band			Modulated Average (dBm)				
	Sensor		a	b	g	n	ac
2.4 GHz WIFI	Active	Maximum		15.5			
		Nominal		15.0			

2.6 DUT Antenna Locations


Device Edges / Sides for SAR Testing							
Mode	Antenna	Rear	Front	Left	Right	Bottom	Top
GSM/GPRS/EDGE 850	Ant. 1	Yes	Yes	Yes	No	Yes	No
UMTS 850	Ant. 1	Yes	Yes	Yes	No	Yes	No
LTE Band 5	Ant. 1	Yes	Yes	Yes	No	Yes	No
LTE Band 7	Ant. 1	Yes	Yes	Yes	No	Yes	No
LTE Band 41	Ant. 1	Yes	Yes	Yes	No	Yes	No
GSM/GPRS/EDGE 1900	Ant. 2	Yes	Yes	No	Yes	Yes	No
UMTS 1900	Ant. 2	Yes	Yes	No	Yes	Yes	No
GSM/GPRS/EDGE 850	Ant. 3	Yes	Yes	No	Yes	No	Yes
GSM/GPRS/EDGE 1900	Ant. 3	Yes	Yes	No	Yes	No	Yes
UMTS 850	Ant. 3	Yes	Yes	No	Yes	No	Yes
UMTS 1900	Ant. 3	Yes	Yes	No	Yes	No	Yes
LTE Band 5	Ant. 3	Yes	Yes	No	Yes	No	Yes
LTE Band 7	Ant. 3	Yes	Yes	No	Yes	No	Yes
LTE Band 41	Ant. 3	Yes	Yes	No	Yes	No	Yes
2.4 GHz WLAN	BT/WLAN Ant	Yes	Yes	Yes	No	No	Yes

Particular EUT edges were not required to be evaluated for Wireless Router SAR if the edges were > 25 mm from the transmitting antenna according to FCC KDB 941225 D06v02r01 on page 2. The distance between the transmit antennas and the edges of the device are included in the filing. The overall dimensions of this device are > 9 X 5 cm. A diagram showing device antenna can be found in SAR_setup_photos. Since the diagonal dimension of this device is > 160 mm and < 200 mm, it is considered a “phablet”.

* Note: All test configurations are based on front view position.

2.8 SAR Summation Scenario

According to FCC KDB 447498 D01v06, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the EUT are shown below paths and are mode in same rectangle to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB 447498 D01v06.

Simultaneous Transmission Scenarios					
Applicable Combination	Antenna	Head	Body-Worn	Hotspot	Extremity
GSM Voice + 2.4 GHz WiFi	Main Ant. 1	Yes	Yes	N/A	Yes
GSM Voice + 2.4 GHz Bluetooth		Yes*	Yes	N/A	Yes
GPRS + 2.4 GHz WiFi		N/A	N/A	Yes	Yes
GPRS + Bluetooth		N/A	N/A	Yes*	Yes
UMTS + 2.4 GHz WiFi		Yes	Yes	Yes	Yes
UMTS + 2.4 GHz Bluetooth		Yes*	Yes	Yes*	Yes
LTE + 2.4 GHz WiFi		Yes	Yes	Yes	Yes
LTE+ 2.4 GHz Bluetooth		Yes*	Yes	Yes*	Yes
GSM Voice + 2.4 GHz WiFi	Main Ant. 2	Yes	Yes	N/A	Yes
GSM Voice + 2.4 GHz Bluetooth		Yes*	Yes	N/A	Yes
GPRS + 2.4 GHz WiFi		N/A	N/A	Yes	Yes
GPRS + Bluetooth		N/A	N/A	Yes*	Yes
UMTS + 2.4 GHz WiFi		Yes	Yes	Yes	Yes
UMTS + 2.4 GHz Bluetooth		Yes*	Yes	Yes*	Yes
GSM Voice + 2.4 GHz WiFi	Main Ant. 3	Yes	Yes	N/A	Yes
GSM Voice + 2.4 GHz Bluetooth		Yes*	Yes	N/A	Yes
GPRS + 2.4 GHz WiFi		N/A	N/A	Yes	Yes
GPRS + Bluetooth		N/A	N/A	Yes*	Yes
UMTS + 2.4 GHz WiFi		Yes	Yes	Yes	Yes
UMTS + 2.4 GHz Bluetooth		Yes*	Yes	Yes*	Yes
LTE + 2.4 GHz WiFi		Yes	Yes	Yes	Yes
LTE+ 2.4 GHz Bluetooth		Yes*	Yes	Yes*	Yes

1. Main Ant 1, Main Ant 2 and Main Ant 3 operate in a switched condition only and cannot transmit simultaneously.
2. 2.4 GHz WLAN and 2.4 GHz Bluetooth share antenna path and cannot transmit simultaneously.
3. All licensed modes share the same antenna path and cannot transmit simultaneously.
4. UMTS +WLAN scenario also represents the UMTS Voice/DATA + WLAN hotspot scenario.
5. Per the manufacturer, GPRS does not support VOIP service.
6. This device support VoLTE.
7. The highest reported SAR for each exposure condition is used for SAR summation purpose.
8. Wi-Fi Hotspot is supported for 2.4GHz WLAN.
9. * Bluetooth tethering is supported.

2.8 SAR Test Exclusions Applied

A) BT / LE

Per FCC KDB 447498 D01v06, The SAR exclusion threshold for distance < 50mm is defined by the following equation:

$$\frac{\text{MaxPowerofChannel(mW)}}{\text{TestSeparationDistance(mm)}} * \sqrt{\text{Frequency(GHz)}} \leq 3.0(1\text{g SAR}), 7.5(10\text{g SAR})$$

Mode	Frequency	Maximum Allowed Power	Separation Distance	≤ 3.0	≤ 7.5
	[MHz]	[mW]	[mm]	1-g SAR	10-g SAR
Bluetooth	2 480	11	15	1.2	-
Bluetooth	2 480	11	10	1.7	-
Bluetooth	2 480	11	5	-	3.5
Bluetooth LE	2 480	6	15	0.6	-
Bluetooth LE	2 480	6	10	0.9	-
Bluetooth LE	2 480	6	5	-	1.9

Based on the maximum conducted power of Bluetooth and antenna to use separation distance, Bluetooth SAR was not required $[(11/15)*\sqrt{2.480}] = 1.2 \leq 3.0$, $[(11/10)*\sqrt{2.480}] = 1.7 \leq 3.0$ for 1-g SAR, $[(11/5)*\sqrt{2.480}] = 3.5 \leq 7.5$ for 10-g Extremity SAR.

Based on the maximum conducted power of Bluetooth LE and antenna to use separation distance, Bluetooth LE SAR was not required $[(6/15)*\sqrt{2.480}] = 0.6 \leq 3.0$, $[(6/10)*\sqrt{2.480}] = 0.9 \leq 3.0$, 0 for 1-g SAR, $[(6/5)*\sqrt{2.480}] = 1.9 \leq 7.5$ for 10-g Extremity SAR.

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v06 IV.C.1iii, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is $\leq 1.6\text{W/kg}$. When standalone SAR is not required to be measured per FCC KDB 447498 D01v06 4.3.22, the following equation must be used to estimate the standalone 1-g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHZ})}}{x} * \frac{(\text{Max Power of channel mW})}{\text{Min Separation Distance}}$$

where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

Mode	Frequency	Maximum Allowed Power	Separation Distance (Body)	Estimated SAR	
				Body (1-g SAR)	Extremity (10-g SAR)
	[MHz]	[mW]	[mm]	[W/kg]	[W/kg]
Bluetooth	2 480	11	15	0.154	-
Bluetooth	2 480	11	10	0.231	-
Bluetooth	2 480	11	5	-	0.185
Bluetooth LE	2 480	6	15	0.084	-
Bluetooth LE	2 480	6	10	0.126	-
Bluetooth LE	2 480	6	5	-	0.101

Note:

- 1) The Estimated SAR results were determined according to FCC KDB447498 D01v06.
- 2) The frequency of Bluetooth and Bluetooth LE using for estimated SAR was selected highest channel of Bluetooth LE for highest estimated SAR.

(C) Licensed Transmitter(s)

GSM/GPRS/EDGE DTM is not supported for US bands. Therefore, the GSM Voice modes in this report do not transmit simultaneously with GPRS/EDGE Data.

This device is only capable of QPSK HSUPA in the uplink. Therefore, no additional SAR tests are required beyond that described for devices with HSUPA in KDB 941225 D01v03r01.

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02r05.

This Device supports 64QAM on the uplink for LTE Operations. Conducted powers for 64QAM uplink configurations were measured per section 5.1 of FCC KDB 941225D05v02r05. SAR was not required for 64QAM since the highest maximum output power for 64QAM is ≤ 0.5 dB higher than the same configuration in QPSK and the reported SAR for QPSK configuration is ≤ 1.45 W/Kg, per section 5.2.4 of FCC KDB941225 D05v02r05.

This device supports LTE Carrier Aggregation (CA) in the downlink only. All uplink communications are identical to Release 8 specifications. Per FCC KDB publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

This device supports both LTE Band 41 and LTE Band 38. Since the supported frequency span for LTE Band 38 involved completely within the supported frequency span for LTE Band 41, both LTE Bands have the same target power, and both LTE bands share the same transmission path, SAR was only assessed for LTE Band 41.

Per FCC KDB 648474 D04v01r03, this device is considered a "Phablet" since the diagonal dimension is greater than 160 mm and less than 200 mm. Therefore, extremity SAR tests are required when wireless router mode does not apply or if wireless router 1g SAR >1.2 W/kg. When hotspot mode applies, 10g SAR required only for the surfaces and edges with hotspot mode scaled to the maximum output power (including tolerance) is 1g SAR > 1.2 W/kg.

Per FCC KDB 941225 D01v03r01, 12.2 kbps RMC is the primary mode and HSPA (HSUPA/HSDPA with RMC) is the secondary mode.

Per FCC KDB 941225 D01v03r01, The SAR test exclusion is applied to the secondary mode by the following equation.

$$\text{Adjusted SAR} = \text{Highest Reported SAR} * \frac{\text{Secondary Max tune - up (mW)}}{\text{Primary Max tune - up(mW)}} \leq 1.2 \text{ W/kg.}$$

Based on the highest Reported SAR, the secondary mode is not required.

$$[0.994 * (178/200)] = 0.885 \text{ W/kg} \leq 1.2 \text{ W/kg}$$

And the maximum output power and tune-up tolerance in secondary mode is ≤ 0.25 dB higher than the primary mode.

3. INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz. 1992 by the Institute of Electrical and Electronics Engineers, Inc., New York 10017. The measurement procedure described in IEEE/ANSI C95.3-1992 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave is used for guidance in measuring SAR due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the National Council on Radiation Protection and Measurements (NCRP) in Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields," NCRP Report No. 86 NCRP, 1986, Bethesda, MD 20814. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative of the incremental electromagnetic energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body.

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right)$$

Figure 1. SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg)

$$SAR = \sigma E^2 / \rho$$

Where:

σ = conductivity of the tissue-simulant material (S/m)
 ρ = mass density of the tissue-simulant material (kg/m³)
 E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.

4. DESCRIPTION OF TEST EQUIPMENT

4.1 SAR MEASUREMENT SETUP

These measurements are performed using the DASY4 automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure.2).

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC with Windows XP or Windows 7 is working with SAR Measurement system DASY4 & DASY5, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 2. HCT SAR Lab. Test Measurement Set-up

The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in.

5. SAR MEASUREMENT PROCEDURE

The evaluation was performed with the following procedure:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no more than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the DUT's head and body area and the horizontal grid resolution was depending on the FCC KDB 865664 D01v01r04 table 4-1 & IEEE 1528-2013.
2. Based on step, the area of the maximum absorption was determined by sophisticated interpolations routines implemented in DASY software. When an Area Scan has measured all reachable point. DASY system computes the field maximal found in the scanned are, within a range of the maximum. SAR at this fixed point was measured and used as a reference value.
3. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB 865664 D01v01r04 table 4-1 and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (reference from the DASY manual.)
 - a. The data at the surface were extrapolated, since the center of the dipoles is no more than 2.7 mm away from the tip of the probe (it is different from the probe type) and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan. If the value changed by more than 5 %, the SAR evaluation and drift measurements were repeated.

Area scan and zoom scan resolution setting follow KDB 865664 D01v01r04 quoted below.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2}\cdot\delta\cdot\ln(2)\pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^{\circ}\pm 1^{\circ}$	$20^{\circ}\pm 1^{\circ}$
Maximum area scan Spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$			≤ 2 GHz: ≤ 15 mm 2-3 GHz: ≤ 12 mm	3-4 GHz: ≤ 12 mm 4-6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan Spatial resolution: $\Delta x_{zoom}, \Delta y_{zoom}$			≤ 2 GHz: ≤ 8 mm 2-3 GHz: ≤ 5 mm*	3-4 GHz: ≤ 5 mm* 4-6 GHz: ≤ 4 mm*
Maximum zoom scan Spatial resolution normal to phantom surface	uniform grid: $\Delta z_{zoom}(n)$		≤ 5 mm	3-4 GHz: ≤ 4 mm 4-5 GHz: ≤ 3 mm 5-6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{zoom}(1)$: between 1 st two Points closest to phantom surface	≤ 4 mm	3-4 GHz: ≤ 3 mm 4-5 GHz: ≤ 2.5 mm 5-6 GHz: ≤ 2 mm
		$\Delta z_{zoom}(n>1)$: between subsequent Points	$\leq 1.5\cdot\Delta z_{zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3-4 GHz: ≥ 28 mm 4-5 GHz: ≥ 25 mm 5-6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the reported SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

6. DESCRIPTION OF TEST POSITION

6.1 EAR REFERENCE POINT

Figure 6-2 shows the front, back and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE.” Each ERP is on the B-M (back-mouth) line located 15 mm behind the entrance-to-ear-canal (EEC) point, as shown in Figure 6-1. The Reference Plane is defined as passing through the two ear reference point and point M. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (See Figure 5-1), Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning.




Figure 6-1
Close-up side view of ERP

6.2 HEAD POSITION

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The device under test was placed in a normal operating position with the acoustic output located along the “vertical centerline” on the front of the device aligned to the “ear reference point”(see Figure 6-3). The acoustic output was then located at the same level as the center of the ear reference point. The device under test was positioned so that the “vertical centerline” was bisecting the front surface of the handset at its top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 6-2
Front, back and side views of SAM Twin Phantom




Figure 6-3. Handset vertical and horizontal reference lines

6.3 Body Holster/Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration. A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with each accessory. If multiple accessory share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used.

Since this EUT does not supply any body worn accessory to the end user a distance of 1.5 cm from the EUT back surface to the liquid interface is configured for the generic test.

"See the Test SET-UP Photo"

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), Including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst case positioning is then documented and used to perform Body SAR testing.

6.4 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01r03 Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in Body-worn accessories. The Body-worn accessory procedures in FCC KDB Publication 447498 D01v06 should be used to test for Body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the Body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body- worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body- worn accessory with a headset attached to the handset.



Figure 6-4
Sample Body-Worn Diagram

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-dip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for Body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters. SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

6.5 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06v02r01 where SAR test considerations for handsets ($L \times W \geq 9\text{cm} \times 5\text{cm}$) are based on a composite test separation distance of 10 mm from the front back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the Body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some Body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions: i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 447498 D01v05 should be applied to determine SAR test requirements.

For smart phones with a display diagonal dimension $> 15.0\text{ cm}$ or an overall diagonal dimension $> 16.0\text{ cm}$ that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear. the phablets procedures outlined in KDB Publication 648474 D04 v01r02 should be applied to evaluate SAR compliance. A device marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance. In addition to the normally required head and body-worn accessory SAR test procedures required for handsets, the UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna $\leq 25\text{ mm}$ from that surface or edge, in direct contact with the phantom, for 10-g SAR. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (including tolerance) is 1-g SAR $> 1.2\text{ W/kg}$.

7. ANSI/ IEEE C95.1 - 1992 RF EXPOSURE LIMITS

HUMAN EXPOSURE	UNCONTROLLED ENVIRONMENT General Population	CONTROLLED ENVIRONMENT Occupational
	(W/kg) or (mW/g)	(W/kg) or (mW/g)
SPATIAL PEAK SAR * (Brain)	1.60	8.00
SPATIAL AVERAGE SAR ** (Whole Body)	0.08	0.40
SPATIAL PEAK SAR *** (Hands / Feet / Ankle / Wrist)	4.00	20.00

Table 8.1 Safety Limits for Partial Body Exposure

NOTES:

* The Spatial Peak value of the SAR averaged over any 1 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

** The Spatial Average value of the SAR averaged over the whole-body.

*** The Spatial Peak value of the SAR averaged over any 10 g of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

8. FCC SAR GENERAL MEASUREMENT PROCEDURES

8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as Reported SAR. The highest reported SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

8.2 3G SAR Test Reduction Procedure

8.2.1 GSM, GPRS AND EDGE

The following procedures may be considered for each frequency band to determine SAR test reduction for devices operating in GSM/GPRS/EDGE modes to demonstrate RF exposure compliance. GSM voice mode transmits with 1 time-slot. GPRS and EDGE may transmit up to 4 time slots in the 8 time-slot frame according to the multi-slot class implemented in a device.

8.2.2 SAR Test Reduction

In FCC KDB 941225 D01v03r01, certain transmission modes within a frequency band and wireless mode evaluated for SAR are defined as primary modes. The equivalent modes considered for SAR test reduction are denoted as secondary modes. When the maximum output power including tune-up tolerance specified for production units in a secondary mode is ≤ 0.25 dB higher than the primary mode or when the highest reported SAR of the primary mode, scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode, is ≤ 1.2 W/kg, SAR measurements are not required for the secondary mode. These criteria are referred to as the 3G SAR test reduction procedure. When the 3G SAR test reduction procedure is not satisfied, SAR measurements are additionally required for the secondary mode.

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested

8.3 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB 941225 D01v03r01 - 3G SAR Measurement Procedures. The handset was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluation SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement Software calculates a reference point at the start and end of the test to Check for power drifts. If conducted Power deviations of more than 5 % occurred, the tests were repeated.

8.4 SAR Measurement Conditions for UMTS

8.4.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in sec. 5.2 of 3GPP TS 34.121, using the appropriate RMC with TPC (transmit power control) set to all “1s” or applying the required inner loop power control procedures to maintain maximum output power while HSUPA is active. Results for all applicable physical channel configurations (DPCCH, DPDCHn and spreading codes, HS-DPCCH etc) are tabulated in this test report. All configurations that are not supported by the DUT or cannot be measured due to technical or equipment limitations are identified.

8.4.2 Head SAR Measurements

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all “1s”. The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for 12.2 kbps AMR in 3.4 kbps SRB (signaling radio bearer) using the highest reported SAR configuration in 12.2 kbps RMC for head exposure.

8.4.3 Body SAR measurements

SAR for body exposure configurations is measured using the 12.2kbps RMC with the TPC bits all “1s”. the 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCHn configurations supported by the handset with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured using and applicable RMC configuration with the corresponding spreading code or DPDCHn, for the highest reported SAR configuration in 12.2kbps RMC.

8.4.4 SAR Measurements with Rel. 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSDPA is measured using and FRC with H-SET 1 in Sub-test and a 12.2 kbps RMC without HSDPA. Handsets with both HSDPA and HSUPA are tested according to release 6 HSPA test procedures. 8.4.5 SAR Measurement with Rel.6 HSUPA The 3G SAR test Reduction Procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, Using H-Set 1 and QPSK for FRC and a 12.2kbps RMC configured in Test Loop Mode 1 and Power Control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing.

8.4.5 SAR Measurements with Rel. 6 HSUPA


The 3G SAR test reduction procedure is applied to HSPA (HSUPA/HSDPA with RMC) body configurations with 12.2 kbps RMC as the primary mode. Otherwise, Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA.

8.4.6 DC-HSDPA

UMTS SAR was tested under RMC 12.2 kbps with HSPA inactive per KDB publication 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

DC-HSDPA Considerations:

- 3GPP Specification 34.121-1 Release 8 Ver 8.10.0 was used for DC-HSDPA guidance
- H-Set 12(QPSK) was confirmed to be used during DC-HSDPA measurements
- Measured maximum output powers for DC-HSDPA were not greater than 1/4 dB higher than the WCDMA 12.2 kbps RMC maximum output and as a result, SAR is not required for DC-HSDPA
- The DUT supports UE category 24 for HSDPA.



8.5 SAR Measurement Conditions for LTE

LTE modes are tested according to FCC KDB 941225 D05v02r05 publication. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluation SAR [4]. The R&S CMW500 or Anritsu MT8820C simulators are used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

8.5.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

8.5.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36. 101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

8.5.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.

8.5.4 Required RB Size and RB offsets for SAR testing

According to FCC KDB 941225 D05v02r05

- a. Per sec 4.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/Kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
- b. Per Sec 4.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Sec 4.2.1.
- c. Per Sec. 4.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
- d. Per Sec. 4.2.4 and 4.3, SAR test for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sec. 4.2.1 through 4.2.3 is less than or equal to 1/2 dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/Kg.

8.5.5 LTE(TDD) Considerations

According to KDB 941225 D05v02r05, for Time-Division Duplex (TDD) systems, SAR must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP LTE TDD configurations.

SAR was tested with the highest transmission duty factor (63.33 %) using Uplink-downlink configuration 0 and Special subframe configuration 6.

LTE TDD Band 41 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special sub frame configurations.

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS)

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS		UpPTS		UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle – Extended cyclic prefix in uplink $\times (T_s) \times \#$ of S + $\#$ of U

Example for calculated Duty Cycle for Uplink-Downlink Configuration 0:

Calculated Duty Cycle = $5120 \times [1/(15000 \times 2048)] \times 2 + 6 \text{ ms} = 63.33 \%$

Where

$T_s = 1/(15000 \times 2048)$ seconds

8.6 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

8.6.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR system to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92-96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

8.6.2 Initial Test Position Procedure

For exposure conditions with multiple test positions, such as handset operating next to the ear, devices with hotspot mode or UMPC mini-tablet, procedures for initial test position can be applied. Using the transmission mode determined by the DSSS procedure or initial test configuration, area scans are measured for all positions in an exposure condition. The test position with the highest extrapolated (peak) SAR is used as the initial test position. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g SAR and ≤ 1.0 W/kg for 10g SAR, no additional testing for the remaining test position is required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg for 1g SAR and ≤ 2.0 W/kg for 10g SAR or all test positions are measured.

8.6.3 2.4 GHz SAR test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.

2.4 GHz 802.11 g/n OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

8.6.4 OFDM Transmission Mode and SAR Test channel Selection

For the 2.4 GHz, when the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate and lowest order 802.11 g/n mode. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11g and 802.11n with the same channel bandwidth, modulation and data rate etc., the lower order 802.11 mode i.e., 802.11g then 802.11n, is used for SAR measurement. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

8.6.5 Initial Test configuration Procedure

For OFDM, in both 2.4 GHZ, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, and lowest data rate. If the average RF output powers of the highest identical transmission modes are within 0.25 dB of each other, mid channel of the transmission mode with highest average RF output power is the initial test channel. Otherwise, the channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements.

8.6.6 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position on procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg for 1g SAR and ≤ 3.0 W/kg for 10g SAR, no additional SAR tests for the subsequent test configurations are required.

.

9. OUTPUT POWER SPECIFICATIONS

This device operates using the following maximum output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB publication 447498 D01v06.

9.1 GSM

9.1.1 Maximum Output Power (Main Ant.1and Main Ant.2 and Main Ant.3)

Main Ant.1and Main Ant.2

GSM Conducted output powers (Burst-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1				EDGE Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)	EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
Maximum Power		32.50	32.50	29.50	28.00	26.50	26.50	26.00	24.00	22.50
Nominal Power		32.00	32.00	29.00	27.50	26.00	26.00	25.50	23.50	22.00
GSM 850	128	32.11	32.10	29.38	27.97	26.48	26.14	25.14	23.12	22.14
	190	31.94	31.91	29.04	27.58	26.12	26.17	25.16	23.21	22.15
	251	32.10	32.09	29.37	27.96	26.48	26.13	25.08	23.17	22.06
Maximum Power		30.50	30.50	27.70	26.50	24.70	26.50	25.50	23.50	22.00
Nominal Power		30.00	30.00	27.20	26.00	24.20	26.00	25.00	23.00	21.50
GSM 1900	512	30.18	30.18	27.56	26.01	24.43	25.99	24.85	22.65	21.54
	661	30.21	30.20	27.64	26.15	24.57	26.13	25.12	23.00	21.81
	810	29.99	29.98	27.29	25.71	24.10	25.99	25.03	22.94	21.73

GSM Conducted output powers (Frame-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1				EDGE Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)	EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
Maximum Power		23.47	23.47	23.48	23.74	23.49	17.47	19.98	19.74	19.49
GSM 850	128	23.08	23.07	23.36	23.71	23.47	17.11	19.12	18.86	19.13
	190	22.91	22.88	23.02	23.32	23.11	17.14	19.14	18.95	19.14
	251	23.07	23.06	23.35	23.70	23.47	17.10	19.06	18.91	19.05
Maximum Power		21.47	21.47	21.68	22.24	21.69	17.47	19.48	19.24	18.99
GSM 1900	512	21.15	21.15	21.54	21.75	21.42	16.96	18.83	18.39	18.53
	661	21.18	21.17	21.62	21.89	21.56	17.10	19.10	18.74	18.80
	810	20.96	20.95	21.27	21.45	21.09	16.96	19.01	18.68	18.72

Main Ant.3

GSM Conducted output powers (Burst-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1				EDGE Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)	EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
Maximum Power		32.50	32.50	29.50	28.00	26.50	26.50	26.00	24.00	22.50
Nominal Power		32.00	32.00	29.00	27.50	26.00	26.00	25.50	23.50	22.00
GSM 850	128	31.71	31.72	28.60	27.15	25.58	25.25	24.18	22.16	21.08
	190	31.62	31.61	28.33	26.85	25.33	25.38	24.33	22.35	21.32
	251	31.86	31.85	28.58	27.10	25.55	25.51	24.51	22.53	21.43
Maximum Power		30.50	30.50	27.70	26.50	24.70	26.50	25.50	23.50	22.00
Nominal Power		30.00	30.00	27.20	26.00	24.20	26.00	25.00	23.00	21.50
GSM 1900	512	30.19	30.19	27.60	26.11	24.47	26.10	25.02	22.85	21.78
	661	30.22	30.22	27.62	26.25	24.52	26.21	25.17	23.05	21.95
	810	30.12	30.11	27.48	26.04	24.21	26.17	25.10	23.04	21.93

GSM Conducted output powers (Frame-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1				EDGE Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)	EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
Maximum Power		23.47	23.47	23.48	23.74	23.49	17.47	19.98	19.74	19.49
GSM 850	128	22.68	22.69	22.58	22.89	22.57	16.22	18.16	17.90	18.07
	190	22.59	22.58	22.31	22.59	22.32	16.35	18.31	18.09	18.31
	251	22.83	22.82	22.56	22.84	22.54	16.48	18.49	18.27	18.42
Maximum Power		21.47	21.47	21.68	22.24	21.69	17.47	19.48	19.24	18.99
GSM 1900	512	21.16	21.16	21.58	21.85	21.46	17.07	19.00	18.59	18.77
	661	21.19	21.19	21.60	21.99	21.51	17.18	19.15	18.79	18.94
	810	21.09	21.08	21.46	21.78	21.20	17.14	19.08	18.78	18.92

9.1.2 Reduced PCE Power – Main Ant 3 (Held to Ear)

GSM Conducted output powers (Burst-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1				EDGE Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)	EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
Maximum Power		30.20	30.20	26.50	24.70	23.00	25.50	24.50	22.50	21.50
Nominal Power		29.70	29.70	26.00	24.20	22.50	25.00	24.00	22.00	21.00
GSM 850	128	30.10	30.12	26.23	24.42	22.72	25.11	24.09	22.06	21.05
	190	29.81	29.81	25.82	24.04	22.27	25.18	24.11	22.05	21.11
	251	29.96	29.95	26.07	24.35	22.39	25.18	24.18	22.19	21.13
Maximum Power		28.50	28.50	25.00	23.00	21.00	25.00	24.00	22.00	20.50
Nominal Power		28.00	28.00	24.50	22.50	20.50	24.50	23.50	21.50	20.00
GSM 1900	512	28.28	28.27	24.83	22.86	20.96	24.80	23.71	21.59	20.45
	661	28.16	28.14	24.76	22.74	20.87	24.73	23.65	21.66	20.48
	810	27.57	27.57	24.82	22.76	20.57	24.43	23.47	21.44	20.28

GSM Conducted output powers (Frame-Average)

Band	Channel	Voice	GPRS(GMSK) Data – CS1				EDGE Data			
		GSM (dBm)	GPRS 1 TX Slot (dBm)	GPRS 2 TX Slot (dBm)	GPRS 3 TX Slot (dBm)	GPRS 4 TX Slot (dBm)	EDGE 1 TX Slot (dBm)	EDGE 2 TX Slot (dBm)	EDGE 3 TX Slot (dBm)	EDGE 4 TX Slot (dBm)
Maximum Power		21.17	21.17	20.48	20.44	19.99	16.47	18.48	18.24	18.49
GSM 850	128	21.07	21.09	20.21	20.16	19.71	16.08	18.07	17.80	18.04
	190	20.78	20.78	19.80	19.78	19.26	16.15	18.09	17.79	18.10
	251	20.93	20.92	20.05	20.09	19.38	16.15	18.16	17.93	18.12
Maximum Power		19.47	19.47	18.98	18.74	17.99	15.97	17.98	17.74	17.49
GSM 1900	512	19.25	19.24	18.81	18.60	17.95	15.77	17.69	17.33	17.44
	661	19.13	19.11	18.74	18.48	17.86	15.70	17.63	17.40	17.47
	810	18.54	18.54	18.80	18.50	17.56	15.40	17.45	17.18	17.27

Note:

Time slot average factor is as follows:


- 1 Tx slot = 9.03 dB, Frame-Average output power = Burst-Average output power – 9.03 dB
- 2 Tx slot = 6.02 dB, Frame-Average output power = Burst-Average output power – 6.02 dB
- 3 Tx slot = 4.26 dB, Frame-Average output power = Burst-Average output power – 4.26 dB
- 4 Tx slot = 3.01 dB, Frame-Average output power = Burst-Average output power – 3.01 dB

GSM Class : B

GSM voice: Head SAR , Body worn SAR

GPRS/EDGE Multi-slots 12 : Hotspot SAR with GPRS/EDGE

Multi-slot Class 12 with CS 1 (GMSK)



9.2 UMTS

HSPA+

This DUT is only capable of QPSK HSPA+ in uplink. Therefore, the RF conducted power is not measured according to 941225 D01 3G SAR.

9.2.1 Maximum Conducted Power

Main Ant.1

WCDMA Band 5

3GPP Release Version	Mode	3GPP 34.121	WCDMA Band 5 [dBm]			3GPP MPR
		Subtest	UL 4132 DL 4357	UL 4183 DL 4408	UL 4233 DL 4458	
99	WCDMA	12.2 kbps RMC	22.31	22.41	22.61	-
99	WCDMA	12.2 kbps AMR	22.28	22.39	22.60	-
5	HSDPA	Subtest 1	21.12	21.18	21.45	0
5		Subtest 2	21.08	21.26	21.44	0
5		Subtest 3	20.63	20.74	20.96	0.5
5		Subtest 4	20.62	20.74	20.95	0.5
6	HSUPA	Subtest 1	20.50	20.52	20.55	0
6		Subtest 2	20.31	20.35	20.44	2
6		Subtest 3	21.16	21.22	21.45	1
6		Subtest 4	19.61	19.73	19.94	2
6		Subtest 5	20.53	20.58	20.54	0
8	DC-HSDPA	Subtest 1	21.31	21.26	21.37	0
8		Subtest 2	21.32	21.29	21.34	0
8		Subtest 3	20.87	20.74	20.84	0.5
8		Subtest 4	20.85	20.79	20.83	0.5

WCDMA Average Conducted output powers

Main Ant.2

WCDMA Band 2

3GPP Release Version	Mode	3GPP 34.121	WCDMA Band 2 [dBm]			3GPP MPR
		Subtest	UL 9262 DL 9662	UL 9400 DL 9800	UL 9538 DL 9938	
99	WCDMA	12.2 kbps RMC	20.24	20.23	20.10	-
99	WCDMA	12.2 kbps AMR	20.23	20.20	20.11	-
5	HSDPA	Subtest 1	19.06	19.22	19.05	0
5		Subtest 2	19.10	19.17	19.02	0
5		Subtest 3	18.67	18.76	18.55	0.5
5		Subtest 4	18.67	18.71	18.53	0.5
6	HSUPA	Subtest 1	18.51	18.58	18.58	0
6		Subtest 2	18.29	18.30	18.18	2
6		Subtest 3	19.07	19.11	19.00	1
6		Subtest 4	17.67	17.64	17.50	2
6		Subtest 5	18.58	18.51	18.51	0
8	DC-HSDPA	Subtest 1	19.06	19.00	19.06	0
8		Subtest 2	18.98	18.97	19.05	0
8		Subtest 3	18.56	18.52	18.56	0.5
8		Subtest 4	18.54	18.47	18.54	0.5

WCDMA Average Conducted output powers

Main Ant 3

WCDMA Band 5

3GPP Release Version	Mode	3GPP 34.121	WCDMA Band 5 [dBm]			3GPP MPR
		Subtest	UL 4132 DL 4357	UL 4183 DL 4408	UL 4233 DL 4458	
99	WCDMA	12.2 kbps RMC	22.28	22.24	22.46	-
99	WCDMA	12.2 kbps AMR	22.26	22.24	22.45	-
5	HSDPA	Subtest 1	21.00	21.07	21.30	0
5		Subtest 2	21.05	21.08	21.29	0
5		Subtest 3	20.54	20.59	20.82	0.5
5		Subtest 4	20.55	20.59	20.81	0.5
6	HSUPA	Subtest 1	20.52	20.51	20.59	0
6		Subtest 2	20.09	20.13	20.33	2
6		Subtest 3	21.12	21.09	21.33	1
6		Subtest 4	19.65	19.59	19.82	2
6		Subtest 5	20.51	20.57	20.53	0
8	DC-HSDPA	Subtest 1	21.36	21.31	21.28	0
8		Subtest 2	21.38	21.31	21.28	0
8		Subtest 3	20.81	20.76	20.79	0.5
8		Subtest 4	20.83	20.74	20.79	0.5

WCDMA Average Conducted output powers

WCDMA Band 2

3GPP Release Version	Mode	3GPP 34.121	WCDMA Band 2 [dBm]			3GPP MPR
		Subtest	UL 9262 DL 9662	UL 9400 DL 9800	UL 9538 DL 9938	
99	WCDMA	12.2 kbps RMC	20.20	20.24	20.18	-
99	WCDMA	12.2 kbps AMR	20.18	20.21	20.12	-
5	HSDPA	Subtest 1	19.11	19.19	19.10	0
5		Subtest 2	19.12	19.18	19.09	0
5		Subtest 3	18.71	18.77	18.68	0.5
5		Subtest 4	18.70	18.74	18.69	0.5
6	HSUPA	Subtest 1	18.58	18.57	18.53	0
6		Subtest 2	18.42	18.41	18.32	2
6		Subtest 3	19.06	19.10	19.04	1
6		Subtest 4	17.62	17.61	17.52	2
6		Subtest 5	18.50	18.53	18.59	0
8	DC-HSDPA	Subtest 1	19.10	19.07	19.10	0
8		Subtest 2	19.08	19.02	19.06	0
8		Subtest 3	18.55	18.53	18.52	0.5
8		Subtest 4	18.56	18.52	18.56	0.5

It is expected by manufacture that MPR for some HSPA subtests may be up to 2dB more than specified by 3GPP, but also as low as 0dB according to the chipset implementation in this model.

9.2.2 Reduced PCE Power – Main ANT 3 (Held to Ear)

WCDMA Band 5

3GPP Release Version	Mode	3GPP 34.121	WCDMA Band 5 [dBm]			3GPP MPR
		Subtest	UL 4132 DL 4357	UL 4183 DL 4408	UL 4233 DL 4458	
99	WCDMA	12.2 kbps RMC	20.21	20.18	20.40	-
99	WCDMA	12.2 kbps AMR	20.20	20.18	20.39	-
5	HSDPA	Subtest 1	19.01	19.01	19.29	0
5		Subtest 2	19.02	19.02	19.25	0
5		Subtest 3	18.56	18.62	18.78	0.5
5		Subtest 4	18.51	18.57	18.76	0.5
6	HSUPA	Subtest 1	18.57	18.58	18.51	0
6		Subtest 2	18.06	18.09	18.33	2
6		Subtest 3	19.05	19.07	19.31	1
6		Subtest 4	17.61	17.61	17.82	2
6		Subtest 5	18.52	18.55	18.52	0
8	DC-HSDPA	Subtest 1	19.39	19.34	19.40	0
8		Subtest 2	19.38	19.33	19.39	0
8		Subtest 3	18.87	18.89	18.90	0.5
8		Subtest 4	18.88	18.86	18.89	0.5

WCDMA Average Conducted output powers

WCDMA Band 2

3GPP Release Version	Mode	3GPP 34.121	WCDMA Band 2 [dBm]			3GPP MPR
		Subtest	UL 9262 DL 9662	UL 9400 DL 9800	UL 9538 DL 9938	
99	WCDMA	12.2 kbps RMC	18.49	18.36	18.11	-
99	WCDMA	12.2 kbps AMR	18.46	18.36	18.11	-
5	HSDPA	Subtest 1	17.27	17.24	17.08	0
5		Subtest 2	17.29	17.21	17.01	0
5		Subtest 3	16.88	16.74	16.52	0.5
5		Subtest 4	16.88	16.71	16.53	0.5
6	HSUPA	Subtest 1	16.53	16.58	16.55	0
6		Subtest 2	16.43	16.38	16.18	2
6		Subtest 3	17.25	17.24	16.98	1
6		Subtest 4	15.74	15.75	15.58	2
6		Subtest 5	16.57	16.50	16.51	0
8	DC-HSDPA	Subtest 1	17.26	17.24	16.98	0
8		Subtest 2	17.22	17.18	16.98	0
8		Subtest 3	16.77	16.72	16.47	0.5
8		Subtest 4	16.75	16.70	16.48	0.5

WCDMA Average Conducted output powers

It is expected by manufacture that MPR for some HSPA subtests may be up to 2dB more than specified by 3GPP, but also as low as 0dB according to the chipset implementation in this model.

9.3 LTE

9.3.1 Maximum Output Power (Main Ant.1)

- LTE Band 5

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20407	20525	20643		
				824.7 MHz	836.5 MHz	848.3 MHz	[dB]	[dB]
1.4 MHz	QPSK	1	0	22.11	22.08	22.15	0	0
		1	3	22.10	22.13	22.19	0	0
		1	5	22.13	22.11	22.20	0	0
		3	0	22.32	22.21	22.25	0	0
		3	1	22.25	22.19	22.22	0	0
		3	3	22.24	22.28	22.30	0	0
		6	0	21.14	21.10	21.11	0-1	1
	16QAM	1	0	21.27	21.23	21.26	0-1	1
		1	3	21.22	21.26	21.13	0-1	1
		1	5	21.23	21.25	21.23	0-1	1
		3	0	21.28	21.31	21.24	0-1	1
		3	1	21.26	21.29	21.27	0-1	1
		3	3	21.21	21.21	21.26	0-1	1
		6	0	20.20	20.17	20.16	0-2	2
	64QAM	1	0	20.22	20.17	20.02	0-2	2
		1	3	20.21	20.19	19.93	0-2	2
		1	5	20.22	20.13	20.10	0-2	2
		3	0	20.27	20.10	20.18	0-2	2
		3	1	20.30	20.16	20.21	0-2	2
		3	3	20.22	20.17	20.24	0-2	2
		6	0	19.60	19.51	19.5	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20415	20525	20635		
				825.5 MHz	836.5 MHz	847.5 MHz	[dB]	[dB]
3 MHz	QPSK	1	0	22.15	22.16	22.21	0	0
		1	7	22.09	22.13	22.18	0	0
		1	14	22.08	22.13	22.16	0	0
		8	0	21.23	21.21	21.28	0-1	1
		8	3	21.24	21.22	21.25	0-1	1
		8	7	21.29	21.26	21.30	0-1	1
		15	0	21.23	21.24	21.27	0-1	1
	16QAM	1	0	21.28	21.28	21.21	0-1	1
		1	7	21.22	21.25	21.22	0-1	1
		1	14	21.26	21.28	21.23	0-1	1
		8	0	20.13	20.16	20.19	0-2	2
		8	3	20.14	20.16	20.19	0-2	2
		8	7	20.17	20.20	20.22	0-2	2
		15	0	20.14	20.13	20.31	0-2	2
	64QAM	1	0	20.14	20.16	20.17	0-2	2
		1	7	20.17	20.23	20.21	0-2	2
		1	14	20.30	20.24	20.17	0-2	2
		8	0	19.33	19.22	19.16	0-3	3
		8	3	19.32	19.18	19.15	0-3	3
		8	7	19.32	19.20	19.14	0-3	3
		15	0	19.23	19.18	19.25	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP [dB]	MPR [dB]
				20425	20525	20625	[dB]	[dB]
				826.5 MHz	836.5 MHz	846.5 MHz		
5 MHz	QPSK	1	0	22.13	22.10	22.18	0	0
		1	12	22.17	22.13	22.21	0	0
		1	24	22.12	22.08	22.16	0	0
		12	0	21.20	21.21	21.26	0-1	1
		12	6	21.22	21.18	21.18	0-1	1
		12	11	21.21	21.21	21.15	0-1	1
		25	0	21.18	21.20	21.20	0-1	1
	16QAM	1	0	21.11	21.19	21.08	0-1	1
		1	12	21.12	21.16	21.06	0-1	1
		1	24	21.02	21.02	21.08	0-1	1
		12	0	20.24	20.21	20.21	0-2	2
		12	6	20.24	20.20	20.14	0-2	2
		12	11	20.23	20.20	20.19	0-2	2
		25	0	20.20	20.24	20.21	0-2	2
	64QAM	1	0	20.13	20.16	20.12	0-2	2
		1	12	20.15	20.12	20.19	0-2	2
		1	24	20.18	20.16	20.16	0-2	2
		12	0	19.38	19.31	19.28	0-3	3
		12	6	19.43	19.31	19.26	0-3	3
		12	11	19.42	19.29	19.25	0-3	3
		25	0	19.34	19.29	19.33	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)	MPR Allowed Per 3GPP	MPR
				20525	[dB]	[dB]
				836.5 MHz		
10 MHz	QPSK	1	0	22.23	0	0
		1	24	22.11	0	0
		1	49	22.21	0	0
		25	0	21.27	0-1	1
		25	12	21.20	0-1	1
		25	24	21.17	0-1	1
		50	0	21.24	0-1	1
	16QAM	1	0	21.27	0-1	1
		1	24	21.26	0-1	1
		1	49	21.29	0-1	1
		25	0	20.28	0-2	2
		25	12	20.21	0-2	2
		25	24	20.18	0-2	2
		50	0	20.27	0-2	2
	64QAM	1	0	20.25	0-2	2
		1	24	20.21	0-2	2
		1	49	20.26	0-2	2
		25	0	19.40	0-3	3
		25	12	19.34	0-3	3
		25	24	19.24	0-3	3
		50	0	19.28	0-3	3

Note: LTE Band 5 at 10 MHz Bandwidth does not support three non-overlapping channels. Per KDB 941225 D05v02r04, when a device supports overlapping channel assignment in a channel bandwidth configuration, the mid channel of the group of overlapping channels should be selected for testing.

- LTE Band 7

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20775	21100	21425		
				2502.5MHz	2535MHz	2567.5MHz	[dB]	[dB]
5 MHz	QPSK	1	0	21.08	21.28	21.19	0	0
		1	12	21.12	21.38	21.22	0	0
		1	24	21.05	21.31	21.12	0	0
		12	0	20.07	20.34	20.27	0-1	1
		12	6	20.11	20.37	20.22	0-1	1
		12	11	20.12	20.36	20.19	0-1	1
		25	0	20.12	20.36	20.24	0-1	1
	16QAM	1	0	20.12	20.11	20.14	0-1	1
		1	12	20.10	20.14	20.16	0-1	1
		1	24	20.33	20.13	20.16	0-1	1
		12	0	19.12	19.35	19.29	0-2	2
		12	6	19.14	19.38	19.24	0-2	2
		12	11	19.13	19.37	19.18	0-2	2
		25	0	19.12	19.37	19.22	0-2	2
	64QAM	1	0	19.13	19.14	19.04	0-2	2
		1	12	19.12	19.16	19.07	0-2	2
		1	24	19.15	19.10	19.06	0-2	2
		12	0	18.16	18.04	18.05	0-3	3
		12	6	17.98	17.99	17.97	0-3	3
		12	11	17.99	17.99	17.93	0-3	3
		25	0	18.08	17.95	17.93	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20800	21100	21400		
				2505MHz	2535MHz	2565MHz	[dB]	[dB]
10 MHz	QPSK	1	0	21.11	21.30	21.25	0	0
		1	24	21.09	21.32	21.20	0	0
		1	49	21.15	21.39	21.22	0	0
		25	0	20.11	20.37	20.39	0-1	1
		25	12	20.12	20.37	20.27	0-1	1
		25	24	20.18	20.35	20.13	0-1	1
		50	0	20.16	20.39	20.29	0-1	1
	16QAM	1	0	20.12	20.15	20.16	0-1	1
		1	24	20.09	20.15	20.15	0-1	1
		1	49	20.16	20.14	20.15	0-1	1
		25	0	19.13	19.42	19.40	0-2	2
		25	12	19.13	19.38	19.27	0-2	2
		25	24	19.18	19.37	19.13	0-2	2
		50	0	19.14	19.36	19.26	0-2	2
	64QAM	1	0	19.50	19.17	18.88	0-2	2
		1	24	19.43	19.19	18.93	0-2	2
		1	49	19.49	19.23	19.02	0-2	2
		25	0	18.12	17.98	18.12	0-3	3
		25	12	18.13	17.95	18.03	0-3	3
		25	24	18.18	17.97	17.94	0-3	3
		50	0	18.05	18.02	18.00	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20825	21100	21375		
				2507.5MHz	2535MHz	2562.5MHz	[dB]	[dB]
15 MHz	QPSK	1	0	21.24	21.37	21.38	0	0
		1	36	21.10	21.32	21.23	0	0
		1	74	21.22	21.42	21.26	0	0
		36	0	20.17	20.45	20.43	0-1	1
		36	18	20.15	20.38	20.31	0-1	1
		36	38	20.27	20.39	20.16	0-1	1
		75	0	20.22	20.42	20.30	0-1	1
	16QAM	1	0	20.10	20.11	20.18	0-1	1
		1	36	20.14	20.10	20.16	0-1	1
		1	74	20.19	20.18	20.14	0-1	1
		36	0	19.15	19.43	19.37	0-2	2
		36	18	19.13	19.37	19.27	0-2	2
		36	38	19.25	19.37	19.13	0-2	2
		75	0	19.22	19.42	19.29	0-2	2
	64QAM	1	0	19.12	19.10	19.12	0-2	2
		1	36	19.11	19.22	19.15	0-2	2
		1	74	19.15	19.17	19.29	0-2	2
		36	0	18.04	18.06	18.05	0-3	3
		36	18	18.02	17.96	18.03	0-3	3
		36	38	18.08	17.98	17.99	0-3	3
		75	0	18.09	18.02	18.13	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20850	21100	21350		
				2510MHz	2535MHz	2560MHz	[dB]	[dB]
20 MHz	QPSK	1	0	21.44	21.43	21.35	0	0
		1	49	21.09	21.31	21.22	0	0
		1	99	21.31	21.43	21.31	0	0
		50	0	20.16	20.56	20.47	0-1	1
		50	25	20.20	20.40	20.34	0-1	1
		50	49	20.39	20.42	20.14	0-1	1
		100	0	20.28	20.49	20.30	0-1	1
	16QAM	1	0	20.13	20.11	20.17	0-1	1
		1	49	20.11	20.18	20.10	0-1	1
		1	99	20.11	20.12	20.13	0-1	1
		50	0	19.17	19.53	19.42	0-2	2
		50	25	19.20	19.39	19.31	0-2	2
		50	49	19.37	19.41	19.11	0-2	2
		100	0	19.27	19.48	19.26	0-2	2
	64QAM	1	0	19.23	19.22	19.18	0-2	2
		1	49	19.23	19.31	19.02	0-2	2
		1	99	19.35	19.47	19.27	0-2	2
		50	0	18.05	18.13	17.99	0-3	3
		50	25	18.05	18.00	18.02	0-3	3
		50	49	18.19	18.01	17.88	0-3	3
		100	0	18.09	18.09	17.96	0-3	3

- LTE TDD Band 38

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37775	38000	38225		
				2572.5 MHz	2595 MHz	2617.5 MHz	[dB]	[dB]
5 MHz	QPSK	1	0	21.19	21.47	20.72	0	0
		1	12	21.28	21.56	20.64	0	0
		1	24	21.23	21.44	20.54	0	0
		12	0	20.24	20.55	19.69	0-1	1
		12	6	20.30	20.62	19.69	0-1	1
		12	11	20.33	20.63	19.64	0-1	1
		25	0	20.28	20.59	19.67	0-1	1
	16QAM	1	0	19.98	20.25	19.76	0-1	1
		1	12	20.06	20.33	19.65	0-1	1
		1	24	20.02	20.21	19.53	0-1	1
		12	0	19.28	19.59	18.72	0-2	2
		12	6	19.35	19.65	18.73	0-2	2
		12	11	19.37	19.64	18.69	0-2	2
		25	0	19.29	19.58	18.66	0-2	2
	64QAM	1	0	19.00	19.29	18.72	0-2	2
		1	12	19.06	19.35	18.73	0-2	2
		1	24	19.03	19.24	18.74	0-2	2
		12	0	18.23	18.52	17.68	0-3	3
		12	6	18.31	18.60	17.68	0-3	3
		12	11	18.32	18.60	17.64	0-3	3
		25	0	18.26	18.54	17.63	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37800	38000	38200		
				2575 MHz	2595 MHz	2615 MHz	[dB]	[dB]
10 MHz	QPSK	1	0	21.25	21.50	21.01	0	0
		1	24	21.28	21.51	20.77	0	0
		1	49	21.40	21.51	20.61	0	0
		25	0	20.30	20.58	19.92	0-1	1
		25	12	20.35	20.59	19.85	0-1	1
		25	24	20.39	20.63	19.79	0-1	1
		50	0	20.35	20.62	19.86	0-1	1
	16QAM	1	0	19.99	20.26	19.97	0-1	1
		1	24	20.03	20.29	19.74	0-1	1
		1	49	20.15	20.25	19.56	0-1	1
		25	0	19.32	19.58	18.94	0-2	2
		25	12	19.36	19.60	18.86	0-2	2
		25	24	19.41	19.63	18.78	0-2	2
		50	0	19.33	19.57	18.81	0-2	2
	64QAM	1	0	19.00	19.29	18.78	0-2	2
		1	24	19.04	19.32	18.65	0-2	2
		1	49	19.17	19.28	18.76	0-2	2
		25	0	18.27	18.53	17.89	0-3	3
		25	12	18.33	18.56	17.86	0-3	3
		25	24	18.37	18.61	17.77	0-3	3
		50	0	18.31	18.55	17.81	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37825	38000	38175		
				2577.5 MHz	2595 MHz	2612.5 MHz	[dB]	[dB]
15 MHz	QPSK	1	0	21.36	21.56	21.30	0	0
		1	36	21.32	21.52	20.89	0	0
		1	74	21.48	21.43	20.64	0	0
		36	0	20.38	20.63	20.16	0-1	1
		36	18	20.39	20.64	20.00	0-1	1
		36	38	20.47	20.62	19.86	0-1	1
		75	0	20.42	20.62	19.99	0-1	1
	16QAM	1	0	20.11	20.33	19.97	0-1	1
		1	36	20.09	20.30	19.67	0-1	1
		1	74	20.22	20.19	19.51	0-1	1
		36	0	19.33	19.58	19.13	0-2	2
		36	18	19.37	19.59	18.97	0-2	2
		36	38	19.43	19.57	18.83	0-2	2
		75	0	19.39	19.57	18.95	0-2	2
	64QAM	1	0	19.11	19.36	19.07	0-2	2
		1	36	19.09	19.28	18.68	0-2	2
		1	74	19.24	19.20	18.60	0-2	2
		36	0	18.32	18.55	18.09	0-3	3
		36	18	18.34	18.53	17.93	0-3	3
		36	38	18.41	18.54	17.80	0-3	3
		75	0	18.41	18.58	17.99	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37850	38000	38150		
				2580 MHz	2595 MHz	2610 MHz	[dB]	[dB]
20 MHz	QPSK	1	0	21.47	21.63	21.58	0	0
		1	49	21.32	21.49	21.02	0	0
		1	99	21.65	21.45	20.74	0	0
		50	0	20.43	20.64	20.32	0-1	1
		50	25	20.44	20.62	20.12	0-1	1
		50	49	20.57	20.65	20.02	0-1	1
		100	0	20.50	20.64	20.16	0-1	1
	16QAM	1	0	20.20	20.37	20.31	0-1	1
		1	49	20.08	20.28	19.78	0-1	1
		1	99	20.39	20.19	19.60	0-1	1
		50	0	19.41	19.60	19.26	0-2	2
		50	25	19.39	19.60	19.07	0-2	2
		50	49	19.52	19.60	18.97	0-2	2
		100	0	19.48	19.62	19.13	0-2	2
	64QAM	1	0	19.22	19.18	19.15	0-2	2
		1	49	19.11	19.29	18.79	0-2	2
		1	99	19.22	19.21	18.73	0-2	2
		50	0	18.40	18.58	18.23	0-3	3
		50	25	18.38	18.57	18.06	0-3	3
		50	49	18.51	18.58	17.96	0-3	3
		100	0	18.47	18.60	18.10	0-3	3

- LTE TDD Band 41

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40265	40740	41215		
				2557.5 MHz	2605 MHz	2652.5 MHz	[dB]	[dB]
5 MHz	QPSK	1	0	21.26	21.20	20.96	0	0
		1	12	21.32	21.19	21.08	0	0
		1	24	21.25	21.05	21.05	0	0
		12	0	20.29	20.26	20.07	0-1	1
		12	6	20.35	20.26	20.12	0-1	1
		12	11	20.36	20.24	20.15	0-1	1
		25	0	20.32	20.26	20.11	0-1	1
	16QAM	1	0	20.09	19.99	19.76	0-1	1
		1	12	20.09	19.96	19.85	0-1	1
		1	24	20.02	19.84	19.84	0-1	1
		12	0	19.35	19.28	19.11	0-2	2
		12	6	19.39	19.29	19.16	0-2	2
		12	11	19.39	19.28	19.18	0-2	2
		25	0	19.32	19.25	19.11	0-2	2
	64QAM	1	0	19.06	19.02	18.75	0-2	2
		1	12	19.09	18.99	18.84	0-2	2
		1	24	19.04	18.86	18.83	0-2	2
		12	0	18.29	18.26	18.04	0-3	3
		12	6	18.33	18.25	18.12	0-3	3
		12	11	18.33	18.24	18.11	0-3	3
		25	0	18.30	18.22	18.06	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40290	40740	41190	[dB]	[dB]
				2560 MHz	2605 MHz	2650 MHz		
10 MHz	QPSK	1	0	21.31	21.35	20.89	0	0
		1	24	21.26	21.18	20.98	0	0
		1	49	21.33	21.08	21.14	0	0
		25	0	20.31	20.29	20.00	0-1	1
		25	12	20.30	20.26	20.07	0-1	1
		25	24	20.32	20.22	20.13	0-1	1
		50	0	20.32	20.26	20.07	0-1	1
	16QAM	1	0	20.04	20.13	19.63	0-1	1
		1	24	20.02	19.96	19.73	0-1	1
		1	49	20.10	19.83	19.89	0-1	1
		25	0	19.33	19.30	19.01	0-2	2
		25	12	19.34	19.27	19.07	0-2	2
		25	24	19.32	19.22	19.12	0-2	2
		50	0	19.29	19.22	19.03	0-2	2
	64QAM	1	0	19.04	19.11	18.63	0-2	2
		1	24	19.03	18.95	18.74	0-2	2
		1	49	19.08	18.84	18.90	0-2	2
		25	0	18.29	18.25	17.95	0-3	3
		25	12	18.28	18.21	18.02	0-3	3
		25	24	18.29	18.20	18.08	0-3	3
		50	0	18.27	18.18	18.01	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40315	40740	41165		
				2562.5 MHz	2605 MHz	2647.5 MHz	[dB]	[dB]
15 MHz	QPSK	1	0	21.43	21.49	20.88	0	0
		1	36	21.29	21.18	20.90	0	0
		1	74	21.36	21.02	21.16	0	0
		36	0	20.41	20.42	19.96	0-1	1
		36	18	20.36	20.30	20.00	0-1	1
		36	39	20.37	20.22	20.11	0-1	1
		75	0	20.39	20.31	20.03	0-1	1
	16QAM	1	0	20.20	20.26	19.62	0-1	1
		1	36	20.06	19.95	19.66	0-1	1
		1	74	20.12	19.76	19.91	0-1	1
		36	0	19.37	19.38	18.91	0-2	2
		36	18	19.32	19.26	18.97	0-2	2
		36	39	19.34	19.18	19.08	0-2	2
		75	0	19.34	19.27	18.98	0-2	2
	64QAM	1	0	19.18	19.29	18.61	0-2	2
		1	36	19.04	18.95	18.65	0-2	2
		1	74	19.10	18.76	18.91	0-2	2
		36	0	18.34	18.33	17.87	0-3	3
		36	18	18.29	18.21	17.93	0-3	3
		36	39	18.30	18.14	18.03	0-3	3
		75	0	18.36	18.27	18.00	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40340	40740	41140		
				2565 MHz	2605 MHz	2645 MHz	[dB]	[dB]
20 MHz	QPSK	1	0	21.52	21.62	20.88	0	0
		1	49	21.24	21.16	20.81	0	0
		1	99	21.47	20.98	21.22	0	0
		50	0	20.42	20.46	19.90	0-1	1
		50	25	20.34	20.29	19.92	0-1	1
		50	49	20.39	20.23	20.07	0-1	1
		100	0	20.40	20.34	19.98	0-1	1
	16QAM	1	0	20.25	20.35	19.60	0-1	1
		1	49	20.00	19.92	19.57	0-1	1
		1	99	20.20	19.72	19.96	0-1	1
		50	0	19.40	19.41	18.84	0-2	2
		50	25	19.30	19.27	18.90	0-2	2
		50	49	19.36	19.18	19.03	0-2	2
		100	0	19.40	19.32	18.96	0-2	2
	64QAM	1	0	19.24	19.38	18.82	0-2	2
		1	49	19.01	18.95	18.77	0-2	2
		1	99	19.23	18.73	18.97	0-2	2
		50	0	18.37	18.40	17.82	0-3	3
		50	25	18.29	18.24	17.87	0-3	3
		50	49	18.34	18.17	18.01	0-3	3
		100	0	18.37	18.28	17.94	0-3	3

9.3.1 Maximum Output Power (Main Ant.3)

- LTE Band 5

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20407	20525	20643		
				824.7 MHz	836.5 MHz	848.3 MHz	[dB]	[dB]
1.4 MHz	QPSK	1	0	21.89	21.77	21.78	0	0
		1	3	21.93	21.78	21.81	0	0
		1	5	21.93	21.8	21.84	0	0
		3	0	22.02	21.98	21.87	0	0
		3	1	22.00	21.91	21.84	0	0
		3	3	22.08	21.92	21.94	0	0
		6	0	20.93	20.81	20.74	0-1	1
	16QAM	1	0	21.25	21.22	20.90	0-1	1
		1	3	21.15	21.16	20.77	0-1	1
		1	5	21.23	21.28	20.88	0-1	1
		3	0	21.12	21.13	20.96	0-1	1
		3	1	21.08	21.13	20.91	0-1	1
		3	3	21.19	21.25	20.89	0-1	1
		6	0	20.02	19.89	19.83	0-2	2
	64QAM	1	0	20.37	20.29	20.25	0-2	2
		1	3	20.22	20.23	20.26	0-2	2
		1	5	20.30	20.29	20.28	0-2	2
		3	0	20.23	20.10	20.02	0-2	2
		3	1	20.33	20.27	20.18	0-2	2
		3	3	20.30	20.28	20.20	0-2	2
		6	0	19.10	19.10	19.07	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20415	20525	20635		
				825.5 MHz	836.5 MHz	847.5 MHz	[dB]	[dB]
3 MHz	QPSK	1	0	21.90	21.88	21.80	0	0
		1	7	21.88	21.85	21.78	0	0
		1	14	21.89	21.81	21.76	0	0
		8	0	21.02	20.93	20.87	0-1	1
		8	3	21.01	20.93	20.86	0-1	1
		8	7	21.04	20.95	20.90	0-1	1
		15	0	21.00	20.94	20.90	0-1	1
	16QAM	1	0	21.41	21.10	21.12	0-1	1
		1	7	21.33	21.12	21.12	0-1	1
		1	14	21.32	21.11	21.14	0-1	1
		8	0	20.12	20.08	20.04	0-2	2
		8	3	20.11	20.08	20.04	0-2	2
		8	7	20.13	20.14	20.07	0-2	2
		15	0	20.11	20.02	20.02	0-2	2
	64QAM	1	0	20.15	19.84	20.13	0-2	2
		1	7	19.97	19.94	20.11	0-2	2
		1	14	20.08	20.21	20.11	0-2	2
		8	0	19.22	19.12	18.93	0-3	3
		8	3	19.20	19.11	18.93	0-3	3
		8	7	19.17	19.11	18.96	0-3	3
		15	0	19.15	18.99	18.89	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP [dB]	MPR [dB]
				20425	20525	20625	[dB]	[dB]
				826.5 MHz	836.5 MHz	846.5 MHz		
5 MHz	QPSK	1	0	21.87	21.88	21.84	0	0
		1	12	21.95	21.90	21.86	0	0
		1	24	21.93	21.83	21.81	0	0
		12	0	20.95	20.90	20.94	0-1	1
		12	6	20.98	20.88	20.84	0-1	1
		12	11	20.92	20.87	20.77	0-1	1
		25	0	20.89	20.90	20.84	0-1	1
	16QAM	1	0	21.50	21.18	21.10	0-1	1
		1	12	21.45	21.25	21.16	0-1	1
		1	24	21.36	21.2	21.15	0-1	1
		12	0	19.98	19.88	19.88	0-2	2
		12	6	20.00	19.86	19.81	0-2	2
		12	11	19.96	19.85	19.73	0-2	2
		25	0	19.91	19.92	19.87	0-2	2
	64QAM	1	0	20.19	20.12	19.92	0-2	2
		1	12	20.17	20.18	19.93	0-2	2
		1	24	20.20	20.11	19.90	0-2	2
		12	0	18.90	18.98	18.85	0-3	3
		12	6	18.99	19.00	18.78	0-3	3
		12	11	19.03	19.02	18.71	0-3	3
		25	0	18.94	18.89	18.82	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)	MPR Allowed Per 3GPP	MPR
				20525	[dB]	[dB]
				836.5 MHz		
10 MHz	QPSK	1	0	22.00	0	0
		1	24	21.84	0	0
		1	49	21.88	0	0
		25	0	21.03	0-1	1
		25	12	20.92	0-1	1
		25	24	20.93	0-1	1
		50	0	21.00	0-1	1
	16QAM	1	0	21.38	0-1	1
		1	24	21.35	0-1	1
		1	49	21.40	0-1	1
		25	0	20.05	0-2	2
		25	12	19.94	0-2	2
		25	24	19.96	0-2	2
		50	0	20.05	0-2	2
	64QAM	1	0	20.37	0-2	2
		1	24	20.37	0-2	2
		1	49	20.39	0-2	2
		25	0	19.21	0-3	3
		25	12	19.12	0-3	3
		25	24	19.13	0-3	3
		50	0	19.20	0-3	3

Note: LTE Band 5 at 10 MHz Bandwidth does not support three non-overlapping channels. Per KDB 941225 D05v02r04, when a device supports overlapping channel assignment in a channel bandwidth configuration, the mid channel of the group of overlapping channels should be selected for testing.

- LTE Band 7

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20775	21100	21425		
				2502.5MHz	2535MHz	2567.5MHz	[dB]	[dB]
5 MHz	QPSK	1	0	21.89	21.83	21.82	0	0
		1	12	21.92	21.91	21.85	0	0
		1	24	21.87	21.88	21.81	0	0
		12	0	20.92	20.91	20.94	0-1	1
		12	6	20.97	20.96	20.93	0-1	1
		12	11	20.99	20.96	20.92	0-1	1
		25	0	20.97	20.96	20.95	0-1	1
	16QAM	1	0	21.16	21.11	21.09	0-1	1
		1	12	21.21	21.20	21.12	0-1	1
		1	24	21.20	21.16	21.08	0-1	1
		12	0	19.95	19.95	19.95	0-2	2
		12	6	20.00	19.97	19.95	0-2	2
		12	11	20.01	19.98	19.93	0-2	2
		25	0	19.98	19.95	19.93	0-2	2
	64QAM	1	0	20.17	19.87	20.17	0-2	2
		1	12	20.18	19.94	20.12	0-2	2
		1	24	20.13	19.92	20.10	0-2	2
		12	0	19.12	18.94	18.88	0-3	3
		12	6	19.16	18.96	18.91	0-3	3
		12	11	19.03	18.94	18.84	0-3	3
		25	0	19.05	19.00	19.00	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20800	21100	21400		
				2505MHz	2535MHz	2565MHz	[dB]	[dB]
10 MHz	QPSK	1	0	21.93	21.86	21.83	0	0
		1	24	21.88	21.90	21.83	0	0
		1	49	21.93	21.98	21.91	0	0
		25	0	20.94	20.99	21.06	0-1	1
		25	12	20.97	20.97	20.96	0-1	1
		25	24	21.02	20.98	20.89	0-1	1
		50	0	21.01	21.00	21.01	0-1	1
	16QAM	1	0	21.19	21.10	21.08	0-1	1
		1	24	21.16	21.16	21.08	0-1	1
		1	49	21.18	21.28	21.10	0-1	1
		25	0	19.95	19.98	20.04	0-2	2
		25	12	19.96	19.97	19.96	0-2	2
		25	24	20.02	19.98	19.88	0-2	2
		50	0	19.98	19.97	19.97	0-2	2
	64QAM	1	0	20.10	20.14	20.22	0-2	2
		1	24	20.16	20.19	20.06	0-2	2
		1	49	20.18	20.41	20.12	0-2	2
		25	0	19.07	19.10	19.05	0-3	3
		25	12	19.11	19.07	18.97	0-3	3
		25	24	19.19	19.07	18.90	0-3	3
		50	0	19.09	19.08	19.00	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20825	21100	21375		
				2507.5MHz	2535MHz	2562.5MHz	[dB]	[dB]
15 MHz	QPSK	1	0	22.03	21.95	21.90	0	0
		1	36	21.86	21.89	21.85	0	0
		1	74	21.95	22.03	21.95	0	0
		36	0	20.97	21.05	21.07	0-1	1
		36	18	20.95	21.01	20.99	0-1	1
		36	38	21.03	21.03	20.95	0-1	1
		75	0	21.01	21.03	21.02	0-1	1
	16QAM	1	0	21.11	21.18	21.13	0-1	1
		1	36	21.13	21.17	21.09	0-1	1
		1	74	21.18	21.30	21.20	0-1	1
		36	0	19.96	20.01	20.02	0-2	2
		36	18	19.93	19.97	19.95	0-2	2
		36	38	20.00	20.02	19.90	0-2	2
		75	0	20.00	20.02	19.98	0-2	2
	64QAM	1	0	20.17	20.01	20.14	0-2	2
		1	36	20.02	19.93	20.10	0-2	2
		1	74	20.10	20.04	20.22	0-2	2
		36	0	19.12	19.07	19.07	0-3	3
		36	18	19.12	19.07	19.03	0-3	3
		36	38	19.15	19.11	18.98	0-3	3
		75	0	19.09	19.05	19.01	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20850	21100	21350		
				2510MHz	2535MHz	2560MHz	[dB]	[dB]
20 MHz	QPSK	1	0	22.11	22.02	22.01	0	0
		1	49	21.84	21.88	21.83	0	0
		1	99	22.03	22.10	22.08	0	0
		50	0	20.96	21.18	21.13	0-1	1
		50	25	20.99	21.04	21.01	0-1	1
		50	49	21.13	21.10	20.90	0-1	1
		100	0	21.02	21.12	21.00	0-1	1
	16QAM	1	0	21.10	21.04	21.04	0-1	1
		1	49	21.10	21.18	21.02	0-1	1
		1	99	21.08	21.01	21.05	0-1	1
		50	0	19.94	20.14	20.06	0-2	2
		50	25	19.96	20.00	19.96	0-2	2
		50	49	20.08	20.06	19.84	0-2	2
		100	0	20.02	20.09	19.94	0-2	2
	64QAM	1	0	20.19	20.17	20.18	0-2	2
		1	49	20.18	20.10	20.10	0-2	2
		1	99	20.16	20.16	20.12	0-2	2
		50	0	19.06	19.14	19.08	0-3	3
		50	25	19.06	19.03	19.01	0-3	3
		50	49	19.16	19.10	18.86	0-3	3
		100	0	19.13	19.14	19.01	0-3	3

- LTE TDD Band 38

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37775	38000	38225		
				2572.5 MHz	2595 MHz	2617.5 MHz	[dB]	[dB]
5 MHz	QPSK	1	0	22.09	22.29	21.74	0	0
		1	12	22.16	22.36	21.72	0	0
		1	24	22.11	22.26	21.58	0	0
		12	0	21.15	21.40	20.76	0-1	1
		12	6	21.21	21.45	20.78	0-1	1
		12	11	21.23	21.45	20.76	0-1	1
		25	0	21.19	21.43	20.75	0-1	1
	16QAM	1	0	20.87	21.11	20.53	0-1	1
		1	12	20.94	21.15	20.50	0-1	1
		1	24	20.90	21.06	20.36	0-1	1
		12	0	20.19	20.40	19.80	0-2	2
		12	6	20.24	20.48	19.81	0-2	2
		12	11	20.25	20.48	19.79	0-2	2
		25	0	20.19	20.42	19.75	0-2	2
	64QAM	1	0	19.99	20.15	19.78	0-2	2
		1	12	20.05	20.17	19.72	0-2	2
		1	24	20.02	20.07	19.70	0-2	2
		12	0	19.23	19.25	18.77	0-3	3
		12	6	19.29	19.34	18.77	0-3	3
		12	11	19.31	19.23	18.75	0-3	3
		25	0	19.26	19.30	18.74	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37800	38000	38200		
				2575 MHz	2595 MHz	2615 MHz	[dB]	[dB]
10 MHz	QPSK	1	0	22.16	22.33	22.06	0	0
		1	24	22.15	22.33	21.79	0	0
		1	49	22.26	22.30	21.69	0	0
		25	0	21.18	21.42	20.96	0-1	1
		25	12	21.23	21.45	20.88	0-1	1
		25	24	21.27	21.45	20.82	0-1	1
		50	0	21.24	21.45	20.90	0-1	1
	16QAM	1	0	20.92	21.08	20.80	0-1	1
		1	24	20.94	21.09	20.56	0-1	1
		1	49	21.01	21.05	20.44	0-1	1
		25	0	20.20	20.42	19.97	0-2	2
		25	12	20.24	20.46	19.89	0-2	2
		25	24	20.27	20.43	19.82	0-2	2
		50	0	20.22	20.40	19.88	0-2	2
	64QAM	1	0	20.03	20.12	19.87	0-2	2
		1	24	20.03	20.14	19.78	0-2	2
		1	49	20.14	20.11	19.86	0-2	2
		25	0	19.28	19.39	18.97	0-3	3
		25	12	19.31	19.41	18.88	0-3	3
		25	24	19.35	19.43	18.82	0-3	3
		50	0	19.28	19.39	18.87	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37825	38000	38175		
				2577.5 MHz	2595 MHz	2612.5 MHz	[dB]	[dB]
15 MHz	QPSK	1	0	22.24	22.38	22.31	0	0
		1	36	22.19	22.33	21.92	0	0
		1	74	22.41	22.28	21.75	0	0
		36	0	21.28	21.46	21.22	0-1	1
		36	18	21.29	21.45	21.06	0-1	1
		36	38	21.39	21.44	20.91	0-1	1
		75	0	21.32	21.43	21.05	0-1	1
	16QAM	1	0	21.01	21.13	21.07	0-1	1
		1	36	20.97	21.13	20.70	0-1	1
		1	74	21.17	21.03	20.51	0-1	1
		36	0	20.25	20.41	20.17	0-2	2
		36	18	20.26	20.42	20.01	0-2	2
		36	38	20.35	20.40	19.87	0-2	2
		75	0	20.29	20.39	20.02	0-2	2
	64QAM	1	0	20.12	19.96	20.13	0-2	2
		1	36	20.07	20.13	19.74	0-2	2
		1	74	20.28	20.07	19.73	0-2	2
		36	0	19.33	19.40	19.19	0-3	3
		36	18	19.33	19.39	19.00	0-3	3
		36	38	19.40	19.37	18.87	0-3	3
		75	0	19.41	19.42	19.06	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max. Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37850	38000	38150		
				2580 MHz	2595 MHz	2610 MHz	[dB]	[dB]
20 MHz	QPSK	1	0	22.37	22.44	22.34	0	0
		1	49	22.21	22.33	22.05	0	0
		1	99	22.45	22.31	21.85	0	0
		50	0	21.35	21.47	21.36	0-1	1
		50	25	21.35	21.48	21.16	0-1	1
		50	49	21.49	21.48	21.06	0-1	1
		100	0	21.43	21.49	21.21	0-1	1
	16QAM	1	0	21.09	21.17	21.30	0-1	1
		1	49	20.97	21.09	20.80	0-1	1
		1	99	21.34	21.03	20.59	0-1	1
		50	0	20.31	20.43	20.31	0-2	2
		50	25	20.32	20.43	20.11	0-2	2
		50	49	20.45	20.43	20.02	0-2	2
		100	0	20.41	20.44	20.18	0-2	2
	64QAM	1	0	20.14	20.16	20.30	0-2	2
		1	49	20.01	20.05	19.78	0-2	2
		1	99	20.40	19.98	19.74	0-2	2
		50	0	19.30	19.37	19.25	0-3	3
		50	25	19.30	19.35	19.05	0-3	3
		50	49	19.41	19.33	18.93	0-3	3
		100	0	19.38	19.37	19.08	0-3	3

- LTE TDD Band 41

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40265	40740	41215		
				2557.5 MHz	2605 MHz	2652.5 MHz	[dB]	[dB]
5 MHz	QPSK	1	0	22.16	22.22	22.34	0	0
		1	12	22.22	22.20	22.46	0	0
		1	24	22.14	22.08	22.46	0	0
		12	0	21.23	21.28	21.46	0-1	1
		12	6	21.25	21.30	21.50	0-1	1
		12	11	21.26	21.28	21.49	0-1	1
		25	0	21.23	21.28	21.50	0-1	1
	16QAM	1	0	20.96	21.00	21.11	0-1	1
		1	12	20.99	21.01	21.21	0-1	1
		1	24	20.94	20.87	21.21	0-1	1
		12	0	20.26	20.30	20.42	0-2	2
		12	6	20.31	20.32	20.41	0-2	2
		12	11	20.29	20.32	20.45	0-2	2
		25	0	20.25	20.27	20.40	0-2	2
	64QAM	1	0	20.10	19.91	20.02	0-2	2
		1	12	20.14	20.06	20.11	0-2	2
		1	24	20.08	19.96	20.13	0-2	2
		12	0	19.35	19.31	19.33	0-3	3
		12	6	19.37	19.32	19.40	0-3	3
		12	11	19.37	19.31	19.42	0-3	3
		25	0	19.35	19.30	19.35	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40290	40740	41190		
				2560 MHz	2605 MHz	2650 MHz	[dB]	[dB]
10 MHz	QPSK	1	0	22.25	22.38	22.29	0	0
		1	24	22.20	22.20	22.36	0	0
		1	49	22.24	22.12	22.46	0	0
		25	0	21.25	21.35	21.43	0-1	1
		25	12	21.25	21.30	21.43	0-1	1
		25	24	21.25	21.27	21.49	0-1	1
		50	0	21.26	21.32	21.46	0-1	1
	16QAM	1	0	20.99	21.14	21.03	0-1	1
		1	24	20.95	20.95	21.09	0-1	1
		1	49	20.99	20.87	21.27	0-1	1
		25	0	20.27	20.33	20.42	0-2	2
		25	12	20.26	20.30	20.47	0-2	2
		25	24	20.26	20.26	20.49	0-2	2
		50	0	20.22	20.28	20.45	0-2	2
	64QAM	1	0	20.15	20.02	19.95	0-2	2
		1	24	20.09	20.04	20.03	0-2	2
		1	49	20.12	20.03	20.18	0-2	2
		25	0	19.37	19.37	19.26	0-3	3
		25	12	19.35	19.32	19.33	0-3	3
		25	24	19.34	19.32	19.37	0-3	3
		50	0	19.34	19.29	19.29	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40315	40740	41165		
				2562.5 MHz	2605 MHz	2647.5 MHz	[dB]	[dB]
15 MHz	QPSK	1	0	22.34	22.47	22.21	0	0
		1	36	22.19	22.18	22.27	0	0
		1	74	22.27	22.09	22.41	0	0
		36	0	21.31	21.43	21.35	0-1	1
		36	18	21.27	21.33	21.40	0-1	1
		36	39	21.28	21.28	21.47	0-1	1
		75	0	21.31	21.34	21.42	0-1	1
	16QAM	1	0	21.10	21.23	20.97	0-1	1
		1	36	20.98	20.96	21.05	0-1	1
		1	74	21.01	20.83	21.33	0-1	1
		36	0	20.28	20.39	20.31	0-2	2
		36	18	20.24	20.30	20.37	0-2	2
		36	39	20.26	20.24	20.48	0-2	2
		75	0	20.27	20.29	20.37	0-2	2
	64QAM	1	0	20.24	20.43	19.90	0-2	2
		1	36	20.07	20.40	19.94	0-2	2
		1	74	20.14	19.88	20.22	0-2	2
		36	0	19.38	19.42	19.17	0-3	3
		36	18	19.32	19.30	19.21	0-3	3
		36	39	19.33	19.24	19.32	0-3	3
		75	0	19.41	19.37	19.29	0-3	3

Bandwidth	Modulation	RB Size	RB Offset	Max.Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40340	40740	41140		
				2565 MHz	2605 MHz	2645 MHz	[dB]	[dB]
20 MHz	QPSK	1	0	22.46	22.48	22.23	0	0
		1	49	22.17	22.19	22.19	0	0
		1	99	22.40	22.08	22.43	0	0
		50	0	21.37	21.47	21.32	0-1	1
		50	25	21.27	21.34	21.33	0-1	1
		50	49	21.34	21.31	21.45	0-1	1
		100	0	21.35	21.40	21.40	0-1	1
	16QAM	1	0	21.18	21.14	20.93	0-1	1
		1	49	20.93	20.95	20.94	0-1	1
		1	99	21.14	20.82	21.40	0-1	1
		50	0	20.32	20.42	20.26	0-2	2
		50	25	20.24	20.30	20.29	0-2	2
		50	49	20.31	20.29	20.42	0-2	2
		100	0	20.34	20.36	20.37	0-2	2
	64QAM	1	0	20.13	20.24	19.90	0-2	2
		1	49	20.06	20.03	19.87	0-2	2
		1	99	20.29	19.86	20.29	0-2	2
		50	0	19.46	19.50	19.16	0-3	3
		50	25	19.33	19.33	19.19	0-3	3
		50	49	19.40	19.28	19.32	0-3	3
		100	0	19.44	19.40	19.26	0-3	3

9.3.3 Reduced PCE Power – Main ANT 3 (Held to Ear)

- LTE Band 5

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20407	20525	20643		
				824.7 MHz	836.5 MHz	848.3 MHz	[dB]	[dB]
1.4 MHz	QPSK	1	0	19.82	19.69	19.62	0	0
		1	3	19.79	19.67	19.60	0	0
		1	5	19.80	19.69	19.63	0	0
		3	0	19.94	19.81	19.75	0	0
		3	1	19.94	19.81	19.74	0	0
		3	3	19.95	19.82	19.76	0	0
		6	0	19.90	19.77	19.71	0-1	0
	16QAM	1	0	19.89	19.83	19.72	0-1	0
		1	3	19.91	19.78	19.76	0-1	0
		1	5	19.93	19.82	19.78	0-1	0
		3	0	19.89	19.81	19.75	0-1	0
		3	1	19.78	19.97	19.92	0-1	0
		3	3	19.86	19.94	19.93	0-1	0
		6	0	19.96	19.85	19.81	0-2	0
	64QAM	1	0	19.90	19.95	19.96	0-2	0
		1	3	19.96	19.92	19.94	0-2	0
		1	5	19.91	20.00	19.97	0-2	0
		3	0	19.99	19.87	19.86	0-2	0
		3	1	20.01	19.89	19.81	0-2	0
		3	3	19.94	19.90	19.84	0-2	0
		6	0	19.82	19.77	19.71	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20415	20525	20635		
				825.5 MHz	836.5 MHz	847.5 MHz	[dB]	[dB]
3 MHz	QPSK	1	0	19.96	19.84	19.77	0	0
		1	7	19.96	19.81	19.76	0	0
		1	14	19.95	19.81	19.79	0	0
		8	0	19.98	19.84	19.81	0-1	0
		8	3	19.97	19.83	19.79	0-1	0
		8	7	19.97	19.81	19.77	0-1	0
		15	0	19.96	19.83	19.78	0-1	0
	16QAM	1	0	19.94	19.82	19.79	0-1	0
		1	7	19.97	19.83	19.80	0-1	0
		1	14	19.95	19.81	19.79	0-1	0
		8	0	19.84	19.91	19.86	0-2	0
		8	3	19.83	19.90	19.84	0-2	0
		8	7	19.99	19.88	19.82	0-2	0
		15	0	19.99	19.86	19.82	0-2	0
	64QAM	1	0	20.01	19.98	19.98	0-2	0
		1	7	20.04	20.01	20.01	0-2	0
		1	14	20.09	19.99	20.02	0-2	0
		8	0	19.84	19.78	19.74	0-3	0
		8	3	19.86	19.76	19.72	0-3	0
		8	7	19.81	19.74	19.64	0-3	0
		15	0	19.82	19.71	19.61	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back-off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20425	20525	20625	[dB]	[dB]
				826.5 MHz	836.5 MHz	846.5 MHz		
5 MHz	QPSK	1	0	19.94	19.82	19.74	0	0
		1	12	19.96	19.84	19.78	0	0
		1	24	19.87	19.78	19.73	0	0
		12	0	19.83	19.79	19.79	0-1	0
		12	6	19.91	19.80	19.73	0-1	0
		12	11	19.88	19.78	19.64	0-1	0
		25	0	19.85	19.77	19.71	0-1	0
	16QAM	1	0	19.84	19.81	19.72	0-1	0
		1	12	19.78	19.72	19.62	0-1	0
		1	24	19.81	19.77	19.74	0-1	0
		12	0	19.85	19.83	19.82	0-2	0
		12	6	19.93	19.84	19.77	0-2	0
		12	11	19.89	19.83	19.69	0-2	0
		25	0	19.85	19.81	19.73	0-2	0
	64QAM	1	0	20.03	20.04	19.95	0-2	0
		1	12	20.07	20.09	20.02	0-2	0
		1	24	20.00	20.05	19.97	0-2	0
		12	0	19.70	19.78	19.74	0-3	0
		12	6	19.82	19.74	19.76	0-3	0
		12	11	19.74	19.78	19.65	0-3	0
		25	0	19.71	19.76	19.67	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)	MPR Allowed Per 3GPP	MPR
				20525	[dB]	[dB]
				836.5 MHz		
10 MHz	QPSK	1	0	19.85	0	0
		1	24	19.81	0	0
		1	49	19.82	0	0
		25	0	19.94	0-1	0
		25	12	19.79	0-1	0
		25	24	19.78	0-1	0
		50	0	19.88	0-1	0
	16QAM	1	0	19.80	0-1	0
		1	24	19.81	0-1	0
		1	49	19.85	0-1	0
		25	0	19.96	0-2	0
		25	12	19.83	0-2	0
		25	24	19.82	0-2	0
		50	0	19.88	0-2	0
	16QAM	1	0	20.01	0-2	0
		1	24	20.01	0-2	0
		1	49	20.07	0-2	0
		25	0	19.84	0-3	0
		25	12	19.81	0-3	0
		25	24	19.77	0-3	0
		50	0	19.81	0-3	0

Note: LTE Band 5 at 10 MHz Bandwidth does not support three non-overlapping channels. Per KDB 941225 D05v02r04, when a device supports overlapping channel assignment in a channel bandwidth configuration, the mid channel of the group of overlapping channels should be selected for testing.

- LTE Band 7

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20775	21100	21425		
				2502.5MHz	2535MHz	2567.5MHz	[dB]	[dB]
5 MHz	QPSK	1	0	16.41	16.51	16.78	0	0
		1	12	16.42	16.59	16.81	0	0
		1	24	16.33	16.53	16.75	0	0
		12	0	16.33	16.50	16.78	0-1	0
		12	6	16.35	16.52	16.77	0-1	0
		12	11	16.36	16.52	16.74	0-1	0
		25	0	16.36	16.49	16.76	0-1	0
	16QAM	1	0	16.66	16.58	16.69	0-1	0
		1	12	16.57	16.63	16.63	0-1	0
		1	24	16.61	16.72	16.65	0-1	0
		12	0	16.39	16.54	16.62	0-2	0
		12	6	16.43	16.56	16.79	0-2	0
		12	11	16.41	16.54	16.77	0-2	0
		25	0	16.38	16.51	16.79	0-2	0
	64QAM	1	0	16.62	16.62	16.89	0-2	0
		1	12	16.50	16.69	16.96	0-2	0
		1	24	16.52	16.64	16.89	0-2	0
		12	0	16.37	16.48	16.78	0-3	0
		12	6	16.39	16.51	16.71	0-3	0
		12	11	16.32	16.47	16.69	0-3	0
		25	0	16.29	16.44	16.68	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20800	21100	21400	[dB]	[dB]
				2505MHz	2535MHz	2565MHz		
10 MHz	QPSK	1	0	16.46	16.51	16.82	0	0
		1	24	16.38	16.55	16.80	0	0
		1	49	16.40	16.62	16.84	0	0
		25	0	16.36	16.53	16.90	0-1	0
		25	12	16.36	16.52	16.78	0-1	0
		25	24	16.39	16.51	16.67	0-1	0
		50	0	16.40	16.53	16.80	0-1	0
	16QAM	1	0	16.67	16.68	16.64	0-1	0
		1	24	16.59	16.52	16.69	0-1	0
		1	49	16.62	16.64	16.63	0-1	0
		25	0	16.40	16.57	16.92	0-2	0
		25	12	16.39	16.55	16.82	0-2	0
		25	24	16.42	16.53	16.72	0-2	0
		50	0	16.41	16.55	16.82	0-2	0
	64QAM	1	0	16.62	16.60	16.81	0-2	0
		1	24	16.52	16.74	16.84	0-2	0
		1	49	16.58	16.70	16.91	0-2	0
		25	0	16.31	16.48	16.84	0-3	0
		25	12	16.32	16.45	16.71	0-3	0
		25	24	16.33	16.41	16.64	0-3	0
		50	0	16.28	16.44	16.71	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20825	21100	21375	[dB]	[dB]
				2507.5MHz	2535MHz	2562.5MHz		
15 MHz	QPSK	1	0	16.56	16.59	16.85	0	0
		1	36	16.39	16.55	16.81	0	0
		1	74	16.48	16.67	16.87	0	0
		36	0	16.43	16.59	16.87	0-1	0
		36	18	16.39	16.55	16.79	0-1	0
		36	38	16.46	16.57	16.72	0-1	0
		75	0	16.43	16.57	16.77	0-1	0
	16QAM	1	0	16.55	16.84	16.55	0-1	0
		1	36	16.58	16.54	16.55	0-1	0
		1	74	16.67	16.64	16.61	0-1	0
		36	0	16.43	16.58	16.55	0-2	0
		36	18	16.38	16.54	16.68	0-2	0
		36	38	16.46	16.57	16.72	0-2	0
		75	0	16.45	16.59	16.79	0-2	0
	64QAM	1	0	16.70	16.78	16.95	0-2	0
		1	36	16.53	16.76	16.95	0-2	0
		1	74	16.61	16.89	17.03	0-2	0
		36	0	16.38	16.52	16.85	0-3	0
		36	18	16.34	16.46	16.78	0-3	0
		36	38	16.40	16.49	16.72	0-3	0
		75	0	16.38	16.51	16.79	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				20850	21100	21350	[dB]	[dB]
				2510MHz	2535MHz	2560MHz		
20 MHz	QPSK	1	0	16.65	16.65	16.89	0	0
		1	49	16.38	16.55	16.78	0	0
		1	99	16.61	16.76	16.94	0	0
		50	0	16.42	16.69	16.84	0-1	0
		50	25	16.39	16.55	16.76	0-1	0
		50	49	16.55	16.61	16.63	0-1	0
		100	0	16.49	16.65	16.75	0-1	0
	16QAM	1	0	16.65	16.53	16.61	0-1	0
		1	49	16.57	16.71	16.61	0-1	0
		1	99	16.55	16.60	16.59	0-1	0
		50	0	16.43	16.70	16.85	0-2	0
		50	25	16.41	16.56	16.77	0-2	0
		50	49	16.56	16.61	16.62	0-2	0
		100	0	16.51	16.66	16.77	0-2	0
	64QAM	1	0	16.79	16.78	16.88	0-2	0
		1	49	16.52	16.69	16.82	0-2	0
		1	99	16.69	16.81	16.99	0-2	0
		50	0	16.38	16.68	16.79	0-3	0
		50	25	16.38	16.52	16.70	0-3	0
		50	49	16.51	16.58	16.58	0-3	0
		100	0	16.48	16.61	16.69	0-3	0

- LTE TDD Band 38

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37775	38000	38225	[dB]	[dB]
				2572.5 MHz	2595 MHz	2617.5 MHz		
5 MHz	QPSK	1	0	18.02	18.38	17.62	0	0
		1	12	18.10	18.47	17.60	0	0
		1	24	18.06	18.34	17.42	0	0
		12	0	18.01	18.38	17.54	0-1	0
		12	6	18.06	18.43	17.54	0-1	0
		12	11	18.08	18.42	17.52	0-1	0
		25	0	18.06	18.40	17.54	0-1	0
	16QAM	1	0	17.77	18.13	17.41	0-1	0
		1	12	17.85	18.23	17.34	0-1	0
		1	24	17.80	18.10	17.18	0-1	0
		12	0	18.06	18.43	17.61	0-2	0
		12	6	18.12	18.48	17.60	0-2	0
		12	11	18.13	18.48	17.58	0-2	0
		25	0	18.06	18.42	17.54	0-2	0
	64QAM	1	0	17.64	18.06	17.33	0-2	0
		1	12	17.71	18.14	17.29	0-2	0
		1	24	17.69	18.01	17.11	0-2	0
		12	0	17.99	18.31	17.51	0-3	0
		12	6	18.01	18.34	17.55	0-3	0
		12	11	18.03	18.35	17.44	0-3	0
		25	0	17.97	18.32	17.48	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37800	38000	38200	[dB]	[dB]
				2575 MHz	2595 MHz	2615 MHz		
10 MHz	QPSK	1	0	18.08	18.42	17.97	0	0
		1	24	18.10	18.44	17.69	0	0
		1	49	18.20	18.38	17.55	0	0
		25	0	18.07	18.40	17.78	0-1	0
		25	12	18.09	18.41	17.69	0-1	0
		25	24	18.12	18.41	17.62	0-1	0
		50	0	18.11	18.42	17.70	0-1	0
	16QAM	1	0	17.80	18.14	17.67	0-1	0
		1	24	17.82	18.16	17.42	0-1	0
		1	49	17.93	18.10	17.28	0-1	0
		25	0	18.09	18.13	17.79	0-2	0
		25	12	18.12	18.14	17.70	0-2	0
		25	24	18.14	18.12	17.62	0-2	0
		50	0	18.08	18.19	17.67	0-2	0
	64QAM	1	0	17.61	18.02	17.61	0-2	0
		1	24	17.66	18.07	17.38	0-2	0
		1	49	17.75	18.00	17.22	0-2	0
		25	0	17.94	18.29	17.72	0-3	0
		25	12	18.06	18.29	17.61	0-3	0
		25	24	18.04	18.38	17.58	0-3	0
		50	0	17.99	18.22	17.55	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37825	38000	38175	[dB]	[dB]
				2577.5 MHz	2595 MHz	2612.5 MHz		
15 MHz	QPSK	1	0	18.17	18.44	18.20	0	0
		1	36	18.13	18.44	17.84	0	0
		1	74	18.33	18.33	17.60	0	0
		36	0	18.14	18.43	18.02	0-1	0
		36	18	18.15	18.44	17.86	0-1	0
		36	38	18.22	18.40	17.68	0-1	0
		75	0	18.19	18.42	17.85	0-1	0
	16QAM	1	0	17.92	18.18	17.96	0-1	0
		1	36	17.87	18.18	17.57	0-1	0
		1	74	18.07	18.07	17.64	0-1	0
		36	0	18.12	18.41	17.99	0-2	0
		36	18	18.14	18.40	17.83	0-2	0
		36	38	18.20	18.38	17.68	0-2	0
		75	0	18.17	18.39	17.84	0-2	0
	64QAM	1	0	17.81	18.06	17.81	0-2	0
		1	36	17.74	18.09	17.69	0-2	0
		1	74	17.99	17.95	17.76	0-2	0
		36	0	18.03	18.27	17.81	0-3	0
		36	18	18.05	18.22	17.73	0-3	0
		36	38	18.11	18.24	17.77	0-3	0
		75	0	18.12	18.19	17.71	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				37850	38000	38150	[dB]	[dB]
				2580 MHz	2595 MHz	2610 MHz		
20 MHz	QPSK	1	0	18.25	18.49	18.46	0	0
		1	49	18.16	18.44	17.96	0	0
		1	99	18.51	18.32	17.68	0	0
		50	0	18.21	18.45	18.18	0-1	0
		50	25	18.20	18.45	17.97	0-1	0
		50	49	18.33	18.44	17.85	0-1	0
		100	0	18.26	18.45	18.02	0-1	0
	16QAM	1	0	17.99	18.21	18.19	0-1	0
		1	49	17.89	18.16	17.70	0-1	0
		1	99	18.25	18.05	17.41	0-1	0
		50	0	18.18	18.45	18.14	0-2	0
		50	25	18.18	18.42	17.95	0-2	0
		50	49	18.30	18.41	17.82	0-2	0
		100	0	18.26	18.45	18.02	0-2	0
	64QAM	1	0	17.82	18.06	18.02	0-2	0
		1	49	17.75	18.04	17.54	0-2	0
		1	99	18.13	17.99	17.35	0-2	0
		50	0	18.02	18.37	18.06	0-3	0
		50	25	18.04	18.36	17.79	0-3	0
		50	49	18.14	18.29	17.74	0-3	0
		100	0	18.11	18.37	17.92	0-3	0

- LTE TDD Band 41

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40265	40740	41215	[dB]	[dB]
				2557.5 MHz	2605 MHz	2652.5 MHz		
5 MHz	QPSK	1	0	18.40	18.43	18.36	0	0
		1	12	18.46	18.43	18.47	0	0
		1	24	18.38	18.29	18.47	0	0
		12	0	18.38	18.37	18.37	0-1	0
		12	6	18.41	18.40	18.43	0-1	0
		12	11	18.41	18.38	18.45	0-1	0
		25	0	18.39	18.38	18.42	0-1	0
	16QAM	1	0	18.16	18.19	18.11	0-1	0
		1	12	18.20	18.18	18.22	0-1	0
		1	24	18.13	18.04	18.21	0-1	0
		12	0	18.44	18.44	18.42	0-2	0
		12	6	18.48	18.45	18.48	0-2	0
		12	11	18.48	18.43	18.51	0-2	0
		25	0	18.43	18.40	18.43	0-2	0
	64QAM	1	0	18.06	18.07	18.05	0-2	0
		1	12	18.12	18.01	18.12	0-2	0
		1	24	18.02	17.92	18.14	0-2	0
		12	0	18.36	18.29	18.32	0-3	0
		12	6	18.37	18.35	18.44	0-3	0
		12	11	18.36	18.32	18.40	0-3	0
		25	0	18.32	18.24	18.31	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40290	40740	41190	[dB]	[dB]
				2560 MHz	2605 MHz	2650 MHz		
10 MHz	QPSK	1	0	18.48	18.59	18.35	0	0
		1	24	18.42	18.42	18.39	0	0
		1	49	18.45	18.31	18.57	0	0
		25	0	18.41	18.45	18.35	0-1	0
		25	12	18.41	18.40	18.37	0-1	0
		25	24	18.41	18.36	18.44	0-1	0
		50	0	18.41	18.42	18.39	0-1	0
	16QAM	1	0	18.21	18.31	18.08	0-1	0
		1	24	18.15	18.15	18.12	0-1	0
		1	49	18.17	18.04	18.28	0-1	0
		25	0	18.46	18.50	18.39	0-2	0
		25	12	18.45	18.43	18.42	0-2	0
		25	24	18.42	18.39	18.45	0-2	0
		50	0	18.40	18.41	18.37	0-2	0
	64QAM	1	0	18.09	18.26	18.03	0-2	0
		1	24	18.07	18.09	18.02	0-2	0
		1	49	18.09	18.00	18.19	0-2	0
		25	0	18.31	18.37	18.34	0-3	0
		25	12	18.32	18.33	18.32	0-3	0
		25	24	18.29	18.32	18.42	0-3	0
		50	0	18.31	18.35	18.28	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40315	40740	41165	[dB]	[dB]
				2562.5 MHz	2605 MHz	2647.5 MHz		
15 MHz	QPSK	1	0	18.54	18.65	18.27	0	0
		1	36	18.41	18.40	18.35	0	0
		1	74	18.46	18.24	18.59	0	0
		36	0	18.47	18.54	18.29	0-1	0
		36	18	18.42	18.44	18.34	0-1	0
		36	39	18.42	18.37	18.43	0-1	0
		75	0	18.46	18.46	18.38	0-1	0
	16QAM	1	0	18.29	18.43	18.06	0-1	0
		1	36	18.15	18.16	18.10	0-1	0
		1	74	18.19	17.97	18.32	0-1	0
		36	0	18.45	18.51	18.27	0-2	0
		36	18	18.40	18.40	18.33	0-2	0
		36	39	18.39	18.34	18.40	0-2	0
		75	0	18.43	18.42	18.36	0-2	0
	64QAM	1	0	18.22	18.29	17.92	0-2	0
		1	36	18.09	18.07	17.99	0-2	0
		1	74	18.08	17.91	18.19	0-2	0
		36	0	18.27	18.38	18.17	0-3	0
		36	18	18.35	18.22	18.24	0-3	0
		36	39	18.29	18.18	18.30	0-3	0
		75	0	18.37	18.24	18.22	0-3	0

Bandwidth	Modulation	RB Size	RB Offset	Back off Average Power (dBm)			MPR Allowed Per 3GPP	MPR
				40340	40740	41140	[dB]	[dB]
				2565 MHz	2605 MHz	2645 MHz		
20 MHz	QPSK	1	0	18.63	18.66	18.25	0	0
		1	49	18.40	18.40	18.26	0	0
		1	99	18.58	18.21	18.64	0	0
		50	0	18.51	18.57	18.26	0-1	0
		50	25	18.43	18.44	18.29	0-1	0
		50	49	18.47	18.40	18.39	0-1	0
		100	0	18.51	18.49	18.35	0-1	0
	16QAM	1	0	18.37	18.52	18.01	0-1	0
		1	49	18.13	18.14	17.99	0-1	0
		1	99	18.32	17.94	18.41	0-1	0
		50	0	18.50	18.57	18.22	0-2	0
		50	25	18.42	18.41	18.27	0-2	0
		50	49	18.46	18.37	18.37	0-2	0
		100	0	18.51	18.49	18.33	0-2	0
	64QAM	1	0	18.27	18.39	17.94	0-2	0
		1	49	18.07	18.01	17.92	0-2	0
		1	99	18.24	17.86	18.32	0-2	0
		50	0	18.39	18.41	18.16	0-3	0
		50	25	18.35	18.26	18.19	0-3	0
		50	49	18.37	18.16	18.27	0-3	0
		100	0	18.41	18.34	18.19	0-3	0

Note;

The EUT enables maximum power reduction in accordance with 3GPP 36.101. The MPR settings are configured during the manufacture process and are not configurable by the network, carrier, or end user.

LTE Carrier Aggregation

This device only supports Downlink intra-band continuous LTE Carrier Aggregation (CA). All uplink communications are identical to Release 8 specifications. Per FCC KDB Publication 941225 D05A v01r02, SAR for LTE CA operations was not needed since the maximum average output power in LTE CA mode was not >0.25 dB higher than the maximum output power when downlink carrier aggregation was inactive.

Downlink Carrier Aggregation

LTE Carrier Aggregation (CA) measurement are made in accordance to 3GPP TS 36.521-1 V10.4.0(2012-12). The RRC connection is only handled by one cell, the Primary component carrier(PCC) for downlink and uplink communications. After making a data connection to the PCC, the UE device adds the Secondary component carrier (SCC) on the downlink only. All uplink communications and acknowledgements remain identical to release 8 specifications on the PCC. Additional output powers are measured using two carriers in the downlink for the release 8 configurations with the highest SAR among all channels, RB configurations and bandwidths for each uplink band. Per FCC KDB Publication 941225 D05A v01r02, no SAR measurements are required when the average output power with downlink carrier aggregation active is not more than 0.25 dB higher than the average output power with downlink carrier aggregation inactive.

LTE Carrier Aggregation Conducted Power -Maximum Power

Intra-band Downlik CA : Main Ant 1

PCC									SCC				Tx Power	
Band	BW	PCC(UL) channel	PCC(UL) Frequency	Modulation	RB	offset	PCC(DL) channel	PCC(DL) Frequency	Band	BW	SCC(DL) channel	SCC(DL) Frequency	Rel 8	Rel 10
41	20	40740	2605	QPSK	1	0	40740	2605	41	20	40938	2624.8	21.62	21.61


Intra-band Downlik CA : Main Ant 3

PCC									SCC				Tx Power	
Band	BW	PCC(UL) channel	PCC(UL) Frequency	Modulation	RB	offset	PCC(DL) channel	PCC(DL) Frequency	Band	BW	SCC(DL) channel	SCC(DL) Frequency	Rel 8	Rel 10
41	20	40740	2605	QPSK	1	0	40740	2605	41	20	40938	2624.8	22.48	22.42

LTE Carrier Aggregation Conducted Power -Reduced Power

Intra-band Downlik CA : Main Ant 3 (Held to Ear)

PCC									SCC				Tx Power	
Band	BW	PCC(UL) channel	PCC(UL) Frequency	Modulation	RB	offset	PCC(DL) channel	PCC(DL) Frequency	Band	BW	SCC(DL) channel	SCC(DL) Frequency	Rel 8	Rel 10
41	20	40740	2605	QPSK	1	0	40740	2605	41	20	40938	2624.8	18.66	18.65



Notes:

This device only supports downlink Carrier Aggregation. Uplink Carrier Aggregation is not supported. For every supported combination of downlink carrier aggregation, power measurements were performed with the downlink carrier aggregation active for the configuration with highest measured maximum conducted power with downlink carrier aggregation inactive measured among the channel bandwidth, modulation and RB combinations in each frequency band.

9.4 WiFi

9.4.1 Maximum conducted Power

IEEE 802.11 Average RF Power (Maximum Conducted Power)

Mode	Freq.	Channel	IEEE 802.11 (2.4 GHz) Conducted Power
	[MHz]		[dBm]
802.11b	2412	1	16.76
	2437	6	16.70
	2462	11	16.58
802.11g	2412	1	13.64
	2437	6	13.72
	2462	11	13.50
802.11n (HT20)	2412	1	11.69
	2437	6	11.62
	2462	11	11.64

9.4.2 Reduced conducted Power (Held to ear VoIP)


IEEE 802.11 Reduced Average RF Conducted Power

Mode	Freq.	Channel	IEEE 802.11 (2.4 GHz) Conducted Power
	[MHz]		[dBm]
802.11b	2412	1	14.55
	2437	6	14.60
	2462	11	14.67

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission mode with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.

Test Configuration



9.5 BT


The Burst averaged-conducted Power

Mode	Channel	BT Power
		[dBm]
DH5	0	9.72
	39	10.41
	78	8.52
2-DH5	0	7.25
	39	7.80
	78	5.91
3-DH5	0	7.26
	39	7.80
	78	5.92

Per October 2016 TCB Workshop Notes:

When call box and Bluetooth protocol are used for BT SAR measurement, time-domain plot is required to identify duty factor for supporting the test setup and result.

Bluetooth duty cycle was measured using Bluetooth tester equipment (CBT / R&S) with Bluetooth protocol. DH5 mode is the highest duty cycle and conducted power. SAR test were performed at DH5 mode.



Duty Cycle

$$= (\text{BT-On time} / \text{BT-Full time}) = (2.874 / 3.750) * 100 = 76.6 \% (\text{DH5})$$

Duty factor= 1/Duty cycle : 1.31

10. SYSTEM VERIFICATION

10.1 Tissue Verification

The Head /body simulating material is calibrated by HCT using the DAKS 3.5 to determine the conductivity and permittivity.

– Main Ant.1and Main Ant. 2

Table for Head Tissue Verification									
Date of Tests	Tissue Temp	Tissue Type	Freq. (MHz)	Measured Conductivity σ (S/m)	Measured Dielectric Constant, ϵ	Target Conductivity σ (S/m)	Target Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/23/2017	21.1	835H	820	0.883	43.023	0.899	41.578	-1.78%	3.48%
			835	0.898	42.802	0.900	41.500	-0.22%	3.14%
			850	0.915	42.554	0.916	41.500	-0.11%	2.54%
06/30/2017	19.1	1900H	1 850	1.340	40.845	1.400	40.000	-4.29%	2.11%
			1 900	1.379	40.532	1.400	40.000	-1.50%	1.33%
			1 910	1.381	40.530	1.400	40.000	-1.36%	1.33%
07/03/2017	20.0	2450H	2 400	1.790	38.624	1.756	39.290	1.94%	-1.70%
			2 450	1.847	38.427	1.800	39.200	2.61%	-1.97%
			2 500	1.905	38.283	1.855	39.140	2.70%	-2.19%
07/05/2017	19.6	2600H	2 500	1.912	39.345	1.855	39.140	3.07%	0.52%
			2 600	2.029	39.017	1.964	39.010	3.31%	0.02%
			2 700	2.150	38.700	2.073	38.880	3.71%	-0.46%
07/07/2017	20.7	2600H	2 500	1.915	38.298	1.855	39.140	3.23%	-2.15%
			2 600	2.030	37.956	1.964	39.010	3.36%	-2.70%
			2 700	2.140	37.600	2.073	38.880	3.23%	-3.29%

– Main ANT 3

Table for Head Tissue Verification									
Date of Tests	Tissue Temp	Tissue Type	Freq. (MHz)	Measured Conductivity σ (S/m)	Measured Dielectric Constant, ϵ	Target Conductivity σ (S/m)	Target Dielectric Constant, ϵ	% dev σ	% dev ϵ
07/22/2017	21.2	835H	820	0.893	41.606	0.899	41.578	-0.67%	0.07%
			835	0.908	41.342	0.900	41.500	0.89%	-0.38%
			850	0.921	41.129	0.916	41.500	0.55%	-0.89%
07/25/2017	20.9	1900H	1 850	1.377	39.547	1.400	40.000	-1.64%	-1.13%
			1 900	1.428	39.438	1.400	40.000	2.00%	-1.40%
			1 910	1.430	39.400	1.400	40.000	2.14%	-1.50%
07/24/2017	19.7	2600H	2 500	1.912	39.355	1.855	39.140	3.07%	0.55%
			2 600	2.028	39.013	1.964	39.010	3.26%	0.01%
			2 700	2.147	38.696	2.073	38.880	3.57%	-0.47%

– Main Ant.1 and Main Ant. 2

Table for Body Tissue Verification									
Date of Tests	Tissue Temp	Tissue Type	Freq. (MHz)	Measured Conductivity σ (S/m)	Measured Dielectric Constant, ϵ	Target Conductivity σ (S/m)	Target Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/26/2017	20.5	835B	820	0.933	56.944	0.969	55.258	-3.72%	3.05%
			835	0.948	56.770	0.970	55.200	-2.27%	2.84%
			850	0.966	56.591	0.988	55.154	-2.23%	2.61%
06/28/2017	22.2	835B	820	0.962	55.702	0.969	55.258	-0.72%	0.80%
			835	0.977	55.564	0.970	55.200	0.72%	0.66%
			850	0.991	55.360	0.988	55.154	0.30%	0.37%
06/28/2017	22.2	1900B	1 850	1.495	53.663	1.520	53.300	-1.64%	0.68%
			1 900	1.554	53.511	1.520	53.300	2.24%	0.40%
			1 910	1.567	53.530	1.520	53.300	3.09%	0.43%
07/04/2017	19.6	2450B	2 400	1.901	52.458	1.902	52.770	-0.05%	-0.59%
			2 450	1.987	52.419	1.950	52.700	1.90%	-0.53%
			2 500	2.050	52.363	2.021	52.640	1.43%	-0.53%
07/06/2017	20.2	2600B	2 500	2.049	51.225	2.021	52.640	1.39%	-2.69%
			2 600	2.166	50.910	2.163	52.510	0.14%	-3.05%
			2 700	2.298	50.580	2.305	52.380	-0.30%	-3.44%
07/10/2017	20.1	2600B	2 500	2.070	54.617	2.021	52.640	2.42%	3.76%
			2 600	2.199	54.346	2.163	52.510	1.66%	3.50%
			2 700	2.330	54.100	2.305	52.380	1.08%	3.28%

– Main ANT 3

Table for Body Tissue Verification									
Date of Tests	Tissue Temp	Tissue Type	Freq. (MHz)	Measured Conductivity σ (S/m)	Measured Dielectric Constant, ϵ	Target Conductivity σ (S/m)	Target Dielectric Constant, ϵ	% dev σ	% dev ϵ
07/27/2017	20.3	835B	820	0.943	56.624	0.969	55.258	-2.68%	2.47%
			835	0.953	56.450	0.970	55.200	-1.75%	2.26%
			850	0.973	56.312	0.988	55.154	-1.52%	2.10%
07/27/2017	19.2	1900B	1 850	1.476	55.506	1.520	53.300	-2.89%	4.14%
			1 900	1.534	55.353	1.520	53.300	0.92%	3.85%
			1 910	1.544	55.353	1.520	53.300	1.58%	3.85%
07/27/2017	22.0	2600B	2 500	1.996	52.501	2.021	52.640	-1.24%	-0.26%
			2 600	2.110	52.200	2.163	52.510	-2.45%	-0.59%
			2 700	2.230	51.900	2.305	52.380	-3.25%	-0.92%

10.2 System Verification

Prior to assessment, the system is verified to the $\pm 10\%$ of the specifications at 835 MHz / 1 900 MHz / 2 450 MHz / 2 600 MHz by using the system Verification kit. (Graphic Plots Attached)

System Verification Results

– Main Ant.1 and Main Ant. 2

SAR System No	Freq. [MHz]	Date	Probe (S/N)	Dipole (S/N)	Liquid	Amb. Temp. [°C]	Liquid Temp. [°C]	1 W Target SAR _{1g} (SPEAG) [W/kg]	Measured SAR _{1g} [W/kg]	1 W Normalized SAR _{1g} [W/kg]	Deviation [%]	Limit [%]	Plot No
7	835	06/23/2017	1630	441	Head	21.4	21.1	9.38	0.972	9.72	+ 3.62	± 10	V1
7	835	06/26/2017	1630		Body	20.8	20.5	9.62	0.968	9.68	+ 0.62	± 10	V2
1	835	06/28/2017	3863		Body	22.5	22.2	9.62	0.977	9.77	+ 1.56	± 10	V3
5	1 900	06/30/2017	3903	5d032	Head	19.5	19.1	40.0	3.9	39.0	- 2.50	± 10	V4
7	1 900	06/28/2017	1630		Body	22.5	22.2	40.5	4.2	42.0	+ 3.70	± 10	V5
12	2 450	07/03/2017	7370	743	Head	20.2	20.0	53.0	5.02	50.2	- 5.28	± 10	V6
12	2 450	07/04/2017	7370		Body	19.8	19.6	50.6	4.68	46.8	- 7.51	± 10	V7
12	2 600	07/05/2017	7370	1015	Head	19.8	19.6	57.5	6.01	60.1	+ 4.52	± 10	V8
12	2 600	07/07/2017	7370		Head	20.9	20.7	57.5	5.62	56.2	- 2.26	± 10	V9
12	2 600	07/06/2017	7370		Body	20.5	20.2	55.1	5.5	55.0	- 0.18	± 10	V10
12	2 600	07/10/2017	7370		Body	20.4	20.1	55.1	5.3	53.0	- 3.81	± 10	V11

– Main ANT 3

SAR System No	Freq. [MHz]	Date	Probe (S/N)	Dipole (S/N)	Liquid	Amb. Temp. [°C]	Liquid Temp. [°C]	1 W Target SAR _{1g} (SPEAG) [W/kg]	Measured SAR _{1g} [W/kg]	1 W Normalized SAR _{1g} [W/kg]	Deviation [%]	Limit [%]	Plot No
3	835	07/22/2017	3797	441	Head	21.4	21.2	9.38	0.899	8.99	- 4.16	± 10	V12
3	835	07/27/2017	3797		Body	20.5	20.3	9.62	0.958	9.58	- 0.42	± 10	V13
8	1 900	07/25/2017	3967	5d032	Head	21.1	20.9	40.0	3.92	39.2	- 2.00	± 10	V14
4	1 900	07/27/2017	1605		Body	19.4	19.2	40.5	4.08	40.8	+ 0.74	± 10	V15
8	2 600	07/24/2017	3967	1015	Head	19.9	19.7	57.5	5.78	57.8	+ 0.52	± 10	V16
8	2 600	07/27/2017	3967		Body	22.3	22.0	55.1	5.76	57.6	+ 4.54	± 10	V17

10.3 System Verification Procedure

SAR measurement was prior to assessment, the system is verified to the $\pm 10\%$ of the specifications at each frequency band by using the system Verification kit. (Graphic Plots Attached)

- Cabling the system, using the Verification kit equipments.
- Generate about 100 mW Input Level from the Signal generator to the Dipole Antenna.
- Dipole Antenna was placed below the Flat phantom.
- The measured one-gram SAR at the surface of the phantom above the dipole feed-point should be within 10 % of the target reference value.
- The results are normalized to 1 W input power.

NOTE;

SAR Verification was performed according to the FCC KDB 865664 D01v01r04.

11. SAR TEST DATA SUMMARY

11.1 HEAD SAR Measurement Results

GSM 850 Head SAR												
Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(W/kg)		(W/kg)	
836.6	190	Voice	32.5	31.94	-0.10	Left Cheek	Ant. 1	1:8.3	0.310	1.138	0.353	-
836.6	190	Voice	32.5	31.94	0.03	Left Tilt	Ant. 1	1:8.3	0.142	1.138	0.162	-
836.6	190	Voice	32.5	31.94	-0.19	Right Cheek	Ant. 1	1:8.3	0.211	1.138	0.240	-
836.6	190	Voice	32.5	31.94	-0.02	Right Tilt	Ant. 1	1:8.3	0.129	1.138	0.147	-
824.2	128	Voice	30.2	30.10	-0.01	Left Cheek	Ant. 3	1:8.3	0.911	1.023	0.932	1
836.6	190	Voice	30.2	29.81	0.16	Left Cheek	Ant. 3	1:8.3	0.891	1.094	0.975	2
848.8	251	Voice	30.2	29.96	0.02	Left Cheek	Ant. 3	1:8.3	0.882	1.057	0.932	-
836.6	190	Voice	30.2	29.81	-0.03	Left Tilt	Ant. 3	1:8.3	0.583	1.094	0.638	-
836.6	190	Voice	30.2	29.81	0.01	Right Cheek	Ant. 3	1:8.3	0.425	1.094	0.465	-
836.6	190	Voice	30.2	29.81	0.10	Right Tilt	Ant. 3	1:8.3	0.368	1.094	0.403	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population						Head 1.6 W/kg (mW/g) Averaged over 1 gram						

GSM 1900 Head SAR												
Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(W/kg)		(W/kg)	
1 880.0	661	Voice	30.5	30.21	-0.02	Left Cheek	Ant. 2	1:8.3	0.112	1.069	0.120	-
1 880.0	661	Voice	30.5	30.21	0.16	Left Tilt	Ant. 2	1:8.3	0.049	1.069	0.052	-
1 880.0	661	Voice	30.5	30.21	0.09	Right Cheek	Ant. 2	1:8.3	0.178	1.069	0.190	-
1 880.0	661	Voice	30.5	30.21	0.16	Right Tilt	Ant. 2	1:8.3	0.054	1.069	0.058	-
1 850.2	512	Voice	28.5	28.28	-0.01	Left Cheek	Ant. 3	1:8.3	0.769	1.052	0.809	-
1 880.0	661	Voice	28.5	28.16	-0.03	Left Cheek	Ant. 3	1:8.3	0.795	1.081	0.859	-
1 909.8	810	Voice	28.5	27.57	-0.01	Left Cheek	Ant. 3	1:8.3	0.840	1.239	1.041	3
1 850.2	512	Voice	28.5	28.28	-0.08	Left Tilt	Ant. 3	1:8.3	0.495	1.052	0.521	-
1 850.2	512	Voice	28.5	28.28	-0.12	Right Cheek	Ant. 3	1:8.3	0.416	1.052	0.438	-
1 850.2	512	Voice	28.5	28.28	-0.09	Right Tilt	Ant. 3	1:8.3	0.317	1.052	0.333	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population						Head 1.6 W/kg (mW/g) Averaged over 1 gram						

UMTS 850 Head SAR

Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(W/kg)		(W/kg)	
836.6	4183	RMC	23.0	22.41	-0.15	Left Cheek	Ant. 1	1:1	0.341	1.146	0.391	-
836.6	4183	RMC	23.0	22.41	0.07	Left Tilt	Ant. 1	1:1	0.139	1.146	0.159	-
836.6	4183	RMC	23.0	22.41	-0.01	Right Cheek	Ant. 1	1:1	0.197	1.146	0.226	-
836.6	4183	RMC	23.0	22.41	0.12	Right Tilt	Ant. 1	1:1	0.149	1.146	0.171	-
826.4	4132	RMC	20.7	20.21	0.03	Left Cheek	Ant. 3	1:1	0.854	1.119	0.956	4
836.6	4183	RMC	20.7	20.18	0.05	Left Cheek	Ant. 3	1:1	0.827	1.127	0.932	-
846.6	4233	RMC	20.7	20.40	0.01	Left Cheek	Ant. 3	1:1	0.815	1.072	0.874	-
836.6	4183	RMC	20.7	20.18	-0.01	Left Tilt	Ant. 3	1:1	0.556	1.127	0.627	-
836.6	4183	RMC	20.7	20.18	-0.07	Right Cheek	Ant. 3	1:1	0.456	1.127	0.514	-
836.6	4183	RMC	20.7	20.18	0.02	Right Tilt	Ant. 3	1:1	0.330	1.127	0.372	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population						Head 1.6 W/kg (mW/g) Averaged over 1 gram						

UMTS 1900 Head SAR

Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(W/kg)		(W/kg)	
1 880.0	9400	RMC	21.0	20.23	0.14	Left Cheek	Ant. 2	1:1	0.120	1.194	0.143	-
1 880.0	9400	RMC	21.0	20.23	0.10	Left Tilt	Ant. 2	1:1	0.054	1.194	0.064	-
1 880.0	9400	RMC	21.0	20.23	-0.01	Right Cheek	Ant. 2	1:1	0.185	1.194	0.221	-
1 880.0	9400	RMC	21.0	20.23	0.11	Right Tilt	Ant. 2	1:1	0.057	1.194	0.068	-
1 852.4	9262	RMC	18.7	18.49	-0.06	Left Cheek	Ant. 3	1:1	0.802	1.050	0.842	5
1 880.0	9400	RMC	18.7	18.36	-0.03	Left Cheek	Ant. 3	1:1	0.793	1.081	0.857	-
1 907.6	9538	RMC	18.7	18.11	-0.02	Left Cheek	Ant. 3	1:1	0.750	1.146	0.860	6
1 880.0	9400	RMC	18.7	18.36	0.02	Left Tilt	Ant. 3	1:1	0.482	1.081	0.521	-
1 880.0	9400	RMC	18.7	18.36	-0.05	Right Cheek	Ant. 3	1:1	0.386	1.081	0.417	-
1 880.0	9400	RMC	18.7	18.36	-0.01	Right Tilt	Ant. 3	1:1	0.247	1.081	0.267	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population						Head 1.6 W/kg (mW/g) Averaged over 1 gram						

LTE Band 5 (Cell) Head SAR

Frequency		Mode	Band width	Tune- Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	MPR	RB Size	RB offset	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(dBm)	(dBm)	(dB)			(dB)				(W/kg)		(W/kg)	
836.5	20525	QPSK	10	22.5	22.23	0.01	Left Cheek	Ant. 1	0	1	0	1:1	0.300	1.064	0.319	-
836.5	20525	QPSK	10	21.5	21.27	-0.07	Left Cheek	Ant. 1	1	25	0	1:1	0.246	1.054	0.259	-
836.5	20525	QPSK	10	22.5	22.23	-0.04	Left Tilt	Ant. 1	0	1	0	1:1	0.158	1.064	0.168	-
836.5	20525	QPSK	10	21.5	21.27	0.15	Left Tilt	Ant. 1	1	25	0	1:1	0.102	1.054	0.108	-
836.5	20525	QPSK	10	22.5	22.23	-0.11	Right Cheek	Ant. 1	0	1	0	1:1	0.144	1.064	0.153	-
836.5	20525	QPSK	10	21.5	21.27	-0.11	Right Cheek	Ant. 1	1	25	0	1:1	0.116	1.054	0.122	-
836.5	20525	QPSK	10	22.5	22.23	-0.01	Right Tilt	Ant. 1	0	1	0	1:1	0.116	1.064	0.123	-
836.5	20525	QPSK	10	21.5	21.27	-0.04	Right Tilt	Ant. 1	1	25	0	1:1	0.090	1.054	0.095	-
836.5	20525	QPSK	10	20.5	19.85	-0.01	Left Cheek	Ant. 3	0	1	0	1:1	0.804	1.161	0.933	7
836.5	20525	QPSK	10	20.5	19.94	0.01	Left Cheek	Ant. 3	0	25	0	1:1	0.758	1.138	0.863	-
836.5	20525	QPSK	10	20.5	19.88	-0.02	Left Cheek	Ant. 3	0	50	0	1:1	0.741	1.153	0.854	-
836.5	20525	QPSK	10	20.5	19.85	0.04	Left Tilt	Ant. 3	0	1	0	1:1	0.593	1.161	0.688	-
836.5	20525	QPSK	10	20.5	19.94	-0.01	Left Tilt	Ant. 3	0	25	0	1:1	0.564	1.138	0.642	-
836.5	20525	QPSK	10	20.5	19.85	-0.07	Right Cheek	Ant. 3	0	1	0	1:1	0.482	1.161	0.560	-
836.5	20525	QPSK	10	20.5	19.94	0.02	Right Cheek	Ant. 3	0	25	0	1:1	0.451	1.138	0.513	-
836.5	20525	QPSK	10	20.5	19.85	-0.01	Right Tilt	Ant. 3	0	1	0	1:1	0.347	1.161	0.403	-
836.5	20525	QPSK	10	20.5	19.94	-0.05	Right Tilt	Ant. 3	0	25	0	1:1	0.324	1.138	0.369	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Head 1.6 W/kg (mW/g) Averaged over 1 gram									

LTE Band 7 Head SAR

Frequency		Mode	Band width	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	MPR	RB Size	RB offset	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(dBm)	(dBm)	(dB)			(dB)				(W/kg)		(W/kg)	
2 510	20850	QPSK	20	22.5	21.44	-0.16	Left Cheek	Ant. 1	0	1	0	1:1	0.237	1.276	0.302	-
2 535	21100	QPSK	20	21.5	20.56	0.11	Left Cheek	Ant. 1	1	50	0	1:1	0.202	1.242	0.251	-
2 510	20850	QPSK	20	22.5	21.44	0.10	Left Tilt	Ant. 1	0	1	0	1:1	0.056	1.276	0.071	-
2 535	21100	QPSK	20	21.5	20.56	0.17	Left Tilt	Ant. 1	1	50	0	1:1	0.040	1.242	0.050	-
2 510	20850	QPSK	20	22.5	21.44	-0.04	Right Cheek	Ant. 1	0	1	0	1:1	0.100	1.276	0.128	-
2 535	21100	QPSK	20	21.5	20.56	0.18	Right Cheek	Ant. 1	1	50	0	1:1	0.103	1.242	0.128	-
2 510	20850	QPSK	20	22.5	21.44	0.14	Right Tilt	Ant. 1	0	1	0	1:1	0.110	1.276	0.140	-
2 535	21100	QPSK	20	21.5	20.56	0.17	Right Tilt	Ant. 1	1	50	0	1:1	0.076	1.242	0.094	-
2 510	20850	QPSK	20	17.5	16.65	-0.02	Left Cheek	Ant. 3	0	1	0	1:1	0.823	1.216	1.001	8
2 535	21100	QPSK	20	17.5	16.76	0.04	Left Cheek	Ant. 3	0	1	99	1:1	0.818	1.186	0.970	-
2 560	21350	QPSK	20	17.5	16.94	0.06	Left Cheek	Ant. 3	0	1	99	1:1	0.797	1.138	0.907	-
2 510	20850	QPSK	20	17.5	16.55	-0.03	Left Cheek	Ant. 3	0	50	49	1:1	0.747	1.245	0.930	-
2 535	21100	QPSK	20	17.5	16.69	0.01	Left Cheek	Ant. 3	0	50	0	1:1	0.733	1.205	0.883	-
2 560	21350	QPSK	20	17.5	16.84	-0.01	Left Cheek	Ant. 3	0	50	0	1:1	0.779	1.164	0.907	-
2 560	21350	QPSK	20	17.5	16.75	0.03	Left Cheek	Ant. 3	0	100	0	1:1	0.714	1.189	0.849	-
2 560	21350	QPSK	20	17.5	16.94	0.03	Left Tilt	Ant. 3	0	1	99	1:1	0.545	1.138	0.620	-
2 560	21350	QPSK	20	17.5	16.84	0.04	Left Tilt	Ant. 3	0	50	0	1:1	0.537	1.164	0.625	-
2 560	21350	QPSK	20	17.5	16.94	0.07	Right Cheek	Ant. 3	0	1	99	1:1	0.204	1.138	0.232	-
2 560	21350	QPSK	20	17.5	16.84	-0.08	Right Cheek	Ant. 3	0	50	0	1:1	0.190	1.164	0.221	-
2 560	21350	QPSK	20	17.5	16.94	0.06	Right Tilt	Ant. 3	0	1	99	1:1	0.180	1.138	0.205	-
2 560	21350	QPSK	20	17.5	16.84	0.12	Right Tilt	Ant. 3	0	50	0	1:1	0.176	1.164	0.205	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Head 1.6 W/kg Averaged over 1 gram									

LTE TDD Band 41 Head SAR																
Frequency		Mode	Band width	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	MPR	RB	RB	Duty Cycle	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(dBm)	(dBm)	(dB)			(dB)	Size	offset		(W/kg)		(W/kg)	
2 605	40740	QPSK	20	22.5	21.62	0.09	Left Cheek	Ant. 1	0	1	0	1:1.58	0.176	1.225	0.216	-
2 605	40740	QPSK	20	21.5	20.46	0.11	Left Cheek	Ant. 1	1	50	0	1:1.58	0.118	1.271	0.150	-
2 605	40740	QPSK	20	22.5	21.62	0.11	Left Tilt	Ant. 1	0	1	0	1:1.58	0.036	1.225	0.044	-
2 605	40740	QPSK	20	21.5	20.46	0.17	Left Tilt	Ant. 1	1	50	0	1:1.58	0.023	1.271	0.029	-
2 605	40740	QPSK	20	22.5	21.62	0.19	Right Cheek	Ant. 1	0	1	0	1:1.58	0.066	1.225	0.081	-
2 605	40740	QPSK	20	21.5	20.46	0.18	Right Cheek	Ant. 1	1	50	0	1:1.58	0.048	1.271	0.061	-
2 605	40740	QPSK	20	22.5	21.62	-0.05	Right Tilt	Ant. 1	0	1	0	1:1.58	0.050	1.225	0.061	-
2 605	40740	QPSK	20	21.5	20.46	0.18	Right Tilt	Ant. 1	1	50	0	1:1.58	0.048	1.271	0.061	-
2 605	40740	QPSK	20	18.7	18.66	-0.04	Left Cheek	Ant. 3	0	1	0	1:1.58	0.688	1.009	0.694	9
2 605	40740	QPSK	20	18.7	18.57	0.04	Left Cheek	Ant. 3	0	50	0	1:1.58	0.652	1.030	0.672	-
2 605	40740	QPSK	20	18.7	18.66	-0.02	Left Tilt	Ant. 3	0	1	0	1:1.58	0.576	1.009	0.581	-
2 605	40740	QPSK	20	18.7	18.57	0.03	Left Tilt	Ant. 3	0	50	0	1:1.58	0.549	1.030	0.565	-
2 605	40740	QPSK	20	18.7	18.66	0.10	Right Cheek	Ant. 3	0	1	0	1:1.58	0.185	1.009	0.187	-
2 605	40740	QPSK	20	18.7	18.57	0.03	Right Cheek	Ant. 3	0	50	0	1:1.58	0.176	1.030	0.181	-
2 605	40740	QPSK	20	18.7	18.66	0.10	Right Tilt	Ant. 3	0	1	0	1:1.58	0.181	1.009	0.183	-
2 605	40740	QPSK	20	18.7	18.57	-0.03	Right Tilt	Ant. 3	0	50	0	1:1.58	0.170	1.030	0.175	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Head 1.6 W/kg (mW/g) Averaged over 1 gram									

DTS Head SAR

Frequency		Mode	Band width	Data Rate	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Duty Cycle	Area Scan Peak SAR	Meas. SAR	Scaling Factor	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(Mbps)	(dBm)	(dBm)	(dB)			(W/kg)	(W/kg)		(Duty)	(W/kg)	
2 462	11	802.11b	22	1	15.5	14.67	0.13	Left Cheek	98.82	0.158	0.114	1.211	1.011	0.140	-
2 462	11	802.11b	22	1	15.5	14.67	-0.14	Left Tilt	98.82	0.147	0.101	1.211	1.011	0.124	-
2 462	11	802.11b	22	1	15.5	14.67	-0.10	Right Cheek	98.82	0.750	0.433	1.211	1.011	0.530	10
2 462	11	802.11b	22	1	15.5	14.67	-0.19	Right Tilt	98.82	0.566	0.359	1.211	1.011	0.440	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population								Head 1.6 W/kg (mW/g) Averaged over 1 gram							

DSS Head SAR

Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Duty Cycle	Meas. SAR	Scaling Factor	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dBm)	(dBm)	(dB)			(W/kg)		(Duty)	(W/kg)	
2 441	39	Bluetooth DH5	10.5	10.41	0.18	Left Cheek	76.6	0.037	1.021	1.31	0.049	-
2 441	39	Bluetooth DH5	10.5	10.41	-0.08	Left Tilt	76.6	0.037	1.021	1.31	0.049	-
2 441	39	Bluetooth DH5	10.5	10.41	-0.02	Right Cheek	76.6	0.145	1.021	1.31	0.194	11
2 441	39	Bluetooth DH5	10.5	10.41	0.11	Right Tilt	76.6	0.100	1.021	1.31	0.134	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Head1.310 1.6 W/kg (mW/g) Averaged over 1 gram					

11.2 Body-worn SAR Measurement Results

GSM/UMTS Body-Worn SAR													
Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(mm)	(W/kg)		(W/kg)	
836.6	190	GSM Voice	32.5	31.94	0.02	Rear	Ant. 1	1:8.3	15	0.445	1.138	0.506	12
836.6	190	GSM Voice	32.5	31.62	-0.08	Rear	Ant. 3	1:8.3	15	0.164	1.225	0.201	13
1 880	661	GSM Voice	30.5	30.21	-0.11	Rear	Ant. 2	1:8.3	15	0.146	1.069	0.156	14
1 880	661	GSM Voice	30.5	30.22	-0.09	Rear	Ant. 3	1:8.3	15	0.064	1.067	0.068	15
836.6	4183	RMC	23.0	22.41	0.01	Rear	Ant. 1	1:1	15	0.429	1.146	0.492	16
836.6	4183	RMC	23.0	22.24	-0.02	Rear	Ant. 3	1:1	15	0.172	1.191	0.205	17
1 880	9400	RMC	21.0	20.23	0.04	Rear	Ant. 2	1:1	15	0.123	1.194	0.147	18
1 880	9400	RMC	21.0	20.24	0.03	Rear	Ant. 3	1:1	15	0.077	1.191	0.092	19
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Body 1.6 W/kg (mW/g) Averaged over 1 gram						

LTE Body-Worn SAR																	
Frequency		Mode	Band width	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	MPR	RB Size	RB offset	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(dBm)	(dBm)	(dB)			(dB)				(mm)	(W/kg)		(W/kg)	
836.5	20525	QPSK	10	22.5	22.23	-0.18	Rear	Ant. 1	0	1	0	1:1	15	0.383	1.064	0.408	20
836.5	20525	QPSK	10	21.5	21.27	0.01	Rear	Ant. 1	1	25	0	1:1	15	0.305	1.054	0.321	-
836.5	20525	QPSK	10	22.5	22.00	-0.06	Rear	Ant. 3	0	1	0	1:1	15	0.204	1.122	0.229	-
836.5	20525	QPSK	10	21.5	21.03	-0.03	Rear	Ant. 3	1	25	0	1:1	15	0.159	1.114	0.177	-
2 510	20850	QPSK	20	22.5	21.44	0.15	Rear	Ant. 1	0	1	0	1:1	15	0.157	1.276	0.200	-
2 535	21100	QPSK	20	21.5	20.56	0.15	Rear	Ant. 1	1	50	0	1:1	15	0.123	1.242	0.153	-
2 510	20850	QPSK	20	22.5	22.11	-0.06	Rear	Ant. 3	0	1	0	1:1	15	0.270	1.094	0.295	21
2 535	21100	QPSK	20	21.5	21.18	-0.077	Rear	Ant. 3	1	50	0	1:1	15	0.246	1.076	0.265	-
2 605	40740	QPSK	20	22.5	21.62	0.18	Rear	Ant. 1	0	1	0	1:1.58	15	0.097	1.225	0.119	-
2 605	40740	QPSK	20	21.5	20.46	-0.05	Rear	Ant. 1	1	50	0	1:1.58	15	0.071	1.271	0.090	-
2 605	40740	QPSK	20	22.5	22.48	-0.173	Rear	Ant. 3	0	1	0	1:1.58	15	0.132	1.005	0.133	22
2 605	40740	QPSK	20	21.5	21.47	-0.187	Rear	Ant. 3	1	50	0	1:1.58	15	0.098	1.007	0.099	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Body 1.6 W/kg (mW/g) Averaged over 1 gram										

DTS Body-Worn SAR																
Frequency		Mode	Band width	Data Rate	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Duty Cycle	Distance	Area Scan Peak SAR	Meas. SAR	Scaling Factor	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(Mbps)	(dBm)	(dBm)	(dB)				(W/kg)	(W/kg)		(Duty)	(W/kg)	
2 412	1	802.11b	22	1	17.5	16.76	0.10	Rear	98.82	15	0.0873	0.065	1.186	1.008	0.078	23
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population								Body 1.6 W/kg (mW/g) Averaged over 1 gram								

11.3 Hotspot SAR Measurement Results

GSM 850 Hotspot SAR													
Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(mm)	(W/kg)		(W/kg)	
824.2	128	GPRS 4Tx	26.5	26.48	-0.05	Rear	Ant. 1	1:2.075	10	0.642	1.005	0.645	-
836.6	190	GPRS 4Tx	26.5	26.12	-0.04	Rear	Ant. 1	1:2.075	10	0.786	1.091	0.858	24
848.8	251	GPRS 4Tx	26.5	26.48	0.01	Rear	Ant. 1	1:2.075	10	0.837	1.005	0.841	25
836.6	190	GPRS 4Tx	26.5	26.12	-0.03	Front	Ant. 1	1:2.075	10	0.493	1.091	0.538	-
836.6	190	GPRS 4Tx	26.5	26.12	0.08	Left	Ant. 1	1:2.075	10	0.477	1.091	0.520	-
836.6	190	GPRS 4Tx	26.5	26.12	-0.04	Bottom	Ant. 1	1:2.075	10	0.309	1.091	0.337	-
836.6	190	GPRS 4Tx	26.5	25.33	-0.04	Rear	Ant. 3	1:2.075	10	0.375	1.309	0.491	-
836.6	190	GPRS 4Tx	26.5	25.33	0.01	Front	Ant. 3	1:2.075	10	0.295	1.309	0.386	-
836.6	190	GPRS 4Tx	26.5	25.33	-0.02	Right	Ant. 3	1:2.075	10	0.139	1.309	0.182	-
836.6	190	GPRS 4Tx	26.5	25.33	-0.01	Top	Ant. 3	1:2.075	10	0.163	1.309	0.213	-
ANSI/ IEEE C95.1 - 1992- Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Body 1.6 W/kg (mW/g) Averaged over 1 gram						

GSM 1900 Hotspot SAR													
Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(dB)	(dB)	(dB)				(mm)	(W/kg)		(W/kg)	
1 880.0	661	GPRS 3Tx	26.5	26.15	-0.13	Rear	Ant. 2	1:2.77	10	0.333	1.084	0.361	26
1 880.0	661	GPRS 3Tx	26.5	26.15	-0.12	Front	Ant. 2	1:2.77	10	0.239	1.084	0.259	-
1 880.0	661	GPRS 3Tx	26.5	26.15	0.01	Right	Ant. 2	1:2.77	10	0.259	1.084	0.281	-
1 880.0	661	GPRS 3Tx	26.5	26.15	0.10	Bottom	Ant. 2	1:2.77	10	0.292	1.084	0.317	-
1 880.0	661	GPRS 3Tx	26.5	26.25	0.14	Rear	Ant. 3	1:2.77	10	0.148	1.059	0.157	-
1 880.0	661	GPRS 3Tx	26.5	26.25	-0.05	Front	Ant. 3	1:2.77	10	0.119	1.059	0.126	-
1 880.0	661	GPRS 3Tx	26.5	26.25	-0.01	Right	Ant. 3	1:2.77	10	0.136	1.059	0.144	-
1 880.0	661	GPRS 3Tx	26.5	26.25	0.07	Top	Ant. 3	1:2.77	10	0.127	1.059	0.134	-
ANSI/ IEEE C95.1 - 1992- Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Body 1.6 W/kg (mW/g) Averaged over 1 gram						

UMTS 850 Hotspot SAR

Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.												
826.4	4132	RMC	23.0	22.31	-0.05	Rear	Ant. 1	1:1	10	0.804	1.172	0.942	-
836.6	4183	RMC	23.0	22.41	-0.01	Rear	Ant. 1	1:1	10	0.867	1.146	0.994	27
846.6	4233	RMC	23.0	22.61	0.01	Rear	Ant. 1	1:1	10	0.816	1.094	0.893	-
836.6	4183	RMC	23.0	22.41	0.01	Front	Ant. 1	1:1	10	0.647	1.146	0.741	-
836.6	4183	RMC	23.0	22.41	-0.05	Left	Ant. 1	1:1	10	0.523	1.146	0.599	-
836.6	4183	RMC	23.0	22.41	0.01	Bottom	Ant. 1	1:1	10	0.325	1.146	0.372	-
836.6	4183	RMC	23.0	22.24	-0.06	Rear	Ant. 3	1:1	10	0.376	1.191	0.448	-
836.6	4183	RMC	23.0	22.24	-0.03	Front	Ant. 3	1:1	10	0.288	1.191	0.343	-
836.6	4183	RMC	23.0	22.24	-0.02	Right	Ant. 3	1:1	10	0.157	1.191	0.187	-
836.6	4183	RMC	23.0	22.24	0.04	Top	Ant. 3	1:1	10	0.171	1.191	0.204	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population						Body 1.6 W/kg (mW/g) Averaged over 1 gram							

UMTS 1900 Hotspot SAR

Frequency		Mode	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.												
1 880.0	9400	RMC	21.0	20.23	-0.07	Rear	Ant. 2	1:1	10	0.417	1.194	0.498	28
1 880.0	9400	RMC	21.0	20.23	-0.01	Front	Ant. 2	1:1	10	0.248	1.194	0.296	-
1 880.0	9400	RMC	21.0	20.23	-0.04	Right	Ant. 2	1:1	10	0.286	1.194	0.341	-
1 880.0	9400	RMC	21.0	20.23	0.11	Bottom	Ant. 2	1:1	10	0.314	1.194	0.375	-
1 880.0	9400	RMC	21.0	20.24	0.02	Rear	Ant. 3	1:1	10	0.153	1.191	0.182	-
1 880.0	9400	RMC	21.0	20.24	0.01	Front	Ant. 3	1:1	10	0.125	1.191	0.149	-
1 880.0	9400	RMC	21.0	20.24	0.05	Right	Ant. 3	1:1	10	0.151	1.191	0.180	-
1 880.0	9400	RMC	21.0	20.24	-0.04	Top	Ant. 3	1:1	10	0.149	1.191	0.177	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population						Body 1.6 W/kg (mW/g) Averaged over 1 gram							

LTE Band 5 (Cell) Hotspot SAR

Frequency		Mode	Band width (MHz)	Tune-Up Limit (dBm)	Meas. Power (dBm)	Power Drift (dB)	Test Position	Antenna Config.	MPR (dB)	RB Size	RB offset	Duty Cycle	Distance (mm)	Meas. SAR (W/kg)	Scaling Factor	Scaled SAR (W/kg)	Plot No.
MHz	Ch.																
836.5	20525	QPSK	10	22.5	22.23	-0.01	Rear	Ant. 1	0	1	0	1:1	10	0.985	1.064	1.048	29
836.5	20525	QPSK	10	21.5	21.27	-0.13	Rear	Ant. 1	1	25	0	1:1	10	0.799	1.054	0.842	-
836.5	20525	QPSK	10	21.5	21.24	0.01	Rear	Ant. 1	1	50	0	1:1	10	0.521	1.062	0.553	-
836.5	20525	QPSK	10	22.5	22.23	0.01	Front	Ant. 1	0	1	0	1:1	10	0.382	1.064	0.406	-
836.5	20525	QPSK	10	21.5	21.27	0.04	Front	Ant. 1	1	25	0	1:1	10	0.409	1.054	0.431	-
836.5	20525	QPSK	10	22.5	22.23	0.02	Left	Ant. 1	0	1	0	1:1	10	0.556	1.064	0.592	-
836.5	20525	QPSK	10	21.5	21.27	0.01	Left	Ant. 1	1	25	0	1:1	10	0.437	1.054	0.461	-
836.5	20525	QPSK	10	22.5	22.23	-0.10	Bottom	Ant. 1	0	1	0	1:1	10	0.327	1.064	0.348	-
836.5	20525	QPSK	10	21.5	21.27	-0.05	Bottom	Ant. 1	1	25	0	1:1	10	0.267	1.054	0.281	-
836.5	20525	QPSK	10	22.5	22.00	-0.01	Rear	Ant. 3	0	1	0	1:1	10	0.467	1.122	0.524	-
836.5	20525	QPSK	10	21.5	21.03	-0.03	Rear	Ant. 3	1	25	0	1:1	10	0.367	1.114	0.409	-
836.5	20525	QPSK	10	22.5	22.00	-0.04	Front	Ant. 3	0	1	0	1:1	10	0.305	1.122	0.342	-
836.5	20525	QPSK	10	21.5	21.03	-0.04	Front	Ant. 3	1	25	0	1:1	10	0.241	1.114	0.268	-
836.5	20525	QPSK	10	22.5	22.00	-0.03	Right	Ant. 3	0	1	0	1:1	10	0.177	1.122	0.199	-
836.5	20525	QPSK	10	21.5	21.03	-0.05	Right	Ant. 3	1	25	0	1:1	10	0.138	1.114	0.154	-
836.5	20525	QPSK	10	22.5	22.00	0.05	Top	Ant. 3	0	1	0	1:1	10	0.181	1.122	0.203	-
836.5	20525	QPSK	10	21.5	21.03	-0.03	Top	Ant. 3	1	25	0	1:1	10	0.142	1.114	0.158	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Body 1.6 W/kg Averaged over 1 gram										

LTE Band 7 Hotspot SAR

Frequency		Mode	Band width	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	MPR	RB Size	RB offset	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(dBm)	(dBm)	(dB)			(dB)				(mm)	(W/kg)		(W/kg)	
2 510	20850	QPSK	20	22.5	21.44	0.01	Rear	Ant. 1	0	1	0	1:1	10	0.383	1.276	0.489	-
2 535	21100	QPSK	20	21.5	20.56	0.19	Rear	Ant. 1	1	50	0	1:1	10	0.346	1.242	0.430	-
2 510	20850	QPSK	20	22.5	21.44	0.11	Front	Ant. 1	0	1	0	1:1	10	0.253	1.276	0.323	-
2 535	21100	QPSK	20	21.5	20.56	0.19	Front	Ant. 1	1	50	0	1:1	10	0.194	1.242	0.241	-
2 510	20850	QPSK	20	22.5	21.44	0.02	Left	Ant. 1	0	1	0	1:1	10	0.378	1.276	0.482	-
2 535	21100	QPSK	20	21.5	20.56	0.01	Left	Ant. 1	1	50	0	1:1	10	0.287	1.242	0.356	-
2 510	20850	QPSK	20	22.5	21.44	0.04	Bottom	Ant. 1	0	1	0	1:1	10	0.168	1.276	0.214	-
2 535	21100	QPSK	20	21.5	20.56	0.07	Bottom	Ant. 1	1	50	0	1:1	10	0.118	1.242	0.147	-
2 510	20850	QPSK	20	22.5	22.11	-0.064	Rear	Ant. 3	0	1	0	1:1	10	0.582	1.094	0.637	30
2 535	21100	QPSK	20	21.5	21.18	-0.036	Rear	Ant. 3	1	50	0	1:1	10	0.442	1.076	0.476	-
2 510	20850	QPSK	20	22.5	22.11	0.016	Front	Ant. 3	0	1	0	1:1	10	0.420	1.094	0.459	-
2 535	21100	QPSK	20	21.5	21.18	0.043	Front	Ant. 3	1	50	0	1:1	10	0.341	1.076	0.367	-
2 510	20850	QPSK	20	22.5	22.11	-0.015	Right	Ant. 3	0	1	0	1:1	10	0.510	1.094	0.558	-
2 535	21100	QPSK	20	21.5	21.18	-0.033	Right	Ant. 3	1	50	0	1:1	10	0.479	1.076	0.515	-
2 510	20850	QPSK	20	22.5	22.11	0.022	Top	Ant. 3	0	1	0	1:1	10	0.207	1.094	0.226	-
2 535	21100	QPSK	20	21.5	21.18	-0.012	Top	Ant. 3	1	50	0	1:1	10	0.203	1.076	0.218	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population							Body 1.6 W/kg Averaged over 1 gram										

LTE TDD Band 41 Hotspot SAR

Frequency		Mode	Band width	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Antenna Config.	MPR	RB Size	RB offset	Duty Cycle	Distance	Meas. SAR	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(dBm)	(dBm)	(dB)			(dB)				(mm)	(W/kg)		(W/kg)	
2 605	40740	QPSK	20	22.5	21.62	-0.16	Rear	Ant. 1	0	1	0	1:1.58	10	0.232	1.225	0.284	-
2 605	40740	QPSK	20	21.5	20.46	0.12	Rear	Ant. 1	1	50	0	1:1.58	10	0.174	1.271	0.221	-
2 605	40740	QPSK	20	22.5	21.62	-0.13	Front	Ant. 1	0	1	0	1:1.58	10	0.153	1.225	0.187	-
2 605	40740	QPSK	20	21.5	20.46	0.14	Front	Ant. 1	1	50	0	1:1.58	10	0.117	1.271	0.149	-
2 605	40740	QPSK	20	22.5	21.62	0.05	Left	Ant. 1	0	1	0	1:1.58	10	0.290	1.225	0.355	31
2 605	40740	QPSK	20	21.5	20.46	0.13	Left	Ant. 1	1	50	0	1:1.58	10	0.193	1.271	0.245	-
2 605	40740	QPSK	20	22.5	21.62	0.16	Bottom	Ant. 1	0	1	0	1:1.58	10	0.085	1.225	0.104	-
2 605	40740	QPSK	20	21.5	20.46	0.16	Bottom	Ant. 1	1	50	0	1:1.58	10	0.063	1.271	0.080	-
2 605	40740	QPSK	20	22.5	22.48	0.112	Rear	Ant. 3	0	1	0	1:1.58	10	0.234	1.005	0.235	-
2 605	40740	QPSK	20	21.5	21.47	-0.132	Rear	Ant. 3	1	50	0	1:1.58	10	0.176	1.007	0.177	-
2 605	40740	QPSK	20	22.5	22.48	-0.016	Front	Ant. 3	0	1	0	1:1.58	10	0.193	1.005	0.194	-
2 605	40740	QPSK	20	21.5	21.47	-0.049	Front	Ant. 3	1	50	0	1:1.58	10	0.146	1.007	0.147	-
2 605	40740	QPSK	20	22.5	22.48	0.004	Right	Ant. 3	0	1	0	1:1.58	10	0.301	1.005	0.303	32
2 605	40740	QPSK	20	21.5	21.47	-0.039	Right	Ant. 3	1	50	0	1:1.58	10	0.232	1.007	0.234	-
2 605	40740	QPSK	20	22.5	22.48	-0.061	Top	Ant. 3	0	1	0	1:1.58	10	0.089	1.005	0.089	-
2 605	40740	QPSK	20	21.5	21.47	0.058	Top	Ant. 3	1	50	0	1:1.58	10	0.088	1.007	0.089	-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population								Body 1.6 W/kg Averaged over 1 gram									

DTS Hotspot SAR

Frequency		Mode	Band width	Data Rate	Tune-Up Limit	Meas. Power	Power Drift	Test Position	Duty Cycle	Distance	Area Scan Peak SAR	Meas. SAR	Scaling Factor	Scaling Factor	Scaled SAR	Plot No.
MHz	Ch.		(MHz)	(Mbps)	(dBm)	(dBm)	(dB)			(mm)	(W/kg)	(W/kg)		(Duty)	(W/kg)	
2 412	1	802.11b	22	1	17.5	16.76	0.12	Rear	98.82	10	0.200	0.154	1.186	1.011	0.185	33
2 412	1	802.11b	22	1	17.5	16.76		Front	98.82	10	0.114		1.186	1.011		-
2 412	1	802.11b	22	1	17.5	16.76		Left	98.82	10	0.194		1.186	1.011		-
2 412	1	802.11b	22	1	17.5	16.76		Top	98.82	10	0.095		1.186	1.011		-
ANSI/ IEEE C95.1 - 1992– Safety Limit Spatial Peak Uncontrolled Exposure/ General Population								Body 1.6 W/kg (mW/g) Averaged over 1 gram								

11.5 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2013, FCC KDB Procedure.
2. Batteries are fully charged at the beginning of the SAR measurements. A standard battery was used for all SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB 447498 D01v06.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 15 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB 648474 D04v01r03, SAR was evaluated without a headset connected to the device. Since the standalone reported SAR was ≤ 1.2 W/kg, no additional SAR evaluation using a headset cable were required.
8. Per KDB 648474 D04v01r03, this device is considered a "Phablet" since the diagonal dimension is > 160 mm and < 200 mm. When hotspot mode applies, extremity SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (with tolerance) is 1 g SAR > 1.2 W/kg.
9. This device utilizes power reduction for some wireless mode and technologies, as outlined in sec. 2.5 and sec.9. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous scenarios.

GSM/GPRS Test Notes:

1. This EUT'S GSM and GPRS device class is B.
2. Body-Worn accessory testing is typically associated with voice operations. Therefore, GSM voice was evaluated for body-worn SAR.
3. Justification for reduced test configurations per KDB 941225 D01v03r01: The source-based time-averaged output power was evaluated for all multi-slot operations. The multi-slot configuration with the highest frame averaged output power including tolerance was evaluated for SAR.
4. Per FCC KDB 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is 1/2 dB, instead of the middle channel, the highest output power channel must be used.
5. Justification for reduced test configurations per KDB Publication 941225 D01v03r01 and October 2013 TCB Workshop Notes: The source-based frame-averaged output power was evaluated for all GPRS/EDGE slot configurations. The configuration with the highest target frame averaged output power was evaluated for hotspot SAR. When the maximum frame-averaged powers are equivalent across two or more slots (within 0.25 dB), the configuration with the most number of time slots was tested.

UMTS Notes:

1. The 12.2 kbps RMC mode is the primary mode per KDB 941225 D01v03r01.
2. UMTS mode in Body SAR was tested under RMC 12.2 kbps with HSPA inactive per KDB 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and Adjusted SAR value was less than 1.2 W/kg.
3. Per FCC KDB 447498 D01v06, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the channel highest output power channel was used.
4. UMTS SAR was tested under RMC 12.2 kbps with HSPA inactive per KDB publication 941225 D01v03r01. HSPA SAR was not required since the average output power of the HSPA subtests was not more than 0.25 dB higher than the RMC level and SAR was less than 1.2 W/kg.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Consideration for LTE Devices in FCC KDB 941225 D05v02r05.
2. According to FCC KDB 941225 D05v02r05:
When the reported SAR is ≤ 0.8 W/kg, testing of the 100%RB allocation and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the 1RB, 50%RB and 100%RB allocation with highest output power for that channel.
Only one channel, and as reported SAR values for 1RB allocation and 50%RB allocation were less than 1.45W/Kg only the highest power RB offset for each allocation was required.
3. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to target MPR is indicated alongside the SAR results.
4. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator.
5. Per KDB 941225 D05Av01r02, SAR for LTE Carrier Aggregation operations was not needed because the maximum average output power in LTE CA mode was not > 0.25 dB higher than the maximum output power when downlink CA was not activated.
6. TDD LTE was tested using UL-DL configuration 0 with 6 UL sub frames and 2S subframes using extended cyclic prefix only and special sub frame configuration 6. SAR tests were performed at maximum output power and worst-case transmission duty factor in extended cyclic prefix. Per 3GPP 36.211 Sec. 4, the duty factor using extended cyclic prefix is 0.633(cf=1.58).
7. SAR test reduction is applied using the following criteria:
Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB, and 50% RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is >0.8 W/kg, testing for other Channels is performed at the highest output power level for 1RB, and 50% RB configuration for that channel. Testing for 100% RB configuration is performed at the highest output power level for 100% RB configuration across the Low, Mid and High Channel when the highest reported SAR for 1 RB and 50% RB are >0.8 W/kg, testing for the remaining required channels is not needed because the reported SAR for 100% RB Allocation <1.45 W/kg. Testing for 16-QAM modulation is not required because the reported SAR for QPSK is <1.45 W/kg and its output power is not more than 0.5 dB higher than that a QPSK. Testing for the other channel bandwidths is not required because the reported SAR for the highest channel bandwidth is <1.45 W/kg and its output power is not more than 0.5 dB higher than that of the highest channel bandwidth.

WLAN Notes:

1. For held-to-ear and hotspot operations, the initial test position procedures were applied. For initial test position, the highest extrapolated peak SAR will be used. When reported SAR for the initial test position is ≤ 0.4 W/kg for 1g SAR and ≤ 1.0 W/kg for 10g SAR, no additional testing for the remaining test positions was required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR results is ≤ 0.8 W/kg for 1g SAR and ≤ 2.0 W/kg for 10g SAR or all test position are measured.
2. Per KDB 248227 D01v02r02 justification for test configurations of 2.4 GHz WiFi Single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11 g/n) was not required due to the maximum allowed powers and the highest reported DSSS SAR.
3. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg or all test channels were measured.
4. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated WLAN test reports.

Bluetooth Notes:

1. Bluetooth SAR was measured with the device connected to a call box with hopping disabled with DH5 operation and Tx Tests mode type. Per October 2016 TCBC Workshop Notes, the reported SAR was scaled to 100% transmission duty factor to determine compliance. Please see sec.9.5 for the time-domain plot and calculation for duty factor of the device.
2. Head Bluetooth SAR were evaluated for BT EDR tethering applications

12. SIMULTANEOUS SAR ANALYSIS

12.1 Simultaneous Transmission Summation for Head

Simultaneous Transmission Summation Scenario with 2.4 GHz WLAN					
Exposure condition	Band	Configuration	WWAN SAR	2.4 GHz WLAN SAR	$\sum$ 1-g SAR
			(W/kg)	(W/kg)	(W/kg)
Head SAR	GSM 850	Left Cheek	0.975	0.140	1.115
		Left Tilt	0.638	0.124	0.762
		Right Cheek	0.465	0.530	0.995
		Right Tilt	0.403	0.440	0.843
	GSM 1900	Left Cheek	1.041	0.140	1.181
		Left Tilt	0.521	0.124	0.645
		Right Cheek	0.438	0.530	0.968
		Right Tilt	0.333	0.440	0.773
	UMTS 850	Left Cheek	0.956	0.140	1.096
		Left Tilt	0.627	0.124	0.751
		Right Cheek	0.514	0.530	1.044
		Right Tilt	0.372	0.440	0.812
	UMTS 1900	Left Cheek	0.860	0.140	1.000
		Left Tilt	0.521	0.124	0.645
		Right Cheek	0.417	0.530	0.947
		Right Tilt	0.267	0.440	0.707
	LTE Band 5	Left Cheek	0.933	0.140	1.073
		Left Tilt	0.688	0.124	0.812
		Right Cheek	0.560	0.530	1.090
		Right Tilt	0.403	0.440	0.843
	LTE Band 7	Left Cheek	1.001	0.140	1.141
		Left Tilt	0.625	0.124	0.749
		Right Cheek	0.232	0.530	0.762
		Right Tilt	0.205	0.440	0.645
	LTE Band 41	Left Cheek	0.694	0.140	0.834
		Left Tilt	0.581	0.124	0.705
		Right Cheek	0.187	0.530	0.717
		Right Tilt	0.183	0.440	0.623

Simultaneous Transmission Summation Scenario with Bluetooth					
Exposure condition	Band	Configuration	WWAN SAR	Bluetooth SAR	$\sum$ 1-g SAR
			(W/kg)	(W/kg)	(W/kg)
Head SAR	GSM 850	Left Cheek	0.975	0.049	1.024
		Left Tilt	0.638	0.049	0.687
		Right Cheek	0.465	0.194	0.659
		Right Tilt	0.403	0.134	0.537
	GSM 1900	Left Cheek	1.041	0.049	1.090
		Left Tilt	0.521	0.049	0.570
		Right Cheek	0.438	0.194	0.632
		Right Tilt	0.333	0.134	0.467
	UMTS 850	Left Cheek	0.956	0.049	1.005
		Left Tilt	0.627	0.049	0.676
		Right Cheek	0.514	0.194	0.708
		Right Tilt	0.372	0.134	0.506
	UMTS 1900	Left Cheek	0.860	0.049	0.909
		Left Tilt	0.521	0.049	0.570
		Right Cheek	0.417	0.194	0.611
		Right Tilt	0.267	0.134	0.401
	LTE Band 5	Left Cheek	0.933	0.049	0.982
		Left Tilt	0.688	0.049	0.737
		Right Cheek	0.560	0.194	0.754
		Right Tilt	0.403	0.134	0.537
	LTE Band 7	Left Cheek	1.001	0.049	1.050
		Left Tilt	0.625	0.049	0.674
		Right Cheek	0.232	0.194	0.426
		Right Tilt	0.205	0.134	0.339
	LTE Band 41	Left Cheek	0.694	0.049	0.743
		Left Tilt	0.581	0.049	0.630
		Right Cheek	0.187	0.194	0.381
		Right Tilt	0.183	0.134	0.317

12.2 Simultaneous Transmission Summation for Body-Worn

Simultaneous Transmission Summation Scenario with 2.4 GHz WLAN					
Exposure condition	Distance	Band	WWAN SAR	2.4 GHz WLAN SAR	Σ 1-g SAR
	(mm)		(W/kg)	(W/kg)	(W/kg)
Body-worn	15	GSM 850	0.506	0.078	0.584
		GSM 1900	0.156	0.078	0.234
		UMTS 850	0.492	0.078	0.570
		UMTS 1900	0.147	0.078	0.225
		LTE Band 5	0.408	0.078	0.486
		LTE Band 7	0.295	0.078	0.373
		LTE Band 41	0.133	0.078	0.211

Simultaneous Transmission Summation Scenario with Bluetooth					
Exposure condition	Distance	Band	WWAN SAR	Bluetooth SAR	Σ 1-g SAR
	(mm)		(W/kg)	(W/kg)	(W/kg)
Body-worn	15	GSM 850	0.506	0.154	0.660
		GSM 1900	0.156	0.154	0.310
		UMTS 850	0.492	0.154	0.646
		UMTS 1900	0.147	0.154	0.301
		LTE Band 5	0.408	0.154	0.562
		LTE Band 7	0.295	0.154	0.449
		LTE Band 41	0.133	0.154	0.287

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498 D01v06. Estimated SAR results were used for SAR summation for body-worn back side at 15 mm to determine simultaneous transmission SAR test exclusion.

12.3 Simultaneous Transmission Summation for Hotspot

Simultaneous Transmission Summation Scenario with 2.4 GHz WLAN					
Exposure condition	Distance	Band	WWAN SAR	2.4 GHz WLAN SAR	Σ 1-g SAR
	(mm)		(W/kg)	(W/kg)	(W/kg)
Hotspot	10	GSM 850	0.858	0.185	1.043
		GSM 1900	0.361	0.185	0.546
		UMTS 850	0.994	0.185	1.179
		UMTS 1900	0.498	0.185	0.683
		LTE Band 5	1.048	0.185	1.233
		LTE Band 7	0.637	0.185	0.822
		LTE Band 41	0.355	0.185	0.540

Simultaneous Transmission Summation Scenario with Bluetooth					
Exposure condition	Distance	Band	WWAN SAR	Bluetooth SAR	Σ 1-g SAR
	(mm)		(W/kg)	(W/kg)	(W/kg)
Hotspot	10	GSM 850	0.858	0.231	1.089
		GSM 1900	0.361	0.231	0.592
		UMTS 850	0.994	0.231	1.225
		UMTS 1900	0.498	0.231	0.729
		LTE Band 5	1.048	0.231	1.279
		LTE Band 7	0.637	0.231	0.868
		LTE Band 41	0.355	0.231	0.586

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498 D01v06. Estimated SAR results were used for SAR summation for hotspot at 10 mm to determine simultaneous transmission SAR test exclusion.

12.4 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit. And therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013.

13. SAR MEASUREMENT VARIABILITY AND UNCERTAINTY

In accordance with KDB procedure 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz, SAR additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement variability was assessed using the following procedures for each frequency band:

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg for 1g SAR or < 2.0 W/kg for 10g SAR; steps 2) through 4) do not apply.
- 2) When the original highest measured 1g SAR is ≥ 0.80 W/kg or 10g SAR ≥ 2.0 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg for 1g SAR or ≥ 3.625 W/kg for 10g SAR ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg for 1g SAR or ≥ 3.75 W/kg for 10g SAR and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Frequency		Modulation	Battery	Configuration	Antenna Config.	Original SAR	Repeated SAR	Largest to Smallest SAR Ratio
MHz	Channel					(W/kg)	(W/kg)	
836.5	20525	LTE Band 5	Standard	Rear	Ant. 1	0.985 (1RB, 0offset)	0.956	1.03
1909.8	810	GSM 1900	Standard	Left touch	Ant. 3	0.840	0.836	1.05
2 510	20850	LTE Band 7	Standard	Left touch	Ant. 3	0.823	0.820	1.01

14. MEASUREMENT UNCERTAINTY

Error Description	Tol (± %)	Prob. dist.	Div.	c _i	Standard Uncertainty (± %)	v _{eff}
1. Measurement System						
Probe Calibration	6.55	N	1	1	6.55	∞
Axial Isotropy	4.70	R	1.73	0.70	1.90	∞
Hemispherical Isotropy	9.60	R	1.73	0.70	3.88	∞
Boundary Effects	2.00	R	1.73	1	1.15	∞
Linearity	4.70	R	1.73	1	2.71	∞
System Detection Limits	0.25	R	1.73	1	0.14	∞
Readout Electronics	0.30	N	1.00	1	0.30	∞
Response Time	0.80	R	1.73	1	0.46	∞
Integration Time	2.60	R	1.73	1	1.50	∞
RF Ambient Noise	3.00	R	1.73	1	1.73	∞
RF Ambient Reflections	3.00	R	1.73	1	1.73	∞
Probe Positioner	0.80	R	1.73	1	0.46	∞
Probe Positioning	6.70	R	1.73	1	3.87	∞
Max SAR Eval	4.00	R	1.73	1	2.31	∞
2. Test Sample Related						
Device Positioning	2.11	N	1.00	1	2.11	9
Device Holder	3.60	N	1.00	1	3.60	5
Power Drift	5.00	R	1.73	1	2.89	∞
Power Scaling	0.00	R	1.73	1	0.00	∞
3. Phantom and Setup						
Phantom Uncertainty	6.60	R	1.73	1	3.82	∞
Liquid Conductivity(target)	5.00	R	1.73	0.64	1.85	∞
Liquid Permittivity(target)	5.00	R	1.73	0.60	1.73	∞
Liquid Conductivity(meas.)	3.80	N	1	0.78	2.96	5
Liquid Permittivity(meas.)	2.60	N	1	0.23	0.60	5
Liquid Conductivity(temp.)	1.70	R	1.73	0.78	0.77	∞
Liquid Permittivity(temp.)	2.70	R	1.73	0.23	0.36	∞
Combine Standard Uncertainty					12.49	
Coverage Factor for 95 %					k=2	
Expanded STD Uncertainty					24.98	

15. SAR TEST EQUIPMENT

Manufacturer	Type / Model	S/N	Calib. Date	Calib.Interval	Calib.Due
SPEAG	SAM Phantom	-	N/A	N/A	N/A
SPEAG	Triple Modular Phantom	-	N/A	N/A	N/A
HP	SAR System Control PC	-	N/A	N/A	N/A
Staubli	Robot RX90B L	F01/5L76A1/A/01	N/A	N/A	N/A
Staubli	TX90 XLspeag	F10/5D1CA1/A/01	N/A	N/A	N/A
Staubli	TX90 XLspeag	F17/59CHA1/A/01	N/A	N/A	N/A
Staubli	TX90 XLspeag	F13/5R4XF1/A/01	N/A	N/A	N/A
Staubli	TX90 XLspeag	F11/5K3RA1/A/01	N/A	N/A	N/A
Staubli	Robot ControllerCS7MB	F01/5L76A1/C/01	N/A	N/A	N/A
Staubli	CS8Cspeag-TX90	F10/5D1CA1/C/01	N/A	N/A	N/A
Staubli	CS8Cspeag-TX90	F17/59CHA1/C/01	N/A	N/A	N/A
Staubli	CS8Cspeag-TX90	F13/5R4XF1/C/01	N/A	N/A	N/A
Staubli	CS8Cspeag-TX90	F11/5K3RA1/C/01	N/A	N/A	N/A
Staubli	Teach Pendant (Joystick)	D21142106	N/A	N/A	N/A
Staubli	Teach Pendant (Joystick)	D22134006 A	N/A	N/A	N/A
Staubli	Teach Pendant (Joystick)	D21142606B	N/A	N/A	N/A
Staubli	Teach Pendant (Joystick)	D21142605	N/A	N/A	N/A
Staubli	Teach Pendant (Joystick)	D21142603	N/A	N/A	N/A
SPEAG	DAE4	652	01/20/2017	Annual	01/20/2018
SPEAG	DAE4	1417	01/19/2017	Annual	01/19/2018
SPEAG	DAE4	869	09/27/2016	Annual	09/27/2017
SPEAG	DAE4	648	05/24/2017	Annual	05/24/2018
SPEAG	DAE4	1225	11/24/2016	Annual	11/24/2017
SPEAG	DAE3	446	01/19/2017	Annual	01/19/2018
SPEAG	E-Field Probe EX3DV4	3903	09/28/2016	Annual	09/28/2017
SPEAG	E-Field Probe EX3DV4	7370	08/30/2016	Annual	08/30/2017
SPEAG	E-Field Probe EX3DV4	3863	05/31/2017	Annual	05/31/2018
SPEAG	E-Field Probe EX3DV4	3797	11/25/2016	Annual	11/25/2017
SPEAG	E-Field Probe EX3DV4	3967	12/14/2016	Annual	12/14/2017
SPEAG	E-Field Probe ET3DV6	1630	02/27/2017	Annual	02/27/2018
SPEAG	E-Field Probe ET3DV6	1605	07/29/2016	Annual	07/29/2017
SPEAG	Dipole D835V2	441	11/16/2016	Annual	11/16/2017
SPEAG	Dipole D1900V2	5d032	03/21/2017	Annual	03/21/2018
SPEAG	Dipole D2450V2	743	03/15/2017	Annual	03/15/2018
SPEAG	Dipole D2600V2	1015	01/18/2017	Annual	01/18/2018
Agilent	Power Meter N1911A	MY45101406	09/28/2016	Annual	09/28/2017
HP	Power Sensor N1921A	MY55220026	08/24/2016	Annual	08/24/2017
SPEAG	DAKS 3.5	1038	05/23/2017	Annual	05/23/2018
SPEAG	VNA-R140	0141013	06/12/2017	Annual	06/12/2018
Agilent	Directional Bridge 86205A	3140A02249	06/09/2017	Annual	06/09/2018
Agilent	Base Station E5515C	GB444400269	02/02/2017	Annual	02/08/2018
HP	Signal Generator E4433B	US40052109	03/10/2017	Annual	03/10/2018
HP	11636B/Power Divider	58698	03/05/2017	Annual	03/05/2018
TESTO	175-H1/Thermometer	40332651310	02/10/2017	Annual	02/10/2018
TESTO	175-H1/Thermometer	40331939309	02/10/2017	Annual	02/10/2018
EMPOWER	RF Power amplifier	1011	10/17/2016	Annual	10/17/2017
Agilent	Attenuator(3dB)	52744	10/16/2016	Annual	10/16/2017
Agilent	Attenuator(20dB)	52664	10/16/2016	Annual	10/16/2017
HP	Dielectric Probe Kit 85070C	00721521	N/A	N/A	N/A
HP	Dual Directional Coupler	16072	10/16/2016	Annual	10/16/2017
R&S	Wideband Radio Communication Tester CMW500	101519	04/27/2017	Annual	04/27/2018

Anritsu	Radio Communication Analyzer/ MT8820C	6200628628	07/04/2017	Annual	07/04/2018
Anritsu	Radio Communication Analyzer/ MT8820C	6200576565	07/04/2017	Annual	07/04/2018
R&S	Bluetooth CBT	100272	03/05/2017	Annual	03/05/2018

NOTE:

1. The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Verification measurement is performed by HCT Lab. before each test. The brain/body simulating material is calibrated by HCT using the DAKS 3.5 to determine the conductivity and permittivity (dielectric constant) of the brain/body-equivalent material.

16. CONCLUSION

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the ANSI/IEEE C95.1 - 1992.

These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests.

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

17. REFERENCES

- [1] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice or Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices.
- [2] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radio frequency Radiation, Aug. 1996.
- [3] ANSI/IEEE C95.1 - 1991, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 kHz to 100 GHz, New York: IEEE, Aug. 1992
- [4] ANSI/IEEE C 95.1 - 2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3 kHz to 300 GHz, New York: IEEE, 2006.
- [5] ANSI/IEEE C95.3 - 1991, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, 1992.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300 MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectro magnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computer mathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10 kHz-300 GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenøssische Technische Hoschs Schule Zòrich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation and procedures – Part 1:Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.

- [21] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz) Mar. 2010.
- [22] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radio Communication Apparatus (All Frequency Band) Issue 5, March 2015.
- [23] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [24] FCC SAR Test procedures for 2G-3G Devices, Mobile Hotspot and UMPC Device KDB 941225 D01.
- [25] SAR Measurement Guidance for IEEE 802.11 transmitters, KDB 248227 D01v02r02
- [26] SAR Evaluation of Handsets with Multiple Transmitters and Antennas KDB 648474 D03, D04.
- [27] SAR Evaluation for Laptop, Notebook, Netbook and Tablet computers KDB 616217 D04.
- [28] SAR Measurement and Reporting Requirements for 100 MHz – 6 GHz, KDB 865664 D01, D02.
- [29] FCC General RF Exposure Guidance and SAR procedures for Dongles, KDB 447498 D01,D02.

Attachment 1. – SAR Test Plots

Test Laboratory: HCT CO., LTD
 EUT Type: Mobile Phone
 Liquid Temperature: 21.2 °C
 Ambient Temperature: 21.4 °C
 Test Date: 07/22/2017
 Plot No.: 1

DUT: SM-C7100; Type: Bar

Communication System: UID 0, GSM 850 ; Frequency: 824.2 MHz;Duty Cycle: 1:8.30042
 Medium parameters used (interpolated): $f = 824.2$ MHz; $\sigma = 0.896$ S/m; $\epsilon_r = 41.524$; $\rho = 1000$ kg/m³
 Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(9.33, 9.33, 9.33); Calibrated: 2016-11-25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1225; Calibrated: 2016-11-24
- Phantom: Twin-SAM
- Measurement SW: DASY52, Version 52.8 (8);


GSM850 Head Ant3.Left touch 128ch back-off/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

GSM850 Head Ant3.Left touch 128ch back-off/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.57 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.92 W/kg

SAR(1 g) = 0.911 W/kg; SAR(10 g) = 0.483 W/kg



0 dB = 0.992 W/kg = -0.03 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 21.2 °C
Ambient Temperature: 21.4 °C
Test Date: 07/22/2017
Plot No.: 2

DUT: SM-C7100; Type: Bar

Communication System: UID 0, GSM 850 (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042
Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.911$ S/m; $\epsilon_r = 41.32$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(9.33, 9.33, 9.33); Calibrated: 2016-11-25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1225; Calibrated: 2016-11-24
- Phantom: Twin-SAM
- Measurement SW: DASY52, Version 52.8 (8);


Ant3. GSM850 Left touch 190ch back-off/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant3. GSM850 Left touch 190ch back-off/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.50 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 0.891 W/kg; SAR(10 g) = 0.477 W/kg



0 dB = 0.964 W/kg = -0.16 dBW/kg

Test Laboratory: HCT CO., LTD
 EUT Type: Mobile Phone
 Liquid Temperature: 20.9 °C
 Ambient Temperature: 21.1 °C
 Test Date: 07/25/2017
 Plot No.: 3

DUT: SM-C7100; Type: Bar

Communication System: UID 0, GSM 1900 (0); Frequency: 1909.8 MHz; Duty Cycle: 1:8.30042
 Medium parameters used: $f = 1910$ MHz; $\sigma = 1.43$ S/m; $\epsilon_r = 39.4$; $\rho = 1000$ kg/m³
 Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(8.22, 8.22, 8.22); Calibrated: 2016-12-14;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);


Ant.3 GSM1900 Left touch 810ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant.3 GSM1900 Left touch 810ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.89 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 0.840 W/kg; SAR(10 g) = 0.489 W/kg



0 dB = 1.07 W/kg = 0.29 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 21.2 °C
Ambient Temperature: 21.4 °C
Test Date: 07/22/2017
Plot No.: 4

DUT: SM-C7100; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 826.4 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 826.4$ MHz; $\sigma = 0.897$ S/m; $\epsilon_r = 41.482$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(9.33, 9.33, 9.33); Calibrated: 2016-11-25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1225; Calibrated: 2016-11-24
- Phantom: Twin-SAM
- Measurement SW: DASY52, Version 52.8 (8);


Ant.3 WCDMA850 Left touch 4132ch back-off/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant.3 WCDMA850 Left touch 4132ch back-off/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.62 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.83 W/kg

SAR(1 g) = 0.854 W/kg; SAR(10 g) = 0.445 W/kg



0 dB = 1.03 W/kg = 0.13 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.9 °C
Ambient Temperature: 21.1 °C
Test Date: 07/25/2017
Plot No.: 5

DUT: SM-C7100; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1852.4$ MHz; $\sigma = 1.38$ S/m; $\epsilon_r = 39.533$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(8.22, 8.22, 8.22); Calibrated: 2016-12-14;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);


Ant.3 WCDMA1900 Left touch 9262ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant.3 WCDMA1900 Left touch 9262ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 16.64 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.802 W/kg; SAR(10 g) = 0.480 W/kg



0 dB = 0.980 W/kg = -0.09 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.9 °C
Ambient Temperature: 21.1 °C
Test Date: 07/25/2017
Plot No.: 6

DUT: SM-C7100; Type: Bar

Communication System: UID 0, WCDMA1900 (0); Frequency: 1907.6 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 1907.6$ MHz; $\sigma = 1.429$ S/m; $\epsilon_r = 39.409$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(8.22, 8.22, 8.22); Calibrated: 2016-12-14;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);


Ant.3 WCDMA1900 Left touch 9538ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant.3 WCDMA1900 Left touch 9538ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 15.11 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.18 W/kg

SAR(1 g) = 0.750 W/kg; SAR(10 g) = 0.447 W/kg



0 dB = 0.934 W/kg = -0.30 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 21.2 °C
Ambient Temperature: 21.4 °C
Test Date: 07/22/2017
Plot No.: 7

DUT: SM-C7100; Type: Bar

Communication System: UID 0, LTE Band 5 (0); Frequency: 836.5 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.911$ S/m; $\epsilon_r = 41.321$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(9.33, 9.33, 9.33); Calibrated: 2016-11-25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1225; Calibrated: 2016-11-24
- Phantom: Twin-SAM
- Measurement SW: DASY52, Version 52.8 (8);

Ant.3 LTE Band5 Left touch QPSK 10MHz 1RB 0offset 20525ch back-off/Area Scan (8x13x1):

Measurement grid: dx=15mm, dy=15mm


Ant.3 LTE Band5 Left touch QPSK 10MHz 1RB 0offset 20525ch back-off/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 25.41 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 0.804 W/kg; SAR(10 g) = 0.432 W/kg



0 dB = 0.963 W/kg = -0.16 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 19.7 °C
Ambient Temperature: 19.9 °C
Test Date: 07/24/2017
Plot No.: 8

DUT: SM-C7100; Type: Bar

Communication System: UID 0, LTE Band 7 (0); Frequency: 2510 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2510 \text{ MHz}$; $\sigma = 1.924 \text{ S/m}$; $\epsilon_r = 39.326$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(7.23, 7.23, 7.23); Calibrated: 2016-12-14;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);

ANT 3. LTE Band7 Head Left Touch QPSK 20MHz 1RB 0offset 20850ch/Area Scan (9x15x1):

Measurement grid: $dx=12\text{mm}$, $dy=12\text{mm}$


ANT 3. LTE Band7 Head Left Touch QPSK 20MHz 1RB 0offset 20850ch/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 11.06 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 1.78 W/kg

SAR(1 g) = 0.823 W/kg; SAR(10 g) = 0.390 W/kg



$$0 \text{ dB} = 0.938 \text{ W/kg} = -0.28 \text{ dBW/kg}$$

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 19.7 °C
Ambient Temperature: 19.9 °C
Test Date: 07/24/2017
Plot No.: 9

DUT: SM-C7100; Type: Bar

Communication System: UID 0, LTE Band 41 (FCC) (0); Frequency: 2605 MHz; Duty Cycle: 1:1.58052
Medium parameters used (interpolated): $f = 2605$ MHz; $\sigma = 2.034$ S/m; $\epsilon_r = 38.998$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(7.23, 7.23, 7.23); Calibrated: 2016-12-14;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);

ANT 3. LTE Band41 Head Left Touch QPSK 20MHz 1RB 0offset 40740ch/Area Scan (9x15x1):

Measurement grid: dx=12mm, dy=12mm


ANT 3. LTE Band41 Head Left Touch QPSK 20MHz 1RB 0offset 40740ch/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.46 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.61 W/kg

SAR(1 g) = 0.688 W/kg; SAR(10 g) = 0.322 W/kg



0 dB = 0.915 W/kg = -0.39 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.0 °C
Ambient Temperature: 20.2 °C
Test Date: 07/03/2017
Plot No.: 10

DUT: SM-C7100; Type: bar

Communication System: UID 0, 2450MHz FCC; Frequency: 2462 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.86$ S/m; $\epsilon_r = 38.376$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN7370; ConvF(7.28, 7.28, 7.28); Calibrated: 2016-08-30;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1417; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);


802.11b Head Right Touch 1Mbps 11ch/Area Scan (9x15x1): Measurement grid: dx=12mm, dy=12mm

802.11b Head Right Touch 1Mbps 11ch/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.644 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.433 W/kg; SAR(10 g) = 0.197 W/kg



0 dB = 0.617 W/kg = -2.10 dBW/kg

Test Laboratory: HCT CO., LTD

EUT Type: Mobile Phone
Liquid Temperature: 20.0 °C
Ambient Temperature: 20.2 °C
Test Date: 07/03/2017
Plot No.: 11

DUT: SM-C7100; Type: bar

Communication System: UID 0, Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.31
Medium parameters used (interpolated): $f = 2441$ MHz; $\sigma = 1.836$ S/m; $\epsilon_r = 38.473$; $\rho = 1000$ kg/m³
Phantom section: Right Section

DASY Configuration:

- Probe: EX3DV4 - SN7370; ConvF(7.28, 7.28, 7.28); Calibrated: 2016-08-30;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1417; Calibrated: 2017-01-19
- Phantom: SAM
- Measurement SW: DASY52, Version 52.8 (8);


BlueTooth DH-5 Head Right Touch 39ch/Area Scan (9x15x1): Measurement grid: dx=12mm, dy=12mm

BlueTooth DH-5 Head Right Touch 39ch/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.268 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 0.358 W/kg

SAR(1 g) = 0.145 W/kg; SAR(10 g) = 0.065 W/kg



0 dB = 0.200 W/kg = -7.00 dBW/kg

Test Laboratory: HCT CO., LTD
 EUT Type: Mobile Phone
 Liquid Temperature: 20.5 °C
 Ambient Temperature: 20.8 °C
 Test Date: 06/26/2017
 Plot No.: 12

DUT: SM-C7100; Type: bar

Communication System: UID 0, GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:8.3
 Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.949 \text{ S/m}$; $\epsilon_r = 56.752$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);


GSM850 Body Ant 1 Rear Voice 190ch 15mm/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

GSM850 Body Ant 1 Rear Voice 190ch 15mm/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 19.79 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 0.608 W/kg


SAR(1 g) = 0.445 W/kg; SAR(10 g) = 0.310 W/kg



$$0 \text{ dB} = 0.459 \text{ W/kg} = -3.38 \text{ dBW/kg}$$

(*)Note : In the report showing the second highest point was actually less than the one measured

The following plot no.12 have measured at the highest peak. Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, Additional zoom scans are not required.



Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.3 °C
Ambient Temperature: 20.5 °C
Test Date: 07/27/2017
Plot No.: 13

DUT: SM-C7100; Type: Bar

Communication System: UID 0, GSM 850 1Tx (0); Frequency: 836.6 MHz; Duty Cycle: 1:8.30042
Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.955$ S/m; $\epsilon_r = 56.416$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(9.42, 9.42, 9.42); Calibrated: 2016-11-25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1225; Calibrated: 2016-11-24
- Phantom: MFP Triple Phantom
- Measurement SW: DASY52, Version 52.8 (8);


Ant.3 GSM850 Body worn Rear 190ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant.3 GSM850 Body worn Rear 190ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.400 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 0.260 W/kg

SAR(1 g) = 0.164 W/kg; SAR(10 g) = 0.095 W/kg



0 dB = 0.205 W/kg = -6.88 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.2 °C
Ambient Temperature: 22.5 °C
Test Date: 06/28/2017
Plot No.: 14

DUT: SM-C7100; Type: bar

Communication System: UID 0, GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.539$ S/m; $\epsilon_r = 53.588$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.07, 5.07, 5.07); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);


GSM1900 Body worn Ant. 2 Rear Voice 661ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

GSM1900 Body worn Ant. 2 Rear Voice 661ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 5.413 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.233 W/kg


SAR(1 g) = 0.146 W/kg; SAR(10 g) = 0.080 W/kg



$$0 \text{ dB} = 0.128 \text{ W/kg} = -8.94 \text{ dBW/kg}$$

(*)Note : In the report showing the second highest point was actually less than the one measured

The following plot no.14 have measured at the highest peak. Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, Additional zoom scans are not required.



Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 19.2 °C
Ambient Temperature: 19.4 °C
Test Date: 07/27/2017
Plot No.: 15

DUT: SM-C7100; Type: Bar

Communication System: UID 0, GSM 1900 (0); Frequency: 1880 MHz; Duty Cycle: 1:8.30042
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.516$ S/m; $\epsilon_r = 55.392$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY5 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.55, 4.55, 4.55); Calibrated: 2016-07-29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2016-09-27
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);


ANT 3.GSM1900 body rear 661ch body worn/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm

ANT 3.GSM1900 body rear 661ch body worn/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.513 V/m; Power Drift = -0.09 dB



Peak SAR (extrapolated) = 0.106 W/kg

SAR(1 g) = 0.064 W/kg; SAR(10 g) = 0.034 W/kg



0 dB = 0.0742 W/kg = -11.30 dBW/kg

The following plot no.15 have measured at the highest peak. Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, Additional zoom scans are not required.



Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.5 °C
Ambient Temperature: 20.8 °C
Test Date: 06/26/2017
Plot No.: 16

DUT: SM-C7100; Type: bar


Communication System: UID 0, WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.949 \text{ S/m}$; $\epsilon_r = 56.752$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

WCDMA850 Body Ant. 1 Rear 4183ch body worn/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

WCDMA850 Body Ant. 1 Rear 4183ch body worn/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
Reference Value = 18.40 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.581 W/kg
SAR(1 g) = 0.429 W/kg; SAR(10 g) = 0.297 W/kg



$$0 \text{ dB} = 0.457 \text{ W/kg} = -3.40 \text{ dBW/kg}$$

(*)Note : In the report showing the second highest point was actually less than the one measured

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.3 °C
Ambient Temperature: 20.5 °C
Test Date: 07/27/2017
Plot No.: 17

DUT: SM-C7100; Type: Bar

Communication System: UID 0, WCDMA850 (0); Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.955 \text{ S/m}$; $\epsilon_r = 56.416$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3797; ConvF(9.42, 9.42, 9.42); Calibrated: 2016-11-25;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1225; Calibrated: 2016-11-24
- Phantom: MFP Triple Phantom
- Measurement SW: DASY52, Version 52.8 (8);


Ant.3 WCDMA850 Body worn Rear 4183ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Ant.3 WCDMA850 Body worn Rear 4183ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.42 V/m; Power Drift = -0.02 dB



Peak SAR (extrapolated) = 0.274 W/kg

SAR(1 g) = 0.172 W/kg; SAR(10 g) = 0.100 W/kg



0 dB = 0.197 W/kg = -7.06 dBW/kg

The following plot no.17 have measured at the highest peak. Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, Additional zoom scans are not required.



Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.2 °C
Ambient Temperature: 22.5 °C
Test Date: 06/28/2017
Plot No.: 18

DUT: SM-C7100; Type: bar

Communication System: UID 0, WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.539 \text{ S/m}$; $\epsilon_r = 53.588$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.07, 5.07, 5.07); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);


WCDMA1900 Body Ant. 2 Rear 9400ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

WCDMA1900 Body Ant. 2 Rear 9400ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.698 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.169 W/kg


SAR(1 g) = 0.123 W/kg; SAR(10 g) = 0.084 W/kg



$$0 \text{ dB} = 0.130 \text{ W/kg} = -8.86 \text{ dBW/kg}$$

(*)Note : In the report showing the second highest point was actually less than the one measured

The following plot no.18 have measured at the highest peak. Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, Additional zoom scans are not required.



Area Scan

Grid Measurement Profile Results Report

Maxima
Find secondary maxima within 2 dB,
and with a peak SAR value greater than 0.15 W/kg,
and at least 5 mm away from the global maximum.

Maxima found:

Value...	X	Y	Z	Yaw	Pitch	Roll
0.211	26.52	-29.97	-171.9	-5.00...	180	-5.00
0.179	70.02	-17.96	-171.7	-5.00...	180	-5.00

Averaged Fast SAR

☒ Linear fit a: -10.7 b: 40.4

☐ Polynomial fit

1g: 0.166 W/kg, Sec. 1g: 0.162 W/kg
10g: 0.0921 W/kg

☐ Interrupt if maximum SAR is below 0.1 W/kg

Close Cancel Apply

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 19.2 °C
Ambient Temperature: 19.4 °C
Test Date: 07/27/2017
Plot No.: 19

DUT: SM-C7100; Type: Bar


Communication System: UID 0, WCDMA1900 (0); Frequency: 1880 MHz;Duty Cycle: 1:1
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.516$ S/m; $\epsilon_r = 55.392$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY5 Configuration:

- Probe: ET3DV6 - SN1605; ConvF(4.55, 4.55, 4.55); Calibrated: 2016-07-29;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn869; Calibrated: 2016-09-27
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

ANT 3. WCDMA1900 body rear body worn 9400ch/Area Scan (8x14x1): Measurement grid: dx=15mm, dy=15mm



ANT 3. WCDMA1900 body rear body worn 9400ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 4.495 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 0.135 W/kg
SAR(1 g) = 0.077 W/kg; SAR(10 g) = 0.042 W/kg



0 dB = 0.0856 W/kg = -10.68 dBW/kg

(*)Note : In the report showing the second highest point was actually less than the one measured

The following plot no.19 have measured at the highest peak. Per KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04, Additional zoom scans are not required.



Test Laboratory: HCT CO., LTD
 EUT Type: Mobile Phone
 Liquid Temperature: 20.5 °C
 Ambient Temperature: 20.8 °C
 Test Date: 06/26/2017
 Plot No.: 20

DUT: SM-C7100; Type: bar


Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 836.5 \text{ MHz}$; $\sigma = 0.949 \text{ S/m}$; $\epsilon_r = 56.753$; $\rho = 1000 \text{ kg/m}^3$
 Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

LTE Band5 Body Ant.1 Rear QPSK 10MHz 1RB 0offset 20525ch Body worn/Area Scan (8x13x1):
 Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

LTE Band5 Body Ant.1 Rear QPSK 10MHz 1RB 0offset 20525ch Body worn/Zoom Scan (5x5x7)/Cube
 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$
 Reference Value = 16.48 V/m; Power Drift = -0.18 dB
 Peak SAR (extrapolated) = 0.524 W/kg
SAR(1 g) = 0.383 W/kg; SAR(10 g) = 0.264 W/kg



$$0 \text{ dB} = 0.399 \text{ W/kg} = -3.99 \text{ dBW/kg}$$

(*)Note : In the report showing the second highest point was actually less than the one measured

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.0 °C
Ambient Temperature: 22.3 °C
Test Date: 07/27/2017
Plot No.: 21

DUT: SM-C7100; Type: bar

Communication System: LTE Band 7; Frequency: 2510 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2510$ MHz; $\sigma = 2$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY4 Configuration:


- Probe: EX3DV4 - SN3967; ConvF(7.28, 7.28, 7.28); Calibrated: 2016-12-14
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY4, V4.7 Build 80
- Postprocessing SW: SEMCAD, V1.8 Build 186

ANT3. LTE Band7 Body Rear QPSK 20MHz 1RB 0offset 20850ch Body Worn/Area Scan (9x16x1):

Measurement grid: dx=12mm, dy=12mm

ANT3. LTE Band7 Body Rear QPSK 20MHz 1RB 0offset 20850ch Body Worn/Zoom Scan (7x7x7)/Cube

0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 6.94 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 0.498 W/kg
SAR(1 g) = 0.270 mW/g; SAR(10 g) = 0.147 mW/g



0 dB = 0.383mW/g

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.0 °C
Ambient Temperature: 22.3 °C
Test Date: 07/27/2017
Plot No.: 22

DUT: SM-C7100; Type: bar

Communication System: LTE Band 41 (FCC); Frequency: 2605 MHz; Duty Cycle: 1:1.58
Medium parameters used (interpolated): $f = 2605$ MHz; $\sigma = 2.12$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(7.28, 7.28, 7.28); Calibrated: 2016-12-14
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY4, V4.7 Build 80
- Postprocessing SW: SEMCAD, V1.8 Build 186

ANT3. LTE Band7 Body Rear QPSK 20MHz 1RB 0offset 40740ch Body Worn/Area Scan (9x16x1):

Measurement grid: dx=12mm, dy=12mm


ANT3. LTE Band7 Body Rear QPSK 20MHz 1RB 0offset 40740ch Body Worn/Zoom Scan (7x7x7)/Cube

0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.16 V/m; Power Drift = -0.173 dB

Peak SAR (extrapolated) = 0.248 W/kg

SAR(1 g) = 0.132 mW/g; SAR(10 g) = 0.070 mW/g



0 dB = 0.188mW/g

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 19.6 °C
Ambient Temperature: 19.8 °C
Test Date: 07/04/2017
Plot No.: 23

DUT: SM-C7100; Type: bar

Communication System: UID 0, 2450MHz FCC; Frequency: 2412 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 2412$ MHz; $\sigma = 1.929$ S/m; $\epsilon_r = 52.446$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN7370; ConvF(7.62, 7.62, 7.62); Calibrated: 2016-08-30;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1417; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);


802.11b Body rear 1Mbps 1ch/Area Scan (9x15x1): Measurement grid: dx=12mm, dy=12mm

802.11b Body rear 1Mbps 1ch/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.533 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.124 W/kg

SAR(1 g) = 0.065 W/kg; SAR(10 g) = 0.035 W/kg



0 dB = 0.0829 W/kg = -10.81 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.5 °C
Ambient Temperature: 20.8 °C
Test Date: 06/26/2017
Plot No.: 24

DUT: SM-C7100; Type: bar

Communication System: UID 0, GSM 850; Frequency: 836.6 MHz; Duty Cycle: 1:2.075
Medium parameters used (interpolated): $f = 836.6 \text{ MHz}$; $\sigma = 0.949 \text{ S/m}$; $\epsilon_r = 56.752$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

GSM850 Body Ant.1 Rear 4Tx 190ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

GSM850 Body Ant.1 Rear 4Tx 190ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.28 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 1.42 W/kg



SAR(1 g) = 0.786 W/kg; SAR(10 g) = 0.434 W/kg

GSM850 Body Ant.1 Rear 4Tx 190ch/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.28 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.972 W/kg

SAR(1 g) = 0.675 W/kg; SAR(10 g) = 0.444 W/kg



0 dB = 0.676 W/kg = -1.70 dBW/kg

Test Laboratory: HCT CO., LTD
 EUT Type: Mobile Phone
 Liquid Temperature: 20.5 °C
 Ambient Temperature: 20.8 °C
 Test Date: 06/26/2017
 Plot No.: 25

DUT: SM-C7100; Type: bar

Communication System: UID 0, GSM 850; Frequency: 848.8 MHz; Duty Cycle: 1:2.075
 Medium parameters used (interpolated): $f = 848.8$ MHz; $\sigma = 0.964$ S/m; $\epsilon_r = 56.606$; $\rho = 1000$ kg/m³
 Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

GSM850 Body Ant.1 Rear 4Tx 251ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.697 W/kg

GSM850 Body Ant.1 Rear 4Tx 251ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.09 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.52 W/kg

SAR(1 g) = 0.837 W/kg; SAR(10 g) = 0.459 W/kg

Maximum value of SAR (measured) = 0.891 W/kg


GSM850 Body Ant.1 Rear 4Tx 251ch/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.09 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.694 W/kg; SAR(10 g) = 0.448 W/kg

Maximum value of SAR (measured) = 0.751 W/kg



$$0 \text{ dB} = 0.697 \text{ W/kg} = -1.57 \text{ dBW/kg}$$

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.2 °C
Ambient Temperature: 22.5 °C
Test Date: 06/28/2017
Plot No.: 26

DUT: SM-C7100; Type: bar

Communication System: UID 0, GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:2.77
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.539 \text{ S/m}$; $\epsilon_r = 53.588$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.07, 5.07, 5.07); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

GSM1900 Body Ant.2 Rear 3TX 661ch/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (measured) = 0.289 W/kg


GSM1900 Body Ant.2 Rear 3TX 661ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.261 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 0.562 W/kg

SAR(1 g) = 0.333 W/kg; SAR(10 g) = 0.175 W/kg

Maximum value of SAR (measured) = 0.381 W/kg



$$0 \text{ dB} = 0.289 \text{ W/kg} = -5.40 \text{ dBW/kg}$$

(*)Note : In the report showing the second highest point was actually less than the one measured

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.5 °C
Ambient Temperature: 20.8 °C
Test Date: 06/26/2017
Plot No.: 27

DUT: SM-C7100; Type: bar

Communication System: UID 0, WCDMA850; Frequency: 836.6 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.949$ S/m; $\epsilon_r = 56.752$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

WCDMA850 Body Ant.1 Rear 4183ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.759 W/kg

WCDMA850 Body Ant.1Rear 4183ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.46 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.57 W/kg

SAR(1 g) = 0.867 W/kg; SAR(10 g) = 0.478 W/kg

Maximum value of SAR (measured) = 0.931 W/kg


WCDMA850 Body Ant.1 Rear 4183ch/Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.46 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.723 W/kg; SAR(10 g) = 0.471 W/kg

Maximum value of SAR (measured) = 0.784 W/kg



$$0 \text{ dB} = 0.759 \text{ W/kg} = -1.20 \text{ dBW/kg}$$

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.2 °C
Ambient Temperature: 22.5 °C
Test Date: 06/28/2017
Plot No.: 28

DUT: SM-C7100; Type: bar

Communication System: UID 0, WCDMA1900; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.539 \text{ S/m}$; $\epsilon_r = 53.588$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(5.07, 5.07, 5.07); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

WCDMA1900 Body Ant.2 Rear 9400ch/Area Scan (8x13x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (measured) = 0.472 W/kg


WCDMA1900 Body Ant.2 Rear 9400ch/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 8.163 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 0.716 W/kg

SAR(1 g) = 0.417 W/kg; SAR(10 g) = 0.216 W/kg

Maximum value of SAR (measured) = 0.455 W/kg



0 dB = 0.455 W/kg = -3.42 dBW/kg

Test Laboratory: HCT CO., LTD
 EUT Type: Mobile Phone
 Liquid Temperature: 20.5 °C
 Ambient Temperature: 20.8 °C
 Test Date: 06/26/2017
 Plot No.: 29

DUT: SM-C7100; Type: bar

Communication System: UID 0, LTE Band 5; Frequency: 836.5 MHz; Duty Cycle: 1:1
 Medium parameters used (interpolated): $f = 836.5$ MHz; $\sigma = 0.949$ S/m; $\epsilon_r = 56.753$; $\rho = 1000$ kg/m³
 Phantom section: Center Section

DASY Configuration:

- Probe: ET3DV6 - SN1630; ConvF(6.73, 6.73, 6.73); Calibrated: 2017-02-27;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn652; Calibrated: 2017-01-20
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

LTE Band5 Body Ant.1 Rear QPSK 10MHz 1RB 0offset 20525ch/Area Scan (8x13x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.941 W/kg

LTE Band5 Body Ant.1 Rear QPSK 10MHz 1RB 0offset 20525ch/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.34 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.81 W/kg

SAR(1 g) = 0.985 W/kg; SAR(10 g) = 0.543 W/kg

Maximum value of SAR (measured) = 1.05 W/kg

LTE Band5 Body Ant.1 Rear QPSK 10MHz 1RB 0offset 20525ch/Zoom Scan (5x5x7)/Cube 1:



Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.34 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.803 W/kg; SAR(10 g) = 0.508 W/kg

Maximum value of SAR (measured) = 0.852 W/kg



$$0 \text{ dB} = 0.941 \text{ W/kg} = -0.27 \text{ dBW/kg}$$

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.0 °C
Ambient Temperature: 22.3 °C
Test Date: 07/27/2017
Plot No.: 30

DUT: SM-C7100; Type: bar



Communication System: LTE Band 7; Frequency: 2510 MHz; Duty Cycle: 1:1
Medium parameters used: $f = 2510 \text{ MHz}$; $\sigma = 2 \text{ mho/m}$; $\epsilon_r = 52.5$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Center Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(7.28, 7.28, 7.28); Calibrated: 2016-12-14
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY4, V4.7 Build 80
- Postprocessing SW: SEMCAD, V1.8 Build 186

ANT3. LTE Band7 Body Rear QPSK 20MHz 1RB 0offset 20850ch/Area Scan (9x16x1): Measurement
grid: $dx=12\text{mm}$, $dy=12\text{mm}$
Maximum value of SAR (measured) = 0.761 mW/g

ANT3. LTE Band7 Body Rear QPSK 20MHz 1RB 0offset 20850ch/Zoom Scan (7x7x7)/Cube 0:
Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 9.36 V/m; Power Drift = -0.064 dB
Peak SAR (extrapolated) = 1.12 W/kg
SAR(1 g) = 0.582 mW/g; SAR(10 g) = 0.302 mW/g
Maximum value of SAR (measured) = 0.833 mW/g



0 dB = 0.833mW/g

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 20.1 °C
Ambient Temperature: 20.4 °C
Test Date: 07/10/2017
Plot No.: 31

DUT: SM-C7100; Type: bar

Communication System: UID 0, LTE Band 41 (FCC); Frequency: 2605 MHz; Duty Cycle: 1:1.58
Medium parameters used (interpolated): $f = 2605$ MHz; $\sigma = 2.205$ S/m; $\epsilon_r = 54.335$; $\rho = 1000$ kg/m³
Phantom section: Center Section



DASY Configuration:

- Probe: EX3DV4 - SN7370; ConvF(7.42, 7.42, 7.42); Calibrated: 2016-08-30;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1417; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

Ant.1 LTE Band41 Body Left QPSK 20MHz 1RB 0offset 40740ch/Area Scan (6x16x1): Measurement
grid: dx=12mm, dy=12mm

Ant.1 LTE Band41 Body Left QPSK 20MHz 1RB 0offset 40740ch/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.21 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.572 W/kg
SAR(1 g) = 0.290 W/kg; SAR(10 g) = 0.144 W/kg



0 dB = 0.403 W/kg = -3.95 dBW/kg

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 22.0 °C
Ambient Temperature: 22.3 °C
Test Date: 07/27/2017
Plot No.: 32

DUT: SM-C7100; Type: bar


Communication System: LTE Band 41 (FCC); Frequency: 2605 MHz; Duty Cycle: 1:1.58
Medium parameters used (interpolated): $f = 2605$ MHz; $\sigma = 2.12$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3967; ConvF(7.28, 7.28, 7.28); Calibrated: 2016-12-14
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn446; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY4, V4.7 Build 80
- Postprocessing SW: SEMCAD, V1.8 Build 186

ANT3. LTE Band41 Body Front QPSK 20MHz 1RB 0offset 40740ch/Area Scan (7x16x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.373 mW/g

ANT3. LTE Band41 Body Front QPSK 20MHz 1RB 0offset 40740ch/Zoom Scan (7x7x7)/Cube 0:
Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 11.0 V/m; Power Drift = 0.004 dB
Peak SAR (extrapolated) = 0.594 W/kg
SAR(1 g) = 0.301 mW/g; SAR(10 g) = 0.147 mW/g
Maximum value of SAR (measured) = 0.443 mW/g



0 dB = 0.443mW/g

Test Laboratory: HCT CO., LTD
EUT Type: Mobile Phone
Liquid Temperature: 19.6 °C
Ambient Temperature: 19.8 °C
Test Date: 07/04/2017
Plot No.: 33

DUT: SM-C7100; Type: bar

Communication System: UID 0, 2450MHz FCC; Frequency: 2412 MHz; Duty Cycle: 1:1
Medium parameters used (interpolated): $f = 2412$ MHz; $\sigma = 1.929$ S/m; $\epsilon_r = 52.446$; $\rho = 1000$ kg/m³
Phantom section: Center Section

DASY Configuration:

- Probe: EX3DV4 - SN7370; ConvF(7.62, 7.62, 7.62); Calibrated: 2016-08-30;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1417; Calibrated: 2017-01-19
- Phantom: Triple Flat Phantom
- Measurement SW: DASY52, Version 52.8 (8);

802.11b Body rear 1Mbps 1ch/Area Scan (9x15x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (measured) = 0.191 W/kg



802.11b Body rear 1Mbps 1ch/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.388 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.292 W/kg

SAR(1 g) = 0.154 W/kg; SAR(10 g) = 0.078 W/kg

Maximum value of SAR (measured) = 0.218 W/kg



$$0 \text{ dB} = 0.218 \text{ W/kg} = -6.62 \text{ dBW/kg}$$