

FCC LTE REPORT

FCC Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.

Address:
129, Samsung-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Date of Issue:
August 10, 2017
Location:

HCT CO., LTD.,
74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
Report No.: HCT-R-1707-F016-1
HCT FRN: 0005866421

FCC ID: A3LSMC7100

APPLICANT: SAMSUNG Electronics Co., Ltd.

FCC Model(s): SM-C7100
Additional FCC Model(s): SM-C7108
EUT Type: Mobile Phone
FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)
FCC Rule Part(s): §27, §2

DEF Mode

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band7 (5)	2502.5 – 2567.5	4M51G7D	QPSK	0.159	22.02
		4M53W7D	16QAM	0.132	21.21
		4M51W7D	64QAM	0.109	20.36
LTE – Band7 (10)	2505.0 – 2565.0	8M97G7D	QPSK	0.156	21.92
		8M98W7D	16QAM	0.129	21.12
		9M02W7D	64QAM	0.108	20.32
LTE – Band7 (15)	2507.5 – 2562.5	13M5G7D	QPSK	0.153	21.86
		13M5W7D	16QAM	0.127	21.05
		13M5W7D	64QAM	0.107	20.29
LTE – Band7 (20)	2510.0 – 2560.0	18M0G7D	QPSK	0.157	21.95
		18M0W7D	16QAM	0.129	21.09
		18M0W7D	64QAM	0.110	20.42

ALT Mode

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band7 (5)	2502.5 – 2567.5	4M50G7D	QPSK	0.106	20.26
		4M52W7D	16QAM	0.090	19.53
		4M51W7D	64QAM	0.066	18.21
LTE – Band7 (10)	2505.0 – 2565.0	9M00G7D	QPSK	0.107	20.31
		8M98W7D	16QAM	0.090	19.55
		9M00W7D	64QAM	0.067	18.24
LTE – Band7 (15)	2507.5 – 2562.5	13M5G7D	QPSK	0.110	20.43
		13M5W7D	16QAM	0.093	19.69
		13M5W7D	64QAM	0.068	18.34
LTE – Band7 (20)	2510.0 – 2560.0	18M0G7D	QPSK	0.112	20.49
		18M0W7D	16QAM	0.094	19.75
		18M0W7D	64QAM	0.088	19.46

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)



Report prepared by : Jeong Ho Kim
Engineer of Telecommunication Testing Center



Report approved by : Jong Seok Lee
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1707-F016	August 03, 2017	- First Approval Report
HCT-R-1707-F016-1	August 10, 2017	- Added the 64QAM test data.

Table of Contents

1. GENERAL INFORMATION	6
2. INTRODUCTION	8
2.1. EUT DESCRIPTION.....	8
2.2. MEASURING INSTRUMENT CALIBRATION	8
2.3. TEST FACILITY	8
3. DESCRIPTION OF TESTS	9
3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	9
3.2 OCCUPIED BANDWIDTH.	10
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	11
3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	12
4. LIST OF TEST EQUIPMENT	13
5. MEASUREMENT UNCERTAINTY	14
6. SUMMARY OF TEST RESULTS	15
7. SAMPLE CALCULATION	16
8. TEST DATA	18
8.1 EQUIVALENT ISOTROPIC RADIATED POWER (DEF Mode)	18
8.2 EQUIVALENT ISOTROPIC RADIATED POWER (ALT Mode).....	21
8.3 RADIATED SPURIOUS EMISSIONS(DEF Mode).....	24
8.3.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)	24
8.3.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)	25
8.3.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)	26
8.3.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)	27
8.4 RADIATED SPURIOUS EMISSIONS(ALT Mode)	28
8.4.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)	28
8.4.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)	29
8.4.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)	30
8.4.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)	31
8.5 OCCUPIED BANDWIDTH	32
8.6 CONDUCTED SPURIOUS EMISSIONS	34
8.6.1 CHANNEL EDGE	36
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE(DEF Mode)	38
8.7.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)	38
8.7.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)	39
8.7.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)	40
8.7.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)	41

8.8 REQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE(ALT Mode)	42
8.8.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)	42
8.8.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)	43
8.8.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)	44
8.8.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)	45
9. TEST PLOTS: DEF Mode.....	46
10. TEST PLOTS: ALT Mode	73

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name: SAMSUNG Electronics Co., Ltd.

Address: 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

FCC ID: A3LSMC7100

Application Type: Certification

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

FCC Rule Part(s): §2 , §27

EUT Type: Mobile Phone

FCC Model(s): SM-C7100

Additional FCC Model(s): SM-C7108

Tx Frequency: 2502.5 MHz – 2567.5 MHz (LTE – Band 7): 5 MHz
2505.0 MHz – 2565.0 MHz (LTE – Band 7): 10 MHz
2507.5 MHz – 2562.5 MHz (LTE – Band 7): 15 MHz
2510.0 MHz – 2560.0 MHz (LTE – Band 7): 20 MHz

Max. RF Output Power:

DEF Mode:

Band 7 (5 MHz) : 0.159 W (QPSK) (22.02 dBm)
0.132 W (16-QAM) (21.21 dBm)
0.109 W (64-QAM) (20.36 dBm)

Band 7 (10 MHz) : 0.156 W (QPSK) (21.92 dBm)
0.129 W (16-QAM) (21.12 dBm)
0.108 W (64-QAM) (20.32 dBm)

Band 7 (15 MHz) : 0.153 W (QPSK) (21.86 dBm)
0.127 W (16-QAM) (21.05 dBm)
0.107 W (64-QAM) (20.29 dBm)

Band 7 (20 MHz) : 0.157 W (QPSK) (21.95 dBm)
0.129 W (16-QAM) (21.09 dBm)
0.110 W (64-QAM) (20.42 dBm)

ALT Mode:

Band 7 (5 MHz) : 0.106 W (QPSK) (20.26 dBm)
0.090 W (16-QAM) (19.53 dBm)
0.066 W (64-QAM) (18.21 dBm)

Band 7 (10 MHz) : 0.107 W (QPSK) (20.31 dBm)
0.090 W (16-QAM) (19.55 dBm)
0.067 W (64-QAM) (18.24 dBm)

Band 7 (15 MHz) : 0.110 W (QPSK) (20.43 dBm)
0.093 W (16-QAM) (19.69 dBm)
0.068 W (64-QAM) (18.34 dBm)

Band 7 (20 MHz) : 0.112 W (QPSK) (20.49 dBm)
0.094 W (16-QAM) (19.75 dBm)
0.088 W (64-QAM) (19.46 dBm)

Emission Designator(s):

DEF Mode:

Band 7 (5 MHz) : 4M51G7D (QPSK) / 4M53W7D (16-QAM) / 4M51W7D (64-QAM)
Band 7 (10 MHz) : 8M97G7D (QPSK) / 8M98W7D (16-QAM) / 9M02W7D (64-QAM)
Band 7 (15 MHz) : 13M5G7D (QPSK) / 13M5W7D (16-QAM) / 13M5W7D (64-QAM)
Band 7 (20 MHz) : 18M0G7D (QPSK) / 18M0W7D (16-QAM) / 18M0W7D (64-QAM)

ALT Mode:

Band 7 (5 MHz) : 4M50G7D (QPSK) / 4M52W7D (16-QAM) / 4M51W7D (64-QAM)
Band 7 (10 MHz) : 9M00G7D (QPSK) / 8M98W7D (16-QAM) / 9M00W7D (64-QAM)
Band 7 (15 MHz) : 13M5G7D (QPSK) / 13M5W7D (16-QAM) / 13M5W7D (64-QAM)
Band 7 (20 MHz) : 18M0G7D (QPSK) / 18M0W7D (16-QAM) / 18M0W7D (64-QAM)

Date(s) of Tests:

June 12, 2017 ~ August 10, 2017

2. INTRODUCTION

2.1. EUT DESCRIPTION

The SAMSUNG Electronics Co., Ltd. SM-C7100 Mobile Phone consists of LTE 7.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

Note: EIRP(Equivalent Isotropic Radiated Power)

Test Procedure

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-D-2010 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using RMS detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d(\text{dBm}) = P_g(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.


The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

Radiated spurious emissions

1. Frequency Range : 9 kHz ~ 10th Harmonics of highest channel fundamental frequency.
2. Measured distance : 30 MHz ~ 11 GHz at 3 m
11 GHz ~ 26 GHz at 1m
3. The EUT was setup to maximum output power. The 100 kHz RBW was used to scan from 30 MHz to 1 GHz. Also, the 1 MHz RBW was used to scan from 1 GHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.

3.2 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2.

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0.

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.


The EUT was setup to maximum output power. The 1 MHz RBW was used to scan from 30 MHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.

- Channel Edge Requirement : In the 1 MHz bands immediately outside and adjacent to the channel, a resolution bandwidth of at least 2 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.

.

3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-D-2010 section 2.2.2.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 100 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block .

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/24/2017	Annual	04/24/2018
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/10/2017	Annual	04/10/2018
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/10/2017	Annual	04/10/2018
Hewlett Packard	11667B / Power Splitter(DC~26.5 GHz)	11275	05/04/2017	Annual	05/04/2018
HP	E3632A/DC Power Supply	KR94907553	06/30/2017	Annual	06/30/2018
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	0093008124	03/31/2017	Annual	03/31/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	147	09/09/2016	Biennial	09/09/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna(1~18GHz)	1298	10/14/2016	Biennial	10/14/2018
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer(10Hz~26.5GHz)	MY52090906	06/01/2017	Annual	06/01/2018
Hewlett Packard	8493C/ATTENUATOR(20dB)	17280	06/22/2017	Annual	06/22/2018
REOHDE & SCHWARZ	FSV40-N/Spectrum Analyzer	101068-SZ	09/23/2016	Annual	09/23/2017
Agilent	8960 (E5515C)/ Base Station	MY48360800	10/19/2016	Annual	10/19/2017
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/06/2017	Biennial	04/06/2019
Schwarzbeck	VULB9160/ Bilog Antenna	3150	09/30/2016	Biennial	09/30/2018
Schwarzbeck	VULB9160/ Bilog Antenna	3368	10/14/2016	Biennial	10/14/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	02/15/2017	Annual	02/15/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	02/13/2017	Annual	02/13/2018
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/18/2017	Annual	07/18/2018

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	6.07

6. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(m)(4)	Band Edge / Conducted Spurious Emissions.	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS
2.1046	* Conducted Output Power	N/A		PASS
2.1055, 27.54	Frequency stability	Emission must remain in band		PASS
27.50(h)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1053, 27.53(m)(4)	Undesirable Emissions	< 40 + 10log10 (P[Watts]) at Channel edges < 43 + 10log10 (P[Watts]) between 5 and X MHz from Channel edges < 55 + 10log10 (P[Watts]) beyond X MHz beyond from Channel edges		PASS

*: See SAR Report

7. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured	Substitute	Ant. Gain	C.L	Pol.	Limit	EIRP	
	channel	Freq.(MHz)	Level(dBm)	LEVEL(dBm)	(dBi)			W	W	dBm
LTE Band7	21100	2,535.00	-22.63	13.30	10.98	2.38	V	< 2.00	0.155	21.90

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of Equivalent Isotropic Radiated Power (**EIRP**).

B. Emission Designator

QPSK Modulation

5 MHz Bandwidth

Emission Designator = 4M50G7D

LTE BW = 4.50 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry;
telecommand

16QAM Modulation

5 MHz Bandwidth

Emission Designator = 4M51W7D

LTE BW = 4.51 MHz

W = main carrier modulated in a
combination of two or more of the
following modes;
amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry;
telecommand

64QAM Modulation

5 MHz Bandwidth

Emission Designator = 4M51W7D

LTE BW = 4.51 MHz

W = main carrier modulated in a
combination of two or more of the
following modes;
amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry;
telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER (DEF Mode)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2502.5	5 MHz	QPSK	-22.54	13.14	10.95	2.35	H	< 2.00	0.149	21.74
		16-QAM	-23.32	12.36	10.95	2.35	H		0.125	20.96
		64-QAM	-24.13	11.55	10.95	2.35	H		0.104	20.15
2535.0		QPSK	-22.51	13.42	10.98	2.38	H		0.159	22.02
		16-QAM	-23.32	12.61	10.98	2.38	H		0.132	21.21
		64-QAM	-24.17	11.76	10.98	2.38	H		0.109	20.36
2567.5		QPSK	-23.26	12.64	11.01	2.39	H		0.134	21.26
		16-QAM	-24.07	11.83	11.01	2.39	H		0.111	20.45
		64-QAM	-24.87	11.03	11.01	2.39	H		0.092	19.65

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2505.0	10 MHz	QPSK	-22.56	13.13	10.95	2.35	H	< 2.00	0.149	21.73
		16-QAM	-23.33	12.36	10.95	2.35	H		0.125	20.96
		64-QAM	-24.10	11.59	10.95	2.35	H		0.104	20.19
2535.0		QPSK	-22.61	13.32	10.98	2.38	H		0.156	21.92
		16-QAM	-23.41	12.52	10.98	2.38	H		0.129	21.12
		64-QAM	-24.21	11.72	10.98	2.38	H		0.108	20.32
2565.0		QPSK	-23.39	12.57	11.00	2.39	H		0.131	21.18
		16-QAM	-24.20	11.76	11.00	2.39	H		0.109	20.37
		64-QAM	-24.98	10.98	11.00	2.39	H		0.091	19.59

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2507.5	15 MHz	QPSK	-22.53	13.16	10.96	2.36	H	< 2.00	0.150	21.76
		16-QAM	-23.24	12.45	10.96	2.36	H		0.127	21.05
		64-QAM	-24.01	11.68	10.96	2.36	H		0.107	20.28
2535.0		QPSK	-22.67	13.26	10.98	2.38	H		0.153	21.86
		16-QAM	-23.48	12.45	10.98	2.38	H		0.127	21.05
		64-QAM	-24.24	11.69	10.98	2.38	H		0.107	20.29
2562.5		QPSK	-22.97	13.05	11.00	2.39	H		0.147	21.66
		16-QAM	-23.77	12.25	11.00	2.39	H		0.122	20.86
		64-QAM	-24.59	11.43	11.00	2.39	H		0.101	20.04

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2510.0	20 MHz	QPSK	-22.48	13.21	10.96	2.36	H	< 2.00	0.152	21.81
		16-QAM	-23.26	12.43	10.96	2.36	H		0.127	21.03
		64-QAM	-23.90	11.79	10.96	2.36	H		0.109	20.39
2535.0		QPSK	-22.58	13.35	10.98	2.38	H		0.157	21.95
		16-QAM	-23.44	12.49	10.98	2.38	H		0.129	21.09
		64-QAM	-24.11	11.82	10.98	2.38	H		0.110	20.42
2560.0		QPSK	-22.99	13.09	11.00	2.39	H		0.148	21.70
		16-QAM	-23.80	12.28	11.00	2.39	H		0.123	20.89
		64-QAM	-24.58	11.50	11.00	2.39	H		0.103	20.11

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Methodaccording to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For 5 MHz, 10MHz BW signals, RBW = 1-5% of the OBW, not to exceed 1MHz, VBW $\geq 3 \times$ RBW, Detector = RMS. A Horn antenna was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is x plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

8.2 EQUIVALENT ISOTROPIC RADIATED POWER (ALT Mode)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2502.5	5 MHz	QPSK	-24.02	11.66	10.95	2.35	H	< 2.00	0.106	20.26
		16-QAM	-24.75	10.93	10.95	2.35	H		0.090	19.53
		64-QAM	-26.08	9.60	10.95	2.35	H		0.066	18.20
2535.0		QPSK	-24.37	11.56	10.98	2.38	H		0.104	20.16
		16-QAM	-25.13	10.80	10.98	2.38	H		0.087	19.40
		64-QAM	-26.32	9.61	10.98	2.38	H		0.066	18.21
2567.5		QPSK	-25.15	10.75	11.01	2.39	H		0.086	19.37
		16-QAM	-25.92	9.98	11.01	2.39	H		0.072	18.60
		64-QAM	-27.22	8.68	11.01	2.39	H		0.054	17.30

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2505.0	10 MHz	QPSK	-23.98	11.71	10.95	2.35	H	< 2.00	0.107	20.31
		16-QAM	-24.74	10.95	10.95	2.35	H		0.090	19.55
		64-QAM	-26.05	9.64	10.95	2.35	H		0.067	18.24
2535.0		QPSK	-24.35	11.58	10.98	2.38	H		0.104	20.18
		16-QAM	-25.13	10.80	10.98	2.38	H		0.087	19.40
		64-QAM	-26.36	9.57	10.98	2.38	H		0.066	18.17
2565.0		QPSK	-25.23	10.73	11.00	2.39	H		0.086	19.34
		16-QAM	-26.04	9.92	11.00	2.39	H		0.071	18.53
		64-QAM	-27.33	8.63	11.00	2.39	H		0.053	17.24

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2507.5	15 MHz	QPSK	-23.86	11.83	10.96	2.36	H	< 2.00	0.110	20.43
		16-QAM	-24.60	11.09	10.96	2.36	H		0.093	19.69
		64-QAM	-25.95	9.74	10.96	2.36	H		0.068	18.34
2535.0		QPSK	-24.33	11.60	10.98	2.38	H		0.105	20.20
		16-QAM	-25.10	10.83	10.98	2.38	H		0.088	19.43
		64-QAM	-26.35	9.58	10.98	2.38	H		0.066	18.18
2562.5		QPSK	-24.79	11.23	11.00	2.39	H		0.096	19.84
		16-QAM	-25.60	10.42	11.00	2.39	H		0.080	19.03
		64-QAM	-26.92	9.10	11.00	2.39	H		0.059	17.71

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2510.0	20 MHz	QPSK	-23.80	11.89	10.96	2.36	H	< 2.00	0.112	20.49
		16-QAM	-24.23	11.46	10.96	2.36	H		0.101	20.06
		64-QAM	-24.83	10.86	10.96	2.36	H		0.088	19.46
2535.0		QPSK	-24.54	11.39	10.98	2.38	H		0.100	19.99
		16-QAM	-25.02	10.91	10.98	2.38	H		0.089	19.51
		64-QAM	-25.60	10.33	10.98	2.38	H		0.078	18.93
2560.0		QPSK	-25.86	10.22	11.00	2.39	H		0.076	18.83
		16-QAM	-26.19	9.89	11.00	2.39	H		0.071	18.50
		64-QAM	-26.85	9.23	11.00	2.39	H		0.061	17.84

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Methodaccording to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For 5 MHz, 10MHz BW signals, RBW = 1-5% of the OBW, not to exceed 1MHz, VBW $\geq 3 \times$ RBW, Detector = RMS. A Horn antenna was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is x plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

8.3 RADIATED SPURIOUS EMISSIONS(DEF Mode)

8.3.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2535.00 MHz
- MEASURED OUTPUT POWER: 22.02 dBm = 0.159 W
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10} (W) =$ 47.02 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20775 (2502.5)	5,005.00	-45.12	12.57	-59.16	3.40	H	-49.99	72.01	Peak
	7,507.50	-46.90	11.71	-55.28	4.18	H	-47.75	69.77	Peak
	10,010.00	-49.50	11.01	-53.34	5.02	H	-47.35	69.37	Peak
21100 (2535.0)	5,070.00	-47.26	12.67	-60.80	3.43	V	-51.56	73.58	Peak
	7,605.00	-47.72	11.64	-56.67	4.29	V	-49.32	71.34	Peak
	10,140.00	-49.82	10.94	-54.01	4.99	H	-48.06	70.08	Peak
21425 (2567.5)	5,135.00	-45.86	12.75	-57.39	3.44	H	-48.08	70.10	Peak
	7,702.50	-48.30	11.56	-57.08	4.27	H	-49.79	71.81	Peak
	10,270.00	-49.11	10.87	-54.41	4.98	H	-48.52	70.54	Peak

- NOTES: 1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.3.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2535.00 MHz
- MEASURED OUTPUT POWER: 21.92 dBm = 0.156 W
- MODULATION SIGNAL: 10 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 46.92 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20800 (2505.0)	5,010.00	-46.39	12.58	-60.06	3.40	H	-50.88	72.80	Peak
	7,515.00	-47.01	11.70	-55.39	4.12	H	-47.81	69.73	Peak
	10,020.00	-50.91	11.01	-54.58	5.04	H	-48.61	70.53	Peak
21100 (2535.0)4	5,070.00	-47.30	12.67	-60.84	3.43	H	-51.60	73.52	Peak
	7,605.00	-46.90	11.64	-55.85	4.29	H	-48.50	70.42	Peak
	10,140.00	-50.85	10.94	-55.04	4.99	H	-49.09	71.01	Peak
21400 (2565.0)	5,130.00	-48.53	12.76	-59.98	3.44	H	-50.66	72.58	Peak
	7,695.00	-48.69	11.57	-57.33	4.26	H	-50.02	71.94	Peak
	10,260.00	-50.62	10.87	-55.74	5.00	H	-49.87	71.79	Peak

- NOTES: 1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.3.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2535.00 MHz
- MEASURED OUTPUT POWER: 21.86 dBm = 0.153 W
- MODULATION SIGNAL: 15 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 46.86 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20825 (2507.5)	5,015.00	-46.23	12.59	-58.86	3.40	H	-49.67	71.53	Peak
	7,522.50	-47.62	11.70	-55.84	4.09	H	-48.23	70.09	Peak
	10,030.00	-51.37	11.00	-55.12	5.16	H	-49.28	71.14	Peak
21100 (2535.0)	5,070.00	-47.86	12.67	-61.40	3.43	H	-52.16	74.02	Peak
	7,605.00	-47.19	11.64	-56.14	4.29	H	-48.79	70.65	Peak
	10,140.00	-51.05	10.94	-55.24	4.99	H	-49.29	71.15	Peak
21375 (2562.5)	5,125.00	-49.82	12.75	-61.52	3.44	H	-52.21	74.07	Peak
	7,687.50	-45.84	11.57	-54.31	4.26	H	-47.00	68.86	Peak
	10,250.00	-49.44	10.88	-53.99	5.04	H	-48.15	70.01	Peak

- NOTES:
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.3.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2535.00 MHz
- MEASURED OUTPUT POWER: 21.95 dBm = 0.157 W
- MODULATION SIGNAL: 20 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 46.95 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20850 (2510.0)	└ 5,020.00	-46.03	12.60	-58.64	3.40	H	-49.44	71.39	Peak
	7,530.00	-47.47	11.69	-55.47	4.08	H	-47.86	69.81	Peak
	10,040.00	-50.33	11.00	-55.18	5.20	H	-49.38	71.33	Peak
21100 (2535.0)	5,070.00	-46.79	12.67	-60.33	3.43	H	-51.09	73.04	Peak
	7,605.00	-46.32	11.64	-55.27	4.29	H	-47.92	69.87	Peak
	10,140.00	-50.81	10.94	-55.00	4.99	H	-49.05	71.00	Peak
21350 (2560.0)	5,120.00	-48.09	12.75	-60.07	3.44	H	-50.76	72.71	Peak
	7,680.00	-45.95	11.58	-54.27	4.26	H	-46.95	68.90	Peak
	10,240.00	-48.23	10.88	-52.55	5.06	H	-46.73	68.68	Peak

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.4 RADIATED SPURIOUS EMISSIONS(ALT Mode)

8.4.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2502.50 MHz
- MEASURED OUTPUT POWER: 20.26 dBm = 0.106 W
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 45.26 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20775 (2502.5)	5,005.00	-47.62	12.57	-61.66	3.40	V	-52.49	72.75	Peak
	7,507.50	-46.86	11.71	-55.24	4.18	H	-47.71	67.97	Peak
	10,010.00	-50.28	11.01	-54.12	5.02	V	-48.13	68.39	Peak
21100 (2535.0)	5,070.00	-47.79	12.67	-61.33	3.43	V	-52.09	72.35	Peak
	7,605.00	-45.83	11.64	-54.78	4.29	H	-47.43	67.69	Peak
	10,140.00	-49.99	10.94	-54.18	4.99	H	-48.23	68.49	Peak
21425 (2567.5)	5,135.00	-47.48	12.75	-59.01	3.44	V	-49.70	69.96	Peak
	7,702.50	-49.91	11.56	-58.69	4.27	H	-51.40	71.66	Peak
	10,270.00	-48.78	10.87	-54.08	4.98	H	-48.19	68.45	Peak

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.4.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2505.00 MHz
- MEASURED OUTPUT POWER: 20.31 dBm = 0.107 W
- MODULATION SIGNAL: 10 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 45.31 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20800 (2505.0)	5,010.00	-49.57	12.58	-63.24	3.40	V	-54.06	74.37	Peak
	7,515.00	-47.23	11.70	-55.61	4.12	H	-48.03	68.34	Peak
	10,020.00	-52.53	11.01	-56.20	5.04	V	-50.23	70.54	Peak
21100 (2535.0)	5,070.00	-50.11	12.67	-63.65	3.43	V	-54.41	74.72	Peak
	7,605.00	-46.41	11.64	-55.36	4.29	V	-48.01	68.32	Peak
	10,140.00	-55.46	10.94	-59.65	4.99	H	-53.70	74.01	Peak
21400 (2565.0)	5,130.00	-49.98	12.76	-61.43	3.44	V	-52.11	72.42	Peak
	7,695.00	-45.55	11.57	-54.19	4.26	H	-46.88	67.19	Peak
	10,260.00	-51.82	10.87	-56.94	5.00	H	-51.07	71.38	Peak

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.4.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2507.50 MHz
- MEASURED OUTPUT POWER: 20.43 dBm = 0.110 W
- MODULATION SIGNAL: 15 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 45.43 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20825 (2507.5)	5,015.00	-48.92	12.59	-61.55	3.40	V	-52.36	72.79	Peak
	7,522.50	-45.62	11.70	-53.84	4.09	H	-46.23	66.66	Peak
	10,030.00	-55.57	11.00	-59.32	5.16	V	-53.48	73.91	Peak
21100 (2535.0)	5,070.00	-50.46	12.67	-64.00	3.43	V	-54.76	75.19	Peak
	7,605.00	-46.15	11.64	-55.10	4.29	H	-47.75	68.18	Peak
	10,140.00	-51.28	10.94	-55.47	4.99	V	-49.52	69.95	Peak
21375 (2562.5)	5,125.00	-51.45	12.75	-63.15	3.44	V	-53.84	74.27	Peak
	7,687.50	-44.46	11.57	-52.93	4.26	H	-45.62	66.05	Peak
	10,250.00	-50.67	10.88	-55.22	5.04	H	-49.38	69.81	Peak

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.4.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 7 LTE)

- OPERATING FREQUENCY : 2510.00 MHz
- MEASURED OUTPUT POWER: 20.49 dBm = 0.112 W
- MODULATION SIGNAL: 20 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 45.49 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc	Detector
20850 (2510.0)	5,020.00	-49.31	12.60	-61.92	3.40	V	-52.72	73.21	Peak
	7,530.00	-47.13	11.69	-55.13	4.08	V	-47.52	68.01	Peak
	10,040.00	-54.30	11.00	-59.15	5.20	V	-53.35	73.84	Peak
21100 (2535.0)	5,070.00	-51.86	12.67	-65.40	3.43	V	-56.16	76.65	Peak
	7,605.00	-43.95	11.64	-52.90	4.29	H	-45.55	66.04	Peak
	10,140.00	-52.88	10.94	-57.07	4.99	H	-51.12	71.61	Peak
21350 (2560.0)	5,120.00	-50.29	12.75	-62.27	3.44	H	-52.96	73.45	Peak
	7,680.00	-44.59	11.58	-52.91	4.26	V	-45.59	66.08	Peak
	10,240.00	-50.89	10.88	-55.21	5.06	H	-49.39	69.88	Peak

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meter by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM, 64QAM and QPSK modulations.
- The worst case data are reported in the table above.

8.5 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
7	5 MHz	2535.0	QPSK	25	0	4.5093
			16-QAM	25	0	4.5340
			64-QAM	25	0	4.5071
	10 MHz		QPSK	50	0	8.9743
			16-QAM	50	0	8.9776
			64-QAM	50	0	9.0170
	15 MHz		QPSK	75	0	13.499
			16-QAM	75	0	13.514
			64-QAM	75	0	13.485
	20 MHz		QPSK	100	0	17.974
			16-QAM	100	0	17.951
			64-QAM	100	0	17.999

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 47 ~ 52.
2. DEF Mode

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
7	5 MHz		QPSK	25	0	4.5038
			16-QAM	25	0	4.5212
			64-QAM	25	0	4.5143
	10 MHz		QPSK	50	0	9.0020
			16-QAM	50	0	8.9814
			64-QAM	50	0	9.0020
	15 MHz		QPSK	75	0	13.493
			16-QAM	75	0	13.486
			64-QAM	75	0	13.523
	20 MHz		QPSK	100	0	18.008
			16-QAM	100	0	17.993
			64-QAM	100	0	17.980

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 74 ~ 79.
2. ALT Mode

8.6 CONDUCTED SPURIOUS EMISSIONS

■ FACTORS FOR FREQUENCY

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20	30.131

Note:

Factor(dB) = Cable Loss + Attenuator + Power Splitter

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
7	5	2502.5	26.1716	30.131	-76.136	-46.005	-25.00
		2535.0	26.1312	30.131	-76.559	-46.428	
		2567.5	26.1110	30.131	-76.422	-46.291	
	10	2505.0	26.1399	30.131	-76.210	-46.079	
		2535.0	26.1259	30.131	-76.398	-46.267	
		2565.0	26.1428	30.131	-76.610	-46.479	
	15	2507.5	26.1510	30.131	-76.394	-46.263	
		2535.0	26.1271	30.131	-76.593	-46.462	
		2562.5	26.1452	30.131	-76.447	-46.316	
	20	2510.0	26.1370	30.131	-76.362	-46.231	
		2535.0	26.1461	30.131	-75.895	-45.764	
		2560.0	26.1028	30.131	-76.593	-46.462	

Note:

1. We are performed 16QAM, 64QAM and QPSK modulations. The worst case data is QPSK modulation.
2. Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Plots of the EUT's Conducted Spurious Emissions are shown Page 61 ~ 72.
5. DEF Mode

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
7	5	2502.5	26.1362	30.131	-76.558	-46.427	-25.00
		2535.0	26.1502	30.131	-76.508	-46.377	
		2567.5	26.1337	30.131	-76.560	-46.429	
	10	2505.0	26.1374	30.131	-76.409	-46.278	
		2535.0	26.1407	30.131	-76.536	-46.405	
		2565.0	25.8342	30.131	-76.518	-46.387	
	15	2507.5	26.4361	30.131	-76.534	-46.403	
		2535.0	26.1514	30.131	-76.419	-46.288	
		2562.5	26.1696	30.131	-76.441	-46.310	
	20	2510.0	26.1774	30.131	-76.525	-46.394	
		2535.0	26.1725	30.131	-76.492	-46.361	
		2560.0	26.1642	30.131	-76.496	-46.365	

Note:

1. We are performed 16QAM, 64QAM and QPSK modulations. The worst case data is QPSK modulation.
2. Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Plots of the EUT's Conducted Spurious Emissions are shown Page 88 ~ 99.
5. ALT Mode

8.6.1 CHANNEL EDGE

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1MHz)		2 496 MHz ~ 2 499 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	2 490.5 MHz ~ 2 496 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Below 2 490.5 MHz	Above (C.E + X MHz)
			Lower	Upper	Lower	Upper	Lower	Upper	Lower	Upper
5MHz (QPSK)	2502.5	25 / 0	-24.53	-23.96	-21.49	-21.52	-29.79	-31.63	-45.56	-34.59
10MHz (QPSK)	2505.0	50 / 0	-27.56	-26.89	-23.85	-22.54	-26.76	-26.30	-35.71	-33.99
15MHz (QPSK)	2507.5	75 / 0	-28.48	-27.47	-25.33	-23.98	-27.61	-25.96	-32.98	-36.24
20MHz (QPSK)	2510.0	100 / 0	-29.08	-27.95	-26.19	-24.80	-27.90	-26.15	-31.88	-36.92
Limit			-10.0		-10.0		-13.0		-25.0	

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
			Lower	Upper	Lower	Upper
5MHz (QPSK)	2535.0	25 / 0	-24.43	-24.31	-22.25	-22.65
	2567.5	25 / 0	-22.57	-22.85	-20.28	-21.56
10MHz (QPSK)	2535.0	50 / 0	-27.52	-27.85	-24.09	-24.26
	2565.0	50 / 0	-25.84	-27.29	-22.17	-23.94
15MHz (QPSK)	2535.0	75 / 0	-28.54	-28.79	-25.84	-25.55
	2562.5	75 / 0	-27.27	-28.78	-24.09	-25.54
20MHz (QPSK)	2535.0	100 / 0	-29.42	-28.94	-26.61	-26.03
	2560.0	100 / 0	-28.52	-29.93	-25.53	-27.20
Limit			-10.0		-10.0	

Band Width (Modulation)	Frequency (MHz)	Resource Block Size	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
			Lower	Upper	Lower	Upper
5MHz (QPSK)	2535.0	25 / 0	-33.23	-33.05	-36.30	-36.37
	2567.5	25 / 0	-32.40	-33.81	-35.39	-37.15
10MHz (QPSK)	2535.0	50 / 0	-28.53	-28.13	-36.08	-35.43
	2565.0	50 / 0	-26.35	-28.28	-34.48	-36.60
15MHz (QPSK)	2535.0	75 / 0	-28.42	-27.50	-37.69	-37.04
	2562.5	75 / 0	-26.35	-28.15	-36.66	-41.60
20MHz (QPSK)	2535.0	100 / 0	-28.36	-27.43	-38.89	-38.88
	2560.0	100 / 0	-27.41	-29.12	-38.30	-47.69
Limit			-13.0		-25.0	

Note:

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. All of RB size has been tested for channel edge, with the Full RB configuration observed as the worst case
5. Plots of the EUT's Band Edge are shown Page 53 ~ 60.
6. DEF Mode

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E $\pm$ 1MHz)		2 496 MHz ~ 2 499 MHz	(C.E + 1 MHz) ~ (C.E + 5 MHz)	2 490.5 MHz ~ 2 496 MHz	(C.E + 5 MHz) ~ (C.E + X MHz)	Below 2 490.5 MHz	Above (C.E + X MHz)
			Lower	Upper	Lower	Upper	Lower	Upper	Lower	Upper
5MHz (QPSK)	2502.5	25 / 0	-25.44	-25.15	-24.28	-24.20	-32.91	-34.52	-46.51	-37.15
10MHz (QPSK)	2505.0	50 / 0	-29.48	-28.05	-26.64	-25.53	-30.09	-28.65	-38.34	-36.55
15MHz (QPSK)	2507.5	75 / 0	-30.17	-29.20	-27.28	-25.82	-29.87	-27.67	-35.60	-38.06
20MHz (QPSK)	2510.0	100 / 0	-30.47	-29.00	-27.64	-26.11	-29.30	-27.28	-33.34	-38.42
Limit			-10.0		-10.0		-13.0		-25.0	

Band Width (Modulation)	Frequency (MHz)	RB Size / Offset	C.E ~ (C.E $\pm$ 1MHz)		(C.E $\pm$ 1 MHz) ~ (C.E $\pm$ 5 MHz)	
			Lower	Upper	Lower	Upper
5MHz (QPSK)	2535.0	25 / 0	-25.50	-25.67	-24.37	-24.84
	2567.5	25 / 0	-23.23	-23.95	-21.23	-22.85
10MHz (QPSK)	2535.0	50 / 0	-29.16	-29.43	-26.44	-26.45
	2565.0	50 / 0	-26.65	-28.40	-22.72	-24.90
15MHz (QPSK)	2535.0	75 / 0	-30.04	-30.22	-27.84	-27.49
	2562.5	75 / 0	-27.15	-29.52	-24.09	-26.26
20MHz (QPSK)	2535.0	100 / 0	-30.66	-30.14	-27.92	-27.38
	2560.0	100 / 0	-28.88	-30.99	-26.25	-28.11
Limit			-10.0		-10.0	

Band Width (Modulation)	Frequency (MHz)	Resource Block Size	(C.E $\pm$ 5 MHz) ~ (C.E $\pm$ X MHz)		Above (C.E $\pm$ X MHz)	
			Lower	Upper	Lower	Upper
5MHz (QPSK)	2535.0	25 / 0	-34.67	-35.19	-37.66	-38.30
	2567.5	25 / 0	-33.39	-35.06	-36.31	-38.02
10MHz (QPSK)	2535.0	50 / 0	-30.68	-30.23	-37.00	-37.43
	2565.0	50 / 0	-26.44	-29.15	-35.13	-37.38
15MHz (QPSK)	2535.0	75 / 0	-30.28	-29.38	-39.42	-38.57
	2562.5	75 / 0	-26.26	-28.83	-37.13	-42.94
20MHz (QPSK)	2535.0	100 / 0	-29.81	-28.60	-40.36	-40.54
	2560.0	100 / 0	-27.99	-30.28	-39.10	-48.61
Limit			-13.0		-25.0	

Note:


1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. All of RB size has been tested for channel edge, with the Full RB configuration observed as the worst case
5. Plots of the EUT's Band Edge are shown Page 80 ~ 87.
6. ALT Mode

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE(DEF Mode)

8.7.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 007	0.0	0.000 000	0.000
100%		-30	2535 000 011	3.7	0.000 000	0.001
100%		-20	2535 000 013	6.1	0.000 000	0.002
100%		-10	2535 000 011	3.9	0.000 000	0.002
100%		0	2535 000 012	4.3	0.000 000	0.002
100%		+10	2535 000 011	3.8	0.000 000	0.001
100%		+30	2535 000 015	7.5	0.000 000	0.003
100%		+40	2535 000 010	3.2	0.000 000	0.001
100%		+50	2535 000 010	2.8	0.000 000	0.001
Batt. Endpoint	3.60	+20	2535 000 002	-5.6	0.000 000	-0.002



8.7.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2534 999 992	0.0	0.000 000	0.000
100%		-30	2534 999 998	6.2	0.000 000	0.002
100%		-20	2534 999 987	-4.3	0.000 000	-0.002
100%		-10	2534 999 997	5.1	0.000 000	0.002
100%		0	2534 999 985	-6.2	0.000 000	-0.002
100%		+10	2534 999 994	2.1	0.000 000	0.001
100%		+30	2534 999 988	-4.1	0.000 000	-0.002
100%		+40	2534 999 998	6.0	0.000 000	0.002
100%		+50	2534 999 995	3.5	0.000 000	0.001
Batt. Endpoint	3.60	+20	2534 999 997	5.0	0.000 000	0.002



8.7.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 005	0.0	0.000 000	0.000
100%		-30	2535 000 013	8.0	0.000 000	0.003
100%		-20	2535 000 010	5.4	0.000 000	0.002
100%		-10	2535 000 011	6.6	0.000 000	0.003
100%		0	2535 000 010	5.4	0.000 000	0.002
100%		+10	2535 000 010	5.0	0.000 000	0.002
100%		+30	2535 000 012	7.1	0.000 000	0.003
100%		+40	2535 000 008	3.9	0.000 000	0.002
100%		+50	2535 000 008	3.8	0.000 000	0.001
Batt. Endpoint	3.60	+20	2535 000 000	-4.1	0.000 000	-0.002



8.7.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 005	0.0	0.000 000	0.000
100%		-30	2535 000 013	7.6	0.000 000	0.003
100%		-20	2535 000 012	6.4	0.000 000	0.003
100%		-10	2535 000 014	8.5	0.000 000	0.003
100%		0	2535 000 013	7.3	0.000 000	0.003
100%		+10	2535 000 011	5.7	0.000 000	0.002
100%		+30	2535 000 013	7.9	0.000 000	0.003
100%		+40	2535 000 013	7.6	0.000 000	0.003
100%		+50	2535 000 012	6.4	0.000 000	0.003
Batt. Endpoint	3.60	+20	2535 000 016	10.8	0.000 000	0.004




8.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE(ALT Mode)

8.8.1 FREQUENCY STABILITY (5 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (℃)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 005	0.0	0.000 000	0.000
100%		-30	2535 000 013	8.2	0.000 000	0.003
100%		-20	2535 000 009	4.0	0.000 000	0.002
100%		-10	2535 000 012	7.3	0.000 000	0.003
100%		0	2535 000 014	8.9	0.000 000	0.004
100%		+10	2535 000 013	8.0	0.000 000	0.003
100%		+30	2535 000 012	6.7	0.000 000	0.003
100%		+40	2535 000 015	10.5	0.000 000	0.004
100%		+50	2535 000 012	7.1	0.000 000	0.003
Batt. Endpoint	3.60	+20	2535 000 011	6.5	0.000 000	0.003



8.8.2 FREQUENCY STABILITY (10 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 007	0.0	0.000 000	0.000
100%		-30	2535 000 013	6.2	0.000 000	0.002
100%		-20	2535 000 013	6.1	0.000 000	0.002
100%		-10	2535 000 016	8.7	0.000 000	0.003
100%		0	2535 000 002	-4.9	0.000 000	-0.002
100%		+10	2535 000 015	7.8	0.000 000	0.003
100%		+30	2535 000 014	6.6	0.000 000	0.003
100%		+40	2535 000 016	9.1	0.000 000	0.004
100%		+50	2535 000 013	6.4	0.000 000	0.003
Batt. Endpoint	3.60	+20	2535 000 012	4.7	0.000 000	0.002



8.8.3 FREQUENCY STABILITY (15 MHz Band 7 LTE)

- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2534 999 996	0.0	0.000 000	0.000
100%		-30	2535 000 002	6.5	0.000 000	0.003
100%		-20	2534 999 991	-4.6	0.000 000	-0.002
100%		-10	2535 000 003	7.3	0.000 000	0.003
100%		0	2535 000 000	4.3	0.000 000	0.002
100%		+10	2534 999 988	-7.4	0.000 000	-0.003
100%		+30	2535 000 001	5.4	0.000 000	0.002
100%		+40	2534 999 991	-4.5	0.000 000	-0.002
100%		+50	2535 000 002	6.4	0.000 000	0.003
Batt. Endpoint	3.60	+20	2535 000 000	4.9	0.000 000	0.002



8.8.4 FREQUENCY STABILITY (20 MHz Band 7 LTE)


- OPERATING FREQUENCY: 2,535,000,000 Hz
- CHANNEL: 21100 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2535 000 005	0.0	0.000 000	0.000
100%		-30	2535 000 000	-5.4	0.000 000	-0.002
100%		-20	2535 000 000	-4.7	0.000 000	-0.002
100%		-10	2534 999 999	-6.0	0.000 000	-0.002
100%		0	2535 000 001	-4.3	0.000 000	-0.002
100%		+10	2535 000 009	4.3	0.000 000	0.002
100%		+30	2535 000 003	-2.6	0.000 000	-0.001
100%		+40	2535 000 010	4.7	0.000 000	0.002
100%		+50	2535 000 009	4.2	0.000 000	0.002
Batt. Endpoint	3.60	+20	2535 000 000	-5.2	0.000 000	-0.002




9. TEST PLOTS: DEF Mode


BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 QPSK RB 25)




BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 16-QAM RB 25)




BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 64-QAM RB 25)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 16-QAM RB 50)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 64-QAM RB 50)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 QPSK RB 75)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 16-QAM RB 75)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 64-QAM RB 75)




BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 QPSK RB 100)



BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 16-QAM RB 100)




BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 64-QAM RB 100)




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK RB25)-1




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK RB25)-2



BAND7. Mid Channel Edge Plot (5MHz Ch.21100 QPSK RB 25)



BAND7. High Channel Edge Plot (5MHz Ch.21425 QPSK RB 25)




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK RB50)-1




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK RB50)-2



BAND7. Mid Channel Edge Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. High Channel Edge Plot (10MHz Ch.21400 QPSK RB 50)




BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK RB75)-1



BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK RB75)-2



BAND7. Mid Channel Edge Plot (15MHz Ch.21100 QPSK RB 75)



BAND7. High Channel Edge Plot (15MHz Ch.21375 QPSK RB 75)




BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK RB100)-1



BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK RB100)-2




BAND7. Mid Channel Edge Plot (20MHz Ch.21100 QPSK RB 100)



BAND7. High Channel Edge Plot (20MHz Ch.21350 QPSK RB 100)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.20775 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.20775 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21425 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.21425 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.20800 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (10MHz Ch.20800 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (10MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21400 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (10MHz Ch.21400 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.20825 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (15MHz Ch.20825 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (15MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21375 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.20850 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.20850 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 1 (20MHz Ch.21350 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (20MHz Ch.21350 QPSK RB 1, Offset 0)




10. TEST PLOTS: ALT Mode


BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 QPSK RB 25)




BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 16-QAM RB 25)




BAND7. Occupied Bandwidth Plot (5MHz Ch.21100 64-QAM RB 25)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 QPSK RB 50)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 16-QAM RB 50)




BAND7. Occupied Bandwidth Plot (10MHz Ch.21100 64-QAM RB 50)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 QPSK RB 75)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 16-QAM RB 75)




BAND7. Occupied Bandwidth Plot (15MHz Ch.21100 64-QAM RB 75)




BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 QPSK RB 100)



BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 16-QAM RB 100)



BAND7. Occupied Bandwidth Plot (20MHz Ch.21100 64-QAM RB 100)




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK_RB25_Offset 0)-1




BAND7. Low Channel Edge Plot (5MHz Ch.20775 QPSK_RB25_Offset 0)-2



BAND7. Mid Channel Edge Plot (5MHz Ch.21100 QPSK_RB25_Offset 0)



BAND7. High Channel Edge Plot (5MHz Ch.21425 QPSK_RB25_Offset 0)




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK_RB50_Offset 0)-1




BAND7. Low Channel Edge Plot (10MHz Ch.20800 QPSK_RB50_Offset 0)-2



BAND7. Mid Channel Edge Plot (10MHz Ch.21100 QPSK_RB50_Offset 0)



BAND7. High Channel Edge Plot (10MHz Ch.21400 QPSK_RB50_Offset 0)




BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK_RB75_Offset 0)-1




BAND7. Low Channel Edge Plot (15MHz Ch.20825 QPSK_RB75_Offset 0)-2



BAND7. Mid Channel Edge Plot (15MHz Ch.21100 QPSK_RB75_Offset 0)




BAND7. High Channel Edge Plot (15MHz Ch.21375 QPSK_RB75_Offset 0)




BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK_RB100_Offset 0)-1



BAND7. Low Channel Edge Plot (20MHz Ch.20850 QPSK_RB100_Offset 0)-2




BAND7. Mid Channel Edge Plot (20MHz Ch.21100 QPSK_RB100_Offset 0)



BAND7. High Channel Edge Plot (20MHz Ch.21350 QPSK_RB100_Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.20775 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.20775 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (5MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (5MHz Ch.21425 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (5MHz Ch.21425 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.20800 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (10MHz Ch.20800 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (10MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (10MHz Ch.21400 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (10MHz Ch.21400 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.20825 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (15MHz Ch.20825 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (15MHz Ch.21100 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (15MHz Ch.21375 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.20850 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 2 (20MHz Ch.20850 QPSK RB 1, Offset 0)




BAND7. Conducted Spurious Plot 1 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21100 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 1 (20MHz Ch.21350 QPSK RB 1, Offset 0)



BAND7. Conducted Spurious Plot 2 (20MHz Ch.21350 QPSK RB 1, Offset 0)

