



FCC CFR47 PART 15 SUBPART C

Bluetooth Low Energy

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac , ANT+ and NFC

MODEL NUMBER : SM-C900F/DS

FCC ID: A3LSMC900F

REPORT NUMBER: 4787745030-E2V1

ISSUE DATE: JAN 06 , 2017

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI,
GYEONGGI-DO, 16677, KOREA

Prepared by
UL Korea, Ltd. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	01/06/17	Initial issue	Junwhan Lee

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION.....	6
4.3. MEASUREMENT UNCERTAINTY	6
5. EQUIPMENT UNDER TEST	7
5.1. DESCRIPTION OF EUT.....	7
5.2. MAXIMUM OUTPUT POWER.....	7
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	7
5.4. WORST-CASE CONFIGURATION AND MODE.....	7
5.5. DESCRIPTION OF TEST SETUP	8
6. TEST AND MEASUREMENT EQUIPMENT	10
7. MEASUREMENT METHODS.....	11
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	11
8.1. ON TIME AND DUTY CYCLE RESULTS.....	11
9. SUMMARY TABLE	12
10. ANTENNA PORT TEST RESULTS.....	13
10.1. 6 dB BANDWIDTH.....	13
10.2. 99% BANDWIDTH.....	15
10.3. OUTPUT POWER.....	17
10.4. AVERAGE POWER.....	19
10.5. PSD.....	20
10.6. CONDUCTED SPURIOUS EMISSIONS	22
11. RADIATED TEST RESULTS.....	26
11.1. LIMITS AND PROCEDURE.....	26
11.2. TRANSMITTER ABOVE 1 GHz.....	28
11.3. WORST-CASE BELOW 1 GHz	38
12. AC POWER LINE CONDUCTED EMISSIONS	40

13. SETUP PHOTOS45

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac , ANT+ and NFC

MODEL NUMBER: SM-C900F/DS

SERIAL NUMBER: R38HC075C7W, 2651b8f6 (RADIATED);
R38HC075DFM (CONDUCTED)

DATE TESTED: DEC 19, 2016 - JAN 03, 2017

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:



CY Choi
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:



Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, KDB 558074 D01 v03r05 and ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro	
☐	Chamber 1
☒	Chamber 2

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at <http://www.iasonline.org/PDF/TL/TL-637.pdf>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamplifier Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.32 dB
Radiated Disturbance, Below 1GHz	4.14 dB
Radiated Disturbance, Above 1 GHz	5.97 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac , ANT+ and NFC.
This test report addresses the DTS (BLE) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2402 - 2480	BLE	Peak	0.456	1.11
		Average	-0.043	0.99

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of 1.12 dBi

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Charger	SAMSUNG	EP-TA20IWE	R37FC5T1661SE3	N/A
Data Cable	SAMSUNG	DP-DN930CWE	N/A	N/A
Earphone	SAMSUNG	EHS64AVFWE	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	C Type USB	Shielded	0.8m	N/A
2	Audio	2	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is a stand-alone unit during the tests.
Test software in hidden menu exercised the EUT to enable BLE mode.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	S/N	Cal Due
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	10-14-18
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	04-25-17
Antenna, Horn, 18 GHz	ETS	3115	00167211	10-14-18
Antenna, Horn, 18 GHz	ETS	3115	00161451	05-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168724	06-17-17
Antenna, Horn, 18 GHz	ETS	3117	00168717	06-17-17
Antenna, Horn, 40 GHz	ETS	3116C	00166155	11-30-17
Antenna, Horn, 40 GHz	ETS	3116C-PA	00168841	12-15-17
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-17-17
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-16-17
Preamplifier	ETS	3115-PA	00167475	08-17-17
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-16-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-17-17
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-16-17
Average Power Sensor	R&S	NRP-Z91	102681	08-16-17
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-17-17
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-16-17
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-16-17
Attenuator / Switch driver	HP	11713A	3748A04272	N/A
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-17-17
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-16-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-17-17
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-16-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	009	08-17-17
High Pass Filter 6GHz	Micro-Tronics	HPM17542	016	08-16-17
LISN	R&S	ENV-216	101836	08-16-17
LISN	R&S	ENV-216	101837	08-16-17
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	11-25-17

7. MEASUREMENT METHODS

KDB 558074 D01 DTS Meas Guidance v03r05: Measurement Procedure §9.1.1 is used for peak power and §10.2 PKPSD is used for power spectral density.

Unwanted emissions within Restricted Bands are measured using traditional radiated procedures.

Band edge emissions within Restricted Bands are measured using RMS with duty cycle factor offset method.


8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None: for reporting purposes only.

8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B [msec]	Period [msec]	Duty Cycle x [linear]	Duty Cycle [%]	Duty Cycle Correction Factor [dB]	1/T Minimum VBW [kHz]
2400MHz Bands						
BLE	0.390	0.625	0.624	62.4%	2.05	2.565



9. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	666.9 kHz
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-55.225 dBm
15.247	TX conducted output power	<30dBm		Pass	0.456 dBm (Peak)
15.247	PSD	<8dBm		Pass	-15.01 dBm (Peak)
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass	42.59 dBuV (Qp)
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass	47.46 dBuV/m (Av)

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS

Channel	Frequency [MHz]	6 dB Bandwidth [kHz]	Minimum Limit [kHz]
Low	2402	673.8	500.0
Mid	2440	666.9	500.0
High	2480	683.3	500.0
Worst		666.9	500.0

6 dB BANDWIDTH PLOTS



10.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.




TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency [MHz]	99% Bandwidth [MHz]
Low	2402	1.056
Mid	2440	1.064
High	2480	1.063
Worst		1.064

99% BANDWIDTH PLOTS

Low CH	 Center Freq: 2.40200000 GHz Trig: Free Run #Atten: 30 dB Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.402 GHz Span 3 MHz #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms Occupied Bandwidth 1.0559 MHz Total Power -2.34 dBm Transmit Freq Error 28.090 kHz OBW Power 99.00 % x dB Bandwidth 1.248 MHz x dB -26.00 dB
Middle CH	 Center Freq: 2.44000000 GHz Trig: Free Run #Atten: 30 dB Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.44 GHz Span 3 MHz #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms Occupied Bandwidth 1.0637 MHz Total Power -1.84 dBm Transmit Freq Error 28.014 kHz OBW Power 99.00 % x dB Bandwidth 1.248 MHz x dB -26.00 dB
High CH	 Center Freq: 2.48000000 GHz Trig: Free Run #Atten: 30 dB Radio Std: None Radio Device: BTS 10 dB/div Ref 20.00 dBm Center 2.48 GHz Span 3 MHz #Res BW 30 kHz VBW 300 kHz #Sweep 100 ms Occupied Bandwidth 1.0628 MHz Total Power -2.79 dBm Transmit Freq Error 28.332 kHz OBW Power 99.00 % x dB Bandwidth 1.248 MHz x dB -26.00 dB

10.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.


TEST PROCEDURE

Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r05 under section 9.1.1 utilizing spectrum analyzer.

RESULTS

Channel	Frequency [MHz]	Peak Power Reading [dBm]	Limit [dBm]	Margin [dB]
Low	2402	-0.048	30.000	-30.048
Mid	2440	0.456	30.000	-29.544
High	2480	-0.481	30.000	-30.481
Worst		0.456		-29.544

OUTPUT POWER PLOTS



10.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 10.1 dB (including 10 dB pad and 0.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency [MHz]	AV power [dBm]	AV power [mW]
Low	2402	-0.39	0.91
Middle	2440	-0.04	0.99
High	2480	-0.83	0.83

10.5. PSD

LIMITS

FCC §15.247

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


TEST PROCEDURE

Power Spectral Density was performed utilizing the "Method PKPSD (Peak PSD)" under KDB558074 D01 DTS Meas Guidance v03r05

RESULTS

Channel	Frequency [MHz]	PSD [dBm]	Limit [dBm]	Margin [dB]
Low	2402	-15.53	8.00	-23.53
Mid	2440	-15.01	8.00	-23.01
High	2480	-16.03	8.00	-24.03

POWER SPECTRAL DENSITY PLOTS



10.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.


TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

RESULTS


BANDEDGE & SPURIOUS EMISSIONS, LOW CHANNEL



SPURIOUS EMISSIONS, MID CHANNEL



SPURIOUS EMISSIONS, HIGH CHANNEL



11. RADIATED TEST RESULTS

11.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits (μV/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1GHz and 150 cm for above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor for average measurements. (Restricted bandedge, Final detection of spurious harmonic emissions) Duty cycle factor = $10 \log(1/x)$. For this sample: DCF = $10 \log(1/0.624) = 2.05 \text{ dB}$ (Spectrum Analyzer round it up to 2.05dB)

Pre-scans to detect harmonic and spurious emissions, the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

The spectrum from 1 GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.
(From 30MHz to 1GHz, test was performed with the EUT set to transmit at the channel with highest output power)


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Note : Emission was pre-scanned from 9KHz to 30MHz; No emissions were detected which was at least 20dB below the specification limit (consider distance correction factor).
Per FCC part 15.31(o), test results were not reported.

Formula for converting the field strength from uV/m to dBuV/m is:
 $\text{Limit (dBuV/m)} = 20 \log \text{limit (uV/m)}$

11.2. TRANSMITTER ABOVE 1 GHz RESTRICTED BANDEDGE (LOW CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	10dB(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.99	Pk	31.7	-18.2	0	54.49	-	-	74	-19.51	162	156	H
2	* 2.386	44.24	Pk	31.7	-18.2	0	57.74	-	-	74	-16.26	162	156	H
3	* 2.39	30.57	RMS	31.7	-18.2	2.05	46.12	54	-7.88	-	-	162	156	H
4	* 2.382	31.32	RMS	31.7	-18.2	2.05	46.87	54	-7.13	-	-	162	156	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	10dB(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.51	Pk	31.7	-18.2	0	54.01	-	-	74	-19.99	205	372	V
2	* 2.35	43.92	Pk	31.6	-18.3	0	57.22	-	-	74	-16.78	205	372	V
3	* 2.39	30.76	RMS	31.7	-18.2	2.05	46.31	54	-7.69	-	-	205	372	V
4	* 2.374	31.28	RMS	31.7	-18.3	2.05	46.73	54	-7.27	-	-	205	372	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

AUTHORIZED BANDEDGE (HIGH CHANNEL)

HORIZONTAL PEAK AND AVERAGE PLOT



HORIZONTAL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	10dB(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.15	Pk	31.8	-18	0	53.95	-	-	74	-20.05	159	142	H
2	2.558	43.96	Pk	31.9	-18	0	57.86	-	-	74	-16.14	159	142	H
3	* 2.484	30.69	RMS	31.8	-18	2.05	46.54	54	-7.46	-	-	159	142	H
4	2.562	31.51	RMS	31.9	-18	2.05	47.46	54	-6.54	-	-	159	142	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

RMS - RMS detection

VERTICAL PEAK AND AVERAGE PLOT



VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(001687 24)_150619	10dB(dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	41.07	Pk	31.8	-18	0	54.87	-	-	74	-19.13	201	343	V
2	2.542	43.5	Pk	31.9	-18	0	57.4	-	-	74	-16.6	201	343	V
3	* 2.484	30.79	RMS	31.8	-18	2.05	46.64	54	-7.36	-	-	201	343	V
4	2.551	31.48	RMS	31.9	-18	2.05	47.43	54	-6.57	-	-	201	343	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS

LOW CHANNEL HORIZONTAL



LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016872 4)_150619	3dB[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.804	25.63	Pk	33.9	-24.3	0	35.23	-	-	74	-38.77	0-360	250	H
4	7.201	22.7	Pk	35.7	-21.6	0	36.8	-	-	74	-37.2	0-360	150	H
5	9.59	20.98	Pk	36.9	-18.4	0	39.48	-	-	74	-34.52	0-360	150	H
2	* 4.802	25.62	Pk	33.9	-24.3	0	35.22	-	-	74	-38.78	0-360	150	V
3	7.202	23.56	Pk	35.7	-21.6	0	37.66	-	-	74	-36.34	0-360	150	V
6	9.597	21.05	Pk	36.9	-18.4	0	39.55	-	-	74	-34.45	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

MID CHANNEL HORIZONTAL



MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA

Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117/0016872 4)_150619	3dB[dB]	DC Corr [dB]	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.896	25.41	Pk	33.9	-24.6	0	34.71	-	-	74	-39.29	0-360	150	H
4	* 7.313	23.42	Pk	35.9	-22	0	37.32	-	-	74	-36.68	0-360	250	H
5	9.777	20.27	Pk	37	-18	0	39.27	-	-	74	-34.73	0-360	250	H
2	* 4.89	25.65	Pk	33.9	-24.6	0	34.95	-	-	74	-39.05	0-360	150	V
3	* 7.318	23.63	Pk	35.9	-22	0	37.53	-	-	74	-36.47	0-360	250	V
6	9.778	21.26	Pk	37	-18	0	40.26	-	-	74	-33.74	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).

HIGH CHANNEL HORIZONTAL



HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	3117(0016872 4)_150619	3dB[dB]	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 4.955	25.56	Pk	33.9	-24.7	0	34.76	-	-	74	-39.24	0-360	150	H
4	* 7.447	22.39	Pk	36	-21	0	37.39	-	-	74	-36.61	0-360	250	H
5	9.918	19.86	Pk	37.1	-18	0	38.96	-	-	74	-35.04	0-360	150	H
2	* 4.949	25.14	Pk	33.9	-24.7	0	34.34	-	-	74	-39.66	0-360	250	V
3	* 7.451	22.95	Pk	36	-21	0	37.95	-	-	74	-36.05	0-360	150	V
6	9.921	19.13	Pk	37.2	-18	0	38.33	-	-	74	-35.67	0-360	150	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band


Pk – Peak detector

Note: Only peak measurement was performed. Because peak measurement result of unwanted emission is less than average limit (54dBuV/m).


11.3. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	VULB9163-749	30-1000MHz[dB]	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	46.575	39.22	Pk	14	-31.5	21.72	40	-18.28	0-360	400	H
2	68.2075	39.52	Pk	10.2	-31.3	18.42	40	-21.58	0-360	300	H
3	153.76	41.64	Pk	8.4	-30.7	19.34	43.52	-24.18	0-360	200	H
4	191.8825	43.8	Pk	10.6	-30.6	23.8	43.52	-19.72	0-360	200	H
5	44.7475	47.98	Pk	13.8	-31.5	30.28	40	-9.72	0-360	100	V
6	51.4625	42.15	Pk	13.9	-31.4	24.65	40	-15.35	0-360	100	V
7	92.7725	37.75	Pk	10.1	-31.1	16.75	43.52	-26.77	0-360	200	V
8	153.4625	38.46	Pk	8.3	-30.7	16.06	43.52	-27.46	0-360	100	V
9	* 284.1	36.39	Pk	13.1	-30.1	19.39	46.02	-26.63	0-360	100	H
10	363.5	35.38	Pk	14.6	-29.8	20.18	46.02	-25.84	0-360	100	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

Pk - Peak detector

12. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT



LINE 1 RESULTS

Trace Markers

Phase L1 .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex- cord_L1	CE Shield Room	Corrected Reading (dB(uVolts)	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
1	.276	35.55	Pk	9.8	0	45.35	60.94	-15.59	-	-
2	.276	21.9	Av	9.8	0	31.7	-	-	50.94	-19.24
3	.42	38.7	Pk	10.1	0	48.8	57.45	-8.65	-	-
4	.42	23.07	Av	10.1	0	33.17	-	-	47.45	-14.28
5	.582	36.8	Pk	10.1	0	46.9	56	-9.1	-	-
6	.564	21.31	Av	10.1	0	31.41	-	-	46	-14.59
7	.708	39.79	Pk	10	0	49.79	56	-6.21	-	-
8	.69	23.71	Av	10.1	0	33.81	-	-	46	-12.19
9	1.266	35.63	Pk	9.9	.1	45.63	56	-10.37	-	-
10	1.257	16.24	Av	9.9	.1	26.24	-	-	46	-19.76
11	2.211	35.68	Pk	9.8	.1	45.58	56	-10.42	-	-
12	2.274	13.54	Av	9.8	.1	23.44	-	-	46	-22.56

Pk - Peak detector


Av - Average detection

Phase L1 .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_L1	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.2805	30.28	Qp	9.8	0	40.08	60.8	-20.72	-	-
.4227	31.3	Qp	10.1	0	41.4	57.39	-15.99	-	-
.5775	32.38	Qp	10.1	0	42.48	56	-13.52	-	-
.7044	32.59	Qp	10	0	42.59	56	-13.41	-	-
1.2696	28.13	Qp	9.9	.1	38.13	56	-17.87	-	-
2.2083	25.28	Qp	9.8	.1	35.18	56	-20.82	-	-

Qp - Quasi-Peak detector

LINE 2 PLOT



LINE 2 RESULTS

Trace Markers

Phase N .15 - 30MHz

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	101837_w ith ex- cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
13	.267	34.53	Pk	9.8	0	44.33	61.21	-16.88	-	-
14	.276	19.62	Av	9.8	0	29.42	-	-	50.94	-21.52
15	.555	36.44	Pk	10.1	0	46.54	56	-9.46	-	-
16	.573	19.3	Av	10.1	0	29.4	-	-	46	-16.6
17	.681	38	Pk	10	0	48	56	-8	-	-
18	.69	21.71	Av	10	0	31.71	-	-	46	-14.29
19	1.293	33.67	Pk	9.8	.1	43.57	56	-12.43	-	-
20	1.257	14.43	Av	9.8	.1	24.33	-	-	46	-21.67
21	1.347	32.08	Pk	9.8	.1	41.98	56	-14.02	-	-
22	1.365	13.53	Av	9.8	.1	23.43	-	-	46	-22.57
23	2.328	33.17	Pk	9.8	.1	43.07	56	-12.93	-	-
24	2.301	13.89	Av	9.8	.1	23.79	-	-	46	-22.21

Pk - Peak detector

Av - Average detection

Phase N .15 - 30MHz

Frequency (MHz)	Meter Reading (dBuV)	Det	101837_wit h ex-cord_N	CE Shield Room	Corrected Reading (dB(uVolts))	CISPR 22 Class B ITE QP	Margin (dB)	CISPR 22 Class B ITE AV	Margin (dB)
.2715	28.26	Qp	9.8	0	38.06	61.07	-23.01	-	-
.5559	26.86	Qp	10.1	0	36.96	56	-19.04	-	-
.6765	31.27	Qp	10	0	41.27	56	-14.73	-	-
1.2894	25.14	Qp	9.8	.1	35.04	56	-20.96	-	-
1.3515	25.39	Qp	9.8	.1	35.29	56	-20.71	-	-
2.3244	23.34	Qp	9.8	.1	33.24	56	-22.76	-	-

Qp - Quasi-Peak detector