CERTIFICATION TEST REPORT

Report Number. : 4789467590-E6V2

Applicant	:	SAMSUNG ELECTRONICS CO., LTD. 129 SAMSUNG-RO, YEONGTONG-GU, SUWON-SI, GYEONGGI-DO, 16677, KOREA
Model	:	SM-F707B, SCG04
FCC ID	:	A3LSMF707B
EUT Description	:	GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, NFC and WPT
Test Standard(s)	:	FCC 47 CFR PART 15 SUBPART C

Date Of Issue:
June 15, 2020

Prepared by:
UL Korea, Ltd.
26th floor, 152, Teheran-ro, Gangnam-gu Seoul, 06236, Korea

Suwon Test Site: UL Korea, LTD. Suwon Laboratory
218 Maeyeong-ro, Yeongtong-gu
Suwon-si, Gyeonggi-do, 16675, Korea
TEL: (031) 337-9902
FAX: (031) 213-5433

IAS ACCREDITED
TL-637

REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	06/05/20	Initial issue	Hyunsik Yun
V2	06/15/20	Updated to address manufacturer's request	Hyunsik Yun

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS 5

2. TEST METHODOLOGY 6

3. FACILITIES AND ACCREDITATION 6

4. DECISION RULES AND MEASUREMENT UNCERTAINTY 7

4.1. METROLOGICAL TRACEABILITY 7

4.2. SAMPLE CALCULATION 7

4.3. DECISION RULES 7

4.4. MEASUREMENT UNCERTAINTY 7

5. EQUIPMENT UNDER TEST 8

5.1. EUT DESCRIPTION 8

5.2. MAXIMUM OUTPUT POWER 8

5.3. DESCRIPTION OF AVAILABLE ANTENNAS 8

5.4. WORST-CASE CONFIGURATION AND MODE 9

5.5. DESCRIPTION OF TEST SETUP 10

6. TEST AND MEASUREMENT EQUIPMENT 12

7. TEST RESULTS SUMMARY 13

8. MEASUREMENT METHODS 14

9. ANTENNA PORT TEST RESULTS 15

9.1. ON TIME AND DUTY CYCLE 15

9.2. 20 dB AND 99% BANDWIDTH 16

9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 17

9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 20

9.3. HOPPING FREQUENCY SEPARATION 23

9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 24

9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 25

9.4. NUMBER OF HOPPING CHANNELS 26

9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 27

9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 29

9.5. AVERAGE TIME OF OCCUPANCY 31

9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 32

9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 35

9.6. OUTPUT POWER 38

9.6.1. BASIC DATA RATE GFSK MODULATION 38

9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION 38

9.6.3. ENHANCED DATA RATE 8PSK MODULATION 38

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.6.1. OUTPUT POWER PLOTS 39

9.7. AVERAGE POWER 43
9.7.1. BASIC DATA RATE GFSK MODULATION 43
9.7.2. ENHANCED DATA RATE PI/4-DQPSK MODULATION 43
9.7.3. ENHANCED DATA RATE 8PSK MODULATION 43

9.8. CONDUCTED SPURIOUS EMISSIONS 44
9.8.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 45
9.8.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 49

10. RADIATED TEST RESULTS 53

10.1. TRANSMITTER ABOVE 1 GHz 55
10.1.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION 55
10.1.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION 79

10.2. WORST CASE BELOW 1 GHZ 103

11. AC POWER LINE CONDUCTED EMISSIONS 105

11.1.1. AC Power Line Host 106

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.

EUT DESCRIPTION: GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, NFC and WPT.

MODEL NUMBER: SM-F707B, SCG04

SERIAL NUMBER: 4393b319891f7ece (CONDUCTED)
4393B6255D1F7ECE, R3CN40D0EAF(RADIATED);

DATE TESTED: MAY 04, 2020 – JUN 04, 2020;

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
CFR 47 Part 15 Subpart C	Complies

UL Korea, Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Korea, Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Korea, Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Korea, Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by IAS, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Korea, Ltd. By:

Junwhan Lee
Suwon Lab Engineer
UL Korea, Ltd.

Tested By:

Hyunsik Yun
Suwon Lab Engineer
UL Korea, Ltd.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with following methods.

1. FCC CFR 47 Part 2.
2. FCC CFR 47 Part 15.
3. KDB 558074 D01 15.247 Meas Guidance v05r02.
4. ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea. Line conducted emissions are measured only at the 218 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

218 Maeyeong-ro
☒ Chamber 1
☒ Chamber 2
☐ Chamber 3

UL Korea, Ltd. is accredited by IAS, Laboratory Code TL-637. The full scope of accreditation can be viewed at https://www.iasonline.org/wp-content/uploads/2017/05/TL-637-cert-New.pdf.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

4.3. DECISION RULES

Decision rule for statement(s) of conformity is based on Procedure 1, Clause 4.4.2 in IEC Guide 115:2007.

4.4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	2.35 dB
Radiated Disturbance, 30 MHz to 1 GHz	3.49 dB
Radiated Disturbance, 1 GHz to 18 GHz	5.82 dB
Radiated Disturbance, 18 GHz to 40 GHz	5.49 dB

Uncertainty figures are valid to a confidence level of 95%.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The EUT is a GSM/WCDMA/LTE Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax, NFC and WPT. This test report addresses the BT(DSS) operational mode.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range [MHz]	Mode	Power Mode	Output Power [dBm]	Output Power [mW]
2 402 ~ 2 480	Basic GFSK	Average	15.459	35.15
		Peak	16.093	40.67
	Enhanced Pi/4-DPSK	Average	15.420	34.83
		Peak	17.815	60.46
	Enhanced 8PSK	Average	15.451	35.08
		Peak	18.256	66.93

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The internal antenna was Permanently attached.
Therefore this E.U.T Complies with the requirement of §15.203.

The radio utilizes an internal antennas, with Antenna 1's maximum gain of -1.11 dBi and Antenna 2's maximum gain of -5.37 dBi

"Sub4" and "Sub7" as indicated in antenna specification are written as Antenna 1 and Antenna 2 in this report.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission below 1GHz and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Radiated emission above 1GHz was performed with the EUT set to transmit low/mid/high channels.

i. Worst Axis condition

For Antenna 1, the fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.
For Antenna 2, the fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

ii. Foldable condition



For Antenna 1, the fundamental of the EUT was investigated in three foldable conditions(Open, Half-folded, Full-folded). It was determined that the “Half-folded” condition was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the “Half-folded” condition.
For Antenna 2, the fundamental of the EUT was investigated in three foldable conditions(Open, Half-folded, Full-folded). It was determined that the “Open” condition was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the “Open” condition.

Note: GFSK, Pi/4-DQPSK, 8PSK average Power are all investigated, The GFSK & 8PSK Power are the worst case. Testing is based on this mode to showing compliance.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	**Manufacturer**	**Model**	**Serial Number**	**FCC ID**
Charger	SAMSUNG	EP-TA200	R37M7QS4CH1DK3	N/A
Data Cable	SAMSUNG	EP-DF700	N/A	N/A
Earphone	SAMSUNG	GH59-15252A	N/A	N/A

I/O CABLE

I/O Cable List						
Cable No.	**Port**	**# of identical ports**	**Connector Type**	**Cable Type**	**Cable Length(m)**	**Remarks**
1	DC Power	1	C Type	Shielded	1.1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.
Test software enable BT communications.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	**Manufacturer**	**Model**	**S/N**	**Next Cal. Date**
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	750	08-04-20
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	749	08-04-20
Antenna, Bilog, 30MHz-1GHz	SCHWARZBECK	VULB9163	845	08-04-20
Antenna, Loop, 9kHz-30MHz	R&S	HFH2-Z2	100418	10-02-21
Antenna, Horn, 18 GHz	ETS	3115	00167211	08-04-20
Antenna, Horn, 18 GHz	ETS	3115	00161451	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00168724	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00168717	08-04-20
Antenna, Horn, 18 GHz	ETS	3117	00205959	08-04-20
Antenna, Horn, 40 GHz	ETS	3116C	00166155	08-14-20
Antenna, Horn, 40 GHz	ETS	3116C	00168645	10-02-21
Preamplifier	ETS	3116C-PA	00168841	08-08-20
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	80108-0004	N/A
Directional Antenna	Cobham	FPA3-0.8-6.0R/1329	110367-0003	N/A
Preamplifier, 1000 MHz	Sonoma	310N	341282	08-05-20
Preamplifier, 1000 MHz	Sonoma	310N	351741	08-05-20
Preamplifier, 1000 MHz	Sonoma	310N	370599	08-05-20
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1876511	08-06-20
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	1896138	08-06-20
Preamplifier, 18 GHz	Miteq	AFS42-00101800-25-S-42	2029169	08-06-20
Spectrum Analyzer, 44 GHz	Keysight	N9030B	MY57143717	01-20-21
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54170614	08-06-20
Spectrum Analyzer, 44 GHz	Agilent / HP	N9030A	MY54490312	08-06-20
Average Power Sensor	Agilent / HP	U2000	MY54270007	08-09-20
Bluetooth Tester	TESCOM	TC-3000C	3000C000546	08-07-20
Combiner	WEINCHEL	1575	2150	08-08-20
Attenuator	PASTERNACK	PE7087-10	A001	08-08-20
Attenuator	PASTERNACK	PE7087-10	A008	08-08-20
Attenuator	PASTERNACK	PE7087-10	2	08-06-20
EMI Test Receive, 40 GHz	R&S	ESU40	100439	08-06-20
EMI Test Receive, 40 GHz	R&S	ESU40	100457	08-06-20
EMI Test Receive, 44 GHz	R&S	ESW44	101590	08-05-20
EMI Test Receive, 3 GHz	R&S	ESR3	101832	08-05-20
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	009	08-06-20
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	015	08-06-20
Low Pass Filter 5GHz	Micro-Tronics	LPS17541	020	08-06-20
High Pass Filter 3GHz	Micro-Tronics	HPM17543	010	08-06-20
High Pass Filter 3GHz	Micro-Tronics	HPM17543	015	08-06-20
High Pass Filter 3GHz	Micro-Tronics	HPM17543	020	08-06-20
High Pass Filter 6GHz	Micro-Tronics	HPS17542	009	08-06-20
High Pass Filter 6GHz	Micro-Tronics	HPS17542	016	08-06-20
High Pass Filter 6GHz	Micro-Tronics	HPS17542	021	08-06-20
LISN	R&S	ENV-216	101837	08-09-20
Termination	WEINSCHEL	M1406A	T01	08-08-20

UL Software			
Description	**Manufacturer**	**Model**	**Version**
Radiated software	UL	UL EMC	Ver 9.5
AC Line Conducted software	UL	UL EMC	Ver 9.5

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7. TEST RESULTS SUMMARY

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1051, 15.247 (d)	Band Edge / Conducted Spurious Emission	-20dBc	Conducted	Pass
15.247 (b)(1)	TX conducted output power	<21dBm		Pass
15.247 (a)(1)	Hopping frequency separation	> two-thirds of the 20 dB bandwidth		Pass
15.247 (a)(1)(iii)	Number of Hopping channels	More than 15 non-overlapping channels		Pass
15.247 (a)(1)(iii)	Avg Time of Occupancy	< 0.4sec		Pass
15.207 (a)	AC Power Line conducted emissions	Section 10	Power Line conducted	Pass
15.205, 15.209	Radiated Spurious Emission	< 54dBuV/m	Radiated	Pass

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

8. MEASUREMENT METHODS

20dB BW : ANSI C63.10, Section 6.9.2

99% BW : ANSI C63.10, Section 6.9.3

HOPPING FREQUENCY SEPARATION : ANSI C63.10, Section 7.8.2

NUMBER OF HOPPING CHANNELS : ANSI C63.10, Section 7.8.3

AVERAGE TIME OF OCCUPANCY : ANSI C63.10, Section 7.8.4

OUTPUT POWER : ANSI C63.10, Section 7.8.5.

Out-of-band EMISSIONS (Conducted) : ANSI C63.10, Section 7.8.6, 7.8.8

Out-of-band EMISSIONS IN NON-RESTRICTED BANDS: ANSI C63.10, Section 6.

Out-of-band EMISSIONS IN RESTRICTED BANDS : ANSI C63.10, Section 6.

AC Power Line Conducted Emission : ANSI C63.10-2013, Section 6.2.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9. ANTENNA PORT TEST RESULTS

9.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.

PROCEDURE

ANSI C63.10, Section 11.6 : Zero-Span Spectrum Analyzer Method.

ON TIME AND DUTY CYCLE RESULTS

Mode	On time [msec]	Period [msec]	Duty Cycle [%]	Duty Cycle Correction Factor[dB]	1/T Minimum VBW [kHz]
2 400 ~ 2483.5 MHz Band					
Bluetooth	2.882	3.751	76.83	1.14	0.347

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.2. 20 dB AND 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to ≥ 1% of the 20 dB bandwidth. The VBW is set to ≥ RBW. The sweep time is coupled.

RESULTS

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.2.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

Chain	Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [kHz]
Antenna 1	0	2 402	916.2	822.1
	39	2 440	904.3	794.6
	77	2 479	903.6	794.8
	78	2 480	905.0	823.5
Antenna 2	0	2 402	905.6	794.1
	39	2 440	905.0	825.0
	77	2 479	904.0	825.0
	78	2 480	904.9	795.3
Worst			**916.2**	**825.0**



20 dB bandwidth / Antenna 1, 0 CHANNEL



20 dB bandwidth / Antenna 2, 0 CHANNEL



20 dB bandwidth / Antenna 1, 39 CHANNEL



20 dB bandwidth / Antenna 2, 39 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



20 dB bandwidth / Antenna 1, 77 CHANNEL



20 dB bandwidth / Antenna 2, 77 CHANNEL



20 dB bandwidth / Antenna 1, 78 CHANNEL



20 dB bandwidth / Antenna 2, 78 CHANNEL

99% bandwidth / Antenna 1, 0 CHANNEL



99% bandwidth / Antenna 2, 0 CHANNEL

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



99% bandwidth / Antenna 1, 39 CHANNEL



99% bandwidth / Antenna 2, 39 CHANNEL



99% bandwidth / Antenna 1, 77 CHANNEL



99% bandwidth / Antenna 2, 77 CHANNEL



99% bandwidth / Antenna 1, 78 CHANNEL



99% bandwidth / Antenna 2, 78 CHANNEL

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.2.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

Chain	Channel	Frequency [MHz]	20 dB Bandwidth [kHz]	99% Bandwidth [kHz]
Antenna 1	0	2 402	1268.0	1163.2
	39	2 440	1266.0	1159.7
	77	2 479	1269.0	1131.0
	78	2 480	1267.0	1161.5
Antenna 2	0	2 402	1270.0	1162.3
	39	2 440	1269.0	1162.7
	77	2 479	1268.0	1131.0
	78	2 480	1268.0	1161.9
Worst			**1270.0**	**1163.2**



20 dB bandwidth / Antenna 1, 0 CHANNEL



20 dB bandwidth / Antenna 2, 0 CHANNEL



20 dB bandwidth / Antenna 1, 39 CHANNEL



20 dB bandwidth / Antenna 2, 39 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



20 dB bandwidth / Antenna 1, 77 CHANNEL



20 dB bandwidth / Antenna 2, 77 CHANNEL



20 dB bandwidth / Antenna 1, 78 CHANNEL



20 dB bandwidth / Antenna 2, 78 CHANNEL

99% bandwidth / Antenna 1, 0 CHANNEL



99% bandwidth / Antenna 2, 0 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



99% bandwidth / Antenna 1, 39 CHANNEL



99% bandwidth / Antenna 2, 39 CHANNEL



99% bandwidth / Antenna 1, 77 CHANNEL



99% bandwidth / Antenna 2, 77 CHANNEL



99% bandwidth / Antenna 1, 78 CHANNEL



99% bandwidth / Antenna 2, 78 CHANNEL

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.3. HOPPING FREQUENCY SEPARATION

LIMITS

FCC §15.247 (a) (1)

RSS-247 (5.1) (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hoping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 300 kHz and the VBW is set to VBW >= RBW. The sweep time is coupled.

RESULTS

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.3.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



Antenna 1 / HOPPING FREQUENCY SEPARATION PLOT



Antenna 2 / HOPPING FREQUENCY SEPARATION PLOT

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.3.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



Antenna 1 / HOPPING FREQUENCY SEPARATION PLOT



Antenna 2 / HOPPING FREQUENCY SEPARATION PLOT

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.4. NUMBER OF HOPPING CHANNELS

LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 non-overlapping channels.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to cover the entire authorized band, in either a single sweep or in multiple contiguous sweeps. The RBW is set to a maximum of 1 % of the span. The analyzer is set to Max Hold.

RESULTS

Normal Mode: All Channels Observed

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.4.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION



Antenna 1 / 100 MHz Span



Antenna 2 / 100 MHz Span



Antenna 1 / 30MHz SPAN, SEGMENT 1 OF 3



Antenna 2 / 30MHz SPAN, SEGMENT 1 OF 3



Antenna 1 / 30MHz SPAN, SEGMENT 2 OF 3



Antenna 2 / 30MHz SPAN, SEGMENT 2 OF 3

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1 / 30MHz SPAN, SEGMENT 3 OF 3



Antenna 2 / 30MHz SPAN, SEGMENT 3 OF 3

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.4.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION



Antenna 1 / 100 MHz Span



Antenna 2 / 100 MHz Span



Antenna 1 / 30MHz SPAN, SEGMENT 1 OF 3



Antenna 2 / 30MHz SPAN, SEGMENT 1 OF 3



Antenna 1 / 30MHz SPAN, SEGMENT 2 OF 3



Antenna 2 / 30MHz SPAN, SEGMENT 2 OF 3

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1 / 30MHz SPAN, SEGMENT 3 OF 3



Antenna 2 / 30MHz SPAN, SEGMENT 3 OF 3

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5. AVERAGE TIME OF OCCUPANCY

LIMITS

FCC §15.247 (a) (1) (iii)

RSS-247 (5.1) (d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The span is set to 0 Hz, centered on a single, selected hopping channel. The width of a single pulse is measured in a fast scan. The number of pulses is measured in a 3.16 second scan, to enable resolution of each occurrence.

The average time of occupancy in the specified 3.16 second period (79 channels * 0.4 s) is equal to 10 * (# of pulses in 3.16 s) * pulse width.

For AFH mode, the average time of occupancy in the specified 8 second period (20 channels * 0.4 seconds) is equal to 10 * (# of pulses in 0.8 s) * pulse width.

RESULTS

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5.1. BLUETOOTH BASIC DATA RATE GFSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Antenna 1 Normal					
DH1	0.377	32	0.120512	0.4	-0.2795
DH3	1.632	16	0.261120	0.4	-0.1389
DH5	2.88	12	0.345600	0.4	-0.0544

DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Antenna 1 AFH					
DH1	0.377	8	0.030128	0.4	-0.3699
DH3	1.632	4	0.065280	0.4	-0.3347
DH5	2.880	3	0.086400	0.4	-0.3136

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Antenna 2 Normal					
DH1	0.377	32	0.120480	0.4	-0.2795
DH3	1.632	16	0.261120	0.4	-0.1389
DH5	2.881	12	0.345720	0.4	-0.0543

DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
GFSK Antenna 2 AFH					
DH1	0.377	8	0.030120	0.4	-0.3699
DH3	1.632	4	0.065280	0.4	-0.3347
DH5	2.881	3	0.086430	0.4	-0.3136

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1 / PULSE WIDTH – DH1



Antenna 2 / PULSE WIDTH – DH1



Antenna 1 / PULSE WIDTH – DH3



Antenna 2 / PULSE WIDTH – DH3



Antenna 1 / PULSE WIDTH – DH5



Antenna 2 / PULSE WIDTH – DH5

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1



Antenna 2 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH1



Antenna 1 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



Antenna 2 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH3



Antenna 1 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5



Antenna 2 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – DH5

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.5.2. BLUETOOTH ENHANCED DATA RATE 8PSK MODULATION

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Antenna 1 Normal					
3-DH1	0.383	32	0.122400	0.4	-0.2776
3-DH3	1.633	16	0.261280	0.4	-0.1387
3-DH5	2.884	12	0.346080	0.4	-0.0539

DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Antenna 1 AFH					
3-DH1	0.383	8	0.030600	0.4	-0.3694
3-DH3	1.633	4	0.065320	0.4	-0.33468
3-DH5	2.884	3	0.086520	0.4	-0.31348

DH Packet	Pulse Width [msec]	Number of Pulses in 3.16 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Antenna 2 Normal					
3-DH1	0.383	32	0.122464	0.4	-0.2775
3-DH3	1.633	16	0.261280	0.4	-0.1387
3-DH5	2.885	12	0.346200	0.4	-0.0538

DH Packet	Pulse Width [msec]	Number of Pulses in 0.8 seconds	Average Time of Occupancy [sec]	Limit [sec]	Margin [sec]
8PSK Antenna 2 AFH					
3-DH1	0.383	8	0.030616	0.4	-0.369384
3-DH3	1.633	4	0.065320	0.4	-0.33468
3-DH5	2.885	3	0.086550	0.4	-0.31345

.

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1 / PULSE WIDTH – 3-DH1



Antenna 2 / PULSE WIDTH – 3-DH1



Antenna 1 / PULSE WIDTH – 3-DH3



Antenna 2 / PULSE WIDTH – 3-DH3



Antenna 1 / PULSE WIDTH – 3-DH5



Antenna 2 / PULSE WIDTH – 3-DH5

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH1



Antenna 2 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH1



Antenna 1 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH3



Antenna 2 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH3



Antenna 1 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH5



Antenna 2 / NUMBER OF PULSES IN 3.16 SECOND OBSERVATION PERIOD – 3-DH5

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.6. OUTPUT POWER

LIMITS

§15.247 (b) (1)
The maximum antenna gain is less than 6 dBi, therefore the limit is 21 dBm.

TEST PROCEDURE
The transmitter output is connected to a spectrum analyzer the analyzer bandwidth is set to a value greater than the 20 dB bandwidth of the EUT.

RESULTS

9.6.1. BASIC DATA RATE GFSK MODULATION

Chain	Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Antenna 1	0	2 402	15.038	21.000	-5.962
	39	2 441	**16.093**	**21.000**	**-4.907**
	77	2 479	14.707	21.000	-6.293
	78	2 480	14.255	21.000	-6.745
Antenna 2	0	2 402	13.748	21.000	-7.252
	39	2 441	15.222	21.000	-5.778
	77	2 479	14.273	21.000	-6.727
	78	2 480	14.050	21.000	-6.950
Worst			16.093	21.000	-4.907

9.6.2. ENHANCED DATA RATE Pi/4-DPSK MODULATION

Chain	Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Antenna 1	0	2 402	16.827	21.000	-4.173
	39	2 441	**17.815**	**21.000**	**-3.185**
	77	2 479	16.326	21.000	-4.674
	78	2 480	15.799	21.000	-5.201
Antenna 2	0	2 402	15.600	21.000	-5.400
	39	2 441	16.999	21.000	-4.001
	77	2 479	15.970	21.000	-5.030
	78	2 480	15.756	21.000	-5.244
Worst			17.815	21.000	-3.185

9.6.3. ENHANCED DATA RATE 8PSK MODULATION

Chain	Channel	Frequency [MHz]	Output Power [dBm]	Limit [dBm]	Margin [dB]
Antenna 1	0	2 402	17.392	21.000	-3.608
	39	2 441	**18.256**	**21.000**	**-2.744**
	77	2 479	16.670	21.000	-4.330
	78	2 480	16.253	21.000	-4.747
Antenna 2	0	2 402	16.146	21.000	-4.854
	39	2 441	17.544	21.000	-3.456
	77	2 479	16.457	21.000	-4.543
	78	2 480	16.164	21.000	-4.836
Worst			18.256	21.000	-2.744

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.6.1. OUTPUT POWER PLOTS

GFSK OUTPUT POWER



Antenna 1, 0 CHANNEL



Antenna 2, 0 CHANNEL



Antenna 1, 39 CHANNEL



Antenna 2, 39 CHANNEL



Antenna 1, 77 CHANNEL



Antenna 2, 77 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1, 78 CHANNEL



Antenna 2, 78 CHANNEL

Pi/4-DPSK OUTPUT POWER



Antenna 1, 0 CHANNEL



Antenna 2, 0 CHANNEL



Antenna 1, 39 CHANNEL



Antenna 2, 39 CHANNEL

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.



Antenna 1, 77 CHANNEL



Antenna 2, 77 CHANNEL



Antenna 1, 78 CHANNEL



Antenna 2, 78 CHANNEL

8PSK OUTPUT POWER



Antenna 1, 0 CHANNEL



Antenna 2, 0 CHANNEL

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_15C(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.