

TEST REPORT

FCC LTE B25 Test for SM-F766B
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2505-FC027-R1

DATE OF ISSUE
May 27, 2025

Tested by
Jae Mun Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2505-FC027-R1

DATE OF ISSUE

May 27, 2025

Applicant

SAMSUNG Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-F766B

Date of Test

February 24, 2025 ~ May 07, 2025

FCC ID

A3LSMF766B

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

Test Standard Used

FCC Rule Part: § 24

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	May 07, 2025	Initial Release
1	May 27, 2025	Revised the Power Supply Voltage. (DC 3.88 V → DC 3.90 V)

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	5
1.1. MAXIMUM OUTPUT POWER	6
2. INTRODUCTION	8
2.1. DESCRIPTION OF EUT	8
2.2. MEASURING INSTRUMENT CALIBRATION	8
2.3. TEST FACILITY	8
3. DESCRIPTION OF TESTS	9
3.1 TEST PROCEDURE	9
3.2 RADIATED POWER	10
3.3 RADIATED SPURIOUS EMISSIONS	11
3.4 PEAK- TO- AVERAGE RATIO	12
3.5 OCCUPIED BANDWIDTH	14
3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	15
3.7 BAND EDGE	16
3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	18
3.9 WORST CASE(RADIATED TEST)	19
3.10 WORST CASE(CONDUCTED TEST)	20
4. LIST OF TEST EQUIPMENT	21
5. MEASUREMENT UNCERTAINTY	22
6. SUMMARY OF TEST RESULTS	23
7. SAMPLE CALCULATION	24
8. TEST DATA(Main 2 ANT)	26
8.1 EQUIVALENT ISOTROPIC RADIATED POWER	26
8.2 RADIATED SPURIOUS EMISSIONS	29
8.3 PEAK-TO-AVERAGE RATIO	30
8.4 OCCUPIED BANDWIDTH	31
8.5 CONDUCTED SPURIOUS EMISSIONS	32
8.6 BAND EDGE	32
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	33
9. TEST DATA(Sub 5 ANT)	51
9.1 EQUIVALENT ISOTROPIC RADIATED POWER	51
9.2 RADIATED SPURIOUS EMISSIONS	54
9.3 PEAK-TO-AVERAGE RATIO	55
9.4 OCCUPIED BANDWIDTH	56
9.5 CONDUCTED SPURIOUS EMISSIONS	57
9.6 BAND EDGE	57
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	58
10. TEST PLOTS(Main 2 ANT)	76
11. TEST PLOTS(Sub 5 ANT)	197
12. ANNEX A_ TEST SETUP PHOTO	318

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMF766B
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§ 24
EUT Type:	Mobile Phone
Model(s):	SM-F766B
Tx Frequency:	1850.7 MHz – 1914.3 MHz (LTE – Band25 (1.4 MHz)) 1851.5 MHz – 1913.5 MHz (LTE – Band25 (3 MHz)) 1852.5 MHz – 1912.5 MHz (LTE – Band25 (5 MHz)) 1855.0 MHz – 1910.0 MHz (LTE – Band25 (10 MHz)) 1857.5 MHz – 1907.5 MHz (LTE – Band25 (15 MHz)) 1860.0 MHz – 1905.0 MHz (LTE – Band25 (20 MHz))
Date(s) of Tests:	February 24, 2025 ~ May 07, 2025
Serial number:	Radiated : R3CY10XMT6Y(Main 2 ANT), R3CY30RSYRA(Sub 5 ANT) Conducted : R3CY209A7CH
Antenna Information	Please refer to the Antenna Specification document.

1.1. MAXIMUM OUTPUT POWER

Main 2 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band25 (1.4)	1850.7 - 1914.3	1M10G7D	QPSK	0.131	21.16
		1M10W7D	16QAM	0.096	19.83
		1M09W7D	64QAM	0.074	18.70
		1M10W7D	256QAM	0.040	15.99
LTE – Band25 (3)	1851.5 - 1913.5	2M72G7D	QPSK	0.133	21.23
		2M70W7D	16QAM	0.101	20.06
		2M70W7D	64QAM	0.078	18.91
		2M71W7D	256QAM	0.042	16.25
LTE – Band25 (5)	1852.5 - 1912.5	4M54G7D	QPSK	0.141	21.50
		4M51W7D	16QAM	0.104	20.19
		4M53W7D	64QAM	0.080	19.05
		4M57W7D	256QAM	0.043	16.33
LTE – Band25 (10)	1855.0 - 1910.0	9M01G7D	QPSK	0.143	21.54
		9M02W7D	16QAM	0.103	20.14
		9M02W7D	64QAM	0.079	18.98
		9M02W7D	256QAM	0.043	16.38
LTE – Band25 (15)	1857.5 - 1907.5	13M5G7D	QPSK	0.147	21.67
		13M5W7D	16QAM	0.105	20.22
		13M5W7D	64QAM	0.081	19.08
		13M5W7D	256QAM	0.044	16.43
LTE – Band25 (20)	1860.0 - 1905.0	18M0G7D	QPSK	0.147	21.66
		18M0W7D	16QAM	0.105	20.22
		18M0W7D	64QAM	0.081	19.06
		18M0W7D	256QAM	0.044	16.42

Sub 5 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band25 (1.4)	1850.7 - 1914.3	1M10G7D	QPSK	0.041	16.09
		1M10W7D	16QAM	0.034	15.33
		1M09W7D	64QAM	0.026	14.13
		1M10W7D	256QAM	0.013	11.14
LTE – Band25 (3)	1851.5 - 1913.5	2M71G7D	QPSK	0.041	16.12
		2M70W7D	16QAM	0.035	15.44
		2M70W7D	64QAM	0.027	14.26
		2M71W7D	256QAM	0.013	11.27
LTE – Band25 (5)	1852.5 - 1912.5	4M53G7D	QPSK	0.041	16.14
		4M51W7D	16QAM	0.035	15.48
		4M53W7D	64QAM	0.027	14.29
		4M56W7D	256QAM	0.013	11.30
LTE – Band25 (10)	1855.0 - 1910.0	8M99G7D	QPSK	0.042	16.19
		9M01W7D	16QAM	0.034	15.31
		9M00W7D	64QAM	0.026	14.14
		9M02W7D	256QAM	0.013	11.22
LTE – Band25 (15)	1857.5 - 1907.5	13M5G7D	QPSK	0.041	16.11
		13M5W7D	16QAM	0.035	15.47
		13M5W7D	64QAM	0.027	14.33
		13M5W7D	256QAM	0.013	11.23
LTE – Band25 (20)	1860.0 - 1905.0	18M0G7D	QPSK	0.041	16.12
		17M9W7D	16QAM	0.037	15.64
		18M0W7D	64QAM	0.028	14.49
		18M0W7D	256QAM	0.014	11.44

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser
if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit)
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets,
and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is
driven by a signal generator and the previously recorded signal was duplicated.
The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_g_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_g is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)


The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.5 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.


The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq$ 3 x RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.6 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup


Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = max hold
5. Sweep time = auto
6. Number of points in sweep $\geq$ 2 x Span / RBW

3.7 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes


According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where Margin < 1 dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.

2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter.
Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 15 MHz(Main 2 ANT), 10 MHz(Sub 5 ANT))
- The EUT was tested in three modes(Open, Half-open, Closed), the worst case configuration results are reported. (Worst case: Half-open(Main 2 Ant), Open mode(Sub 5 Ant))
- The worst case is reported with the EUT positioning, modulations, RB sizes and offsets, and channel bandwidth configurations shown in the test data.
- Please refer to the table below.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.

[Main 2 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		X
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		X

[Sub 5 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Isotropic Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		Z
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Y

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Peak-To-Average Ratio	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10, 15, 20	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
		15	Low	1	0
			High	1	74
		20	Low	1	0
			High	1	99
		1.4, 3, 5, 10, 15, 20	Low, High	Full RB	0
Spurious and Harmonic Emissions at Antenna Terminal	QPSK	1.4, 3, 5, 10, 15, 20	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacturer	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1.2 G HPF+LNA)	HCT CO., LTD.	F1L1	11/11/2025	Annual
RF Switching System	Switch box(3.3 G HPF+LNA)	HCT CO., LTD.	F1L2	11/11/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.	F1L4	11/11/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.	F1L7	11/11/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/10/2026	Annual
DC Power Supply	E3632A	Agilent	MY40010147	08/06/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/11/2026	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	147	08/17/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	9120D-1298	09/11/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/23/2027	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/14/2026	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/10/2026	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	REOHDE & SCHWARZ	100931	08/06/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Wideband Radio Communication Tester	MT8821C	Anritsu Corp.	6262094331	11/13/2025	Annual
Radio Communication Test Station	MT8000A	Anritsu Corp.	6272613402	08/28/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	05/23/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)
Parameter	Expanded Uncertainty ($\pm$ kHz)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.68 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.75 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

-. The decision rule applies 'simple acceptance'

6.1 Test Condition: Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 24.238(a)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Peak- to- Average Ratio	§ 24.232(d)	< 13 dB	PASS
Frequency stability / variation of ambient temperature	§ 24.235	Emission must remain in band	PASS

Note:

1. See SAR Report

6.2 Test Condition: Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Equivalent Isotropic Radiated Power	§ 24.232(c)	< 2 Watts max. EIRP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 24.238(a)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

6.3. Data Referencing (Main Ant)

Rule Part	Test item	Data Referencing	Comments
§ 2.1049	Occupied Bandwidth	Y	-
§ 2.1051, § 24.238(a)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal..	Y	-
§ 24.232(d)	Peak- to- Average Ratio	Y	-
§ 24.235	Frequency stability	Y	-
§ 24.232(c)	Equivalent Isotropic Radiated Power	Y	Spot-check
§ 2.1053, § 24.238(a)	Radiated Spurious Emissions	Y	Spot-check
§ 2.1046	Conducted Output Power	Y	-

Spot-Check Result

1. Data was leveraged from model SM-F766U for the certification of SM-F766B.
2. Please refer to the [FCC Evaluation] Report.

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 2 ANT)

8.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1850.7	LTE B25 (1.4 MHz)	QPSK	-22.42	12.10	10.40	2.07	H	<2.00	0.110	20.43	1	5
		16-QAM	-23.73	10.79	10.40	2.07	H		0.082	19.12		
		64-QAM	-24.88	9.64	10.40	2.07	H		0.063	17.97		
		256-QAM	-27.51	7.01	10.40	2.07	H		0.034	15.34		
1882.5		QPSK	-22.10	12.88	10.40	2.21	H		0.128	21.07	1	0
		16-QAM	-23.41	11.57	10.40	2.21	H		0.095	19.76		
		64-QAM	-24.58	10.40	10.40	2.21	H		0.072	18.59		
		256-QAM	-27.23	7.75	10.40	2.21	H		0.039	15.94		
1914.3		QPSK	-22.08	12.93	10.40	2.17	H		0.131	21.16	1	0
		16-QAM	-23.41	11.60	10.40	2.17	H		0.096	19.83		
		64-QAM	-24.54	10.47	10.40	2.17	H		0.074	18.70		
		256-QAM	-27.25	7.76	10.40	2.17	H		0.040	15.99		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1851.5	LTE B25 (3 MHz)	QPSK	-22.41	12.11	10.40	2.07	H	< 2.00	0.111	20.44	1	14
		16-QAM	-23.66	10.86	10.40	2.07	H		0.083	19.19		
		64-QAM	-24.82	9.70	10.40	2.07	H		0.064	18.03		
		256-QAM	-27.51	7.01	10.40	2.07	H		0.034	15.34		
1882.5		QPSK	-21.96	13.02	10.40	2.21	H		0.132	21.21	1	0
		16-QAM	-23.26	11.72	10.40	2.21	H		0.098	19.91		
		64-QAM	-24.41	10.57	10.40	2.21	H		0.075	18.76		
		256-QAM	-27.04	7.94	10.40	2.21	H		0.041	16.13		
1913.5		QPSK	-22.01	13.00	10.40	2.17	H		0.133	21.23	1	0
		16-QAM	-23.18	11.83	10.40	2.17	H		0.101	20.06		
		64-QAM	-24.33	10.68	10.40	2.17	H		0.078	18.91		
		256-QAM	-26.99	8.02	10.40	2.17	H		0.042	16.25		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1852.5	LTE B25 (5 MHz)	QPSK	-22.32	12.25	10.40	2.08	H	<2.00	0.114	20.57	1	24
		16-QAM	-23.64	10.93	10.40	2.08	H		0.084	19.25		
		64-QAM	-24.79	9.78	10.40	2.08	H		0.065	18.10		
		256-QAM	-27.42	7.15	10.40	2.08	H		0.035	15.47		
1882.5		QPSK	-21.89	13.09	10.40	2.21	H		0.134	21.28	1	0
		16-QAM	-23.20	11.78	10.40	2.21	H		0.099	19.97		
		64-QAM	-24.34	10.64	10.40	2.21	H		0.076	18.83		
		256-QAM	-27.00	7.98	10.40	2.21	H		0.041	16.17		
1912.5		QPSK	-21.74	13.27	10.40	2.17	H		0.141	21.50	1	0
		16-QAM	-23.05	11.96	10.40	2.17	H		0.104	20.19		
		64-QAM	-24.19	10.82	10.40	2.17	H		0.080	19.05		
		256-QAM	-26.91	8.10	10.40	2.17	H		0.043	16.33		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1855	LTE B25 (10 MHz)	QPSK	-22.27	12.30	10.40	2.08	H	<2.00	0.115	20.62	1	49
		16-QAM	-23.60	10.97	10.40	2.08	H		0.085	19.29		
		64-QAM	-24.74	9.83	10.40	2.08	H		0.065	18.15		
		256-QAM	-27.40	7.17	10.40	2.08	H		0.035	15.49		
1882.5		QPSK	-21.79	13.19	10.40	2.21	H		0.137	21.38	1	49
		16-QAM	-23.12	11.86	10.40	2.21	H		0.101	20.05		
		64-QAM	-24.26	10.72	10.40	2.21	H		0.078	18.91		
		256-QAM	-26.93	8.05	10.40	2.21	H		0.042	16.24		
1910		QPSK	-21.63	13.31	10.40	2.17	H		0.143	21.54	1	0
		16-QAM	-23.03	11.91	10.40	2.17	H		0.103	20.14		
		64-QAM	-24.19	10.75	10.40	2.17	H		0.079	18.98		
		256-QAM	-26.79	8.15	10.40	2.17	H		0.043	16.38		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1857.5	LTE B25 (15 MHz)	QPSK	-21.96	12.68	10.40	2.10	H	<2.00	0.125	20.98	1	74
		16-QAM	-23.25	11.39	10.40	2.10	H		0.093	19.69		
		64-QAM	-24.41	10.23	10.40	2.10	H		0.071	18.53		
		256-QAM	-27.04	7.60	10.40	2.10	H		0.039	15.90		
1882.5		QPSK	-21.96	13.02	10.40	2.21	H		0.132	21.21	1	0
		16-QAM	-23.30	11.68	10.40	2.21	H		0.097	19.87		
		64-QAM	-24.42	10.56	10.40	2.21	H		0.075	18.75		
		256-QAM	-27.06	7.92	10.40	2.21	H		0.041	16.11		
1907.5		QPSK	-21.50	13.44	10.40	2.17	H		0.147	21.67	1	0
		16-QAM	-22.95	11.99	10.40	2.17	H		0.105	20.22		
		64-QAM	-24.09	10.85	10.40	2.17	H		0.081	19.08		
		256-QAM	-26.74	8.20	10.40	2.17	H		0.044	16.43		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1860	LTE B25 (20 MHz)	QPSK	-21.89	12.75	10.40	2.10	H	<2.00	0.127	21.05	1	99
		16-QAM	-23.20	11.44	10.40	2.10	H		0.094	19.74		
		64-QAM	-24.34	10.30	10.40	2.10	H		0.072	18.60		
		256-QAM	-27.01	7.63	10.40	2.10	H		0.039	15.93		
1882.5		QPSK	-21.79	13.19	10.40	2.21	H		0.137	21.38	1	0
		16-QAM	-23.12	11.86	10.40	2.21	H		0.101	20.05		
		64-QAM	-24.27	10.71	10.40	2.21	H		0.078	18.90		
		256-QAM	-26.89	8.09	10.40	2.21	H		0.043	16.28		
1905		QPSK	-21.47	13.45	10.40	2.19	H		0.147	21.66	1	0
		16-QAM	-22.91	12.01	10.40	2.19	H		0.105	20.22		
		64-QAM	-24.07	10.85	10.40	2.19	H		0.081	19.06		
		256-QAM	-26.71	8.21	10.40	2.19	H		0.044	16.42		

8.2 RADIATED SPURIOUS EMISSIONS

■ MOD: LTE B25
 ■ MODULATION SIGNAL: 15 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: -13 dBm

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
26115 (1857.5)	3 715.00	-43.79	12.28	-60.88	3.11	V	-51.71	1	74
	5 572.50	-43.48	13.06	-55.63	3.89	V	-46.46		
	7 430.00	-41.75	10.78	-44.76	4.56	H	-38.54		
26365 (1882.5)	3 765.00	-43.78	12.22	-59.62	3.11	H	-50.51	1	0
	5 647.50	-44.31	13.12	-56.48	3.96	V	-47.32		
	7 530.00	-44.83	10.85	-47.47	4.60	H	-41.22		
26615 (1907.5)	3 815.00	-43.03	12.16	-59.47	3.20	H	-50.51	1	0
	5 722.50	-43.21	13.05	-55.58	4.00	H	-46.53		
	7 630.00	-45.11	11.18	-47.91	4.66	H	-41.39		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
25	1.4 MHz	1882.5	QPSK	6	0	5.11
			16-QAM			5.88
			64-QAM			6.04
			256-QAM			5.79
	3 MHz		QPSK	15		5.23
			16-QAM			6.01
			64-QAM			6.06
			256-QAM			5.87
	5 MHz		QPSK	25		5.22
			16-QAM			5.98
			64-QAM			6.09
			256-QAM			5.89
	10 MHz		QPSK	50		5.24
			16-QAM			5.98
			64-QAM			6.20
			256-QAM			5.88
	15 MHz		QPSK	75		5.25
			16-QAM			6.00
			64-QAM			6.16
			256-QAM			5.82
	20 MHz		QPSK	100		5.28
			16-QAM			6.04
			64-QAM			6.19
			256-QAM			5.88

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 77 ~ 100.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
25	1.4 MHz	1882.5	QPSK	6	0	1.0966
			16-QAM			1.0947
			64-QAM			1.0942
			256-QAM			1.0954
	3 MHz		QPSK	15		2.7179
			16-QAM			2.7026
			64-QAM			2.7044
			256-QAM			2.7133
	5 MHz		QPSK	25		4.5354
			16-QAM			4.5133
			64-QAM			4.5292
			256-QAM			4.5700
	10 MHz		QPSK	50		9.0142
			16-QAM			9.0159
			64-QAM			9.0201
			256-QAM			9.0241
	15 MHz		QPSK	75		13.472
			16-QAM			13.478
			64-QAM			13.475
			256-QAM			13.476
	20 MHz		QPSK	100		18.029
			16-QAM			17.997
			64-QAM			17.979
			256-QAM			17.994

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 101 ~ 124.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
25	1.4	1850.70	7.7468	28.591	-67.310	-38.719	-13.00
		1882.50	4.0080	27.976	-67.859	-39.883	
		1914.30	2.4029	27.976	-60.890	-32.914	
	3	1851.50	8.6640	28.591	-67.380	-38.789	
		1882.50	2.4826	27.976	-61.830	-33.854	
		1913.50	8.7737	28.591	-68.422	-39.831	
	5	1852.50	2.4826	27.976	-64.456	-36.480	
		1882.50	3.7987	27.976	-65.996	-38.020	
		1912.50	9.1526	28.591	-67.538	-38.947	
	10	1855.00	9.6511	28.591	-66.043	-37.452	
		1882.50	2.4826	27.976	-64.217	-36.241	
		1910.00	8.3250	28.591	-66.997	-38.406	
	15	1857.50	2.4826	27.976	-65.359	-37.383	
		1882.50	5.9223	28.591	-67.289	-38.698	
		1907.50	5.2044	28.591	-67.493	-38.902	
	20	1860.00	9.7009	28.591	-67.777	-39.186	
		1882.50	7.8066	28.591	-67.150	-38.559	
		1905.00	4.9851	27.976	-68.389	-40.413	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 125 ~ 160.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 161 ~ 196.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B25</u>
OPERATING FREQUENCY:	<u>1850,700,000 Hz</u>
CHANNEL:	<u>26047 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.900	+20(Ref)	1850 699 990	0.0	0.000 000	0.000
100 %		-30	1850 699 981	-8.5	0.000 000	-0.005
100 %		-20	1850 699 981	-8.8	0.000 000	-0.005
100 %		-10	1850 699 981	-8.5	0.000 000	-0.005
100 %		0	1850 699 983	-7.4	0.000 000	-0.004
100 %		+10	1850 699 984	-5.9	0.000 000	-0.003
100 %		+30	1850 699 982	-7.6	0.000 000	-0.004
100 %		+40	1850 699 982	-7.8	0.000 000	-0.004
100 %		+50	1850 699 981	-9.0	0.000 000	-0.005
Batt. Endpoint	3.300	+20	1850 699 982	-8.2	0.000 000	-0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1851,500,000 Hz
- ▣ CHANNEL: 26055 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1851 499 996	0.0	0.000 000	0.000
100 %		-30	1851 499 991	-4.5	0.000 000	-0.002
100 %		-20	1851 499 986	-9.3	-0.000 001	-0.005
100 %		-10	1851 499 991	-4.6	0.000 000	-0.002
100 %		0	1851 499 991	-4.7	0.000 000	-0.003
100 %		+10	1851 499 999	3.6	0.000 000	0.002
100 %		+30	1851 500 001	5.5	0.000 000	0.003
100 %		+40	1851 500 000	4.8	0.000 000	0.003
100 %		+50	1851 499 988	-7.9	0.000 000	-0.004
Batt. Endpoint	3.300	+20	1851 499 989	-6.5	0.000 000	-0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1852,500,000 Hz
- ▣ CHANNEL: 26065 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1852 500 006	0.0	0.000 000	0.000
100 %		-30	1852 500 011	4.8	0.000 000	0.003
100 %		-20	1852 500 013	6.8	0.000 000	0.004
100 %		-10	1852 500 012	5.2	0.000 000	0.003
100 %		0	1852 500 001	-5.0	0.000 000	-0.003
100 %		+10	1852 500 013	6.8	0.000 000	0.004
100 %		+30	1852 500 012	6.0	0.000 000	0.003
100 %		+40	1852 500 012	5.9	0.000 000	0.003
100 %		+50	1852 500 012	5.5	0.000 000	0.003
Batt. Endpoint	3.300	+20	1852 500 011	5.1	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1855,000,000 Hz
- ▣ CHANNEL: 26090 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1855 000 006	0.0	0.000 000	0.000
100 %		-30	1855 000 013	7.6	0.000 000	0.004
100 %		-20	1855 000 014	7.7	0.000 000	0.004
100 %		-10	1855 000 013	7.4	0.000 000	0.004
100 %		0	1855 000 014	8.1	0.000 000	0.004
100 %		+10	1855 000 013	6.9	0.000 000	0.004
100 %		+30	1855 000 013	6.7	0.000 000	0.004
100 %		+40	1855 000 013	6.7	0.000 000	0.004
100 %		+50	1855 000 012	6.4	0.000 000	0.003
Batt. Endpoint	3.300	+20	1855 000 013	7.1	0.000 000	0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1857,500,000 Hz
- ▣ CHANNEL: 26115 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1857 500 007	0.0	0.000 000	0.000
100 %		-30	1857 500 014	7.2	0.000 000	0.004
100 %		-20	1857 500 014	7.2	0.000 000	0.004
100 %		-10	1857 500 015	8.0	0.000 000	0.004
100 %		0	1857 500 013	5.8	0.000 000	0.003
100 %		+10	1857 500 015	7.7	0.000 000	0.004
100 %		+30	1857 500 014	7.2	0.000 000	0.004
100 %		+40	1857 500 013	6.1	0.000 000	0.003
100 %		+50	1857 500 015	7.8	0.000 000	0.004
Batt. Endpoint	3.300	+20	1857 500 014	6.6	0.000 000	0.004




MODE:	<u>LTE B25</u>
OPERATING FREQUENCY:	<u>1860,000,000 Hz</u>
CHANNEL:	<u>26140 (20 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1860 000 009	0.0	0.000 000	0.000
100 %		-30	1860 000 018	8.9	0.000 000	0.005
100 %		-20	1860 000 015	6.6	0.000 000	0.004
100 %		-10	1860 000 017	7.8	0.000 000	0.004
100 %		0	1860 000 018	8.8	0.000 000	0.005
100 %		+10	1860 000 017	8.4	0.000 000	0.005
100 %		+30	1860 000 016	7.1	0.000 000	0.004
100 %		+40	1860 000 016	6.7	0.000 000	0.004
100 %		+50	1860 000 016	7.1	0.000 000	0.004
Batt. Endpoint	3.300	+20	1860 000 016	7.3	0.000 000	0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 499 993	0.0	0.000 000	0.000
100 %		-30	1882 499 987	-6.0	0.000 000	-0.003
100 %		-20	1882 499 985	-7.8	0.000 000	-0.004
100 %		-10	1882 499 986	-7.1	0.000 000	-0.004
100 %		0	1882 499 987	-6.3	0.000 000	-0.003
100 %		+10	1882 499 987	-5.6	0.000 000	-0.003
100 %		+30	1882 499 986	-7.5	0.000 000	-0.004
100 %		+40	1882 499 987	-6.0	0.000 000	-0.003
100 %		+50	1882 499 987	-5.7	0.000 000	-0.003
Batt. Endpoint	3.300	+20	1882 499 987	-6.4	0.000 000	-0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 005	0.0	0.000 000	0.000
100 %		-30	1882 499 998	-7.0	0.000 000	-0.004
100 %		-20	1882 500 000	-4.8	0.000 000	-0.003
100 %		-10	1882 500 010	5.2	0.000 000	0.003
100 %		0	1882 500 010	4.7	0.000 000	0.002
100 %		+10	1882 500 011	5.3	0.000 000	0.003
100 %		+30	1882 499 999	-6.0	0.000 000	-0.003
100 %		+40	1882 499 999	-6.7	0.000 000	-0.004
100 %		+50	1882 500 012	7.2	0.000 000	0.004
Batt. Endpoint	3.300	+20	1882 499 997	-7.9	0.000 000	-0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 005	0.0	0.000 000	0.000
100 %		-30	1882 500 000	-5.0	0.000 000	-0.003
100 %		-20	1882 500 011	6.0	0.000 000	0.003
100 %		-10	1882 500 012	6.3	0.000 000	0.003
100 %		0	1882 500 011	5.6	0.000 000	0.003
100 %		+10	1882 500 011	5.9	0.000 000	0.003
100 %		+30	1882 500 001	-4.5	0.000 000	-0.002
100 %		+40	1882 500 010	4.9	0.000 000	0.003
100 %		+50	1882 500 009	3.9	0.000 000	0.002
Batt. Endpoint	3.300	+20	1882 500 011	5.7	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 007	0.0	0.000 000	0.000
100 %		-30	1882 500 013	6.1	0.000 000	0.003
100 %		-20	1882 500 014	7.7	0.000 000	0.004
100 %		-10	1882 500 014	7.5	0.000 000	0.004
100 %		0	1882 500 012	5.3	0.000 000	0.003
100 %		+10	1882 500 014	7.8	0.000 000	0.004
100 %		+30	1882 500 014	7.5	0.000 000	0.004
100 %		+40	1882 500 013	6.1	0.000 000	0.003
100 %		+50	1882 500 014	7.3	0.000 000	0.004
Batt. Endpoint	3.300	+20	1882 500 013	6.0	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 006	0.0	0.000 000	0.000
100 %		-30	1882 500 013	6.6	0.000 000	0.004
100 %		-20	1882 500 012	5.8	0.000 000	0.003
100 %		-10	1882 500 011	5.3	0.000 000	0.003
100 %		0	1882 500 013	6.8	0.000 000	0.004
100 %		+10	1882 500 010	4.3	0.000 000	0.002
100 %		+30	1882 500 013	6.8	0.000 000	0.004
100 %		+40	1882 500 014	8.0	0.000 000	0.004
100 %		+50	1882 500 012	6.3	0.000 000	0.003
Batt. Endpoint	3.300	+20	1882 500 013	6.6	0.000 000	0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 006	0.0	0.000 000	0.000
100 %		-30	1882 500 013	6.5	0.000 000	0.003
100 %		-20	1882 500 012	6.1	0.000 000	0.003
100 %		-10	1882 500 013	7.0	0.000 000	0.004
100 %		0	1882 500 013	7.1	0.000 000	0.004
100 %		+10	1882 500 013	7.1	0.000 000	0.004
100 %		+30	1882 500 014	7.5	0.000 000	0.004
100 %		+40	1882 500 012	5.8	0.000 000	0.003
100 %		+50	1882 500 015	8.3	0.000 000	0.004
Batt. Endpoint	3.300	+20	1882 500 015	8.2	0.000 000	0.004




MODE:	<u>LTE B25</u>
OPERATING FREQUENCY:	<u>1914,300,000 Hz</u>
CHANNEL:	<u>26683 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1914 299 994	0.0	0.000 000	0.000
100 %		-30	1914 299 989	-5.6	0.000 000	-0.003
100 %		-20	1914 299 982	-12.2	-0.000 001	-0.006
100 %		-10	1914 299 981	-12.9	-0.000 001	-0.007
100 %		0	1914 299 982	-12.5	-0.000 001	-0.007
100 %		+10	1914 299 982	-12.2	-0.000 001	-0.006
100 %		+30	1914 299 980	-14.0	-0.000 001	-0.007
100 %		+40	1914 299 982	-12.1	-0.000 001	-0.006
100 %		+50	1914 299 984	-10.7	-0.000 001	-0.006
Batt. Endpoint	3.300	+20	1914 299 999	4.9	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1913,500,000 Hz
- ▣ CHANNEL: 26675 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1913 500 014	0.0	0.000 000	0.000
100 %		-30	1913 500 028	13.8	0.000 001	0.007
100 %		-20	1913 500 021	7.5	0.000 000	0.004
100 %		-10	1913 500 004	-9.7	-0.000 001	-0.005
100 %		0	1913 500 029	15.4	0.000 001	0.008
100 %		+10	1913 500 004	-9.7	-0.000 001	-0.005
100 %		+30	1913 500 027	13.2	0.000 001	0.007
100 %		+40	1913 500 007	-7.3	0.000 000	-0.004
100 %		+50	1913 500 022	7.8	0.000 000	0.004
Batt. Endpoint	3.300	+20	1913 500 029	15.2	0.000 001	0.008




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1912,500,000 Hz
- ▣ CHANNEL: 26665 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1912 500 008	0.0	0.000 000	0.000
100 %		-30	1912 500 019	11.0	0.000 001	0.006
100 %		-20	1912 500 018	10.2	0.000 001	0.005
100 %		-10	1912 500 017	9.9	0.000 001	0.005
100 %		0	1912 500 014	6.9	0.000 000	0.004
100 %		+10	1912 500 016	8.7	0.000 000	0.005
100 %		+30	1912 500 015	7.6	0.000 000	0.004
100 %		+40	1912 500 018	10.4	0.000 001	0.005
100 %		+50	1912 500 016	8.3	0.000 000	0.004
Batt. Endpoint	3.300	+20	1912 500 016	8.2	0.000 000	0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1910,000,000 Hz
- ▣ CHANNEL: 26640 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1910 000 009	0.0	0.000 000	0.000
100 %		-30	1910 000 017	7.9	0.000 000	0.004
100 %		-20	1910 000 014	5.4	0.000 000	0.003
100 %		-10	1910 000 014	5.4	0.000 000	0.003
100 %		0	1910 000 018	8.6	0.000 000	0.005
100 %		+10	1910 000 017	7.8	0.000 000	0.004
100 %		+30	1910 000 016	6.6	0.000 000	0.003
100 %		+40	1910 000 014	5.5	0.000 000	0.003
100 %		+50	1910 000 015	6.2	0.000 000	0.003
Batt. Endpoint	3.300	+20	1910 000 017	8.4	0.000 000	0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1907,500,000 Hz
- ▣ CHANNEL: 26615 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1907 499 993	0.0	0.000 000	0.000
100 %		-30	1907 499 985	-7.6	0.000 000	-0.004
100 %		-20	1907 499 984	-8.2	0.000 000	-0.004
100 %		-10	1907 499 985	-7.2	0.000 000	-0.004
100 %		0	1907 500 002	9.0	0.000 000	0.005
100 %		+10	1907 500 001	8.1	0.000 000	0.004
100 %		+30	1907 500 003	10.3	0.000 001	0.005
100 %		+40	1907 500 003	10.4	0.000 001	0.005
100 %		+50	1907 499 999	6.4	0.000 000	0.003
Batt. Endpoint	3.300	+20	1907 500 000	7.2	0.000 000	0.004



- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1905,000,000 Hz
- ▣ CHANNEL: 26590 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1904 999 993	0.0	0.000 000	0.000
100 %		-30	1904 999 999	6.4	0.000 000	0.003
100 %		-20	1904 999 999	6.4	0.000 000	0.003
100 %		-10	1905 000 000	7.1	0.000 000	0.004
100 %		0	1905 000 003	10.3	0.000 001	0.005
100 %		+10	1905 000 003	10.2	0.000 001	0.005
100 %		+30	1905 000 003	10.0	0.000 001	0.005
100 %		+40	1905 000 000	7.7	0.000 000	0.004
100 %		+50	1904 999 999	6.7	0.000 000	0.004
Batt. Endpoint	3.300	+20	1905 000 001	8.4	0.000 000	0.004



9. TEST DATA(Sub 5 ANT)

9.1 EQUIVALENT ISOTROPIC RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1850.7	LTE B25 (1.4 MHz)	QPSK	-26.76	7.76	10.40	2.07	V	<2.00	0.041	16.09	1	0
		16-QAM	-27.52	7.00	10.40	2.07	V		0.034	15.33		
		64-QAM	-28.72	5.80	10.40	2.07	V		0.026	14.13		
		256-QAM	-31.71	2.81	10.40	2.07	V		0.013	11.14		
1882.5		QPSK	-27.09	7.89	10.40	2.21	V		0.041	16.08	1	0
		16-QAM	-27.88	7.10	10.40	2.21	V		0.034	15.29		
		64-QAM	-29.07	5.91	10.40	2.21	V		0.026	14.10		
		256-QAM	-32.05	2.93	10.40	2.21	V		0.013	11.12		
1914.3		QPSK	-27.70	7.31	10.40	2.17	V		0.036	15.54	1	0
		16-QAM	-28.37	6.64	10.40	2.17	V		0.031	14.87		
		64-QAM	-29.59	5.42	10.40	2.17	V		0.023	13.65		
		256-QAM	-32.71	2.30	10.40	2.17	V		0.011	10.53		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1851.5	LTE B25 (3 MHz)	QPSK	-26.73	7.79	10.40	2.07	V	<2.00	0.041	16.12	1	0
		16-QAM	-27.49	7.03	10.40	2.07	V		0.034	15.36		
		64-QAM	-28.69	5.83	10.40	2.07	V		0.026	14.16		
		256-QAM	-31.68	2.84	10.40	2.07	V		0.013	11.17		
1882.5		QPSK	-27.05	7.93	10.40	2.21	V		0.041	16.12	1	0
		16-QAM	-27.73	7.25	10.40	2.21	V		0.035	15.44		
		64-QAM	-28.91	6.07	10.40	2.21	V		0.027	14.26		
		256-QAM	-31.90	3.08	10.40	2.21	V		0.013	11.27		
1913.5		QPSK	-27.50	7.51	10.40	2.17	V		0.037	15.74	1	0
		16-QAM	-28.14	6.87	10.40	2.17	V		0.032	15.10		
		64-QAM	-29.36	5.65	10.40	2.17	V		0.024	13.88		
		256-QAM	-32.50	2.51	10.40	2.17	V		0.012	10.74		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1852.5	LTE B25 (5 MHz)	QPSK	-26.75	7.82	10.40	2.08	V	<2.00	0.041	16.14	1	0
		16-QAM	-27.53	7.04	10.40	2.08	V		0.034	15.36		
		64-QAM	-28.72	5.85	10.40	2.08	V		0.026	14.17		
		256-QAM	-31.70	2.87	10.40	2.08	V		0.013	11.19		
1882.5		QPSK	-27.06	7.92	10.40	2.21	V		0.041	16.11	1	0
		16-QAM	-27.69	7.29	10.40	2.21	V		0.035	15.48		
		64-QAM	-28.88	6.10	10.40	2.21	V		0.027	14.29		
		256-QAM	-31.87	3.11	10.40	2.21	V		0.013	11.30		
1912.5		QPSK	-27.43	7.58	10.40	2.17	V		0.038	15.81	1	0
		16-QAM	-28.15	6.86	10.40	2.17	V		0.032	15.09		
		64-QAM	-29.37	5.64	10.40	2.17	V		0.024	13.87		
		256-QAM	-32.44	2.57	10.40	2.17	V		0.012	10.80		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1855	LTE B25 (10 MHz)	QPSK	-26.70	7.87	10.40	2.08	V	<2.00	0.042	16.19	1	0
		16-QAM	-27.58	6.99	10.40	2.08	V		0.034	15.31		
		64-QAM	-28.75	5.82	10.40	2.08	V		0.026	14.14		
		256-QAM	-31.67	2.90	10.40	2.08	V		0.013	11.22		
1882.5		QPSK	-27.03	7.95	10.40	2.21	V		0.041	16.14	1	0
		16-QAM	-27.89	7.09	10.40	2.21	V		0.034	15.28		
		64-QAM	-29.07	5.91	10.40	2.21	V		0.026	14.10		
		256-QAM	-32.03	2.95	10.40	2.21	V		0.013	11.14		
1910		QPSK	-27.31	7.63	10.40	2.17	V		0.039	15.86	1	0
		16-QAM	-28.12	6.82	10.40	2.17	V		0.032	15.05		
		64-QAM	-29.27	5.67	10.40	2.17	V		0.025	13.90		
		256-QAM	-32.28	2.66	10.40	2.17	V		0.012	10.89		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1857.5	LTE B25 (15 MHz)	QPSK	-26.83	7.81	10.40	2.10	V	<2.00	0.041	16.11	1	0
		16-QAM	-27.64	7.00	10.40	2.10	V		0.034	15.30		
		64-QAM	-28.78	5.86	10.40	2.10	V		0.026	14.16		
		256-QAM	-31.76	2.88	10.40	2.10	V		0.013	11.18		
1882.5		QPSK	-27.07	7.91	10.40	2.21	V		0.041	16.10	1	0
		16-QAM	-27.70	7.28	10.40	2.21	V		0.035	15.47		
		64-QAM	-28.84	6.14	10.40	2.21	V		0.027	14.33		
		256-QAM	-31.94	3.04	10.40	2.21	V		0.013	11.23		
1907.5		QPSK	-27.23	7.71	10.40	2.17	V		0.039	15.94	1	0
		16-QAM	-27.88	7.06	10.40	2.17	V		0.034	15.29		
		64-QAM	-29.05	5.89	10.40	2.17	V		0.026	14.12		
		256-QAM	-32.27	2.67	10.40	2.17	V		0.012	10.90		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol	Limit	EIRP		RB	
								W	W	dBm	Size	Offset
1860	LTE B25 (20 MHz)	QPSK	-26.82	7.82	10.40	2.10	V	<2.00	0.041	16.12	1	0
		16-QAM	-27.41	7.23	10.40	2.10	V		0.036	15.53		
		64-QAM	-28.57	6.07	10.40	2.10	V		0.027	14.37		
		256-QAM	-31.50	3.14	10.40	2.10	V		0.014	11.44		
1882.5		QPSK	-27.11	7.87	10.40	2.21	V		0.040	16.06	1	0
		16-QAM	-27.53	7.45	10.40	2.21	V		0.037	15.64		
		64-QAM	-28.68	6.30	10.40	2.21	V		0.028	14.49		
		256-QAM	-31.79	3.19	10.40	2.21	V		0.014	11.38		
1905		QPSK	-27.43	7.49	10.40	2.19	V		0.037	15.70	1	0
		16-QAM	-28.09	6.83	10.40	2.19	V		0.032	15.04		
		64-QAM	-29.28	5.64	10.40	2.19	V		0.024	13.85		
		256-QAM	-32.47	2.45	10.40	2.19	V		0.012	10.66		

9.2 RADIATED SPURIOUS EMISSIONS

■ MOD: LTE B25
 ■ MODULATION SIGNAL: 10 MHz QPSK
 ■ DISTANCE: 3 meters
 ■ LIMIT: -13 dBm

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	RB	
								Size	Offset
26090 (1855.0)	3 710.00	-33.41	12.28	-50.59	3.08	H	-41.39	1	0
	5 565.00	-44.91	13.05	-56.91	3.88	H	-47.74		
	7 420.00	-45.71	10.78	-48.66	4.55	H	-42.43		
26365 (1882.5)	3 765.00	-37.70	12.22	-53.54	3.11	H	-44.43	1	0
	5 647.50	-44.67	13.12	-56.84	3.96	H	-47.68		
	7 530.00	-45.49	10.85	-48.13	4.60	H	-41.88		
26640 (1910.0)	3 820.00	-37.07	12.16	-53.72	3.19	H	-44.75	1	0
	5 730.00	-44.34	13.04	-56.61	4.00	H	-47.57		
	7 640.00	-45.28	11.21	-48.11	4.68	H	-41.58		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
25	1.4 MHz	1882.5	QPSK	6	0	5.54
			16-QAM			6.35
			64-QAM			6.38
			256-QAM			6.10
	3 MHz		QPSK	15		5.57
			16-QAM			6.23
			64-QAM			6.45
			256-QAM			6.26
	5 MHz		QPSK	25		5.69
			16-QAM			6.35
			64-QAM			6.44
			256-QAM			6.22
	10 MHz		QPSK	50		5.73
			16-QAM			6.41
			64-QAM			6.48
			256-QAM			6.20
	15 MHz		QPSK	75		5.68
			16-QAM			6.34
			64-QAM			6.40
			256-QAM			6.18
	20 MHz		QPSK	100		5.72
			16-QAM			6.38
			64-QAM			6.50
			256-QAM			6.29

Note:

1. Plots of the EUT's Peak- to- Average Ratio are shown Page 198 ~ 221.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
25	1.4 MHz	1882.5	QPSK	6	0	1.0990
			16-QAM			1.0946
			64-QAM			1.0923
			256-QAM			1.0949
	3 MHz		QPSK	15		2.7181
			16-QAM			2.7062
			64-QAM			2.7060
			256-QAM			2.7124
	5 MHz		QPSK	25		4.5321
			16-QAM			4.5134
			64-QAM			4.5258
			256-QAM			4.5576
	10 MHz		QPSK	50		9.0018
			16-QAM			9.0024
			64-QAM			9.0017
			256-QAM			9.0200
	15 MHz		QPSK	75		13.458
			16-QAM			13.469
			64-QAM			13.483
			256-QAM			13.503
	20 MHz		QPSK	100		18.010
			16-QAM			17.930
			64-QAM			17.919
			256-QAM			17.967

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 222 ~ 245.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
25	1.4	1850.70	5.2643	28.591	-67.802	-39.211	-13.00
		1882.50	4.0080	27.976	-66.631	-38.655	
		1914.30	8.5743	28.591	-67.337	-38.746	
	3	1851.50	9.9801	28.591	-67.695	-39.104	
		1882.50	4.0579	27.976	-67.047	-39.071	
		1913.50	9.9502	28.591	-67.492	-38.901	
	5	1852.50	9.9003	28.591	-68.388	-39.797	
		1882.50	4.9253	27.976	-66.871	-38.895	
		1912.50	9.9202	28.591	-68.329	-39.738	
	10	1855.00	6.0519	28.591	-67.291	-38.700	
		1882.50	7.1984	28.591	-67.359	-38.768	
		1910.00	4.9253	27.976	-67.800	-39.824	
	15	1857.50	3.7388	27.976	-67.929	-39.953	
		1882.50	8.2553	28.591	-67.523	-38.932	
		1907.50	9.7607	28.591	-67.732	-39.141	
	20	1860.00	4.9452	27.976	-66.947	-38.971	
		1882.50	9.2523	28.591	-67.534	-38.943	
		1905.00	9.5713	28.591	-67.940	-39.349	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 246 ~ 281.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor(dB) = Cable Loss + Ext. Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


9.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 282 ~ 317.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B25</u>
OPERATING FREQUENCY:	<u>1850,700,000 Hz</u>
CHANNEL:	<u>26047 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.900	+20(Ref)	1850 699 997	0.0	0.000 000	0.000
100 %		-30	1850 699 992	-5.6	0.000 000	-0.003
100 %		-20	1850 699 992	-5.1	0.000 000	-0.003
100 %		-10	1850 699 995	-2.7	0.000 000	-0.001
100 %		0	1850 700 000	2.7	0.000 000	0.001
100 %		+10	1850 699 994	-3.5	0.000 000	-0.002
100 %		+30	1850 700 000	2.3	0.000 000	0.001
100 %		+40	1850 699 992	-5.0	0.000 000	-0.003
100 %		+50	1850 699 995	-2.5	0.000 000	-0.001
Batt. Endpoint	3.300	+20	1850 699 994	-3.8	0.000 000	-0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1851,500,000 Hz
- ▣ CHANNEL: 26055 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1851 500 004	0.0	0.000 000	0.000
100 %		-30	1851 500 001	-2.5	0.000 000	-0.001
100 %		-20	1851 500 002	-1.5	0.000 000	-0.001
100 %		-10	1851 500 002	-2.1	0.000 000	-0.001
100 %		0	1851 500 007	2.7	0.000 000	0.001
100 %		+10	1851 500 007	2.7	0.000 000	0.001
100 %		+30	1851 500 006	2.5	0.000 000	0.001
100 %		+40	1851 500 002	-1.6	0.000 000	-0.001
100 %		+50	1851 500 007	3.1	0.000 000	0.002
Batt. Endpoint	3.300	+20	1851 500 008	3.7	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1852,500,000 Hz
- ▣ CHANNEL: 26065 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1852 500 004	0.0	0.000 000	0.000
100 %		-30	1852 500 008	3.8	0.000 000	0.002
100 %		-20	1852 500 007	2.9	0.000 000	0.002
100 %		-10	1852 500 002	-2.5	0.000 000	-0.001
100 %		0	1852 500 009	4.5	0.000 000	0.002
100 %		+10	1852 500 007	2.5	0.000 000	0.001
100 %		+30	1852 500 008	3.7	0.000 000	0.002
100 %		+40	1852 500 007	3.2	0.000 000	0.002
100 %		+50	1852 500 008	3.4	0.000 000	0.002
Batt. Endpoint	3.300	+20	1852 500 007	2.8	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1855,000,000 Hz
- ▣ CHANNEL: 26090 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1855 000 005	0.0	0.000 000	0.000
100 %		-30	1855 000 007	2.0	0.000 000	0.001
100 %		-20	1855 000 007	2.3	0.000 000	0.001
100 %		-10	1855 000 007	2.2	0.000 000	0.001
100 %		0	1855 000 009	4.1	0.000 000	0.002
100 %		+10	1855 000 009	4.3	0.000 000	0.002
100 %		+30	1855 000 008	3.1	0.000 000	0.002
100 %		+40	1855 000 007	2.6	0.000 000	0.001
100 %		+50	1855 000 007	2.6	0.000 000	0.001
Batt. Endpoint	3.300	+20	1855 000 009	4.2	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1857,500,000 Hz
- ▣ CHANNEL: 26115 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1857 500 003	0.0	0.000 000	0.000
100 %		-30	1857 500 006	3.2	0.000 000	0.002
100 %		-20	1857 500 006	3.1	0.000 000	0.002
100 %		-10	1857 500 005	2.6	0.000 000	0.001
100 %		0	1857 500 005	1.9	0.000 000	0.001
100 %		+10	1857 500 007	4.4	0.000 000	0.002
100 %		+30	1857 500 005	2.2	0.000 000	0.001
100 %		+40	1857 500 006	3.5	0.000 000	0.002
100 %		+50	1857 500 006	2.9	0.000 000	0.002
Batt. Endpoint	3.300	+20	1857 500 006	3.1	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1860,000,000 Hz
- ▣ CHANNEL: 26140 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1860 000 003	0.0	0.000 000	0.000
100 %		-30	1860 000 005	2.6	0.000 000	0.001
100 %		-20	1860 000 006	3.0	0.000 000	0.002
100 %		-10	1860 000 006	3.0	0.000 000	0.002
100 %		0	1860 000 006	3.1	0.000 000	0.002
100 %		+10	1860 000 006	3.4	0.000 000	0.002
100 %		+30	1860 000 007	3.7	0.000 000	0.002
100 %		+40	1860 000 006	3.3	0.000 000	0.002
100 %		+50	1860 000 005	2.3	0.000 000	0.001
Batt. Endpoint	3.300	+20	1860 000 006	2.9	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 499 998	0.0	0.000 000	0.000
100 %		-30	1882 499 996	-2.2	0.000 000	-0.001
100 %		-20	1882 500 001	2.3	0.000 000	0.001
100 %		-10	1882 500 001	2.4	0.000 000	0.001
100 %		0	1882 500 001	2.7	0.000 000	0.001
100 %		+10	1882 500 000	2.2	0.000 000	0.001
100 %		+30	1882 499 996	-1.8	0.000 000	-0.001
100 %		+40	1882 500 001	2.7	0.000 000	0.001
100 %		+50	1882 499 994	-4.0	0.000 000	-0.002
Batt. Endpoint	3.300	+20	1882 500 001	2.4	0.000 000	0.001




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 004	0.0	0.000 000	0.000
100 %		-30	1882 500 001	-2.8	0.000 000	-0.001
100 %		-20	1882 500 006	1.9	0.000 000	0.001
100 %		-10	1882 500 006	2.4	0.000 000	0.001
100 %		0	1882 500 008	3.7	0.000 000	0.002
100 %		+10	1882 500 006	1.8	0.000 000	0.001
100 %		+30	1882 500 006	2.3	0.000 000	0.001
100 %		+40	1882 500 007	2.9	0.000 000	0.002
100 %		+50	1882 500 006	2.3	0.000 000	0.001
Batt. Endpoint	3.300	+20	1882 500 007	2.7	0.000 000	0.001




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 005	0.0	0.000 000	0.000
100 %		-30	1882 500 007	2.6	0.000 000	0.001
100 %		-20	1882 500 007	2.5	0.000 000	0.001
100 %		-10	1882 500 008	3.5	0.000 000	0.002
100 %		0	1882 500 007	2.8	0.000 000	0.001
100 %		+10	1882 500 008	2.9	0.000 000	0.002
100 %		+30	1882 500 007	2.6	0.000 000	0.001
100 %		+40	1882 500 008	3.3	0.000 000	0.002
100 %		+50	1882 500 008	3.7	0.000 000	0.002
Batt. Endpoint	3.300	+20	1882 500 008	3.6	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 002	0.0	0.000 000	0.000
100 %		-30	1882 500 005	2.3	0.000 000	0.001
100 %		-20	1882 500 005	2.5	0.000 000	0.001
100 %		-10	1882 500 006	3.7	0.000 000	0.002
100 %		0	1882 500 005	2.8	0.000 000	0.001
100 %		+10	1882 500 005	2.5	0.000 000	0.001
100 %		+30	1882 500 005	2.7	0.000 000	0.001
100 %		+40	1882 500 006	3.9	0.000 000	0.002
100 %		+50	1882 500 005	2.6	0.000 000	0.001
Batt. Endpoint	3.300	+20	1882 500 004	2.0	0.000 000	0.001




MODE:	<u>LTE B25</u>
OPERATING FREQUENCY:	<u>1882,500,000 Hz</u>
CHANNEL:	<u>26365 (15 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 003	0.0	0.000 000	0.000
100 %		-30	1882 500 006	2.8	0.000 000	0.001
100 %		-20	1882 500 005	2.5	0.000 000	0.001
100 %		-10	1882 500 007	4.3	0.000 000	0.002
100 %		0	1882 500 005	2.2	0.000 000	0.001
100 %		+10	1882 500 005	2.3	0.000 000	0.001
100 %		+30	1882 500 005	2.7	0.000 000	0.001
100 %		+40	1882 500 005	2.5	0.000 000	0.001
100 %		+50	1882 500 006	3.2	0.000 000	0.002
Batt. Endpoint	3.300	+20	1882 500 004	1.6	0.000 000	0.001




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1882,500,000 Hz
- ▣ CHANNEL: 26365 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1882 500 003	0.0	0.000 000	0.000
100 %		-30	1882 500 006	3.1	0.000 000	0.002
100 %		-20	1882 500 005	2.6	0.000 000	0.001
100 %		-10	1882 500 005	2.4	0.000 000	0.001
100 %		0	1882 500 005	2.5	0.000 000	0.001
100 %		+10	1882 500 005	2.5	0.000 000	0.001
100 %		+30	1882 500 005	2.5	0.000 000	0.001
100 %		+40	1882 500 005	2.0	0.000 000	0.001
100 %		+50	1882 500 005	2.8	0.000 000	0.001
Batt. Endpoint	3.300	+20	1882 500 005	2.7	0.000 000	0.001




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1914,300,000 Hz
- ▣ CHANNEL: 26683 (1.4 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1914 299 996	0.0	0.000 000	0.000
100 %		-30	1914 300 001	4.6	0.000 000	0.002
100 %		-20	1914 299 999	3.1	0.000 000	0.002
100 %		-10	1914 300 001	4.8	0.000 000	0.003
100 %		0	1914 300 000	3.6	0.000 000	0.002
100 %		+10	1914 299 992	-4.4	0.000 000	-0.002
100 %		+30	1914 300 001	4.7	0.000 000	0.002
100 %		+40	1914 299 992	-4.3	0.000 000	-0.002
100 %		+50	1914 300 000	4.1	0.000 000	0.002
Batt. Endpoint	3.300	+20	1914 300 000	4.2	0.000 000	0.002




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1913,500,000 Hz
- ▣ CHANNEL: 26675 (3 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1913 500 004	0.0	0.000 000	0.000
100 %		-30	1913 500 014	10.5	0.000 001	0.005
100 %		-20	1913 500 000	-4.3	0.000 000	-0.002
100 %		-10	1913 500 010	5.8	0.000 000	0.003
100 %		0	1913 500 015	11.4	0.000 001	0.006
100 %		+10	1913 500 009	5.5	0.000 000	0.003
100 %		+30	1913 500 014	10.5	0.000 001	0.005
100 %		+40	1913 500 015	10.7	0.000 001	0.006
100 %		+50	1913 500 008	4.4	0.000 000	0.002
Batt. Endpoint	3.300	+20	1913 500 009	5.2	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1912,500,000 Hz
- ▣ CHANNEL: 26665 (5 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1912 500 005	0.0	0.000 000	0.000
100 %		-30	1912 500 010	4.5	0.000 000	0.002
100 %		-20	1912 500 012	7.0	0.000 000	0.004
100 %		-10	1912 500 011	5.3	0.000 000	0.003
100 %		0	1912 500 012	7.1	0.000 000	0.004
100 %		+10	1912 500 012	7.2	0.000 000	0.004
100 %		+30	1912 500 011	5.8	0.000 000	0.003
100 %		+40	1912 500 009	4.0	0.000 000	0.002
100 %		+50	1912 500 010	4.6	0.000 000	0.002
Batt. Endpoint	3.300	+20	1912 500 012	6.3	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1910,000,000 Hz
- ▣ CHANNEL: 26640 (10 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1910 000 003	0.0	0.000 000	0.000
100 %		-30	1910 000 008	4.1	0.000 000	0.002
100 %		-20	1910 000 009	5.5	0.000 000	0.003
100 %		-10	1910 000 010	6.3	0.000 000	0.003
100 %		0	1910 000 009	5.2	0.000 000	0.003
100 %		+10	1910 000 009	5.6	0.000 000	0.003
100 %		+30	1910 000 009	5.9	0.000 000	0.003
100 %		+40	1910 000 009	5.7	0.000 000	0.003
100 %		+50	1910 000 008	4.8	0.000 000	0.003
Batt. Endpoint	3.300	+20	1910 000 010	6.8	0.000 000	0.004




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1907,500,000 Hz
- ▣ CHANNEL: 26615 (15 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1907 500 006	0.0	0.000 000	0.000
100 %		-30	1907 500 012	5.8	0.000 000	0.003
100 %		-20	1907 500 010	3.3	0.000 000	0.002
100 %		-10	1907 500 010	4.0	0.000 000	0.002
100 %		0	1907 500 002	-4.2	0.000 000	-0.002
100 %		+10	1907 500 013	6.5	0.000 000	0.003
100 %		+30	1907 500 002	-3.8	0.000 000	-0.002
100 %		+40	1907 500 009	2.9	0.000 000	0.002
100 %		+50	1907 500 011	5.0	0.000 000	0.003
Batt. Endpoint	3.300	+20	1907 500 011	5.2	0.000 000	0.003




- ▣ MODE: LTE B25
- ▣ OPERATING FREQUENCY: 1905,000,000 Hz
- ▣ CHANNEL: 26590 (20 MHz)
- ▣ REFERENCE VOLTAGE: 3.900 VDC
- ▣ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	1905 000 007	0.0	0.000 000	0.000
100 %		-30	1905 000 013	6.7	0.000 000	0.004
100 %		-20	1905 000 012	5.7	0.000 000	0.003
100 %		-10	1905 000 014	6.9	0.000 000	0.004
100 %		0	1905 000 011	4.5	0.000 000	0.002
100 %		+10	1905 000 013	6.2	0.000 000	0.003
100 %		+30	1905 000 012	5.4	0.000 000	0.003
100 %		+40	1905 000 010	3.2	0.000 000	0.002
100 %		+50	1905 000 013	6.0	0.000 000	0.003
Batt. Endpoint	3.300	+20	1905 000 012	5.3	0.000 000	0.003




10. TEST PLOTS(Main 2 ANT)


LTE B25_1.4M_PAR_Mid_QPSK_FullRB




LTE B25_1.4M_PAR_Mid_16QAM_FullRB




LTE B25_1.4M_PAR_Mid_64QAM_FullRB




LTE B25_1.4M_PAR_Mid_256QAM_FullRB




LTE B25_3 M_PAR_Mid_QPSK_FullRB




LTE B25_3 M_PAR_Mid_16QAM_FullRB




LTE B25_3 M_PAR_Mid_64QAM_FullRB




LTE B25_3 M_PAR_Mid_256QAM_FullRB




LTE B25_5 M_PAR_Mid_QPSK_FullRB




LTE B25_5 M_PAR_Mid_16QAM_FullRB




LTE B25_5 M_PAR_Mid_64QAM_FullRB




LTE B25_5 M_PAR_Mid_256QAM_FullRB




LTE B25_10 M_PAR_Mid_QPSK_FullRB




LTE B25_10 M_PAR_Mid_16QAM_FullRB




LTE B25_10 M_PAR_Mid_64QAM_FullRB




LTE B25_10 M_PAR_Mid_256QAM_FullRB




LTE B25_15 M_PAR_Mid_QPSK_FullRB




LTE B25_15 M_PAR_Mid_16QAM_FullRB




LTE B25_15 M_PAR_Mid_64QAM_FullRB




LTE B25_15 M_PAR_Mid_256QAM_FullRB




LTE B25_20 M_PAR_Mid_QPSK_FullRB




LTE B25_20 M_PAR_Mid_16QAM_FullRB




LTE B25_20 M_PAR_Mid_64QAM_FullRB




LTE B25_20 M_PAR_Mid_256QAM_FullRB




LTE B25_1.4M_OBW_Mid_QPSK_FullRB




LTE B25_1.4M_OBW_Mid_16QAM_FullRB




LTE B25_1.4M_OBW_Mid_64QAM_FullRB




LTE B25_1.4M_OBW_Mid_256QAM_FullRB




LTE B25_3 M_OBW_Mid_QPSK_FullRB




LTE B25_3 M_OBW_Mid_16QAM_FullRB




LTE B25_3 M_OBW_Mid_64QAM_FullRB




LTE B25_3 M_OBW_Mid_256QAM_FullRB




LTE B25_5 M_OBW_Mid_QPSK_FullRB




LTE B25_5 M_OBW_Mid_16QAM_FullRB




LTE B25_5 M_OBW_Mid_64QAM_FullRB




LTE B25_5 M_OBW_Mid_256QAM_FullRB




LTE B25_10 M_OBW_Mid_QPSK_FullRB




LTE B25_10 M_OBW_Mid_16QAM_FullRB




LTE B25_10 M_OBW_Mid_64QAM_FullRB




LTE B25_10 M_OBW_Mid_256QAM_FullRB




LTE B25_15 M_OBW_Mid_QPSK_FullRB




LTE B25_15 M_OBW_Mid_16QAM_FullRB




LTE B25_15 M_OBW_Mid_64QAM_FullRB




LTE B25_15 M_OBW_Mid_256QAM_FullRB




LTE B25_20 M_OBW_Mid_QPSK_FullRB




LTE B25_20 M_OBW_Mid_16QAM_FullRB




LTE B25_20 M_OBW_Mid_64QAM_FullRB




LTE B25_20 M_OBW_Mid_256QAM_FullRB



LTE B25_1.4M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B25_1.4M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B25_1.4M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B25_3 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



LTE B25_3 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B25_3 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B25_5 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B25_5 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B25_5 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B25_10 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



LTE B25_10 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B25_10 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B25_15 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB



LTE B25_15 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



LTE B25_15 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



LTE B25_20 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB

