

TEST REPORT

FCC LTE B12 Test for SM-F766U
Certification

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2504-FC006-R1

DATE OF ISSUE
May 23, 2025

Tested by
Jae Mun Do



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

**HCT CO.,LTD.**

2-6, 73, 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea
Tel. +82 31 645 6300 Fax. +82 31 645 6401

TEST REPORT

REPORT NO.

HCT-RF-2504-FC006-R1

DATE OF ISSUE

May 23, 2025

Additional Model

SM-F766U1

Applicant**SAMSUNG Electronics Co., Ltd.**

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

Mobile Phone

Model Name

SM-F766U

Date of Test

February 24, 2025 ~ April 21, 2025

FCC ID

A3LSMF766U

Location of Test

☒ Permanent Testing Lab ☐ On Site Testing

(Address: 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea)

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

Test Standard Used

FCC Rule Part: § 27

Test Results

PASS

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	April 22, 2025	Initial Release
1	May 23, 2025	Revised the Power Supply Voltage. (DC 3.88 V → DC 3.90 V)

Notice

Content

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section § 2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C.853(a)

The results shown in this test report only apply to the sample(s), as received, provided by the applicant, unless otherwise stated.

The test results have only been applied with the test methods required by the standard(s).

The laboratory is not accredited for the test results marked *.

Information provided by the applicant is marked **.

Test results provided by external providers are marked ***.

When confirmation of authenticity of this test report is required, please contact www.hct.co.kr

The test results in this test report are not associated with the ((KS Q) ISO/IEC 17025) accreditation by KOLAS (Korea Laboratory Accreditation Scheme) / A2LA (American Association for Laboratory Accreditation) that are under the ILAC (International Laboratory Accreditation Cooperation) Mutual Recognition Agreement (MRA).

CONTENTS

1. GENERAL INFORMATION	6
1.1 MAXIMUM OUTPUT POWER	7
2. INTRODUCTION	8
2.1. DESCRIPTION OF EUT	8
2.2. MEASURING INSTRUMENT CALIBRATION	8
2.3. TEST FACILITY	8
3. DESCRIPTION OF TESTS	9
3.1 TEST PROCEDURE	9
3.2 RADIATED POWER.....	10
3.3 RADIATED SPURIOUS EMISSIONS.....	11
3.4 OCCUPIED BANDWIDTH.....	12
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	13
3.6 BAND EDGE	14
3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	16
3.8 PEAK- TO- AVERAGE RATIO	17
3.9 WORST CASE(RADIATED TEST)	19
3.10 WORST CASE(CONDUCTED TEST).....	20
4. LIST OF TEST EQUIPMENT.....	21
5. MEASUREMENT UNCERTAINTY.....	22
6. SUMMARY OF TEST RESULTS.....	23
7. SAMPLE CALCULATION	24
8. TEST DATA(Main 1 ANT).....	26
8.1 EFFECTIVE RADIATED POWER.....	26
8.2 RADIATED SPURIOUS EMISSIONS.....	28
8.3 PEAK-TO-AVERAGE RATIO	29
8.4 OCCUPIED BANDWIDTH.....	30
8.5 CONDUCTED SPURIOUS EMISSIONS	31
8.6 BAND EDGE	31
8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	32
9. TEST DATA (Sub 1 ANT)	44
9.1 EFFECTIVE RADIATED POWER.....	44
9.2 RADIATED SPURIOUS EMISSIONS.....	46
9.3 PEAK-TO-AVERAGE RATIO	47
9.4 OCCUPIED BANDWIDTH.....	48
9.5 CONDUCTED SPURIOUS EMISSIONS	49
9.6 BAND EDGE	49
9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	50

10. TEST PLOTS(Main 1 Ant).....	62
11. TEST PLOTS(Sub 1 ANT)	135
12. ANNEX A_ TEST SETUP PHOTO	208

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMF766U
Application Type:	Certification
FCC Classification:	PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§ 27
EUT Type:	Mobile Phone
Model(s):	SM-F766U
Additional Model(s)	SM-F766U1
Tx Frequency:	699.7 MHz – 715.3 MHz (LTE – Band 12 (1.4 MHz)) 700.5 MHz – 714.5 MHz (LTE – Band 12 (3 MHz)) 701.5 MHz – 713.5 MHz (LTE – Band 12 (5 MHz)) 704.0 MHz – 711.0 MHz (LTE – Band 12 (10 MHz))
Date(s) of Tests:	February 24, 2025 ~ April 21, 2025
Serial number:	Radiated : R3CY209A7NT(Main 1 Ant), R3CY207MAGN(Sub 1 Ant) Conducted : R3CY209A7CH(Main 1 ANT), R3CY209A7FF(Sub 1 ANT)
Antenna Information	Please refer to the Antenna Specification document.

1.1 MAXIMUM OUTPUT POWER

Main 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 12 (1.4)	699.7 – 715.3	1M10G7D	QPSK	0.124	20.93
		1M09W7D	16-QAM	0.091	19.60
		1M10W7D	64-QAM	0.070	18.45
		1M10W7D	256-QAM	0.039	15.96
LTE – Band 12 (3)	700.5 – 714.5	2M72G7D	QPSK	0.119	20.77
		2M70W7D	16-QAM	0.089	19.48
		2M70W7D	64-QAM	0.068	18.32
		2M71W7D	256-QAM	0.037	15.67
LTE – Band 12 (5)	701.5 – 713.5	4M54G7D	QPSK	0.120	20.80
		4M52W7D	16-QAM	0.088	19.44
		4M53W7D	64-QAM	0.068	18.33
		4M57W7D	256-QAM	0.038	15.85
LTE – Band 12 (10)	704.0 – 711.0	9M01G7D	QPSK	0.119	20.75
		9M00W7D	16-QAM	0.086	19.36
		8M99W7D	64-QAM	0.067	18.24
		9M01W7D	256-QAM	0.038	15.78

Sub 1 ANT

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	ERP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band 12 (1.4)	699.7 – 715.3	1M10G7D	QPSK	0.043	16.30
		1M09W7D	16-QAM	0.032	15.05
		1M09W7D	64-QAM	0.025	13.97
		1M10W7D	256-QAM	0.014	11.54
LTE – Band 12 (3)	700.5 – 714.5	2M72G7D	QPSK	0.042	16.28
		2M70W7D	16-QAM	0.031	14.95
		2M70W7D	64-QAM	0.025	13.93
		2M71W7D	256-QAM	0.014	11.47
LTE – Band 12 (5)	701.5 – 713.5	4M53G7D	QPSK	0.043	16.31
		4M51W7D	16-QAM	0.031	14.89
		4M53W7D	64-QAM	0.024	13.80
		4M56W7D	256-QAM	0.014	11.38
LTE – Band 12 (10)	704.0 – 711.0	9M00G7D	QPSK	0.041	16.13
		8M98W7D	16-QAM	0.030	14.75
		8M99W7D	64-QAM	0.023	13.68
		8M98W7D	256-QAM	0.013	11.25

2. INTRODUCTION

2.1. DESCRIPTION OF EUT

Please refer to the [2G3G] Test Report.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, Republic of Korea**

3. DESCRIPTION OF TESTS

3.1 TEST PROCEDURE

Test Description	Test Procedure Used
Occupied Bandwidth	- KDB 971168 D01 v03r01 – Section 4.3 - ANSI C63.26-2015 – Section 5.4.4
Band Edge	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Spurious and Harmonic Emissions at Antenna Terminal	- KDB 971168 D01 v03r01 – Section 6.0 - ANSI C63.26-2015 – Section 5.7
Conducted Output Power	- N/A (See SAR Report)
Peak- to- Average Ratio	- KDB 971168 D01 v03r01 – Section 5.7 - ANSI C63.26-2015 – Section 5.2.3.4
Frequency stability	- ANSI C63.26-2015 – Section 5.6
Radiated Power	- ANSI C63.26-2015 – Section 5.2.4.4 - KDB 971168 D01 v03r01 – Section 5.8
Radiated Spurious and Harmonic Emissions	- ANSI C63.26-2015 – Section 5.5.3 - KDB 971168 D01 v03r01 – Section 5.8

3.2 RADIATED POWER

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna.

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation.
2. RBW = 1 – 5 % of the expected OBW, not to exceed 1 MHz
3. VBW $\geq$ 3 x RBW
4. Span = 1.5 times the OBW
5. No. of sweep points > 2 x span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto".
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation.
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

Test Note

1. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission.
2. A half wave dipole is then substituted in place of the EUT. For emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_d \text{ (dBm)} = P_g \text{ (dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.

3. The maximum value is calculated by adding the forward power to the calibrated source plus its appropriate gain value.

These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

4. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
5. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

3.3 RADIATED SPURIOUS EMISSIONS

Test Overview

Radiated tests are performed in the Fully-anechoic chamber.

Radiated Spurious Emission Measurements at 3 meters by Substitution Method.

Test Settings

1. RBW = 100 kHz for emissions below 1 GHz and 1 MHz for emissions above 1 GHz
2. VBW $\geq 3 \times$ RBW
3. Span = 1.5 times the OBW
4. No. of sweep points $> 2 \times$ span / RBW
5. Detector = Peak
6. Trace mode = Max Hold
7. The trace was allowed to stabilize
8. Test channel : Low/ Middle/ High
9. Frequency range : We are performed all frequency to 10th harmonics from 9 kHz.

Test Note

1. Measurements value show only up to 3 maximum emissions noted, or would be lesser
if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit)
and considered that's already beyond the background noise floor.
2. The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
The worst case emissions are reported with the EUT positioning, modulations, RB sizes and offsets,
and channel bandwidth configurations shown in the test data
3. For spurious emissions above 1 GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is
driven by a signal generator and the previously recorded signal was duplicated.
The spurious emissions is calculated by the following formula;


$$\text{Result}_{(\text{dBm})} = P_{\text{g}}_{(\text{dBm})} - \text{cable loss}_{(\text{dB})} + \text{antenna gain}_{(\text{dBi})}$$

Where: P_{g} is the generator output power into the substitution antenna.

If the fundamental frequency is below 1 GHz, RF output power has been converted to EIRP.

$$\text{EIRP}_{(\text{dBm})} = \text{ERP}_{(\text{dBm})} + 2.15$$

3.4 OCCUPIED BANDWIDTH.



Test setup

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

The EUT makes a call to the communication simulator.


The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99 % occupied bandwidth and the 26 dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5 % of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5 % of the 99 % occupied bandwidth observed in Step 7

3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL



Test setup

Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.


All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. RBW = 1 MHz
2. VBW $\geq$ 3 MHz
3. Detector = Peak
4. Trace Mode = Max Hold
5. Sweep time = auto
6. Number of points in sweep $\geq$ 2 x Span / RBW

3.6 BAND EDGE



Test setup

Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1 % of the emission bandwidth
4. VBW > 3 x RBW
5. Detector = RMS
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = trace average
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Notes

According to FCC 22.917, 24.238, 27.53 specified that power of any emission outside of The authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

All measurements were done at 2 channels (low and high operational frequency range.)

The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

Where $\text{Margin} < 1$ dB the emission level is either corrected by $10 \log(1 \text{ MHz} / \text{RB})$ or the emission is integrated over a 1 MHz bandwidth to determine the final result. When using the integration method the integration window is either centered on the emission or, for emissions at the band edge, centered by an offset of 500 kHz from the block edge so that the integration window is the 1 MHz adjacent to the block edge.

3.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE



Test setup

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26-2015.

The frequency stability of the transmitter is measured by:

1. Temperature:

The temperature is varied from -30 °C to +50 °C in 10 °C increments using an environmental chamber.


2. Primary Supply Voltage:

- .- Unless otherwise specified, vary primary supply voltage from 85 % to 115 % of the nominal value for other than hand carried battery equipment.
- .- For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.

Test Settings

1. The carrier frequency of the transmitter is measured at room temperature (20 °C to provide a reference).
2. The equipment is turned on in a “standby” condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10 °C intervals ranging from -30 °C to +50 °C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

3.8 PEAK- TO- AVERAGE RATIO



Test setup

① CCDF Procedure for PAPR

Test Settings

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Set the measurement interval as follows:
 - .- for continuous transmissions, set to 1 ms,
 - .- or burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
4. Record the maximum PAPR level associated with a probability of 0.1 %.

② Alternate Procedure for PAPR

Use one of the procedures presented in 5.2(ANSI C63.26-2015) to measure the total peak power and record as P_{Pk} .

Use one of the applicable procedures presented 5.2(ANSI C63.26-2015) to measure the total average power and record as P_{Avg} . Determine the P.A.R. from:

$$P.A.R. (dB) = P_{Pk} (dBm) - P_{Avg} (dBm) \quad (P_{Avg} = \text{Average Power} + \text{Duty cycle Factor})$$

Test Settings(Peak Power)

The measurement instrument must have a RBW that is greater than or equal to the OBW of the signal to be measured and a VBW $\geq 3 \times$ RBW.

1. Set the RBW $\geq$ OBW.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 2 \times$ OBW.
4. Sweep time $\geq 10 \times$ (number of points in sweep) $\times$ (transmission symbol period).
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the peak amplitude level.

Test Settings(Average Power)

1. Set span to $2 \times$ to $3 \times$ the OBW.
2. Set RBW $\geq$ OBW.
3. Set VBW $\geq 3 \times$ RBW.
4. Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
5. Sweep time:
Set $\geq [10 \times (\text{number of points in sweep}) \times (\text{transmission period})]$ for single sweep (automation-compatible) measurement. The transmission period is the (on + off) time.
6. Detector = power averaging (rms).
7. Set sweep trigger to "free run."
8. Trace average at least 100 traces in power averaging (rms) mode if sweep is set to auto-couple. (To accurately determine the average power over the on and off period of the transmitter, it can be necessary to increase the number of traces to be averaged above 100 or, if using a manually configured sweep time, increase the sweep time.)
9. Use the peak marker function to determine the maximum amplitude level.
10. Add $[10 \log (1/\text{duty cycle})]$ to the measured maximum power level to compute the average power during continuous transmission. For example, add $[10 \log (1/0.25)] = 6 \text{ dB}$ if the duty cycle is a constant 25 %.

3.9 WORST CASE(RADIATED TEST)

- The EUT was tested in three orthogonal planes(X, Y, Z) and in all possible test configurations and positioning.
- All modes of operation were investigated and the worst case configuration results are reported.
Mode : Stand alone, Stand alone + External accessories (Earphone, AC adapter, etc)
Worst case : Stand alone
- All simultaneous transmission scenarios of operation were investigated, and the test results showed no additional significant emissions relative to the least restrictive limit were observed.
Therefore, only the worst case(stand-alone) results were reported.
- In the case of radiated spurious emissions, all bandwidth of operation were investigated and the worst case bandwidth results are reported. (Worst case : 1.4 MHz(Main 1 ANT), 5 MHz(Sub 1 ANT))
- The EUT was tested in three modes(Open, Half-open, Closed), the worst case configuration results are reported. (Worst case: Open mode)
- The worst case is reported with the EUT positioning, modulations, and paging service configurations shown in the test data
- Please refer to the table below.
- SM-F766U & additional models were tested and the worst case results are reported.
(Worst case : SM- SM-F766U)

[Main 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 8.1		Y
Radiated Spurious and Harmonic Emissions	QPSK	See Section 8.2		Z

[Sub 1 ANT Worst case]

Test Description	Modulation	RB size	RB offset	Axis
Effective Radiated Power	QPSK, 16QAM, 64QAM, 256QAM	See Section 9.1		Y
Radiated Spurious and Harmonic Emissions	QPSK	See Section 9.2		Z

3.10 WORST CASE(CONDUCTED TEST)

- All modes of operation were investigated and the worst case configuration results are reported.
 - SM-F766U & additional models were tested and the worst case results are reported.
- (Worst case : SM- SM-F766U)

[Worst case]

Test Description	Modulation	Bandwidth (MHz)	Frequency	RB size	RB offset
Occupied Bandwidth	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10	Mid	Full RB	0
PEAK- TO- AVERAGE RATIO	QPSK, 16QAM, 64QAM, 256QAM	1.4, 3, 5, 10	Mid	Full RB	0
Band Edge	QPSK	1.4	Low	1	0
			High	1	5
		3	Low	1	0
			High	1	14
		5	Low	1	0
			High	1	24
		10	Low	1	0
			High	1	49
Band Edge	QPSK	1.4, 3, 5, 10	Low, High	Full RB	0
		1.4, 3, 5, 10	Low, Mid, High	1	0

4. LIST OF TEST EQUIPMENT

Equipment	Model	Manufacture	Serial No.	Due to Calibration	Calibration Interval
RF Switching System	Switch box(1 G HPF+LNA)	HCT CO., LTD.,	F2L2	12/12/2025	Annual
RF Switching System	Switch box(3 G HPF+LNA)	HCT CO., LTD.,	F2L3	12/12/2025	Annual
RF Switching System	Switch box(LNA)	HCT CO., LTD.,	F2L5	12/12/2025	Annual
RF Switching System	Switch box(6 G HPF+LNA)	HCT CO., LTD.,	F2L14	12/12/2025	Annual
Power Amplifier	CBL18265035	CERNEX	22966	11/07/2025	Annual
Power Amplifier	CBL26405040	CERNEX	25956	02/19/2026	Annual
Power Splitter(DC ~ 26.5 GHz)	11667B	Hewlett Packard	5001	04/10/2026	Annual
DC Power Supply	E3632A	Agilent	MY40010147	08/06/2025	Annual
Dipole Antenna	UHAP	Schwarzbeck	01274	03/10/2026	Biennial
Dipole Antenna	UHAP	Schwarzbeck	01288	08/07/2026	Biennial
Chamber	SU-642	ESPEC	93008124	02/11/2026	Annual
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	03197	11/28/2025	Biennial
Horn Antenna(1 ~ 18 GHz)	BBHA 9120D	Schwarzbeck	03201	11/28/2025	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170342	09/20/2026	Biennial
Horn Antenna(15 ~ 40 GHz)	BBHA 9170	Schwarzbeck	BBHA9170124	03/23/2027	Biennial
Signal Analyzer(10 Hz ~ 26.5 GHz)	N9020A	Agilent	MY52090906	04/14/2026	Annual
ATTENUATOR(20 dB)	8493C	Hewlett Packard	17280	04/10/2026	Annual
Spectrum Analyzer(10 Hz ~ 40 GHz)	FSV40	ROHDE & SCHWARZ	101733	09/19/2025	Annual
Base Station	8960 (E5515C)	Agilent	MY48360800	08/05/2025	Annual
Loop Antenna(9 kHz ~ 30 MHz)	FMZB1513	Schwarzbeck	1513-333	03/07/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	895	08/28/2026	Biennial
Trilog Broadband Antenna	VULB9168	Schwarzbeck	1135	08/19/2026	Biennial
Radio Communication Test Station	MT8000A	Anritsu Corp.	6272613402	08/28/2025	Annual
SIGNAL GENERATOR (100 kHz ~ 40 GHz)	SMB100A	REOHDE & SCHWARZ	177633	07/26/2025	Annual
Signal Analyzer(5 Hz ~ 40.0 GHz)	N9030B	KEYSIGHT	MY55480167	05/17/2025	Annual
Signal Analyzer(2 Hz ~ 50.0 GHz)	N9040B	KEYSIGHT	US55230216	12/09/2025	Annual
Signal & Spectrum Analyzer (2 Hz~67 GHz)	FSW67	REOHDE & SCHWARZ	101736	05/23/2025	Annual
FCC LTE Mobile Conducted RF Automation Test Software	-	HCT CO., LTD.,	-	-	-

Note:

- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.
- Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ kHz)
Occupied Bandwidth	95 (Confidence level about 95 %, $k=2$)
Frequency stability	28 (Confidence level about 95 %, $k=2$)
Parameter	Expanded Uncertainty ($\pm$ kHz)
Block Edge	0.70 (Confidence level about 95 %, $k=2$)
Conducted Spurious Emissions	1.18 (Confidence level about 95 %, $k=2$)
Peak- to- Average Ratio	0.68 (Confidence level about 95 %, $k=2$)
Radiated Power	4.74 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (9 kHz ~ 30 MHz)	4.36 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (30 MHz ~ 1 GHz)	5.68 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (1 GHz ~ 18 GHz)	5.75 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (18 GHz ~ 40 GHz)	5.82 (Confidence level about 95 %, $k=2$)
Radiated Disturbance (Above 40 GHz)	5.58 (Confidence level about 95 %, $k=2$)

6. SUMMARY OF TEST RESULTS

-. The decision rule applies 'simple acceptance'

6.1 Test Condition: Conducted Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Occupied Bandwidth	§ 2.1049	N/A	PASS
Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	§ 2.1051, § 27.53(g)	< 43 + 10log10 (P[Watts]) at Band Edge and for all out-of-band emissions	PASS
Conducted Output Power	§ 2.1046	N/A	<u>See Note1</u>
Frequency stability / variation of ambient temperature	§ 2.1055, § 27.54	Emission must remain in band	PASS

Note:

1. See SAR Report

6.2 Test Condition: Radiated Test

Test Description	FCC Part Section(s)	Test Limit	Test Result
Effective Radiated Power	§ 27.50(c)(10)	< 3 Watts max. ERP	PASS
Radiated Spurious and Harmonic Emissions	§ 2.1053, § 27.53(g)	< 43 + 10log10 (P[Watts]) for all out-of band emissions	PASS

7. SAMPLE CALCULATION

7.1 ERP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol.	ERP	
channel	Freq.(MHz)						W	dBm
128	824.20	-21.37	38.40	-10.61	0.95	H	0.483	26.84

$$\text{ERP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power.

7.2 EIRP Sample Calculation

Ch./ Freq.		Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBi)	C.L	Pol.	EIRP	
channel	Freq.(MHz)						W	dBm
20175	1,732.50	-15.75	18.45	9.90	1.76	H	0.456	26.59

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a non-conductive turntable is 2.5 meter above test site ground level.
- 2) During the test, the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of equivalent isotropic radiated power.

7.3. Emission Designator

GSM Emission Designator

Emission Designator = 249KGXW
GSM BW = 249 kHz
G = Phase Modulation
X = Cases not otherwise covered
W = Combination (Audio/Data)

EDGE Emission Designator

Emission Designator = 249KG7W
GSM BW = 249 kHz
G = Phase Modulation
7 = Quantized/Digital Info
W = Combination (Audio/Data)

WCDMA Emission Designator

Emission Designator = 4M17F9W
WCDMA BW = 4.17 MHz
F = Frequency Modulation
9 = Composite Digital Info
W = Combination (Audio/Data)

QPSK Modulation

Emission Designator = 4M48G7D
LTE BW = 4.48 MHz
G = Phase Modulation
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

QAM Modulation

Emission Designator = 4M48W7D
LTE BW = 4.48 MHz
W = Amplitude/Angle Modulated
7 = Quantized/Digital Info
D = Data transmission; telemetry; telecommand

8. TEST DATA(Main 1 ANT)

8.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
699.7	LTE B12 (1.4 MHz)	QPSK	-28.10	31.73	-9.65	1.29	V	<3.00	0.120	20.79	1	0
		16-QAM	-29.49	30.34	-9.65	1.29	V		0.087	19.40		
		64-QAM	-30.67	29.16	-9.65	1.29	V		0.066	18.22		
		256-QAM	-33.10	26.73	-9.65	1.29	V		0.038	15.79		
707.5		QPSK	-28.50	31.41	-9.65	1.30	V		0.111	20.46	1	0
		16-QAM	-29.94	29.97	-9.65	1.30	V		0.080	19.02		
		64-QAM	-31.06	28.85	-9.65	1.30	V		0.062	17.90		
		256-QAM	-33.46	26.45	-9.65	1.30	V		0.036	15.50		
715.3		QPSK	-28.39	31.90	-9.65	1.32	V		0.124	20.93	1	0
		16-QAM	-29.72	30.57	-9.65	1.32	V		0.091	19.60		
		64-QAM	-30.87	29.42	-9.65	1.32	V		0.070	18.45		
		256-QAM	-33.36	26.93	-9.65	1.32	V		0.039	15.96		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
700.5	LTE B12 (3 MHz)	QPSK	-28.31	31.52	-9.65	1.29	V	< 3.00	0.114	20.58	1	0
		16-QAM	-29.70	30.13	-9.65	1.29	V		0.083	19.19		
		64-QAM	-30.85	28.98	-9.65	1.29	V		0.064	18.04		
		256-QAM	-33.31	26.52	-9.65	1.29	V		0.036	15.58		
707.5		QPSK	-28.46	31.45	-9.65	1.30	V		0.112	20.50	1	0
		16-QAM	-29.79	30.12	-9.65	1.30	V		0.083	19.17		
		64-QAM	-30.92	28.99	-9.65	1.30	V		0.064	18.04		
		256-QAM	-33.43	26.48	-9.65	1.30	V		0.036	15.53		
714.5		QPSK	-28.49	31.73	-9.65	1.31	V		0.119	20.77	1	0
		16-QAM	-29.78	30.44	-9.65	1.31	V		0.089	19.48		
		64-QAM	-30.94	29.28	-9.65	1.31	V		0.068	18.32		
		256-QAM	-33.59	26.63	-9.65	1.31	V		0.037	15.67		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
701.5	LTE B12 (5 MHz)	QPSK	-28.10	31.74	-9.65	1.29	V	< 3.00	0.120	20.80	1	0
		16-QAM	-29.46	30.38	-9.65	1.29	V		0.088	19.44		
		64-QAM	-30.57	29.27	-9.65	1.29	V		0.068	18.33		
		256-QAM	-33.05	26.79	-9.65	1.29	V		0.038	15.85		
707.5		QPSK	-28.40	31.51	-9.65	1.30	V		0.114	20.56	1	0
		16-QAM	-29.75	30.16	-9.65	1.30	V		0.083	19.21		
		64-QAM	-30.87	29.04	-9.65	1.30	V		0.064	18.09		
		256-QAM	-33.35	26.56	-9.65	1.30	V		0.036	15.61		
713.5		QPSK	-28.52	31.64	-9.65	1.31	V		0.117	20.68	1	0
		16-QAM	-29.82	30.34	-9.65	1.31	V		0.087	19.38		
		64-QAM	-31.07	29.09	-9.65	1.31	V		0.065	18.13		
		256-QAM	-33.62	26.54	-9.65	1.31	V		0.036	15.58		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
								W	W	dBm	Size	Offset
704	LTE B12 (10 MHz)	QPSK	-28.35	31.51	-9.65	1.29	V	<3.00	0.114	20.57	1	0
		16-QAM	-29.72	30.14	-9.65	1.29	V		0.083	19.20		
		64-QAM	-30.83	29.03	-9.65	1.29	V		0.064	18.09		
		256-QAM	-33.31	26.55	-9.65	1.29	V		0.036	15.61		
707.5		QPSK	-28.21	31.70	-9.65	1.30	V		0.119	20.75	1	0
		16-QAM	-29.60	30.31	-9.65	1.30	V		0.086	19.36		
		64-QAM	-30.72	29.19	-9.65	1.30	V		0.067	18.24		
		256-QAM	-33.18	26.73	-9.65	1.30	V		0.038	15.78		
711		QPSK	-28.42	31.60	-9.65	1.30	V		0.116	20.65	1	0
		16-QAM	-29.80	30.22	-9.65	1.30	V		0.085	19.27		
		64-QAM	-30.89	29.13	-9.65	1.30	V		0.066	18.18		
		256-QAM	-33.37	26.65	-9.65	1.30	V		0.037	15.70		

8.2 RADIATED SPURIOUS EMISSIONS

■ MODE: LTE B12
 ■ MODULATION SIGNAL: 1.4 MHz QPSK
 ■ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
23017 (699.7)	1 399.40	-43.56	7.77	-56.57	1.85	H	-50.65	-13.00	1	0
	2 099.10	-33.95	9.53	-45.19	2.34	V	-38.00	-13.00		
	2 798.80	-52.81	10.62	-63.25	2.66	H	-55.29	-13.00		
23095 (707.5)	1 415.00	-42.68	7.84	-55.71	1.87	V	-49.74	-13.00	1	0
	2 122.50	-30.16	9.36	-41.80	2.28	H	-34.72	-13.00		
	2 830.00	-52.65	10.73	-62.88	2.70	H	-54.85	-13.00		
23173 (715.3)	1 430.60	-44.17	7.90	-57.04	1.87	H	-51.01	-13.00	1	0
	2 145.90	-29.60	9.22	-41.21	2.27	V	-34.26	-13.00		
	2 861.20	-52.12	10.78	-62.45	2.76	V	-54.43	-13.00		

8.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
12	1.4 MHz	707.5	QPSK	Full RB		5.73
			16-QAM			6.47
			64-QAM			6.71
			256-QAM			6.66
	3 MHz		QPSK			5.81
			16-QAM			6.42
			64-QAM			6.73
			256-QAM			6.69
	5 MHz		QPSK			5.78
			16-QAM			6.52
			64-QAM			6.63
			256-QAM			6.69
	10 MHz		QPSK			5.79
			16-QAM			6.45
			64-QAM			6.59
			256-QAM			6.62

Note:

1. Plots of the EUT's P.A.P.R are shown Page 63 ~ 78.
2. P.A.P.R is not required. These values are reported for information only.

8.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
12	1.4 MHz	707.5	QPSK	6	0	1.0968
			16-QAM			1.0934
			64-QAM			1.0945
			256-QAM			1.0969
	3 MHz		QPSK	15		2.7166
			16-QAM			2.7044
			64-QAM			2.7016
			256-QAM			2.7106
	5 MHz		QPSK	25		4.5368
			16-QAM			4.5177
			64-QAM			4.5332
			256-QAM			4.5648
	10 MHz		QPSK	50		9.0103
			16-QAM			8.9948
			64-QAM			8.9920
			256-QAM			9.0107

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 79 ~ 94.

8.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
12	1.4	699.70	3.7987	27.976	-57.906	-29.930	-13.00
		707.50	8.5643	28.591	-58.300	-29.709	
		715.30	9.7707	28.591	-56.836	-28.245	
	3	700.50	3.7488	27.976	-56.554	-28.578	
		707.50	6.0120	28.591	-57.977	-29.386	
		714.50	8.0459	28.591	-57.801	-29.210	
	5	701.50	8.8734	28.591	-57.319	-28.728	
		707.50	8.8535	28.591	-57.965	-29.374	
		713.50	7.4975	28.591	-57.903	-29.312	
	10	704.00	4.9253	27.976	-57.632	-29.656	
		707.50	3.8086	27.976	-57.504	-29.528	
		711.00	9.6810	28.591	-58.380	-29.789	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 95 ~ 106.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


8.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 107 ~ 134.

8.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B12</u>
OPERATING FREQUENCY:	<u>699,700,000 Hz</u>
CHANNEL:	<u>23017 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	699 700 002	0.0	0.000 000	0.000
100 %		-30	699 699 997	-4.5	-0.000 001	-0.006
100 %		-20	699 699 997	-4.7	-0.000 001	-0.007
100 %		-10	699 700 004	2.5	0.000 000	0.004
100 %		0	699 699 997	-4.4	-0.000 001	-0.006
100 %		+10	699 699 997	-4.9	-0.000 001	-0.007
100 %		+30	699 700 004	2.6	0.000 000	0.004
100 %		+40	699 700 000	-1.9	0.000 000	-0.003
100 %		+50	699 700 003	1.6	0.000 000	0.002
Batt. Endpoint	3.300	+20	699 700 003	1.5	0.000 000	0.002




MODE: LTE B12
 OPERATING FREQUENCY: 700,500,000 Hz
 CHANNEL: 23025 (3 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	700 500 002	0.0	0.000 000	0.000
100 %		-30	700 499 999	-3.4	0.000 000	-0.005
100 %		-20	700 500 005	2.6	0.000 000	0.004
100 %		-10	700 500 004	2.2	0.000 000	0.003
100 %		0	700 499 999	-3.1	0.000 000	-0.004
100 %		+10	700 500 004	2.0	0.000 000	0.003
100 %		+30	700 499 999	-3.0	0.000 000	-0.004
100 %		+40	700 499 999	-3.1	0.000 000	-0.004
100 %		+50	700 500 000	-2.7	0.000 000	-0.004
Batt. Endpoint	3.300	+20	700 499 999	-3.2	0.000 000	-0.005




MODE: LTE B12
 OPERATING FREQUENCY: 701,500,000 Hz
 CHANNEL: 23035 (5 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	701 500 002	0.0	0.000 000	0.000
100 %		-30	701 499 997	-5.8	-0.000 001	-0.008
100 %		-20	701 500 005	2.6	0.000 000	0.004
100 %		-10	701 499 997	-5.3	-0.000 001	-0.008
100 %		0	701 499 998	-4.6	-0.000 001	-0.007
100 %		+10	701 499 998	-4.8	-0.000 001	-0.007
100 %		+30	701 500 005	2.3	0.000 000	0.003
100 %		+40	701 500 005	2.6	0.000 000	0.004
100 %		+50	701 499 998	-4.6	-0.000 001	-0.007
Batt. Endpoint	3.300	+20	701 499 997	-4.9	-0.000 001	-0.007




■ MODE: LTE B12
 ■ OPERATING FREQUENCY: 704,000,000 Hz
 ■ CHANNEL: 23060 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.900 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	703 999 996	0.0	0.000 000	0.000
100 %		-30	703 999 992	-3.4	0.000 000	-0.005
100 %		-20	703 999 998	2.0	0.000 000	0.003
100 %		-10	703 999 998	2.2	0.000 000	0.003
100 %		0	703 999 991	-4.5	-0.000 001	-0.006
100 %		+10	703 999 999	3.0	0.000 000	0.004
100 %		+30	703 999 992	-3.5	0.000 000	-0.005
100 %		+40	703 999 993	-2.9	0.000 000	-0.004
100 %		+50	703 999 993	-3.1	0.000 000	-0.004
Batt. Endpoint	3.300	+20	703 999 998	2.8	0.000 000	0.004




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (1.4 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 499 997	0.0	0.000 000	0.000
100 %		-30	707 499 994	-3.0	0.000 000	-0.004
100 %		-20	707 499 993	-4.9	-0.000 001	-0.007
100 %		-10	707 499 992	-5.3	-0.000 001	-0.007
100 %		0	707 500 002	4.5	0.000 001	0.006
100 %		+10	707 499 992	-5.2	-0.000 001	-0.007
100 %		+30	707 499 993	-4.8	-0.000 001	-0.007
100 %		+40	707 499 994	-3.6	-0.000 001	-0.005
100 %		+50	707 499 992	-5.4	-0.000 001	-0.008
Batt. Endpoint	3.300	+20	707 499 996	-1.6	0.000 000	-0.002




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (3 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 500 005	0.0	0.000 000	0.000
100 %		-30	707 500 001	-4.3	-0.000 001	-0.006
100 %		-20	707 500 010	4.7	0.000 001	0.007
100 %		-10	707 500 008	2.7	0.000 000	0.004
100 %		0	707 500 007	2.2	0.000 000	0.003
100 %		+10	707 500 010	4.6	0.000 001	0.007
100 %		+30	707 500 009	3.8	0.000 001	0.005
100 %		+40	707 500 001	-3.6	-0.000 001	-0.005
100 %		+50	707 500 009	3.9	0.000 001	0.006
Batt. Endpoint	3.300	+20	707 500 001	-4.0	-0.000 001	-0.006




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (5 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 500 005	0.0	0.000 000	0.000
100 %		-30	707 500 009	4.6	0.000 001	0.007
100 %		-20	707 500 009	4.3	0.000 001	0.006
100 %		-10	707 499 999	-5.3	-0.000 001	-0.007
100 %		0	707 500 007	2.4	0.000 000	0.003
100 %		+10	707 500 007	2.3	0.000 000	0.003
100 %		+30	707 500 000	-4.7	-0.000 001	-0.007
100 %		+40	707 499 999	-5.8	-0.000 001	-0.008
100 %		+50	707 500 000	-4.9	-0.000 001	-0.007
Batt. Endpoint	3.300	+20	707 500 009	4.5	0.000 001	0.006




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (10 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 500 003	0.0	0.000 000	0.000
100 %		-30	707 499 999	-4.2	-0.000 001	-0.006
100 %		-20	707 500 007	3.6	0.000 001	0.005
100 %		-10	707 500 007	3.1	0.000 000	0.004
100 %		0	707 500 000	-3.4	0.000 000	-0.005
100 %		+10	707 500 006	2.9	0.000 000	0.004
100 %		+30	707 500 000	-3.8	-0.000 001	-0.005
100 %		+40	707 500 006	2.8	0.000 000	0.004
100 %		+50	707 500 000	-3.7	-0.000 001	-0.005
Batt. Endpoint	3.300	+20	707 499 999	-4.6	-0.000 001	-0.007




■ MODE: LTE B12
 ■ OPERATING FREQUENCY: 715,300,000 Hz
 ■ CHANNEL: 23173 (1.4 MHz)
 ■ REFERENCE VOLTAGE: 3.900 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	715 300 004	0.0	0.000 000	0.000
100 %		-30	715 299 998	-6.4	-0.000 001	-0.009
100 %		-20	715 300 008	3.9	0.000 001	0.005
100 %		-10	715 299 998	-5.9	-0.000 001	-0.008
100 %		0	715 299 998	-6.0	-0.000 001	-0.008
100 %		+10	715 300 007	3.0	0.000 000	0.004
100 %		+30	715 300 008	4.0	0.000 001	0.006
100 %		+40	715 300 008	3.4	0.000 000	0.005
100 %		+50	715 299 998	-6.0	-0.000 001	-0.008
Batt. Endpoint	3.300	+20	715 300 007	3.1	0.000 000	0.004




MODE: LTE B12
 OPERATING FREQUENCY: 714,500,000 Hz
 CHANNEL: 23165 (3 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	714 499 995	0.0	0.000 000	0.000
100 %		-30	714 500 006	10.7	0.000 001	0.015
100 %		-20	714 500 007	11.1	0.000 002	0.016
100 %		-10	714 500 006	10.7	0.000 001	0.015
100 %		0	714 499 989	-6.3	-0.000 001	-0.009
100 %		+10	714 500 006	10.3	0.000 001	0.014
100 %		+30	714 499 999	3.4	0.000 000	0.005
100 %		+40	714 499 989	-6.4	-0.000 001	-0.009
100 %		+50	714 500 006	10.4	0.000 001	0.015
Batt. Endpoint	3.300	+20	714 499 999	3.5	0.000 000	0.005




MODE: LTE B12
 OPERATING FREQUENCY: 713,500,000 Hz
 CHANNEL: 23155 (5 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	713 499 996	0.0	0.000 000	0.000
100 %		-30	713 500 000	3.1	0.000 000	0.004
100 %		-20	713 499 992	-4.4	-0.000 001	-0.006
100 %		-10	713 500 001	4.6	0.000 001	0.006
100 %		0	713 499 999	3.0	0.000 000	0.004
100 %		+10	713 499 991	-5.0	-0.000 001	-0.007
100 %		+30	713 500 000	3.5	0.000 000	0.005
100 %		+40	713 499 993	-3.7	-0.000 001	-0.005
100 %		+50	713 500 001	4.9	0.000 001	0.007
Batt. Endpoint	3.300	+20	713 499 992	-4.4	-0.000 001	-0.006



MODE: LTE B12
 OPERATING FREQUENCY: 711,000,000 Hz
 CHANNEL: 23130 (10 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100 %	3.900	+20(Ref)	710 999 996	0.0	0.000 000	0.000
100 %		-30	711 000 000	4.2	0.000 001	0.006
100 %		-20	710 999 999	3.5	0.000 000	0.005
100 %		-10	710 999 992	-4.3	-0.000 001	-0.006
100 %		0	710 999 999	3.4	0.000 000	0.005
100 %		+10	710 999 993	-3.3	0.000 000	-0.005
100 %		+30	710 999 994	-2.3	0.000 000	-0.003
100 %		+40	710 999 991	-4.5	-0.000 001	-0.006
100 %		+50	710 999 992	-3.5	0.000 000	-0.005
Batt. Endpoint	3.300	+20	710 999 992	-4.2	-0.000 001	-0.006



9. TEST DATA (Sub 1 ANT)

9.1 EFFECTIVE RADIATED POWER

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
699.7	LTE B12 (1.4 MHz)	QPSK	-34.06	25.77	-9.65	1.29	V	< 3.00	0.030	14.83	1	5
		16-QAM	-35.35	24.48	-9.65	1.29	V		0.023	13.54		
		64-QAM	-36.47	23.36	-9.65	1.29	V		0.018	12.42		
		256-QAM	-39.05	20.78	-9.65	1.29	V		0.010	9.84		
707.5		QPSK	-33.76	26.15	-9.65	1.30	V		0.033	15.20	1	5
		16-QAM	-35.07	24.84	-9.65	1.30	V		0.025	13.89		
		64-QAM	-36.18	23.73	-9.65	1.30	V		0.019	12.78		
		256-QAM	-38.65	21.26	-9.65	1.30	V		0.011	10.31		
715.3		QPSK	-33.02	27.27	-9.65	1.32	V		0.043	16.30	1	5
		16-QAM	-34.27	26.02	-9.65	1.32	V		0.032	15.05		
		64-QAM	-35.35	24.94	-9.65	1.32	V		0.025	13.97		
		256-QAM	-37.78	22.51	-9.65	1.32	V		0.014	11.54		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
700.5	LTE B12 (3 MHz)	QPSK	-33.84	25.99	-9.65	1.29	V	< 3.00	0.032	15.05	1	14
		16-QAM	-35.14	24.69	-9.65	1.29	V		0.024	13.75		
		64-QAM	-36.22	23.61	-9.65	1.29	V		0.019	12.67		
		256-QAM	-38.84	20.99	-9.65	1.29	V		0.010	10.05		
707.5		QPSK	-33.30	26.61	-9.65	1.30	V		0.037	15.66	1	14
		16-QAM	-34.59	25.32	-9.65	1.30	V		0.027	14.37		
		64-QAM	-35.69	24.22	-9.65	1.30	V		0.021	13.27		
		256-QAM	-38.20	21.71	-9.65	1.30	V		0.012	10.76		
714.5		QPSK	-32.98	27.24	-9.65	1.31	V		0.042	16.28	1	14
		16-QAM	-34.31	25.91	-9.65	1.31	V		0.031	14.95		
		64-QAM	-35.33	24.89	-9.65	1.31	V		0.025	13.93		
		256-QAM	-37.79	22.43	-9.65	1.31	V		0.014	11.47		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
701.5	LTE B12 (5 MHz)	QPSK	-33.77	26.07	-9.65	1.29	V	< 3.00	0.033	15.13	1	24
		16-QAM	-35.10	24.74	-9.65	1.29	V		0.024	13.80		
		64-QAM	-36.20	23.64	-9.65	1.29	V		0.019	12.70		
		256-QAM	-38.70	21.14	-9.65	1.29	V		0.011	10.20		
707.5		QPSK	-33.17	26.74	-9.65	1.30	V		0.038	15.79	1	24
		16-QAM	-34.51	25.40	-9.65	1.30	V		0.028	14.45		
		64-QAM	-35.67	24.24	-9.65	1.30	V		0.021	13.29		
		256-QAM	-38.11	21.80	-9.65	1.30	V		0.012	10.85		
713.5		QPSK	-32.89	27.27	-9.65	1.31	V		0.043	16.31	1	24
		16-QAM	-34.31	25.85	-9.65	1.31	V		0.031	14.89		
		64-QAM	-35.40	24.76	-9.65	1.31	V		0.024	13.80		
		256-QAM	-37.82	22.34	-9.65	1.31	V		0.014	11.38		

Freq (MHz)	Mod/ Bandwidth	Modulation	Measured	Substitute	Ant. Gain (dBd)	C.L	Pol	Limit	ERP		RB	
			Level (dBm)	Level (dBm)				W	W	dBm	Size	Offset
704.0	LTE B12 (10 MHz)	QPSK	-33.32	26.54	-9.65	1.29	V	< 3.00	0.036	15.60	1	49
		16-QAM	-34.72	25.14	-9.65	1.29	V		0.026	14.20		
		64-QAM	-35.81	24.05	-9.65	1.29	V		0.021	13.11		
		256-QAM	-38.22	21.64	-9.65	1.29	V		0.012	10.70		
707.5		QPSK	-32.94	26.97	-9.65	1.30	V		0.040	16.02	1	49
		16-QAM	-34.28	25.63	-9.65	1.30	V		0.029	14.68		
		64-QAM	-35.41	24.50	-9.65	1.30	V		0.023	13.55		
		256-QAM	-37.96	21.95	-9.65	1.30	V		0.013	11.00		
711.0		QPSK	-32.94	27.08	-9.65	1.30	V		0.041	16.13	1	49
		16-QAM	-34.32	25.70	-9.65	1.30	V		0.030	14.75		
		64-QAM	-35.39	24.63	-9.65	1.30	V		0.023	13.68		
		256-QAM	-37.82	22.20	-9.65	1.30	V		0.013	11.25		

9.2 RADIATED SPURIOUS EMISSIONS

■ MODE: LTE B12
 ■ MODULATION SIGNAL: 5 MHz QPSK
 ■ DISTANCE: 3 meters

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBd)	Substitute Level (dBm)	C.L	Pol	Result (dBm)	Limit (dBm)	RB	
									Size	Offset
23035 (701.5)	1 403.00	-42.84	7.79	-55.87	1.86	V	-49.94	-13.00	1	24
	2 104.50	-35.86	9.49	-47.21	2.34	V	-40.06	-13.00		
	2 806.00	-52.48	10.64	-62.87	2.68	V	-54.91	-13.00		
23095 (707.5)	1 415.00	-41.68	7.84	-54.71	1.87	V	-48.74	-13.00	1	24
	2 122.50	-32.22	9.36	-43.86	2.28	V	-36.78	-13.00		
	2 830.00	-52.01	10.73	-62.24	2.70	V	-54.21	-13.00		
23155 (713.5)	1 427.00	-43.33	7.88	-56.26	1.87	V	-50.25	-13.00	1	24
	2 140.50	-34.09	9.26	-45.76	2.24	H	-38.74	-13.00		
	2 854.00	-52.18	10.79	-62.50	2.74	V	-54.45	-13.00		

9.3 PEAK-TO-AVERAGE RATIO

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (dB)
12	1.4 MHz	707.5	QPSK	Full RB		5.49
			16-QAM			6.34
			64-QAM			6.48
			256-QAM			6.61
	3 MHz		QPSK			5.61
			16-QAM			6.30
			64-QAM			6.57
			256-QAM			6.66
	5 MHz		QPSK			5.61
			16-QAM			6.34
			64-QAM			6.64
			256-QAM			6.68
	10 MHz		QPSK			5.66
			16-QAM			6.37
			64-QAM			6.61
			256-QAM			6.61

Note:

1. Plots of the EUT's P.A.P.R are shown Page 136 ~ 151.
2. P.A.P.R is not required. These values are reported for information only.

9.4 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
12	1.4 MHz	707.5	QPSK	6	0	1.0998
			16-QAM			1.0925
			64-QAM			1.0942
			256-QAM			1.0956
	3 MHz		QPSK	15		2.7149
			16-QAM			2.7033
			64-QAM			2.7028
			256-QAM			2.7076
	5 MHz		QPSK	25		4.5301
			16-QAM			4.5116
			64-QAM			4.5273
			256-QAM			4.5581
	10 MHz		QPSK	50		8.9989
			16-QAM			8.9820
			64-QAM			8.9866
			256-QAM			8.9796

Note:

1. Plots of the EUT's Occupied Bandwidth are shown Page 152 ~ 167.

9.5 CONDUCTED SPURIOUS EMISSIONS

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
12	1.4	699.7	9.5214	28.591	-57.950	-29.359	-13.00
		707.5	3.7688	27.976	-56.696	-28.720	
		715.3	8.9033	28.591	-57.361	-28.770	
	3	700.5	9.7308	28.591	-57.558	-28.967	
		707.5	4.2573	27.976	-57.508	-29.532	
		714.5	8.2852	28.591	-58.367	-29.776	
	5	701.5	3.8385	27.976	-57.797	-29.821	
		707.5	4.1177	27.976	-57.784	-29.808	
		713.5	8.9133	28.591	-58.490	-29.899	
	10	704.0	8.0459	28.591	-58.022	-29.431	
		707.5	3.7588	27.976	-55.954	-27.978	
		711.0	3.7089	27.976	-57.717	-29.741	

Note:

1. Plots of the EUT's Conducted Spurious Emissions are shown Page 168 ~ 179.
2. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
3. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)
4. Factor (dB) = Cable Loss + Attenuator + Power Splitter

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.270
1 – 5	27.976
5 – 10	28.591
10 – 15	29.116
15 – 20	29.489
Above 20(26.5)	30.131


9.6 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 180 ~ 207.

9.7 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE


MODE:	<u>LTE B12</u>
OPERATING FREQUENCY:	<u>699,700,000 Hz</u>
CHANNEL:	<u>23017 (1.4 MHz)</u>
REFERENCE VOLTAGE:	<u>3.900 VDC</u>
DEVIATION LIMIT:	<u>Emission must remain in band</u>

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	699 700 007	0.0	0.000 000	0.000
100 %		-30	699 700 014	7.1	0.000 001	0.010
100 %		-20	699 700 014	6.6	0.000 001	0.009
100 %		-10	699 700 011	3.9	0.000 001	0.006
100 %		0	699 700 010	2.8	0.000 000	0.004
100 %		+10	699 700 002	-5.2	-0.000 001	-0.007
100 %		+30	699 700 015	7.8	0.000 001	0.011
100 %		+40	699 700 014	6.9	0.000 001	0.010
100 %		+50	699 700 014	6.9	0.000 001	0.010
Batt. Endpoint	3.300	+20	699 700 003	-4.2	-0.000 001	-0.006




MODE: LTE B12
 OPERATING FREQUENCY: 700,500,000 Hz
 CHANNEL: 23025 (3 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	700 500 004	0.0	0.000 000	0.000
100 %		-30	700 500 011	6.5	0.000 001	0.009
100 %		-20	700 500 009	4.9	0.000 001	0.007
100 %		-10	700 500 012	7.6	0.000 001	0.011
100 %		0	700 500 011	7.2	0.000 001	0.010
100 %		+10	700 500 000	-4.5	-0.000 001	-0.006
100 %		+30	700 500 009	5.0	0.000 001	0.007
100 %		+40	700 500 001	-3.7	-0.000 001	-0.005
100 %		+50	700 500 011	7.2	0.000 001	0.010
Batt. Endpoint	3.300	+20	700 500 009	4.7	0.000 001	0.007




MODE: LTE B12
 OPERATING FREQUENCY: 701,500,000 Hz
 CHANNEL: 23035 (5 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	701 500 003	0.0	0.000 000	0.000
100 %		-30	701 500 011	7.8	0.000 001	0.011
100 %		-20	701 500 005	2.4	0.000 000	0.003
100 %		-10	701 500 010	6.7	0.000 001	0.010
100 %		0	701 500 010	7.4	0.000 001	0.011
100 %		+10	701 500 010	7.3	0.000 001	0.010
100 %		+30	701 500 010	7.2	0.000 001	0.010
100 %		+40	701 500 009	6.4	0.000 001	0.009
100 %		+50	701 500 006	3.0	0.000 000	0.004
Batt. Endpoint	3.300	+20	701 500 006	3.2	0.000 000	0.005




■ MODE: LTE B12
 ■ OPERATING FREQUENCY: 704,000,000 Hz
 ■ CHANNEL: 23060 (10 MHz)
 ■ REFERENCE VOLTAGE: 3.900 VDC
 ■ DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	704 000 005	0.0	0.000 000	0.000
100 %		-30	704 000 010	4.9	0.000 001	0.007
100 %		-20	704 000 009	4.1	0.000 001	0.006
100 %		-10	704 000 011	5.5	0.000 001	0.008
100 %		0	704 000 011	5.9	0.000 001	0.008
100 %		+10	704 000 000	-5.0	-0.000 001	-0.007
100 %		+30	704 000 010	4.3	0.000 001	0.006
100 %		+40	704 000 011	5.5	0.000 001	0.008
100 %		+50	704 000 009	4.0	0.000 001	0.006
Batt. Endpoint	3.300	+20	704 000 011	5.9	0.000 001	0.008




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (1.4 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 500 003	0.0	0.000 000	0.000
100 %		-30	707 499 998	-5.2	-0.000 001	-0.007
100 %		-20	707 500 006	2.5	0.000 000	0.004
100 %		-10	707 499 998	-4.9	-0.000 001	-0.007
100 %		0	707 500 006	3.0	0.000 000	0.004
100 %		+10	707 500 006	3.1	0.000 000	0.004
100 %		+30	707 499 998	-4.8	-0.000 001	-0.007
100 %		+40	707 499 998	-5.5	-0.000 001	-0.008
100 %		+50	707 499 998	-4.8	-0.000 001	-0.007
Batt. Endpoint	3.300	+20	707 500 007	3.6	0.000 001	0.005




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (3 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 499 995	0.0	0.000 000	0.000
100 %		-30	707 499 991	-4.3	-0.000 001	-0.006
100 %		-20	707 499 991	-4.3	-0.000 001	-0.006
100 %		-10	707 499 999	3.5	0.000 000	0.005
100 %		0	707 499 990	-5.2	-0.000 001	-0.007
100 %		+10	707 499 998	2.9	0.000 000	0.004
100 %		+30	707 499 998	2.5	0.000 000	0.004
100 %		+40	707 499 991	-4.5	-0.000 001	-0.006
100 %		+50	707 499 990	-5.2	-0.000 001	-0.007
Batt. Endpoint	3.300	+20	707 499 998	3.1	0.000 000	0.004




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (5 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 499 995	0.0	0.000 000	0.000
100 %		-30	707 499 990	-4.8	-0.000 001	-0.007
100 %		-20	707 499 989	-5.6	-0.000 001	-0.008
100 %		-10	707 499 999	4.1	0.000 001	0.006
100 %		0	707 499 990	-4.9	-0.000 001	-0.007
100 %		+10	707 499 990	-5.0	-0.000 001	-0.007
100 %		+30	707 499 999	3.9	0.000 001	0.006
100 %		+40	707 499 990	-5.0	-0.000 001	-0.007
100 %		+50	707 499 990	-4.9	-0.000 001	-0.007
Batt. Endpoint	3.300	+20	707 499 999	4.1	0.000 001	0.006




MODE: LTE B12
 OPERATING FREQUENCY: 707,500,000 Hz
 CHANNEL: 23095 (10 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	707 499 996	0.0	0.000 000	0.000
100 %		-30	707 499 993	-2.6	0.000 000	-0.004
100 %		-20	707 500 001	5.1	0.000 001	0.007
100 %		-10	707 500 000	4.4	0.000 001	0.006
100 %		0	707 499 998	2.3	0.000 000	0.003
100 %		+10	707 499 992	-3.9	-0.000 001	-0.006
100 %		+30	707 500 001	4.8	0.000 001	0.007
100 %		+40	707 499 998	2.3	0.000 000	0.003
100 %		+50	707 500 001	4.5	0.000 001	0.006
Batt. Endpoint	3.300	+20	707 500 001	4.8	0.000 001	0.007




MODE: LTE B12
 OPERATING FREQUENCY: 715,300,000 Hz
 CHANNEL: 23173 (1.4 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	715 299 994	0.0	0.000 000	0.000
100 %		-30	715 299 989	-5.3	-0.000 001	-0.007
100 %		-20	715 300 000	5.9	0.000 001	0.008
100 %		-10	715 299 989	-5.4	-0.000 001	-0.008
100 %		0	715 299 989	-5.8	-0.000 001	-0.008
100 %		+10	715 300 001	6.2	0.000 001	0.009
100 %		+30	715 299 998	3.8	0.000 001	0.005
100 %		+40	715 300 001	6.5	0.000 001	0.009
100 %		+50	715 299 998	3.7	0.000 001	0.005
Batt. Endpoint	3.300	+20	715 299 989	-5.6	-0.000 001	-0.008




MODE: LTE B12
 OPERATING FREQUENCY: 714,500,000 Hz
 CHANNEL: 23165 (3 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	714 499 993	0.0	0.000 000	0.000
100 %		-30	714 499 985	-7.7	-0.000 001	-0.011
100 %		-20	714 499 985	-8.1	-0.000 001	-0.011
100 %		-10	714 499 985	-7.8	-0.000 001	-0.011
100 %		0	714 499 985	-8.2	-0.000 001	-0.011
100 %		+10	714 499 986	-6.5	-0.000 001	-0.009
100 %		+30	714 500 002	9.0	0.000 001	0.013
100 %		+40	714 500 001	8.6	0.000 001	0.012
100 %		+50	714 500 002	9.3	0.000 001	0.013
Batt. Endpoint	3.300	+20	714 500 003	9.8	0.000 001	0.014




MODE: LTE B12
 OPERATING FREQUENCY: 713,500,000 Hz
 CHANNEL: 23155 (5 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	713 499 996	0.0	0.000 000	0.000
100 %		-30	713 500 001	5.2	0.000 001	0.007
100 %		-20	713 500 002	6.0	0.000 001	0.008
100 %		-10	713 499 999	3.3	0.000 000	0.005
100 %		0	713 500 001	5.1	0.000 001	0.007
100 %		+10	713 499 999	3.2	0.000 000	0.004
100 %		+30	713 500 002	6.0	0.000 001	0.008
100 %		+40	713 499 992	-4.5	-0.000 001	-0.006
100 %		+50	713 500 002	5.7	0.000 001	0.008
Batt. Endpoint	3.300	+20	713 499 992	-4.0	-0.000 001	-0.006




MODE: LTE B12
 OPERATING FREQUENCY: 711,000,000 Hz
 CHANNEL: 23130 (10 MHz)
 REFERENCE VOLTAGE: 3.900 VDC
 DEVIATION LIMIT: Emission must remain in band

Voltage	Power	Temp.	Frequency	Frequency Error	Deviation	ppm
(%)	(VDC)	(°C)	(Hz)	(Hz)	(%)	
100 %	3.900	+20(Ref)	711 000 006	0.0	0.000 000	0.000
100 %		-30	711 000 012	6.1	0.000 001	0.009
100 %		-20	711 000 011	5.6	0.000 001	0.008
100 %		-10	711 000 011	5.0	0.000 001	0.007
100 %		0	711 000 011	5.5	0.000 001	0.008
100 %		+10	711 000 012	6.6	0.000 001	0.009
100 %		+30	711 000 001	-4.5	-0.000 001	-0.006
100 %		+40	711 000 008	2.3	0.000 000	0.003
100 %		+50	711 000 001	-4.7	-0.000 001	-0.007
Batt. Endpoint	3.300	+20	711 000 001	-5.0	-0.000 001	-0.007




10. TEST PLOTS(Main 1 Ant)


LTE B12_1.4M_PAR_Mid_QPSK_FullRB



LTE B12_1.4M_PAR_Mid_16QAM_FullRB




LTE B12_1.4M_PAR_Mid_64QAM_FullRB




LTE B12_1.4M_PAR_Mid_256QAM_FullRB




LTE B12_3 M_PAR_Mid_QPSK_FullRB




LTE B12_3 M_PAR_Mid_16QAM_FullRB




LTE B12_3 M_PAR_Mid_64QAM_FullRB




LTE B12_3 M_PAR_Mid_256QAM_FullRB




LTE B12_5 M_PAR_Mid_QPSK_FullRB




LTE B12_5 M_PAR_Mid_16QAM_FullRB




LTE B12_5 M_PAR_Mid_64QAM_FullRB




LTE B12_5 M_PAR_Mid_256QAM_FullRB




LTE B12_10 M_PAR_Mid_QPSK_FullRB



LTE B12_10 M_PAR_Mid_16QAM_FullRB




LTE B12_10 M_PAR_Mid_64QAM_FullRB




LTE B12_10 M_PAR_Mid_256QAM_FullRB




LTE B12_1.4M_OBW_Mid_QPSK_FullRB




LTE B12_1.4M_OBW_Mid_16QAM_FullRB




LTE B12_1.4M_OBW_Mid_64QAM_FullRB




LTE B12_1.4M_OBW_Mid_256QAM_FullRB




LTE B12_3 M_OBW_Mid_QPSK_FullRB




LTE B12_3 M_OBW_Mid_16QAM_FullRB




LTE B12_3 M_OBW_Mid_64QAM_FullRB




LTE B12_3 M_OBW_Mid_256QAM_FullRB




LTE B12_5 M_OBW_Mid_QPSK_FullRB




LTE B12_5 M_OBW_Mid_16QAM_FullRB




LTE B12_5 M_OBW_Mid_64QAM_FullRB




LTE B12_5 M_OBW_Mid_256QAM_FullRB




LTE B12_10 M_OBW_Mid_QPSK_FullRB




LTE B12_10 M_OBW_Mid_16QAM_FullRB




LTE B12_10 M_OBW_Mid_64QAM_FullRB




LTE B12_10 M_OBW_Mid_256QAM_FullRB




LTE B12_1.4M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B12_1.4M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B12_1.4M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B12_3 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B12_3 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B12_3 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B12_5 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B12_5 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB




LTE B12_5 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB




LTE B12_10 M_Conducted Spurious(30 M-10 G)_Low_QPSK_1RB




LTE B12_10 M_Conducted Spurious(30 M-10 G)_Mid_QPSK_1RB



LTE B12_10 M_Conducted Spurious(30 M-10 G)_High_QPSK_1RB



LTE B12_1.4M_Band Edge_Low_QPSK_1RB



LTE B12_1.4M_Band Edge_Low_QPSK_FullRB



LTE B12_1.4M_Extended Band Edge_Low_QPSK_FullRB



LTE B12_1.4M_Band Edge_High_QPSK_1RB(1)



LTE B12_1.4M_Band Edge_High_QPSK_1RB(2)



LTE B12_1.4M_Band Edge_High_QPSK_FullRB



LTE B12_1.4M_Extended Band Edge_High_QPSK_FullRB



Spectrum Analyzer 1
Swept SA

Input: RF
Coupling: DC
Align: Auto

Input Z: 50 Ω
Corr CCorr
Freq Ref: Int (S)
NFE: Adaptive

#Atten: 20 dB
Preamp: Off

PNO: Best Wide
Gate: Off
IF Gain: Low
Sig Track: Off

#Avg Type: Power (RMS)
Trig: Free Run

1 2 3 4 5 6
A A A A A A A

Center Frequency
698.000000 MHz

Span
4.00000000 MHz

Swept Span
Zero Span

Full Span

Start Freq
696.000000 MHz

Stop Freq
700.000000 MHz

AUTO TUNE

CF Step
400.000 kHz

Auto
Man

Freq Offset
0 Hz

X Axis Scale
Log
Lin

Signal Track
(Span, Zoom)

1 Spectrum
Scale/Div 10 dB
Log

Ref Lvl Offset 27.07 dB
Ref Level 27.07 dBm

Mkr1 697.932 MHz
-37.117 dBm

DL1 -13.00 dBm
RMS

Center 698.000 MHz
#Res BW 100 kHz

#Video BW 300 kHz

Span 4.000 MHz
#Sweep ~2.01 s (1001 pts)

Feb 27, 2025
3:58:03 PM

LTE B12_3 M_Band Edge_Low_QPSK_FullRB



LTE B12_3 M_Extended Band Edge_Low_QPSK_FullRB



LTE B12_3 M_Band Edge_High_QPSK_1RB(1)



LTE B12_3 M_Band Edge_High_QPSK_1RB(2)




LTE B12_3 M_Band Edge_High_QPSK_FullRB



LTE B12_3 M_Extended Band Edge_High_QPSK_FullIRB



LTE B12_5 M_Band Edge_Low_QPSK_1RB



LTE B12_5 M_Band Edge_Low_QPSK_FullRB



LTE B12_5 M_Extended Band Edge_Low_QPSK_FullRB



LTE B12_5 M_Band Edge_High_QPSK_1RB(1)



LTE B12_5 M_Band Edge_High_QPSK_1RB(2)



LTE B12_5 M_Band Edge_High_QPSK_FullRB



LTE B12_5 M_Extended Band Edge_High_QPSK_FullRB



LTE B12_10 M_Band Edge_Low_QPSK_1RB

