






Plot 7-79. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 6 Ch. 105)




Plot 7-80. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 7 Ch. 149)




Plot 7-81. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 8 Ch. 209)


FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 93 of 118		



Plot 7-82. Radiated Spurious Plot 18GHz - 26.5GHz (802.11a) – Ch. 45



Plot 7-83. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a) – Ch. 45



Plot 7-84. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11be 80MHz BW (20MHz Puncture – UNII Band 5 Ch. 45)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 94 of 118		

MIMO Radiated Spurious Emission Measurements – UNII Band 5

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	5	2	5935	*	11870.00	Average	V	-	-	-77.27	9.61	0.00	39.34	53.98	-14.64
					*	11870.00	Peak	V	-	-	-65.62	9.61	0.00	50.99	73.98	-22.99
					*	17805.00	Average	V	-	-	-77.38	15.94	0.00	45.56	53.98	-8.42
					*	17805.00	Peak	V	-	-	-66.18	15.94	0.00	56.76	73.98	-17.22
					*	23740.00	Average	V	-	-	-63.00	3.52	-9.54	37.98	53.98	-15.99
					*	23740.00	Peak	V	-	-	-51.57	3.52	-9.54	49.41	73.98	-24.57
			45	6175		29675.00	Peak	V	-	-	-51.42	5.49	-9.54	51.53	68.20	-16.67
					*	12350.00	Average	V	-	-	-77.55	9.39	0.00	38.84	53.98	-15.14
					*	12350.00	Peak	V	-	-	-65.83	9.39	0.00	50.56	73.98	-23.42
					*	18525.00	Average	V	-	-	-61.27	1.22	-9.54	37.41	53.98	-16.57
					*	18525.00	Peak	V	-	-	-49.43	1.22	-9.54	49.25	73.98	-24.73
						24700.00	Peak	V	-	-	-51.20	3.70	-9.54	49.96	68.20	-18.24
			93	6415		30875.00	Peak	V	-	-	-51.48	6.38	-9.54	52.36	68.20	-15.84
						12830.00	Peak	V	135	262	-64.81	9.58	0.00	51.77	68.20	-16.43
					*	19245.00	Average	V	-	-	-61.46	1.95	-9.54	37.95	53.98	-16.03
					*	19245.00	Peak	V	-	-	-50.16	1.95	-9.54	49.25	73.98	-24.73
						25660.00	Peak	V	-	-	-50.86	3.70	-9.54	50.30	68.20	-17.90
						32075.00	Peak	V	-	-	-51.33	7.33	-9.54	53.46	68.20	-14.74

Table 7-30. Radiated Measurements MIMO – VLP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.				-Page 95 of 118

MIMO Radiated Spurious Emission Measurements – UNII Band 6

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	6	97	6435		12870.00	Peak	V	161	260	-63.52	9.89	0.00	53.37	68.20	-14.83
					*	19305.00	Average	V	-	-	-61.63	1.78	-9.54	37.61	53.98	-16.37
					*	19305.00	Peak	V	-	-	-49.59	1.78	-9.54	49.65	73.98	-24.33
						25740.00	Peak	V	-	-	-50.77	3.63	-9.54	50.32	68.20	-17.88
						32175.00	Peak	V	-	-	-52.46	7.35	-9.54	52.35	68.20	-15.85
			105	6475		12950.00	Peak	V	353	259	-63.82	9.83	0.00	53.01	68.20	-15.19
					*	19425.00	Average	V	-	-	-61.63	1.96	-9.54	37.80	53.98	-16.18
					*	19425.00	Peak	V	-	-	-50.11	1.96	-9.54	49.31	73.98	-24.67
						25900.00	Peak	V	-	-	-50.62	3.93	-9.54	50.77	68.20	-17.43
						32375.00	Peak	V	-	-	-52.87	6.85	-9.54	51.44	68.20	-16.76
			113	6515		13030.00	Peak	V	162	265	-62.69	10.09	0.00	54.40	68.20	-13.80
					*	19545.00	Average	V	-	-	-61.62	2.06	-9.54	37.90	53.98	-16.08
					*	19545.00	Peak	V	-	-	-50.64	2.06	-9.54	48.88	73.98	-25.10
						26060.00	Peak	V	-	-	-51.36	3.93	-9.54	50.04	68.20	-18.16
						32575.00	Peak	V	-	-	-51.87	6.73	-9.54	52.32	68.20	-15.88

Table 7-31. Radiated Measurements MIMO – VLP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 96 of 118		

MIMO Radiated Spurious Emission Measurements – UNII Band 7

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	7	117	6535		13070.00	Peak	V	149	265	-63.53	10.22	0.00	53.69	68.20	-14.51
					*	19605.00	Average	V	-	-	-62.22	4.13	-9.54	39.37	53.98	-14.61
					*	19605.00	Peak	V	-	-	-51.27	4.13	-9.54	50.32	73.98	-23.66
						26140.00	Peak	V	-	-	-51.59	7.38	-9.54	53.25	68.20	-14.95
						32675.00	Peak	V	-	-	-52.00	6.84	-9.54	52.30	68.20	-15.90
			149	6695	*	13390.00	Average	V	321	265	-74.87	11.02	0.00	43.15	53.98	-10.83
					*	13390.00	Peak	V	321	265	-62.85	11.02	0.00	55.17	73.98	-18.81
					*	20085.00	Average	V	-	-	-62.04	2.60	-9.54	38.02	53.98	-15.96
					*	20085.00	Peak	V	-	-	-50.48	2.60	-9.54	49.58	73.98	-24.40
						26780.00	Peak	V	-	-	-51.27	4.13	-9.54	50.32	68.20	-17.88
			185	6875		33475.00	Peak	V	-	-	-51.59	7.38	-9.54	53.25	68.20	-14.95
						13750.00	Peak	V	-	-	-65.51	11.87	0.00	53.36	68.20	-14.84
					*	20625.00	Average	V	-	-	-62.29	3.15	-9.54	38.32	53.98	-15.66
					*	20625.00	Peak	V	-	-	-50.63	3.15	-9.54	49.98	73.98	-24.00
						27500.00	Peak	V	-	-	-51.62	4.02	-9.54	49.85	68.20	-18.35
						34375.00	Peak	V	-	-	-52.46	7.66	-9.54	52.65	68.20	-15.55

Table 7-32. Radiated Measurements MIMO – VLP

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	7	149	6695		13390.00	Average	V	275	353	-75.75	11.02	0.00	42.27	53.98	-11.71
						13390.00	Peak	V	275	353	-63.85	11.02	0.00	54.17	73.98	-19.81
						20085.00	Average	V	-	-	-62.16	2.60	-9.54	37.90	53.98	-16.08
						20085.00	Peak	V	-	-	-50.94	2.60	-9.54	49.12	73.98	-24.86
						26780.00	Peak	V	-	-	-51.27	4.13	-9.54	50.32	68.20	-17.88
						33475.00	Peak	V	-	-	-51.59	7.38	-9.54	53.25	68.20	-14.95

Table 7-33. Radiated Measurements MIMO – with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 97 of 118		

MIMO Radiated Spurious Emission Measurements – UNII Band 8

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	8	189	6895		13790.00	Peak	V	-	-	-66.16	11.58	0.00	52.42	68.20	-15.78
					*	20685.00	Average	V	-	-	-62.22	3.16	-9.54	38.40	53.98	-15.58
					*	20685.00	Peak	V	-	-	-50.81	3.16	-9.54	49.81	73.98	-24.17
						27580.00	Peak	V	-	-	-52.21	4.05	-9.54	49.30	68.20	-18.90
						34475.00	Peak	V	-	-	-51.99	7.56	-9.54	53.03	68.20	-15.17
			209	6995		13990.00	Peak	V	-	-	-64.92	11.69	0.00	53.77	68.20	-14.43
					*	20985.00	Average	V	-	-	-62.73	3.48	-9.54	38.21	53.98	-15.76
					*	20985.00	Peak	V	-	-	-51.59	3.48	-9.54	49.35	73.98	-24.63
						27980.00	Peak	V	-	-	-51.16	4.31	-9.54	50.61	68.20	-17.59
						34975.00	Peak	V	-	-	-52.11	7.83	-9.54	53.17	68.20	-15.03
			233	7115		14230.00	Peak	V	-	-	-65.65	12.70	0.00	54.05	68.20	-14.15
					*	21345.00	Average	V	-	-	-62.70	3.69	-9.54	38.46	53.98	-15.52
					*	21345.00	Peak	V	-	-	-51.23	3.69	-9.54	49.92	73.98	-24.06
						28460.00	Peak	V	-	-	-51.61	4.65	-9.54	50.51	68.20	-17.69
						35575.00	Peak	V	-	-	-52.17	7.99	-9.54	53.28	68.20	-14.92

Table 7-34. Radiated Measurements MIMO – VLP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 98 of 118		


7.8.2 MIMO Radiated Band Edge Measurements (20MHz BW)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	5935MHz
Channel:	2



Plot 7-85. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)


Worst Case Mode:	802.11be
Worst Case Transfer Rate:	MCS0
Distance of Measurements:	3 Meters
Operating Frequency:	7115MHz
Channel:	233



Plot 7-86. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			-Page 99 of 118

Worst Case Mode: 802.11a
 Worst Case Transfer Rate: 6Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 7115MHz
 Channel: 233




Plot 7-87. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8) – WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 100 of 118		


7.8.3 MIMO Radiated Band Edge Measurements (40MHz BW)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5965MHz
Channel: 3



Plot 7-88. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7085MHz
Channel: 227




Plot 7-89. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 101 of 118		


7.8.4 MIMO Radiated Band Edge Measurements (80MHz BW)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5985MHz
Channel: 7



Plot 7-90. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7025MHz
Channel: 215




Plot 7-91. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 102 of 118		


7.8.5 MIMO Radiated Band Edge Measurements (80MHz BW - Punctured)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5985MHz
Channel: 7



Plot 7-92. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7025MHz
Channel: 215




Plot 7-93. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 103 of 118		


7.8.6 MIMO Radiated Band Edge Measurements (160MHz BW)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6025MHz
Channel: 15



Plot 7-94. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6985MHz
Channel: 207




Plot 7-95. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 104 of 118		


7.8.7 MIMO Radiated Band Edge Measurements (160MHz BW - Punctured)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6025MHz
Channel: 15



Plot 7-96. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6985MHz
Channel: 207




Plot 7-97. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 105 of 118		


7.8.8 MIMO Radiated Band Edge Measurements (320MHz BW)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 6105MHz
 Channel: 31



Plot 7-98. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 6905MHz
 Channel: 191




Plot 7-99. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 106 of 118		


7.8.9 MIMO Radiated Band Edge Measurements (320MHz BW – Punctured)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6105MHz
Channel: 31



Plot 7-100. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6905MHz
Channel: 191



Plot 7-101. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 107 of 118		

7.9 Line Conducted Test Data

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst-case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-35. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			-Page 108 of 118

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-10. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz is specified in 15.207.
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 109 of 118		




Plot 7-102. Line Conducted Plot with 802.11a UNII Band 5 (L1)




Plot 7-103. Line Conducted Plot with 802.11a UNII Band 5 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			-Page 110 of 118




Plot 7-104. Line Conducted Plot with 802.11a UNII Band 6 (L1)




Plot 7-105. Line Conducted Plot with 802.11a UNII Band 6 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	-Page 111 of 118		




Plot 7-106. Line Conducted Plot with 802.11a UNII Band 7 (L1)




Plot 7-107. Line Conducted Plot with 802.11a UNII Band 7 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 112 of 118




Plot 7-108. Line Conducted Plot with 802.11a UNII Band 8 (L1)




Plot 7-109. Line Conducted Plot with 802.11a UNII Band 8 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 113 of 118




Plot 7-110. Line Conducted Plot with 802.11a UNII Band 5 (L1) with WCP




Plot 7-111. Line Conducted Plot with 802.11a UNII Band 5 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 114 of 118




Plot 7-112. Line Conducted Plot with 802.11a UNII Band 6 (L1) with WCP




Plot 7-113. Line Conducted Plot with 802.11a UNII Band 6 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 115 of 118




Plot 7-114. Line Conducted Plot with 802.11a UNII Band 7 (L1) with WCP




Plot 7-115. Line Conducted Plot with 802.11a UNII Band 7 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 116 of 118



Plot 7-116. Line Conducted Plot with 802.11a UNII Band 8 (L1) with WCP



Plot 7-117. Line Conducted Plot with 802.11a UNII Band 8 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		-Page 117 of 118

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF776B** is in compliance with FCC Part Subpart E (15.407) of the FCC rules for operation as a Very Low Power Device.

- END OF TEST REPORT -

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 5/11/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-19-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			-Page 118 of 118