






Plot 7-88. Contention Based Protocol Timing Plot (20MHz (UNII Band 7) – Ch. 149)




Plot 7-89. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 Low)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 92 of 135		




Plot 7-90. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 Mid)




Plot 7-91. Contention Based Protocol Timing Plot (320MHz (UNII Band 7) – Ch. 159 High)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 93 of 135		




Plot 7-92. Contention Based Protocol Timing Plot (20MHz (UNII Band 8) – Ch. 197)




Plot 7-93. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 Low)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 94 of 135		



Date: 23.APR.2026 16:21:14

Plot 7-94. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 Mid)



Date: 23.APR.2026 16:36:09


Plot 7-95. Contention Based Protocol Timing Plot (320MHz (UNII Band 8) – Ch. 191 High)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 95 of 135		

7.6.3 Channel Move Plots


This section demonstrates the effect of injecting the AWGN signal at various locations throughout the 802.11be 320MHz signal. The blue trace shows the full 320MHz signal prior to AWGN injection while the black trace shows the spectrum following AWGN injection. The following items were observed as demonstrated in the three plots shown below:

- When a 10 MHz AWGN signal centered at 6110 MHz (lower edge of channel) is injected, the channel completely stops transmitting.
- When a 10 MHz AWGN signal centered at 6265 MHz (middle of channel) is injected, the channel did not completely cease transmission; however, a reduction in the transmission bandwidth was observed.
- When a 10 MHz AWGN signal centered at 6420 MHz (upper edge of channel) is injected, the channel did not completely cease transmission; however, a reduction in the transmission bandwidth was observed.




Plot 7-96. CBP 320MHz Channel - Injection Lower Edge – [6110 MHz]

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 96 of 135



Plot 7-97. CBP 320MHz Channel - Injection Center – [6265 MHz]



Plot 7-98. CBP 320MHz Channel - Injection Upper Edge – [6420 MHz]

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 97 of 135		

7.7 Dual Client Device Additional Requirement (AFC Protocol) 15.407

Test Overview and Limit

Dual Client Device additional requirements (AFC Protocol) are tested per the test procedures listed below. During testing, the EUT is connected to a standard power access point to show compliance with 15.407.

The maximum power limits shall remain at least 6dB below the power levels authorized for the associated standard-power access point.

The EUT must distinguish its associated access point as standard or low power and control its power levels accordingly.

Test Procedure Used

ANSI C63.10.2020 – Section 12.4.3.2 Method PM-G
ANSI C63.10.2020 – Section 14.5.2.3 Measure-and-Sum Technique
KDB 987594 D02 v03

Test Setup/Method

The EUT was connected via an RF cable to a power meter and a callbox acting as a 6GHz standard power access point. For LPI measurement, the device is connected to a power meter via an RF cable and to an LPI access point wirelessly.

1. Standard Power callbox:
 - a. Enable 6GHz standard power access point
 - b. Send command to set power limit
 - c. Connect EUT to callbox AP (CMX500) and generate traffic via iperf.
 - d. Measure output power at conducted ports of client EUT
2. Low power indoor access point:
 - a. Connect EUT to LPI AP network (TPLink Archer BE900) and generate traffic via iPerf.
 - b. Measure output power at conducted ports of client EUT

Test Notes

- The EUT is a Dual Client Device.
- The test was executed with the CMX SP AP authorized to transmit up to 21dBm, 28.5dBm, and 36dBm on Ch. 53 (6215MHz). The LPI AP was operating on channel 53.
- The lowest 9.00dBm power level is based on the EIRP resulting from the conducted power targets specified in the manufacturer's "WLAN and Bluetooth Maximum Power Document".
- For LPI power verification, the EUT was connected via a conducted connection to the power meter. Simultaneously, the EUT was able to see and establish a radiated connection with the low power indoor access point.
- The CMX 'Max Tx Power' values shown below are calculated as twice the value of (the set maximum EIRP level in dBm minus 6 dB); i.e., $\text{Max Tx Power} = (\text{Max EIRP [dBm]} - 6) \times 2$. $\text{Max Tx Power} = (60) = 36\text{dBm}$

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 98 of 135

Test Setup Diagram

The testing was set up as shown in the diagram below:




Figure 7-6. Test Setup Diagram for Power Reduction Verification Test

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 99 of 135		



Figure 7-7. Callbox Power Authorization – 36.00dBm




Figure 7-8. Callbox Power Authorization – 28.50dBm

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 100 of 135		



Figure 7-9. Callbox Power Authorization – 21.00dBm

AFC Authorized EIRP for AP [dBm]	Dual Client ANT1 Conducted Power [dBm]	Antenna Gain [dBi]	Dual Client EIRP [dBm]	Client EIRP Limit [dBm]	Margin [dB]
36.00	16.15	-10.4	5.75	30.00	-24.25
28.50	16.14	-10.4	5.74	22.50	-16.76
21.00	8.95	-10.4	-1.45	15.00	-16.45

Table 7-39. Dual Client Output Power Results – Ch.53

AP	AFC Authorized EIRP for AP [dBm]	Dual Client ANT1 Conducted Power [dBm]	Antenna Gain [dBi]	Dual Client MIMO EIRP [dBm]	Client EIRP Limit [dBm]	Margin [dB]
SP	36.00	16.50	-10.4	6.10	30.00	-23.90
LPI		10.73	-10.4	0.33	24.00	-23.67

Table 7-40. Power Adjustment based on Associated AP Results – Ch.53

Sample e.i.r.p. Calculation:

At 6215MHz in 802.11ax (20MHz BW) mode, the average conducted power was 16.15 dBm with antenna gain of -10.4 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$16.15 \text{ dBm} + -10.4 \text{ dBi} = 5.75 \text{ dBm}$$

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 101 of 135		

7.8 Radiated Emission Measurements

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in ANSI C63.10:2020, and at the appropriate frequencies. All channels, modes (e.g. 802.11a, 802.11ax, 802.11be (20/40/80/160/320MHz), and modulations/data rates were investigated among all UNII bands. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

For transmitters operating in the 5.925-7.125 GHz band: All emissions outside of the 5.925-7.125 GHz band shall not exceed an EIRP of -27dBm/MHz (68.2dBuV/m at a 3m distance). Emissions found in a restricted band are subject to the limits of 15.209 as shown in the table below.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400\F (kHz)	300
0.490 – 1.705 MHz	24000\F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-41. Radiated Limits

Test Procedures Used

ANSI C63.10:2020 – Sections 12.7.7.2, 12.7.6, 12.7.5

Test Settings – Above 1GHz

Average Field Strength Measurements (Method AD – Average Detection)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span} \backslash \text{RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces.

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 102 of 135

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize.

Test Settings – Below 1GHz

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest.
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-10. Radiated Test Setup < 30MHz

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 103 of 135




Figure 7-11. Radiated Test Setup < 1GHz




Figure 7-12. Radiated Test Setup > 1GHz

Test Notes

1. All spurious emissions lying in restricted bands specified in §15.205 are below the limits specified in §15.209. All spurious emissions that do not lie in a restricted band are subject to an average limit of -27dBm/MHz. At 3 meters, the field strength limit in dB μ V/m can be determined by adding a “conversion” factor of 95.2dB to the EIRP limit of -27dBm/MHz to obtain the limit for out of band spurious emissions of 68.2dB μ V/m.

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 104 of 135		

2. All spurious emissions that do not lie in a restricted band are subject to a peak limit not to exceed 20dB of the average limit [68.2dB μ V/m]. If a peak measurement passes the average limit, it was determined no further investigation is necessary.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported, however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. In the case where a peak-detector measurement passed the given RMS limit it was determined sufficient to demonstrate compliance.
9. The results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
10. In this section, plots showing measurements shown as "channel power" are recorded using the integration methods described in Section 11.12.3.2 of ANSI C63.10:2020 for average and peak measurements as allowed per Section 12.7.4.4.1. Also, the average measurements include the duty cycle correction factor shown in Section 2.2 of this report.

Sample Calculations

Determining Spurious Emissions Levels


- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB/m]
- AFCL [dB/m] = Antenna Factor [dB/m] + Cable Loss [dB]
- Margin [dB] = Field Strength Level [dB μ V/m] – Limit [dB μ V/m]

Radiated Band Edge Measurement Offset

The amplitude offset shown in the radiated restricted band edge plots was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 105 of 135

7.8.1 MIMO Radiated Spurious Emission Measurements




Plot 7-99. Radiated Spurious Plot below 1GHz MIMO (802.11a)


Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
802.11a	MIMO	1	40	5200	115.00	Quasi-Peak	H	-	-	-60.10	-15.09	31.81	43.52	-11.71
					160.00	Quasi-Peak	H	-	-	-61.13	-16.61	29.26	43.52	-14.26
					285.00	Quasi-Peak	H	-	-	-63.98	-12.06	30.96	46.02	-15.06

Table 7-42. Radiated Measurements below 1GHz MIMO (802.11a)


FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.				Page 106 of 135



Plot 7-100. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 5 Ch. 45)




Plot 7-101. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 6 Ch. 105)




Plot 7-102. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – UNII Band 7 Ch. 149)


FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 107 of 135		



Plot 7-103. Radiated Spurious Plot 1GHz – 18GHz MIMO (802.11a – U Band 8 Ch. 209)




Plot 7-104. Radiated Spurious Plot above 1GHz MIMO (802.11be – UNII Band 5 Ch. 39 – Punctured)



Plot 7-105. Radiated Spurious Plot 18GHz - 26.5GHz (802.11a) – Ch. 45

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 108 of 135		



Plot 7-106. Radiated Spurious Plot 26.5GHz - 40GHz (802.11a) – Ch. 45

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 109 of 135		

MIMO Radiated Spurious Emission Measurements – UNII Band 5

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	5	2	5935	*	11870.00	Average	V	133	249	-72.86	9.61	0.00	43.75	53.98	-10.23
					*	11870.00	Peak	V	133	249	-60.43	9.61	0.00	56.18	73.98	-17.80
					*	17805.00	Average	V	-	-	-77.42	15.94	0.00	45.52	53.98	-8.46
					*	17805.00	Peak	V	-	-	-65.59	15.94	0.00	57.35	73.98	-16.63
					*	23740.00	Average	V	-	-	-62.96	3.52	-9.54	38.02	53.98	-15.96
					*	23740.00	Peak	V	-	-	-51.24	3.52	-9.54	49.74	73.98	-24.24
			45	6175		29675.00	Peak	V	-	-	-52.68	5.49	-9.54	50.27	68.20	-17.93
					*	12350.00	Average	V	273	308	-68.02	9.39	0.00	48.37	53.98	-5.61
					*	12350.00	Peak	V	273	308	-56.04	9.39	0.00	60.35	73.98	-13.63
					*	18525.00	Average	V	-	-	-61.52	1.22	-9.54	37.16	53.98	-16.82
					*	18525.00	Peak	V	-	-	-50.23	1.22	-9.54	48.45	73.98	-25.53
						24700.00	Peak	V	-	-	-50.91	3.70	-9.54	50.24	68.20	-17.96
			93	6415		30875.00	Peak	V	-	-	-52.21	6.39	-9.54	51.65	68.20	-16.55
						12830.00	Peak	V	180	255	-52.21	9.58	0.00	64.37	68.20	-3.83
					*	19245.00	Average	V	-	-	-61.53	1.95	-9.54	37.88	53.98	-16.10
					*	19245.00	Peak	V	-	-	-49.58	1.95	-9.54	49.84	73.98	-24.14
						25660.00	Peak	V	-	-	-51.02	3.70	-9.54	50.14	68.20	-18.06
						32075.00	Peak	V	-	-	-52.93	7.32	-9.54	51.85	68.20	-16.35

Table 7-43. Radiated Measurements MIMO – SP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 110 of 135		

MIMO Radiated Spurious Emission Measurements – UNII Band 6

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	6	97	6435		12870.00	Peak	V	163	263	-56.70	9.89	0.00	60.19	68.20	-8.01
					*	19305.00	Average	V	-	-	-61.74	1.76	-9.54	37.48	53.98	-16.50
					*	19305.00	Peak	V	-	-	-50.12	1.75	-9.54	49.08	73.98	-24.90
						25740.00	Peak	V	-	-	-50.92	3.63	-9.54	50.18	68.20	-18.02
						32175.00	Peak	V	-	-	-51.72	7.35	-9.54	53.09	68.20	-15.11
			105	6475		12950.00	Peak	V	157	263	-56.57	9.83	0.00	60.26	68.20	-7.94
					*	19425.00	Average	V	-	-	-61.73	1.96	-9.54	37.69	53.98	-16.29
					*	19425.00	Peak	V	-	-	-50.23	1.96	-9.54	49.20	73.98	-24.78
						25900.00	Peak	V	-	-	-51.42	3.93	-9.54	49.97	68.20	-18.23
						32375.00	Peak	V	-	-	-52.82	6.87	-9.54	51.50	68.20	-16.70
			113	6515		13030.00	Peak	V	336	262	-56.07	10.09	0.00	61.02	68.20	-7.18
					*	19545.00	Average	V	-	-	-61.74	2.06	-9.54	37.77	53.98	-16.21
					*	19545.00	Peak	V	-	-	-50.29	2.06	-9.54	49.23	73.98	-24.75
						26060.00	Peak	V	-	-	-51.80	3.85	-9.54	49.52	68.20	-18.68
						32575.00	Peak	V	-	-	-51.46	6.73	-9.54	52.73	68.20	-15.47

Table 7-44. Radiated Measurements MIMO – LPI

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 111 of 135

MIMO Radiated Spurious Emission Measurements – UNII Band 7

Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	7	117	6535		13070.00	Peak	V	168	264	-52.88	10.22	0.00	64.34	68.20	-3.86
					*	19605.00	Average	V	-	-	-61.97	2.36	-9.54	37.85	53.98	-16.13
					*	19605.00	Peak	V	-	-	-50.18	2.36	-9.54	49.64	73.98	-24.34
						26140.00	Peak	V	-	-	-51.20	4.01	-9.54	50.27	68.20	-17.93
						32675.00	Peak	V	-	-	-52.25	6.84	-9.54	52.05	68.20	-16.15
			149	6695	*	13390.00	Average	V	269	266	-67.45	11.02	0.00	50.57	53.98	-3.41
					*	13390.00	Peak	V	269	266	-55.68	11.02	0.00	62.34	73.98	-11.64
					*	20085.00	Average	V	-	-	-62.35	2.60	-9.54	37.71	53.98	-16.27
					*	20085.00	Peak	V	-	-	-50.39	2.59	-9.54	49.65	73.98	-24.33
						26780.00	Peak	V	-	-	-50.30	4.13	-9.54	51.29	68.20	-16.91
			185	6875		33475.00	Peak	V	-	-	-51.58	7.38	-9.54	53.26	68.20	-14.94
						13750.00	Peak	V	239	266	-54.78	11.87	0.00	64.09	68.20	-4.11
					*	20625.00	Average	V	-	-	-62.43	3.08	-9.54	38.10	53.98	-15.87
					*	20625.00	Peak	V	-	-	-50.56	3.08	-9.54	49.97	73.98	-24.01
						27500.00	Peak	V	-	-	-51.49	4.02	-9.54	49.99	68.20	-18.21
						34375.00	Peak	V	-	-	-52.68	7.66	-9.54	52.43	68.20	-15.77

Table 7-45. Radiated Measurements MIMO – SP

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	7	149	6695		13390.00	Average	V	299	350	-68.82	11.02	0.00	49.20	53.98	-4.78
						13390.00	Peak	V	299	350	-56.92	11.02	0.00	61.10	73.98	-12.88
						20085.00	Average	V	-	-	-63.40	2.60	0.00	46.20	53.98	-7.78
						20085.00	Peak	V	-	-	-55.43	2.59	-9.54	44.62	73.98	-29.36
						26780.00	Peak	V	-	-	-53.24	4.13	-9.54	48.35	68.20	-19.85
						33475.00	Peak	V	-	-	-51.34	7.38	-9.54	53.90	68.20	-14.70

Table 7-46. Radiated Measurements MIMO – SP - WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)		Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 112 of 135		

MIMO Radiated Spurious Emission Measurements – UNII Band 8


Worst Case Mode: 802.11a
Worst Case Transfer Rate: 6Mbps
Distance of Measurements: 1 & 3 Meters

Mode	Antenna	UNII Band	Channel	Test Channel Freq. [MHz]	Restricted	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
802.11a	MIMO	8	189	6895		13790.00	Peak	H	400	218	-63.23	11.58	0.00	55.35	68.20	-12.85
					*	20685.00	Average	V	-	-	-62.40	3.16	-9.54	38.22	53.98	-15.76
					*	20685.00	Peak	V	-	-	-51.20	3.16	-9.54	49.43	73.98	-24.55
						27580.00	Peak	V	-	-	-52.30	4.05	-9.54	49.22	68.20	-18.98
						34475.00	Peak	V	-	-	-51.67	7.56	-9.54	53.36	68.20	-14.84
			209	6995		13990.00	Peak	H	399	210	-63.95	11.69	0.00	54.74	68.20	-13.46
					*	20985.00	Average	V	-	-	-62.89	3.48	-9.54	38.05	53.98	-15.93
					*	20985.00	Peak	V	-	-	-51.93	3.48	-9.54	49.02	73.98	-24.96
						27980.00	Peak	V	-	-	-51.51	4.31	-9.54	50.27	68.20	-17.93
						34975.00	Peak	V	-	-	-52.31	7.83	-9.54	52.98	68.20	-15.22
			233	7115		14230.00	Peak	H	-	-	-65.56	12.70	0.00	54.14	68.20	-14.06
					*	21345.00	Average	V	-	-	-62.97	3.69	-9.54	38.18	53.98	-15.80
					*	21345.00	Peak	V	-	-	-51.47	3.69	-9.54	49.68	73.98	-24.30
						28460.00	Peak	V	-	-	-51.77	4.65	-9.54	50.34	68.20	-17.86
						35575.00	Peak	V	-	-	-52.17	7.99	-9.54	53.28	68.20	-14.92


Table 7-47. Radiated Measurements MIMO – LPI

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 113 of 135


7.8.2 MIMO Radiated Spurious Emission Measurements – Simultaneous Transmission



Plot 7-107. Radiated Spurious Plot below 1GHz MIMO 802.11b (2.4GHz – Ch.6) + MIMO 802.11a (6GHz – Ch.2)




Plot 7-108. Radiated Spurious Plot above 1GHz MIMO 802.11b (2.4GHz – Ch.6) + MIMO 802.11a (6GHz – Ch.2)



Plot 7-109. Radiated Spurious Plot 18GHz – 26.6GHz MIMO 802.11b (2.4GHz – Ch.6) + MIMO 802.11a (6GHz – Ch.2)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 114 of 135		



Plot 7-110. Radiated Spurious Plot 26.6GHz – 40GHz MIMO 802.11b (2.4GHz – Ch.6) + MIMO 802.11a (6GHz – Ch.2)


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
77.19	Peak	H	210.00	290.00	-66.51	-18.89	0.00	21.60	40.00	-18.40
291.07	Peak	H	-	-	-73.50	-11.82	0.00	21.68	46.02	-24.34
697.12	Peak	H	-	-	-76.34	-3.88	0.00	26.78	46.02	-19.24
1897.00	Peak	H	-	-	-66.61	1.48	0.00	41.87	73.98	-32.11
4798.00	Average	H	-	-	-80.44	14.16	0.00	40.72	53.98	-13.26
4798.00	Peak	H	-	-	-68.73	14.16	0.00	52.43	73.98	-21.55
10097.00	Peak	H	-	-	-71.92	18.91	0.00	53.99	73.98	-19.99
15012.00	Peak	H	-	-	-72.91	27.54	0.00	61.63	73.98	-12.35
20002.00	Average	H	-	-	-63.13	2.62	-9.54	36.95	53.98	-17.03
20002.00	Peak	H	-	-	-50.59	2.62	-9.54	49.49	73.98	-24.49
26989.00	Peak	H	-	-	-51.28	3.94	-9.54	50.11	73.98	-23.87

Table 7-48. Radiated Measurements MIMO 2.4GHz + 6GHz

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 115 of 135		


7.8.3 MIMO Radiated Band Edge Measurements (20MHz BW)

Worst Case Mode: 802.11ax
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5935MHz
 Channel: 2



Plot 7-111. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)


Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 7115MHz
 Channel: 233



Plot 7-112. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 116 of 135		

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 7115MHz
 Channel: 233




Plot 7-113. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5) – WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 117 of 135		


7.8.4 MIMO Radiated Band Edge Measurements (40MHz BW)

Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5965MHz
Channel: 3



Plot 7-114. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7085MHz
Channel: 227




Plot 7-115. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 118 of 135		


7.8.5 MIMO Radiated Band Edge Measurements (80MHz BW)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 5985MHz
 Channel: 7



Plot 7-116. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 7025MHz
 Channel: 215




Plot 7-117. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 119 of 135		


7.8.6 MIMO Radiated Band Edge Measurements (80MHz BW - Punctured)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 5985MHz
Channel: 7



Plot 7-118. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 7025MHz
Channel: 215




Plot 7-119. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 120 of 135		


7.8.7 MIMO Radiated Band Edge Measurements (160MHz BW)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 6025MHz
 Channel: 15



Plot 7-120. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 6985MHz
 Channel: 207




Plot 7-121. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 121 of 135		


7.8.8 MIMO Radiated Band Edge Measurements (160MHz BW - Punctured)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6025MHz
Channel: 15



Plot 7-122. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6985MHz
Channel: 207




Plot 7-123. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 122 of 135		


7.8.9 MIMO Radiated Band Edge Measurements (320MHz BW)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6105MHz
Channel: 31



Plot 7-124. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 6905MHz
Channel: 191




Plot 7-125. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 123 of 135		


7.8.10 MIMO Radiated Band Edge Measurements (320MHz BW – Punctured)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 6105MHz
 Channel: 31



Plot 7-126. Radiated Lower Band Edge Plot MIMO (Average & Peak – UNII Band 5)

Worst Case Mode: 802.11be
 Worst Case Transfer Rate: MCS0
 Distance of Measurements: 3 Meters
 Operating Frequency: 6905MHz
 Channel: 191



Plot 7-127. Radiated Upper Band Edge Plot MIMO (Average & Peak – UNII Band 8)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 124 of 135		

7.9 Line Conducted Test Data

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst-case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-49. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest.
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize.

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 125 of 135

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-13. Test Instrument & Measurement Setup


Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz is specified in 15.207.
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 126 of 135		




Plot 7-128. Line Conducted Plot with 802.11a UNII Band 5 (L1)




Plot 7-129. Line Conducted Plot with 802.11a UNII Band 5 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 127 of 135		




Plot 7-130. Line Conducted Plot with 802.11a UNII Band 6 (L1)




Plot 7-131. Line Conducted Plot with 802.11a UNII Band 6 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 128 of 135		




Plot 7-132. Line Conducted Plot with 802.11a UNII Band 7 (L1)




Plot 7-133. Line Conducted Plot with 802.11a UNII Band 7 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 129 of 135		




Plot 7-134. Line Conducted Plot with 802.11a UNII Band 8 (L1)




Plot 7-135. Line Conducted Plot with 802.11a UNII Band 8 (N)

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 130 of 135		




Plot 7-136. Line Conducted Plot with 802.11a UNII Band 5 (L1) with WCP




Plot 7-137. Line Conducted Plot with 802.11a UNII Band 5 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 131 of 135		




Plot 7-138. Line Conducted Plot with 802.11a UNII Band 6 (L1) with WCP




Plot 7-139. Line Conducted Plot with 802.11a UNII Band 6 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 132 of 135		




Plot 7-140. Line Conducted Plot with 802.11a UNII Band 7 (L1) with WCP




Plot 7-141. Line Conducted Plot with 802.11a UNII Band 7 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 133 of 135		



Plot 7-142. Line Conducted Plot with 802.11a UNII Band 8 (L1) with WCP



Plot 7-143. Line Conducted Plot with 802.11a UNII Band 8 (N) with WCP

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 134 of 135		

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF776B** is in compliance with FCC Part Subpart E (15.407) of the FCC rules for operation as a Dual Client Device.

- END OF TEST REPORT -

FCC ID: A3LSMF776B	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 3/11/26 - 4/23/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2603110020-17-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 135 of 135