



Plot 7-115. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT 2



Plot 7-116. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – SISO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 82 of 146



Plot 7-117. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – MIMO ANT 1



Plot 7-118. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – MIMO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 83 of 146



Plot 7-119. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – MIMO ANT 1



Plot 7-120. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – MIMO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 84 of 146



Plot 7-121. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 0) – MIMO ANT 2



Plot 7-122. Band Edge Plot (Bluetooth with Hopping Disabled, 3 Mbps – Ch. 78) – MIMO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 85 of 146



Plot 7-123. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – MIMO ANT 2



Plot 7-124. Band Edge Plot (Bluetooth with Hopping Enabled, 3 Mbps) – MIMO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 86 of 146

7.5 Carrier Frequency Separation

Test Overview and Limit

Measurement is made with EUT operating in hopping mode. ***The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.***

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.2

Test Settings

1. Span = Wide enough to capture peaks of two adjacent channels
2. RBW = 30% of channel spacing. Adjust as necessary to best identify center of each individual channel
3. VBW $\geq$ RBW
4. Sweep = Auto
5. Detector = Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize.
8. Marker-delta function used to determine separation between peaks of the adjacent channels

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup


Test Notes

The EUT complies with the minimum channel separation requirement when it is operating in 1x/EDR mode using 79 channels and when operating in AFH mode using 20 channels.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.	Page 87 of 146		

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Min. Channel Separation [MHz]
2402	1.0	0	0.620
2441	1.0	39	0.627
2480	1.0	78	0.630
2402	2.0	0	0.861
2441	2.0	39	0.892
2480	2.0	78	0.849
2402	3.0	0	0.896
2441	3.0	39	0.901
2480	3.0	78	0.883

Table 7-9. Minimum Channel Separation – SISO Ant 1




Plot 7-125. Channel Spacing Plot (Bluetooth) – SISO Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 88 of 146

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Min. Channel Separation [MHz]
2402	1.0	0	0.628
2441	1.0	39	0.629
2480	1.0	78	0.630
2402	2.0	0	0.906
2441	2.0	39	0.891
2480	2.0	78	0.905
2402	3.0	0	0.881
2441	3.0	39	0.889
2480	3.0	78	0.842

Table 7-10. Minimum Channel Separation – SISO Ant 2




Plot 7-126. Channel Spacing Plot (Bluetooth) – SISO Ant 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 89 of 146

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Min. Channel Separation [MHz]
2402	1.0	0	0.619
2441	1.0	39	0.623
2480	1.0	78	0.624
2402	2.0	0	0.908
2441	2.0	39	0.889
2480	2.0	78	0.888
2402	3.0	0	0.884
2441	3.0	39	0.869
2480	3.0	78	0.879

Table 7-11. Minimum Channel Separation – MIMO Ant 1




Plot 7-127. Channel Spacing Plot (Bluetooth) – MIMO Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 90 of 146

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Min. Channel Separation [MHz]
2402	1.0	0	0.635
2441	1.0	39	0.625
2480	1.0	78	0.624
2402	2.0	0	0.895
2441	2.0	39	0.873
2480	2.0	78	0.885
2402	3.0	0	0.884
2441	3.0	39	0.853
2480	3.0	78	0.867

Table 7-12. Minimum Channel Separation – MIMO Ant 2



Plot 7-128. Channel Spacing Plot (Bluetooth) – MIMO Ant 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 91 of 146

7.6 Time of Occupancy

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode with the spectrum analyzer set to zero span. ***The maximum permissible time of occupancy is 400 ms within a period of 400ms multiplied by the number of hopping channels employed.***

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.4

Test Settings

1. Span = zero span, centered on a hopping channel
2. RBW $\leq$ channel spacing and $\gg 1/T$, where T is expected dwell time per channel
3. Sweep = as necessary to capture entire dwell time. Second plot may be required to demonstrate two successive hops on a channel
4. Trigger is set with appropriate trigger delay to place pulse near the center of the plot
5. Detector = peak
6. Trace mode = Clear Write
7. Marker-delta function used to determine transmit time per hop

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

Test Notes

None

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 92 of 146



Plot 7-129. Time of Occupancy Plot (Bluetooth) – SISO Ant 1

Bluetooth Time of Occupancy Calculation


Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.880 \text{ ms/channel} = 307.20 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.880 \text{ ms/channel} = 153.56 \text{ ms}$ (worst case dwell time for one channel in AFH mode)

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 93 of 146



Plot 7-130. Time of Occupancy Plot (Bluetooth) – SISO Ant 2

Bluetooth Time of Occupancy Calculation


Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.880 \text{ ms/channel} = 307.20 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.880 \text{ ms/channel} = 153.56 \text{ ms}$ (worst case dwell time for one channel in AFH mode)

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 94 of 146



Plot 7-131. Time of Occupancy Plot (Bluetooth) – MIMO Ant 1

Bluetooth Time of Occupancy Calculation


Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.875 \text{ ms/channel} = 306.67 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.875 \text{ ms/channel} = 153.30 \text{ ms}$ (worst case dwell time for one channel in AFH mode)

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 95 of 146



Plot 7-132. Time of Occupancy Plot (Bluetooth) – MIMO Ant 2

Bluetooth Time of Occupancy Calculation

Typically, Bluetooth 1x/EDR mode has a channel hopping rate of 1600 hops/s. Since 1x/EDR modes use 5 transmit and 1 receive slot, for a total of 6 slots, the Bluetooth transmitter is actually hopping at a rate of $1600 / 6 = 266.67$ hops/s/slot

- $400\text{ms} \times 79$ hopping channels = 31.6 sec (Time of Occupancy Limit)
- Worst case BT has 266.67 hops/second (for 1x/EDR modes with DH5 operation)
- $266.67 \text{ hops/second} / 79 \text{ channels} = 3.38 \text{ hops/second}$ (# of hops/second on one channel)
- $3.38 \text{ hops/second/channel} \times 31.6 \text{ seconds} = 106.67 \text{ hops}$ (# hops over a 31.6 second period)
- $106.67 \text{ hops} \times 2.875 \text{ ms/channel} = 306.67 \text{ ms}$ (worst case dwell time for one channel in 1x/EDR modes)

With AFH, the number of channels is reduced to a minimum of 20 channels and the channel hopping rate is reduced by 50% to 800 hops/s. AFH mode also uses 6 total slots so the Bluetooth transmitter hops at a rate of $800 / 6 = 133.3$ hops/s/slot

- $400\text{ms} \times 20$ hopping channels = 8 sec (Time of Occupancy Limit)
- Worst case BT has 133.3 hops/second/slot (for AFH mode with DH5 operation)
- $133.3 \text{ hops/s} / 20 \text{ channels} = 6.67 \text{ hops/second}$ (# of hops/second on one channel)
- $6.67 \text{ hops/s} / \text{channel} \times 8 \text{ seconds} = 53.34 \text{ hops}$ (# hops over a 8 second period)
- $53.34 \text{ hops} \times 2.875 \text{ ms/channel} = 153.30 \text{ ms}$ (worst case dwell time for one channel in AFH mode)
-

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 96 of 146

7.7 Number of Hopping Channels

Test Overview and Limit

Measurement is made while EUT is operating in hopping mode. ***This frequency hopping system must employ a minimum of 15 hopping channels.***

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.3

Test Settings

1. Span = frequency of band of operation (divided into two plots)
2. RBW < 30% of channel spacing or 20dB bandwidth, whichever is smaller
3. VBW ≥ RBW
4. Sweep = auto
5. Detector = peak
6. Trace mode = max hold
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-6. Test Instrument & Measurement Setup


Test Notes

The frequency spectrum was broken up into two sub-ranges to clearly show all the hopping frequencies. In AFH mode, this device operates using 20 channels so the requirement for minimum number of hopping channels is satisfied.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 97 of 146




Plot 7-133. Low End Spectrum Channel Hopping Plot (Bluetooth) – SISO Ant 1




Plot 7-134. High End Spectrum Channel Hopping Plot (Bluetooth) – SISO Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 98 of 146




Plot 7-135. Low End Spectrum Channel Hopping Plot (Bluetooth) – SISO ANT 2




Plot 7-136. High End Spectrum Channel Hopping Plot (Bluetooth) – SISO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 99 of 146




Plot 7-137. Low End Spectrum Channel Hopping Plot (Bluetooth) – MIMO Ant 1




Plot 7-138. High End Spectrum Channel Hopping Plot (Bluetooth) – MIMO Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 100 of 146



Plot 7-139. Low End Spectrum Channel Hopping Plot (Bluetooth) – MIMO ANT 2



Plot 7-140. High End Spectrum Channel Hopping Plot (Bluetooth) – MIMO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 101 of 146

7.8 Conducted Spurious Emissions

Test Overview and Limit

Conducted out-of-band spurious emissions were investigated from 30MHz up to 25GHz to include the 10th harmonic of the fundamental transmit frequency. **The maximum permissible out-of-band emission level is 20 dBc.**

Test Procedure Used

ANSI C63.10:2020 – Section 7.8.7

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz* (See note below)
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Test Instrument & Measurement Setup


Test Notes

Out-of-band conducted spurious emissions were investigated for all data rates and the worst-case emissions were found with the EUT transmitting at N/AMbps. The display line shown in the following plots is the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, the traces in the following plots are measured with a 1MHz RBW to reduce test time, so the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 102 of 146




Plot 7-141. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 1




Plot 7-142. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L	 This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.			Page 103 of 146




Plot 7-143. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 1




Plot 7-144. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 104 of 146




Plot 7-145. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 1




Plot 7-146. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 105 of 146




Plot 7-147. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 2




Plot 7-148. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – SISO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 106 of 146




Plot 7-149. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 2




Plot 7-150. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – SISO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 107 of 146




Plot 7-151. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 2




Plot 7-152. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – SISO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 108 of 146




Plot 7-153. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – MIMO ANT 1




Plot 7-154. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – MIMO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 109 of 146




Plot 7-155. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – MIMO ANT 1




Plot 7-156. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – MIMO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 110 of 146




Plot 7-157. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – MIMO ANT 1




Plot 7-158. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – MIMO ANT 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 111 of 146




Plot 7-159. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – MIMO ANT 2




Plot 7-160. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 0) – MIMO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 112 of 146




Plot 7-161. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – MIMO ANT 2




Plot 7-162. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 39) – MIMO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 113 of 146



Plot 7-163. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – MIMO ANT 2



Plot 7-164. Conducted Spurious Plot (Bluetooth, 3Mbps – Ch. 78) – MIMO ANT 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 114 of 146

7.9 Radiated Spurious Emission Measurements – Above 1GHz

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-13. Radiated Limits

Test Procedure Used

ANSI C63.10:2020 – Section 6.6.4.3

Test Settings

Average Field Strength Measurements per Section 4.1.5.2.3 of ANSI C63.10:2020

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 1kHz $\geq 1/\tau$ Hz, where τ = pulse width in seconds
4. Averaging type was set to RMS to ensure that video filtering was applied in the power domain
5. Detector = peak
6. Sweep time = auto
7. Trace mode = max hold
8. Trace was allowed to stabilize

Peak Field Strength Measurements per Section 4.1.5.2.2 of ANSI C63.10:2020

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW is set depending on measurement frequency, as specified in Table 7-14 below
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 115 of 146

Frequency	RBW
9 – 150kHz	200 – 300Hz
0.15 – 30MHz	9 – 10kHz
30 – 1000MHz	100 – 120kHz
> 1000MHz	1MHz

Table 7-14. RBW as a Function of Frequency

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-8. Radiated Test Setup >1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in §15.209.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
6. The duty cycle correction factor was not applied to noise floor measurements.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables is used to denote a noise floor measurement.
9. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 116 of 146

Sample Calculation

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]} + \text{Duty Cycle Correction}_{[dB]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$


Duty Cycle Correction Factor Calculation

- Channel hop rate = 800 hops/second (AFHMode)
- Adjusted channel hop rate for DH5 mode = 133.33 hops/second
- Time per channel hop = $1 / 133.33 \text{ hops/second} = 7.50 \text{ ms}$
- Time to cycle through all channels = $7.50 \times 20 \text{ channels} = 150 \text{ ms}$
- Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1 \text{ time(s)}$
- Worst case dwell time = 7.5 ms
- Duty cycle correction factor = $20\log_{10}(7.5\text{ms}/100\text{ms}) = -22.5 \text{ dB}$


FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 117 of 146

Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]



Plot 7-165. Radiated Spurious Plot above 1GHz (BT – Ch. 0) – Ant 1



Plot 7-166. Radiated Spurious Plot above 1GHz (BT – Ch. 39) – Ant 1




Plot 7-167. Radiated Spurious Plot above 1GHz (BT – Ch. 78) – Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 118 of 146

Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-168. Radiated Spurious Plot above 18GHz – Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 119 of 146

Radiated Spurious Emission Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Avg	H	383	358	-77.41	2.24	-22.50	9.33	53.98	-44.65
4804.00	Peak	H	383	358	-56.89	2.24	0.00	52.35	73.98	-21.63
12010.00	Avg	H	-	-	-79.06	12.88	0.00	40.82	53.98	-13.16
12010.00	Peak	H	-	-	-72.36	12.88	0.00	47.52	73.98	-26.46

Table 7-15. Radiated Measurements – Ant 1

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	357	245	-76.08	2.72	-22.50	11.14	53.98	-42.84
4882.00	Peak	H	357	245	-64.69	2.72	0.00	45.03	73.98	-28.95
7323.00	Avg	H	392	165	-74.22	8.98	-22.50	19.26	53.98	-34.72
7323.00	Peak	H	392	165	-63.10	8.98	0.00	52.88	73.98	-21.10
12205.00	Avg	H	-	-	-78.55	12.56	0.00	41.01	53.98	-12.97
12205.00	Peak	H	-	-	-72.78	12.56	0.00	46.78	73.98	-27.20

Table 7-16. Radiated Measurements– Ant 1

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 120 of 146

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	386	58	-71.73	2.79	-22.50	15.56	53.98	-38.42
4960.00	Peak	H	386	58	-68.26	2.79	0.00	41.53	73.98	-32.45
7440.00	Avg	H	385	58	-74.53	8.54	-22.50	18.51	53.98	-35.47
7440.00	Peak	H	385	58	-69.34	8.54	0.00	46.20	73.98	-27.78
12400.00	Avg	H	-	-	-74.66	12.67	0.00	45.01	53.98	-8.97
12400.00	Peak	H	-	-	-72.58	12.67	0.00	47.09	73.98	-26.89

Table 7-17. Radiated Measurements – Ant 1

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	295	193	-77.47	2.72	-22.50	9.75	53.98	-44.23
4882.00	Peak	H	295	193	-64.97	2.72	0.00	44.75	73.98	-29.23
7323.00	Avg	H	147	346	-77.95	8.98	-22.50	15.53	53.98	-38.45
7323.00	Peak	H	147	346	-60.93	8.98	0.00	55.05	73.98	-18.93
12205.00	Avg	H	-	-	-78.93	12.56	0.00	40.63	53.98	-13.35
12205.00	Peak	H	-	-	-74.62	12.56	0.00	44.94	73.98	-29.04

Table 7-18. Radiated Measurements – Ant 1 - WCP


FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 121 of 146

Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]



Plot 7-169. Radiated Spurious Plot above 1GHz (BT – Ch. 0) – Ant 2



Plot 7-170. Radiated Spurious Plot above 1GHz (BT – Ch. 39) – Ant 2




Plot 7-171. Radiated Spurious Plot above 1GHz (BT – Ch. 78) – Ant 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 122 of 146

Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-172. Radiated Spurious Plot above 18GHz – Ant 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 123 of 146

Radiated Spurious Emission Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Avg	H	-	-	-77.06	2.24	32.18	53.98	-21.80
4804.00	Peak	H	-	-	-71.70	2.24	37.54	73.98	-36.44
12010.00	Avg	H	-	-	-78.80	12.88	41.08	53.98	-12.90
12010.00	Peak	H	-	-	-72.62	12.88	47.26	73.98	-26.72

Table 7-19. Radiated Measurements – Ant 2

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	-	-	-77.46	2.72	32.26	53.98	-21.72
4882.00	Peak	H	-	-	-71.85	2.72	37.87	73.98	-36.11
7323.00	Avg	H	-	-	-78.00	8.98	37.98	53.98	-16.00
7323.00	Peak	H	-	-	-72.13	8.98	43.85	73.98	-30.13
12205.00	Avg	H	-	-	-78.92	12.56	40.64	53.98	-13.34
12205.00	Peak	H	-	-	-72.64	12.56	46.92	73.98	-27.06

Table 7-20. Radiated Measurements – Ant 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 124 of 146

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	-	-	-76.59	2.79	33.20	53.98	-20.78
4960.00	Peak	H	-	-	-71.90	2.79	37.89	73.98	-36.09
7440.00	Avg	H	-	-	-78.18	8.54	37.36	53.98	-16.62
7440.00	Peak	H	-	-	-72.26	8.54	43.28	73.98	-30.70
12400.00	Avg	H	-	-	-78.62	12.67	41.05	53.98	-12.93
12400.00	Peak	H	-	-	-72.24	12.67	47.43	73.98	-26.55

Table 7-21. Radiated Measurements – Ant 2

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	-	-	-77.40	2.72	32.32	53.98	-21.66
4882.00	Peak	H	-	-	-70.20	2.72	39.52	73.98	-34.46
7323.00	Avg	H	-	-	-77.95	8.98	38.03	53.98	-15.95
7323.00	Peak	H	-	-	-70.29	8.98	45.69	73.98	-28.29
12205.00	Avg	H	-	-	-76.36	12.56	43.20	53.98	-10.78
12205.00	Peak	H	-	-	-70.94	12.56	48.62	73.98	-25.36

Table 7-22. Radiated Measurements – Ant 2 - WCP


FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 125 of 146

Radiated Spurious Emission Measurements


§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]



Plot 7-173. Radiated Spurious Plot above 1GHz (BT – Ch. 0) – MIMO



Plot 7-174. Radiated Spurious Plot above 1GHz (BT – Ch. 39) – MIMO




Plot 7-175. Radiated Spurious Plot above 1GHz (BT – Ch. 78) – MIMO

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 126 of 146

Radiated Spurious Emissions Measurements (Above 18GHz)

§15.209; RSS-Gen [8.9]



Plot 7-176. Radiated Spurious Plot above 18GHz – MIMO

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 127 of 146

Radiated Spurious Emission Measurements

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2402MHz
Channel: 0

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Avg	H	-	-	-74.42	-0.81	31.77	53.98	-22.21
4804.00	Peak	H	-	-	-68.04	-0.81	38.15	73.98	-35.83
12010.00	Avg	H	-	-	-77.04	9.90	39.86	53.98	-14.11
12010.00	Peak	H	-	-	-71.23	9.90	45.67	73.98	-28.30

Table 7-23. Radiated Measurements – MIMO

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	-	-	-74.11	-0.50	32.39	53.98	-21.59
4882.00	Peak	H	-	-	-68.16	-0.50	38.34	73.98	-35.64
7323.00	Avg	H	-	-	-75.83	4.39	35.56	53.98	-18.42
7323.00	Peak	H	-	-	-69.33	4.39	42.06	73.98	-31.92
12205.00	Avg	H	-	-	-77.40	9.35	38.95	53.98	-15.03
12205.00	Peak	H	-	-	-70.99	9.35	45.36	73.98	-28.62

Table 7-24. Radiated Measurements – MIMO

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 128 of 146

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2480MHz
Channel: 78

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4960.00	Avg	H	-	-	-74.38	-0.36	32.26	53.98	-21.72
4960.00	Peak	H	-	-	-68.56	-0.36	38.08	73.98	-35.90
7440.00	Avg	H	-	-	-75.45	4.30	35.85	53.98	-18.13
7440.00	Peak	H	-	-	-68.66	4.30	42.64	73.98	-31.34
12400.00	Avg	H	-	-	-78.14	9.55	38.41	53.98	-15.57
12400.00	Peak	H	-	-	-71.94	9.55	44.61	73.98	-29.37

Table 7-25. Radiated Measurements – MIMO

Worst Case Mode: Bluetooth
Worst Case Data Rate: 1 Mbps
Measurement Distance: 3 Meters
Operating Frequency: 2441MHz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4882.00	Avg	H	-	-	-74.16	-0.50	32.34	53.98	-21.64
4882.00	Peak	H	-	-	-67.95	-0.50	38.55	73.98	-35.43
7323.00	Avg	H	-	-	-76.08	4.39	35.31	53.98	-18.67
7323.00	Peak	H	-	-	-68.73	4.39	42.66	73.98	-31.32
12205.00	Avg	H	-	-	-77.41	9.35	38.94	53.98	-15.04
12205.00	Peak	H	-	-	-71.21	9.35	45.14	73.98	-28.84

Table 7-26. Radiated Measurements with WCP – MIMO

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 129 of 146

7.10 Radiated Restricted Band Edge Measurements

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated emissions at the band edge are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power, at the appropriate frequencies, and with hopping disabled. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-27. Radiated Limits

Test Procedure Used

ANSI C63.10:2020 – Section 6.10.5.2

Test Settings

1. Span is set large enough to capture the peak level of the emission operating on the channel closest to the band edge
2. Reference level offset is set with the appropriate corrections for the frequencies shown in the plots
3. Reference level is set to provide the appropriate amount of “head room” above the signal as specified in ANSI C63.10:2020 Section 4.1.6.2
4. Attenuation is set to a low enough level to maintain enough dynamic range between the noise floor and the radiated limit
5. Sweep time = Auto coupled
6. RBW = 1MHz
7. VBW = 3 x RBW for peak measurements and 1kHz for RMS measurements
8. Detector = RMS and peak
9. Trace = Max Hold
10. Trace was allowed to stabilize

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 130 of 146

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-9. Radiated Test Setup >1GHz

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limits shown in §15.209.
2. No significant radiated emissions were found in the 2310 - 2390MHz restricted band.
3. The antenna is manipulated through typical positions, polarity, and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
6. Two different amplitude offsets were used depending on whether peak or average measurements were measured. The average measurements use a duty cycle correction factor (DCCF).

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain} + \text{DCCF}$$


7. The "-" shown in the following RSE tables is used to denote a noise floor measurement.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 131 of 146


Radiated Restricted Band Edge Measurements – Ant 1

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]


Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78




Plot 7-177. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-178. Radiated Restricted Upper Band Edge Measurement (Peak)



Plot 7-179. Radiated Restricted Upper Band Edge Measurement (Average) – with WCP




Plot 7-180. Radiated Restricted Upper Band Edge Measurement (Peak) – with WCP

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 132 of 146


Radiated Restricted Band Edge Measurements – Ant 2

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]


Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78




Plot 7-181. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-182. Radiated Restricted Upper Band Edge Measurement (Peak)



Plot 7-183. Radiated Restricted Upper Band Edge Measurement (Average) – with WCP




Plot 7-184. Radiated Restricted Upper Band Edge Measurement (Peak) – with WCP

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 133 of 146


Radiated Restricted Band Edge Measurements – Dual

§15.205 §15.209 §15.247 (d); RSS-Gen [8.9]


Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78




Plot 7-185. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-186. Radiated Restricted Upper Band Edge Measurement (Peak)



Plot 7-187. Radiated Restricted Upper Band Edge Measurement (Average) – with WCP



Plot 7-188. Radiated Restricted Upper Band Edge Measurement (Peak) – with WCP

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 134 of 146

7.11 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions must not exceed the limits shown below per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-28. Radiated Limits

Test Procedures Used

ANSI C63.10:2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 135 of 146

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-10. Radiated Test Setup < 30Mhz




Figure 7-11. Radiated Test Setup < 1GHz

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 136 of 146


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limits shown in §15.209.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 137 of 146

Radiated Spurious Emissions Measurements (Below 1GHz)


§15.209; RSS-Gen [8.9]



Plot 7-189. Radiated Spurious Plot below 1GHz – Ant 1

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
109.80	Quasi-Peak	H	-	-	-96.54	19.31	29.77	43.52	-13.76
309.85	Quasi-Peak	H	-	-	-96.98	21.23	31.25	46.02	-14.77
545.95	Quasi-Peak	H	-	-	-96.86	26.19	36.33	46.02	-9.69

Table 7-29. Radiated Spurious Emissions Below 1GHz – Ant 1




Plot 7-190. Radiated Spurious Plot below 1GHz – Ant 2

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
60.55	Quasi-Peak	H	-	-	-94.85	14.24	26.39	40.00	-13.61

Table 7-30. Radiated Spurious Emissions Below 1GHz – Ant 2

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 138 of 146



Plot 7-191. Radiated Spurious Plot below 1GHz – MIMO

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
766.40	Quasi-Peak	H	-	-	-95.39	29.33	40.94	46.02	-5.08

Table 7-31. Radiated Spurious Emissions Below 1GHz – MIMO

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 139 of 146

7.12 Line Conducted Measurement Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-32. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10:2020, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 140 of 146

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-12. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated, and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207 and RSS-Gen (8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 141 of 146



Plot 7-192. Line-Conducted Test Plot (L1)





Table 7-33. Line-Conducted Test Data (N)

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 142 of 146



Plot 7-193. Line-Conducted Test Plot (L1) - WCP




Table 7-34. Line-Conducted Test Data (N) - WCP

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 143 of 146

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF776JPN** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules. The data referenced from **FCC ID: A3LSMF776U** (Model SM-F776U) included in this report have been reviewed and are deemed acceptable to support the compliance of **FCC ID: A3LSMF776JPN**.

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 144 of 146

9.0 APPENDIX A – DATA REFERENCING SPOT-CHECKS

Overview

The spot-check data presented in this section was measured on the variant model following the guidance of the FCC's Data Referencing guidance in KDB 484596 D01 v03. Each spot-check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device. For the worst-case RSE data, the measurement is determined by an actual emission and not by noise floor.

All test cases were performed to verify the variant EUT is still in compliance with the spot-checked results to the reference device and was performed using the guidance of ANSI C63.10:2020.

Notes


Each spot check test on the EUT was performed using the same procedure and setting that were used to perform the test on the corresponding reference device.

Radiated Spot-Checks – Model: SC-55G

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Duty Cycle Correction [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
7323.00	Avg	H	397	64	-77.21	8.19	-22.50	15.48	53.98	-38.49

Table 9-1. RSE Measurements (Spot-check)

Worst Case Mode:	Bluetooth
Worst Case Data Rate:	3 Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480MHz
Channel:	78



Plot 9-1. Radiated Restricted Upper Band Edge Measurement (Average)

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 145 of 146

Results

FCC Rules	Test Item	Test Case	Units	Limit	Reference Model: A3LSMF776U	Variant Model: A3LSMF776JPN	Deviation (dB)	Max Deviation (dB)	Pass/Fail
15.209	Radiated Spurious Emissions	SISO ANT1 - Ch.39 - Average - 7323MHz	dBuV/m	53.98	19.26	15.48	-3.78	4.925*	PASS
15.209	Radiated Band Edge Emissions	MIMO Ch.78 - Average	dBuV/m	53.98	40.82	38.22	-2.60	3	PASS

Table 9-2. Summary of Spot-checks

Note: the maximization deviation tolerance of 4.925dB from Radiated Spurious Emission is calculated from guidance in KDB 484596 D01 v03 section 3.2.1, $d_{dBmax}(M_{dB}) = (3 + M_{dB} / 20) \text{ dB}$, for $0 \leq M_{dB} \leq 60 \text{ dB}$

- END OF TEST REPORT -

FCC ID: A3LSMF776JPN	MEASUREMENT REPORT (CERTIFICATION)	Test Dates: 2/24/2026 - 5/21/2026	EUT Type: Portable Handset	Approved by: Technical Manager
Test Report S/N: 1M2604240033-05-R1.A3L		This report is Blockchain Verified. To verify the report authenticity, please visit HTTPS://WWW.BLOCKCHAIN-VERIFIED.COM or by clicking on the Blockchain logo.		Page 146 of 146