EMC TEST REPORT

Project No.	LBE20190548	**Issue No.**	0
Applicant	**Name of organization**	Samsung Electronics Co., Ltd.	
	Address	(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea	
	Date of application	March 22, 2019	
EUT	**Type of device**	☒ All other Receivers subject to part15 ☒ Class B Personal Computers and peripherals ☒ Other Class B digital devices and peripherals ☒ FM Broadcast Receiver	
	Equipment authorization	☒ Certification ☐ Supplier's Declaration of Conformity	
	FCC ID	A3LSMF907N	
	Kind of product	Mobile Phone	
	Model No.	SM-F907N	
	Variant Model No.	Refer to clause 4.6	
	Manufacturer	SAMSUNG ELECTRONICS CO., LTD 94-1, Imsu-dong, Gumi-si, Gyengsangbuk-do, 730-722, Republic of Korea	
		SAMSUNG ELECTRONICS HUIZHOU CO.,LTD. 516229, Chenjiang Town, HuiZhou City, Guangdong Province, China	
Applied Standards		47 CFR Part 15, Subpart B, Class B / ANSI C63.4-2014	
Test Period		March 26, 2019 ~ April 12, 2019	
Issue date		April 15, 2019	

Test result : Complied

The equipment under test has found to be compliant with the applied standards.
(Refer to the attached test result for more detail.)

Tested by : Soo-Joon Kim S. J. Kim	**Reviewed by** : Young-Hun Kim Y. H. Kim

The test results in this report only apply to the tested sample. This report must not be reproduced, except in full, without written permission from Global CS Center.

Global CS Center of Samsung Electronics Co., Ltd.
(Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea

Table of contents

1. Report Information

1.1 Revision history ---- 3

2. Summary of test results

2.1 Emission ---- 3

3. General Information

3.1 Test facility ---- 3

4. Test Configuration

4.1 Test Peripherals ---- 4

4.2 EUT operating mode ---- 5

4.3 Details of Sampling ---- 5

4.4 Used cable description ---- 6

4.5 Test arrangement ---- 7

4.6 EUT Description ---- 11

4.7 EUT Frequencies ---- 11

4.8 Test configuration and condition ---- 12

4.9 Measurement uncertainty ---- 12

5. Result of individual tests

5.1 Conducted disturbance ---- 13

5.2 Radiated disturbance ---- 19

This report must not be reproduced, except in full, without written permission from Global CS Center.

1. Report Information

1.1 Revision history

No.	Revised detailed information
Issue 0	There are no revisions and this version is basic test report.

1.2 RSE test report no.

No.	Remark
1M1902200029-15	The cellular receiver mode refers to the radiated spurious emissions test report.

2. Summary of test results

2.1 Emission

The EUT has been tested according to the following specifications:

Applied	Test type	Applied standard	Result
☒	Conducted Disturbance (Mains port)	47 CFR Part 15 Subpart B / ANSI C63.4-2014 (Class B)	Complied
☒	Radiated Disturbance		Complied

3. General Information

3.1 Test facility

The Global CS Center is located on Samsung Electronics Co., Ltd. at (Maetan-dong) 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Republic of Korea.
All testing are performed in Semi-anechoic chambers conforming to the site attenuation characteristics defined by ANSI C63.4, CISPR 32, CISPR 16-1-4 and Shielded rooms.
And all antennas are properly calibrated using ANSI C63.5:2017.

The Global CS Center is operated as testing laboratory in accordance with the requirements of ISO/IEC 17025:2005.

This report must not be reproduced, except in full, without written permission from Global CS Center.

4. Test Setup configuration

4.1 Test Peripherals

The cables used for these peripherals are either permanently attached by the peripheral manufacturer or coupled with an assigned cable as defined below.
The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Mark	Description	Model No.	Serial No.	Manufacturer / Trademark	FCC ID
A	Mobile Phone	SM-F907N	-	SAMSUNG	A3LSMF907N
B	Battery	Main: EB-BF907ABA Sub: EB-BF901ABA	-	SAMSUNG	-
C	Headset	SM-R170	-	SAMSUNG	-
D	Data Cable	EP-DG970BBE	-	SAMSUNG	-
E	Travel Adapter	EP-TA200	R37M19A0051DK3	SAMSUNG	-
F	Laptop Computer	Latitude5580	1CHRYM2	Dell	-
			D3HRYM2	Dell	-
G	Router	DIR-806A	RF0F1D5000688	D-Link	-
			RF0F1D8011504	ASUS	-
H	Mouse	AA-SM7PCP	BDV8J48P4393	SAMSUNG	-
		SC-1000	1034000281	SAMSUNG	-
I	Laptop AC Adapter	LA65NM130	5D77	Dell	-
			5DEA	Dell	-
J	OTG Gender	EE-UG970	-	SAMSUNG	-
K	DP Cable	JCA141	BW1B1607001082	J5create	-
L	Monitor	27UD88	605NTHM9B769	LG	-
M	Monitor AC Adaptor	LCAP31	EG3VN629490050658	LG	-
N	USB memory stick	64GB	-	Sandisk	-
O	FM Radio Antenna	GH81-17060A	-	SAMSUNG	-

This report must not be reproduced, except in full, without written permission from Global CS Center.

4.2 EUT operating mode

To achieve compliance applied standard specification, the following mode(s) were made during compliance testing:

4.2.1 Conducted Emission

No.	Operating mode
1	Camera (tripple) + Charging (w/ TA) + Cellular receiver (GSM850 Center Frequency)
2	Camera (dual) + Charging (w/ TA)
3	Camera (single) + Charging (w/ TA)
4	Video + Audio playback from internal memory data + Charging (w/ TA)
5	USB Data Communication with PC (from external memory data)

4.2.2 Radiated Emission

No.	Operating mode
1	Camera (tripple) + Charging (w/ TA)
2	Camera (dual) +USB OTG (USB memory stick)
3	Camera (single) + FM (Low Ch.)
4	FM (Mid Ch.)
5	FM (High Ch.)
6	Video + Audio playback from internal memory data + Display out(Direct DP Cable)
7	USB Data Communication with PC (from external memory data)

4.3 Details of Sampling

Customer selected, single unit.

This report must not be reproduced, except in full, without written permission from Global CS Center.

4.4 Used cable description

The EUT is configured, installed, arranged and operated in a manner consistent with typical applications. Interface cables/loads/devices are connected to at least one of each type of interface port of the EUT, and where practical, each cable shall be terminated in a device typical of actual usage. The type(s) of interconnecting cables to be used and the interface port (of the EUT) to which these were connected:

No.	Connected cable	Length [m]	Shielded [Y/N]	Note
1	Data Cable	1.0	Yes	From EUT to Laptop Computer
2	DP Cable	1.1	Yes	From EUT to DP Monitor
3	Power	1.8	No	From Laptop Computer to AC Adapter
4	Power	1.2	No	From Monitor to AC Adapter
5	Power	1.5	No	For Laptop AC Adapter
6	Power	1.8	No	For Monitor AC Adpater
7	LAN	1.5	No	From Laptop Computer to Router
8	USB	0.8	Yes	From Laptop Computer PC to Router
9	USB	1.8	Yes	From Laptop Computer to Mouse

This report must not be reproduced, except in full, without written permission from Global CS Center.

4.5 Test arrangement

4.5.1 Conducted Emission



[Mode 1 ~ 4]



[Mode 5]

This report must not be reproduced, except in full, without written permission from Global CS Center.

Form No.: SRA-TRF-46/8

4.5.2 Radiated Emission



[Mode 1]

[Mode 2]

This report must not be reproduced, except in full, without written permission from Global CS Center.



[Mode 3 - 5]



[Mode 6]

This report must not be reproduced, except in full, without written permission from Global CS Center.

Form No.: SRA-TRF-46/8



[Mode 7]

This report must not be reproduced, except in full, without written permission from Global CS Center.

4.6 EUT Description

The EUT is a foldable type mobile phone which can operate on GSM850/900/1800/1900, WCDMA FDD1/2/4/5/8, LTE FDD1/2/3/4/5/7/8/12/13/18/19/20/25/26/28/66, LTE TDD38/39/40/41, TD-SCDMA B34/39 bands and incorporates a Camera, Bluetooth, Wi-Fi, ANT+, MST, NFC, GNSS, DP, OTG, FM Radio, MP3 and MP4 player.

4.6.1 The variant models

- None

4.7 EUT Frequencies

The highest frequencies (Generated and used)	Frequency [MHz]
Wi-Fi	5 825

This report must not be reproduced, except in full, without written permission from Global CS Center.

4.8 Test configuration and condition

The system was configured for testing in a typical fashion that a customer would normally use. Cables were attached to each of the available I/O Ports. Where applicable, peripherals were attached to the I/O cables. All the external I/O ports are exercised, as well as internal and the external SD card if available, by writing and reading arbitrary data or charging with TA.

The EUT was investigated in three orientations and the worst case orientation is reported.

RX mode(850MHz) testing was performed with the GSM850 RX Test mode at center frequency. All licensed communication (850MHz) RX mode, GSM/WCDMA/LTE, test results are not significantly different.

The FM radio mode radiated testing was performed with the Low/Mid/High channel.

The video and music were repetitively played with the wirelessly connected earphone.

The video and music were played on monitor through Display Out function using direct DP Cable or DP converter.

The EUT was connected to USB memory stick using USB OTG gender

The camera of the EUT was operated continuously.

Power source for the EUT operating was supplied by CVCF made by the Pacific Corp.

- Test Voltage : AC 120 V, 60 Hz

4.9 Measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus: (According to CISPR 16-4-2 and UKAS M3003)

4.9.1 Emission

Test type		Measurement uncertainty (C.L. 95 %, k = 2)
Conducted disturbance	AC Mains	3.52 dB
Radiated Disturbance (Below 1 GHz)	Horizontal	4.99 dB
	Vertical	4.90 dB
Radiated Disturbance (Above 1 GHz)	Horizontal	5.33 dB
	Vertical	5.32 dB

This report must not be reproduced, except in full, without written permission from Global CS Center.

5. Results of individual test

5.1 Conducted disturbance

The EUT is connected to a LISN via travel adapter. If the EUT is connected to the Laptop Computer USB port, the Laptop AC adapter is connected to a LISN.

Both conducted lines are measured in Quasi-Peak and CISPR-Average mode, including the worst-case data points for each tested configuration. The EUT measured in accordance with the methods described in standards.

Limits for conducted disturbance at the mains ports of Class B ITE

Frequency range Limits [MHz]	Resolution Bandwidth [kHz]	Limits [dB(μV)]	
		Quasi-peak	Average
0,15 to 0,50	9	66 to 56	56 to 46
0,50 to 5	9	56	46
5 to 30	9	60	50
NOTE 1 The lower limit shall apply at the transition frequency. NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.			

5.1.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-127	Two-Line -Network	ENV216	R&S	102061	2018-07-23	12
E5I-017	EMI Test Receiver	ESU8	R&S	100483	2019-01-16	12
-	Test software	EMC32	R&S	Ver 9.26.01	-	-

5.1.2 Temperature and humidity condition

Test date	2019-04-11 ~ 2019-04-12	**Test engineer**	Soo-Joon Kim
Climate condition	Ambient temperature	(22.6 ~ 22.9) ℃	Limit (15.0 to 35.0) ℃
	Relative humidity	(39.8 ~ 41.0) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(101.1 ~ 101.6) kPa	Limit (86.0 to 106.0) kPa
Test place	Shield Room (SR8)		

This report must not be reproduced, except in full, without written permission from Global CS Center.

5.1.3 Test results

☐ Operating Mode 1: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.209	41.9	---	63.3	21.4	L1	10.0
0.213	---	26.8	53.1	26.3	N	9.9
0.562	---	23.7	46.0	22.3	L1	10.2
0.566	32.3	---	56.0	23.7	L1	10.2
0.632	38.6	---	56.0	17.4	L1	10.2
0.634	---	31.9	46.0	14.1	L1	10.2
0.699	37.3	---	56.0	18.7	L1	10.1
0.706	---	31.9	46.0	14.1	L1	10.1
4.920	29.7	---	56.0	26.3	L1	10.0
4.990	---	20.6	46.0	25.4	L1	10.0
9.089	32.4	---	60.0	27.6	L1	10.1
9.492	---	24.6	50.0	25.4	L1	10.1

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 2: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.211	43.7	---	63.2	19.5	L1	10.0
0.213	---	27.5	53.1	25.6	N	9.9
0.560	32.9	---	56.0	23.1	L1	10.2
0.564	---	24.1	46.0	21.9	L1	10.2
0.634	38.3	---	56.0	17.7	L1	10.2
0.634	---	31.9	46.0	14.1	L1	10.2
0.706	---	32.1	46.0	13.9	N	10.0
0.708	37.4	---	56.0	18.6	L1	10.1
4.900	27.9	---	56.0	28.1	L1	10.0
4.990	---	20.7	46.0	25.3	L1	10.0
9.488	33.8	---	60.0	26.2	L1	10.1
9.492	---	24.6	50.0	25.4	L1	10.1

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 3: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.211	44.9	---	63.2	18.3	L1	10.0
0.213	---	28.4	53.1	24.7	N	9.9
0.562	33.3	---	56.0	22.7	L1	10.2
0.564	---	24.2	46.0	21.8	L1	10.2
0.634	37.8	---	56.0	18.2	L1	10.2
0.636	---	31.6	46.0	14.4	L1	10.2
0.701	37.6	---	56.0	18.4	L1	10.1
0.706	---	32.0	46.0	14.0	L1	10.1
4.990	---	20.5	46.0	25.5	L1	10.0
4.994	29.9	---	56.0	26.1	L1	10.0
9.384	30.6	---	60.0	29.4	L1	10.1
9.490	---	24.0	50.0	26.0	L1	10.1

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 4: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.213	---	27.9	53.1	25.2	N	9.9
0.213	44.2	---	63.1	18.9	L1	10.0
0.560	33.1	---	56.0	22.9	L1	10.2
0.564	---	24.1	46.0	21.9	N	10.2
0.629	38.2	---	56.0	17.8	L1	10.2
0.636	---	31.7	46.0	14.3	L1	10.2
0.697	36.1	---	56.0	19.9	L1	10.1
0.706	---	32.1	46.0	13.9	N	10.0
4.918	30.4	---	56.0	25.6	L1	10.0
4.990	---	20.7	46.0	25.3	L1	10.0
9.011	32.0	---	60.0	28.0	L1	10.1
9.492	---	24.5	50.0	25.5	L1	10.1

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 5: AC Mains



Note 1) Two graphs measured for both Live(L1) and Neutral(N) of the LISN are combined into one graph.

QP / CAV final measurement results table:

Frequency (MHz)	QP (dBµV)	CAV (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.150	54.5	---	66.0	11.5	N	9.7
0.150	---	34.6	56.0	21.4	L1	9.8
0.223	40.7	---	62.7	22.0	N	9.8
0.231	---	25.3	52.4	27.1	L1	9.7
0.508	---	27.7	46.0	18.3	L1	10.0
0.509	38.3	---	56.0	17.7	L1	10.0
1.422	---	18.8	46.0	27.2	N	9.8
1.634	25.0	---	56.0	31.0	N	9.8
3.942	---	22.7	46.0	23.3	L1	9.8
4.107	34.1	---	56.0	21.9	L1	9.8
9.886	---	26.7	50.0	23.3	L1	9.8
9.902	33.5	---	60.0	26.5	L1	9.8

Note 2) Level (QP and/or CAV) = Meter Reading (QP and/or CAV) + Corr. (LISN Insertion Loss + Cable Loss)
Margin (QP and/or CAV) = Limit – Level (QP and/or CAV)
QP = Quasi-Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

5.2 Radiated disturbance

The following data lists the significant emission frequencies, measured levels, correction factors (for antenna and cables), orientation of table, polarization and height of antenna, the corrected reading, the limit, and the amount of margin.

Peak measurements were made over the changeable frequency range 30 MHz to 1 GHz at a measurement distance of 10 m for the following antenna and turntable arrangements:

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [kHz]	Video Bandwidth [kHz]	Turntable position [degrees]
100 ~ 400	Horizontal, Vertical	120	300	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.
Final measurements were made using quasi-peak detector.

Peak/CISPR-Average measurements were made over the changeable frequency range 1 GHz to 40 GHz or 5th harmonics of the highest frequency generated or used in the device or on which the device operate or tunes at a measurement distance of 3 m for the following antenna and turntable arrangements. The measurements above 1 GHz were performed with the bore-sighting antenna aimed at the EUT.

Antenna Height [cm]	Antenna Polarisation	Resolution Bandwidth [MHz]	Video Bandwidth [MHz]	Turntable position
100 ~ 400	Horizontal, Vertical	1	3	Continuous

Measurements within 6 dB of the limit were then maximized by adjusting turntable position.
Final measurements were made using peak and CISPR-average detectors.

Limits for radiated disturbance of Class B ITE at a measuring distance of 3 m and 10 m

Frequency range Limits [MHz]	Field Strength		
	3 m [μV/m]	3 m [dB(μV/m)]	10 m [dB(μV/m)]
30 to 88	100	40.0	29.5
88 to 216	150	43.5	33.0
216 to 960	200	46.0	35.5
Above 960	500	54.0	43.5

Results checked manually; and points close to the limit line were re-measured.

This report must not be reproduced, except in full, without written permission from Global CS Center.

5.2.1 Test instrumentation

EMC No.	Test Instrument	Model name	Manufacturer	Serial No.	Calibration	
					Date	Interval (Month)
E5I-022	Signal Generator	SMB100A	R&S	175856	2018-05-11	12
E5I-021	EMI Test Receiver	ESU40	R&S	100376	2019-01-30	12
E5I-016	EMI Test Receiver	ESU8	R&S	100482	2018-06-08	12
E5I-149	Horn Antenna	HF907	R&S	102525	2018-06-15	24
E5I-039	Signal Conditioning Unit	SCU-18	R&S	10211	2019-01-22	12
E5I-037	Wide Band Horn Antenna	WBH 18-40K	R&S	11201	2019-01-31	24
E5I-042	Signal Conditioning Unit	SCU-40A	R&S	10004	2018-09-05	12
E5I-120	BiLog Antenna	CBL6112D	TESEQ	36997	2018-04-23	24
E5I-072	BiLog Antenna	CBL6112D	TESEQ	36009	2018-04-23	24
E5I-075	Preamplifier	310N	SONOMA	332018	2018-05-25	12
E5I-076	Preamplifier	310N	SONOMA	332019	2018-05-25	12
-	Test software	EP7RE	TOYO	Ver 5.8.2	-	-
-	Test software	EMC32	R&S	Ver 9.25.00	-	-

5.2.2 Temperature and humidity condition

Test date	2019-03-26 ~ 2019-03-27	**Test engineer**	Soo-Joon Kim
Climate condition	Ambient temperature	(22.6 ~ 22.9) ℃	Limit (15.0 to 35.0) ℃
	Relative humidity	(42.7 ~ 44.5) % R.H.	Limit (25.0 to 75.0) % R.H.
	Atmospheric pressure	(100.7 ~ 101.9) kPa	Limit (86.0 to 106.0) kPa
Test place	Semi-Anechoic Chamber (SAC4)		

This report must not be reproduced, except in full, without written permission from Global CS Center.

Form No.: SRA-TRF-46/8

5.2.3 Test results

☐ Operating Mode 1

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System	Remark
1	33.516	V	25.5	-7.7	17.8	29.5	11.7	101	281	2	
2	64.071	V	30.1	-18.7	11.4	29.5	18.1	208	80	2	
3	82.138	V	22.6	-17.2	5.4	29.5	24.1	123	297	2	
4	133.911	V	22.0	-11.9	10.1	33.0	22.9	270	0	2	
5	556.346	H	21.4	-3.9	17.5	35.5	18.0	270	0	1	
6	991.391	V	19.2	1.4	20.6	43.5	22.9	125	57	2	

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Radiated emissions (Tx/Rx frequency 2 400 MHz to 2 483.5 MHz) from the transceiver shall be ignored
Note 3) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 2

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System	Remark
1	30.243	V	22.4	-6.6	15.8	29.5	13.7	213	26	2	
2	39.943	V	22.4	-10.5	11.9	29.5	17.6	372	7	2	
3	48.188	V	22.2	-15.7	6.5	29.5	23.0	272	308	2	
4	455.587	H	21.9	-6.4	15.5	35.5	20.0	400	262	1	
5	982.297	H	19.5	1.0	20.5	43.5	23.0	374	73	1	
6	995.877	V	19.1	1.6	20.7	43.5	22.8	324	130	2	

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Radiated emissions (Tx/Rx frequency 2 400 MHz to 2 483.5 MHz) from the transceiver shall be ignored
Note 3) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 3

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System	Remark
1	32.910	V	22.2	-7.5	14.7	29.5	14.8	270	167	2	
2	41.640	H	22.3	-12.3	10.0	29.5	19.5	311	0	1	
3	87.958	V	36.1	-16.2	19.9	29.5	9.6	170	148	2	
4	127.364	V	21.8	-11.9	9.9	33.0	23.1	102	0	2	
5	614.183	H	21.3	-3.9	17.4	35.5	18.1	381	0	1	
6	979.145	V	19.3	1.1	20.4	43.5	23.1	223	0	2	

* Radiated emissions (Rx frequency 87.958 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Radiated emissions (Tx/Rx frequency 2 400 MHz to 2 483.5 MHz) from the transceiver shall be ignored
Note 3) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 4

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System	Remark
1	31.061	H	22.8	-8.8	14.0	29.5	15.5	301	83	1	
2	31.298	V	22.5	-8.9	13.6	29.5	15.9	271	164	2	
3	34.492	H	21.9	-11.3	10.6	29.5	18.9	184	96	1	
4	36.959	V	21.8	-11.4	10.4	29.5	19.1	289	253	2	
5	98.014	V	32.0	-14.1	17.9	33.0	15.1	370	124	2	
6	993.928	H	19.5	1.9	21.4	43.5	22.1	222	173	1	

* Radiated emissions (Rx frequency 98.014 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Radiated emissions (Tx/Rx frequency 2 400 MHz to 2 483.5 MHz) from the transceiver shall be ignored
Note 3) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 5

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System	Remark
1	31.334	H	22.7	-9.0	13.7	29.5	15.8	303	360	1	
2	39.579	V	22.5	-12.7	9.8	29.5	19.7	301	360	2	
3	107.986	V	32.2	-13.3	18.9	33.0	14.1	114	360	2	
4	323.910	H	21.6	-10.0	11.6	35.5	23.9	328	360	1	
5	536.583	H	21.4	-4.9	16.5	35.5	19.0	130	360	1	
6	964.837	V	19.6	1.4	21.0	43.5	22.5	399	360	2	

* Radiated emissions (Rx frequency 107.986 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Radiated emissions (Tx/Rx frequency 2 400 MHz to 2 483.5 MHz) from the transceiver shall be ignored
Note 3) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 6

- Frequencies below 1 GHz



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	System	Remark
1	94.626	V	28.3	-14.5	13.8	33.0	19.2	124	280	2	
2	143.854	V	28.8	-13.7	15.1	33.0	17.9	101	308	2	
3	401.995	H	38.1	-7.3	30.8	35.5	4.7	180	291	1	
4	495.600	H	30.8	-5.5	25.3	35.5	10.2	190	151	1	
5	731.553	H	29.1	-2.5	26.6	35.5	8.9	109	117	1	
6	994.422	H	23.4	2.0	25.4	43.5	18.1	100	212	1	

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Frequency (MHz)	PK (dBµV/m)	CAV (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 047.500	46.6	---	74.0	27.4	100.0	H	55.0	6.1
1 050.000	---	36.4	54.0	17.6	100.0	H	60.0	6.1
5 400.000	---	42.3	54.0	11.7	100.0	H	310.0	6.7
5 400.000	44.8	---	74.0	29.2	100.0	H	310.0	6.7
17 847.500	---	40.7	54.0	13.3	100.0	V	226.0	30.5
17 859.000	45.6	---	74.0	28.4	100.0	H	252.0	30.5

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Radiated emissions (Tx/Rx frequency 2 400 MHz to 2 483.5 MHz) from the transceiver shall be ignored
Note 3) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

☐ Operating Mode 7

- Frequencies below 1 GHz



Final Result

No.	Frequency	(P)	Reading QP	c.f	Result QP	Limit QP	Margin QP	Height	Angle	System	Remark
	[MHz]		[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]		
1	30.121	V	22.8	-7.5	15.3	29.5	14.2	278	131	2	
2	54.008	V	32.8	-18.2	14.6	29.5	14.9	400	2	2	
3	479.959	H	38.0	-6.2	31.8	35.5	3.7	170	23	1	
4	500.086	V	22.3	-4.9	17.4	35.5	18.1	100	35	2	
5	590.054	V	24.0	-3.4	20.6	35.5	14.9	286	4	2	
6	934.525	V	19.7	0.6	20.3	35.5	15.2	100	99	2	

* Radiated emissions (Rx frequency 108.048 MHz) from the transceiver shall be ignored

Note1) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 10 m, Antenna Height : 1 to 4 meters
Result (QP) = Reading (QP) + c.f (Antenna Factor + Cable Loss - Amp. Gain)
Margin (QP) = Limit – Level (QP)
QP = Quasi-Peak, c.f = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.

- Frequencies above 1 GHz



Frequency (MHz)	PK (dBµV/m)	CAV (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
1 598.000	---	28.7	54.0	25.3	100.0	V	124.0	9.4
1 598.000	40.8	---	74.0	33.2	100.0	V	124.0	9.4
1 724.000	47.6	---	74.0	26.4	100.0	V	124.0	10.2
1 724.000	---	42.0	54.0	12.0	100.0	V	124.0	10.2
1 858.000	44.5	---	74.0	29.5	100.0	V	0.0	11.1
1 862.000	---	32.5	54.0	21.5	100.0	V	0.0	11.1
2 125.500	---	35.2	54.0	18.8	100.0	V	202.0	12.4
2 130.000	50.9	---	74.0	23.1	100.0	V	26.0	12.4
2 656.500	---	32.7	54.0	21.3	100.0	V	283.0	14.6
2 678.000	43.8	---	74.0	30.2	100.0	H	0.0	14.7
17 700.000	---	41.6	54.0	12.4	100.0	H	251.0	30.3
17 728.500	46.1	---	74.0	27.9	100.0	H	266.0	30.3

Note 1) We have also tested from 18 GHz to 30 GHz and found no emissions
Note 2) Receiving antenna polarization : Horizontal, Vertical
Test Distance : 3 m, Antenna Height : 1 to 4 meters
Level (PK and/or CAV) = Reading (PK and/or CAV) + Corr. (Antenna Factor + Cable Loss - Amp. Gain)
Margin (PK and/or CAV) = Limit – Level (PK and/or CAV)
PK = Peak, CAV = CISPR-Average, Corr. = Correction Factor

This report must not be reproduced, except in full, without written permission from Global CS Center.