



PART 0 SAR CHAR REPORT

Applicant Name:

Samsung Electronics Co., Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

06/08/21 - 07/23/21

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Document Serial No.:

1M2106280073-05.A3L

FCC ID:

A3LSMF926U

APPLICANT:

SAMSUNG ELECTRONICS CO., LTD

Report Type:

Part 0 SAR Characterization

Application Type:

Class II Permissive Change

DUT Type:

Portable Handset

Model(s):

SM-F926U

Additional Model:

SM-F926U1

Original Date of Certification:

06/23/2021

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Test results reported herein relate only to the item(s) tested.



Randy Ortanez
President



FCC ID: A3LSMF926U	 PCTEST[®] Proud to be part of element	PART 0 SAR CHAR REPORT	 SAMSUNG	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset	Page 1 of 12	

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
1.1	Device Overview	3
1.2	Time-Averaging for SAR and Power Density	4
1.3	Nomenclature for Part 0 Report	4
1.4	Bibliography	4
2	SAR AND POWER DENSITY MEASUREMENTS	5
2.1	SAR Definition	5
2.2	SAR Measurement Procedure	5
3	SAR CHARACTERIZATION	7
3.1	DSI and SAR Determination	7
3.2	SAR Design Target	8
3.3	SAR Char	8
4	EQUIPMENT LIST	11
5	MEASUREMENT UNCERTAINTIES	12
	APPENDIX A: SAR TEST RESULTS FOR P_{Limit} CALCULATIONS	1

FCC ID: A3LSMF926U	 PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset
		Page 2 of 12

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
CDMA/EVDO BC10 (§90S)	Voice/Data	817.90 - 823.10 MHz
CDMA/EVDO BC0 (§22H)	Voice/Data	824.70 - 848.31 MHz
PCS CDMA/EVDO	Voice/Data	1851.25 - 1908.75 MHz
GSM/GPRS/EDGE 850	Voice/Data	824.20 - 848.80 MHz
GSM/GPRS/EDGE 1900	Voice/Data	1850.20 - 1909.80 MHz
UMTS 850	Voice/Data	826.40 - 846.60 MHz
UMTS 1750	Voice/Data	1712.4 - 1752.6 MHz
UMTS 1900	Voice/Data	1852.4 - 1907.6 MHz
LTE Band 71	Voice/Data	673 - 688 MHz
LTE Band 12	Voice/Data	704 - 711 MHz
LTE Band 13	Voice/Data	782 - 782 MHz
LTE Band 14	Voice/Data	793 - 793 MHz
LTE Band 26 (Cell)	Voice/Data	821.5 - 841.5 MHz
LTE Band 5 (Cell)	Voice/Data	829 - 844 MHz
LTE Band 66 (AWS)	Voice/Data	1720 - 1770 MHz
LTE Band 4 (AWS)	Voice/Data	1720 - 1745 MHz
LTE Band 25 (PCS)	Voice/Data	1860 - 1905 MHz
LTE Band 2 (PCS)	Voice/Data	1860 - 1900 MHz
LTE Band 30	Voice/Data	2310 - 2310 MHz
LTE Band 7	Voice/Data	2510 - 2560 MHz
LTE Band 48	Voice/Data	3560 - 3690 MHz
LTE Band 41	Voice/Data	2498.5 - 2687.5 MHz
LTE Band 38	Voice/Data	2580 - 2610 MHz
NR Band n71	Data	665.5 - 695.5 MHz
NR Band n12	Data	701.5 - 713.5 MHz
NR Band n5 (Cell)	Data	826.5 - 846.5 MHz
NR Band n66 (AWS)	Data	1712.5 - 1777.5 MHz
NR Band n25 (PCS)	Data	1852.5 - 1912.5 MHz
NR Band n2 (PCS)	Data	1852.5 - 1907.5 MHz
NR Band n30	Data	2307.5 - 2312.5 MHz
NR Band n41	Data	2506.02 - 2679.99 MHz
NR Band n77 DoD	Data	3460.02 - 3540 MHz
NR Band n77	Data	3710.01 - 3969.99 MHz
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
U-NII-5	Voice/Data	5925 - 6425 MHz
U-NII-6	Voice/Data	6425 - 6525 MHz
U-NII-7	Voice/Data	6525 - 6875 MHz
U-NII-8	Voice/Data	6875 - 7125 MHz
Bluetooth	Data	2402 - 2480 MHz
NFC	Data	13.56 MHz
NR Band n260	Data	37000 - 40000 MHz
NR Band n261	Data	27500 - 28350 MHz
UWB	Data	6489.6 - 7987.2 MHz

FCC ID: A3LSMF926U	 PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset
		Page 3 of 12

This device uses the Qualcomm® Smart Transmit feature to control and manage transmitting power in real time and to ensure the time-averaged RF exposure is in compliance with the FCC requirement at all times for 2G/3G/4G/5G WWAN operations. Additionally, this device supports WLAN/BT/NFC/MST technologies, but the output power of these modems is not controlled by the Smart Transmit algorithm.

1.2 Time-Averaging for SAR and Power Density

This device is enabled with Qualcomm® Smart Transmit algorithm to control and manage transmitting power in real time and to ensure that the time-averaged RF exposure from 2G/3G/4G/5G Sub-6 NR WWAN is in compliance with FCC requirements. This Part 0 report shows SAR characterization of WWAN radios for 2G/3G/4G/5G Sub-6 NR. Characterization is achieved by determining P_{Limit} for 2G/3G/4G/5G Sub-6 NR that corresponds to the exposure design targets after accounting for all device design related uncertainties, i.e., SAR_design_target (< FCC SAR limit) for sub-6 radio. The SAR characterization is denoted as SAR Char in this report. Section 1.3 includes a nomenclature of the specific terms used in this report.

The compliance test under the static transmission scenario and simultaneous transmission analysis are reported in Part 1 report. The validation of the time-averaging algorithm and compliance under the dynamic (time- varying) transmission scenario for WWAN technologies are reported in Part 2 report (report SN could be found in Section 1.4 – Bibliography).

1.3 Nomenclature for Part 0 Report

Technology	Term	Description
2G/3G/4G/5G Sub-6 NR	P_{limit}	Power level that corresponds to the exposure design target (<i>SAR_design_target</i>) after accounting for all device design related uncertainties
	P_{max}	Maximum tune up output power
	<i>SAR_design_target</i>	Target SAR level < FCC SAR limit after accounting for all device design related uncertainties
	<i>SAR Char</i>	Table containing P_{limit} for all technologies and bands

1.4 Bibliography

Report Type	Report Serial Number
FCC SAR Evaluation Report (Part 1)	1M2106280073-04.A3L

FCC ID: A3LSMF926U	 PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset
		Page 4 of 12

2 SAR AND POWER DENSITY MEASUREMENTS

2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 2-1).

Equation 2-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ	=	conductivity of the tissue-simulating material (S/m)
ρ	=	mass density of the tissue-simulating material (kg/m ³)
E	=	Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

2.2 SAR Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 2-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.




Figure 2-1
Sample SAR Area Scan

FCC ID: A3LSMF926U	 PCTEST® Proud to be part of 	PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset	Page 5 of 12

3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 2-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 2-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

Table 2-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	$\leq 1.5^* \Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	$\leq 1.5^* \Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	$\leq 1.5^* \Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	$\leq 1.5^* \Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	$\leq 1.5^* \Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: A3LSMF926U	 PCTEST® Proud to be part of  element	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset		Page 6 of 12

3 SAR CHARACTERIZATION

3.1 DSI and SAR Determination

This device uses different Device State Index (DSI) to configure different time averaged power levels based on certain exposure scenarios. Depending on the detection scheme implemented in the smartphone, the worst-case SAR was determined by measurements for the relevant exposure conditions for that DSI. Detailed descriptions of the detection mechanisms are included in the operational description.

When 1g SAR and 10g SAR exposure comparison is needed, the worst-case was determined from SAR normalized to 1g or 10g SAR limit.

The device state index (DSI) conditions used in Table 3-1 represent different exposure scenarios.

Table 3-1
DSI and Corresponding Exposure Scenarios

Scenario	Description	SAR Test Cases
Head – Folder Open (DSI = 3)	- Device positioned next to head - Receiver Active - Folder Open	Head SAR per KDB Publication 648474 D04
Head – Folder Closed (DSI = 4)	- Device positioned next to head - Receiver Active - Folder Closed	Head SAR per KDB Publication 648474 D04
Hotspot mode – Folder Open (DSI = 5)	- Device transmits in hotspot mode near body - Hotspot Mode Active - Folder Open	UMPC Mini-Tablet SAR per KDB 941225 D07v01r02
Hotspot mode – Folder Closed (DSI = 6)	- Device transmits in hotspot mode near body - Hotspot Mode Active - Folder Closed	Hotspot SAR per KDB Publication 941225 D06
Extremity Grip – Folder Open (DSI=1 or 7)	- Device is held with hand and grip sensor is triggered - Grip sensor triggered or earjack is active - Folder Open	Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04
Phablet Grip – Folder Closed (DSI=2 or 8)	- Device is held with hand and grip sensor is triggered - Grip sensor triggered or earjack is active - Folder Closed	Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04
Extremity – Folder Open (DSI = 0)	- Device is held with hand and grip sensor is not triggered - Distance grip sensor not triggered - Folder Open	UMPC Mini-Tablet SAR per KDB 941225 D07v01r02
Phablet – Folder Closed (DSI = 11)	- Device is held with hand and grip sensor is not triggered - Distance grip sensor not triggered - Folder Closed	Phablet SAR per KDB Publication 648474 D04 & KDB Publication 616217 D04
Body-worn – Folder Open (DSI = 0)	- Device being used with a body-worn accessory - Folder Open	UMPC Mini-Tablet SAR per KDB 941225 D07v01r02
Body-worn – Folder Closed (DSI = 11)	- Device being used with a body-worn accessory - Folder Closed	Body-worn SAR per KDB Publication 648474 D04

FCC ID: A3LSMF926U	 PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset

3.2 SAR Design Target

SAR_design_target is determined by ensuring that it is less than FCC SAR limit after accounting for total device designed related uncertainties specified by the manufacturer (see Table 3-2).

Table 3-2
***SAR_design_target* Calculations**

<i>SAR_design_target</i>			
$SAR_design_target < SAR_regulatory_limit \times 10^{\frac{-Total\ Uncertainty}{10}}$			
1g SAR (W/kg)		10g SAR (W/kg)	
<i>Total Uncertainty</i>	1.0 dB	<i>Total Uncertainty</i>	1.0 dB
<i>SAR_regulatory_limit</i>	1.6 W/kg	<i>SAR_regulatory_limit</i>	4.0 W/kg
<i>SAR_design_target</i>	1.0 W/kg	<i>SAR_design_target</i>	2.5 W/kg

3.3 SAR Char

SAR test results corresponding to *Pmax* for each antenna/technology/band/DSI can be found in Appendix A.

Plimit is calculated by linearly scaling with the measured SAR at the Ppart0 to correspond to the *SAR_design_target*. When *Plimit* < *Pmax*, *Ppart0* was used as *Plimit* in the Smart Transmit EFS. When *Plimit* > *Pmax* and *Ppart0*=*Pmax*, calculated *Plimit* was used in the Smart Transmit EFS. All reported SAR obtained from the Ppart0 SAR tests was less than *SAR_Design_target*+ 1 dB Uncertainty. The final *Plimit* determination for each exposure scenario corresponding to *SAR_design_target* are shown in Table 3-3.

FCC ID: A3LSMF926U	 PCTEST® Proud to be part of 	PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset	Page 8 of 12

Table 3-3
***P*Limit Determination**

Device State Index (DSI)	<i>P</i> Limit Determination Scenarios
0 or 11	The worst-case SAR exposure is determined as maximum SAR normalized to the limit among: - UMPC 1g SAR folder open - Measured at 12 and 16 mm fro back and bottom surfaces respectively. - Measured at 10 mm for front, left and right surfaces. - Body Worn SAR folder closed. - UMPC 10g SAR folder open. - Measured at 12, 9 and 16 mm for back, front, and bottom surfaces respectively. - Measured at 0 mm for left and right surfaces - Extremity SAR folder closed. - Measured at 10 and 12 mm spacing for back and bottom respectively - Measured at 0 mm for front, left and right surfaces
1 or 7	<i>P</i> _{limit} is calculated based on 1g Body SAR at 10 mm for back and bottom surfaces and 10g Extremity SAR at 0 mm for back, front, and bottom surfaces with folder open
2 or 8	<i>P</i> _{limit} is calculated based on 10g Extremity SAR at 0 mm for back, front, and bottom surfaces with folder closed
3 or 4	<i>P</i> _{limit} is calculated based on 1g Head SAR
5 or 6	<i>P</i> _{limit} is calculated based on 1g Hotspot SAR at 10 mm

Note:

For DSI = 0, *P*_{limit} is calculated by:

$$P_{limit} = \min\{ \begin{array}{l} P_{limit} \text{ corresponding to 1g Body Worn SAR evaluation at 15 mm spacing,} \\ P_{limit} \text{ corresponding to 1g Body SAR evaluation at 10 mm spacing for front, right and left surfaces} \\ P_{limit} \text{ corresponding to 1g Body SAR evaluation at 12~16 mm spacing,} \\ P_{limit} \text{ corresponding to 10g Extremity SAR evaluation at 9~16 mm spacing,} \\ P_{limit} \text{ corresponding to 10g Extremity SAR evaluation at 0 mm for left and right surfaces} \end{array} \}$$

FCC ID: A3LSMF926U	 PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset
		Page 9 of 12

Table 3-4
SAR Characterizations

Exposure Scenario:	Body-Worn	Phablet	Body	Extremity	Grip Sensor Active		Head		Hotspot		Earjack	Earjack	Maximum Tune-up Output Power*
Averaging Volume:	1g	10g	1g	10g	10g	1g, 10g	1g	1g	1g	1g	10g	10g	
Spacing:	15 mm	10, 12 mm	12, 16, 10 mm	12, 9, 16 mm	0 mm	10, 0 mm	0 mm	0 mm	10 mm	10 mm	0 mm	0 mm	
DSI:	11	11	0	0	2	1	4	3	6	5	8	7	
Configuration	Folder Closed		Folder Open		Folder Closed	Folder Open	Folder Closed	Folder Open	Folder Closed	Folder Open	Folder Closed	Folder Open	Pmax
Technology/Band	Antenna												
CDMA/EVDO BC10	A, A+B	26.7		28.4	26.7	27.9	33.1	33.1	29.6	29.6	26.7	27.9	25.0
CDMA/EVDO BC0	A, A+B	26.7		26.7	26.7	26.9	32.1	32.1	26.9	26.9	26.7	26.9	25.0
UMTS B5	A, A+B	28.3		28.0	28.0	27.7	32.0	32.0	28.3	28.5	28.0	27.7	24.8
LTE FDD B71	A, A+B	27.8		28.8	28.2	27.8	34.4	34.4	28.2	27.8	28.2	27.8	24.8
LTE FDD B12	A, A+B	27.4		27.4	27.4	27.4	32.6	32.6	27.6	28.0	27.4	27.4	24.8
LTE FDD B17	A, A+B	27.4		27.4	27.4	27.4	32.6	32.6	27.6	28.0	27.4	27.4	24.8
LTE FDD B13	A, A+B	27.8		27.9	27.8	27.4	33.3	33.3	27.9	28.2	27.8	27.4	24.8
LTE FDD B14	A, A+B	27.9		28.4	27.9	27.2	33.3	33.3	27.9	28.1	27.9	27.2	24.8
LTE FDD B26	A, A+B	26.9		28.6	26.9	27.9	33.5	33.5	27.0	28.3	26.9	27.9	24.8
LTE FDD B5	A, A+B	26.5		27.4	26.5	27.3	32.7	32.7	26.6	28.0	26.5	27.3	24.8
NR FDD n71	A, A+B	27.9		28.2	27.6	27.4	34.9	34.9	27.4	27.4	27.6	27.4	24.5
NR FDD n12	A, A+B	27.4		26.7	27.4	26.7	33.7	33.7	27.5	27.2	27.4	26.7	24.5
NR FDD n5	A, A+B	26.8		29.1	26.8	27.8	33.5	33.5	27.0	27.8	26.8	27.8	24.5

Notes:

- For all modes/bands, when Hotspot Mode (DSI=5,6) and Extremity sensor (DSI=1, 2) are triggered at the same time, DSI=1, 2 takes priority, thus the P_{limit} for DSI=1, 2 is set to be less or equal to P_{limit} for DSI=5, 6.
- When $P_{max} < P_{limit}$, the DUT will operate at a power level up to P_{max} .
- P_{limit} for DSI=1 and DSI =7 are the same.
- P_{limit} for DSI=2 and DSI =8 are the same.
- The modes/bands affected by the permissive changes were evaluated for part 0. Please refer to RF Exposure Technical Report S/N 1M2104020031-30.A3L (Rev 1) for original compliance evaluation.

FCC ID: A3LSMF926U	 PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset
Page 10 of 12		

4

EQUIPMENT LIST

For SAR measurements

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85033E	3.5mm Standard Calibration Kit	7/7/2021	Annual	7/7/2022	MY53402352
Agilent	8753ES	S-Parameter Vector Network Analyzer	9/16/2020	Annual	9/16/2021	MY40000670
Agilent	E4438C	ESG Vector Signal Generator	12/2/2020	Annual	12/2/2021	MY42081752
Agilent	E4440A	PSA Series Spectrum Analyzer	1/29/2021	Annual	1/29/2022	MY46186272
Agilent	E5515C	Wireless Communications Test Set	5/4/2021	Biennial	5/4/2023	GB41450275
Agilent	N4010A	Wireless Connectivity Test Set	N/A	N/A	N/A	GB44450273
Agilent	N5182A	MXG Vector Signal Generator	6/21/2021	Annual	6/21/2022	MY47420603
Agilent	N9020A	MXA Signal Analyzer	12/21/2020	Annual	12/21/2021	MY50200571
Amplifier Research	150A100C	Amplifier	CBT	N/A	CBT	350132
Anritsu	MA24106A	USB Power Sensor	9/15/2020	Annual	9/15/2021	1244515
Anritsu	MA24106A	USB Power Sensor	3/2/2021	Annual	3/2/2022	1244524
Anritsu	MT8820C	Radio Communication Analyzer	9/30/2020	Annual	9/30/2021	6201240328
Anritsu	MT8821C	Radio Communication Analyzer	4/16/2021	Annual	4/16/2022	6200901190
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4040	Therm./ Clock/ Humidity Monitor	2/23/2021	Annual	2/23/2022	160574418
Control Company	4352	Ultra Long Stem Thermometer	3/2/2021	Annual	3/2/2022	160508097
Control Company	4352	Long Stem Thermometer	1/24/2020	Biennial	1/24/2022	200043588
HEWLETT PACKARD	8753E	Network Analyzer	12/10/2020	Annual	12/10/2021	US38161081
Keysight	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Keysight	E7515B	UXM 5G WIRELESS TEST PLATFORM	11/14/2020	Annual	11/14/2021	MY60192562
Keysight	E7770A	CIU Common Interface Unit w/ Kit	10/23/2020	Annual	10/23/2021	MY60250248
Keysight Technologies	85033E	Standard Mechanical Calibration Kit (DC to 9GHz, 3.5mm)	9/1/2020	Annual	9/1/2021	MY53401181
Keysight Technologies	N9020A	MXA Signal Analyzer	2/24/2021	Annual	2/24/2022	MY48010233
Keysight Technologies	N9020A	MXA Signal Analyzer	8/14/2020	Annual	8/14/2021	US46470561
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Pasternack	NC-100	Torque Wrench	8/4/2020	Biennial	8/4/2022	1445
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Radio Communication Tester	11/4/2020	Annual	11/4/2021	100976
Rohde & Schwarz	CMW500	Radio Communication Tester	10/16/2020	Annual	10/16/2021	101699
Seekonk	NC-100	Torque Wrench	8/5/2020	Biennial	8/5/2022	N/A
Seekonk Inc	NC-100	Torque Wrench	8/4/2020	Biennial	8/4/2022	N/A
SPEAG	D750V3	750 MHz SAR Dipole	3/16/2020	Biennial	3/16/2022	1003
SPEAG	D750V3	750 MHz SAR Dipole	3/9/2021	Annual	3/9/2022	1054
SPEAG	D750V3	750 MHz SAR Dipole	10/19/2018	Triennial	10/19/2021	1161
SPEAG	D835V2	835 MHz SAR Dipole	1/21/2021	Annual	1/21/2022	4d132
SPEAG	D835V2	835 MHz SAR Dipole	10/19/2018	Triennial	10/19/2021	4d133
SPEAG	DAE4	Dasy Data Acquisition Electronics	6/15/2021	Annual	6/15/2022	1334
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/7/2021	Annual	4/7/2022	1407
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/11/2020	Annual	8/11/2021	1450
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/7/2020	Annual	12/7/2021	1533
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/13/2021	Annual	1/13/2022	1558
SPEAG	DAK-3.5	Dielectric Assessment Kit	5/12/2021	Annual	5/12/2022	1070
SPEAG	EX3DV4	SAR Probe	1/20/2021	Annual	1/20/2022	3589
SPEAG	EX3DV4	SAR Probe	7/31/2020	Annual	7/31/2021	7308
SPEAG	EX3DV4	SAR Probe	4/19/2021	Annual	4/19/2022	7357
SPEAG	EX3DV4	SAR Probe	6/21/2021	Annual	6/21/2022	7409
SPEAG	EX3DV4	SAR Probe	12/11/2020	Annual	12/11/2021	7571
SPEAG	MAIA	Modulation and Audio Interference Analyzer	N/A	N/A	N/A	1237

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item was used solely within its respective calibration period.

FCC ID: A3LSMF926U	 PCTEST Proud to be part of 	PART 0 SAR CHAR REPORT 	Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset	Page 11 of 12

© 2021 PCTEST

REV 1.0

06/01/2019

© 2021 PCTEST. All rights reserved. Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from PCTEST. If you have any questions about this international copyright or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact INFO@PCTEST.COM.

5 MEASUREMENT UNCERTAINTIES

For SAR Measurements

a	c	d	e = f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System								
Probe Calibration	6.55	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	2.0	R	1.73	1.0	1.0	1.2	1.2	∞
Linearity	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	0.25	R	1.73	1.0	1.0	0.1	0.1	∞
Readout Electronics	0.3	N	1	1.0	1.0	0.3	0.3	∞
Response Time	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions - Noise	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
RF Ambient Conditions - Reflections	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	6.7	R	1.73	1.0	1.0	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Test Sample Related								
Test Sample Positioning	2.7	N	1	1.0	1.0	2.7	2.7	35
Device Holder Uncertainty	1.67	N	1	1.0	1.0	1.7	1.7	5
Output Power Variation - SAR drift measurement	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
SAR Scaling	0.0	R	1.73	1.0	1.0	0.0	0.0	∞
Phantom & Tissue Parameters								
Phantom Uncertainty (Shape & Thickness tolerances)	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	4.2	N	1	0.78	0.71	3.3	3.0	10
Liquid Permittivity - measurement uncertainty	4.1	N	1	0.23	0.26	1.0	1.1	10
Liquid Conductivity - Temperature Uncertainty	3.4	R	1.73	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	0.6	R	1.73	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)	RSS					11.5	11.3	60
Expanded Uncertainty (95% CONFIDENCE LEVEL)	k=2					23.0	22.6	

FCC ID: A3LSMF926U	 PCTEST® Proud to be part of 	PART 0 SAR CHAR REPORT		Approved by: Quality Manager
Document S/N: 1M2106280073-05.A3L	Test Dates: 06/08/21 - 07/23/21	DUT Type: Portable Handset		Page 12 of 12