



Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 65
Distance of Measurements: 3 Meters
Operating Frequency: 5510MHz
Channel: 102




Plot 7-286. Radiated Lower Band Edge Plot MIMO (Average - UNII Band 2C - 484 Tones)



Plot 7-287. Radiated Lower Band Edge Plot MIMO (Peak - UNII Band 2C - 484 Tones)


Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 65
Distance of Measurements: 3 Meters
Operating Frequency: 5795MHz
Channel: 159




Plot 7-288. Radiated Upper Band Edge Plot MIMO (Peak - UNII Band 3 - 484 Tones)

FCC ID: A3LSMF926U	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 194 of 205

Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 65
Distance of Measurements: 3 Meters
Operating Frequency: 5190MHz
Channel: 38



Plot 7-289. Radiated Lower Band Edge Plot MIMO with WCP (Average – UNII Band 1 – 484 Tones)




Plot 7-290. Radiated Lower Band Edge Plot MIMO with WCP (Peak – UNII Band 1 – 484 Tones)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 195 of 205


6.6.3 MIMO Radiated Band Edge Measurements (80MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5210MHz
Channel:	42




Plot 7-291. Radiated Lower Band Edge Plot MIMO (Average – UNII Band 1 – 996 Tones)




Plot 7-292. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5290MHz
Channel:	58




Plot 7-293. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 996 Tones)




Plot 7-294. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 996 Tones)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 196 of 205

Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 67
Distance of Measurements: 3 Meters
Operating Frequency: 5530MHz
Channel: 106




Plot 7-295. Radiated Lower Band Edge Plot MIMO (Average - UNII Band 2C - 996 Tones)



Plot 7-296. Radiated Lower Band Edge Plot MIMO (Peak - UNII Band 2C - 996 Tones)


Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 67
Distance of Measurements: 3 Meters
Operating Frequency: 5775MHz
Channel: 155




Plot 7-297. Radiated Upper Band Edge Plot MIMO (Peak - UNII Band 3 - 996 Tones)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 197 of 205

Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 67
Distance of Measurements: 3 Meters
Operating Frequency: 5530MHz
Channel: 106



Plot 7-298. Radiated Lower Band Edge Plot MIMO with WCP (Average – UNII Band 2C – 996 Tones)




Plot 7-299. Radiated Lower Band Edge Plot MIMO with WCP (Peak – UNII Band 2C – 996 Tones)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 198 of 205


6.6.4 MIMO Radiated Band Edge Measurements (160MHz BW) §15.407(b.1)(b.2) §15.205 §15.209; RSS-Gen [8.9]

996 Tones

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5250MHz
Channel:	50




Plot 7-300. Radiated Lower Band Edge Plot MIMO(Average – UNII Band 1 – 996 Tones)




Plot 7-301. Radiated Lower Band Edge Plot MIMO (Peak – UNII Band 1 – 996 Tones)

Worst Case Mode:	802.11ax
Worst Case Transfer Rate:	MCS0
RU Index:	67
Distance of Measurements:	3 Meters
Operating Frequency:	5250MHz
Channel:	50




Plot 7-302. Radiated Upper Band Edge Plot MIMO (Average – UNII Band 2A – 996 Tones)




Plot 7-303. Radiated Upper Band Edge Plot MIMO (Peak – UNII Band 2A – 996 Tones)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 199 of 205

Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 65
Distance of Measurements: 3 Meters
Operating Frequency: 5570MHz
Channel: 114




Plot 7-304. Radiated Lower Band Edge Plot MIMO (Average - UNII Band 2C - 996 Tones)




Plot 7-305. Radiated Lower Band Edge Plot MIMO (Peak - UNII Band 2C - 996 Tones)

Worst Case Mode: 802.11ax
Worst Case Transfer Rate: MCS0
RU Index: 65
Distance of Measurements: 3 Meters
Operating Frequency: 5570MHz
Channel: 114



Plot 7-306. Radiated Lower Band Edge Plot MIMO with WCP (Average - UNII Band 2C - 996 Tones)



Plot 7-307. Radiated Lower Band Edge Plot MIMO with WCP (Peak - UNII Band 2C - 996 Tones)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 200 of 205

7.7 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-70 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-70. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: A3LSMF926U	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 201 of 205

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: A3LSMF926U	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 202 of 205


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-70.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.


FCC ID: A3LSMF926U	 PCTEST Proud to be part of 	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 203 of 205

MIMO Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-308. Radiated Spurious Plot below 1GHz MIMO (802.11ax – 26 Tones – U3 Ch. 157)



Plot 7-309. Radiated Spurious Plot below 1GHz MIMO (802.11ax – 242 Tones – U3 Ch. 157)

FCC ID: A3LSMF926U	PCTEST Proud to be part of element	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 204 of 205

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Samsung Portable Handset FCC ID: A3LSMF926U** is in compliance with Part 15 Subpart E (15.407) of the FCC Rules and with RSS-247 of the Innovation, Science, and Economic Development Canada rules.

FCC ID: A3LSMF926U	 PCTEST Proud to be part of  element	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2104020031-15.A3L	Test Dates: 03/26 - 06/08/21	EUT Type: Portable Handset		Page 205 of 205