

APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS

E.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D04v01 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter

E.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D04v01 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg (or 4 W/kg for 10g). The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR. Alternatively, simultaneous transmission SAR test exclusion may be evaluated using Total Exposure Ratio (TER). The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the TER.

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR (“-”).

This device is enabled with Qualcomm® Smart Transmit Gen2 with pre-defined antenna groups (AG0 and AG1). Sub6 antennas cannot be decoupled from each other due to lack of regulatory criteria. The Simultaneous transmission analysis is performed per antenna groups. Below analysis demonstrates the mutually exclusive operation of AG0 and AG1, and the compliance between each antenna group with non-Smart Transmit Radios. For this model, WWAN/WLAN/BT Radios are managed under Smart Transmit. Non-Smart Transmit Radios include NFC/UWB.

When operating in the same antenna group, the compliance under dynamic transmission condition, including all supported simultaneous transmission scenarios, should be assessed and demonstrated in the Part 2 Report during algorithm validation. Therefore, no further simultaneous analysis is needed within an antenna group.

When all WWAN/WLAN/BT Radios are managed under Smart Transmit, TER for WWAN/WLAN/BT is covered in Part 2 testing. Only external radios outside of WWAN/WLAN/BT (UWB, NFC) require TER analysis with WWAN/WLAN/BT during simultaneous transmissions.

E.3 Sub6 Antenna Groups

The 2nd generation of Smart Transmit (GEN2) operates based on pre-defined antenna groups (AG). Sub6/WLAN/BT Tx antennas in the device are grouped based on spatial variation of RF exposure distributions, where the RF exposure of one AG is mutually exclusive from other AG. This is accomplished by demonstrating either of below conditions for all exposure scenarios:

- a) Sum of SAR of one antenna from each of the sub6 AGs and the RF exposure from radios outside Smart Transmit is less than regulatory limits. This condition must be demonstrated for all antenna combinations of sub6 AGs.

(or)

- b) Every antenna from each sub6 AG meets SPLSR criteria (Section 4.3.2(c) in FCC KDB 447498 D04) with every antenna from another sub6 AG. These criteria must be demonstrated for all antenna combinations for each pair of AGs.

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 1 of 21

This device supports two AGs: AG0 and AG1, with AG0 having 4 antennas (A, B, C, D) and AG1 having 4 antennas (E, F, G, H).

The conditions are verified through the following criteria:

- i) Sum of SAR: Demonstrate that the sum of *max.norm.exp.AG0* and *max.norm.exp.AG1* and the reported normalized SAR values from radios outside Smart Transmit (denoted as *reported.norm.exp.ER*) should be less than the regulatory limit for each supported DSI following the below procedure:
 1. Obtain the worst-case *Adjusted Ratio to Limit* for each antenna group, i.e., maximum *reported* SAR at EFS $P_{limit} + unc$ (or max of $\{P_{max} + unc, EFS P_{limit}\}$ when $EFS P_{limit} > P_{max}$) out of all supported technologies, frequency bands and antennas in AG0 and AG1, then normalized to the regulatory limit to get the maximum normalized SAR for each antenna group, denoted as *max.norm.exp.AG0* and *max.norm.exp.AG1*
 2. For external radios outside of Smart Transmit (NFC/UWB): Obtain the worst-case RF exposure for each external radio normalized to regulatory limit to get the normalized SAR for each external radio, denoted as *reported.norm.exp.NFC* and *reported.norm.exp.UWB*
 3. Demonstrate that the sum of these RF exposures meets: $\{max.norm.exp.AG0 + max.norm.exp.AG1 + normalized\ NFC\ SAR + normalized\ UWB\ SAR\} \leq 1$.
- ii) SPLSR or composite exposure distribution criteria: when TER sum of an antenna pair is over the limit for a DSI/exposure position, SPLSR or composite exposure distribution can be done to demonstrate simultaneous transmission compliance.
 1. SPLSR analysis for sub6 antenna pairs: For each antenna, obtain the highest *Adjusted Ratio to Limit* at EFS $P_{limit} + unc$ (or max of $\{P_{max} + unc, EFS P_{limit}\}$ when $EFS P_{limit} > P_{max}$) out of all supported technologies for each frequency band. Using these values, demonstrate for a given DSI that every antenna from one AG meets SPLSR criteria with every antenna in another AG for all frequency bands. This criterion must be demonstrated for all antenna pair combinations irrespective of supported simultaneous transmission scenarios as given below for each DSI. As it can be seen, these include all combinations of antenna groups, antennas, and frequency bands.
 - If SPLSR criteria evaluation and analysis is needed to determine compliance for a certain DSI configuration, SPLSR is performed by taking the highest reported SAR for each of the supported technologies and bands per antenna, along with the peak SAR locations. Per Qualcomm guidance, only Y-axis coordinates are recorded in the analysis for calculation simplicity (assumes all 0mm of separation on the x-axis). Peak locations are documented in the Highest Report SAR and Hotspot Location Section below for each DSI configuration. For bottom AG0, Y_max coordinates represents the worst-case hotspot location that is closest to the top AG1. Similarly, for top AG1, Y_min coordinate represents the worst-case hotspot location that is closest to the bottom AG0
 - The following formula is used to calculate the SPLSR between AG0 and AG1 for each exposure configuration:

$$SPLSR = \frac{(Max\ SAR\ AG0 + Max\ SAR\ AG1)^{1.5}}{|Y_{max} - Y_{min}|}$$

E.4 Exposure Ratios

Exposure ratio (ER) for different transmitters is calculated as following:

$$ER_{SAR,n} = \frac{SAR_n}{SAR_{limit}}$$

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 2 of 21

$$ER_{PD,n} = \frac{PD_n}{PD_{limit}}$$

Where:

- SAR_n is the SAR value for the n -th transmitter/test frequency
- SAR_{limit} is the basic restriction limit that is applicable to the n -th transmitter/test frequency
- P_{txm} is the higher of maximum time-averaged conducted power or EIRP associated with the m -th UWB transmitters

Compliance with the SAR-UWB based RF exposure limits is achieved if $TER_{SAR-UWB} \leq 1$. When $TER_{SAR-UWB} > 1$, SPLSR is additionally evaluated per below equation:

$$SPLSR = \frac{(ER_j + ER_k)^{1.5}}{R}$$

Where:

- ER_j and ER_k are exposure ratio of transmitter j and k
- R is the distance between transmitter j and k

When SPLSR is ≤ 0.02 for 1g exposure conditions or SPLSR is ≤ 0.013 for 10g exposure conditions simultaneous SAR evaluation is not required.

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 3 of 21

E.5 Head (DSI = 3) SAR Antenna Group Analysis

Table E-1
DSI=3 Held-to-ear AG0 Highest Adjusted Ratio to Limit

AG0 Ratio to Limit							
Head	Configuration	A	A+C	B	C	D	Max
	Right Cheek	0.258	0.368	0.356	0.000	0.012	0.368
	Right Tilt	0.181	0.214	0.215	0.000	0.000	0.215
	Left Cheek	0.227	0.247	0.350	0.000	0.000	0.350
	Left Tilt	0.136	0.164	0.165	0.000	0.000	0.165

Table E-2
DSI=3 Held-to-ear AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit							
Head	Configuration	E	F	G	H	MIMO	Max
	Right Cheek	0.545	0.518	0.543	0.614	0.520	0.614
	Right Tilt	0.613	0.610	0.779	0.203	0.621	0.779
	Left Cheek	0.624	0.608	0.647	0.618	0.551	0.647
	Left Tilt	0.619	0.619	0.831	0.395	0.616	0.831

Table E-3
DSI=3 Held-to-ear AG Verifications

Head	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	NFC + UWB Ratio to Limit	AG0 + AG1 Ratio to Limit
	Right Cheek	0.368	0.614	0.000	0.982
	Right Tilt	0.215	0.779	0.000	0.994
	Left Cheek	0.350	0.647	0.000	0.997
	Left Tilt	0.165	0.831	0.000	0.996

Notes:

1. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 5 of 21

E.6 Body-worn (DSI = 1) SAR Antenna Group Analysis

Table E-4
DSI=1 Body-worn AG0 Highest Adjusted Ratio to Limit

AG0 Ratio to Limit							
Bodyworn	Configuration	A	A+C	B	C	D	Max
	Back	0.536	0.624	0.821	0.460	0.026	0.821
	Front	0.194	0.214	0.417	0.042	0.000	0.417

Table E-5
DSI=1 Body-worn AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit							
Bodyworn	Configuration	E	F	G	H	MIMO	Max
	Back	0.740	0.801	0.822	0.619	0.823	0.823
	Front	0.169	0.174	0.230	0.079	0.217	0.230

Table E-6
DSI=1 Body-worn AG Verification

Bodyworn	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.821	0.823	See Table Below
	Front	0.417	0.230	0.647

Back							
AG0			AG1			AG0 + AG1 Ratio to Limit	SPLSR
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position		
Ant A	0.536	-82.800	Ant E	0.740	58.200	See Note 2	0.01
Ant A	0.536	-82.800	Ant F	0.801	69.700	See Note 2	0.01
Ant A	0.536	-82.800	Ant G	0.822	73.300	See Note 2	0.01
Ant A	0.536	-82.800	Ant H	0.619	20.500	See Note 2	0.01
Ant A	0.536	-82.800	MIMO	0.823	0.000	See Note 2	0.02
Ant A+C	0.624	-79.200	Ant E	0.740	58.200	See Note 2	0.01
Ant A+C	0.624	-79.200	Ant F	0.801	69.700	See Note 2	0.01
Ant A+C	0.624	-79.200	Ant G	0.822	73.300	See Note 2	0.01
Ant A+C	0.624	-79.200	Ant H	0.619	20.500	See Note 2	0.01
Ant A+C	0.624	-79.200	MIMO	0.823	0.000	See Note 2	0.02
Ant B	0.821	-90.600	Ant E	0.740	58.200	See Note 2	0.01
Ant B	0.821	-90.600	Ant F	0.801	69.700	See Note 2	0.01
Ant B	0.821	-90.600	Ant G	0.822	73.300	See Note 2	0.01
Ant B	0.821	-90.600	Ant H	0.619	20.500	See Note 2	0.02
Ant B	0.821	-90.600	MIMO	0.823	0.000	See Note 2	0.02
Ant C	0.460	-84.100	Ant E	0.740	58.200	See Note 2	0.01
Ant C	0.460	-84.100	Ant F	0.801	69.700	See Note 2	0.01
Ant C	0.460	-84.100	Ant G	0.822	73.300	See Note 2	0.01
Ant C	0.460	-84.100	Ant H	0.619	20.500	See Note 2	0.01
Ant C	0.460	-84.100	MIMO	0.823	0.000	See Note 2	0.02
Ant D	0.026	N/A	Ant E	0.740	N/A	0.766	N/A
Ant D	0.026	N/A	Ant F	0.801	N/A	0.827	N/A
Ant D	0.026	N/A	Ant G	0.822	N/A	0.848	N/A
Ant D	0.026	N/A	Ant H	0.619	N/A	0.645	N/A
Ant D	0.026	N/A	MIMO	0.823	N/A	0.849	N/A

Notes:

1. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.
2. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D04v01. Please see the Highest Report ER and Hotspot Location Section for Y-axis peak locations

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 7 of 21

E.7 Hotspot (DSI = 1) SAR Antenna Group Analysis

Table E-7
DSI=1 Hotspot AG0 Adjusted Ratio to Limit

AG0 Ratio to Limit							
Hotspot	Configuration	A	A+C	B	C	D	Max
	Back	0.536	0.624	0.821	0.460	0.026	0.821
	Front	0.194	0.214	0.417	0.042	0.000	0.417
	Top	-	-	-	-	-	-
	Bottom	0.116	0.169	0.518	0.095	-	0.518
	Right	0.253	0.416	-	0.012	0.000	0.416
	Left	-	0.123	0.073	0.010	-	0.123

Table E-8
DSI=1 Hotspot AG1 Adjusted Ratio to Limit

AG1 Ratio to Limit							
Hotspot	Configuration	E	F	G	H	MIMO	Max
	Back	0.625	0.801	0.822	0.619	0.666	0.822
	Front	0.169	0.090	0.230	0.079	0.168	0.230
	Top	0.249	0.229	0.417	-	0.389	0.417
	Bottom	-	-	-	-	-	-
	Right	0.328	-	0.059	0.166	0.189	0.328
	Left	-	0.035	-	-	0.051	0.051

Table E-9
DSI=1 Hotspot AG Verification

Hotspot	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.821	0.822	See Table Below
	Front	0.417	0.230	0.647
	Top	-	0.417	0.417
	Bottom	0.518	-	0.518
	Right	0.416	0.328	0.744
	Left	0.123	0.051	0.174

Back							SPLSR
AG0			AG1			AG0 + AG1 Ratio to Limit	
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position		
Ant A	0.536	-82.800	Ant E	0.625	58.200	See Note 2	0.01
Ant A	0.536	-82.800	Ant F	0.801	69.700	See Note 2	0.01
Ant A	0.536	-82.800	Ant G	0.822	73.300	See Note 2	0.01
Ant A	0.536	-82.800	Ant H	0.619	20.500	See Note 2	0.01
Ant A	0.536	-82.800	MIMO	0.666	0.000	See Note 2	0.02
Ant A+C	0.624	-79.200	Ant E	0.625	58.200	See Note 2	0.01
Ant A+C	0.624	-79.200	Ant F	0.801	69.700	See Note 2	0.01
Ant A+C	0.624	-79.200	Ant G	0.822	73.300	See Note 2	0.01
Ant A+C	0.624	-79.200	Ant H	0.619	20.500	See Note 2	0.01
Ant A+C	0.624	-79.200	MIMO	0.666	0.000	See Note 2	0.02
Ant B	0.821	-90.600	Ant E	0.625	58.200	See Note 2	0.01
Ant B	0.821	-90.600	Ant F	0.801	69.700	See Note 2	0.01
Ant B	0.821	-90.600	Ant G	0.822	73.300	See Note 2	0.01
Ant B	0.821	-90.600	Ant H	0.619	20.500	See Note 2	0.02
Ant B	0.821	-90.600	MIMO	0.666	0.000	See Note 2	0.02
Ant C	0.460	-84.100	Ant E	0.625	58.200	See Note 2	0.01
Ant C	0.460	-84.100	Ant F	0.801	69.700	See Note 2	0.01
Ant C	0.460	-84.100	Ant G	0.822	73.300	See Note 2	0.01
Ant C	0.460	-84.100	Ant H	0.619	20.500	See Note 2	0.01
Ant C	0.460	-84.100	MIMO	0.666	0.000	See Note 2	0.01
Ant D	0.026	-39.300	Ant E	0.625	58.200	0.651	N/A
Ant D	0.026	-39.300	Ant F	0.801	69.700	0.827	N/A
Ant D	0.026	-39.300	Ant G	0.822	73.300	0.848	N/A
Ant D	0.026	-39.300	Ant H	0.619	20.500	0.645	N/A
Ant D	0.026	-39.300	MIMO	0.666	0.000	0.692	N/A

Notes:

1. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.
2. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D04v01. Please see the Highest Report ER and Hotspot Location Section for Y-axis peak locations

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 9 of 21

E.8 Max Phablet (DSI = 1) and Reduced Phablet (DSI=5) SAR Antenna Group Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.

Table E-10
DSI=1 and DSI=5 Max and Reduced Phablet AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit					
Phablet	Configuration	E	F	MIMO	Max
	Back	0.358	0.376	0.429	0.429
	Front	0.091	0.109	0.142	0.142
	Top	0.403	0.495	0.377	0.495
	Bottom	-	-	-	-
	Right	0.151	-	0.267	0.267
	Left	-	0.032	0.015	0.032

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 10 of 21

Table E-11
Simultaneous Transmission Scenarios of NFC/UWB (Phablet)

	Configuration	NFC Ratio to Limit	UWB Ratio to Limit
Phablet SAR	Back	0.000	0.000
	Front	0.000	0.000
	Top	0.000	0.000
	Bottom	-	-
	Right	-	0.000
	Left	0.000	-

Table E-12
DSI=1 and DSI=5 Max and Reduced Phablet AG Verification

	Configuration	AG1 Ratio to Limit	NFC + UWB Ratio to Limit	AG0 + AG1 + NFC + UWB Ratio to Limit
Phablet	Back	0.429	0.000	0.429
	Front	0.142	0.000	0.142
	Top	0.495	0.000	0.495
	Bottom	-	-	-
	Right	0.267	0.000	0.267
	Left	0.032	0.000	0.032

Notes:

- For all combinations where the TER sum of AG1+UWB+NFC is not greater than 1, there's no further analysis required for compliance demonstration.

E.9 Max Tablet (DSI=0) SAR Antenna Group Analysis

Table E-13
DSI=0 Max Tablet AG0 Highest Adjusted Ratio to Limit

AG0 Ratio to Limit							
Body	Configuration	A	A+C	B	C	D	Max
	Back	0.553	0.740	0.824	0.623	0.166	0.824
	Front	-	-	-	-	-	-
	Top	0.001	0.041	0.007	0.000	0.000	0.041
	Bottom	0.068	0.546	0.767	0.464	0.006	0.767
	Right	0.053	0.739	0.042	0.150	0.042	0.739
	Left	0.000	0.030	0.015	0.006	0.010	0.030

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 11 of 21

Table E-14
DSI=0 Max Tablet AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit							
Body	Configuration	E	F	G	H	MIMO	Max
	Back	0.761	0.696	0.855	0.807	0.835	0.855
	Front	-	-	-	-	-	-
	Top	0.833	0.817	0.505	0.042	0.795	0.833
	Bottom	0.062	0.003	0.029	0.007	0.015	0.062
	Right	0.727	0.017	0.865	0.581	0.669	0.865
	Left	0.028	0.009	0.144	0.001	0.015	0.144

Table E-15
Simultaneous Transmission Scenarios of NFC/UWB (Tablet)

	Right	NFC Ratio to Limit	UWB Ratio to Limit
Body SAR	Back	0.001	0.001
	Front	-	-
	Top	0.000	0.003
	Bottom	0.000	0.001
	Right	0.000	0.001
	Left	0.000	0.001

Table E-16
DSI=0 Max Tablet AG Verification

Body	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	NFC + UWB Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.824	0.855	0.002	See Table Below
	Front	-	-	-	-
	Top	0.041	0.835	0.003	0.876
	Bottom	0.767	0.062	0.001	0.829
	Right	0.739	0.865	0.001	See Table Below
	Left	0.030	0.144	0.001	0.174

Back											
Bottom Set			Top Set							AG0 + AG1+ NFC + UWB Ratio to Limit	SPLSR
AG0			AG1			NFC		UWB			
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	Position	Ratio to Limit	Position		
Ant A	0.553	-74.600	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	Ant G	0.855	83.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A	0.553	-74.600	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.740	-79.600	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.740	-79.600	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.740	-79.600	Ant G	0.855	83.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.740	-79.600	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.740	-79.600	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant G	0.855	83.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant C	0.623	-81.900	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	Ant G	0.855	83.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant C	0.623	-81.900	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant D	0.166	N/A	Ant E	0.761	N/A	0.001	37.800	0.001	N/A	0.929	N/A
Ant D	0.166	N/A	Ant F	0.696	N/A	0.001	37.800	0.001	N/A	0.864	N/A
Ant D	0.166	-38.900	Ant G	0.855	83.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant D	0.166	N/A	Ant H	0.807	N/A	0.001	37.800	0.001	N/A	0.975	N/A
Ant D	0.166	-38.900	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.01

Right											
Bottom Set			Top Set							AG0 + AG1 Ratio to Limit	SPLSR
AG0			AG1			NFC		UWB			
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	Position	Ratio to Limit	Position		
Ant A	0.053	N/A	Ant E	0.727	N/A	0.000	N/A	0.001	N/A	0.781	N/A
Ant A	0.053	N/A	Ant F	0.017	N/A	0.000	N/A	0.001	N/A	0.071	N/A
Ant A	0.053	N/A	Ant G	0.865	N/A	0.000	N/A	0.001	N/A	0.919	N/A
Ant A	0.053	N/A	Ant H	0.595	N/A	0.000	N/A	0.001	N/A	0.649	N/A
Ant A	0.053	N/A	MIMO	0.669	N/A	0.000	N/A	0.001	N/A	0.723	N/A
Ant A+C	0.739	35.000	Ant E	0.727	-43.800	0.000	-79.000	0.001	-54.000	See Note 2	0.02
Ant A+C	0.739	N/A	Ant F	0.017	N/A	0.000	N/A	0.001	N/A	0.757	N/A
Ant A+C	0.739	35.000	Ant G	0.865	-48.100	0.000	-79.000	0.001	-54.000	See Note 2	0.02
Ant A+C	0.739	35.000	Ant H	0.595	-32.700	0.000	-79.000	0.001	-54.000	See Note 2	0.02
Ant A+C	0.739	35.000	MIMO	0.669	-31.600	0.000	-79.000	0.001	-54.000	See Note 2	0.02
Ant B	0.042	N/A	Ant E	0.727	N/A	0.000	N/A	0.001	N/A	0.770	N/A
Ant B	0.042	N/A	Ant F	0.017	N/A	0.000	N/A	0.001	N/A	0.060	N/A
Ant B	0.042	N/A	Ant G	0.865	N/A	0.000	N/A	0.001	N/A	0.908	N/A
Ant B	0.042	N/A	Ant H	0.595	N/A	0.000	N/A	0.001	N/A	0.638	N/A
Ant B	0.042	N/A	MIMO	0.669	N/A	0.000	N/A	0.001	N/A	0.712	N/A
Ant C	0.150	N/A	Ant E	0.727	N/A	0.000	N/A	0.001	N/A	0.878	N/A
Ant C	0.150	N/A	Ant F	0.017	N/A	0.000	N/A	0.001	N/A	0.168	N/A
Ant C	0.150	47.100	Ant G	0.865	-48.100	0.000	-79.000	0.001	-54.000	See Note 2	0.01
Ant C	0.150	N/A	Ant H	0.595	N/A	0.000	N/A	0.001	N/A	0.746	N/A
Ant C	0.150	N/A	MIMO	0.669	N/A	0.000	N/A	0.001	N/A	0.820	N/A
Ant D	0.042	N/A	Ant E	0.727	N/A	0.000	N/A	0.001	N/A	0.770	N/A
Ant D	0.042	N/A	Ant F	0.017	N/A	0.000	N/A	0.001	N/A	0.060	N/A
Ant D	0.042	N/A	Ant G	0.865	N/A	0.000	N/A	0.001	N/A	0.908	N/A
Ant D	0.042	N/A	Ant H	0.595	N/A	0.000	N/A	0.001	N/A	0.638	N/A
Ant D	0.042	N/A	MIMO	0.669	N/A	0.000	N/A	0.001	N/A	0.712	N/A

Notes:

- For all combinations where the TER sum of AG0+AG1+UWB+NFC is not greater than 1, there's no further analysis required for compliance demonstration.
- No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D04v01. Please see the Highest Report SAR and Hotspot Location Section for Y-axis peak locations.

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 13 of 21

E.10 Reduced Tablet (DSI=4) SAR Antenna Group Analysis

Please refer to the above section, E.9 Max Tablet (DSI=0) SAR Antenna Group Analysis for DSI=4 evaluation for bottom, left, and right tablet edges as there is no change in these edges between DSI=0 and DSI=4.

Table E-17
DSI=4 Reduced Tablet AG0 Highest Adjusted Ratio to Limit

AG0 Ratio to Limit							
Body	Configuration	A	A+C	B	C	D	Max
	Back	0.553	0.740	0.824	0.623	0.166	0.824
	Top	0.001	0.041	0.007	0.000	0.000	0.041

Table E-18
DSI=4 Reduced Tablet AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit							
Body	Configuration	E	F	G	H	MIMO	Max
	Back	0.761	0.696	0.685	0.807	0.835	0.835
	Top	0.833	0.817	0.777	0.042	0.795	0.833

Table E-19
DSI=4 Reduced Tablet AG Verification

Body	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	NFC + UWB Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.824	0.835	0.002	See Table Below
	Top	0.041	0.833	0.003	0.877

Back											
Bottom Set			Top Set								SPLSR
AG0			AG1			NFC		UWB		AG0 + AG1 + NFC + UWB Ratio to Limit	
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	Position	Ratio to Limit	Position		
Ant A	0.553	-74.600	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	Ant G	0.685	83.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A	0.553	-74.600	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.623	-79.600	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A+C	0.623	-79.600	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A+C	0.623	-79.600	Ant G	0.685	83.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant A+C	0.623	-79.600	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant A+C	0.623	-79.600	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant G	0.685	83.200	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant B	0.824	-86.200	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant C	0.623	-81.900	Ant E	0.761	102.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	Ant F	0.696	58.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	Ant G	0.685	83.200	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	Ant H	0.807	80.000	0.001	37.800	0.001	113.500	See Note 2	0.01
Ant C	0.623	-81.900	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.02
Ant D	0.166	N/A	Ant E	0.761	N/A	0.001	37.800	0.001	N/A	0.929	N/A
Ant D	0.166	N/A	Ant F	0.696	N/A	0.001	37.800	0.001	N/A	0.864	N/A
Ant D	0.166	-38.900	Ant G	0.685	83.200	0.001	37.800	0.001	113.500	0.851	N/A
Ant D	0.166	N/A	Ant H	0.807	N/A	0.001	37.800	0.001	N/A	0.975	N/A
Ant D	0.166	-38.900	MIMO	0.835	80.000	0.001	37.800	0.001	113.500	See Note 2	0.01

Please see Table E-13 for AG0 Tablet worst case results and Table E-15 for NFC/UWB Tablet worst case results

Notes:

- For all combinations where the TER sum of AG0+AG1+UWB+NFC is not greater than 1, there's no further analysis required for compliance demonstration.
- No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D04v01. Please see the Highest Report SAR and Hotspot Location Section for Y-axis peak locations.

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 15 of 21

E.11 Highest Report SAR and SAR Hotspot Locations

As a conservative assessment, the distances between Bottom Set and Top Set were determined using the y-axis coordinates of the peak locations only (assumes 0 mm separation on x/z axis)

Table E-20
DSI=0 Body-worn Back Peak Y Coordinates

Body-worn Back											
Back											
Bottom Set											
Top Set											
AG1											
Mode/Band	Distance	A	A+C	B	C	D	E	F	G	H	MIMO
		5 mm	5 mm	5 mm	5 mm	5 mm	5 mm	5 mm	5 mm	5 mm	5 mm
GSM 850 Ant A	ER	0.252									
	Y-Axis	-80.200									
GSM 850 Ant A+C	ER		0.611								
	Y-Axis		-77.400								
GSM 850 Ant E	ER						0.619				
	Y-Axis						76.000				
GSM 1900 Ant B	ER			0.771							
	Y-Axis			-86.400							
UMTS 850 Ant A	ER	0.427									
	Y-Axis	-77.700									
UMTS 850 Ant A+C	ER		0.616								
	Y-Axis		-71.500								
UMTS 850 Ant E	ER						0.621				
	Y-Axis						80.400				
UMTS 1750 Ant G	ER								0.822		
	Y-Axis								74.900		
UMTS 1900 Ant B	ER			0.812							
	Y-Axis			-85.300							
LTE Band 12 Ant A	ER	0.383									
	Y-Axis	-73.800									
LTE Band 12 Ant A+C	ER		0.624								
	Y-Axis		-73.400								
LTE Band 12 Ant E	ER						0.624				
	Y-Axis						72.900				
LTE Band 13 Ant A	ER	0.536									
	Y-Axis	-77.900									
LTE Band 13 Ant A+C	ER		0.528								
	Y-Axis		-76.800								
LTE Band 13 Ant E	ER						0.615				
	Y-Axis						72.300				
LTE Band 26 Ant A	ER	0.477									
	Y-Axis	-82.800									
LTE Band 26 Ant A+C	ER		0.619								
	Y-Axis		-79.200								
LTE Band 26 Ant E	ER						0.618				
	Y-Axis						58.200				
LTE Band 66 Ant B	ER			0.815							
	Y-Axis			-90.600							
LTE Band 66 Ant G	ER								0.630		
	Y-Axis								73.300		
LTE Band 25 Ant B	ER		0.821								
	Y-Axis		-89.700								
LTE Band 25 Ant G	ER								0.721		
	Y-Axis								81.500		
LTE Band 41 Ant B	ER		0.322								
	Y-Axis		-84.900								
LTE Band 41 Ant G	ER								0.692		
	Y-Axis								78.600		
NR Band n71 Ant A	ER	0.409									
	Y-Axis	-71.400									
NR Band n71 Ant A+C	ER		0.615								
	Y-Axis		-77.100								
NR Band n71 Ant E	ER						0.625				
	Y-Axis						69.400				
NR Band n5 Ant A	ER	0.419									
	Y-Axis	-80.100									
NR Band n5 Ant A+C	ER		0.620								
	Y-Axis		-79.100								
NR Band n5 Ant E	ER						0.624				
	Y-Axis						78.600				
NR Band n66 Ant B	ER			0.559							
	Y-Axis			-79.000							
NR Band n66 Ant G	ER								0.443		
	Y-Axis								81.500		
NR Band n25 Ant B	ER		0.773								
	Y-Axis		-								
NR Band n25 Ant G	ER								0.531		
	Y-Axis								81.300		
NR Band n41 Ant B	ER		0.444								
	Y-Axis		-83.000								
NR Band n41 Ant G	ER								0.662		
	Y-Axis								86.700		
NR Band n41 Ant H	ER									0.024	
	Y-Axis									23.200	
NR Band n41 Ant D	ER					0.026					
	Y-Axis					-39.300					
NR Band n77 Ant A	ER	0.264									
	Y-Axis	-70.300									
NR Band n77 Ant C	ER			0.460							
	Y-Axis			-84.100							
NR Band n77 Ant F	ER						0.801				
	Y-Axis						70.300				
NR Band n77 Ant G	ER							0.212			
	Y-Axis							77.500			
2.4 GHz WiFi Ant H	ER								0.570		
	Y-Axis								20.500		
2.4 GHz WiFi Ant F	ER						0.265				
	Y-Axis						72.600				
2.4 GHz WiFi Ant MIMO	ER									0.595	
	Y-Axis									24.100	
5 GHz WiFi Ant F	ER							0.328			
	Y-Axis							71.100			
5 GHz WiFi Ant E	ER					0.740					
	Y-Axis					72.000					
5 GHz WiFi Ant MIMO	ER									0.823	
	Y-Axis									72.700	
6 GHz WiFi Ant F	ER							0.334			
	Y-Axis							69.700			
6 GHz WiFi Ant E	ER						0.344				
	Y-Axis						71.000				
6 GHz WiFi Ant MIMO	ER									0.549	
	Y-Axis									68.500	
2.4 GHz Bluetooth Ant H	ER								0.619		
	Y-Axis								23.800		
2.4 GHz Bluetooth Ant F	ER						0.611				
	Y-Axis						73.500				
2.4 GHz Bluetooth Ant MIMO	ER									0.609	
	Y-Axis									22.300	

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 16 of 21

Table E-21
DSI=0 Hotspot Back Side Peak Y Coordinates

Hotspot Back											
Back											
Bottom Set						Top Set					
AG0						AG1					
Mode/Band	Distance	A 5 mm	A+C 5 mm	B 5 mm	C 5 mm	D 5 mm	E 5 mm	F 5 mm	G 5 mm	H 5 mm	MIMO 5 mm
GSM 850 Ant A	ER	0.252									
	Y-Axis	-80.200									
GSM 850 Ant A+C	ER		0.611								
	Y-Axis		-77.400								
GSM 850 Ant E	ER						0.619				
	Y-Axis						76.000				
GSM 1900 Ant B	ER			0.771							
	Y-Axis			-86.400							
UMTS 850 Ant A	ER	0.427									
	Y-Axis	-77.700									
UMTS 850 Ant A+C	ER		0.616								
	Y-Axis		-71.500								
UMTS 850 Ant E	ER						0.621				
	Y-Axis						80.400				
UMTS 1750 Ant G	ER								0.822		
	Y-Axis								74.900		
UMTS 1900 Ant B	ER			0.812							
	Y-Axis			-85.300							
LTE Band 12 Ant A	ER	0.383									
	Y-Axis	-73.800									
LTE Band 12 Ant A+C	ER		0.624								
	Y-Axis		-73.400								
LTE Band 12 Ant E	ER						0.624				
	Y-Axis						72.900				
LTE Band 13 Ant A	ER	0.536									
	Y-Axis	-77.900									
LTE Band 13 Ant A+C	ER		0.528								
	Y-Axis		-76.800								
LTE Band 13 Ant E	ER						0.615				
	Y-Axis						72.300				
LTE Band 26 Ant A	ER	0.477									
	Y-Axis	-82.800									
LTE Band 26 Ant A+C	ER		0.619								
	Y-Axis		-79.200								
LTE Band 26 Ant E	ER						0.618				
	Y-Axis						58.200				
LTE Band 66 Ant B	ER			0.815							
	Y-Axis			-90.600							
LTE Band 66 Ant G	ER								0.630		
	Y-Axis								73.300		
LTE Band 25 Ant B	ER			0.821							
	Y-Axis			-89.700							
LTE Band 25 Ant G	ER								0.721		
	Y-Axis								81.500		
LTE Band 41 Ant B	ER			0.322							
	Y-Axis			-84.900							
LTE Band 41 Ant G	ER								0.692		
	Y-Axis								78.600		
NR Band n71 Ant A	ER	0.409									
	Y-Axis	-71.400									
NR Band n71 Ant A+C	ER		0.615								
	Y-Axis		-77.100								
NR Band n71 Ant E	ER						0.625				
	Y-Axis						69.400				
NR Band n5 Ant A	ER	0.419									
	Y-Axis	-80.100									
NR Band n5 Ant A+C	ER		0.620								
	Y-Axis		-79.100								
NR Band n5 Ant E	ER						0.624				
	Y-Axis						78.600				
NR Band n66 Ant B	ER			0.559							
	Y-Axis			-79.000							
NR Band n66 Ant G	ER								0.443		
	Y-Axis								81.500		
NR Band n25 Ant B	ER			0.773							
	Y-Axis			-							
NR Band n25 Ant G	ER								0.531		
	Y-Axis								81.300		
NR Band n41 Ant B	ER			0.444							
	Y-Axis			-83.000							
NR Band n41 Ant G	ER								0.662		
	Y-Axis								86.700		
NR Band n41 Ant H	ER									0.024	
	Y-Axis									23.200	
NR Band n41 Ant D	ER					0.026					
	Y-Axis					-39.300					
NR Band n77 Ant A	ER	0.264									
	Y-Axis	-70.300									
NR Band n77 Ant C	ER			0.460							
	Y-Axis			-84.100							
NR Band n77 Ant F	ER							0.801			
	Y-Axis							70.300			
NR Band n77 Ant G	ER								0.212		
	Y-Axis								77.500		
2.4 GHz WIFI Ant H	ER									0.570	
	Y-Axis									20.500	
2.4 GHz WIFI Ant F	ER						0.265				
	Y-Axis						72.600				
2.4 GHz WIFI Ant MIMO	ER										0.595
	Y-Axis										24.100
5 GHz WIFI Ant F	ER							0.328			
	Y-Axis							71.100			
5 GHz WIFI Ant E	ER						0.740				
	Y-Axis						72.000				
5 GHz WIFI Ant MIMO	ER									0.823	
	Y-Axis									72.700	
2.4 GHz Bluetooth Ant H	ER									0.619	
	Y-Axis									23.800	

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 17 of 21

Table E-22
DSI=0 Max Tablet Back Side Peak Y Coordinates

Body Back											
Back											
Bottom Set						Top Set					
AG0						AG1					
Mode/Band	Distance	A	A+C	B	C	D	E	F	G	H	MIMO
		0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	9 mm	0 mm	0 mm
GSM 850 Ant A	ER										
	Y-Axis										
GSM 850 Ant A+C	ER		0.493								
	Y-Axis		-77.200								
GSM 850 Ant E	ER						0.196				
	Y-Axis						76.000				
GSM 1900 Ant B	ER			0.622							
	Y-Axis			-82.000							
UMTS 850 Ant A	ER										
	Y-Axis										
UMTS 850 Ant A+C	ER		0.740								
	Y-Axis		-79.600								
UMTS 850 Ant E	ER						0.593				
	Y-Axis						80.400				
UMTS 1750 Ant G	ER								0.231		
	Y-Axis								74.900		
UMTS 1900 Ant B	ER			0.793							
	Y-Axis			-86.200							
LTE Band 12 Ant A	ER										
	Y-Axis										
LTE Band 12 Ant A+C	ER		0.699								
	Y-Axis		-77.800								
LTE Band 12 Ant E	ER						0.661				
	Y-Axis						72.900				
LTE Band 13 Ant A	ER										
	Y-Axis										
LTE Band 13 Ant A+C	ER		0.662								
	Y-Axis		-73.900								
LTE Band 13 Ant E	ER						0.558				
	Y-Axis						72.300				
LTE Band 26 Ant A	ER										
	Y-Axis										
LTE Band 26 Ant A+C	ER		0.419								
	Y-Axis		-77.400								
LTE Band 26 Ant E	ER						0.645				
	Y-Axis						58.200				
LTE Band 66 Ant B	ER			0.717							
	Y-Axis			-85.000							
LTE Band 66 Ant G	ER								0.855		
	Y-Axis								73.300		
LTE Band 25 Ant B	ER			0.755							
	Y-Axis			-85.600							
LTE Band 25 Ant G	ER								0.838		
	Y-Axis								81.500		
LTE Band 41 Ant B	ER			0.472							
	Y-Axis			-83.900							
LTE Band 41 Ant G	ER								0.609		
	Y-Axis								78.600		
NR Band n71 Ant A	ER										
	Y-Axis										
NR Band n71 Ant A+C	ER		0.659								
	Y-Axis		-78.000								
NR Band n71 Ant E	ER						0.672				
	Y-Axis						69.400				
NR Band n5 Ant A	ER										
	Y-Axis										
NR Band n5 Ant A+C	ER		0.508								
	Y-Axis		-								
NR Band n5 Ant E	ER						0.548				
	Y-Axis						78.600				
NR Band n66 Ant B	ER			0.257							
	Y-Axis			-81.700							
NR Band n66 Ant G	ER								0.147		
	Y-Axis								81.500		
NR Band n25 Ant B	ER			0.824							
	Y-Axis			-82.000							
NR Band n25 Ant G	ER								0.653		
	Y-Axis								81.300		
NR Band n41 Ant B	ER			0.584							
	Y-Axis			-81.600							
NR Band n41 Ant G	ER								0.284		
	Y-Axis								86.700		
NR Band n41 Ant H	ER									0.157	
	Y-Axis									23.200	
NR Band n41 Ant D	ER					0.166					
	Y-Axis					-38.900					
NR Band n77 Ant A	ER	0.553									
	Y-Axis	-74.600									
NR Band n77 Ant C	ER			0.623							
	Y-Axis			-81.900							
NR Band n77 Ant F	ER						0.696				
	Y-Axis						70.300				
NR Band n77 Ant G	ER							0.235			
	Y-Axis							77.500			
2.4 GHz WiFi Ant H	ER									0.807	
	Y-Axis									20.500	
2.4 GHz WiFi Ant F	ER						0.334				
	Y-Axis						72.600				
2.4 GHz WiFi Ant MIMO	ER									0.824	
	Y-Axis									24.100	
5 GHz WiFi Ant F	ER						0.317				
	Y-Axis						71.100				
5 GHz WiFi Ant E	ER					0.761					
	Y-Axis					72.000					
5 GHz WiFi Ant MIMO	ER									0.719	
	Y-Axis									72.700	
6 GHz WiFi Ant F	ER						0.498				
	Y-Axis						69.700				
6 GHz WiFi Ant E	ER					0.558					
	Y-Axis					71.000					
6 GHz WiFi Ant MIMO	ER									0.547	
	Y-Axis									68.500	
2.4 GHz Bluetooth Ant H	ER									0.782	
	Y-Axis									23.800	
2.4 GHz Bluetooth Ant F	ER						0.262				
	Y-Axis						73.500				
2.4 GHz Bluetooth Ant MIMO	ER									0.844	
	Y-Axis									22.300	
	Configuration	NFC Ratio to Limit		NFC y-coord		UWB Ratio to Limit		UWB y-coord			
Body	Back	0.001		37.800		0.001		113.500			

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT				Approved by: Technical Manager
DUT Type: Portable Handset					APPENDIX E: Page 18 of 21

Table E-23
DSI=0 Max Tablet Right Edge Peak Y Coordinates

Body Right											
		Bottom Set					Top Set				
		AG0					AG1				
Mode/Band	Distance	A	A+C	B	C	D	E	F	G	H	MIMO
		0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm
GSM 850 Ant A	ER										
	Y-Axis										
GSM 850 Ant A+C	ER		0.590								
	Y-Axis		-77.400								
GSM 850 Ant E	ER						0.295				
	Y-Axis						76.000				
GSM 1900 Ant B	ER			0.042							
	Y-Axis			-86.400							
UMTS 850 Ant A	ER										
	Y-Axis										
UMTS 850 Ant A+C	ER		0.735								
	Y-Axis		-71.500								
UMTS 850 Ant E	ER						0.476				
	Y-Axis						80.400				
UMTS 1750 Ant G	ER								0.153		
	Y-Axis								74.900		
UMTS 1900 Ant B	ER		0.021								
	Y-Axis		-85.300								
LTE Band 12 Ant A	ER										
	Y-Axis										
LTE Band 12 Ant A+C	ER		0.739								
	Y-Axis		-73.400								
LTE Band 12 Ant E	ER						0.611				
	Y-Axis						72.900				
LTE Band 13 Ant A	ER										
	Y-Axis										
LTE Band 13 Ant A+C	ER		0.734								
	Y-Axis		-76.800								
LTE Band 13 Ant E	ER						0.377				
	Y-Axis						72.300				
LTE Band 26 Ant A	ER										
	Y-Axis										
LTE Band 26 Ant A+C	ER		0.568								
	Y-Axis		-79.200								
LTE Band 26 Ant E	ER						0.398				
	Y-Axis						58.200				
LTE Band 66 Ant B	ER			0.014							
	Y-Axis			-90.600							
LTE Band 66 Ant G	ER								0.685		
	Y-Axis								73.300		
LTE Band 25 Ant B	ER		0.024								
	Y-Axis		-89.700								
LTE Band 25 Ant G	ER								0.796		
	Y-Axis								81.500		
LTE Band 41 Ant B	ER		0.021								
	Y-Axis		-84.900								
LTE Band 41 Ant G	ER								0.195		
	Y-Axis								78.600		
NR Band n71 Ant A	ER										
	Y-Axis										
NR Band n71 Ant A+C	ER		0.631								
	Y-Axis		-77.100								
NR Band n71 Ant E	ER						0.727				
	Y-Axis						69.400				
NR Band n5 Ant A	ER										
	Y-Axis										
NR Band n5 Ant A+C	ER		0.667								
	Y-Axis		-79.100								
NR Band n5 Ant E	ER						0.376				
	Y-Axis						78.600				
NR Band n66 Ant B	ER			0.001							
	Y-Axis			-79.000							
NR Band n66 Ant G	ER								0.146		
	Y-Axis								81.500		
NR Band n25 Ant B	ER		0.025								
	Y-Axis		-								
NR Band n25 Ant G	ER								0.865		
	Y-Axis								81.300		
NR Band n41 Ant B	ER		0.037								
	Y-Axis		-83.000								
NR Band n41 Ant G	ER								0.169		
	Y-Axis								86.700		
NR Band n41 Ant H	ER									0.128	
	Y-Axis									23.200	
NR Band n41 Ant D	ER					0.042					
	Y-Axis					-39.300					
NR Band n77 Ant A	ER	0.053									
	Y-Axis	-70.300									
NR Band n77 Ant C	ER			0.150							
	Y-Axis			-84.100							
NR Band n77 Ant F	ER							0.009			
	Y-Axis							70.300			
NR Band n77 Ant G	ER								0.057		
	Y-Axis								77.500		
2.4 GHz WiFi Ant H	ER									0.581	
	Y-Axis									20.500	
2.4 GHz WiFi Ant F	ER							0.009			
	Y-Axis							72.600			
2.4 GHz WiFi Ant MIMO	ER										0.669
	Y-Axis										24.100
5 GHz WiFi Ant F	ER							0.017			
	Y-Axis							71.100			
5 GHz WiFi Ant E	ER					0.209					
	Y-Axis					72.000					
5 GHz WiFi Ant MIMO	ER										0.098
	Y-Axis										72.700
6 GHz WiFi Ant F	ER						0.015				
	Y-Axis						69.700				
6 GHz WiFi Ant E	ER					0.272					
	Y-Axis					71.000					
6 GHz WiFi Ant MIMO	ER										0.073
	Y-Axis										68.500
2.4 GHz Bluetooth Ant H	ER								0.595		
	Y-Axis								23.800		
2.4 GHz Bluetooth Ant F	ER						0.007				
	Y-Axis						73.500				
2.4 GHz Bluetooth Ant MIMO	ER										0.548
	Y-Axis										22.300
	Configuration	NFC Ratio to Limit		NFC y-coord		UWB Ratio to Limit		UWB y-coord			
Body	Right	0.000		-79.000		0.001		-54.000			

Table E-24
DSI=4 Reduced Tablet Back Side Peak Y Coordinates

Body Back											
Back											
Bottom Set						Top Set					
AG0						AG1					
Mode/Band	Distance	A	A+C	B	C	D	E	F	G	H	MIMO
		0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm
GSM 850 Ant A	ER										
	Y-Axis										
GSM 850 Ant A+C	ER		0.493								
	Y-Axis		-77.200								
GSM 850 Ant E	ER						0.196				
	Y-Axis						76.000				
GSM 1900 Ant B	ER			0.622							
	Y-Axis			-82.000							
UMTS 850 Ant A	ER										
	Y-Axis										
UMTS 850 Ant A+C	ER		0.740								
	Y-Axis		-79.500								
UMTS 850 Ant E	ER						0.593				
	Y-Axis						80.400				
UMTS 1750 Ant G	ER								0.231		
	Y-Axis								74.900		
UMTS 1900 Ant B	ER			0.793							
	Y-Axis			-86.200							
LTE Band 12 Ant A	ER										
	Y-Axis										
LTE Band 12 Ant A+C	ER		0.699								
	Y-Axis		-77.800								
LTE Band 12 Ant E	ER						0.661				
	Y-Axis						72.900				
LTE Band 13 Ant A	ER										
	Y-Axis										
LTE Band 13 Ant A+C	ER		0.662								
	Y-Axis		-73.900								
LTE Band 13 Ant E	ER						0.558				
	Y-Axis						72.300				
LTE Band 26 Ant A	ER										
	Y-Axis										
LTE Band 26 Ant A+C	ER		0.419								
	Y-Axis		-77.400								
LTE Band 26 Ant E	ER						0.645				
	Y-Axis						58.200				
LTE Band 66 Ant B	ER			0.717							
	Y-Axis			-85.000							
LTE Band 66 Ant G	ER								0.855		
	Y-Axis								73.300		
LTE Band 25 Ant B	ER			0.755							
	Y-Axis			-85.600							
LTE Band 25 Ant G	ER								0.838		
	Y-Axis								81.500		
LTE Band 41 Ant B	ER			0.472							
	Y-Axis			-83.900							
LTE Band 41 Ant G	ER								0.609		
	Y-Axis								78.600		
NR Band n71 Ant A	ER										
	Y-Axis										
NR Band n71 Ant A+C	ER		0.659								
	Y-Axis		-78.000								
NR Band n71 Ant E	ER						0.672				
	Y-Axis						69.400				
NR Band n5 Ant A	ER										
	Y-Axis										
NR Band n5 Ant A+C	ER		0.508								
	Y-Axis		-								
NR Band n5 Ant E	ER						0.548				
	Y-Axis						78.600				
NR Band n66 Ant B	ER			0.257							
	Y-Axis			-81.700							
NR Band n66 Ant G	ER								0.147		
	Y-Axis								81.500		
NR Band n25 Ant B	ER			0.824							
	Y-Axis			-82.000							
NR Band n25 Ant G	ER								0.653		
	Y-Axis								81.300		
NR Band n41 Ant B	ER			0.584							
	Y-Axis			-81.600							
NR Band n41 Ant G	ER								0.284		
	Y-Axis								86.700		
NR Band n41 Ant H	ER									0.157	
	Y-Axis									23.200	
NR Band n41 Ant D	ER					0.166					
	Y-Axis					-38.900					
NR Band n77 Ant A	ER	0.553									
	Y-Axis	-74.600									
NR Band n77 Ant C	ER				0.623						
	Y-Axis				-81.900						
NR Band n77 Ant F	ER							0.696			
	Y-Axis							70.300			
NR Band n77 Ant G	ER								0.235		
	Y-Axis								77.500		
2.4 GHz WiFi Ant H	ER									0.807	
	Y-Axis									20.500	
2.4 GHz WiFi Ant F	ER							0.334			
	Y-Axis							72.600			
2.4 GHz WiFi Ant MIMO	ER										0.824
	Y-Axis										24.100
5 GHz WiFi Ant F	ER								0.317		
	Y-Axis								71.100		
5 GHz WiFi Ant E	ER						0.761				
	Y-Axis						72.000				
5 GHz WiFi Ant MIMO	ER										0.719
	Y-Axis										72.700
6 GHz WiFi Ant F	ER							0.498			
	Y-Axis							69.700			
6 GHz WiFi Ant E	ER						0.558				
	Y-Axis						71.000				
6 GHz WiFi Ant MIMO	ER										0.547
	Y-Axis										68.500
2.4 GHz Bluetooth Ant H	ER									0.782	
	Y-Axis									23.800	
2.4 GHz Bluetooth Ant F	ER						0.262				
	Y-Axis						73.500				
2.4 GHz Bluetooth Ant MIMO	ER										0.844
	Y-Axis										22.300
	Configuration	NFC		NFC	UWB		UWB				
		Ratio to		y-coord	Ratio to		y-coord				
		Limit			Limit						
Body	Back	0.001		37.800	0.001		113.500				

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 20 of 21

E.12 Conclusion

The above numerical summed TER results and SPLSR for all the combinations of antenna groups are sufficient to show that AG0 is mutually exclusive from AG1 and TER is <1. TER simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D04v01 and IEEE 1528- 2013 Section 6.3.4.1.

FCC ID A3LSMF966B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 21 of 21