

APPENDIX H: LTE AND NR LOWER BANDWIDTH RF CONDUCTED POWERS

All conducted power measurements for Sub6 WWAN technologies and bands in this section were performed by setting *Reserve_power_margin* (Qualcomm® Smart Transmit EFS entry) to 0 dB, so that the EUT transmits continuously at minimum (P_{limit} , maximum tune up output power P_{max}).

Note: Some bands do not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

H.1 LTE Lower Bandwidth RF Conducted Powers

H.1.1 LTE Band 71 Antenna A and Antenna A+C

Table H-1
LTE Band 71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel 133297 (680.5 MHz) Conducted Power [dBm]	MPR Allowed per 3GPP [dB]	MPR [dB]
QPSK	1	0	24.35	0	0
	1	36	24.25		0
	1	74	24.07		0
	36	0	23.42	0-1	1
	36	18	23.34		1
	36	37	23.21		1
	75	0	23.31		1
16QAM	1	0	23.74	0-1	1
	1	36	23.57		1
	1	74	23.29		1
	36	0	22.44	0-2	2
	36	18	22.38		2
	36	37	22.20		2
	75	0	22.33		2
64QAM	1	0	22.72	0-2	2
	1	36	22.56		2
	1	74	22.39		2
	36	0	21.37	0-3	3
	36	18	21.35		3
	36	37	21.19		3
	75	0	21.31		3
256QAM	1	0	19.50	0-5	5
	1	36	19.49		5
	1	74	19.21		5
	36	0	19.37		5
	36	18	19.34		5
	36	37	19.14		5
	75	0	19.27		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 1 of 426

Table H-2
LTE Band 71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.92	24.41	24.03	0	0	
	1	25	24.91	24.37	24.17		0	
	1	49	24.78	24.28	23.88		0	
	25	0	23.69	23.41	23.14	0-1	1	
	25	12	23.59	23.40	23.13		1	
	25	25	23.52	23.26	23.06		1	
16QAM	50	0	23.57	23.39	23.09	0-1	1	
	1	0	24.07	23.85	23.29		1	
	1	25	23.90	23.67	23.32		1	
	1	49	23.97	23.50	23.22	0-2	1	
	25	0	22.74	22.47	22.14		2	
	25	12	22.64	22.43	22.11		2	
64QAM	25	25	22.56	22.28	22.04	0-2	2	
	50	0	22.59	22.35	22.09		2	
	1	0	22.98	22.75	22.36	0-2	2	
	1	25	22.95	22.65	22.40		2	
	1	49	22.87	22.46	22.29		2	
	25	0	21.68	21.46	21.14	0-3	3	
25	12	21.59	21.43	21.13	3			
25	25	21.52	21.26	21.04	3			
256QAM	50	0	21.59	21.37	21.10	0-3	3	
	1	0	19.86	19.53	19.12		0-5	5
	1	25	19.75	19.44	19.27			5
	1	49	19.52	19.28	18.98	5		
	25	0	19.63	19.37	19.07	5		
	25	12	19.56	19.36	19.09	5		
25	25	19.52	19.22	19.01	5			
	50	0	19.51	19.33	19.06		5	

Table H-3
LTE Band 71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.79	24.33	24.16	0	0
	1	12	24.81	24.35	24.12		0
	1	24	24.74	24.24	24.00		0
	12	0	23.70	23.38	23.05	0-1	1
	12	6	23.72	23.37	23.09		1
	12	13	23.58	23.26	22.99		1
	25	0	23.60	23.35	23.04		1
16QAM	1	0	24.11	23.82	23.44	0-1	1
	1	12	24.09	23.82	23.46		1
	1	24	23.98	23.65	23.35		1
	12	0	22.76	22.41	22.07	0-2	2
	12	6	22.77	22.40	22.14		2
	12	13	22.66	22.24	22.04		2
	25	0	22.64	22.33	22.01		2
64QAM	1	0	23.05	22.53	22.23	0-2	2
	1	12	22.96	22.60	22.30		2
	1	24	22.88	22.49	22.06		2
	12	0	21.70	21.40	21.05	0-3	3
	12	6	21.75	21.43	21.08		3
	12	13	21.57	21.25	21.01		3
	25	0	21.60	21.33	21.01		3
256QAM	1	0	19.80	19.53	19.22	0-5	5
	1	12	19.86	19.53	19.19		5
	1	24	19.64	19.33	19.09		5
	12	0	19.67	19.35	19.00	0-5	5
	12	6	19.70	19.34	19.03		5
	12	13	19.47	19.20	18.93		5
	25	0	19.54	19.32	18.99		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 2 of 426

Table H-4
LTE Band 71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.61	0	0
	1	36	18.40		0
	1	74	18.21		0
	36	0	18.63	0-1	0
	36	18	18.54		0
	36	37	18.40		0
	75	0	18.50		0
16QAM	1	0	18.79	0-1	0
	1	36	18.64		0
	1	74	18.46		0
	36	0	18.64	0-2	0
	36	18	18.58		0
	36	37	18.43		0
	75	0	18.52		0
64QAM	1	0	18.84	0-2	0
	1	36	18.77		0
	1	74	18.58		0
	36	0	18.61	0-3	0
	36	18	18.56		0
	36	37	18.42		0
	75	0	18.55		0
256QAM	1	0	18.83	0-5	0
	1	36	18.64		0
	1	74	18.47		0
	36	0	18.63		0
	36	18	18.60		0
	36	37	18.40		0
	75	0	18.57		0

Table H-5
LTE Band 71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.94	18.70	18.44	0	0
	1	25	18.96	18.63	18.20		0
	1	49	18.77	18.40	18.08		0
	25	0	18.82	18.63	18.36	0-1	0
	25	12	18.71	18.62	18.36		0
	25	25	18.66	18.46	18.27		0
	50	0	18.67	18.58	18.34		0
16QAM	1	0	19.16	18.87	18.58	0-1	0
	1	25	19.11	18.69	18.48		0
	1	49	18.95	18.66	18.43		0
	25	0	18.86	18.64	18.39	0-2	0
	25	12	18.76	18.65	18.40		0
	25	25	18.67	18.48	18.28		0
	50	0	18.73	18.63	18.32		0
64QAM	1	0	19.05	18.94	18.59	0-2	0
	1	25	19.06	18.91	18.65		0
	1	49	18.86	18.81	18.46		0
	25	0	18.85	18.69	18.41	0-3	0
	25	12	18.77	18.66	18.40		0
	25	25	18.67	18.52	18.34		0
	50	0	18.70	18.63	18.35		0
256QAM	1	0	19.05	18.76	18.49	0-5	0
	1	25	18.96	18.75	18.49		0
	1	49	18.67	18.40	18.25		0
	25	0	18.82	18.62	18.35		0
	25	12	18.73	18.64	18.34		0
	25	25	18.67	18.48	18.29		0
	50	0	18.69	18.59	18.32		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 3 of 426

Table H-6
LTE Band 71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.87	18.58	18.37	0	0
	1	12	18.93	18.54	18.33		0
	1	24	18.80	18.38	18.22		0
	12	0	18.86	18.63	18.27	0-1	0
	12	6	18.84	18.62	18.31		0
	12	13	18.72	18.48	18.21		0
	25	0	18.73	18.56	18.24		0
16QAM	1	0	19.17	18.83	18.61	0-1	0
	1	12	19.15	18.84	18.66		0
	1	24	19.01	18.72	18.51		0
	12	0	18.91	18.63	18.32	0-2	0
	12	6	18.92	18.66	18.38		0
	12	13	18.78	18.51	18.26		0
	25	0	18.76	18.60	18.27		0
64QAM	1	0	19.11	18.78	18.42	0-2	0
	1	12	19.13	18.84	18.52		0
	1	24	19.02	18.63	18.41		0
	12	0	18.90	18.65	18.35	0-3	0
	12	6	18.90	18.71	18.33		0
	12	13	18.77	18.53	18.27		0
	25	0	18.79	18.62	18.33		0
256QAM	1	0	19.01	18.73	18.46	0-5	0
	1	12	19.08	18.87	18.49		0
	1	24	18.81	18.57	18.39		0
	12	0	18.82	18.61	18.31		0
	12	6	18.88	18.65	18.26		0
	12	13	18.71	18.46	18.23		0
	25	0	18.74	18.60	18.25		0

H.1.2 LTE Band 71 Antenna E

Table H-7
LTE Band 71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.23	0	0
	1	36	24.14		0
	1	74	23.99		0
	36	0	23.24	0-1	1
	36	18	23.15		1
	36	37	23.09		1
	75	0	23.14		1
16QAM	1	0	23.49	0-1	1
	1	36	23.48		1
	1	74	23.25		1
	36	0	22.28	0-2	2
	36	18	22.21		2
	36	37	22.11		2
	75	0	22.17		2
64QAM	1	0	22.51	0-2	2
	1	36	22.42		2
	1	74	22.21		2
	36	0	21.23	0-3	3
	36	18	21.17		3
	36	37	21.08		3
	75	0	21.15		3
256QAM	1	0	19.37	0-5	5
	1	36	19.23		5
	1	74	19.17		5
	36	0	19.18		5
	36	18	19.14		5
	36	37	19.03		5
	75	0	19.10		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 4 of 426

Table H-8
LTE Band 71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.49	24.47	24.13	0	0
	1	25	24.52	24.44	24.10		0
	1	49	24.51	24.16	24.03		0
	25	0	23.51	23.24	22.95	0-1	1
	25	12	23.51	23.22	22.94		1
	25	25	23.36	23.17	22.93		1
	50	0	23.38	23.19	22.90		1
16QAM	1	0	23.70	23.61	23.31	0-1	1
	1	25	23.71	23.48	23.30		1
	1	49	23.54	23.29	23.14		1
	25	0	22.54	22.25	21.98	0-2	2
	25	12	22.52	22.27	21.94		2
	25	25	22.35	22.16	21.95		2
	50	0	22.41	22.21	21.90		2
64QAM	1	0	22.79	22.63	22.13	0-2	2
	1	25	22.71	22.52	22.19		2
	1	49	22.57	22.29	22.07		2
	25	0	21.52	21.26	20.97	0-3	3
	25	12	21.53	21.21	20.94		3
	25	25	21.34	21.14	20.94		3
	50	0	21.40	21.18	20.91		3
256QAM	1	0	19.62	19.37	18.96	0-5	5
	1	25	19.60	19.30	19.17		5
	1	49	19.34	19.12	18.81		5
	25	0	19.50	19.21	18.90		5
	25	12	19.46	19.22	18.91		5
	25	25	19.35	19.13	18.93		5
	50	0	19.36	19.16	18.90		5

Table H-9
LTE Band 71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.90	24.26	23.95	0	0	
	1	12	24.89	24.36	24.00		0	
	1	24	24.73	24.23	23.86		0	
	12	0	23.64	23.23	22.94	0-1	1	
	12	6	23.54	23.26	22.96		1	
	12	13	23.47	23.17	22.87		1	
16QAM	25	0	23.47	23.19	22.92	0-1	1	
	1	0	23.96	23.58	23.27		1	
	1	12	23.98	23.63	23.41		1	
	1	24	23.97	23.53	23.25	0-2	1	
	12	0	22.66	22.23	21.96		2	
	12	6	22.56	22.28	22.02		2	
64QAM	12	13	22.53	22.19	21.95	0-2	2	
	25	0	22.48	22.21	21.93		2	
	1	0	22.88	22.35	22.11	0-2	2	
	1	12	22.84	22.49	22.13		2	
	1	24	22.71	22.33	22.00		2	
	12	0	21.58	21.22	20.94	0-3	3	
12	6	21.56	21.24	20.98	3			
12	13	21.44	21.17	20.91	3			
256QAM	25	0	21.46	21.20	20.90	0-3	3	
	1	0	19.65	19.29	18.99		0-5	5
	1	12	19.76	19.33	19.06			5
	1	24	19.54	19.16	18.97	5		
	12	0	19.55	19.20	18.94	0-5	5	
	12	6	19.49	19.22	18.94		5	
12	13	19.40	19.14	18.88	5			
	25	0	19.43	19.15	18.90		5	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 5 of 426

Table H-10
LTE Band 71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133297 (680.5 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.56	0	0
	1	36	18.54		0
	1	74	18.78		0
	36	0	18.73	0-1	0
	36	18	18.67		0
	36	37	18.57		0
	75	0	18.61		0
16QAM	1	0	19.01	0-1	0
	1	36	18.74		0
	1	74	18.69		0
	36	0	18.84	0-2	0
	36	18	18.82		0
	36	37	18.57		0
	75	0	18.67		0
64QAM	1	0	19.08	0-2	0
	1	36	18.84		0
	1	74	18.86		0
	36	0	18.83	0-3	0
	36	18	18.78		0
	36	37	18.60		0
	75	0	18.64		0
256QAM	1	0	18.98	0-5	0
	1	36	18.56		0
	1	74	18.58		0
	36	0	18.86		0
	36	18	18.70		0
	36	37	18.66		0
	75	0	18.70		0

Table H-11
LTE Band 71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 71 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133172 (668.0 MHz)	133297 (680.5 MHz)	133422 (693.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.05	18.79	18.55	0	0
	1	25	18.96	18.68	18.46		0
	1	49	18.76	18.76	18.44		0
	25	0	19.01	18.80	18.56	0-1	0
	25	12	18.99	18.81	18.52		0
	25	25	18.87	18.65	18.46		0
	50	0	19.01	18.74	18.59		0
16QAM	1	0	19.20	18.95	18.67	0-1	0
	1	25	19.12	18.87	18.71		0
	1	49	19.10	18.68	18.53		0
	25	0	19.02	18.81	18.63	0-2	0
	25	12	19.01	18.79	18.55		0
	25	25	18.82	18.70	18.45		0
	50	0	19.10	18.77	18.49		0
64QAM	1	0	19.19	18.93	18.66	0-2	0
	1	25	19.03	19.04	18.69		0
	1	49	18.88	18.85	18.64		0
	25	0	19.17	18.80	18.58	0-3	0
	25	12	19.06	18.81	18.63		0
	25	25	18.88	18.70	18.37		0
	50	0	19.00	18.70	18.53		0
256QAM	1	0	19.15	18.88	18.60	0-5	0
	1	25	19.20	18.95	18.80		0
	1	49	18.80	18.79	18.50		0
	25	0	19.08	18.75	18.56		0
	25	12	19.15	18.80	18.44		0
	25	25	18.79	18.71	18.53		0
	50	0	19.04	18.70	18.55		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 6 of 426

Table H-12
LTE Band 71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 71 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			133147 (665.5 MHz)	133297 (680.5 MHz)	133447 (695.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.96	18.65	18.38	0	0
	1	12	19.00	18.64	18.38		0
	1	24	18.80	18.69	18.25		0
	12	0	19.05	18.76	18.46	0-1	0
	12	6	18.94	18.72	18.39		0
	12	13	18.91	18.67	18.41		0
	25	0	18.91	18.66	18.42		0
16QAM	1	0	19.15	18.89	18.61	0-1	0
	1	12	19.29	18.93	18.65		0
	1	24	19.08	18.74	18.38		0
	12	0	19.11	18.80	18.42	0-2	0
	12	6	19.00	18.79	18.44		0
	12	13	19.00	18.60	18.35		0
	25	0	18.93	18.67	18.35		0
64QAM	1	0	19.19	18.76	18.56	0-2	0
	1	12	19.13	18.96	18.54		0
	1	24	18.92	18.74	18.38		0
	12	0	19.10	18.70	18.48	0-3	0
	12	6	19.02	18.80	18.51		0
	12	13	18.91	18.64	18.39		0
	25	0	18.93	18.73	18.38		0
256QAM	1	0	19.06	18.83	18.48	0-5	0
	1	12	19.14	18.77	18.46		0
	1	24	18.86	18.57	18.33		0
	12	0	19.02	18.69	18.44		0
	12	6	18.99	18.72	18.48		0
	12	13	18.82	18.73	18.41		0
	25	0	18.92	18.68	18.33		0

H.1.1.3 LTE Band 12 Antenna A and Antenna A+C

Table H-13
LTE Band 12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.04	23.72	23.89	0	0
	1	12	24.01	23.68	23.99		0
	1	24	23.86	23.63	23.97		0
	12	0	22.96	22.73	22.81	0-1	1
	12	6	22.88	22.73	22.86		1
	12	13	22.81	22.70	22.86		1
25	0	22.84	22.72	22.79	1		
16QAM	1	0	23.29	23.21	23.16	0-1	1
	1	12	23.29	23.15	23.34		1
	1	24	23.18	23.12	23.31		1
	12	0	21.99	21.80	21.84	0-2	2
	12	6	21.91	21.82	21.87		2
	12	13	21.80	21.72	21.90		2
25	0	21.86	21.73	21.83	2		
64QAM	1	0	22.20	22.01	21.93	0-2	2
	1	12	22.27	21.93	22.16		2
	1	24	22.07	21.92	22.11		2
	12	0	20.99	20.74	20.82	0-3	3
	12	6	20.88	20.78	20.85		3
	12	13	20.80	20.68	20.90		3
25	0	20.84	20.70	20.80	3		
256QAM	1	0	19.00	18.82	18.91	0-5	5
	1	12	19.09	18.89	19.12		5
	1	24	18.87	18.87	18.89		5
	12	0	18.92	18.70	18.74		5
	12	6	18.87	18.74	18.81		5
	12	13	18.74	18.66	18.82		5
25	0	18.79	18.64	18.75	5		

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 7 of 426

Table H-14
LTE Band 12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.96	23.70	23.76	0	0	
	1	7	24.18	23.82	23.89		0	
	1	14	23.97	23.65	23.79		0	
	8	0	22.97	22.72	22.87	0-1	1	
	8	4	22.93	22.74	22.98		1	
	8	7	22.86	22.69	22.88		1	
16QAM	15	0	22.92	22.70	22.83	0-1	1	
	1	0	23.35	23.06	23.02		1	
	1	7	23.54	23.06	23.26		1	
	1	14	23.21	22.92	23.13	0-2	1	
	8	0	22.04	21.82	21.91		2	
	8	4	21.97	21.83	22.02		2	
64QAM	8	7	21.94	21.78	22.02	0-2	2	
	15	0	21.97	21.75	21.87		2	
	1	0	22.18	21.97	22.00		2	
	1	7	22.33	21.98	22.28	0-2	2	
	1	14	22.08	21.89	22.07		2	
	8	0	21.06	20.75	20.86		0-3	3
8	4	20.96	20.78	20.97	3			
8	7	20.91	20.73	20.93	3			
256QAM	15	0	20.90	20.74	20.86	0-3	3	
	1	0	18.98	18.77	18.84		0-5	5
	1	7	19.15	18.84	19.08			5
	1	14	18.84	18.75	18.87	5		
	8	0	18.97	18.70	18.81	5		
	8	4	18.94	18.69	18.96	5		
256QAM	8	7	18.86	18.67	18.89	0-5	5	
	15	0	18.85	18.64	18.80		5	

Table H-15
LTE Band 12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.90	23.71	23.89	0	0
	1	2	23.93	23.81	23.84		0
	1	5	23.90	23.69	23.88		0
	3	0	23.91	23.66	23.81		0
	3	2	23.89	23.63	23.85		0
	3	3	23.87	23.71	23.82		0
16QAM	6	0	22.90	22.64	22.75	0-1	1
	1	0	23.29	22.97	23.10		1
	1	2	23.28	23.08	23.10	0-1	1
	1	5	23.27	23.05	23.04		1
	3	0	23.13	22.81	22.97		1
	3	2	23.19	22.84	23.04		1
	3	3	23.13	22.85	23.05		1
	6	0	22.05	21.77	21.84		1
64QAM	1	0	22.22	22.00	22.00	0-2	2
	1	2	22.33	21.98	22.15		2
	1	5	22.30	21.94	22.15	0-2	2
	3	0	22.19	21.93	22.00		2
	3	2	22.21	21.85	22.03		2
	3	3	22.19	21.89	22.01		2
	6	0	21.00	20.74	20.88	0-3	3
	1	0	19.04	18.82	18.91		5
256QAM	1	2	19.03	18.78	18.93	0-5	5
	1	5	19.12	18.83	18.96		5
	3	0	19.06	18.76	18.84		5
	3	2	19.00	18.73	18.94		5
	3	3	19.02	18.73	18.92		5
	6	0	18.98	18.63	18.76		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 8 of 426

Table H-16
LTE Band 12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.15	17.91	18.01	0	0
	1	12	18.14	17.87	18.13		0
	1	24	17.96	17.85	18.06		0
	12	0	18.05	17.94	17.92	0-1	0
	12	6	18.00	17.96	17.98		0
	12	13	17.88	17.90	17.99		0
	25	0	17.96	17.93	17.92		0
16QAM	1	0	18.43	18.28	18.23	0-1	0
	1	12	18.47	18.16	18.47		0
	1	24	18.32	18.15	18.34		0
	12	0	18.12	17.92	17.99	0-2	0
	12	6	18.08	17.95	18.02		0
	12	13	17.97	17.89	18.05		0
	25	0	17.99	17.93	17.98		0
64QAM	1	0	18.28	18.12	18.10	0-2	0
	1	12	18.36	18.17	18.21		0
	1	24	18.15	18.06	18.17		0
	12	0	18.11	17.92	17.94	0-3	0
	12	6	18.05	17.95	17.99		0
	12	13	17.94	17.90	17.99		0
	25	0	17.99	17.93	17.94		0
256QAM	1	0	18.18	18.15	18.02	0-5	0
	1	12	18.32	18.11	18.26		0
	1	24	17.98	18.10	18.11		0
	12	0	18.10	17.99	17.93		0
	12	6	18.01	17.99	17.98		0
	12	13	17.96	17.94	17.97		0
	25	0	17.99	17.94	17.93		0

Table H-17
LTE Band 12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.11	17.88	17.97	0	0
	1	7	18.31	17.91	18.22		0
	1	14	18.15	17.83	17.95		0
	8	0	18.18	17.93	18.05	0-1	0
	8	4	18.09	17.96	18.12		0
	8	7	18.07	17.91	18.11		0
16QAM	15	0	18.11	17.94	18.04	0	
	1	0	18.40	17.99	18.23	0-1	0
	1	7	18.49	18.15	18.41		0
	1	14	18.32	18.01	18.15		0
	8	0	18.32	17.98	18.10	0-2	0
	8	4	18.20	18.00	18.24		0
	8	7	18.16	17.98	18.19		0
	15	0	18.10	17.94	18.09		0
64QAM	1	0	18.30	18.11	18.18	0-2	0
	1	7	18.41	18.25	18.41		0
	1	14	18.20	18.14	18.24		0
	8	0	18.27	17.97	18.06	0-3	0
	8	4	18.13	18.03	18.20		0
	8	7	18.16	17.97	18.16		0
	15	0	18.10	17.94	18.10		0
256QAM	1	0	18.24	17.96	18.14	0-5	0
	1	7	18.41	18.09	18.23		0
	1	14	18.14	17.89	18.18		0
	8	0	18.26	17.99	18.08		0
	8	4	18.14	17.99	18.20		0
	8	7	18.10	17.96	18.16		0
	15	0	18.11	17.95	18.08		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 9 of 426

Table H-18

LTE Band 12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.09	17.78	18.02	0	0
	1	2	18.08	17.94	18.08		0
	1	5	18.06	17.91	18.09		0
	3	0	18.13	17.84	18.00		0
	3	2	18.14	17.79	18.01		0
	3	3	18.05	17.86	18.00		0
16QAM	6	0	18.14	17.82	17.94	0-1	0
	1	0	18.37	18.28	18.18		0
	1	2	18.44	18.26	18.20	0-1	0
	1	5	18.33	18.19	18.27		0
	3	0	18.34	17.94	18.30		0
	3	2	18.32	18.07	18.23		0
	3	3	18.26	18.01	18.25		0
	6	0	18.25	17.95	18.12		0-2
64QAM	1	0	18.38	18.14	18.22	0-2	0
	1	2	18.36	18.15	18.29		0
	1	5	18.35	18.04	18.32		0
	3	0	18.30	18.08	18.21		0
	3	2	18.31	18.10	18.21		0
	3	3	18.35	18.07	18.23		0
	6	0	18.21	17.97	18.01	0-3	0
256QAM	1	0	18.35	18.07	18.25	0-5	0
	1	2	18.37	18.07	18.24		0
	1	5	18.30	18.08	18.18		0
	3	0	18.28	18.02	18.12		0
	3	2	18.29	18.01	18.17		0
	3	3	18.22	18.00	18.10		0
	6	0	18.23	17.89	18.08		0

H.1.4 LTE Band 12 Antenna E

Table H-19

LTE Band 12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.47	24.16	24.30	0	0
	1	12	24.51	24.23	24.41		0
	1	24	24.29	24.17	24.51		0
	12	0	23.37	23.17	23.32	0-1	1
	12	6	23.27	23.20	23.37		1
	12	13	23.18	23.14	23.39		1
16QAM	25	0	23.22	23.14	23.30		1
	1	0	23.60	23.49	23.61	0-1	1
	1	12	23.73	23.53	23.79		1
	1	24	23.51	23.48	23.74		1
	12	0	22.37	22.19	22.35	0-2	2
	12	6	22.33	22.19	22.39		2
12	13	22.19	22.13	22.40	2		
64QAM	25	0	22.24	22.17	22.35		2
	1	0	22.65	22.28	22.42	0-2	2
	1	12	22.68	22.40	22.68		2
	1	24	22.40	22.25	22.64		2
	12	0	21.33	21.16	21.33	0-3	3
	12	6	21.29	21.19	21.38		3
12	13	21.21	21.11	21.39	3		
256QAM	25	0	21.26	21.16	21.30		3
	1	0	19.53	19.23	19.28	0-5	5
	1	12	19.45	19.29	19.52		5
	1	24	19.36	19.27	19.41		5
	12	0	19.31	19.16	19.28		5
	12	6	19.24	19.19	19.33		5
12	13	19.16	19.09	19.35	5		
	25	0	19.18	19.11	19.26		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 10 of 426

Table H-20
LTE Band 12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.26	24.16	24.29	0	0
	1	7	24.42	24.23	24.46		0
	1	14	24.29	24.05	24.34		0
	8	0	23.33	23.12	23.34	0-1	1
	8	4	23.25	23.14	23.45		1
	8	7	23.20	23.09	23.41		1
	15	0	23.27	23.15	23.34		1
16QAM	1	0	23.60	23.27	23.65	0-1	1
	1	7	23.58	23.42	23.78		1
	1	14	23.42	23.27	23.66		1
	8	0	22.37	22.18	22.39	0-2	2
	8	4	22.35	22.23	22.54		2
	8	7	22.30	22.16	22.50		2
	15	0	22.27	22.19	22.35		2
64QAM	1	0	22.55	22.16	22.57	0-2	2
	1	7	22.64	22.41	22.73		2
	1	14	22.42	22.24	22.62		2
	8	0	21.42	21.18	21.32	0-3	3
	8	4	21.30	21.19	21.43		3
	8	7	21.27	21.14	21.43		3
	15	0	21.25	21.13	21.32		3
256QAM	1	0	19.31	19.17	19.29	0-5	5
	1	7	19.53	19.23	19.58		5
	1	14	19.16	19.07	19.42		5
	8	0	19.33	19.13	19.36		5
	8	4	19.28	19.11	19.47		5
	8	7	19.23	19.11	19.40		5
	15	0	19.20	19.11	19.33		5

Table H-21
LTE Band 12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.16	24.08	24.48	0	0
	1	2	24.27	24.10	24.53		0
	1	5	24.32	24.01	24.55		0
	3	0	24.28	23.99	24.35		0
	3	2	24.27	24.01	24.38		0
	3	3	24.32	24.02	24.41		0
	6	0	23.23	23.05	23.30	0-1	1
16QAM	1	0	23.62	23.22	23.68	0-1	1
	1	2	23.45	23.36	23.71		1
	1	5	23.55	23.25	23.63		1
	3	0	23.49	23.24	23.52		1
	3	2	23.52	23.18	23.52		1
	3	3	23.50	23.19	23.55		1
	6	0	22.38	22.17	22.42	0-2	2
64QAM	1	0	22.68	22.30	22.59	0-2	2
	1	2	22.63	22.33	22.59		2
	1	5	22.46	22.22	22.65		2
	3	0	22.49	22.27	22.56		2
	3	2	22.52	22.26	22.57		2
	3	3	22.51	22.22	22.53		2
	6	0	21.33	21.15	21.40	0-3	3
256QAM	1	0	19.46	19.20	19.60	0-5	5
	1	2	19.35	19.25	19.67		5
	1	5	19.41	19.26	19.56		5
	3	0	19.38	19.19	19.42		5
	3	2	19.40	19.16	19.46		5
	3	3	19.35	19.19	19.52		5
	6	0	19.27	19.08	19.28	5	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 11 of 426

Table H-22
LTE Band 12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 12 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23035 (701.5 MHz)	23095 (707.5 MHz)	23155 (713.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.17	18.95	19.04	0	0
	1	12	19.28	19.03	19.26		0
	1	24	18.95	18.86	19.06		0
	12	0	19.24	19.01	19.04	0-1	0
	12	6	19.14	19.10	19.13		0
	12	13	19.04	18.96	19.09		0
25	0	19.12	18.96	19.08	0		
16QAM	1	0	19.44	19.14	19.05	0-1	0
	1	12	19.35	19.12	19.23		0
	1	24	19.16	19.15	19.31		0
	12	0	19.21	19.07	19.02	0-2	0
	12	6	19.25	19.04	19.15		0
	12	13	19.01	18.97	19.18		0
25	0	19.14	18.99	18.99	0		
64QAM	1	0	19.25	19.04	19.17	0-2	0
	1	12	19.22	19.11	19.39		0
	1	24	19.20	19.02	19.34		0
	12	0	19.32	19.04	19.11	0-3	0
	12	6	19.26	19.11	19.10		0
	12	13	19.08	19.00	19.06		0
25	0	19.16	18.97	19.06	0		
256QAM	1	0	19.29	19.06	19.11	0-5	0
	1	12	19.29	19.08	19.34		0
	1	24	19.10	18.97	19.18		0
	12	0	19.24	19.06	19.01	0	0
	12	6	19.20	18.99	19.19		0
	12	13	19.06	19.02	19.19		0
25	0	19.22	19.03	19.06	0		

Table H-23
LTE Band 12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 12 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23025 (700.5 MHz)	23095 (707.5 MHz)	23165 (714.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.11	18.95	18.96	0	0
	1	7	19.26	19.10	19.04		0
	1	14	18.94	18.83	19.01		0
	8	0	19.22	19.00	19.06	0-1	0
	8	4	19.23	19.03	19.16		0
	8	7	19.13	19.07	19.15		0
16QAM	15	0	19.17	18.97	19.11	0-1	0
	1	0	19.30	19.28	19.18		0
	1	7	19.51	19.07	19.45		0
	1	14	19.17	19.20	19.24	0-2	0
	8	0	19.22	19.00	19.08		0
	8	4	19.16	18.99	19.28		0
	8	7	19.13	19.09	19.10	0	
	15	0	19.18	19.02	19.10	0	
64QAM	1	0	19.35	18.99	19.14	0-2	0
	1	7	19.59	19.14	19.42		0
	1	14	19.10	19.04	19.17		0
	8	0	19.23	19.05	19.04	0-3	0
	8	4	19.16	19.10	19.23		0
	8	7	19.06	19.03	19.15		0
	15	0	19.26	18.91	19.18	0-5	0
	1	0	19.22	19.24	19.06		0
256QAM	1	7	19.34	19.06	19.25		0
	1	14	19.15	18.86	19.19	0	
	8	0	19.33	19.07	19.11	0	
	8	4	19.24	19.03	19.30	0	
	8	7	19.25	18.91	19.21	0	
	15	0	19.18	18.99	19.19	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 12 of 426

Table H-24

LTE Band 12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 12 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23017 (699.7 MHz)	23095 (707.5 MHz)	23173 (715.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.22	18.88	19.09	0	0
	1	2	19.22	18.84	19.21		0
	1	5	19.10	18.83	19.18		0
	3	0	19.07	18.92	18.91		0
	3	2	19.15	18.87	18.95		0
	3	3	19.06	18.80	19.13		0
16QAM	6	0	19.15	18.84	18.96	0-1	0
	1	0	19.40	19.12	19.12		0
	1	2	19.15	19.13	19.26		0
	1	5	19.41	18.93	19.31		0
	3	0	19.27	18.97	19.20		0
	3	2	19.22	19.06	19.33		0
64QAM	3	3	19.26	19.02	19.03	0-2	0
	6	0	19.26	19.04	19.18		0
	1	0	19.22	19.09	19.36		0
	1	2	19.06	19.00	19.25		0
	1	5	19.42	18.93	19.27		0
	3	0	19.27	19.11	19.11		0
256QAM	3	2	19.44	18.96	19.23	0-3	0
	3	3	19.30	19.04	19.39		0
	6	0	19.29	18.91	19.15		0
	1	0	19.24	19.08	19.30		0
	1	2	19.38	18.95	19.32		0
	1	5	19.22	19.04	19.29		0
256QAM	3	0	19.33	18.92	19.28	0-5	0
	3	2	19.40	18.95	19.34		0
	3	3	19.25	19.04	19.29		0
	6	0	19.15	19.10	19.03		0

H.1.5 LTE Band 13 Antenna A and Antenna A+C

Table H-25

LTE Band 13 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.98	0	0
	1	12	24.80		0
	1	24	24.62		0
	12	0	23.78	0-1	1
	12	6	23.76		1
	12	13	23.62		1
	25	0	23.73		1
16QAM	1	0	24.23	0-1	1
	1	12	24.11		1
	1	24	23.97		1
	12	0	22.84	0-2	2
	12	6	22.82		2
	12	13	22.64		2
	25	0	22.75		2
64QAM	1	0	23.10	0-2	2
	1	12	22.95		2
	1	24	22.82		2
	12	0	21.74	0-3	3
	12	6	21.81		3
	12	13	21.60		3
	25	0	21.72		3
256QAM	1	0	19.84	0-5	5
	1	12	19.82		5
	1	24	19.55		5
	12	0	19.77		5
	12	6	19.75		5
	12	13	19.60		5
	25	0	19.68		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 13 of 426

Table H-26
LTE Band 13 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz) Conducted Power [dBm]		
QPSK	1	0	18.76	0	0
	1	12	18.75		0
	1	24	18.39		0
	12	0	18.77	0-1	0
	12	6	18.69		0
	12	13	18.52		0
	25	0	18.71		0
16QAM	1	0	19.07	0-1	0
	1	12	19.09		0
	1	24	18.75		0
	12	0	18.78	0-2	0
	12	6	18.72		0
	12	13	18.58		0
	25	0	18.76		0
64QAM	1	0	19.01	0-2	0
	1	12	18.81		0
	1	24	18.63		0
	12	0	18.79	0-3	0
	12	6	18.78		0
	12	13	18.58		0
	25	0	18.69		0
256QAM	1	0	18.90	0-5	0
	1	12	18.90		0
	1	24	18.56		0
	12	0	18.86		0
	12	6	18.84		0
	12	13	18.59		0
	25	0	18.70		0

H.1.6 LTE Band 13 Antenna E

Table H-27
LTE Band 13 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz) Conducted Power [dBm]		
QPSK	1	0	24.90	0	0
	1	12	25.14		0
	1	24	24.87		0
	12	0	24.13	0-1	1
	12	6	24.07		1
	12	13	24.01		1
	25	0	24.06		1
16QAM	1	0	23.59	0-1	1
	1	12	24.32		1
	1	24	24.26		1
	12	0	23.17	0-2	2
	12	6	23.15		2
	12	13	22.92		2
	25	0	23.02		2
64QAM	1	0	23.19	0-2	2
	1	12	23.16		2
	1	24	23.25		2
	12	0	22.09	0-3	3
	12	6	22.07		3
	12	13	21.92		3
	25	0	22.10		3
256QAM	1	0	20.15	0-5	5
	1	12	20.20		5
	1	24	19.81		5
	12	0	20.06		5
	12	6	20.00		5
	12	13	19.92		5
	25	0	19.98		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 14 of 426

Table H-28
LTE Band 13 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5
MHz Bandwidth

LTE Band 13 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23230 (782.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.00	0	0
	1	12	19.29		0
	1	24	19.03		0
	12	0	19.23	0-1	0
	12	6	19.28		0
	12	13	19.12		0
	25	0	19.22		0
16QAM	1	0	19.57	0-1	0
	1	12	19.42		0
	1	24	19.29		0
	12	0	19.35	0-2	0
	12	6	19.21		0
	12	13	19.18		0
	25	0	19.30		0
64QAM	1	0	19.48	0-2	0
	1	12	19.48		0
	1	24	19.40		0
	12	0	19.26	0-3	0
	12	6	19.29		0
	12	13	19.13		0
	25	0	19.24		0
256QAM	1	0	19.51	0-5	0
	1	12	19.34		0
	1	24	19.20		0
	12	0	19.35		0
	12	6	19.20		0
	12	13	19.18		0
	25	0	19.27		0

H.1.7 LTE Band 14 Antenna A and Antenna A+C

Table H-29
LTE Band 14 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head,
Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.69	0	0
	1	12	24.78		0
	1	24	24.65		0
	12	0	23.52	0-1	1
	12	6	23.54		1
	12	13	23.45		1
	25	0	23.47		1
16QAM	1	0	23.92	0-1	1
	1	12	23.95		1
	1	24	23.79		1
	12	0	22.54	0-2	2
	12	6	22.55		2
	12	13	22.43		2
	25	0	22.49		2
64QAM	1	0	22.81	0-2	2
	1	12	22.88		2
	1	24	22.59		2
	12	0	21.50	0-3	3
	12	6	21.51		3
	12	13	21.43		3
	25	0	21.47		3
256QAM	1	0	19.63	0-5	5
	1	12	19.72		5
	1	24	19.48		5
	12	0	19.47		5
	12	6	19.50		5
	12	13	19.42		5
	25	0	19.43		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 15 of 426

Table H-30
LTE Band 14 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.76	0	0
	1	12	18.63		0
	1	24	18.60		0
	12	0	18.79	0-1	0
	12	6	18.69		0
	12	13	18.51		0
	25	0	18.67		0
16QAM	1	0	18.91	0-1	0
	1	12	18.83		0
	1	24	18.78		0
	12	0	18.80	0-2	0
	12	6	18.74		0
	12	13	18.57		0
	25	0	18.75		0
64QAM	1	0	18.79	0-2	0
	1	12	18.84		0
	1	24	18.64		0
	12	0	18.82	0-3	0
	12	6	18.78		0
	12	13	18.57		0
	25	0	18.65		0
256QAM	1	0	19.05	0-5	0
	1	12	18.81		0
	1	24	18.57		0
	12	0	18.83		0
	12	6	18.75		0
	12	13	18.62		0
	25	0	18.71		0

H.1.8 LTE Band 14 Antenna E

Table H-31
LTE Band 14 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	24.63	0	0
	1	12	24.92		0
	1	24	24.59		0
	12	0	23.70	0-1	1
	12	6	23.66		1
	12	13	23.59		1
	25	0	23.64		1
16QAM	1	0	23.93	0-1	1
	1	12	23.89		1
	1	24	23.49		1
	12	0	22.70	0-2	2
	12	6	22.72		2
	12	13	22.55		2
	25	0	22.65		2
64QAM	1	0	22.88	0-2	2
	1	12	22.94		2
	1	24	22.74		2
	12	0	21.70	0-3	3
	12	6	21.60		3
	12	13	21.54		3
	25	0	21.65		3
256QAM	1	0	19.51	0-5	5
	1	12	19.69		5
	1	24	19.49		5
	12	0	19.66		5
	12	6	19.63		5
	12	13	19.58		5
	25	0	19.49		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 16 of 426

Table H-32
LTE Band 14 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 14 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			23330 (793.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	18.87	0	0
	1	12	19.01		0
	1	24	18.74		0
	12	0	18.87	0-1	0
	12	6	18.83		0
	12	13	18.79		0
16QAM	25	0	18.80	0-1	0
	1	0	19.01		0
	1	12	19.10		0
	1	24	18.99	0-2	0
	12	0	18.81		0
	12	6	18.89		0
64QAM	12	13	18.78	0-2	0
	25	0	18.75		0
	1	0	19.03	0-2	0
	1	12	18.95		0
	1	24	18.90		0
	12	0	18.88	0-3	0
256QAM	12	6	18.92		0
	12	13	18.73		0
	25	0	18.85	0-5	0
	1	0	18.80		0
	1	12	18.98		0
	1	24	18.64		0
256QAM	12	0	18.86	0-5	0
	12	6	18.83		0
	12	13	18.69		0
	25	0	18.81		0

H.1.9 LTE Band 26 Antenna A and Antenna A+C

Table H-33
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.46	24.59	24.43	0	0	
	1	25	24.78	24.76	24.46		0	
	1	49	24.73	24.62	24.36		0	
	25	0	23.52	23.68	23.58	0-1	1	
	25	12	23.62	23.69	23.57		1	
	25	25	23.62	23.68	23.44		1	
16QAM	50	0	23.63	23.66	23.55	0-1	1	
	1	0	23.67	23.81	23.83		1	
	1	25	23.70	24.02	23.77		1	
	1	49	23.68	23.83	23.67	0-2	1	
	25	0	22.54	22.68	22.60		2	
	25	12	22.64	22.69	22.56		2	
64QAM	25	25	22.63	22.65	22.48	0-2	2	
	50	0	22.62	22.69	22.55		2	
	1	0	22.65	22.87	22.69		0-2	2
	1	25	22.78	22.90	22.80	2		
	1	49	22.80	22.78	22.57	2		
	25	0	21.54	21.69	21.56	0-3	3	
25	12	21.66	21.70	21.56	3			
25	25	21.59	21.67	21.46	3			
256QAM	50	0	21.64	21.67	21.54	0-3	3	
	1	0	19.58	19.66	19.74		0-5	5
	1	25	19.73	19.86	19.63			5
	1	49	19.67	19.61	19.40	5		
	25	0	19.52	19.66	19.56	5		
	25	12	19.63	19.69	19.56	5		
25	25	19.58	19.63	19.43	5			
	50	0	19.60	19.64	19.54		5	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 17 of 426

Table H-34
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.65	24.71	24.48	0	0
	1	12	24.70	24.79	24.50		0
	1	24	24.60	24.66	24.38		0
	12	0	23.50	23.70	23.55	0-1	1
	12	6	23.61	23.71	23.55		1
	12	13	23.57	23.68	23.48		1
16QAM	25	0	23.57	23.65	23.51	0-1	1
	1	0	23.85	23.99	23.84		1
	1	12	23.89	24.10	23.84		1
	1	24	23.83	23.95	23.80	0-2	1
	12	0	22.54	22.71	22.55		2
	12	6	22.64	22.74	22.56		2
64QAM	12	13	22.59	22.66	22.49	0-2	2
	25	0	22.57	22.67	22.53		2
	1	0	22.69	22.86	22.71	0-2	2
	1	12	22.94	22.92	22.69		2
	1	24	22.73	22.80	22.49		2
	12	0	21.51	21.69	21.56	0-3	3
	12	6	21.59	21.71	21.53		3
	12	13	21.56	21.61	21.48		3
256QAM	25	0	21.58	21.63	21.48	0-5	3
	1	0	19.58	19.73	19.66		5
	1	12	19.64	19.82	19.60		5
	1	24	19.59	19.65	19.42		5
	12	0	19.47	19.64	19.51		5
	12	6	19.59	19.70	19.50		5
	12	13	19.53	19.64	19.50		5
25	0	19.52	19.62	19.47	5		

Table H-35
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.48	24.68	24.41	0	0
	1	7	24.56	24.84	24.48		0
	1	14	24.48	24.66	24.30		0
	8	0	23.55	23.66	23.51	0-1	1
	8	4	23.54	23.63	23.47		1
	8	7	23.53	23.62	23.48		1
	15	0	23.54	23.67	23.50		1
16QAM	1	0	23.62	23.89	23.67	0-1	1
	1	7	23.68	24.05	23.68		1
	1	14	23.66	23.88	23.69		1
	8	0	22.61	22.72	22.53	0-2	2
	8	4	22.61	22.72	22.54		2
	8	7	22.59	22.71	22.52		2
	15	0	22.59	22.66	22.49		2
64QAM	1	0	22.72	22.85	22.60	0-2	2
	1	7	22.70	22.94	22.65		2
	1	14	22.67	22.87	22.45		2
	8	0	21.56	21.68	21.53	0-3	3
	8	4	21.61	21.70	21.49		3
	8	7	21.58	21.65	21.48		3
	15	0	21.57	21.66	21.51		3
256QAM	1	0	19.51	19.64	19.50	0-5	5
	1	7	19.66	19.81	19.52		5
	1	14	19.57	19.71	19.45		5
	8	0	19.55	19.64	19.51		5
	8	4	19.52	19.64	19.47		5
	8	7	19.52	19.64	19.42		5
	15	0	19.51	19.64	19.45		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 18 of 426

Table H-36
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.44	24.62	24.55	0	0
	1	2	24.50	24.73	24.53		0
	1	5	24.49	24.71	24.51		0
	3	0	24.46	24.60	24.46		0
	3	2	24.47	24.68	24.43		0
	3	3	24.49	24.68	24.42		0
	6	0	23.46	23.60	23.39	0-1	1
16QAM	1	0	23.73	23.93	23.67	0-1	1
	1	2	23.83	24.01	23.74		1
	1	5	23.66	23.96	23.63		1
	3	0	23.65	23.79	23.60		1
	3	2	23.67	23.92	23.52		1
	3	3	23.61	23.88	23.57		1
	6	0	22.59	22.76	22.53	0-2	2
64QAM	1	0	22.71	22.98	22.53	0-2	2
	1	2	22.66	23.05	22.51		2
	1	5	22.65	22.94	22.51		2
	3	0	22.68	22.81	22.51		2
	3	2	22.66	22.91	22.56		2
	3	3	22.63	22.86	22.55		2
	6	0	21.53	21.69	21.41	0-3	3
256QAM	1	0	19.57	19.76	19.60	0-5	5
	1	2	19.61	19.81	19.64		5
	1	5	19.58	19.91	19.63		5
	3	0	19.63	19.73	19.52		5
	3	2	19.58	19.83	19.54		5
	3	3	19.59	19.79	19.57		5
	6	0	19.49	19.62	19.39		5

Table H-37
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.96	18.07	17.92	0	0
	1	25	17.97	18.09	17.89		0
	1	49	17.93	17.98	17.81		0
	25	0	17.98	18.10	18.05	0-1	0
	25	12	18.08	18.09	17.99		0
	25	25	18.08	18.02	17.91		0
	50	0	18.04	18.00	17.97		0
16QAM	1	0	18.21	18.31	18.15	0-1	0
	1	25	18.19	18.31	18.01		0
	1	49	17.95	18.06	18.13		0
	25	0	17.97	18.06	17.98	0-2	0
	25	12	17.97	18.11	17.93		0
	25	25	18.00	18.05	17.82		0
	50	0	18.05	18.02	17.96		0
64QAM	1	0	18.25	18.16	18.16	0-2	0
	1	25	18.14	18.37	18.17		0
	1	49	18.02	18.25	17.91		0
	25	0	18.07	18.09	18.02	0-3	0
	25	12	18.07	18.17	18.05		0
	25	25	18.01	18.13	17.96		0
	50	0	18.09	18.06	17.94		0
256QAM	1	0	18.07	18.24	18.15	0-5	0
	1	25	18.16	18.26	17.94		0
	1	49	18.14	18.12	17.75		0
	25	0	17.98	18.05	17.99		0
	25	12	18.04	18.09	17.97		0
	25	25	18.02	18.06	17.84		0
	50	0	18.11	18.07	17.98	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 19 of 426

Table H-38
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	18.00	18.00	17.89	0	0	
	1	12	18.01	18.14	17.92		0	
	1	24	17.84	17.92	17.71		0	
	12	0	17.97	18.07	17.96	0-1	0	
	12	6	18.09	18.11	17.97		0	
	12	13	17.99	18.03	17.89		0	
16QAM	25	0	18.07	18.04	17.92	0-1	0	
	1	0	18.12	18.22	18.13		0	
	1	12	18.17	18.25	18.15		0	
	1	24	18.07	18.21	17.85	0-2	0	
	12	0	18.01	18.01	18.01		0	
	12	6	18.15	18.05	18.02		0	
64QAM	12	13	18.10	18.07	17.93	0-2	0	
	25	0	18.03	18.03	17.93		0	
	1	0	17.99	18.26	18.00		0-2	0
	1	12	18.12	18.11	17.95	0		
	1	24	18.13	18.33	17.89	0-3		0
	12	0	18.03	18.02	18.04		0	
12	6	18.04	18.01	17.96	0			
256QAM	12	13	18.06	18.10	17.93	0-3	0	
	25	0	18.06	18.09	17.97		0-5	0
	1	0	17.99	18.07	18.02			0
	1	12	18.26	18.16	18.10	0-5		0
	1	24	18.00	18.03	17.84		0	
	12	0	18.08	18.08	17.97		0	
256QAM	12	6	18.10	18.11	18.03	0-5	0	
	12	13	18.03	18.03	17.90		0	
	25	0	18.07	17.97	17.97		0	

Table H-39
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.94	17.94	17.83	0	0
	1	7	17.97	18.25	17.98		0
	1	14	17.93	17.97	17.84		0
	8	0	18.03	18.00	17.87	0-1	0
	8	4	18.08	18.04	17.95		0
	8	7	18.00	18.04	17.83		0
	15	0	18.09	18.05	17.94	0	
16QAM	1	0	18.12	18.43	18.09	0-1	0
	1	7	18.40	18.22	18.03		0
	1	14	18.10	18.19	17.97		0
	8	0	18.12	18.08	17.93	0-2	0
	8	4	18.05	18.04	17.92		0
	8	7	18.01	18.02	17.90		0
	15	0	18.05	18.08	17.93	0	
64QAM	1	0	18.05	18.16	17.96	0-2	0
	1	7	18.12	18.47	18.14		0
	1	14	18.01	18.18	17.93		0
	8	0	18.00	18.07	17.94	0-3	0
	8	4	18.05	18.11	17.97		0
	8	7	18.06	18.03	17.90		0
	15	0	18.07	18.06	17.95	0	
256QAM	1	0	18.04	18.02	17.92	0-5	0
	1	7	18.08	18.20	18.18		0
	1	14	17.86	18.16	17.98		0
	8	0	18.07	18.14	17.88	0-5	0
	8	4	18.06	18.06	17.97		0
	8	7	18.04	18.08	17.83		0
	15	0	18.05	18.07	17.91	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 20 of 426

Table H-40
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.94	18.03	17.88	0	0
	1	2	17.78	18.05	17.88		0
	1	5	17.96	18.03	17.85		0
	3	0	17.98	18.02	17.85		0
	3	2	18.00	18.08	17.85		0
	3	3	17.90	18.15	17.84		0
	6	0	17.93	17.99	17.88	0-1	0
16QAM	1	0	18.36	18.56	17.97	0-1	0
	1	2	18.11	18.35	18.42		0
	1	5	18.21	18.39	18.30		0
	3	0	18.04	18.16	17.96		0
	3	2	18.08	18.16	17.91		0
	3	3	18.13	18.24	17.91		0
	6	0	18.07	18.13	17.91	0-2	0
64QAM	1	0	18.03	17.97	17.99	0-2	0
	1	2	18.17	18.25	18.01		0
	1	5	18.07	18.15	17.83		0
	3	0	17.94	18.16	18.15		0
	3	2	18.05	18.16	17.87		0
	3	3	18.04	18.20	17.86		0
	6	0	18.00	18.04	17.91	0-3	0
256QAM	1	0	18.10	17.91	17.95	0-5	0
	1	2	18.12	18.08	18.17		0
	1	5	17.86	18.31	17.82		0
	3	0	17.99	18.05	17.99		0
	3	2	18.06	18.17	18.01		0
	3	3	18.08	18.31	17.92		0
	6	0	17.98	17.85	17.85	0	

H.1.10 LTE Band 26 Antenna E

Table H-41
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.41	24.42	24.41	0	0
	1	25	24.51	24.59	24.24		0
	1	49	24.30	24.46	24.11		0
	25	0	23.30	23.44	23.32		1
	25	12	23.42	23.45	23.33		1
	25	25	23.38	23.38	23.21		1
	50	0	23.40	23.41	23.33		1
16QAM	1	0	23.47	23.60	23.62	0-1	1
	1	25	23.58	23.75	23.55		1
	1	49	23.47	23.67	23.37		1
	25	0	22.32	22.43	22.33		2
	25	12	22.43	22.46	22.33		2
	25	25	22.39	22.40	22.19		2
	50	0	22.40	22.44	22.30		2
64QAM	1	0	22.51	22.60	22.44	0-2	2
	1	25	22.56	22.66	22.47		2
	1	49	22.41	22.69	22.37		2
	25	0	21.31	21.43	21.30		3
	25	12	21.36	21.47	21.33		3
	25	25	21.37	21.40	21.18		3
	50	0	21.38	21.41	21.27		3
256QAM	1	0	19.42	19.45	19.44	0-5	5
	1	25	19.43	19.61	19.39		5
	1	49	19.55	19.39	19.22		5
	25	0	19.30	19.42	19.31		5
	25	12	19.38	19.47	19.30		5
	25	25	19.38	19.40	19.15		5
	50	0	19.35	19.38	19.27		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 21 of 426

Table H-42
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	24.49	24.70	24.27	0	0	
	1	12	24.54	24.69	24.29		0	
	1	24	24.44	24.49	23.91		0	
	12	0	23.31	23.43	23.27	0-1	1	
	12	6	23.39	23.49	23.29		1	
	12	13	23.33	23.40	23.18		1	
16QAM	25	0	23.38	23.42	23.24	0-1	1	
	1	0	23.67	23.94	23.74		0-2	1
	1	12	23.67	23.97	23.65			1
	1	24	23.58	23.77	23.42	0-2		1
	12	0	22.34	22.48	22.29		2	
	12	6	22.41	22.53	22.31		2	
64QAM	12	13	22.36	22.42	22.26	0-2	2	
	25	0	22.35	22.45	22.25		0-3	2
	1	0	22.59	22.74	22.47			2
	1	12	22.60	22.82	22.49	0-2		2
	1	24	22.49	22.49	22.20		0-3	2
	12	0	21.28	21.42	21.28			3
256QAM	12	6	21.38	21.46	21.29	0-3		3
	12	13	21.31	21.42	21.23		0-5	3
	25	0	21.34	21.40	21.23			3
	1	0	19.33	19.47	19.30	0-5		5
	1	12	19.48	19.62	19.28		5	
	1	24	19.40	19.38	19.07		5	
12	0	19.25	19.45	19.24	5			
12	6	19.38	19.46	19.27	5			
12	13	19.31	19.38	19.17	5			
	25	0	19.29	19.43	19.20		5	

Table H-43
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.19	24.57	24.30	0	0
	1	7	24.38	24.66	24.28		0
	1	14	24.32	24.54	23.83		0
	8	0	23.35	23.41	23.21	0-1	1
	8	4	23.33	23.40	23.25		1
	8	7	23.31	23.40	23.20		1
	15	0	23.34	23.42	23.21		1
16QAM	1	0	23.50	23.78	23.50	0-1	1
	1	7	23.56	23.87	23.59		1
	1	14	23.45	23.67	23.40		1
	8	0	22.37	22.52	22.31	0-2	2
	8	4	22.37	22.50	22.29		2
	8	7	22.37	22.47	22.24		2
	15	0	22.39	22.43	22.25		2
64QAM	1	0	22.46	22.72	22.46	0-2	2
	1	7	22.56	22.87	22.43		2
	1	14	22.39	22.71	22.24		2
	8	0	21.40	21.46	21.23	0-3	3
	8	4	21.38	21.46	21.25		3
	8	7	21.35	21.47	21.18		3
	15	0	21.38	21.42	21.21		3
256QAM	1	0	19.34	19.45	19.27	0-5	5
	1	7	19.48	19.64	19.26		5
	1	14	19.31	19.40	19.23		5
	8	0	19.38	19.43	19.23		5
	8	4	19.37	19.40	19.23		5
	8	7	19.33	19.38	19.17		5
	15	0	19.29	19.41	19.15		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 22 of 426

Table H-44
LTE Band 26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.27	24.48	24.35	0	0
	1	2	24.31	24.56	24.24		0
	1	5	24.37	24.54	23.82		0
	3	0	24.34	24.39	24.12		0
	3	2	24.29	24.53	24.01		0
	3	3	24.32	24.53	23.84		0
	6	0	23.30	23.35	23.13	0-1	1
16QAM	1	0	23.54	23.80	23.51	0-1	1
	1	2	23.52	23.92	23.34		1
	1	5	23.48	23.86	23.38		1
	3	0	23.47	23.65	23.30		1
	3	2	23.51	23.80	23.29		1
	3	3	23.47	23.73	23.29		1
	6	0	22.47	22.54	22.27	0-2	2
64QAM	1	0	22.60	22.76	22.37	0-2	2
	1	2	22.57	22.92	22.41		2
	1	5	22.45	22.82	22.21		2
	3	0	22.57	22.63	22.27		2
	3	2	22.53	22.73	22.31		2
	3	3	22.51	22.71	22.14		2
	6	0	21.36	21.45	21.14	0-3	3
256QAM	1	0	19.55	19.45	19.34	0-5	5
	1	2	19.42	19.63	19.43		5
	1	5	19.39	19.53	19.35		5
	3	0	19.39	19.44	19.18		5
	3	2	19.29	19.55	19.18		5
	3	3	19.37	19.49	19.19		5
	6	0	19.26	19.38	19.15		5

Table H-45
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 26 (Cell) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26740 (819.0 MHz)	26865 (831.5 MHz)	26990 (844.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.42	19.50	19.41	0	0
	1	25	19.54	19.56	19.52		0
	1	49	19.39	19.53	19.43		0
	25	0	19.41	19.53	19.39	0-1	0
	25	12	19.50	19.49	19.40		0
	25	25	19.43	19.46	19.34		0
	50	0	19.45	19.55	19.31		0
16QAM	1	0	19.49	19.82	19.37	0-1	0
	1	25	19.82	19.77	19.61		0
	1	49	19.57	19.63	19.39		0
	25	0	19.49	19.49	19.36	0-2	0
	25	12	19.51	19.63	19.36		0
	25	25	19.44	19.50	19.35		0
	50	0	19.47	19.48	19.38		0
64QAM	1	0	19.65	19.64	19.49	0-2	0
	1	25	19.63	19.81	19.39		0
	1	49	19.41	19.64	19.40		0
	25	0	19.54	19.53	19.40	0-3	0
	25	12	19.49	19.57	19.42		0
	25	25	19.44	19.54	19.44		0
	50	0	19.46	19.57	19.42		0
256QAM	1	0	19.24	19.28	19.30	0-5	1
	1	25	19.28	19.46	19.16		1
	1	49	19.32	19.34	18.91		1
	25	0	19.24	19.30	19.08		1
	25	12	19.20	19.21	19.09		1
	25	25	19.23	19.26	19.04		1
	50	0	19.31	19.20	19.13	1	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 23 of 426

Table H-46
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 26 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26715 (816.5 MHz)	26865 (831.5 MHz)	27015 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.51	19.45	19.33	0	0
	1	12	19.44	19.62	19.42		0
	1	24	19.43	19.32	19.38		0
	12	0	19.34	19.53	19.26	0-1	0
	12	6	19.46	19.52	19.33		0
	12	13	19.40	19.47	19.29		0
	25	0	19.38	19.51	19.25		0
16QAM	1	0	19.66	19.74	19.35	0-1	0
	1	12	19.80	19.79	19.46		0
	1	24	19.56	19.58	19.30		0
	12	0	19.46	19.50	19.37	0-2	0
	12	6	19.45	19.59	19.35		0
	12	13	19.44	19.58	19.29		0
	25	0	19.49	19.50	19.30		0
64QAM	1	0	19.55	19.75	19.60	0-2	0
	1	12	19.54	19.67	19.39		0
	1	24	19.38	19.56	19.28		0
	12	0	19.35	19.51	19.43	0-3	0
	12	6	19.57	19.54	19.42		0
	12	13	19.48	19.49	19.27		0
	25	0	19.42	19.63	19.36		0
256QAM	1	0	19.11	19.26	19.19	0-5	1
	1	12	19.32	19.31	19.22		1
	1	24	19.32	19.08	19.02		1
	12	0	19.16	19.24	19.10		1
	12	6	19.30	19.29	19.12		1
	12	13	19.27	19.19	19.06		1
	25	0	19.16	19.28	19.02		1

Table H-47
LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 26 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26705 (815.5 MHz)	26865 (831.5 MHz)	27025 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.35	19.46	19.25	0	0
	1	7	19.38	19.51	19.27		0
	1	14	19.42	19.46	19.31		0
	8	0	19.43	19.41	19.28	0-1	0
	8	4	19.38	19.48	19.20		0
	8	7	19.33	19.48	19.24		0
	15	0	19.45	19.46	19.27		0
16QAM	1	0	19.41	19.70	19.49	0-1	0
	1	7	19.67	19.68	19.48		0
	1	14	19.56	19.76	19.21		0
	8	0	19.55	19.55	19.25	0-2	0
	8	4	19.48	19.50	19.36		0
	8	7	19.50	19.61	19.30		0
	15	0	19.32	19.52	19.30		0
64QAM	1	0	19.56	19.68	19.45	0-2	0
	1	7	19.33	19.80	19.48		0
	1	14	19.56	19.58	19.25		0
	8	0	19.47	19.58	19.37	0-3	0
	8	4	19.43	19.55	19.34		0
	8	7	19.49	19.58	19.29		0
	15	0	19.47	19.58	19.29		0
256QAM	1	0	19.12	19.19	19.07	0-5	1
	1	7	19.30	19.39	19.09		1
	1	14	19.22	19.27	19.01		1
	8	0	19.21	19.29	19.07		1
	8	4	19.24	19.28	19.01		1
	8	7	19.17	19.33	19.05		1
	15	0	19.17	19.26	19.01		1

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 24 of 426

Table H-48

LTE Band 26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 26 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26697 (814.7 MHz)	26865 (831.5 MHz)	27033 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.45	19.43	19.38	0	0
	1	2	19.54	19.44	19.53		0
	1	5	19.40	19.49	19.44		0
	3	0	19.48	19.52	19.22		0
	3	2	19.39	19.43	19.33		0
	3	3	19.45	19.45	19.21		0
	6	0	19.40	19.59	19.39	0-1	0
16QAM	1	0	19.70	19.70	19.49	0-1	0
	1	2	19.47	19.70	19.44		0
	1	5	19.55	19.67	19.40		0
	3	0	19.46	19.53	19.28		0
	3	2	19.50	19.74	19.36		0
	3	3	19.52	19.57	19.27		0
	6	0	19.46	19.47	19.39	0-2	0
64QAM	1	0	19.50	19.67	19.41	0-2	0
	1	2	19.71	19.69	19.40		0
	1	5	19.56	19.60	19.35		0
	3	0	19.64	19.57	19.51		0
	3	2	19.64	19.62	19.50		0
	3	3	19.51	19.72	19.41		0
	6	0	19.51	19.42	19.32	0-3	0
256QAM	1	0	19.36	19.15	19.08	0-5	1
	1	2	19.25	19.19	19.20		1
	1	5	19.25	19.07	19.05		1
	3	0	19.29	19.23	19.01		1
	3	2	19.22	19.31	19.02		1
	3	3	19.14	19.42	18.90		1
	6	0	19.17	19.18	18.70		1

H.1.11 LTE Band 5 Antenna A and Antenna A+C

Table H-49

LTE Band 5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.98	24.77	24.70	0	0
	1	12	24.92	24.78	24.56		0
	1	24	24.97	24.69	24.47		0
	12	0	23.82	23.66	23.61	0-1	1
	12	6	23.82	23.75	23.61		1
	12	13	23.77	23.60	23.55		1
	25	0	23.78	23.65	23.56		1
16QAM	1	0	24.00	23.95	23.90	0-1	1
	1	12	23.99	23.90	23.95		1
	1	24	23.95	23.99	23.78		1
	12	0	22.83	22.70	22.65	0-2	2
	12	6	22.82	22.78	22.66		2
	12	13	22.79	22.65	22.57		2
	25	0	22.82	22.64	22.60		2
64QAM	1	0	22.95	22.87	22.91	0-2	2
	1	12	22.90	22.93	22.77		2
	1	24	22.77	22.82	22.64		2
	12	0	21.81	21.66	21.62	0-3	3
	12	6	21.83	21.75	21.60		3
	12	13	21.80	21.58	21.54		3
	25	0	21.81	21.60	21.56		3
256QAM	1	0	19.92	19.70	19.62	0-5	5
	1	12	19.89	19.76	19.66		5
	1	24	19.77	19.63	19.47		5
	12	0	19.77	19.63	19.61		5
	12	6	19.79	19.75	19.61		5
	12	13	19.73	19.62	19.51		5
	25	0	19.75	19.59	19.56		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 25 of 426

Table H-50
LTE Band 5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.64	24.67	24.42	0	0
	1	7	24.72	24.78	24.57		0
	1	14	24.55	24.48	24.23		0
	8	0	23.58	23.51	23.38	0-1	1
	8	4	23.56	23.47	23.35		1
	8	7	23.55	23.38	23.32		1
	15	0	23.61	23.42	23.36		1
16QAM	1	0	23.86	23.71	23.69	0-1	1
	1	7	23.72	23.74	23.63		1
	1	14	23.74	23.63	23.58		1
	8	0	22.65	22.59	22.44	0-2	2
	8	4	22.64	22.57	22.42		2
	8	7	22.61	22.47	22.39		2
	15	0	22.60	22.46	22.39		2
64QAM	1	0	22.87	22.66	22.66	0-2	2
	1	7	22.86	22.81	22.55		2
	1	14	22.80	22.68	22.46		2
	8	0	21.67	21.54	21.40	0-3	3
	8	4	21.61	21.52	21.36		3
	8	7	21.58	21.41	21.35		3
	15	0	21.60	21.45	21.38		3
256QAM	1	0	19.55	19.56	19.39	0-5	5
	1	7	19.76	19.59	19.37		5
	1	14	19.56	19.40	19.36		5
	8	0	19.59	19.47	19.36		5
	8	4	19.58	19.49	19.32		5
	8	7	19.54	19.37	19.31		5
	15	0	19.55	19.40	19.31		5

Table H-51
LTE Band 5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.61	24.46	24.43	0	0
	1	2	24.52	24.49	24.42		0
	1	5	24.49	24.41	24.41		0
	3	0	24.57	24.42	24.26		0
	3	2	24.52	24.41	24.31		0
	3	3	24.50	24.42	24.27		0
16QAM	6	0	23.52	23.45	23.28	0-1	1
	1	0	23.80	23.70	23.60	0-1	1
	1	2	23.76	23.70	23.59		1
	1	5	23.81	23.67	23.53		1
	3	0	23.88	23.64	23.45		1
	3	2	23.72	23.60	23.41		1
	3	3	23.70	23.61	23.45		1
	6	0	22.63	22.53	22.38	0-2	2
64QAM	1	0	22.77	22.76	22.43	0-2	2
	1	2	22.73	22.70	22.44		2
	1	5	22.68	22.71	22.27		2
	3	0	22.73	22.66	22.39		2
	3	2	22.86	22.65	22.35		2
	3	3	22.64	22.68	22.36		2
256QAM	6	0	21.58	21.50	21.32	0-3	3
	1	0	19.56	19.59	19.53	0-5	5
	1	2	19.65	19.58	19.48		5
	1	5	19.58	19.61	19.39		5
	3	0	19.65	19.52	19.34		5
	3	2	19.62	19.55	19.34		5
3	3	19.60	19.51	19.36	5		
	6	0	19.50	19.44	19.19		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 26 of 426

Table H-52
LTE Band 5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.32	20.15	19.89	0	0
	1	12	20.15	20.02	19.91		0
	1	24	20.24	20.00	19.73		0
	12	0	20.37	20.25	20.01	0-1	0
	12	6	20.34	20.13	20.00		0
	12	13	20.24	20.04	19.87		0
	25	0	20.17	20.09	19.94		0
16QAM	1	0	20.40	20.15	20.12	0-1	0
	1	12	20.28	20.27	20.17		0
	1	24	20.29	20.28	20.04		0
	12	0	20.39	20.21	20.08	0-2	0
	12	6	20.40	20.13	20.07		0
	12	13	20.32	20.11	20.01		0
	25	0	20.16	20.07	19.93		0
64QAM	1	0	20.38	20.31	20.10	0-2	0
	1	12	20.36	20.26	20.20		0
	1	24	20.38	20.07	19.96		0
	12	0	20.39	20.15	19.96	0-3	0
	12	6	20.33	20.13	19.96		0
	12	13	20.28	20.10	20.01		0
	25	0	20.16	20.09	19.90		0
256QAM	1	0	20.00	19.98	19.70	0-5	1
	1	12	19.99	19.98	19.63		1
	1	24	20.00	19.79	19.52		1
	12	0	19.97	19.88	19.70		1
	12	6	19.96	19.89	19.68		1
	12	13	19.94	19.78	19.65		1
	25	0	19.87	19.70	19.67		1

Table H-53
LTE Band 5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.30	19.99	19.86	0	0
	1	7	20.15	20.16	19.78		0
	1	14	20.18	19.85	19.66		0
	8	0	20.36	20.14	19.92	0-1	0
	8	4	20.51	20.12	19.93		0
	8	7	20.32	20.10	19.84		0
	15	0	20.29	20.02	19.87		0
16QAM	1	0	20.31	20.36	20.16	0-1	0
	1	7	20.32	20.30	19.98		0
	1	14	20.38	20.04	19.90		0
	8	0	20.38	20.17	19.95	0-2	0
	8	4	20.35	20.11	19.95		0
	8	7	20.39	20.13	19.94		0
	15	0	20.40	20.09	19.93		0
64QAM	1	0	20.36	20.35	20.06	0-2	0
	1	7	20.39	20.19	20.19		0
	1	14	20.39	20.18	19.93		0
	8	0	20.35	20.13	19.86	0-3	0
	8	4	20.37	20.15	19.98		0
	8	7	20.36	20.15	19.92		0
	15	0	20.36	20.08	19.95		0
256QAM	1	0	20.00	19.76	19.65	0-5	1
	1	7	19.99	19.80	19.62		1
	1	14	19.96	19.72	19.58		1
	8	0	19.93	19.85	19.62		1
	8	4	19.97	19.78	19.61		1
	8	7	19.99	19.76	19.58		1
	15	0	19.98	19.72	19.63		1

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 27 of 426

Table H-54
LTE Band 5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	20.25	20.00	19.86	0	0	
	1	2	20.16	19.98	19.85		0	
	1	5	20.22	20.08	19.82		0	
	3	0	20.28	19.94	19.73		0	
	3	2	20.45	19.90	19.81		0	
	3	3	20.19	20.01	19.67		0	
16QAM	6	0	20.39	20.12	19.85	0-1	0	
	1	0	20.38	20.29	20.02	0-1	0	
	1	2	20.39	20.23	20.01		0	
	1	5	20.33	20.16	20.05		0	
	3	0	20.38	20.16	19.89		0	
	3	2	20.28	20.19	19.89		0	
64QAM	3	3	20.41	20.08	19.91		0-2	0
	6	0	20.37	20.10	20.01	0		
	1	0	20.40	20.18	20.02	0		
	1	2	20.35	20.04	19.95	0		
	1	5	20.39	20.19	19.99	0		
	3	0	20.54	20.29	20.07	0		
256QAM	3	2	20.41	20.23	20.19	0-3	0	
	3	3	20.57	20.25	19.96		0	
	6	0	20.37	19.99	20.01		0	
	1	0	20.00	19.50	19.55		0-5	1
	1	2	19.96	19.42	19.65			1
	1	5	19.99	19.49	19.67			1
3	0	19.56	19.46	19.59	1			
3	2	19.70	19.51	19.59	1			
256QAM	3	3	19.98	19.52	19.53	1		
	6	0	19.96	19.48	19.57	1		

H.1.12 LTE Band 5 Antenna E

Table H-55
LTE Band 5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.85	24.54	24.36	0	0
	1	12	24.82	24.58	24.40		0
	1	24	24.77	24.50	23.80		0
	12	0	23.66	23.49	23.42	0-1	1
	12	6	23.67	23.56	23.40		1
	12	13	23.64	23.45	23.33		1
16QAM	25	0	23.64	23.44	23.40		1
	1	0	23.99	23.85	23.77	0-1	1
	1	12	23.98	23.94	23.75		1
	1	24	23.95	23.75	23.63		1
	12	0	22.70	22.51	22.44	0-2	2
	12	6	22.68	22.57	22.44		2
12	13	22.68	22.47	22.38	2		
64QAM	25	0	22.68	22.46	22.39		2
	1	0	22.95	22.74	22.63	0-2	2
	1	12	22.95	22.59	22.63		2
	1	24	22.96	22.56	22.39		2
	12	0	21.69	21.48	21.40	0-3	3
	12	6	21.68	21.55	21.43		3
12	13	21.65	21.40	21.34	3		
256QAM	25	0	21.63	21.41	21.36		3
	1	0	19.77	19.51	19.50	0-5	5
	1	12	19.73	19.52	19.48		5
	1	24	19.66	19.40	19.21		5
	12	0	19.61	19.41	19.35		5
	12	6	19.59	19.53	19.37		5
12	13	19.56	19.36	19.27	5		
	25	0	19.58	19.37	19.29		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 28 of 426

Table H-56
LTE Band 5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.66	24.67	24.42	0	0
	1	7	24.67	24.56	24.31		0
	1	14	24.63	24.60	23.88		0
	8	0	23.62	23.51	23.35	0-1	1
	8	4	23.58	23.49	23.36		1
	8	7	23.59	23.41	23.32		1
16QAM	15	0	23.62	23.43	23.35	0-1	1
	1	0	23.87	23.70	23.76		1
	1	7	23.92	23.85	23.62		1
	1	14	23.88	23.56	23.50	0-2	1
	8	0	22.69	22.56	22.41		2
	8	4	22.66	22.53	22.40		2
	8	7	22.67	22.44	22.37		2
	15	0	22.65	22.43	22.36		2
64QAM	1	0	22.96	22.74	22.53	0-2	2
	1	7	22.87	22.75	22.57		2
	1	14	22.88	22.57	22.39		2
	8	0	21.66	21.52	21.35	0-3	3
	8	4	21.66	21.53	21.36		3
	8	7	21.67	21.38	21.30		3
	15	0	21.66	21.39	21.32		3
256QAM	1	0	19.71	19.58	19.34	0-5	5
	1	7	19.61	19.51	19.36		5
	1	14	19.59	19.49	19.26		5
	8	0	19.61	19.47	19.28		5
	8	4	19.58	19.45	19.31		5
	8	7	19.58	19.35	19.30		5
	15	0	19.59	19.39	19.28		5

Table H-57
LTE Band 5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 5 (Cell)							
1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	24.53	24.48	24.35	0	0
	1	2	24.66	24.50	24.03		0
	1	5	24.66	24.44	23.75		0
	3	0	24.58	24.40	23.99		0
	3	2	24.56	24.39	23.70		0
	3	3	24.59	24.41	23.65		0
16QAM	6	0	23.50	23.45	23.25	0-1	1
	1	0	23.77	23.69	23.53	0-1	1
	1	2	23.93	23.72	23.51		1
	1	5	23.89	23.61	23.56		1
	3	0	23.72	23.60	23.44		1
	3	2	23.75	23.62	23.42		1
	3	3	23.72	23.57	23.48		1
	6	0	22.65	22.55	22.35	0-2	2
64QAM	1	0	22.84	22.77	22.45	0-2	2
	1	2	22.90	22.78	22.38		2
	1	5	22.85	22.55	22.57		2
	3	0	22.68	22.60	22.32		2
	3	2	22.76	22.70	22.38		2
	3	3	22.67	22.67	22.34		2
256QAM	6	0	21.59	21.49	21.33	0-3	3
	1	0	19.63	19.63	19.38	0-5	5
	1	2	19.65	19.52	19.49		5
	1	5	19.60	19.46	19.37		5
	3	0	19.63	19.54	19.35		5
	3	2	19.71	19.60	19.30		5
3	3	19.61	19.57	19.36	5		
256QAM	6	0	19.54	19.43	19.20		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 29 of 426

Table H-58
LTE Band 5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 5 (Cell) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20425 (826.5 MHz)	20525 (836.5 MHz)	20625 (846.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.32	20.15	19.89	0	0
	1	12	20.15	20.02	19.91		0
	1	24	20.24	20.00	19.73		0
	12	0	20.37	20.25	20.01	0-1	0
	12	6	20.34	20.13	20.00		0
	12	13	20.24	20.04	19.87		0
	25	0	20.17	20.09	19.94		0
16QAM	1	0	20.40	20.15	20.12	0-1	0
	1	12	20.28	20.27	20.17		0
	1	24	20.29	20.28	20.04		0
	12	0	20.39	20.21	20.08	0-2	0
	12	6	20.40	20.13	20.07		0
	12	13	20.32	20.11	20.01		0
	25	0	20.16	20.07	19.93		0
64QAM	1	0	20.38	20.31	20.10	0-2	0
	1	12	20.36	20.26	20.20		0
	1	24	20.38	20.07	19.96		0
	12	0	20.39	20.15	19.96	0-3	0
	12	6	20.33	20.13	19.96		0
	12	13	20.28	20.10	20.01		0
	25	0	20.16	20.09	19.90		0
256QAM	1	0	20.00	19.98	19.70	0-5	1
	1	12	19.99	19.98	19.63		1
	1	24	20.00	19.79	19.52		1
	12	0	19.97	19.88	19.70		1
	12	6	19.96	19.89	19.68		1
	12	13	19.94	19.78	19.65		1
	25	0	19.87	19.70	19.67		1

Table H-59
LTE Band 5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 5 (Cell) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20415 (825.5 MHz)	20525 (836.5 MHz)	20635 (847.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.30	19.99	19.86	0	0
	1	7	20.15	20.16	19.78		0
	1	14	20.18	19.85	19.66		0
	8	0	20.36	20.14	19.92	0-1	0
	8	4	20.51	20.12	19.93		0
	8	7	20.32	20.10	19.84		0
	15	0	20.29	20.02	19.87		0
16QAM	1	0	20.31	20.36	20.16	0-1	0
	1	7	20.32	20.30	19.98		0
	1	14	20.38	20.04	19.90		0
	8	0	20.38	20.17	19.95	0-2	0
	8	4	20.35	20.11	19.95		0
	8	7	20.39	20.13	19.94		0
	15	0	20.40	20.09	19.93		0
64QAM	1	0	20.36	20.35	20.06	0-2	0
	1	7	20.39	20.19	20.19		0
	1	14	20.39	20.18	19.93		0
	8	0	20.35	20.13	19.86	0-3	0
	8	4	20.37	20.15	19.98		0
	8	7	20.36	20.15	19.92		0
	15	0	20.36	20.08	19.95		0
256QAM	1	0	20.00	19.76	19.65	0-5	1
	1	7	19.99	19.80	19.62		1
	1	14	19.96	19.72	19.58		1
	8	0	19.93	19.85	19.62		1
	8	4	19.97	19.78	19.61		1
	8	7	19.99	19.76	19.58		1
	15	0	19.98	19.72	19.63		1

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 30 of 426

Table H-60
LTE Band 5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 5 (Cell) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20407 (824.7 MHz)	20525 (836.5 MHz)	20643 (848.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	20.25	20.00	19.86	0	0	
	1	2	20.16	19.98	19.85		0	
	1	5	20.22	20.08	19.82		0	
	3	0	20.28	19.94	19.73		0	
	3	2	20.45	19.90	19.81		0	
	3	3	20.19	20.01	19.67		0	
16QAM	6	0	20.39	20.12	19.85	0-1	0	
	1	0	20.38	20.29	20.02	0-1	0	
	1	2	20.39	20.23	20.01		0	
	1	5	20.33	20.16	20.05		0	
	3	0	20.38	20.16	19.89		0	
	3	2	20.28	20.19	19.89		0	
64QAM	3	3	20.41	20.08	19.91		0-2	0
	6	0	20.37	20.10	20.01	0		
	1	0	20.40	20.18	20.02	0		
	1	2	20.35	20.04	19.95	0		
	1	5	20.39	20.19	19.99	0		
	3	0	20.54	20.29	20.07	0		
256QAM	3	2	20.41	20.23	20.19	0-2	0	
	3	3	20.57	20.25	19.96		0	
	6	0	20.37	19.99	20.01		0	
	1	0	20.00	19.50	19.55		0-3	1
	1	2	19.96	19.42	19.65			1
	1	5	19.99	19.49	19.67			1
3	0	19.56	19.46	19.59	0-5	1		
3	2	19.70	19.51	19.59		1		
3	3	19.98	19.52	19.53		1		
6	0	19.96	19.48	19.57		1		

H.1.13 LTE Band 66 Antenna B

Table H-61
LTE Band 66 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.47	23.42	23.33	0	0
	1	36	23.43	23.30	23.21		0
	1	74	23.37	23.33	23.27		0
	36	0	22.24	22.24	22.34	0-1	1
	36	18	22.36	22.32	22.34		1
	36	37	22.33	22.27	22.38		1
	75	0	22.30	22.26	22.38		1
16QAM	1	0	22.59	22.65	22.40	0-1	1
	1	36	22.57	22.58	22.65		1
	1	74	22.54	22.41	22.71		1
	36	0	21.39	21.34	21.47	0-2	2
	36	18	21.45	21.43	21.49		2
	36	37	21.44	21.43	21.49		2
	75	0	21.42	21.40	21.51		2
64QAM	1	0	21.67	21.76	21.40	0-2	2
	1	36	21.64	21.76	21.76		2
	1	74	21.53	21.58	21.70		2
	36	0	20.39	20.37	20.48	0-3	3
	36	18	20.46	20.45	20.47		3
	36	37	20.46	20.38	20.50		3
	75	0	20.42	20.39	20.53		3
256QAM	1	0	18.57	18.56	18.45	0-5	5
	1	36	18.51	18.53	18.70		5
	1	74	18.47	18.40	18.50		5
	36	0	18.34	18.32	18.46		5
	36	18	18.42	18.41	18.43		5
	36	37	18.42	18.40	18.47		5
	75	0	18.40	18.40	18.47		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 31 of 426

Table H-62
LTE Band 66 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.46	23.27	23.26	0	0
	1	25	23.61	23.33	23.24		0
	1	49	23.61	23.30	23.34		0
	25	0	22.27	22.25	22.36	0-1	1
	25	12	22.37	22.34	22.45		1
	25	25	22.33	22.31	22.44		1
	50	0	22.35	22.30	22.44		1
16QAM	1	0	22.59	22.50	22.52	0-1	1
	1	25	22.59	22.47	22.52		1
	1	49	22.53	22.38	22.54		1
	25	0	21.32	21.27	21.38	0-2	2
	25	12	21.42	21.38	21.48		2
	25	25	21.36	21.36	21.44		2
	50	0	21.34	21.31	21.43		2
64QAM	1	0	21.56	21.62	21.64	0-2	2
	1	25	21.56	21.52	21.70		2
	1	49	21.43	21.51	21.52		2
	25	0	20.26	20.26	20.38	0-3	3
	25	12	20.37	20.35	20.46		3
	25	25	20.33	20.35	20.44		3
	50	0	20.33	20.33	20.47		3
256QAM	1	0	18.48	18.31	18.47	0-5	5
	1	25	18.46	18.46	18.62		5
	1	49	18.29	18.33	18.51		5
	25	0	18.24	18.26	18.38		5
	25	12	18.36	18.37	18.48		5
	25	25	18.33	18.34	18.44		5
	50	0	18.31	18.29	18.42		5

Table H-63
LTE Band 66 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.47	23.26	23.45	0	0
	1	12	23.40	23.29	23.44		0
	1	24	23.46	23.24	23.44		0
	12	0	22.36	22.26	22.38	0-1	1
	12	6	22.41	22.36	22.50		1
	12	13	22.34	22.31	22.44		1
	25	0	22.35	22.30	22.43		1
16QAM	1	0	22.63	22.47	22.88	0-1	1
	1	12	22.65	22.59	22.89		1
	1	24	22.66	22.57	22.83		1
	12	0	21.40	21.33	21.42	0-2	2
	12	6	21.44	21.40	21.56		2
	12	13	21.37	21.36	21.47		2
	25	0	21.34	21.32	21.47		2
64QAM	1	0	21.62	21.46	21.63	0-2	2
	1	12	21.62	21.63	21.74		2
	1	24	21.62	21.54	21.71		2
	12	0	20.35	20.29	20.38	0-3	3
	12	6	20.44	20.41	20.55		3
	12	13	20.37	20.32	20.46		3
	25	0	20.34	20.35	20.47		3
256QAM	1	0	18.35	18.39	18.53	0-5	5
	1	12	18.58	18.53	18.64		5
	1	24	18.49	18.50	18.62		5
	12	0	18.37	18.25	18.36		5
	12	6	18.41	18.34	18.46		5
	12	13	18.33	18.32	18.42		5
	25	0	18.34	18.29	18.44		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 32 of 426

Table H-64
LTE Band 66 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.24	23.20	23.36	0	0
	1	7	23.50	23.38	23.54		0
	1	14	23.34	23.27	23.32		0
	8	0	22.35	22.27	22.41	0-1	1
	8	4	22.39	22.34	22.48		1
	8	7	22.33	22.33	22.48		1
	15	0	22.37	22.32	22.45		1
16QAM	1	0	22.57	22.40	22.67	0-1	1
	1	7	22.76	22.62	22.78		1
	1	14	22.57	22.44	22.65		1
	8	0	21.47	21.31	21.47	0-2	2
	8	4	21.47	21.43	21.54		2
	8	7	21.43	21.40	21.54		2
	15	0	21.39	21.32	21.46		2
64QAM	1	0	21.41	21.49	21.62	0-2	2
	1	7	21.63	21.64	21.83		2
	1	14	21.38	21.51	21.70		2
	8	0	20.39	20.29	20.44	0-3	3
	8	4	20.43	20.41	20.55		3
	8	7	20.35	20.33	20.50		3
	15	0	20.36	20.36	20.47		3
256QAM	1	0	18.35	18.31	18.42	0-5	5
	1	7	18.54	18.52	18.60		5
	1	14	18.44	18.38	18.43		5
	8	0	18.35	18.29	18.34		5
	8	4	18.38	18.39	18.50		5
	8	7	18.31	18.31	18.51		5
	15	0	18.37	18.34	18.46		5

Table H-65
LTE Band 66 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.30	23.22	23.44	0	0
	1	2	23.26	23.20	23.34		0
	1	5	23.29	23.22	23.42		0
	3	0	23.22	23.12	23.31		0
	3	2	23.25	23.12	23.26		0
	3	3	23.19	23.12	23.32		0
	6	0	22.25	22.22	22.38	0-1	1
16QAM	1	0	22.43	22.46	22.58	0-1	1
	1	2	22.35	22.42	22.55		1
	1	5	22.38	22.48	22.59		1
	3	0	22.48	22.38	22.61		1
	3	2	22.47	22.36	22.58		1
	3	3	22.51	22.40	22.63		1
	6	0	21.42	21.37	21.53	0-2	2
64QAM	1	0	21.49	21.59	21.73	0-2	2
	1	2	21.44	21.66	21.77		2
	1	5	21.54	21.64	21.71		2
	3	0	21.45	21.53	21.58		2
	3	2	21.38	21.42	21.50		2
	3	3	21.49	21.44	21.52		2
	6	0	20.33	20.33	20.47	0-3	3
256QAM	1	0	18.52	18.41	18.54	0-5	5
	1	2	18.40	18.38	18.53		5
	1	5	18.43	18.32	18.59		5
	3	0	18.37	18.34	18.57		5
	3	2	18.38	18.34	18.53		5
	3	3	18.36	18.37	18.45		5
	6	0	18.23	18.32	18.41	5	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 33 of 426

Table H-66
LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.68	18.36	18.98	0	0
	1	36	18.92	18.32	18.61		0
	1	74	18.80	18.40	18.83		0
	36	0	18.50	18.53	18.58	0-1	0
	36	18	18.65	18.66	18.67		0
	36	37	18.67	18.59	18.78		0
	75	0	18.64	18.56	18.67		0
16QAM	1	0	18.58	18.67	18.85	0-1	0
	1	36	18.73	18.68	18.81		0
	1	74	18.71	18.68	18.84		0
	36	0	18.62	18.53	18.66	0-2	0
	36	18	18.59	18.59	18.66		0
	36	37	18.56	18.61	18.74		0
	75	0	18.62	18.57	18.72		0
64QAM	1	0	18.75	18.93	18.82	0-2	0
	1	36	18.67	18.64	18.86		0
	1	74	18.76	18.67	18.90		0
	36	0	18.53	18.56	18.52	0-3	0
	36	18	18.64	18.59	18.66		0
	36	37	18.66	18.69	18.65		0
	75	0	18.59	18.60	18.66		0
256QAM	1	0	18.56	18.46	18.80	0-5	0
	1	36	18.80	18.93	18.91		0
	1	74	18.61	18.70	18.81		0
	36	0	18.53	18.47	18.66		0
	36	18	18.73	18.67	18.73		0
	36	37	18.67	18.64	18.76		0
	75	0	18.60	18.63	18.65		0

Table H-67
LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.39	18.37	18.79	0	0
	1	25	18.60	18.39	18.69		0
	1	49	18.63	18.38	18.57		0
	25	0	18.56	18.53	18.70	0-1	0
	25	12	18.62	18.69	18.71		0
	25	25	18.68	18.63	18.71		0
	50	0	18.61	18.60	18.67		0
16QAM	1	0	18.67	18.94	18.83	0-1	0
	1	25	18.76	18.68	18.74		0
	1	49	18.80	18.72	18.87		0
	25	0	18.55	18.56	18.73	0-2	0
	25	12	18.70	18.69	18.73		0
	25	25	18.70	18.73	18.71		0
	50	0	18.68	18.55	18.68		0
64QAM	1	0	18.67	18.69	18.86	0-2	0
	1	25	18.84	18.76	18.90		0
	1	49	18.65	18.79	18.79		0
	25	0	18.53	18.52	18.69	0-3	0
	25	12	18.69	18.65	18.72		0
	25	25	18.64	18.65	18.71		0
	50	0	18.61	18.74	18.71		0
256QAM	1	0	18.63	18.70	18.73	0-5	0
	1	25	18.71	18.81	18.78		0
	1	49	18.77	18.69	18.81		0
	25	0	18.54	18.59	18.68		0
	25	12	18.62	18.61	18.73		0
	25	25	18.74	18.64	18.80		0
	50	0	18.69	18.63	18.72		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 34 of 426

Table H-68

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.60	18.44	18.63	0	0
	1	12	18.49	18.45	18.82		0
	1	24	18.62	18.56	18.76		0
	12	0	18.69	18.61	18.65	0-1	0
	12	6	18.66	18.70	18.70		0
	12	13	18.64	18.61	18.72		0
	25	0	18.57	18.59	18.57		0
16QAM	1	0	18.55	18.82	18.81	0-1	0
	1	12	18.78	18.71	18.83		0
	1	24	18.70	18.70	18.73		0
	12	0	18.68	18.62	18.65	0-2	0
	12	6	18.74	18.80	18.71		0
	12	13	18.73	18.71	18.72		0
	25	0	18.65	18.70	18.66		0
64QAM	1	0	18.91	18.63	18.61	0-2	0
	1	12	18.70	18.77	18.90		0
	1	24	18.53	18.87	18.85		0
	12	0	18.62	18.54	18.70	0-3	0
	12	6	18.71	18.63	18.68		0
	12	13	18.74	18.63	18.64		0
	25	0	18.64	18.65	18.64		0
256QAM	1	0	18.45	18.73	18.66	0-5	0
	1	12	18.56	18.80	18.95		0
	1	24	18.65	18.70	18.86		0
	12	0	18.65	18.56	18.72		0
	12	6	18.76	18.70	18.68		0
	12	13	18.72	18.60	18.73		0
	25	0	18.67	18.65	18.61		0

MHz Bandwidth

Table H-69

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 3

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.42	18.45	18.69	0	0
	1	7	18.53	18.42	18.81		0
	1	14	18.51	18.54	18.63		0
	8	0	18.62	18.59	18.59	0-1	0
	8	4	18.68	18.63	18.68		0
	8	7	18.66	18.57	18.70		0
	15	0	18.64	18.71	18.60		0
16QAM	1	0	18.67	18.81	18.94	0-1	0
	1	7	18.84	18.97	18.73		0
	1	14	18.66	18.68	18.81		0
	8	0	18.60	18.53	18.68	0-2	0
	8	4	18.66	18.74	18.72		0
	8	7	18.68	18.72	18.79		0
	15	0	18.58	18.67	18.68		0
64QAM	1	0	18.79	18.64	18.71	0-2	0
	1	7	18.95	18.77	18.88		0
	1	14	18.65	18.73	18.90		0
	8	0	18.62	18.60	18.72	0-3	0
	8	4	18.71	18.69	18.73		0
	8	7	18.69	18.60	18.67		0
	15	0	18.67	18.65	18.56		0
256QAM	1	0	18.54	18.40	18.64	0-5	0
	1	7	18.70	18.76	18.75		0
	1	14	18.60	18.57	18.72		0
	8	0	18.59	18.50	18.72		0
	8	4	18.69	18.73	18.80		0
	8	7	18.69	18.60	18.77		0
	15	0	18.62	18.61	18.62		0

MHz Bandwidth

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 35 of 426

Table H-70

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) –

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.23	18.28	18.35	0	0
	1	2	18.38	18.18	18.24		0
	1	5	18.22	18.35	18.36		0
	3	0	18.36	18.28	18.28		0
	3	2	18.19	18.18	18.16		0
	3	3	18.19	18.27	18.31		0
	6	0	18.19	18.22	18.31		0-1
16QAM	1	0	18.39	18.65	18.53	0-1	0
	1	2	18.30	18.37	18.50		0
	1	5	18.38	18.53	18.43		0
	3	0	18.35	18.48	18.69		0
	3	2	18.31	18.43	18.51		0
	3	3	18.32	18.37	18.51		0
	6	0	18.32	18.43	18.43		0-2
64QAM	1	0	18.38	18.55	18.62	0-2	0
	1	2	18.39	18.55	18.80		0
	1	5	18.59	18.50	18.45		0
	3	0	18.42	18.39	18.50		0
	3	2	18.33	18.33	18.45		0
	3	3	18.38	18.57	18.58		0
	6	0	18.38	18.36	18.43		0-3
256QAM	1	0	18.36	18.52	18.56	0-5	0
	1	2	18.28	18.40	18.42		0
	1	5	18.50	18.35	18.55		0
	3	0	18.44	18.44	18.47		0
	3	2	18.49	18.43	18.45		0
	3	3	18.39	18.57	18.38		0
	6	0	18.33	18.21	18.49		0

Table H-71

LTE Band 66 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.18	11.25	11.33	0	0
	1	36	11.31	11.01	11.29		0
	1	74	11.16	11.14	11.43	0-1	0
	36	0	11.26	10.96	11.31		0
	36	18	11.35	11.14	11.40		0
	36	37	11.33	11.18	11.41		0
75	0	11.30	11.16	11.31	0		
16QAM	1	0	11.34	11.35	11.52	0-1	0
	1	36	11.42	11.39	11.78		0
	1	74	11.44	11.32	11.49	0	
	36	0	11.32	11.07	11.34	0-2	0
	36	18	11.32	11.10	11.32		0
	36	37	11.33	11.20	11.44		0
75	0	11.38	11.18	11.35	0		
64QAM	1	0	11.14	11.06	11.31	0-2	0
	1	36	11.27	11.21	11.40		0
	1	74	11.21	11.18	11.57	0-3	0
	36	0	11.11	10.93	11.17		0
	36	18	11.19	11.03	11.28		0
	36	37	11.20	10.96	11.37		0
75	0	11.13	11.00	11.36	0		
256QAM	1	0	11.12	11.04	11.31	0-5	0
	1	36	11.31	11.13	11.36		0
	1	74	11.14	11.20	11.49		0
	36	0	10.99	10.94	11.20		0
	36	18	11.16	11.06	11.18		0
	36	37	11.15	11.03	11.39		0
75	0	11.14	11.06	11.29	0		

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 36 of 426

Table H-72

LTE Band 66 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.16	11.15	11.38	0	0
	1	25	11.33	11.12	11.32		0
	1	49	11.32	11.20	11.51		0
	25	0	11.34	11.09	11.36	0-1	0
	25	12	11.34	11.21	11.41		0
	25	25	11.40	11.18	11.50		0
	50	0	11.30	11.17	11.37		0
16QAM	1	0	11.32	11.37	11.41	0-1	0
	1	25	11.49	11.24	11.69		0
	1	49	11.35	11.30	11.55		0
	25	0	11.25	11.14	11.40	0-2	0
	25	12	11.40	11.22	11.42		0
	25	25	11.35	11.21	11.44		0
	50	0	11.34	11.20	11.50		0
64QAM	1	0	11.21	11.08	11.41	0-2	0
	1	25	11.34	11.14	11.70		0
	1	49	11.29	11.10	11.40		0
	25	0	11.13	10.96	11.31	0-3	0
	25	12	11.24	11.00	11.38		0
	25	25	11.23	10.96	11.47		0
	50	0	11.22	10.95	11.40		0
256QAM	1	0	11.05	11.01	11.33	0-5	0
	1	25	11.26	11.24	11.53		0
	1	49	11.17	11.12	11.45		0
	25	0	11.11	10.97	11.25		0
	25	12	11.23	11.07	11.36		0
	25	25	11.27	11.02	11.46		0
	50	0	11.14	11.07	11.37		0

Table H-73

LTE Band 66 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.41	11.18	11.32	0	0
	1	12	11.34	11.06	11.46		0
	1	24	11.32	11.06	11.37		0
	12	0	11.37	11.17	11.39	0-1	0
	12	6	11.39	11.22	11.53		0
	12	13	11.35	11.17	11.47		0
	25	0	11.29	11.17	11.36		0
16QAM	1	0	11.38	11.35	11.65	0-1	0
	1	12	11.47	11.63	11.68		0
	1	24	11.49	11.40	11.66		0
	12	0	11.38	11.21	11.36	0-2	0
	12	6	11.49	11.28	11.51		0
	12	13	11.42	11.22	11.48		0
	25	0	11.39	11.18	11.44		0
64QAM	1	0	11.25	11.14	11.61	0-2	0
	1	12	11.40	11.27	11.72		0
	1	24	11.36	11.27	11.51		0
	12	0	11.19	10.92	11.33	0-3	0
	12	6	11.31	11.09	11.42		0
	12	13	11.28	11.05	11.40		0
	25	0	11.22	11.05	11.42		0
256QAM	1	0	11.14	10.92	11.39	0-5	0
	1	12	11.25	11.08	11.44		0
	1	24	11.31	11.21	11.64		0
	12	0	11.22	10.92	11.32		0
	12	6	11.25	11.03	11.44		0
	12	13	11.25	11.05	11.42		0
	25	0	11.16	11.03	11.42		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 37 of 426

Table H-74
LTE Band 66 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.22	11.06	11.38	0	0
	1	7	11.34	11.14	11.40		0
	1	14	11.29	11.09	11.41		0
	8	0	11.34	11.19	11.35	0-1	0
	8	4	11.30	11.21	11.51		0
	8	7	11.35	11.18	11.45		0
	15	0	11.32	11.17	11.50		0
16QAM	1	0	11.37	11.28	11.59	0-1	0
	1	7	11.54	11.46	11.74		0
	1	14	11.44	11.37	11.55		0
	8	0	11.36	11.31	11.49	0-2	0
	8	4	11.41	11.28	11.51		0
	8	7	11.39	11.20	11.44		0
	15	0	11.35	11.15	11.47		0
64QAM	1	0	11.26	10.99	11.50	0-2	0
	1	7	11.44	11.22	11.62		0
	1	14	11.25	11.11	11.45		0
	8	0	11.20	10.90	11.31	0-3	0
	8	4	11.35	11.11	11.49		0
	8	7	11.20	11.08	11.41		0
	15	0	11.14	11.09	11.36		0
256QAM	1	0	11.11	10.89	11.26	0-5	0
	1	7	11.24	11.19	11.57		0
	1	14	11.29	11.05	11.43		0
	8	0	11.18	10.95	11.30	0-5	0
	8	4	11.27	11.09	11.48		0
	8	7	11.19	11.10	11.33		0
	15	0	11.24	11.06	11.27		0

Table H-75
LTE Band 66 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.32	11.09	11.35	0	0
	1	2	11.16	11.04	11.47		0
	1	5	11.28	11.08	11.43		0
	3	0	11.13	11.03	11.38		0
	3	2	11.18	10.98	11.37		0
	3	3	11.14	11.03	11.45		0
6	0	11.22	11.05	11.50	0-1	0	
16QAM	1	0	11.62	11.31	11.62	0-1	0
	1	2	11.51	11.20	11.70		0
	1	5	11.55	11.53	11.57		0
	3	0	11.30	11.30	11.66		0
	3	2	11.28	11.10	11.63		0
	3	3	11.32	11.24	11.52		0
6	0	11.39	11.24	11.37	0-2	0	
1	0	11.24	11.22	11.54		0	
64QAM	1	2	11.29	11.11	11.47	0-2	0
	1	5	11.54	11.15	11.50		0
	3	0	11.29	11.16	11.50		0
	3	2	11.28	11.20	11.48		0
	3	3	11.14	11.13	11.44		0
	6	0	11.14	10.97	11.40		0-3
256QAM	1	0	11.40	11.42	11.56	0-5	0
	1	2	11.24	11.12	11.50		0
	1	5	11.38	11.16	11.44		0
	3	0	11.23	11.05	11.44		0
	3	2	11.29	11.21	11.44		0
	3	3	11.23	11.03	11.46		0
6	0	11.23	10.95	11.31		0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 38 of 426

H.1.14 LTE Band 66 Antenna G

Table H-76
LTE Band 66 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.07	20.64	20.57	0	0
	1	36	21.17	20.50	20.81		0
	1	74	20.76	20.69	20.81		0
	36	0	20.96	20.68	20.72	0-1	0
	36	18	20.91	20.72	20.78		0
	36	37	20.85	20.56	20.73		0
	75	0	20.92	20.64	20.74		0
16QAM	1	0	21.26	20.82	20.93	0-1	0
	1	36	21.40	21.01	20.83		0
	1	74	20.92	20.87	21.04		0
	36	0	20.97	20.71	20.70	0-2	0
	36	18	21.08	20.68	20.79		0
	36	37	20.93	20.65	20.74		0
	75	0	20.95	20.68	20.83		0
64QAM	1	0	21.26	20.89	20.67	0-2	0
	1	36	21.09	20.88	20.91		0
	1	74	21.14	20.84	20.84		0
	36	0	20.96	20.58	20.79	0-3	0
	36	18	21.13	20.66	20.70		0
	36	37	20.97	20.62	20.77		0
	75	0	20.98	20.71	20.83		0
256QAM	1	0	19.31	19.02	19.03	0-5	1.5
	1	36	19.33	18.99	19.17		1.5
	1	74	19.27	18.90	19.09		1.5
	36	0	19.28	18.84	18.93		1.5
	36	18	19.29	18.96	19.07		1.5
	36	37	19.16	18.88	19.01		1.5
	75	0	19.20	18.91	18.85		1.5

Table H-77
LTE Band 66 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.98	20.49	20.62	0	0
	1	25	20.94	20.65	20.74		0
	1	49	21.15	20.60	20.63		0
	25	0	21.12	20.67	20.72	0-1	0
	25	12	21.11	20.68	20.87		0
	25	25	20.96	20.71	20.90		0
16QAM	50	0	21.10	20.67	20.80	0-1	0
	1	0	21.22	20.87	20.90		0
	1	25	21.30	20.84	20.93		0
	1	49	21.23	20.81	20.96	0-2	0
	25	0	21.07	20.68	20.80		0
	25	12	21.19	20.70	20.83		0
64QAM	25	25	21.11	20.68	20.99	0-2	0
	50	0	21.11	20.78	20.85		0
	1	0	21.26	20.82	20.63		0
	1	25	21.36	20.86	21.00	0-2	0
	1	49	21.12	20.92	20.77		0
	25	0	21.10	20.65	20.75	0-3	0
25	12	21.16	20.60	20.80	0		
25	25	21.05	20.47	20.90	0		
256QAM	50	0	21.15	20.90	20.77	0-5	0
	1	0	19.34	19.06	18.84		1.5
	1	25	19.45	19.06	19.08		1.5
	1	49	19.35	19.09	18.91		1.5
	25	0	19.25	19.25	18.99		1.5
	25	12	19.40	18.84	19.09		1.5
	25	25	19.28	18.82	19.04		1.5
	50	0	19.37	18.91	19.01		1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 39 of 426

Table H-78
LTE Band 66 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.06	20.69	20.70	0	0
	1	12	21.23	20.73	20.87		0
	1	24	20.94	20.51	20.68		0
	12	0	21.12	20.65	20.80	0-1	0
	12	6	21.13	20.67	20.88		0
	12	13	21.05	20.59	20.78		0
	25	0	21.19	20.71	20.83		0
16QAM	1	0	21.40	20.80	20.88	0-1	0
	1	12	21.45	21.04	21.03		0
	1	24	21.24	20.66	20.88		0
	12	0	21.10	20.73	20.76	0-2	0
	12	6	21.15	20.80	20.68		0
	12	13	21.16	20.65	21.11		0
	25	0	21.19	20.66	21.20		0
64QAM	1	0	21.28	20.76	20.93	0-2	0
	1	12	21.38	20.95	20.94		0
	1	24	21.01	20.74	21.23		0
	12	0	21.17	20.69	20.90	0-3	0
	12	6	21.30	20.66	20.89		0
	12	13	21.17	20.69	20.78		0
	25	0	21.19	20.56	20.86		0
256QAM	1	0	19.52	18.79	19.06	0-5	1.5
	1	12	19.54	19.13	19.22		1.5
	1	24	19.31	18.84	19.11		1.5
	12	0	19.48	18.90	18.98		1.5
	12	6	19.48	19.04	19.03		1.5
	12	13	19.31	18.82	19.05		1.5
	25	0	19.40	18.91	19.02		1.5

Table H-79
LTE Band 66 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.03	20.50	20.70	0	0
	1	7	20.99	20.59	20.71		0
	1	14	20.90	20.60	20.73		0
	8	0	21.15	20.64	20.76	0-1	0
	8	4	21.23	20.72	20.87		0
	8	7	21.05	20.57	20.81		0
	15	0	21.05	20.66	20.83		0
16QAM	1	0	21.23	20.86	20.71	0-1	0
	1	7	21.24	21.00	21.00		0
	1	14	21.24	20.76	20.97		0
	8	0	21.26	20.76	20.67	0-2	0
	8	4	21.22	20.75	21.20		0
	8	7	21.08	20.64	20.82		0
	15	0	21.04	20.79	20.85		0
64QAM	1	0	21.19	20.73	20.89	0-2	0
	1	7	21.54	20.83	20.87		0
	1	14	21.05	20.61	20.81		0
	8	0	21.20	20.80	20.84	0-3	0
	8	4	21.30	20.76	20.91		0
	8	7	21.15	20.49	20.82		0
	15	0	21.12	20.89	20.85		0
256QAM	1	0	19.43	19.01	18.98	0-5	1.5
	1	7	19.57	19.09	19.09		1.5
	1	14	19.31	18.97	19.05		1.5
	8	0	19.48	18.95	19.07		1.5
	8	4	19.53	18.94	19.06		1.5
	8	7	19.42	18.82	19.12		1.5
	15	0	19.38	18.88	19.04		1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 40 of 426

Table H-80
LTE Band 66 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.07	20.76	20.75	0	0
	1	2	20.94	20.64	20.80		0
	1	5	21.05	20.62	20.78		0
	3	0	21.04	20.57	20.60		0
	3	2	20.97	20.54	20.67		0
	3	3	21.04	20.65	20.75		0
	6	0	21.11	20.68	20.79		0
16QAM	1	0	21.16	20.50	20.85	0-1	0
	1	2	21.25	20.95	20.93		0
	1	5	21.31	20.69	20.84		0
	3	0	21.05	20.76	20.74		0
	3	2	21.16	20.70	20.76		0
	3	3	21.14	20.62	20.85		0
	6	0	21.26	20.75	20.99		0
64QAM	1	0	21.36	20.99	21.09	0-2	0
	1	2	21.15	20.83	20.71		0
	1	5	21.29	20.60	20.90		0
	3	0	21.05	20.78	20.87		0
	3	2	21.22	20.79	20.73		0
	3	3	21.31	20.97	20.83		0
	6	0	21.26	20.92	20.79		0
256QAM	1	0	19.39	18.98	19.09	0-3	1.5
	1	2	19.39	18.99	19.27		1.5
	1	5	19.22	18.95	19.23		1.5
	3	0	19.38	18.82	19.01		1.5
	3	2	19.36	18.94	19.05		1.5
	3	3	19.50	18.78	19.01		1.5
	6	0	19.41	18.87	19.00		1.5

Table H-81
LTE Band 66 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.59	19.24	19.04	0	0
	1	36	19.37	19.01	19.29		0
	1	74	19.50	19.26	19.32		0
	36	0	19.53	19.10	19.14	0-1	0
	36	18	19.48	19.17	19.25		0
	36	37	19.47	19.20	19.29		0
	75	0	19.52	19.20	19.29		0
16QAM	1	0	19.62	19.41	19.11	0-1	0
	1	36	19.61	19.37	19.29		0
	1	74	19.59	19.27	19.46		0
	36	0	19.47	19.21	19.19	0-2	0
	36	18	19.57	19.23	19.33		0
	36	37	19.46	19.19	19.21		0
	75	0	19.50	19.20	19.27		0
64QAM	1	0	19.78	19.29	19.36	0-2	0
	1	36	19.73	19.40	19.36		0
	1	74	19.45	19.34	19.32		0
	36	0	19.55	19.10	19.21	0-3	0
	36	18	19.55	19.23	19.27		0
	36	37	19.48	19.14	19.18		0
	75	0	19.40	19.21	19.28		0
256QAM	1	0	19.38	18.98	19.08	0-5	0
	1	36	19.41	19.05	19.07		0
	1	74	19.30	18.74	18.96		0
	36	0	19.35	18.91	18.91		0
	36	18	19.27	18.87	19.01		0
	36	37	19.19	18.86	18.95		0
	75	0	19.20	18.90	18.99		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 41 of 426

Table H-82
LTE Band 66 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	19.73	18.93	19.17	0	0	
	1	25	19.50	19.17	19.26		0	
	1	49	19.35	19.09	19.26		0	
	25	0	19.56	19.24	19.30	0-1	0	
	25	12	19.60	19.11	19.31		0	
	25	25	19.43	19.16	19.28		0	
16QAM	50	0	19.56	19.19	19.28	0-1	0	
	1	0	19.73	19.31	19.33		0-1	0
	1	25	19.89	19.54	19.52			0
	1	49	19.78	19.23	19.37	0-2		0
	25	0	19.63	19.07	19.29		0	
	25	12	19.69	19.23	19.31		0	
64QAM	25	25	19.54	19.17	19.38	0-2	0	
	50	0	19.64	19.26	19.31		0	
	1	0	19.53	19.27	19.24		0-2	0
	1	25	19.71	19.32	19.52	0		
	1	49	19.64	19.22	19.20	0-3		0
	25	0	19.57	19.22	19.21		0	
256QAM	25	12	19.70	19.18	19.29		0-3	0
	25	25	19.60	19.16	19.31	0		
	50	0	19.61	19.22	19.29	0-5		0
	1	0	19.40	18.86	18.99		0	
	1	25	19.33	18.90	19.05		0	
	1	49	19.43	19.04	19.10	0		
256QAM	25	0	19.35	18.96	18.91	0-5	0	
	25	12	19.30	18.94	19.00		0	
	25	25	19.26	18.88	19.09		0	
	50	0	19.36	18.97	18.97		0	

Table H-83
LTE Band 66 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	19.45	19.10	19.07	0	0	
	1	12	19.60	19.30	19.15		0	
	1	24	19.66	19.13	19.18		0	
	12	0	19.66	19.19	19.27	0-1	0	
	12	6	19.67	19.22	19.38		0	
	12	13	19.57	19.15	19.30		0	
16QAM	25	0	19.68	19.16	19.35	0-1	0	
	1	0	19.70	19.40	19.32		0-1	0
	1	12	19.75	19.54	19.50			0
	1	24	19.81	19.36	19.29	0-2		0
	12	0	19.69	19.23	19.32		0	
	12	6	19.70	19.26	19.42		0	
64QAM	12	13	19.65	19.06	19.41	0-2	0	
	25	0	19.63	19.18	19.34		0-3	0
	1	0	19.73	19.30	19.41			0
	1	12	19.73	19.38	19.40	0-2		0
	1	24	19.56	19.15	19.29		0	
	12	0	19.69	19.25	19.31		0-3	0
256QAM	12	6	19.74	19.24	19.31	0-3		0
	12	13	19.63	19.15	19.31			0-5
	25	0	19.64	19.15	19.36		0	
	1	0	19.48	18.96	19.06	0-5	0	
	1	12	19.60	19.07	19.15		0	
	1	24	19.44	18.94	18.85		0	
12	0	19.40	18.88	19.01	0			
12	6	19.54	18.99	19.10	0			
256QAM	12	13	19.37	18.92	18.98	0-5	0	
	25	0	19.44	18.94	18.98		0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 42 of 426

Table H-84
LTE Band 66 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.54	18.90	19.19	0	0
	1	7	19.55	19.17	19.14		0
	1	14	19.53	19.01	19.12		0
	8	0	19.62	19.14	19.20	0-1	0
	8	4	19.59	19.31	19.35		0
	8	7	19.62	19.18	19.35		0
	15	0	19.57	19.21	19.32		0
16QAM	1	0	19.77	19.39	19.26	0-1	0
	1	7	19.89	19.45	19.97		0
	1	14	20.05	19.21	19.44		0
	8	0	19.77	19.27	19.26	0-2	0
	8	4	19.76	19.35	19.32		0
	8	7	19.61	19.18	19.43		0
	15	0	19.59	19.25	19.23		0
64QAM	1	0	19.67	19.21	19.48	0-2	0
	1	7	19.88	19.42	19.65		0
	1	14	19.70	19.27	19.33		0
	8	0	19.65	19.15	19.39	0-3	0
	8	4	19.68	19.29	19.38		0
	8	7	19.61	19.09	19.28		0
	15	0	19.63	19.22	19.22		0
256QAM	1	0	19.40	18.74	19.01	0-5	0
	1	7	19.50	19.19	19.16		0
	1	14	19.40	18.67	19.09		0
	8	0	19.42	18.88	19.06		0
	8	4	19.46	18.99	19.05		0
	8	7	19.43	18.92	19.06		0
	15	0	19.25	18.90	19.02		0

Table H-85
LTE Band 66 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.40	19.08	19.15	0	0
	1	2	19.42	19.05	19.23		0
	1	5	19.56	19.12	19.06		0
	3	0	19.66	18.93	19.30		0
	3	2	19.59	19.05	19.08		0
	3	3	19.62	19.21	19.16		0
	6	0	19.56	19.07	19.16	0-1	0
16QAM	1	0	19.79	19.12	19.46	0-1	0
	1	2	20.08	19.26	19.83		0
	1	5	19.69	19.49	19.41		0
	3	0	19.71	19.24	19.34		0
	3	2	19.75	19.12	19.30		0
	3	3	19.74	19.32	19.34		0
	6	0	19.75	19.32	19.34	0-2	0
64QAM	1	0	19.68	19.11	19.37	0-2	0
	1	2	19.82	19.24	19.36		0
	1	5	19.76	19.17	19.37		0
	3	0	19.85	19.14	19.26		0
	3	2	19.95	19.15	19.23		0
	3	3	19.76	19.22	19.46		0
	6	0	19.74	19.20	19.28	0-3	0
256QAM	1	0	19.63	18.94	19.20	0-5	0
	1	2	19.52	19.05	19.07		0
	1	5	19.43	18.92	19.17		0
	3	0	19.36	18.97	19.23		0
	3	2	19.47	18.94	19.04		0
	3	3	19.52	19.03	19.29		0
	6	0	19.42	18.90	18.94	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 43 of 426

Table H-86
LTE Band 66 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 15 MHz Bandwidth

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.21	10.41	10.28	0	0
	1	36	10.70	10.54	10.63		0
	1	74	10.64	10.55	10.44		0
	36	0	10.80	10.36	10.39	0-1	0
	36	18	10.79	10.33	10.44		0
	36	37	10.73	10.36	10.41		0
	75	0	10.72	10.39	10.46		0
16QAM	1	0	10.97	10.85	10.65	0-1	0
	1	36	10.91	10.69	10.74		0
	1	74	10.87	10.57	10.47		0
	36	0	10.82	10.43	10.44	0-2	0
	36	18	10.85	10.38	10.49		0
	36	37	10.70	10.36	10.46		0
	75	0	10.79	10.38	10.48		0
64QAM	1	0	11.21	10.71	10.42	0-2	0
	1	36	11.10	10.57	10.63		0
	1	74	10.78	10.57	10.62		0
	36	0	10.85	10.43	10.39	0-3	0
	36	18	10.81	10.43	10.43		0
	36	37	10.79	10.33	10.38		0
	75	0	10.75	10.42	10.43		0
256QAM	1	0	11.01	10.64	10.53	0-5	0
	1	36	11.14	10.47	10.46		0
	1	74	10.81	10.56	10.50		0
	36	0	10.87	10.40	10.37		0
	36	18	10.87	10.46	10.54		0
	36	37	10.69	10.40	10.49		0
	75	0	10.75	10.42	10.49		0

Table H-87
LTE Band 66 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 10 MHz Bandwidth

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.99	10.31	10.32	0	0
	1	25	11.08	10.34	10.45		0
	1	49	10.80	10.25	10.35		0
	25	0	10.82	10.40	10.46	0-1	0
	25	12	10.82	10.41	10.50		0
	25	25	10.70	10.39	10.41		0
	50	0	10.76	10.46	10.42		0
16QAM	1	0	11.00	10.64	10.54	0-1	0
	1	25	11.08	10.67	10.60		0
	1	49	11.20	10.49	10.56		0
	25	0	10.87	10.43	10.49	0-2	0
	25	12	10.89	10.46	10.52		0
	25	25	10.80	10.41	10.38		0
	50	0	10.82	10.43	10.50		0
64QAM	1	0	11.03	10.67	10.56	0-2	0
	1	25	11.04	10.63	10.67		0
	1	49	11.01	10.51	10.41		0
	25	0	10.88	10.43	10.45	0-3	0
	25	12	10.94	10.46	10.52		0
	25	25	10.77	10.35	10.50		0
	50	0	10.75	10.43	10.48		0
256QAM	1	0	11.04	10.54	10.55	0-5	0
	1	25	11.18	10.60	10.53		0
	1	49	10.76	10.46	10.37		0
	25	0	10.81	10.49	10.44		0
	25	12	10.85	10.43	10.58		0
	25	25	10.80	10.40	10.50		0
	50	0	10.78	10.49	10.49		0

Table H-88
LTE Band 66 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 5 MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.00	10.45	10.39	0	0
	1	12	10.78	10.43	10.41		0
	1	24	10.75	10.32	10.32		0
	12	0	10.85	10.44	10.49	0-1	0
	12	6	10.83	10.47	10.49		0
	12	13	10.78	10.27	10.50		0
	25	0	10.88	10.35	10.50		0
16QAM	1	0	11.27	10.58	10.72	0-1	0
	1	12	11.04	10.76	10.83		0
	1	24	10.93	10.69	10.57		0
	12	0	10.94	10.43	10.48	0-2	0
	12	6	11.01	10.50	10.60		0
	12	13	10.82	10.36	10.50		0
	25	0	10.91	10.36	10.42		0
64QAM	1	0	11.22	10.62	10.57	0-2	0
	1	12	11.09	10.55	10.74		0
	1	24	11.01	10.46	10.50		0
	12	0	10.99	10.44	10.54	0-3	0
	12	6	11.00	10.52	10.51		0
	12	13	10.84	10.41	10.57		0
	25	0	10.93	10.46	10.51		0
256QAM	1	0	11.07	10.56	10.58	0-5	0
	1	12	11.27	10.57	10.63		0
	1	24	10.86	10.40	10.53		0
	12	0	10.97	10.45	10.49		0
	12	6	11.00	10.53	10.62		0
	12	13	10.86	10.34	10.47		0
	25	0	10.95	10.43	10.50		0

Table H-89
LTE Band 66 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.98	10.25	10.36	0	0
	1	7	10.84	10.53	10.55		0
	1	14	10.68	10.31	10.25		0
	8	0	10.89	10.37	10.43	0-1	0
	8	4	10.76	10.38	10.39		0
	8	7	10.77	10.27	10.46		0
	15	0	10.99	10.31	10.50		0
16QAM	1	0	11.06	11.02	10.56	0-1	0
	1	7	11.13	10.56	11.17		0
	1	14	10.97	10.52	10.68		0
	8	0	10.89	10.35	10.53	0-2	0
	8	4	10.84	10.38	10.61		0
	8	7	10.93	10.33	10.47		0
	15	0	10.87	10.34	10.47		0
64QAM	1	0	10.93	10.65	10.47	0-2	0
	1	7	11.06	10.50	10.62		0
	1	14	10.88	10.53	10.49		0
	8	0	10.92	10.41	10.42	0-3	0
	8	4	10.86	10.54	10.49		0
	8	7	10.87	10.40	10.48		0
	15	0	10.86	10.38	10.48		0
256QAM	1	0	11.02	10.62	10.40	0-5	0
	1	7	11.13	10.48	10.67		0
	1	14	10.86	10.43	10.54		0
	8	0	10.95	10.43	10.56		0
	8	4	10.78	10.42	10.58		0
	8	7	10.86	10.35	10.51		0
	15	0	10.89	10.42	10.54		0

Table H-90
LTE Band 66 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.91	10.26	10.28	0	0
	1	2	10.73	10.44	10.42		0
	1	5	10.85	10.36	10.34		0
	3	0	10.82	10.45	10.29		0
	3	2	10.79	10.33	10.32		0
	3	3	10.78	10.22	10.27		0
	6	0	10.74	10.30	10.41		0
16QAM	1	0	11.01	10.62	10.81	0-1	0
	1	2	11.05	10.63	10.56		0
	1	5	11.10	10.42	10.45		0
	3	0	10.94	10.51	10.55		0
	3	2	10.92	10.41	10.42		0
	3	3	10.94	10.35	10.47		0
	6	0	10.92	10.35	10.43		0
64QAM	1	0	11.25	10.63	10.62	0-2	0
	1	2	10.92	10.48	10.47		0
	1	5	11.00	10.55	10.71		0
	3	0	11.04	10.35	10.43		0
	3	2	10.92	10.33	10.48		0
	3	3	11.15	10.35	10.49		0
	6	0	10.99	10.65	10.47		0
256QAM	1	0	11.03	10.89	10.79	0-3	0
	1	2	11.00	10.55	10.42		0
	1	5	11.17	10.51	10.57		0
	3	0	10.89	10.42	10.51		0
	3	2	11.00	10.52	10.62		0
	3	3	10.97	10.41	10.42		0
	6	0	10.80	10.40	10.44		0

Table H-91
LTE Band 66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 15

LTE Band 66 (AWS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132047 (1717.5 MHz)	132322 (1745.0 MHz)	132597 (1772.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.79	17.76	17.53	0	0
	1	36	17.81	17.91	17.62		0
	1	74	17.70	17.56	17.63		0
	36	0	17.66	17.71	17.71	0-1	0
	36	18	17.71	17.77	17.74		0
	36	37	17.70	17.61	17.60		0
	75	0	17.71	17.70	17.70		0
16QAM	1	0	17.78	17.97	17.94	0-1	0
	1	36	17.83	17.82	17.78		0
	1	74	17.83	17.84	17.80		0
	36	0	17.84	17.78	17.67	0-2	0
	36	18	17.72	17.82	17.76		0
	36	37	17.68	17.73	17.62		0
	75	0	17.77	17.82	17.77		0
64QAM	1	0	17.97	17.92	17.75	0-2	0
	1	36	17.87	17.80	17.81		0
	1	74	17.63	17.88	17.83		0
	36	0	17.69	17.80	17.74	0-3	0
	36	18	17.73	17.75	17.68		0
	36	37	17.68	17.76	17.67		0
	75	0	17.73	17.81	17.80		0
256QAM	1	0	17.93	17.95	17.80	0-5	0
	1	36	17.83	17.86	17.73		0
	1	74	17.71	17.84	17.69		0
	36	0	17.79	17.75	17.68		0
	36	18	17.80	17.79	17.77		0
	36	37	17.68	17.77	17.70		0
	75	0	17.74	17.75	17.69		0

MHz Bandwidth

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 46 of 426

Table H-92

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 10

LTE Band 66 (AWS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			132022 (1715.0 MHz)	132322 (1745.0 MHz)	132622 (1775.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.59	17.64	17.54	0	0
	1	25	17.68	17.78	17.70		0
	1	49	17.76	17.64	17.59		0
	25	0	17.73	17.83	17.64	0-1	0
	25	12	17.73	17.71	17.71		0
	25	25	17.80	17.67	17.64		0
	50	0	17.71	17.72	17.70		0
16QAM	1	0	17.98	17.90	17.79	0-1	0
	1	25	17.96	17.88	17.82		0
	1	49	17.91	17.81	17.77		0
	25	0	17.79	17.80	17.74	0-2	0
	25	12	17.81	17.83	17.81		0
	25	25	17.78	17.66	17.66		0
	50	0	17.80	17.77	17.73		0
64QAM	1	0	17.90	17.62	17.80	0-2	0
	1	25	17.97	17.80	18.00		0
	1	49	17.91	17.81	17.81		0
	25	0	17.79	17.73	17.78	0-3	0
	25	12	17.75	17.84	17.77		0
	25	25	17.64	17.70	17.71		0
	50	0	17.69	17.77	17.78		0
256QAM	1	0	17.95	17.84	17.68	0-5	0
	1	25	17.76	17.96	17.88		0
	1	49	17.75	17.82	17.62		0
	25	0	17.71	17.77	17.71		0
	25	12	17.59	17.81	17.78		0
	25	25	17.73	17.75	17.71		0
	50	0	17.73	17.81	17.79		0

MHz Bandwidth

MHz Bandwidth

Table H-93

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 5
MHz Bandwidth

LTE Band 66 (AWS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131997 (1712.5 MHz)	132322 (1745.0 MHz)	132647 (1777.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.90	17.66	17.55	0	0
	1	12	17.85	17.69	17.59		0
	1	24	17.84	17.58	17.57		0
	12	0	17.82	17.80	17.73	0-1	0
	12	6	17.85	17.77	17.74		0
	12	13	17.71	17.74	17.71		0
	25	0	17.77	17.77	17.68		0
16QAM	1	0	17.95	17.70	17.80	0-1	0
	1	12	17.89	17.83	17.95		0
	1	24	17.84	17.94	17.76		0
	12	0	17.87	17.77	17.72	0-2	0
	12	6	17.98	17.82	17.84		0
	12	13	17.84	17.68	17.75		0
	25	0	17.85	17.73	17.72		0
64QAM	1	0	17.84	17.92	17.72	0-2	0
	1	12	17.99	17.84	17.84		0
	1	24	18.00	17.90	17.82		0
	12	0	17.86	17.78	17.75	0-3	0
	12	6	17.89	17.84	17.78		0
	12	13	17.78	17.74	17.75		0
	25	0	17.85	17.74	17.71		0
256QAM	1	0	17.97	17.77	17.87	0-5	0
	1	12	17.79	17.97	17.82		0
	1	24	17.70	17.79	17.74		0
	12	0	17.80	17.75	17.77		0
	12	6	17.85	17.83	17.77		0
	12	13	17.75	17.72	17.76		0
	25	0	17.80	17.81	17.69		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 47 of 426

Table H-94

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 3 MHz Bandwidth

LTE Band 66 (AWS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			131987 (1711.5 MHz)	132322 (1745.0 MHz)	132657 (1778.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.67	17.55	17.50	0	0
	1	7	17.79	17.71	17.57		0
	1	14	17.74	17.56	17.60		0
	8	0	17.86	17.66	17.65	0-1	0
	8	4	17.81	17.72	17.74		0
	8	7	17.80	17.70	17.68		0
	15	0	17.80	17.74	17.72		0
16QAM	1	0	17.78	17.76	17.82	0-1	0
	1	7	17.76	17.87	17.80		0
	1	14	17.93	17.82	17.69		0
	8	0	17.94	17.78	17.76	0-2	0
	8	4	17.96	17.83	17.81		0
	8	7	17.89	17.74	17.73		0
	15	0	17.85	17.81	17.72		0
64QAM	1	0	17.89	17.85	17.84	0-2	0
	1	7	17.75	17.72	17.99		0
	1	14	17.94	17.76	17.76		0
	8	0	17.93	17.86	17.71	0-3	0
	8	4	17.88	17.94	17.80		0
	8	7	17.84	17.70	17.78		0
	15	0	17.73	17.75	17.82		0
256QAM	1	0	17.89	17.86	17.74	0-5	0
	1	7	17.88	17.96	17.77		0
	1	14	17.77	17.72	17.73		0
	8	0	17.93	17.82	17.74		0
	8	4	17.86	17.86	17.77		0
	8	7	17.96	17.69	17.72		0
	15	0	17.82	17.75	17.78		0

Table H-95

LTE Band 66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 1.4 MHz Bandwidth

LTE Band 66 (AWS) 1.4 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			131979 (1710.7 MHz)	132322 (1745.0 MHz)	132665 (1779.3 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	17.80	17.71	17.63	0	0	
	1	2	17.67	17.73	17.58		0	
	1	5	17.82	17.56	17.56		0	
	3	0	17.82	17.59	17.50		0	
	3	2	17.67	17.47	17.60		0	
	3	3	17.76	17.57	17.54		0	
16QAM	6	0	17.75	17.70	17.53	0-1	0	
	1	0	17.80	17.98	17.87	0-1	0	
	1	2	17.78	17.87	17.87		0	
	1	5	17.73	17.81	17.83		0	
	3	0	17.76	17.81	17.74		0	
	3	2	17.80	17.65	17.60		0	
64QAM	3	3	17.87	17.91	17.79		0-2	0
	6	0	17.96	17.86	17.76	0		
	1	0	17.93	17.85	17.70	0		
	1	2	17.91	17.86	17.82	0		
	1	5	17.92	17.91	17.86	0		
	3	0	18.00	17.74	17.60	0		
256QAM	3	2	17.89	17.81	17.73	0-3	0	
	3	3	17.90	17.81	17.65		0	
	6	0	17.90	17.82	17.75		0	
	1	0	18.00	17.83	17.94		0-5	0
	1	2	17.98	17.75	17.77			0
	1	5	17.92	17.89	17.73			0
3	0	17.91	17.83	17.72	0			
256QAM	3	2	17.66	17.77	17.79	0	0	
	3	3	17.95	17.82	17.77		0	
	6	0	17.84	17.78	17.73		0	
	6	0	17.84	17.78	17.73		0	
	6	0	17.84	17.78	17.73		0	
	6	0	17.84	17.78	17.73		0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 48 of 426

H.1.15 LTE Band 25 Antenna B

Table H-96
LTE Band 25 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.02	23.52	23.57	0	0	
	1	36	23.03	23.28	23.65		0	
	1	74	23.12	23.35	23.41		0	
	36	0	22.01	22.22	22.47	0-1	1	
	36	18	22.08	22.23	22.46		1	
	36	37	22.06	22.28	22.51		1	
16QAM	75	0	22.02	22.25	22.50	0-1	1	
	1	0	22.23	22.36	22.56		1	
	1	36	22.26	22.50	22.68		1	
	1	74	22.16	22.55	22.75	0-2	1	
	36	0	21.04	21.23	21.48		2	
	36	18	21.10	21.26	21.49		2	
64QAM	36	37	21.08	21.32	21.55	0-2	2	
	75	0	21.08	21.31	21.53		2	
	1	0	21.37	21.49	21.55	0-2	2	
	1	36	21.35	21.58	21.78		2	
	1	74	21.22	21.61	21.68		2	
	36	0	19.99	20.23	20.47	0-3	3	
36	18	20.10	20.26	20.47	3			
36	37	20.04	20.32	20.52	3			
256QAM	75	0	20.07	20.29	20.55	0-3	3	
	1	0	18.15	18.26	18.52		0-5	5
	1	36	18.26	18.46	18.68			5
	1	74	18.17	18.38	18.61	5		
	36	0	18.00	18.20	18.47	5		
	36	18	18.08	18.26	18.48	5		
36	37	18.05	18.32	18.52	5			
75	0	18.02	18.29	18.51	5			

Table H-97
LTE Band 25 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)			
Conducted Power [dBm]								
QPSK	1	0	23.19	23.17	23.32	0	0	
	1	25	23.21	23.30	23.37		0	
	1	49	23.13	23.22	23.37		0	
	25	0	22.09	22.24	22.46	0-1	1	
	25	12	22.12	22.26	22.50		1	
	25	25	22.05	22.30	22.56		1	
16QAM	50	0	22.06	22.30	22.54	0-1	1	
	1	0	22.40	22.26	22.66		0-1	1
	1	25	22.45	22.45	22.62			1
	1	49	22.31	22.47	22.71	0-2		1
	25	0	21.11	21.28	21.52		2	
	25	12	21.17	21.29	21.55		0-2	2
64QAM	25	25	21.10	21.35	21.58	0-2		2
	50	0	21.07	21.29	21.56			2
	1	0	21.32	21.45	21.74		0-2	2
	1	25	21.25	21.57	21.85	0-2		2
	1	49	21.25	21.49	21.74			0-3
	25	0	20.09	20.26	20.52		0-3	
256QAM	25	12	20.15	20.26	20.56	0-3		
	25	25	20.12	20.34	20.58			0-3
	50	0	20.10	20.33	20.57		0-5	
	1	0	18.21	18.32	18.52	0-5		
	1	25	18.25	18.41	18.70			5
	1	49	18.16	18.35	18.65		5	
25	0	18.09	18.22	18.48	5			
25	12	18.13	18.29	18.50	5			
25	25	18.09	18.32	18.56	5			
256QAM	50	0	18.05	18.32	18.55	0-5	5	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 49 of 426

Table H-98
LTE Band 25 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.31	23.20	23.61	0	0
	1	12	23.20	23.24	23.63		0
	1	24	23.22	23.23	23.65		0
	12	0	22.10	22.22	22.46	0-1	1
	12	6	22.15	22.27	22.55		1
	12	13	22.10	22.31	22.61		1
	25	0	22.11	22.32	22.49		1
16QAM	1	0	22.46	22.48	22.95	0-1	1
	1	12	22.42	22.58	22.99		1
	1	24	22.39	22.55	23.00		1
	12	0	21.18	21.23	21.57	0-2	2
	12	6	21.22	21.34	21.59		2
	12	13	21.21	21.38	21.66		2
	25	0	21.14	21.34	21.53		2
64QAM	1	0	21.36	21.34	21.69	0-2	2
	1	12	21.39	21.54	21.84		2
	1	24	21.28	21.52	21.88		2
	12	0	20.15	20.26	20.52	0-3	3
	12	6	20.17	20.30	20.59		3
	12	13	20.15	20.37	20.64		3
	25	0	20.16	20.33	20.54		3
256QAM	1	0	18.13	18.27	18.58	0-5	5
	1	12	18.27	18.51	18.89		5
	1	24	18.16	18.49	18.73		5
	12	0	18.10	18.25	18.50		5
	12	6	18.19	18.30	18.58		5
	12	13	18.13	18.35	18.60		5
	25	0	18.13	18.31	18.54		5

Table H-99
LTE Band 25 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.02	23.21	23.42	0	0
	1	7	23.18	23.41	23.63		0
	1	14	23.06	23.24	23.50		0
	8	0	22.10	22.25	22.55	0-1	1
	8	4	22.15	22.37	22.66		1
	8	7	22.14	22.36	22.63		1
	15	0	22.12	22.31	22.59		1
16QAM	1	0	22.35	22.29	22.62	0-1	1
	1	7	22.51	22.56	22.98		1
	1	14	22.30	22.48	22.75		1
	8	0	21.21	21.31	21.58	0-2	2
	8	4	21.28	21.46	21.71		2
	8	7	21.25	21.41	21.67		2
	15	0	21.12	21.33	21.62		2
64QAM	1	0	21.16	21.39	21.69	0-2	2
	1	7	21.41	21.63	21.99		2
	1	14	21.23	21.53	21.73		2
	8	0	20.18	20.28	20.56	0-3	3
	8	4	20.21	20.41	20.66		3
	8	7	20.19	20.39	20.66		3
	15	0	20.14	20.38	20.66		3
256QAM	1	0	18.07	18.22	18.49	0-5	5
	1	7	18.34	18.44	18.76		5
	1	14	18.23	18.37	18.67		5
	8	0	18.14	18.23	18.50		5
	8	4	18.19	18.37	18.69		5
	8	7	18.19	18.40	18.63		5
	15	0	18.14	18.32	18.62		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 50 of 426

Table H-100
LTE Band 25 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.05	23.26	23.54	0	0
	1	2	22.92	23.23	23.43		0
	1	5	23.01	23.30	23.48		0
	3	0	22.94	23.23	23.38		0
	3	2	23.02	23.17	23.45		0
	3	3	23.00	23.16	23.42		0
	6	0	22.02	22.18	22.51	0-1	1
16QAM	1	0	22.20	22.60	22.71	0-1	1
	1	2	22.24	22.51	22.69		1
	1	5	22.18	22.59	22.74		1
	3	0	22.21	22.39	22.66		1
	3	2	22.19	22.38	22.68		1
	3	3	22.26	22.36	22.67		1
	6	0	21.17	21.35	21.64	0-2	2
64QAM	1	0	21.37	21.52	21.95	0-2	2
	1	2	21.40	21.38	21.94		2
	1	5	21.33	21.39	21.96		2
	3	0	21.24	21.41	21.74		2
	3	2	21.28	21.52	21.68		2
	3	3	21.23	21.41	21.75		2
	6	0	20.16	20.27	20.62	0-3	3
256QAM	1	0	18.26	18.36	18.81	0-5	5
	1	2	18.26	18.44	18.63		5
	1	5	18.29	18.39	18.69		5
	3	0	18.17	18.31	18.64		5
	3	2	18.11	18.31	18.63		5
	3	3	18.11	18.29	18.62		5
	6	0	18.06	18.21	18.55		5

Table H-101
LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.22	18.29	18.28	0	0
	1	36	18.16	18.07	18.16		0
	1	74	18.14	18.27	18.25		0
	36	0	17.91	18.13	18.13	0-1	0
	36	18	18.03	18.19	18.19		0
	36	37	18.03	18.20	18.22		0
	75	0	17.99	18.08	18.15		0
16QAM	1	0	18.18	18.04	18.31	0-1	0
	1	36	18.14	18.36	18.45		0
	1	74	18.11	18.22	18.32		0
	36	0	17.91	18.12	18.11	0-2	0
	36	18	18.05	18.04	18.13		0
	36	37	18.03	18.17	18.19		0
	75	0	18.07	18.03	18.13		0
64QAM	1	0	18.04	18.27	18.33	0-2	0
	1	36	18.21	18.18	18.50		0
	1	74	18.20	18.12	18.27		0
	36	0	17.98	18.16	18.11	0-3	0
	36	18	18.04	18.10	18.27		0
	36	37	17.97	18.20	18.23		0
	75	0	18.00	18.10	18.19		0
256QAM	1	0	18.13	18.10	18.23	0-5	0
	1	36	18.15	18.31	18.31		0
	1	74	18.10	18.37	18.06		0
	36	0	17.90	18.05	18.14		0
	36	18	18.08	18.05	18.15		0
	36	37	18.06	18.23	18.24		0
	75	0	18.00	18.09	18.09		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 51 of 426

Table H-102

LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.05	18.11	18.32	0	0
	1	25	18.10	18.12	18.22		0
	1	49	18.01	18.16	18.23		0
	25	0	17.98	18.05	18.10	0-1	0
	25	12	18.08	18.19	18.23		0
	25	25	18.08	18.24	18.19		0
	50	0	18.05	18.07	18.16	0	
16QAM	1	0	18.14	18.37	18.33	0-1	0
	1	25	18.34	18.37	18.46		0
	1	49	18.09	18.24	18.20		0
	25	0	18.06	18.12	18.15	0-2	0
	25	12	18.06	18.20	18.23		0
	25	25	18.06	18.21	18.21		0
	50	0	18.01	18.08	18.27	0	
64QAM	1	0	18.09	18.09	18.39	0-2	0
	1	25	18.06	18.49	18.30		0
	1	49	18.09	18.31	18.38		0
	25	0	18.06	18.12	18.13	0-3	0
	25	12	18.12	18.19	18.24		0
	25	25	17.98	18.25	18.32		0
	50	0	18.01	18.18	18.30	0	
256QAM	1	0	17.98	18.23	18.15	0-5	0
	1	25	18.38	18.38	18.32		0
	1	49	18.08	18.18	18.32		0
	25	0	18.01	18.20	18.13	0-5	0
	25	12	18.08	18.24	18.17		0
	25	25	18.08	18.16	18.19		0
	50	0	18.01	18.19	18.19	0	

Table H-103

LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.16	18.21	18.33	0	0
	1	12	17.97	18.26	18.25		0
	1	24	18.07	18.15	18.16		0
	12	0	17.98	18.14	18.14	0-1	0
	12	6	18.10	18.21	18.17		0
	12	13	18.02	18.25	18.16		0
	25	0	17.99	18.10	18.08		0
16QAM	1	0	18.26	18.41	18.47	0-1	0
	1	12	18.35	18.44	18.31		0
	1	24	18.31	18.31	18.34		0
	12	0	18.03	18.13	18.11	0-2	0
	12	6	18.18	18.19	18.12		0
	12	13	18.08	18.29	18.25		0
	25	0	18.08	18.15	18.10		0
64QAM	1	0	18.31	18.35	18.34	0-2	0
	1	12	17.92	18.29	18.36		0
	1	24	18.07	18.21	18.28		0
	12	0	17.98	18.08	18.12	0-3	0
	12	6	18.11	18.14	18.23		0
	12	13	18.07	18.18	18.28		0
	25	0	17.94	18.06	18.08		0
256QAM	1	0	18.19	18.21	18.15	0-5	0
	1	12	18.18	18.33	18.31		0
	1	24	18.14	18.34	18.11		0
	12	0	18.04	18.14	18.04		0
	12	6	18.07	18.15	18.19		0
	12	13	18.14	18.24	18.29		0
	25	0	18.00	18.10	18.09		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 52 of 426

Table H-104

LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	17.89	18.05	17.96	0	0	
	1	7	18.18	18.34	18.27		0	
	1	14	18.02	18.12	18.12		0	
	8	0	18.01	18.10	18.09	0-1	0	
	8	4	18.09	18.13	18.20		0	
	8	7	18.03	18.17	18.20		0	
16QAM	15	0	18.04	18.16	18.27	0-1	0	
	1	0	18.20	18.17	18.21		0	
	1	7	18.45	18.35	18.38		0	
	1	14	18.14	18.35	18.40	0-2	0	
	8	0	18.06	18.11	18.10		0	
	8	4	18.13	18.22	18.25		0	
64QAM	8	7	18.10	18.19	18.38	0-2	0	
	15	0	17.89	18.21	18.08		0	
	1	0	18.04	18.13	18.08	0-2	0	
	1	7	18.40	18.40	18.42		0	
	1	14	17.96	18.10	18.38		0	
	8	0	18.00	18.13	18.13	0-3	0	
8	4	18.08	18.26	18.21	0			
8	7	18.13	18.24	18.27	0			
256QAM	15	0	18.04	18.24	18.12	0-3	0	
	1	0	17.98	18.14	18.23		0-5	0
	1	7	18.24	18.31	18.36			0
	1	14	17.94	18.30	18.13	0		
	8	0	18.02	18.12	18.02	0		
	8	4	18.04	18.28	18.17	0		
8	7	18.12	18.19	18.27	0-5	0		
15	0	18.12	18.22	18.15		0		

Table H-105

LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.97	18.08	18.19	0	0
	1	2	17.93	18.00	18.01		0
	1	5	18.00	18.10	18.21		0
	3	0	18.19	18.01	18.10		0
	3	2	17.82	18.15	18.07		0
	3	3	17.89	17.99	18.00		0
	6	0	17.98	18.01	18.02	0-1	0
16QAM	1	0	18.34	18.35	18.38	0-1	0
	1	2	18.21	18.23	18.34		0
	1	5	18.39	18.27	18.49		0
	3	0	18.08	18.18	18.32		0
	3	2	18.20	18.30	18.15		0
	3	3	18.10	18.15	18.27		0
	6	0	18.29	18.08	18.16	0-2	0
64QAM	1	0	18.12	18.35	18.24	0-2	0
	1	2	18.11	18.39	18.45		0
	1	5	18.17	18.30	18.46		0
	3	0	18.24	18.12	18.44		0
	3	2	18.24	18.29	18.17		0
	3	3	18.12	18.19	18.14		0
	6	0	18.02	18.14	18.24	0-3	0
256QAM	1	0	18.36	18.26	18.27	0-5	0
	1	2	17.93	18.36	18.02		0
	1	5	18.12	18.24	18.38		0
	3	0	18.22	18.16	18.15		0
	3	2	18.14	18.32	18.22		0
	3	3	18.18	18.12	18.30		0
	6	0	17.98	18.14	18.04	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 53 of 426

Table H-106
LTE Band 25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.67	11.52	11.66	0	0
	1	36	11.39	11.58	11.51		0
	1	74	11.44	11.50	11.63		0
	36	0	11.36	11.39	11.50	0-1	0
	36	18	11.39	11.51	11.51		0
	36	37	11.45	11.58	11.57		0
	75	0	11.36	11.42	11.52		0
16QAM	1	0	11.52	11.69	11.63	0-1	0
	1	36	11.47	11.74	11.71		0
	1	74	11.61	11.80	11.73		0
	36	0	11.29	11.49	11.55	0-2	0
	36	18	11.48	11.52	11.60		0
	36	37	11.44	11.57	11.55		0
	75	0	11.44	11.42	11.47		0
64QAM	1	0	11.49	11.61	11.53	0-2	0
	1	36	11.65	11.68	11.75		0
	1	74	11.62	11.68	11.62		0
	36	0	11.39	11.50	11.48	0-3	0
	36	18	11.46	11.53	11.52		0
	36	37	11.45	11.59	11.50		0
	75	0	11.43	11.45	11.56		0
256QAM	1	0	11.39	11.50	11.47	0-5	0
	1	36	11.59	11.58	11.74		0
	1	74	11.40	11.53	11.73		0
	36	0	11.28	11.47	11.57		0
	36	18	11.44	11.48	11.53		0
	36	37	11.38	11.55	11.56		0
	75	0	11.41	11.44	11.85		0

Table H-107
LTE Band 25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.46	11.55	11.42	0	0
	1	25	11.44	11.57	11.57		0
	1	49	11.36	11.52	11.50		0
	25	0	11.43	11.54	11.52	0-1	0
	25	12	11.50	11.50	11.64		0
	25	25	11.41	11.61	11.58		0
	50	0	11.46	11.43	11.54		0
16QAM	1	0	11.54	11.56	11.59	0-1	0
	1	25	11.70	11.60	11.84		0
	1	49	11.47	11.62	11.51		0
	25	0	11.44	11.46	11.54	0-2	0
	25	12	11.45	11.55	11.64		0
	25	25	11.43	11.56	11.60		0
	50	0	11.43	11.47	11.55		0
64QAM	1	0	11.57	11.64	11.63	0-2	0
	1	25	11.56	11.60	11.65		0
	1	49	11.45	11.63	11.70		0
	25	0	11.41	11.48	11.56	0-3	0
	25	12	11.52	11.49	11.65		0
	25	25	11.42	11.57	11.60		0
	50	0	11.47	11.47	11.60		0
256QAM	1	0	11.50	11.50	11.62	0-5	0
	1	25	11.53	11.63	11.71		0
	1	49	11.42	11.61	11.61		0
	25	0	11.47	11.53	11.52		0
	25	12	11.45	11.58	11.62		0
	25	25	11.40	11.63	11.57		0
	50	0	11.47	11.48	11.72		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 54 of 426

Table H-108
LTE Band 25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5
MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.38	11.57	11.49	0	0
	1	12	11.48	11.49	11.49		0
	1	24	11.30	11.52	11.52		0
	12	0	11.42	11.47	11.54	0-1	0
	12	6	11.54	11.48	11.59		0
	12	13	11.45	11.58	11.53		0
	25	0	11.45	11.51	11.52		0
16QAM	1	0	11.52	11.59	11.75	0-1	0
	1	12	11.73	11.77	11.81		0
	1	24	11.71	11.80	11.76		0
	12	0	11.44	11.44	11.55	0-2	0
	12	6	11.54	11.51	11.62		0
	12	13	11.44	11.60	11.65		0
	25	0	11.46	11.55	11.54		0
64QAM	1	0	11.46	11.65	11.60	0-2	0
	1	12	11.60	11.66	11.83		0
	1	24	11.48	11.64	11.75		0
	12	0	11.54	11.49	11.47	0-3	0
	12	6	11.52	11.55	11.55		0
	12	13	11.41	11.55	11.64		0
	25	0	11.44	11.50	11.53		0
256QAM	1	0	11.47	11.39	11.56	0-5	0
	1	12	11.62	11.76	11.76		0
	1	24	11.53	11.50	11.70		0
	12	0	11.45	11.43	11.51		0
	12	6	11.47	11.59	11.56		0
	12	13	11.51	11.58	11.59		0
	25	0	11.40	11.42	11.51		0

Table H-109
LTE Band 25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 3
MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.31	11.56	11.59	0	0
	1	7	11.52	11.58	11.56		0
	1	14	11.38	11.53	11.45		0
	8	0	11.37	11.44	11.46	0-1	0
	8	4	11.45	11.65	11.57		0
	8	7	11.41	11.61	11.55		0
16QAM	15	0	11.40	11.52	11.55		0
	1	0	11.65	11.50	11.65	0-1	0
	1	7	11.80	11.70	11.84		0
	1	14	11.46	11.72	11.65		0
	8	0	11.45	11.51	11.55	0-2	0
	8	4	11.54	11.59	11.58		0
8	7	11.54	11.56	11.68	0		
64QAM	15	0	11.50	11.56	11.57		0
	1	0	11.46	11.55	11.67	0-2	0
	1	7	11.70	11.71	11.79		0
	1	14	11.46	11.70	11.64		0
	8	0	11.45	11.50	11.54	0-3	0
	8	4	11.53	11.58	11.53		0
8	7	11.49	11.60	11.62	0		
256QAM	15	0	11.52	11.58	11.57		0
	1	0	11.37	11.48	11.52	0-5	0
	1	7	11.55	11.66	11.65		0
	1	14	11.50	11.54	11.63		0
	8	0	11.48	11.49	11.50		0
	8	4	11.52	11.64	11.62		0
8	7	11.46	11.58	11.61	0		
	15	0	11.46	11.50	11.54		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 55 of 426

Table H-110
LTE Band 25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	11.29	11.44	11.51	0	0
	1	2	11.31	11.42	11.43		0
	1	5	11.26	11.53	11.50		0
	3	0	11.29	11.38	11.45		0
	3	2	11.23	11.44	11.49		0
	3	3	11.30	11.47	11.55		0
	6	0	11.32	11.45	11.48		0-1
16QAM	1	0	11.68	11.60	11.76	0-1	0
	1	2	11.54	11.70	11.68		0
	1	5	11.43	11.68	11.71		0
	3	0	11.49	11.56	11.62		0
	3	2	11.43	11.60	11.58		0
	3	3	11.42	11.51	11.63		0
	6	0	11.50	11.50	11.64		0-2
64QAM	1	0	11.62	11.72	11.54	0-2	0
	1	2	11.78	11.65	11.62		0
	1	5	11.54	11.50	11.73		0
	3	0	11.56	11.58	11.60		0
	3	2	11.42	11.59	11.64		0
	3	3	11.59	11.63	11.62		0
	6	0	11.48	11.43	11.58		0-3
256QAM	1	0	11.58	11.58	11.67	0-5	0
	1	2	11.43	11.61	11.56		0
	1	5	11.49	11.68	11.83		0
	3	0	11.40	11.61	11.59		0
	3	2	11.33	11.52	11.69		0
	3	3	11.45	11.54	11.57		0
	6	0	11.39	11.35	11.56		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 56 of 426

H.1.16 LTE Band 25 Antenna G

Table H-111
LTE Band 25 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	20.97	20.64	20.45	0	0	
	1	36	20.83	20.83	20.84		0	
	1	74	20.82	20.75	20.48		0	
	36	0	20.91	20.71	20.55	0-1	0	
	36	18	20.90	20.74	20.61		0	
	36	37	20.90	20.59	20.57		0	
16QAM	75	0	20.89	20.69	20.51	0-1	0	
	1	0	21.11	20.76	20.65		0-2	0
	1	36	21.17	20.80	20.63			0
	1	74	21.09	20.76	20.70	0-2		0
	36	0	20.96	20.73	20.56		0	
	36	18	20.93	20.73	20.59		0	
64QAM	36	37	20.98	20.66	20.51	0-2	0	
	75	0	20.96	20.70	20.53		0-3	0
	1	0	20.95	20.94	20.63			0
	1	36	21.17	20.90	20.72	0-2		0
	1	74	21.19	20.78	20.66		0-3	0
	36	0	21.08	20.67	20.62			0
256QAM	36	18	20.99	20.78	20.55	0-3		0
	36	37	20.95	20.62	20.57		0-5	0
	75	0	20.97	20.69	20.60			0
	1	0	19.29	19.11	19.14	0-5		2
	1	36	19.23	18.97	18.90		2	
	1	74	19.25	18.78	18.75		2	
36	0	19.22	18.92	18.82	2			
36	18	19.23	18.96	18.75	2			
36	37	19.13	18.85	18.77	2			
256QAM	75	0	19.10	18.91	18.78	0-5	2	

Table H-112
LTE Band 25 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	20.92	20.68	20.45	0	0	
	1	25	20.98	20.70	20.48		0	
	1	49	20.87	20.64	20.43		0	
	25	0	21.04	20.79	20.60	0-1	0	
	25	12	20.99	20.76	20.56		0	
	25	25	20.92	20.63	20.59		0	
16QAM	50	0	20.95	20.75	20.52	0-1	0	
	1	0	21.16	20.97	20.70		0-1	0
	1	25	21.23	20.79	20.66			0
	1	49	21.04	20.81	20.72	0-2		0
	25	0	21.05	20.69	20.57		0	
	25	12	21.06	20.83	20.62		0	
64QAM	25	25	21.03	20.61	20.62	0-2	0	
	50	0	21.01	20.68	20.63		0	
	1	0	21.20	20.89	20.71		0-2	0
	1	25	21.26	20.82	20.69	0		
	1	49	20.91	20.65	20.65	0-3		0
	25	0	21.05	20.71	20.58		0	
256QAM	25	12	21.07	20.73	20.59		0-3	0
	25	25	21.03	20.64	20.42	0		
	50	0	21.09	20.72	20.51	0-5		0
	1	0	19.37	19.05	19.00		2	
	1	25	19.51	19.04	18.87		2	
	1	49	19.16	18.84	18.76		2	
25	0	19.26	18.89	18.77	2			
25	12	19.24	18.96	18.81	2			
256QAM	25	25	19.21	18.83	18.78	2		
	50	0	19.25	19.01	18.78	2		

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 57 of 426

Table H-113
LTE Band 25 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	20.91	20.56	20.45	0	0	
	1	12	21.08	20.71	20.59		0	
	1	24	20.97	20.58	20.60		0	
	12	0	21.00	20.67	20.44	0-1	0	
	12	6	21.06	20.69	20.63		0	
	12	13	21.01	20.68	20.47		0	
16QAM	25	0	21.02	20.71	20.48	0-1	0	
	1	0	21.23	20.72	20.77		0-2	0
	1	12	21.32	20.92	20.74			0
	1	24	21.16	20.92	20.68	0		
	12	0	21.02	20.77	20.57	0		
	12	6	21.11	20.78	20.66	0		
64QAM	12	13	21.11	20.67	20.54	0-2	0	
	25	0	20.98	20.71	20.55		0	
	1	0	21.13	20.84	20.75	0-2	0	
	1	12	21.11	20.88	20.80		0	
	1	24	21.09	20.84	20.86	0-3	0	
	12	0	21.04	20.76	20.51		0	
256QAM	12	6	21.16	20.77	20.65	0-3	0	
	12	13	21.13	20.68	20.50		0	
	25	0	21.05	20.74	20.58	0-5	0	
	1	0	19.26	19.34	19.21		2	
	1	12	19.35	19.18	18.90		2	
	1	24	19.33	18.95	18.72	0-5	2	
12	0	19.25	18.90	18.72	2			
12	6	19.30	18.98	18.78	2			
256QAM	12	13	19.26	18.84	18.71	0-5	2	
	25	0	19.33	18.95	18.77		2	

Table H-114
LTE Band 25 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	21.11	20.59	20.40	0	0
	1	7	20.98	20.71	20.69		0
	1	14	20.99	20.69	20.38		0
	8	0	20.93	20.67	20.54	0-1	0
	8	4	21.08	20.73	20.51		0
	8	7	21.01	20.72	20.52		0
16QAM	15	0	20.98	20.69	20.59	0-1	0
	1	0	21.55	20.84	20.71		0
	1	7	21.64	20.89	20.82		0
	1	14	21.41	20.82	20.82	0-2	0
	8	0	21.09	20.73	20.55		0
	8	4	21.19	20.85	20.60		0
64QAM	8	7	21.18	20.80	20.54	0-2	0
	15	0	21.06	20.70	20.61		0
	1	0	21.02	20.83	20.65		0-2
	1	7	21.25	20.81	20.69	0	
	1	14	21.22	20.72	20.74	0-3	
	8	0	21.12	20.76	20.57		0
256QAM	8	4	21.19	20.72	20.79		0-3
	8	7	21.03	20.71	20.61	0	
	15	0	21.10	20.75	20.56	0	
	1	0	19.26	19.06	19.34	0-5	2
	1	7	19.75	19.12	18.83		2
	1	14	19.23	18.97	18.70		2
8	0	19.31	18.92	18.79	2		
8	4	19.32	18.92	18.80	2		
8	7	19.28	18.99	18.78	2		
256QAM	15	0	19.22	18.97	18.79	2	

Table H-115
LTE Band 25 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	20.93	20.62	20.47	0	0
	1	2	20.77	20.81	20.51		0
	1	5	20.84	20.70	20.43		0
	3	0	20.82	20.65	20.41		0
	3	2	20.95	20.62	20.45		0
	3	3	20.82	20.69	20.48		0
	6	0	20.89	20.57	20.54	0-1	0
16QAM	1	0	21.12	20.79	20.68	0-1	0
	1	2	21.31	20.70	20.62		0
	1	5	21.15	21.04	20.70		0
	3	0	21.05	20.78	20.56		0
	3	2	21.24	20.85	20.49		0
	3	3	21.07	20.72	20.63		0
	6	0	21.06	20.73	20.59	0-2	0
64QAM	1	0	21.10	20.79	20.78	0-2	0
	1	2	21.10	20.73	20.69		0
	1	5	21.25	20.83	20.64		0
	3	0	21.12	20.74	20.57		0
	3	2	21.01	20.80	20.84		0
	3	3	21.08	20.93	20.65		0
	6	0	21.10	20.73	20.57	0-3	0
256QAM	1	0	19.37	19.50	19.00	0-5	2
	1	2	19.32	19.23	18.99		2
	1	5	19.71	19.04	18.89		2
	3	0	19.21	18.89	18.79		2
	3	2	19.21	18.92	18.74		2
	3	3	19.41	18.91	18.80		2
	6	0	19.18	18.78	18.76	2	

Table H-116
LTE Band 25 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
Conducted Power [dBm]							
QPSK	1	0	19.23	19.08	19.10	0	0
	1	36	19.47	18.87	19.03		0
	1	74	19.16	18.89	18.76		0
	36	0	19.32	19.04	18.86	0-1	0
	36	18	19.23	19.11	18.92		0
	36	37	19.18	18.99	18.90		0
	75	0	19.24	19.04	18.91		0
16QAM	1	0	19.42	19.30	19.00	0-1	0
	1	36	19.50	19.29	19.02		0
	1	74	19.51	19.61	19.17		0
	36	0	19.34	19.01	19.00	0-2	0
	36	18	19.31	19.04	18.97		0
	36	37	19.25	18.98	18.84		0
	75	0	19.25	19.10	18.93		0
64QAM	1	0	19.10	19.37	18.99	0-2	0
	1	36	19.59	19.18	19.00		0
	1	74	19.43	19.12	19.06		0
	36	0	19.24	19.08	18.92	0-3	0
	36	18	19.32	19.06	18.89		0
	36	37	19.27	19.01	18.88		0
	75	0	19.28	19.04	18.91		0
256QAM	1	0	19.59	18.87	18.63	0-5	0.5
	1	36	19.28	19.00	18.62		0.5
	1	74	19.10	18.80	18.52		0.5
	36	0	19.07	18.70	18.54		0.5
	36	18	18.98	18.83	18.57		0.5
	36	37	19.08	18.73	18.58		0.5
	75	0	19.01	18.78	18.63		0.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 59 of 426

Table H-117
LTE Band 25 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.18	18.99	18.84	0	0
	1	25	19.36	18.94	18.88		0
	1	49	19.23	18.77	18.81		0
	25	0	19.33	19.06	18.86	0-1	0
	25	12	19.27	18.99	18.92		0
	25	25	19.40	18.97	18.95		0
16QAM	50	0	19.27	19.10	18.85	0-1	0
	1	0	19.37	19.13	19.05		0
	1	25	19.57	19.09	19.23		0
	1	49	19.47	19.22	18.98	0-2	0
	25	0	19.42	19.07	18.92		0
	25	12	19.32	19.00	19.09		0
64QAM	25	25	19.29	19.11	18.81	0-2	0
	50	0	19.26	19.08	18.91		0
	1	0	19.51	19.14	18.92	0-2	0
	1	25	19.58	18.99	19.08		0
	1	49	19.53	19.14	18.95		0-3
	25	0	19.36	18.90	18.83	0	
256QAM	25	12	19.35	19.00	18.92	0-3	
	25	25	19.27	19.04	18.85		0
	50	0	19.28	19.06	18.95		0
	1	0	19.18	18.96	18.72	0-5	0.5
	1	25	19.29	19.04	18.65		0.5
	1	49	19.09	18.78	18.55		0.5
25	0	19.15	18.72	18.60	0.5		
25	12	19.05	18.87	18.73	0.5		
25	25	19.03	18.70	18.62	0.5		
256QAM	50	0	19.07	18.82	18.67	0.5	

Table H-118
LTE Band 25 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
Conducted Power [dBm]							
QPSK	1	0	19.21	18.96	18.75	0	0
	1	12	19.48	18.93	18.93		0
	1	24	19.30	18.93	18.82		0
	12	0	19.32	19.08	18.89	0-1	0
	12	6	19.42	19.01	18.94		0
	12	13	19.30	18.96	18.78		0
16QAM	25	0	19.38	19.05	18.89	0-1	0
	1	0	19.36	19.23	19.12		0
	1	12	19.50	19.29	19.08		0
	1	24	19.54	19.32	19.18	0-2	0
	12	0	19.32	19.10	18.90		0
	12	6	19.42	19.09	18.94		0
64QAM	12	13	19.39	19.03	18.91	0-2	0
	25	0	19.39	19.05	18.84		0
	1	0	19.29	19.06	18.82	0-2	0
	1	12	19.40	19.15	19.05		0
	1	24	19.43	18.84	19.01		0
	256QAM	12	0	19.31	19.00	18.85	0-3
12		6	19.30	19.09	18.96	0	
12		13	19.38	18.91	18.83	0	
25		0	19.39	19.06	18.95	0-5	0
1		0	19.02	18.73	18.64		0.5
1		12	19.28	18.76	18.68		0.5
1	24	19.24	18.77	18.37	0.5		
12	0	19.11	18.79	18.54	0.5		
256QAM	12	6	19.16	18.82	18.73	0-5	0.5
	12	13	19.11	18.76	18.58		0.5
	25	0	19.13	18.75	18.57		0.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 60 of 426

Table H-119
LTE Band 25 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.21	18.95	18.72	0	0
	1	7	19.31	19.10	18.82		0
	1	14	19.31	19.01	18.72		0
	8	0	19.31	19.12	18.81	0-1	0
	8	4	19.41	19.04	18.88		0
	8	7	19.35	19.05	18.87		0
	15	0	19.33	19.06	18.87		0
16QAM	1	0	19.50	19.30	19.02	0-1	0
	1	7	19.45	19.35	19.02		0
	1	14	19.47	19.19	18.91		0
	8	0	19.37	19.01	18.93	0-2	0
	8	4	19.40	19.15	18.89		0
	8	7	19.35	19.13	18.89		0
	15	0	19.39	19.12	18.98		0
64QAM	1	0	19.25	19.01	18.73	0-2	0
	1	7	19.50	19.28	19.04		0
	1	14	19.53	19.03	18.97		0
	8	0	19.35	18.98	18.90	0-3	0
	8	4	19.41	19.09	18.87		0
	8	7	19.37	19.06	18.89		0
	15	0	19.46	19.03	18.86		0
256QAM	1	0	19.07	18.65	18.59	0-5	0.5
	1	7	19.20	19.02	18.74		0.5
	1	14	19.16	18.72	18.51		0.5
	8	0	19.18	18.77	18.63		0.5
	8	4	19.13	18.76	18.73		0.5
	8	7	19.16	18.73	18.60		0.5
	15	0	19.13	18.78	18.56		0.5

Table H-120
LTE Band 25 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.25	18.87	18.77	0	0
	1	2	19.25	18.78	18.67		0
	1	5	19.17	19.03	18.85		0
	3	0	19.18	18.99	18.78		0
	3	2	19.15	18.89	18.68		0
	3	3	19.22	18.90	18.83		0
	6	0	19.37	18.97	18.80	0-1	0
16QAM	1	0	19.41	19.29	18.99	0-1	0
	1	2	19.46	19.05	19.02		0
	1	5	19.43	19.12	18.97		0
	3	0	19.41	19.17	19.07		0
	3	2	19.63	19.07	18.80		0
	3	3	19.38	19.28	18.96		0
	6	0	19.40	19.02	18.99	0-2	0
64QAM	1	0	19.53	19.08	19.05	0-2	0
	1	2	19.35	18.95	18.98		0
	1	5	19.48	19.20	19.31		0
	3	0	19.52	19.05	19.04		0
	3	2	19.37	19.25	18.83		0
	3	3	19.39	19.07	18.93		0
	6	0	19.24	18.98	18.91	0-3	0
256QAM	1	0	18.99	18.66	18.72	0-5	0.5
	1	2	19.22	18.85	18.74		0.5
	1	5	19.25	19.14	18.70		0.5
	3	0	19.13	18.91	18.51		0.5
	3	2	19.03	18.86	18.61		0.5
	3	3	19.09	18.70	18.78		0.5
	6	0	19.00	18.69	18.55		0.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 61 of 426

Table H-121
LTE Band 25 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.50	10.65	10.09	0	0
	1	36	10.78	10.36	9.97		0
	1	74	10.41	10.18	9.87		0
	36	0	10.51	10.24	10.07	0-1	0
	36	18	10.61	10.23	10.06		0
	36	37	10.41	10.27	10.00		0
16QAM	75	0	10.42	10.28	10.07	0-1	0
	1	0	10.63	10.30	10.19		0
	1	36	10.54	10.31	10.54		0
	1	74	10.45	10.23	10.13	0-2	0
	36	0	10.52	10.27	10.12		0
	36	18	10.52	10.24	10.15		0
64QAM	36	37	10.55	10.18	10.00	0-2	0
	75	0	10.49	10.23	10.09		0
	1	0	10.65	10.42	10.16		0-2
	1	36	10.68	10.38	10.21	0	
	1	74	10.69	10.27	10.24	0	
	36	0	10.58	10.21	10.02	0-3	0
256QAM	36	18	10.61	10.34	10.12		0
	36	37	10.42	10.17	10.06		0
	75	0	10.49	10.23	10.07	0-5	0
	1	0	10.73	10.46	10.13		0
	1	36	10.70	10.38	10.23		0
	256QAM	1	74	10.50	10.32	10.09	0-5
36		0	10.58	10.28	10.09	0	
36		18	10.55	10.37	10.17	0	
36		37	10.55	10.22	10.04	0	
75		0	10.51	10.24	10.13	0	

Table H-122
LTE Band 25 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
Conducted Power [dBm]							
QPSK	1	0	10.42	10.20	10.11	0	0
	1	25	10.78	10.33	10.07		0
	1	49	10.57	10.29	10.10		0
	25	0	10.52	10.37	10.06	0-1	0
	25	12	10.53	10.29	10.06		0
	25	25	10.51	10.21	10.03		0
16QAM	50	0	10.53	10.29	10.12	0-1	0
	1	0	10.78	10.41	10.15		0
	1	25	10.76	10.41	10.38		0
	1	49	10.60	10.27	10.50	0-2	0
	25	0	10.57	10.26	10.05		0
	25	12	10.52	10.24	10.12		0
64QAM	25	25	10.52	10.20	10.09	0-2	0
	50	0	10.49	10.21	10.06		0
	1	0	10.67	10.38	10.16		0
	1	25	10.70	10.38	10.13	0-2	0
	1	49	10.59	10.33	10.23		0
	25	0	10.59	10.25	10.12		0-3
25	12	10.50	10.35	10.13	0		
25	25	10.50	10.15	10.05	0		
256QAM	50	0	10.49	10.25	10.06	0-3	0
	1	0	10.72	10.32	10.21		0
	1	25	10.71	10.49	10.29		0-5
	1	49	10.60	10.21	10.09	0	
	25	0	10.58	10.29	10.10	0	
	25	12	10.55	10.30	10.17	0	
25	25	10.49	10.26	10.10	0		
256QAM	50	0	10.52	10.31	10.04	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 62 of 426

Table H-123
LTE Band 25 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.42	10.24	10.02	0	0
	1	12	10.56	10.38	10.19		0
	1	24	10.57	10.21	9.92		0
	12	0	10.60	10.29	10.00	0-1	0
	12	6	10.57	10.31	10.08		0
	12	13	10.59	10.18	10.01		0
16QAM	25	0	10.61	10.18	10.04	0-1	0
	1	0	10.56	10.30	10.12		0
	1	12	10.83	10.44	10.16		0
	1	24	10.72	10.33	10.16	0-2	0
	12	0	10.61	10.23	10.05		0
	12	6	10.76	10.32	10.10		0
64QAM	12	13	10.61	10.29	10.04	0-2	0
	25	0	10.56	10.19	10.10		0
	1	0	10.76	10.39	10.18	0-2	0
	1	12	10.80	10.39	10.30		0
	1	24	10.63	10.37	10.22		0
	256QAM	12	0	10.58	10.18	10.02	0-3
12		6	10.55	10.33	10.11	0	
12		13	10.65	10.17	10.09	0	
25		0	10.65	10.27	10.10	0-5	0
1		0	10.58	10.35	10.06		0
1		12	10.80	10.42	10.17		0
1	24	10.70	10.23	10.06	0		
256QAM	12	0	10.59	10.26	10.02	0-5	0
	12	6	10.66	10.40	10.15		0
	12	13	10.55	10.25	10.11		0
	25	0	10.50	10.21	10.07		0

Table H-124
LTE Band 25 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.43	10.15	10.00	0	0
	1	7	10.45	10.27	10.08		0
	1	14	10.47	10.18	9.87		0
	8	0	10.55	10.25	10.01	0-1	0
	8	4	10.60	10.33	10.06		0
	8	7	10.48	10.22	10.12		0
16QAM	15	0	10.53	10.31	10.05	0-1	0
	1	0	10.89	10.31	10.15		0
	1	7	10.69	10.77	10.19		0
	1	14	10.67	10.53	10.00	0-2	0
	8	0	10.62	10.25	10.06		0
	8	4	10.62	10.39	10.04		0
64QAM	8	7	10.59	10.13	10.14	0-2	0
	15	0	10.56	10.32	10.02		0
	1	0	10.59	10.29	10.03	0-2	0
	1	7	10.80	10.50	10.20		0
	1	14	10.79	10.33	10.19		0
	8	0	10.58	10.35	9.99	0-3	0
8	4	10.63	10.37	10.09	0		
8	7	10.63	10.23	10.04	0		
256QAM	15	0	10.56	10.26	10.06	0-3	0
	1	0	10.45	10.40	10.11		0
	1	7	10.65	10.47	10.22		0
	1	14	10.70	10.21	10.12	0-5	0
	8	0	10.59	10.27	9.99		0
	8	4	10.70	10.30	10.20		0
8	7	10.65	10.22	10.12	0		
15	0	10.63	10.22	10.06	0		

Table H-125
LTE Band 25 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.50	10.16	9.96	0	0
	1	2	10.35	10.06	9.97		0
	1	5	10.31	10.21	9.88		0
	3	0	10.31	10.13	10.01		0
	3	2	10.42	10.15	10.06		0
	3	3	10.51	10.12	9.91		0
	6	0	10.45	10.19	9.98	0-1	0
16QAM	1	0	11.00	10.45	10.47	0-1	0
	1	2	10.80	10.21	10.73		0
	1	5	10.62	10.37	10.07		0
	3	0	10.48	10.35	10.09		0
	3	2	10.64	10.17	10.41		0
	3	3	10.48	10.30	10.14		0
	6	0	10.61	10.24	10.03	0-2	0
64QAM	1	0	10.66	10.43	10.14	0-2	0
	1	2	10.98	10.40	10.12		0
	1	5	10.65	10.35	10.10		0
	3	0	10.48	10.44	10.11		0
	3	2	10.95	10.19	9.99		0
	3	3	10.60	10.35	10.22		0
	6	0	10.58	10.16	10.05	0-3	0
256QAM	1	0	10.67	10.40	10.21	0-5	0
	1	2	10.63	10.48	10.23		0
	1	5	10.62	10.34	10.11		0
	3	0	10.61	10.32	10.12		0
	3	2	10.54	10.25	10.12		0
	3	3	10.67	10.25	10.33		0
	6	0	10.56	10.27	10.00		0

Table H-126
LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 15 MHz Bandwidth

LTE Band 25 (PCS) 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26115 (1857.5 MHz)	26365 (1882.5 MHz)	26615 (1907.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.77	17.56	17.73	0	0
	1	36	17.89	17.67	17.54		0
	1	74	17.73	17.69	17.39		0
	36	0	17.91	17.63	17.49	0-1	0
	36	18	17.92	17.63	17.58		0
	36	37	17.85	17.53	17.49		0
	75	0	17.83	17.57	17.57		0
16QAM	1	0	17.93	17.74	17.55	0-1	0
	1	36	17.93	17.80	17.56		0
	1	74	17.86	17.72	17.68		0
	36	0	17.96	17.66	17.56	0-2	0
	36	18	17.91	17.64	17.55		0
	36	37	17.93	17.58	17.50		0
	75	0	17.83	17.67	17.58		0
64QAM	1	0	17.92	17.81	17.59	0-2	0
	1	36	17.86	17.56	17.84		0
	1	74	17.92	17.67	17.58		0
	36	0	17.88	17.63	17.59	0-3	0
	36	18	17.98	17.62	17.54		0
	36	37	17.86	17.55	17.57		0
	75	0	17.90	17.61	17.56		0
256QAM	1	0	17.90	17.77	17.47	0-5	0
	1	36	17.94	17.68	17.68		0
	1	74	17.93	17.66	17.58		0
	36	0	17.90	17.53	17.48		0
	36	18	18.00	17.64	17.64		0
	36	37	17.92	17.53	17.51		0
	75	0	17.93	17.57	17.51		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 64 of 426

Table H-127

LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 10 MHz Bandwidth

LTE Band 25 (PCS) 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26090 (1855.0 MHz)	26365 (1882.5 MHz)	26640 (1910.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.67	17.45	17.22	0	0
	1	25	17.85	17.77	17.32		0
	1	49	17.55	17.37	17.49		0
	25	0	17.76	17.46	17.32	0-1	0
	25	12	17.73	17.49	17.38		0
	25	25	17.71	17.37	17.34		0
	50	0	17.65	17.42	17.42		0
16QAM	1	0	17.80	17.66	17.54	0-1	0
	1	25	17.83	17.68	17.47		0
	1	49	17.83	17.58	17.56		0
	25	0	17.84	17.48	17.32	0-2	0
	25	12	17.82	17.51	17.48		0
	25	25	17.74	17.44	17.41		0
	50	0	17.74	17.54	17.43		0
64QAM	1	0	17.85	17.47	17.61	0-2	0
	1	25	17.88	17.72	17.60		0
	1	49	17.80	17.45	17.41		0
	25	0	17.82	17.50	17.37	0-3	0
	25	12	17.68	17.49	17.41		0
	25	25	17.73	17.43	17.38		0
	50	0	17.73	17.50	17.40		0
256QAM	1	0	17.66	17.65	17.40	0-5	0
	1	25	17.95	17.61	17.46		0
	1	49	17.81	17.42	17.30		0
	25	0	17.83	17.58	17.38		0
	25	12	17.78	17.51	17.43		0
	25	25	17.79	17.50	17.42		0
	50	0	17.75	17.52	17.30		0

Table H-128

LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 5 MHz Bandwidth

LTE Band 25 (PCS) 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26065 (1852.5 MHz)	26365 (1882.5 MHz)	26665 (1912.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.64	17.50	17.25	0	0
	1	12	17.80	17.41	17.26		0
	1	24	17.65	17.47	17.24		0
	12	0	17.75	17.46	17.29	0-1	0
	12	6	17.72	17.51	17.37		0
	12	13	17.78	17.40	17.29		0
	25	0	17.83	17.48	17.29		0
16QAM	1	0	17.88	17.57	17.48	0-1	0
	1	12	17.87	17.66	17.64		0
	1	24	17.94	17.73	17.50		0
	12	0	17.69	17.46	17.33	0-2	0
	12	6	17.86	17.54	17.43		0
	12	13	17.89	17.45	17.27		0
	25	0	17.78	17.48	17.34		0
64QAM	1	0	17.79	17.67	17.44	0-2	0
	1	12	17.77	17.74	17.45		0
	1	24	17.91	17.50	17.42		0
	12	0	17.82	17.56	17.40	0-3	0
	12	6	17.82	17.49	17.41		0
	12	13	17.87	17.41	17.32		0
	25	0	17.75	17.46	17.36		0
256QAM	1	0	17.79	17.65	17.30	0-5	0
	1	12	17.76	17.61	17.40		0
	1	24	17.96	17.47	17.27		0
	12	0	17.79	17.55	17.38		0
	12	6	17.91	17.51	17.45		0
	12	13	17.87	17.39	17.32		0
	25	0	17.82	17.58	17.33		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 65 of 426

Table H-129
LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 3 MHz Bandwidth

LTE Band 25 (PCS) 3 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26055 (1851.5 MHz)	26365 (1882.5 MHz)	26675 (1913.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.55	17.50	17.11	0	0
	1	7	17.74	17.57	17.32		0
	1	14	17.73	17.38	17.28		0
	8	0	17.72	17.53	17.33	0-1	0
	8	4	17.81	17.42	17.34		0
	8	7	17.84	17.43	17.30		0
	15	0	17.75	17.48	17.43		0
16QAM	1	0	17.75	17.76	17.28	0-1	0
	1	7	17.90	17.48	17.59		0
	1	14	17.83	17.59	17.49		0
	8	0	17.75	17.55	17.39	0-2	0
	8	4	17.91	17.51	17.38		0
	8	7	17.84	17.52	17.40		0
	15	0	17.79	17.48	17.36		0
64QAM	1	0	17.76	17.40	17.43	0-2	0
	1	7	17.94	17.64	17.62		0
	1	14	17.94	17.59	17.50		0
	8	0	17.67	17.46	17.40	0-3	0
	8	4	17.86	17.55	17.45		0
	8	7	17.82	17.53	17.46		0
	15	0	17.86	17.48	17.40		0
256QAM	1	0	17.69	17.53	17.19	0-5	0
	1	7	17.99	17.63	17.44		0
	1	14	17.87	17.51	17.48		0
	8	0	17.79	17.47	17.40		0
	8	4	17.90	17.56	17.52		0
	8	7	17.80	17.59	17.37		0
	15	0	17.85	17.48	17.31		0

Table H-130
LTE Band 25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 1.4 MHz Bandwidth

LTE Band 25 (PCS) 1.4 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			26047 (1850.7 MHz)	26365 (1882.5 MHz)	26683 (1914.3 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.73	17.44	17.41	0	0
	1	2	17.69	17.60	17.32		0
	1	5	17.81	17.49	17.32		0
	3	0	17.55	17.35	17.08		0
	3	2	17.54	17.50	17.21		0
	3	3	17.66	17.39	17.25		0
	6	0	17.69	17.36	17.34	0-1	0
16QAM	1	0	17.96	17.40	17.51	0-1	0
	1	2	17.89	17.43	17.32		0
	1	5	17.77	17.87	17.50		0
	3	0	17.80	17.48	17.36		0
	3	2	17.80	17.38	17.40		0
	3	3	17.83	17.48	17.48		0
	6	0	17.94	17.58	17.38	0-2	0
64QAM	1	0	17.94	17.53	17.37	0-2	0
	1	2	17.71	17.68	17.37		0
	1	5	17.86	17.64	17.54		0
	3	0	17.83	17.71	17.36		0
	3	2	17.82	17.43	17.35		0
	3	3	17.83	17.48	17.44		0
	6	0	17.79	17.52	17.42	0-3	0
256QAM	1	0	17.87	17.27	17.43	0-5	0
	1	2	17.83	17.60	17.40		0
	1	5	17.96	17.53	17.78		0
	3	0	17.94	17.40	17.32		0
	3	2	17.80	17.43	17.37		0
	3	3	17.92	17.49	17.28		0
	6	0	17.81	17.46	17.21	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 66 of 426

H.1.17 LTE Band 30 Antenna B

Table H-131
LTE Band 30 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	23.51	0	0
	1	12	23.55		0
	1	24	23.36		0
	12	0	22.93	0-1	1
	12	6	22.97		1
	12	13	22.95		1
16QAM	25	0	22.69		1
	1	0	22.85	0-1	1
	1	12	22.54		1
	1	24	22.32		1
	12	0	21.94	0-2	2
	12	6	21.99		2
64QAM	12	13	22.02		2
	25	0	21.89		2
	1	0	21.80	0-2	2
	1	12	21.68		2
	1	24	21.35		2
	12	0	21.03	0-3	3
256QAM	12	6	20.97		3
	12	13	20.92		3
	25	0	20.93		3
	1	0	18.60	0-5	5
	1	12	18.52		5
	1	24	18.55		5
	12	0	18.97		5
	12	6	18.92		5
	12	13	18.91		5
	25	0	18.89		5

Table H-132

LTE Band 30 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	18.96	0	0
	1	12	19.05		0
	1	24	19.10		0
	12	0	19.04	0-1	0
	12	6	19.12		0
	12	13	19.09		0
16QAM	25	0	18.97		0
	1	0	19.23	0-1	0
	1	12	19.27		0
	1	24	19.30		0
	12	0	19.14	0-2	0
	12	6	19.17		0
64QAM	12	13	19.12		0
	25	0	19.05		0
	1	0	19.16	0-2	0
	1	12	19.29		0
	1	24	19.27		0
	12	0	19.12	0-3	0
256QAM	12	6	19.21		0
	12	13	19.12		0
	25	0	19.11		0
	1	0	18.90	0-5	0
	1	12	18.55		0
	1	24	18.46		0
	12	0	18.43		0
	12	6	18.38		0
	12	13	18.45		0
	25	0	18.42		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 67 of 426

Table H-133
LTE Band 30 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	11.51	0	0
	1	12	11.55		0
	1	24	11.54		0
	12	0	11.55	0-1	0
	12	6	11.62		0
	12	13	11.60		0
	25	0	11.54		0
16QAM	1	0	11.87	0-1	0
	1	12	11.67		0
	1	24	11.70		0
	12	0	11.62	0-2	0
	12	6	11.68		0
	12	13	11.68		0
	25	0	11.56		0
64QAM	1	0	11.74	0-2	0
	1	12	11.77		0
	1	24	11.69		0
	12	0	11.57	0-3	0
	12	6	11.58		0
	12	13	11.61		0
	25	0	11.61		0
256QAM	1	0	11.60	0-5	0
	1	12	11.66		0
	1	24	11.64		0
	12	0	11.70		0
	12	6	11.56		0
	12	13	11.63		0
	25	0	11.56		0

H.1.18 LTE Band 30 Antenna G

Table H-134
LTE Band 30 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz) Conducted Power [dBm]		
QPSK	1	0	20.71	0	0
	1	12	20.65		0
	1	24	20.67		0
	12	0	20.79	0-1	0
	12	6	20.69		0
	12	13	20.71		0
	25	0	20.72		0
16QAM	1	0	20.92	0-1	0
	1	12	21.12		0
	1	24	20.93		0
	12	0	20.87	0-2	0
	12	6	20.77		0
	12	13	20.65		0
	25	0	20.73		0
64QAM	1	0	20.93	0-2	0
	1	12	20.93		0
	1	24	20.88		0
	12	0	20.06	0-3	0.5
	12	6	19.98		0.5
	12	13	19.92		0.5
	25	0	19.97		0.5
256QAM	1	0	18.47	0-5	2.5
	1	12	18.06		2.5
	1	24	17.94		2.5
	12	0	18.01		2.5
	12	6	17.87		2.5
	12	13	17.83		2.5
	25	0	17.89		2.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 68 of 426

Table H-135
LTE Band 30 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	19.82	0	0
	1	12	19.79		0
	1	24	19.75		0
	12	0	19.71	0-1	0
	12	6	19.67		0
	12	13	19.63		0
	25	0	19.70		0
16QAM	1	0	20.11	0-1	0
	1	12	20.20		0
	1	24	20.00		0
	12	0	19.72	0-2	0
	12	6	19.69		0
	12	13	19.63		0
	25	0	19.58		0
64QAM	1	0	20.03	0-2	0
	1	12	20.11		0
	1	24	19.86		0
	12	0	19.75	0-3	0
	12	6	19.75		0
	12	13	19.72		0
	25	0	19.64		0
256QAM	1	0	18.09	0-5	1.5
	1	12	18.05		1.5
	1	24	17.99		1.5
	12	0	18.00		1.5
	12	6	17.93		1.5
	12	13	17.80		1.5
	25	0	17.85		1.5

Table H-136
LTE Band 30 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			27710 (2310.0 MHz)		
			Conducted Power [dBm]		
QPSK	1	0	9.08	0	0
	1	12	9.16		0
	1	24	8.95		0
	12	0	9.11	0-1	0
	12	6	9.11		0
	12	13	8.97		0
	25	0	9.11		0
16QAM	1	0	9.21	0-1	0
	1	12	9.21		0
	1	24	9.20		0
	12	0	9.17	0-2	0
	12	6	9.24		0
	12	13	9.08		0
	25	0	9.14		0
64QAM	1	0	9.27	0-2	0
	1	12	9.30		0
	1	24	9.20		0
	12	0	9.13	0-3	0
	12	6	9.12		0
	12	13	9.12		0
	25	0	9.13		0
256QAM	1	0	9.01	0-5	0
	1	12	9.05		0
	1	24	9.06		0
	12	0	9.14		0
	12	6	9.01		0
	12	13	8.97		0
	25	0	9.00		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 69 of 426

Table H-137

LTE Band 30 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 5 MHz Bandwidth

LTE Band 30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Mid Channel 27710 (2310.0 MHz)	MPR Allowed per 3GPP [dB]	MPR [dB]
			Conducted Power [dBm]		
QPSK	1	0	17.72	0	0
	1	12	17.74		0
	1	24	17.64		0
	12	0	17.84	0-1	0
	12	6	17.63		0
	12	13	17.61		0
	25	0	17.63		0
	1	0	17.73		0
16QAM	1	12	17.81	0-1	0
	1	24	17.69		0
	12	0	17.74		0
	12	6	17.68	0-2	0
	12	13	17.58		0
	25	0	17.62		0
	1	0	17.90		0
	1	12	17.86	0-2	0
64QAM	1	24	17.69		0
	12	0	17.70	0-3	0
	12	6	17.75		0
	12	13	17.60		0
	25	0	17.51		0
	1	0	17.82		0
	1	12	17.78	0-5	0
	1	24	17.66		0
256QAM	12	0	17.60		0
	12	6	17.69		0
	12	13	17.69		0
	25	0	17.69		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 70 of 426

H.1.19 LTE Band 7 Antenna B

Table H-138

LTE Band 7 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.61	23.90	23.48	0	0
	1	36	23.64	23.93	23.40		0
	1	74	23.85	23.92	23.31		0
	36	0	22.69	22.92	22.61	0-1	1
	36	18	22.77	22.94	22.60		1
	36	37	22.74	22.89	22.49		1
	75	0	22.73	22.86	22.55		1
16QAM	1	0	22.82	23.13	22.74	0-1	1
	1	36	22.98	23.15	22.69		1
	1	74	22.81	22.99	22.62		1
	36	0	21.73	21.94	21.62	0-2	2
	36	18	21.83	21.95	21.62		2
	36	37	21.79	21.92	21.52		2
	75	0	21.77	21.90	21.60		2
64QAM	1	0	21.91	22.11	21.80	0-2	2
	1	36	21.91	22.26	21.86		2
	1	74	21.85	22.12	21.75		2
	36	0	20.71	20.97	20.64	0-3	3
	36	18	20.80	20.96	20.60		3
	36	37	20.79	20.92	20.51		3
	75	0	20.78	20.92	20.58		3
256QAM	1	0	18.85	19.10	18.78	0-5	5
	1	36	18.90	19.13	18.71		5
	1	74	18.93	18.96	18.55		5
	36	0	18.68	18.91	18.60		5
	36	18	18.76	18.93	18.58		5
	36	37	18.75	18.93	18.54		5
	75	0	18.75	18.93	18.60		5

Table H-139

LTE Band 7 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	23.87	23.95	23.47	0	0
	1	25	23.95	24.02	23.43		0
	1	49	23.97	23.94	23.39		0
	25	0	22.68	22.97	22.63	0-1	1
	25	12	22.80	22.98	22.64		1
	25	25	22.78	22.94	22.50		1
	50	0	22.78	22.94	22.58		1
16QAM	1	0	23.00	23.21	22.75	0-1	1
	1	25	23.10	23.29	22.76		1
	1	49	23.10	23.08	22.60		1
	25	0	21.73	21.98	21.63	0-2	2
	25	12	21.85	22.02	21.64		2
	25	25	21.82	21.97	21.51		2
	50	0	21.81	21.97	21.60		2
64QAM	1	0	21.99	22.31	21.80	0-2	2
	1	25	21.98	22.44	21.82		2
	1	49	22.04	22.18	21.72		2
	25	0	20.75	20.97	20.63	0-3	3
	25	12	20.85	21.04	20.64		3
	25	25	20.78	20.96	20.54		3
	50	0	20.76	20.99	20.60		3
256QAM	1	0	18.78	19.08	18.77	0-5	5
	1	25	18.93	19.21	18.74		5
	1	49	18.83	19.00	18.59		5
	25	0	18.74	18.99	18.63		5
	25	12	18.85	19.03	18.62		5
	25	25	18.76	18.94	18.47		5
	50	0	18.77	18.95	18.59		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 71 of 426

Table H-140
LTE Band 7 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 7								
5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	23.65	24.09	23.78	0	0	
	1	12	23.74	24.10	23.70		0	
	1	24	23.72	24.12	23.71		0	
	12	0	22.67	22.94	22.56	0-1	1	
	12	6	22.80	22.99	22.63		1	
	12	13	22.77	22.97	22.50		1	
16QAM	25	0	22.74	22.94	22.55	0-1	1	
	1	0	22.89	23.40	22.86		1	
	1	12	23.04	23.42	22.82		1	
	1	24	23.03	23.28	22.80	0-2	1	
	12	0	21.71	22.01	21.60		2	
	12	6	21.86	22.03	21.67		2	
64QAM	12	13	21.77	22.02	21.56	0-2	2	
	25	0	21.78	22.01	21.59		2	
	1	0	21.89	22.15	21.84		0-2	2
	1	12	21.90	22.20	21.71	2		
	1	24	21.91	22.21	21.69	0-3		2
	12	0	20.66	21.00	20.59		3	
256QAM	12	6	20.84	21.08	20.66		0-3	3
	12	13	20.80	21.04	20.50	3		
	25	0	20.79	20.96	20.57	3		
	256QAM	1	0	18.79	19.11	18.68	0-5	5
		1	12	18.97	19.29	18.80		5
		1	24	18.96	19.08	18.57		5
12		0	18.66	18.94	18.57	0-5	5	
12		6	18.79	19.00	18.61		5	
12		13	18.77	18.99	18.52		5	
	25	0	18.75	18.97	18.58	5		

Table H-141
LTE Band 7 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 7								
15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	18.69	18.63	18.60	0	0	
	1	36	18.55	18.49	18.35		0	
	1	74	18.44	18.70	18.36		0	
	36	0	18.38	18.61	18.35	0-1	0	
	36	18	18.54	18.57	18.41		0	
	36	37	18.53	18.60	18.29		0	
16QAM	75	0	18.36	18.49	18.38	0-1	0	
	1	0	18.70	18.65	18.63		0-2	0
	1	36	18.62	18.90	18.56			0
	1	74	18.79	18.78	18.59	0-2		0
	36	0	18.54	18.58	18.53		0	
	36	18	18.41	18.66	18.42		0	
64QAM	36	37	18.45	18.54	18.32	0-2	0	
	75	0	18.40	18.58	18.42		0-3	0
	1	0	18.60	18.71	18.46			0
	1	36	18.59	18.75	18.54	0-3		0
	1	74	18.54	18.76	18.59		0	
	36	0	18.27	18.56	18.41		0	
256QAM	36	18	18.40	18.60	18.32	0-5	0	
	36	37	18.41	18.52	18.24		0-5	0
	75	0	18.36	18.64	18.43			0
	1	0	18.50	18.64	18.60	0-5		0
	1	36	18.49	18.73	18.46		0	
	1	74	18.35	18.61	18.43		0	
256QAM	36	0	18.35	18.49	18.39	0-5	0	
	36	18	18.48	18.65	18.38		0	
	36	37	18.41	18.61	18.36		0	
	75	0	18.38	18.58	18.46	0-5	0	
							0	
							0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 72 of 426

Table H-142

LTE Band 7 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.39	18.67	18.47	0	0
	1	25	18.56	18.63	18.38		0
	1	49	18.49	18.67	18.29		0
	25	0	18.42	18.59	18.36	0-1	0
	25	12	18.51	18.56	18.42		0
	25	25	18.42	18.61	18.29		0
	50	0	18.49	18.56	18.37		0
16QAM	1	0	18.46	18.81	18.59	0-1	0
	1	25	18.46	18.65	18.54		0
	1	49	18.53	18.65	18.56		0
	25	0	18.33	18.65	18.46	0-2	0
	25	12	18.51	18.65	18.46		0
	25	25	18.45	18.67	18.43		0
	50	0	18.35	18.59	18.43		0
64QAM	1	0	18.49	18.65	18.56	0-2	0
	1	25	18.55	18.75	18.44		0
	1	49	18.50	18.71	18.53		0
	25	0	18.29	18.61	18.48	0-3	0
	25	12	18.44	18.64	18.42		0
	25	25	18.42	18.58	18.43		0
	50	0	18.45	18.69	18.42		0
256QAM	1	0	18.40	18.72	18.44	0-5	0
	1	25	18.52	18.88	18.50		0
	1	49	18.49	18.54	18.40		0
	25	0	18.41	18.67	18.46		0
	25	12	18.47	18.67	18.52		0
	25	25	18.42	18.70	18.32		0
	50	0	18.38	18.51	18.48		0

Table H-143

LTE Band 7 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	18.50	18.87	18.49	0	0
	1	12	18.62	18.59	18.48		0
	1	24	18.55	18.69	18.48		0
	12	0	18.33	18.54	18.37	0-1	0
	12	6	18.59	18.60	18.48		0
	12	13	18.62	18.58	18.39		0
	25	0	18.55	18.56	18.36		0
16QAM	1	0	18.51	18.77	18.87	0-1	0
	1	12	18.49	18.82	18.81		0
	1	24	18.52	18.88	18.69		0
	12	0	18.36	18.62	18.43	0-2	0
	12	6	18.47	18.59	18.47		0
	12	13	18.51	18.67	18.50		0
	25	0	18.39	18.70	18.43		0
64QAM	1	0	18.58	18.66	18.62	0-2	0
	1	12	18.61	19.06	18.46		0
	1	24	18.61	18.77	18.38		0
	12	0	18.36	18.58	18.44	0-3	0
	12	6	18.40	18.66	18.48		0
	12	13	18.45	18.61	18.37		0
	25	0	18.42	18.59	18.47		0
256QAM	1	0	18.44	18.78	18.48	0-5	0
	1	12	18.58	18.89	18.57		0
	1	24	18.42	18.71	18.41		0
	12	0	18.36	18.62	18.43		0
	12	6	18.47	18.62	18.53		0
	12	13	18.44	18.65	18.42		0
	25	0	18.43	18.62	18.49		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 73 of 426

Table H-144
LTE Band 7 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.45	10.54	10.51	0	0
	1	36	10.22	10.57	10.53		0
	1	74	10.30	10.63	10.33		0
	36	0	10.28	10.65	10.47	0-1	0
	36	18	10.38	10.65	10.48		0
	36	37	10.34	10.65	10.40		0
	75	0	10.41	10.61	10.51		0
16QAM	1	0	10.47	10.71	10.59	0-1	0
	1	36	10.55	11.04	10.59		0
	1	74	10.62	10.70	10.53		0
	36	0	10.50	10.60	10.49	0-2	0
	36	18	10.47	10.67	10.45		0
	36	37	10.43	10.67	10.42		0
	75	0	10.41	10.69	10.47		0
64QAM	1	0	10.64	10.69	10.54	0-2	0
	1	36	10.60	10.85	10.53		0
	1	74	10.59	10.75	10.49		0
	36	0	10.49	10.67	10.50	0-3	0
	36	18	10.45	10.73	10.46		0
	36	37	10.47	10.66	10.47		0
	75	0	10.44	10.64	10.45		0
256QAM	1	0	10.48	10.67	10.61	0-5	0
	1	36	10.55	10.81	10.56		0
	1	74	10.47	10.65	10.32		0
	36	0	10.30	10.55	10.50		0
	36	18	10.42	10.65	10.48		0
	36	37	10.42	10.69	10.41		0
	75	0	10.62	10.73	10.47		0

Table H-145
LTE Band 7 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	10.52	10.73	10.65	0	0
	1	25	10.31	10.68	10.45		0
	1	49	10.24	10.58	10.29		0
	25	0	10.31	10.63	10.55	0-1	0
	25	12	10.42	10.68	10.56		0
	25	25	10.43	10.66	10.47		0
	50	0	10.42	10.66	10.52		0
16QAM	1	0	10.49	11.01	10.63	0-1	0
	1	25	10.60	10.93	10.55		0
	1	49	10.55	10.74	10.61		0
	25	0	10.40	10.73	10.53	0-2	0
	25	12	10.52	10.76	10.52		0
	25	25	10.44	10.75	10.45		0
	50	0	10.42	10.74	10.50		0
64QAM	1	0	10.58	10.87	10.82	0-2	0
	1	25	10.67	10.84	10.76		0
	1	49	10.65	11.05	10.39		0
	25	0	10.37	10.63	10.53	0-3	0
	25	12	10.51	10.68	10.54		0
	25	25	10.44	10.66	10.37		0
	50	0	10.47	10.67	10.51		0
256QAM	1	0	10.46	10.79	10.59	0-5	0
	1	25	10.60	10.78	10.65		0
	1	49	10.46	10.72	10.46		0
	25	0	10.34	10.75	10.54		0
	25	12	10.48	10.70	10.51		0
	25	25	10.42	10.68	10.40		0
	50	0	10.41	10.74	10.43		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 74 of 426

Table H-146
LTE Band 7 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)			
			Conducted Power [dBm]					
QPSK	1	0	10.33	10.63	10.41	0	0	
	1	12	10.30	10.75	10.53		0	
	1	24	10.37	10.58	10.46		0	
	12	0	10.35	10.63	10.52	0-1	0	
	12	6	10.42	10.75	10.50		0	
	12	13	10.37	10.68	10.54		0	
16QAM	25	0	10.37	10.68	10.52	0-1	0	
	1	0	10.67	10.99	10.62		0	
	1	12	10.60	11.16	10.65		0	
	1	24	10.66	10.90	10.62	0-2	0	
	12	0	10.45	10.72	10.51		0	
	12	6	10.53	10.75	10.59		0	
64QAM	12	13	10.46	10.71	10.53	0-2	0	
	25	0	10.45	10.69	10.51		0	
	1	0	10.56	10.78	10.51		0-2	0
	1	12	10.67	10.88	10.79	0		
	1	24	10.60	10.84	10.47	0		
	12	0	10.43	10.65	10.45	0-3	0	
12	6	10.53	10.75	10.52	0			
12	13	10.45	10.66	10.48	0			
256QAM	25	0	10.39	10.73	10.45	0-3	0	
	1	0	10.42	10.70	10.44		0-5	0
	1	12	10.65	10.95	10.67			0
	1	24	10.54	10.69	10.38	0		
	12	0	10.49	10.65	10.50	0		
	12	6	10.52	10.77	10.58	0		
	12	13	10.48	10.69	10.53		0	
	25	0	10.44	10.61	10.51		0	

H.1.20 LTE Band 7 Antenna G

Table H-147
LTE Band 7 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.31	19.73	19.46	0	0
	1	36	19.43	20.21	19.54		0
	1	74	19.49	19.49	19.22		0
	36	0	19.38	19.81	19.36	0-1	0
	36	18	19.48	19.86	19.46		0
	36	37	19.54	19.80	19.42		0
	75	0	19.52	19.82	19.45		0
16QAM	1	0	19.56	20.05	19.57	0-1	0
	1	36	19.61	20.19	19.64		0
	1	74	19.68	20.06	19.43		0
	36	0	19.37	19.79	19.57	0-2	0
	36	18	19.53	19.90	19.48		0
	36	37	19.52	19.82	19.35		0
	75	0	19.49	19.82	19.45		0
64QAM	1	0	19.51	20.08	19.61	0-2	0
	1	36	19.82	20.06	19.62		0
	1	74	19.46	19.66	19.45		0
	36	0	19.38	19.78	19.47	0-3	0
	36	18	19.54	19.81	19.41		0
	36	37	19.57	19.76	19.33		0
	75	0	19.54	19.78	19.50		0
256QAM	1	0	19.19	19.75	19.36	0-5	0.5
	1	36	19.27	19.75	19.28		0.5
	1	74	19.51	19.50	19.13		0.5
	36	0	19.20	19.57	19.23		0.5
	36	18	19.24	19.55	19.23		0.5
	36	37	19.37	19.59	19.10		0.5
	75	0	19.28	19.57	19.22		0.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 75 of 426

Table H-148
LTE Band 7 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.42	19.87	19.54	0	0
	1	25	19.72	19.83	19.44		0
	1	49	19.58	19.75	19.41		0
	25	0	19.42	19.89	19.59	0-1	0
	25	12	19.52	19.91	19.50		0
	25	25	19.54	19.92	19.47		0
	50	0	19.50	19.83	19.50		0
16QAM	1	0	19.62	19.87	19.65	0-1	0
	1	25	19.71	20.00	19.72		0
	1	49	19.88	19.76	19.50		0
	25	0	19.46	19.83	19.46	0-2	0
	25	12	19.61	19.89	19.57		0
	25	25	19.59	19.84	19.43		0
	50	0	19.53	19.92	19.53		0
64QAM	1	0	19.83	20.12	19.74	0-2	0
	1	25	19.80	20.08	19.73		0
	1	49	19.61	20.02	19.55		0
	25	0	19.52	19.93	19.49	0-3	0
	25	12	19.60	19.87	19.60		0
	25	25	19.57	19.87	19.44		0
	50	0	19.55	19.82	19.45		0
256QAM	1	0	19.19	19.84	19.33	0-5	0.5
	1	25	19.34	19.96	19.48		0.5
	1	49	19.33	19.84	19.24		0.5
	25	0	19.23	19.72	19.23		0.5
	25	12	19.37	19.73	19.30		0.5
	25	25	19.31	19.60	19.11		0.5
	50	0	19.36	19.64	19.24		0.5

Table H-149
LTE Band 7 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	19.37	19.86	19.36	0	0
	1	12	19.65	19.95	19.48		0
	1	24	19.48	19.96	19.35		0
	12	0	19.37	19.91	19.51	0-1	0
	12	6	19.62	19.97	19.60		0
	12	13	19.56	19.89	19.48		0
16QAM	25	0	19.49	19.83	19.49	0	
	1	0	19.55	20.24	19.75	0-1	0
	1	12	19.81	20.20	19.59		0
	1	24	19.85	19.90	19.57		0
	12	0	19.50	19.93	19.45	0-2	0
	12	6	19.69	20.00	19.52		0
64QAM	12	13	19.56	19.90	19.40		0
	25	0	19.54	19.86	19.45	0	
	1	0	19.65	20.05	19.65	0-2	0
	1	12	19.64	20.13	19.60		0
	1	24	19.69	19.96	19.62		0
	12	0	19.49	19.88	19.39	0-3	0
12	6	19.55	19.88	19.56	0		
12	13	19.61	19.86	19.49	0		
256QAM	25	0	19.51	19.93	19.50	0	
	1	0	19.15	19.69	19.08	0-5	0.5
	1	12	19.62	19.90	19.36		0.5
	1	24	19.39	19.57	19.09		0.5
	12	0	19.28	19.67	19.17	0.5	
	12	6	19.37	19.70	19.22	0.5	
12	13	19.33	19.63	19.14	0.5		
25	0	19.25	19.66	19.18	0.5		

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 76 of 426

Table H-150
LTE Band 7 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.03	17.65	17.10	0	0
	1	36	16.87	17.52	17.09		0
	1	74	17.01	17.15	16.89		0
	36	0	16.98	17.42	17.06		0
	36	18	17.11	17.34	16.97	0-1	0
	36	37	17.12	17.27	16.92		0
	75	0	17.10	17.35	17.03		0
	75	0	17.10	17.35	17.03		0
16QAM	1	0	17.00	17.44	17.11	0-1	0
	1	36	17.18	17.54	17.13		0
	1	74	17.29	17.33	17.14		0
	36	0	17.00	17.44	17.10		0
	36	18	17.17	17.45	17.04	0-2	0
	36	37	17.26	17.36	17.01		0
	75	0	17.16	17.35	17.02		0
	75	0	17.16	17.35	17.02		0
64QAM	1	0	17.00	17.50	17.01	0-2	0
	1	36	17.17	17.38	17.15		0
	1	74	17.16	17.50	17.07		0
	36	0	17.11	17.45	17.14		0
	36	18	17.16	17.45	17.06	0-3	0
	36	37	17.24	17.38	17.02		0
	75	0	17.10	17.46	17.03		0
	75	0	17.10	17.46	17.03		0
256QAM	1	0	17.08	17.50	17.13	0-5	0
	1	36	17.21	17.61	17.41		0
	1	74	17.15	17.33	17.10		0
	36	0	17.05	17.40	17.10		0
	36	18	17.17	17.33	16.89		0
	36	37	17.31	17.39	16.92		0
	75	0	17.16	17.41	17.02		0
	75	0	17.16	17.41	17.02		0

Table H-151
LTE Band 7 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	17.07	17.62	17.10	0	0
	1	25	17.08	17.29	17.04		0
	1	49	17.12	17.27	17.03		0
	25	0	17.01	17.48	17.09		0
	25	12	17.07	17.44	17.04	0-1	0
	25	25	17.18	17.46	16.97		0
	50	0	17.05	17.50	17.10		0
	50	0	17.05	17.50	17.10		0
16QAM	1	0	17.27	17.58	17.14	0-1	0
	1	25	17.42	17.82	17.14		0
	1	49	17.30	17.64	17.07		0
	25	0	17.10	17.45	17.07		0
	25	12	17.17	17.46	17.15	0-2	0
	25	25	17.24	17.42	17.01		0
	50	0	17.14	17.41	17.04		0
	50	0	17.14	17.41	17.04		0
64QAM	1	0	17.01	17.55	17.23	0-2	0
	1	25	17.30	17.52	17.14		0
	1	49	17.17	17.27	17.15		0
	25	0	17.00	17.43	17.04		0
	25	12	17.14	17.44	17.10	0-3	0
	25	25	17.22	17.45	16.96		0
	50	0	17.18	17.39	16.99		0
	50	0	17.18	17.39	16.99		0
256QAM	1	0	17.10	17.54	17.03	0-5	0
	1	25	17.18	17.43	17.17		0
	1	49	17.31	17.37	17.10		0
	25	0	17.13	17.41	17.15		0
	25	12	17.13	17.38	17.06		0
	25	25	17.05	17.29	16.89		0
	50	0	17.19	17.44	17.18		0
	50	0	17.19	17.44	17.18		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 77 of 426

Table H-152
LTE Band 7 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.93	17.22	16.92	0	0
	1	12	17.16	17.52	17.09		0
	1	24	17.03	17.46	16.97		0
	12	0	16.95	17.48	17.00	0-1	0
	12	6	17.06	17.51	17.03		0
	12	13	17.09	17.53	16.96		0
16QAM	25	0	17.10	17.39	17.03	0	
	1	0	17.17	17.49	17.11	0-1	0
	1	12	17.39	17.54	17.48		0
	1	24	17.21	17.67	17.17		0
	12	0	17.05	17.39	17.00	0-2	0
	12	6	17.20	17.57	17.06		0
64QAM	12	13	17.14	17.46	16.90		0
	25	0	17.07	17.47	17.02	0	
	1	0	17.08	17.75	17.17	0-2	0
	1	12	17.21	17.71	17.20		0
	1	24	17.22	17.54	17.08		0
	12	0	17.04	17.44	17.05	0-3	0
12	6	17.13	17.47	17.06	0		
12	13	17.05	17.41	16.99	0		
256QAM	25	0	17.15	17.51	17.11	0	
	1	0	17.06	17.45	17.20	0-5	0
	1	12	17.14	17.49	17.35		0
	1	24	17.19	17.32	16.93		0
	12	0	17.01	17.45	17.02		0
	12	6	17.17	17.49	17.03		0
	12	13	17.16	17.49	16.85		0
	25	0	17.12	17.48	17.18		0

Table H-153
LTE Band 7 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	8.77	9.29	9.09	0	0
	1	36	9.17	9.17	8.92		0
	1	74	9.24	9.25	8.80		0
	36	0	8.81	9.30	9.06	0-1	0
	36	18	8.96	9.28	9.00		0
	36	37	8.98	9.26	8.90		0
16QAM	75	0	9.06	9.20	9.08	0	
	1	0	9.02	9.29	9.39	0-1	0
	1	36	9.03	9.50	9.17		0
	1	74	9.16	9.35	9.07		0
	36	0	8.88	9.34	9.00	0-2	0
	36	18	8.95	9.19	9.07		0
64QAM	36	37	9.08	9.30	9.00		0
	75	0	9.01	9.25	9.02	0	
	1	0	9.10	9.49	9.26	0-2	0
	1	36	9.01	9.46	9.03		0
	1	74	9.13	9.43	9.21		0
	36	0	8.83	9.17	9.05	0-3	0
36	18	8.97	9.30	8.97	0		
36	37	9.07	9.30	8.96	0		
75	0	9.01	9.30	9.08	0		
256QAM	1	0	8.83	9.29	9.17	0-5	0
	1	36	9.01	9.38	9.22		0
	1	74	9.11	9.19	9.05		0
	36	0	8.82	9.30	9.01		0
	36	18	8.89	9.31	9.04		0
	36	37	9.05	9.25	9.00		0
	75	0	8.99	9.29	9.04		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 78 of 426

Table H-154
LTE Band 7 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	8.86	9.26	8.92	0	0
	1	25	8.80	9.29	8.91		0
	1	49	8.90	9.19	8.84		0
	25	0	8.90	9.29	9.10	0-1	0
	25	12	8.94	9.36	9.01		0
	25	25	8.98	9.26	8.92		0
	50	0	8.97	9.28	9.01		0
16QAM	1	0	9.02	9.40	9.06	0-1	0
	1	25	9.10	9.59	9.21		0
	1	49	9.20	9.48	9.05		0
	25	0	8.89	9.30	9.12	0-2	0
	25	12	8.98	9.32	9.00		0
	25	25	8.92	9.16	8.90		0
	50	0	8.97	9.24	9.03		0
64QAM	1	0	9.06	9.40	9.03	0-2	0
	1	25	9.05	9.36	9.16		0
	1	49	9.12	9.26	9.06		0
	25	0	8.91	9.36	9.03	0-3	0
	25	12	9.02	9.35	9.02		0
	25	25	9.03	9.24	8.92		0
	50	0	9.00	9.33	8.99		0
256QAM	1	0	8.97	9.23	9.03	0-5	0
	1	25	9.05	9.60	9.17		0
	1	49	9.10	9.38	9.06		0
	25	0	8.83	9.34	9.06		0
	25	12	9.05	9.32	9.01		0
	25	25	8.93	9.24	8.92		0
	50	0	8.97	9.26	9.01		0

Table H-155
LTE Band 7 Measured P_{Limit} for DSI = 4 (Folder Open-Grip) – 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	8.95	9.41	9.13	0	0
	1	12	8.89	9.27	9.01		0
	1	24	8.89	9.16	8.89		0
	12	0	8.82	9.28	8.94	0-1	0
	12	6	8.94	9.36	9.09		0
	12	13	8.93	9.30	8.86		0
16QAM	25	0	8.94	9.26	8.98	0-1	0
	1	0	8.91	9.57	9.15		0
	1	12	9.30	9.67	9.18		0
	1	24	9.09	9.50	9.02	0-2	0
	12	0	8.98	9.30	8.98		0
	12	6	8.98	9.40	9.00		0
64QAM	12	13	8.89	9.29	8.91	0-2	0
	25	0	8.94	9.29	8.98		0
	1	0	8.90	9.28	9.08		0
	1	12	9.01	9.58	9.07	0-2	0
	1	24	8.94	9.35	9.19		0
	12	0	8.92	9.22	8.98		0
256QAM	12	6	8.95	9.22	9.07	0-3	0
	12	13	8.97	9.23	8.91		0
	25	0	9.01	9.25	8.98		0
	1	0	8.89	9.24	8.99	0-5	0
	1	12	8.97	9.47	9.16		0
	1	24	9.00	9.25	9.10		0
12	0	8.86	9.24	9.03	0		
12	6	8.97	9.33	9.03	0		
12	13	8.96	9.26	8.92	0		
	25	0	8.96	9.29	9.03	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 79 of 426

Table H-156

LTE Band 7 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 15 MHz Bandwidth

LTE Band 7 15 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20825 (2507.5 MHz)	21100 (2535.0 MHz)	21375 (2562.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.32	16.77	16.44	0	0
	1	36	16.21	17.00	16.25		0
	1	74	16.47	16.63	16.36		0
	36	0	16.44	16.78	16.41	0-1	0
	36	18	16.47	16.83	16.41		0
	36	37	16.52	16.80	16.35		0
	75	0	16.55	16.86	16.40		0
16QAM	1	0	16.44	17.03	16.57	0-1	0
	1	36	16.67	17.10	16.68		0
	1	74	16.98	16.90	16.66		0
	36	0	16.45	16.87	16.52	0-2	0
	36	18	16.58	16.95	16.49		0
	36	37	16.60	16.80	16.30		0
	75	0	16.43	16.89	16.41		0
64QAM	1	0	16.43	16.90	16.51	0-2	0
	1	36	16.56	17.10	16.74		0
	1	74	16.62	16.75	16.54		0
	36	0	16.50	16.84	16.50	0-3	0
	36	18	16.60	16.86	16.47		0
	36	37	16.56	16.78	16.39		0
	75	0	16.52	16.84	16.53		0
256QAM	1	0	16.52	16.90	16.67	0-5	0
	1	36	16.60	17.09	16.48		0
	1	74	16.65	16.84	16.41		0
	36	0	16.45	16.88	16.42		0
	36	18	16.56	16.87	16.46		0
	36	37	16.59	16.87	16.38		0
	75	0	16.53	16.87	16.43		0

Table H-157

LTE Band 7 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 10 MHz Bandwidth

LTE Band 7 10 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20800 (2505.0 MHz)	21100 (2535.0 MHz)	21400 (2565.0 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.48	16.94	16.48	0	0
	1	25	16.44	16.81	16.42		0
	1	49	16.47	16.83	16.47		0
	25	0	16.52	16.93	16.52	0-1	0
	25	12	16.52	16.90	16.54		0
	25	25	16.60	16.92	16.51		0
	50	0	16.62	16.90	16.54		0
16QAM	1	0	16.60	17.06	16.66	0-1	0
	1	25	16.88	17.27	16.66		0
	1	49	16.85	17.22	16.70		0
	25	0	16.59	16.94	16.49	0-2	0
	25	12	16.64	16.96	16.51		0
	25	25	16.67	16.97	16.48		0
	50	0	16.62	16.93	16.54		0
64QAM	1	0	16.52	17.08	16.72	0-2	0
	1	25	16.65	17.20	16.45		0
	1	49	16.85	16.98	16.57		0
	25	0	16.60	16.91	16.54	0-3	0
	25	12	16.67	16.94	16.58		0
	25	25	16.63	16.95	16.53		0
	50	0	16.67	16.90	16.47		0
256QAM	1	0	16.45	17.02	16.78	0-5	0
	1	25	16.76	16.99	16.81		0
	1	49	16.45	16.87	16.54		0
	25	0	16.58	16.96	16.50		0
	25	12	16.66	17.00	16.65		0
	25	25	16.59	16.79	16.48		0
	50	0	16.65	16.92	16.46		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 80 of 426

Table H-158
LTE Band 7 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 5 MHz Bandwidth

LTE Band 7 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Low Channel	Mid Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			20775 (2502.5 MHz)	21100 (2535.0 MHz)	21425 (2567.5 MHz)		
			Conducted Power [dBm]				
QPSK	1	0	16.31	16.97	16.41	0	0
	1	12	16.57	17.07	16.55		0
	1	24	16.57	16.83	16.37		0
	12	0	16.37	16.90	16.42	0-1	0
	12	6	16.59	16.95	16.54		0
	12	13	16.55	16.99	16.38		0
	25	0	16.53	16.88	16.56		0
16QAM	1	0	16.55	17.16	16.89	0-1	0
	1	12	16.79	17.16	16.75		0
	1	24	16.75	17.02	16.68		0
	12	0	16.42	16.93	16.45	0-2	0
	12	6	16.63	17.01	16.62		0
	12	13	16.61	16.91	16.41		0
	25	0	16.51	16.90	16.52		0
64QAM	1	0	16.64	16.88	16.72	0-2	0
	1	12	16.75	17.12	16.73		0
	1	24	16.89	17.18	16.65		0
	12	0	16.44	16.85	16.49	0-3	0
	12	6	16.61	16.98	16.61		0
	12	13	16.64	16.94	16.53		0
	25	0	16.60	16.83	16.52		0
256QAM	1	0	16.53	16.89	16.45	0-5	0
	1	12	16.68	17.18	16.52		0
	1	24	16.69	17.10	16.62		0
	12	0	16.57	16.90	16.43		0
	12	6	16.65	16.98	16.61		0
	12	13	16.61	17.01	16.41		0
	25	0	16.54	16.82	16.48		0

H.1.21 LTE Band 41 Antenna B

Table H-159
LTE Band 41 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	23.41	23.80	23.68	23.84	24.47	0	0
	1	36	23.59	23.57	23.62	23.83	24.62		0
	1	74	23.63	23.51	23.57	23.79	24.37		0
	36	0	22.49	22.72	22.71	22.91	23.22	0-1	1
	36	18	22.66	22.72	22.84	22.91	23.25		1
	36	37	22.62	22.61	22.74	22.95	23.28		1
	75	0	22.59	22.69	22.79	22.94	23.23		1
16QAM	1	0	22.56	22.67	22.89	22.99	23.49	0-1	1
	1	36	22.55	22.68	22.67	22.88	23.55		1
	1	74	22.69	22.59	22.58	22.98	23.44		1
	36	0	21.57	21.73	21.78	21.93	22.27	0-2	2
	36	18	21.67	21.75	21.82	21.87	22.24		2
	36	37	21.66	21.62	21.74	21.91	22.28		2
	75	0	21.62	21.71	21.78	21.93	22.24		2
64QAM	1	0	21.74	21.74	21.82	22.03	22.62	0-2	2
	1	36	21.67	21.72	21.80	21.96	22.56		2
	1	74	21.71	21.60	21.77	21.97	22.52		2
	36	0	20.56	20.71	20.77	20.93	21.25	0-3	3
	36	18	20.65	20.71	20.82	20.91	21.28		3
	36	37	20.66	20.61	20.77	20.93	21.27		3
	75	0	20.64	20.66	20.81	21.01	21.21		3
256QAM	1	0	18.38	18.68	18.73	18.77	19.16	0-5	5
	1	36	18.64	18.59	18.73	18.89	19.22		5
	1	74	18.62	18.46	18.67	18.78	19.13		5
	36	0	18.51	18.66	18.74	18.90	19.24		5
	36	18	18.62	18.68	18.76	18.88	19.23		5
	36	37	18.67	18.57	18.76	18.91	19.27		5
	75	0	18.66	18.68	18.82	19.00	19.21		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 81 of 426

Table H-160

LTE Band 41 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth											
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]		
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)				
			Conducted Power [dBm]								
QPSK	1	0	23.50	23.85	23.77	23.90	24.64	0	0		
	1	25	23.60	23.50	23.78	23.86	24.97		0		
	1	49	23.63	23.52	23.66	23.84	24.52		0		
	25	0	22.56	22.73	22.83	23.01	23.32	0-1	1		
	25	12	22.67	22.73	22.87	23.04	23.28		1		
	25	25	22.68	22.67	22.86	23.02	23.33		1		
16QAM	50	0	22.64	22.73	22.85	23.04	23.25	0-1	1		
	1	0	22.53	22.63	22.87	22.90	23.48		1		
	1	25	22.59	22.65	22.90	23.09	23.68		1		
	1	49	22.63	22.60	22.72	22.93	23.56	0-2	1		
	25	0	21.60	21.78	21.83	22.00	22.29		2		
	25	12	21.74	21.82	21.87	22.06	22.32		2		
	25	25	21.68	21.69	21.87	22.01	22.34		2		
	50	0	21.67	21.74	21.88	22.00	22.33	0-2	2		
	64QAM	1	0	21.58	21.78	21.84	21.97		22.70	0-2	2
		1	25	21.71	21.83	21.90	22.09		22.84		2
1		49	21.73	21.66	21.79	21.91	22.46		2		
25		0	20.57	20.71	20.78	21.00	21.33		0-3	3	
25		12	20.70	20.79	20.86	21.06	21.29			3	
25		25	20.71	20.71	20.87	21.03	21.33	3			
50		0	20.70	20.73	20.92	21.02	21.30	3			
256QAM		1	0	18.36	18.55	18.66	18.92	19.24	0-5	5	
		1	25	18.55	18.67	18.77	18.84	19.40		5	
	1	49	18.69	18.49	18.67	18.82	19.27	5			
	25	0	18.54	18.71	18.79	18.96	19.31	5			
	25	12	18.72	18.72	18.87	19.01	19.31	5			
	25	25	18.66	18.62	18.82	18.97	19.32	5			
	50	0	18.69	18.70	18.82	19.04	19.30	5			

Table H-161

LTE Band 41 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	23.45	23.90	23.71	23.77	25.00	0	0	
	1	12	23.53	23.63	23.73	23.86	24.95		0	
	1	24	23.55	23.53	23.69	23.82	24.99		0	
	12	0	22.58	22.74	22.87	22.92	23.25	0-1	1	
	12	6	22.70	22.74	22.92	23.00	23.27		1	
	12	13	22.64	22.72	22.86	22.99	23.30		1	
16QAM	25	0	22.67	22.71	22.83	22.98	23.22	1	1	
	1	0	22.63	22.70	22.69	22.87	23.89		0-1	1
	1	12	22.50	22.67	22.80	22.92	24.00			1
	1	24	22.62	22.71	22.70	22.81	23.45	0-2		1
	12	0	21.61	21.75	21.86	21.91	22.27		2	
	12	6	21.71	21.76	21.91	22.04	22.25		2	
64QAM	12	13	21.69	21.77	21.84	21.97	22.34	2	2	
	25	0	21.67	21.73	21.81	22.00	22.23		0-2	2
	1	0	21.65	21.79	21.83	21.90	22.85			2
	1	12	21.78	21.84	21.82	22.07	22.56	0-3		2
	1	24	21.81	21.76	21.82	21.96	22.60		2	
	12	0	20.60	20.72	20.83	20.93	21.26		3	
256QAM	12	6	20.70	20.74	20.88	21.04	21.31	3	3	
	12	13	20.63	20.75	20.84	20.98	21.30		0-5	3
	25	0	20.69	20.73	20.85	21.01	21.18			3
	1	0	18.46	18.67	18.55	18.77	19.22	5		5
	1	12	18.59	18.67	18.90	18.93	19.29		5	
	1	24	18.51	18.42	18.61	18.83	19.12		5	
12	0	18.54	18.73	18.78	18.90	19.24	5			
12	6	18.64	18.72	18.85	19.03	19.27	5			
	12	13	18.68	18.64	18.77	18.98	19.28	5		
	25	0	18.64	18.69	18.79	19.00	19.22	5		

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 82 of 426

Table H-162

LTE Band 41 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	19.13	19.39	19.35	19.51	19.62	0	0
	1	36	19.18	19.22	19.27	19.46	19.89		0
	1	74	19.20	19.14	19.14	19.43	19.80		0
	36	0	19.28	19.37	19.43	19.60	19.92	0-1	0
	36	18	19.33	19.40	19.49	19.60	19.91		0
	36	37	19.35	19.27	19.44	19.60	19.92		0
	75	0	19.29	19.31	19.44	19.60	19.87		0
16QAM	1	0	19.12	19.26	19.44	19.49	20.57	0-1	0
	1	36	19.30	19.49	19.50	19.61	20.13		0
	1	74	19.38	19.25	19.42	19.47	20.08		0
	36	0	19.25	19.37	19.42	19.59	19.89	0-2	0
	36	18	19.35	19.39	19.47	19.58	19.90		0
	36	37	19.38	19.28	19.44	19.61	19.91		0
	75	0	19.29	19.30	19.41	19.62	19.83		0
64QAM	1	0	19.35	19.47	19.57	19.75	19.99	0-2	0
	1	36	19.45	19.49	19.42	19.62	19.82		0
	1	74	19.43	19.37	19.29	19.63	20.32		0
	36	0	19.25	19.37	19.43	19.62	19.88	0-3	0
	36	18	19.35	19.39	19.48	19.59	19.89		0
	36	37	19.41	19.32	19.45	19.65	19.96		0
	75	0	19.31	19.38	19.51	19.65	19.87		0
256QAM	1	0	18.33	18.53	18.72	18.90	19.22	0-5	0.5
	1	36	18.60	18.67	18.75	18.91	19.21		0.5
	1	74	18.67	18.58	18.60	18.73	19.07		0.5
	36	0	18.54	18.63	18.74	18.92	19.24		0.5
	36	18	18.65	18.67	18.78	18.88	19.25		0.5
	36	37	18.64	18.58	18.74	18.96	19.26		0.5
	75	0	18.66	18.71	18.79	18.97	19.24		0.5

Table H-163

LTE Band 41 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	19.13	19.26	19.38	19.58	19.83	0	0
	1	25	19.10	19.21	19.42	19.45	19.80		0
	1	49	19.17	19.22	19.27	19.48	19.93		0
	25	0	19.26	19.41	19.46	19.65	19.95	0-1	0
	25	12	19.34	19.40	19.56	19.70	19.98		0
	25	25	19.34	19.31	19.52	19.65	19.99		0
	50	0	19.30	19.39	19.51	19.66	19.95		0
16QAM	1	0	19.11	19.41	19.55	19.60	19.95	0-1	0
	1	25	19.23	19.38	19.32	19.57	19.91		0
	1	49	19.36	19.36	19.50	19.48	20.03		0
	25	0	19.24	19.38	19.47	19.65	19.97	0-2	0
	25	12	19.35	19.43	19.58	19.75	20.01		0
	25	25	19.36	19.33	19.51	19.69	20.03		0
	50	0	19.30	19.37	19.48	19.68	19.87		0
64QAM	1	0	19.29	19.46	19.89	19.74	20.30	0-2	0
	1	25	19.31	19.50	19.44	19.72	20.41		0
	1	49	19.34	19.35	19.53	19.59	20.45		0
	25	0	19.26	19.37	19.47	19.67	19.91	0-3	0
	25	12	19.36	19.42	19.56	19.70	20.00		0
	25	25	19.39	19.37	19.53	19.68	20.04		0
	50	0	19.39	19.42	19.56	19.70	19.96		0
256QAM	1	0	18.46	18.54	18.62	18.95	19.17	0-5	0.5
	1	25	18.60	18.63	18.77	18.97	19.29		0.5
	1	49	18.52	18.42	18.64	18.85	19.17		0.5
	25	0	18.54	18.73	18.79	18.98	19.26		0.5
	25	12	18.64	18.75	18.91	19.01	19.26		0.5
	25	25	18.69	18.65	18.81	18.99	19.30		0.5
	50	0	18.64	18.69	18.86	18.99	19.25		0.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 83 of 426

Table H-164

LTE Band 41 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	19.17	19.38	19.35	19.51	19.80	0	0
	1	12	19.28	19.37	19.40	19.57	20.06		0
	1	24	19.25	19.24	19.31	19.51	19.89		0
	12	0	19.21	19.39	19.52	19.59	19.92	0-1	0
	12	6	19.33	19.40	19.51	19.71	19.92		0
	12	13	19.30	19.36	19.50	19.64	19.97		0
16QAM	25	0	19.32	19.36	19.47	19.63	19.87	0-1	0
	1	0	19.33	19.35	19.47	19.51	20.02		0
	1	12	19.24	19.43	19.45	19.57	19.85		0
	1	24	19.36	19.26	19.44	19.63	19.98	0-2	0
	12	0	19.23	19.40	19.53	19.63	19.92		0
	12	6	19.33	19.41	19.48	19.69	19.94		0
64QAM	12	13	19.30	19.37	19.50	19.67	20.00	0-2	0
	25	0	19.30	19.38	19.50	19.66	19.91		0
	1	0	19.30	19.43	19.86	19.53	20.41		0-2
	1	12	19.45	19.53	19.82	19.75	20.26	0	
	1	24	19.34	19.19	19.59	19.72	20.11	0	
	12	0	19.24	19.39	19.48	19.61	19.97	0-3	0
12	6	19.33	19.42	19.56	19.66	19.95	0		
12	13	19.35	19.42	19.45	19.66	20.04	0		
256QAM	25	0	19.34	19.40	19.50	19.69	19.94	0-5	0
	1	0	18.50	18.51	18.62	18.78	19.18		0.5
	1	12	18.67	18.58	18.77	18.91	19.36		0.5
	1	24	18.53	18.52	18.71	18.81	19.15	0.5	
	12	0	18.58	18.68	18.79	18.86	19.25	0.5	
	12	6	18.68	18.70	18.87	19.02	19.29	0.5	
	12	13	18.63	18.67	18.80	19.00	19.29	0.5	
	25	0	18.64	18.70	18.79	18.97	19.19	0.5	

Table H-165

LTE Band 41 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 41 15 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39765 (2507.5 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	13.00	13.32	13.34	13.32	13.32	0	0
	1	36	13.03	13.42	13.41	13.40	13.43		0
	1	74	13.06	13.29	13.32	13.28	13.30		0
	36	0	12.99	13.42	13.39	13.40	13.39	0-1	0
	36	18	13.02	13.39	13.41	13.40	13.37		0
	36	37	13.10	13.42	13.42	13.43	13.39		0
	75	0	13.04	13.37	13.35	13.36	13.35		0
16QAM	1	0	12.83	13.39	13.43	13.38	13.33	0-1	0
	1	36	12.87	13.39	13.37	13.36	13.38		0
	1	74	12.91	13.24	13.30	13.14	13.22		0
	36	0	12.93	13.40	13.36	13.32	13.38	0-2	0
	36	18	13.04	13.35	13.38	13.37	13.36		0
	36	37	13.07	13.39	13.38	13.38	13.38		0
	75	0	12.99	13.34	13.32	13.33	13.30		0
64QAM	1	0	12.98	13.42	13.44	13.47	13.52	0-2	0
	1	36	13.04	13.44	13.46	13.66	13.46		0
	1	74	13.15	13.47	13.28	13.31	13.31		0
	36	0	12.98	13.41	13.39	13.38	13.39	0-3	0
	36	18	13.06	13.38	13.38	13.39	13.38		0
	36	37	13.07	13.37	13.38	13.38	13.40		0
	75	0	13.03	13.38	13.33	13.34	13.35		0
256QAM	1	0	12.87	13.44	13.29	13.35	13.37	0-5	0
	1	36	12.91	13.40	13.39	13.38	13.41		0
	1	74	12.88	13.32	13.28	13.29	13.32		0
	36	0	12.94	13.41	13.38	13.42	13.39		0
	36	18	13.10	13.39	13.35	13.37	13.39		0
	36	37	13.06	13.40	13.39	13.43	13.41		0
	75	0	13.05	13.34	13.33	13.39	13.31		0

Table H-166

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 84 of 426

LTE Band 41 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39740 (2505 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	13.00	12.94	13.07	13.24	13.43	0	0
	1	25	13.08	12.88	13.08	13.14	13.41		0
	1	49	13.03	12.84	12.99	13.17	13.39		0
	25	0	13.00	12.99	13.06	13.21	13.44	0-1	0
	25	12	13.08	13.01	13.13	13.22	13.43		0
	25	25	13.09	12.88	13.09	13.26	13.48		0
16QAM	50	0	13.04	12.96	13.09	13.17	13.50	0-1	0
	1	0	12.86	12.70	13.00	13.09	13.42		0
	1	25	12.94	12.94	13.12	13.15	13.42		0
	1	49	12.92	12.64	12.98	13.05	13.28	0-2	0
	25	0	12.95	12.91	13.05	13.18	13.43		0
	25	12	13.06	12.98	13.11	13.17	13.38		0
64QAM	25	25	13.05	12.83	13.09	13.19	13.47	0-2	0
	50	0	12.99	12.93	13.07	13.14	13.49		0
	1	0	12.93	12.87	13.10	13.18	13.37		0-3
	1	25	13.10	13.01	13.20	13.36	13.43	0	
	1	49	13.15	12.82	13.00	13.06	13.30	0	
	25	0	12.96	12.93	13.03	13.18	13.47	0-3	0
256QAM	25	12	13.06	12.92	13.10	13.16	13.44		0
	25	25	13.08	12.85	13.07	13.21	13.45		0
	50	0	13.04	12.94	13.11	13.17	13.43	0-5	0
	1	0	12.84	12.82	13.07	13.17	13.33		0
	1	25	12.99	12.87	13.03	13.30	13.43		0
	1	49	12.94	12.78	12.93	13.05	13.36	0	
256QAM	25	0	12.93	12.94	13.06	13.21	13.45	0-5	0
	25	12	13.03	12.97	13.14	13.19	13.40		0
	25	25	13.03	12.83	13.07	13.22	13.49		0
	50	0	13.02	12.99	13.10	13.18	13.49		0

Table H-167

LTE Band 41 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39715 (2502.5 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	12.89	12.87	12.94	13.10	13.35	0	0
	1	12	13.03	12.94	13.04	13.17	13.41		0
	1	24	13.00	12.80	12.91	13.11	13.33		0
	12	0	13.02	12.98	13.02	13.17	13.41	0-1	0
	12	6	13.05	13.00	13.10	13.20	13.44		0
	12	13	13.04	12.88	13.06	13.24	13.48		0
	25	0	13.02	12.95	13.11	13.18	13.47		0
16QAM	1	0	12.86	12.75	12.95	12.99	13.24	0-1	0
	1	12	12.97	12.91	13.08	13.15	13.44		0
	1	24	12.96	12.67	12.88	13.07	13.33		0
	12	0	12.95	12.92	13.04	13.17	13.43	0-2	0
	12	6	13.00	12.93	13.12	13.09	13.43		0
	12	13	12.99	12.86	13.06	13.21	13.50		0
	25	0	13.02	12.95	13.11	13.14	13.48		0
64QAM	1	0	13.02	12.97	13.10	13.09	13.54	0-2	0
	1	12	13.13	13.03	13.06	13.25	13.65		0
	1	24	12.87	12.84	13.03	13.20	13.44		0
	12	0	13.03	12.98	13.00	13.15	13.43	0-3	0
	12	6	13.04	12.97	13.09	13.17	13.43		0
	12	13	13.06	12.85	13.07	13.21	13.45		0
	25	0	13.00	12.93	13.07	13.14	13.47		0
256QAM	1	0	12.78	12.92	12.86	13.05	13.38	0-5	0
	1	12	12.94	12.89	13.00	13.19	13.44		0
	1	24	12.87	12.77	12.90	13.10	13.37		0
	12	0	13.03	12.95	13.02	13.13	13.42		0
	12	6	13.04	12.94	13.13	13.21	13.43		0
	12	13	13.02	12.85	13.04	13.23	13.48		0
	25	0	13.02	12.93	13.10	13.17	13.50		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 85 of 426

H.1.22 LTE Band 41 Antenna G

Table H-168

LTE Band 41 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39765 (2507.5 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.01	21.10	21.18	21.10	21.06	0	0
	1	36	21.21	21.10	21.13	21.10	21.02		0
	1	74	21.24	21.05	21.00	21.00	20.96		0
	36	0	21.14	21.15	21.21	21.15	21.17	0-1	0
	36	18	21.20	21.19	21.10	21.13	21.14		0
	36	37	21.23	21.09	21.03	21.03	21.01		0
	75	0	21.20	21.19	21.06	21.12	21.13		0
16QAM	1	0	21.03	21.10	21.13	21.17	21.08	0-1	0
	1	36	21.20	21.16	21.05	21.11	21.07		0
	1	74	21.23	21.12	20.98	20.99	20.95		0
	36	0	21.12	21.20	21.21	21.18	21.18	0-2	0
	36	18	21.26	21.21	21.08	21.19	21.18		0
	36	37	21.26	21.10	21.03	21.06	21.03		0
	75	0	21.22	21.18	21.04	21.13	21.13		0
64QAM	1	0	21.22	21.29	21.41	21.37	21.30	0-2	0
	1	36	21.28	21.39	21.20	21.21	21.28		0
	1	74	21.38	21.11	21.03	21.16	21.18		0
	36	0	21.15	21.15	21.24	21.18	21.19	0-3	0
	36	18	21.25	21.21	21.08	21.18	21.18		0
	36	37	21.26	21.11	21.02	21.04	21.02		0
	75	0	21.25	21.18	21.09	21.13	21.14		0
256QAM	1	0	19.02	19.14	19.13	19.17	19.04	0-5	2
	1	36	19.17	19.23	19.06	19.22	19.09		2
	1	74	19.21	19.10	18.94	18.95	18.75		2
	36	0	19.10	19.16	19.22	19.16	19.15		2
	36	18	19.23	19.21	19.12	19.14	19.16		2
	36	37	19.27	19.12	19.08	19.03	19.05		2
	75	0	19.23	19.19	19.09	19.13	19.16		2

Table H-169

LTE Band 41 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39740 (2505 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.10	21.11	21.32	21.20	21.16	0	0
	1	25	21.11	21.19	21.22	21.06	21.08		0
	1	49	21.15	21.12	21.14	21.06	21.01		0
	25	0	21.09	21.24	21.31	21.21	21.19	0-1	0
	25	12	21.20	21.25	21.18	21.25	21.24		0
	25	25	21.21	21.19	21.17	21.09	21.09		0
	50	0	21.25	21.25	21.18	21.19	21.17		0
16QAM	1	0	21.13	21.06	21.26	21.28	21.18	0-1	0
	1	25	21.20	21.33	21.18	21.18	21.10		0
	1	49	21.24	21.03	21.12	20.88	21.01		0
	25	0	21.14	21.24	21.29	21.26	21.20	0-2	0
	25	12	21.27	21.31	21.22	21.24	21.23		0
	25	25	21.26	21.16	21.13	21.14	21.10		0
	50	0	21.21	21.21	21.17	21.22	21.19		0
64QAM	1	0	21.22	21.26	21.37	21.25	21.34	0-2	0
	1	25	21.28	21.15	21.29	21.28	21.24		0
	1	49	21.34	21.14	21.23	21.06	21.16		0
	25	0	21.16	21.26	21.32	21.25	21.28	0-3	0
	25	12	21.29	21.26	21.20	21.24	21.24		0
	25	25	21.25	21.18	21.16	21.12	21.10		0
	50	0	21.27	21.25	21.18	21.18	21.23		0
256QAM	1	0	18.95	19.02	19.24	19.23	19.18	0-5	2
	1	25	19.19	19.16	19.31	19.19	19.14		2
	1	49	19.06	19.07	19.25	19.08	18.99		2
	25	0	19.15	19.24	19.30	19.27	19.22		2
	25	12	19.28	19.25	19.20	19.27	19.26		2
	25	25	19.26	19.18	19.12	19.13	19.10		2
	50	0	19.21	19.25	19.21	19.23	19.24		2

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 86 of 426

Table H-170
LTE Band 41 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39715 (2502.5 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	21.05	21.12	21.09	21.04	21.00	0	0
	1	12	21.16	21.19	21.19	21.14	21.10		0
	1	24	21.15	21.06	21.05	21.02	21.00		0
	12	0	21.20	21.23	21.23	21.21	21.18	0-1	0
	12	6	21.25	21.26	21.24	21.21	21.20		0
	12	13	21.20	21.13	21.12	21.09	21.17		0
16QAM	25	0	21.24	21.23	21.14	21.18	21.16	0-1	0
	1	0	21.07	21.14	21.10	21.05	21.06		0
	1	12	21.17	21.12	21.25	21.19	21.02		0
	1	24	21.12	21.10	20.99	21.04	21.02	0-2	0
	12	0	21.20	21.22	21.24	21.19	21.20		0
	12	6	21.23	21.26	21.23	21.20	21.21		0
64QAM	12	13	21.23	21.12	21.19	21.10	21.16	0-2	0
	25	0	21.24	21.23	21.15	21.22	21.17		0
	1	0	21.19	21.23	21.21	21.05	21.09		0-2
	1	12	21.29	21.22	21.32	21.20	21.25	0	
	1	24	21.19	21.21	21.11	21.17	20.99	0	
	12	0	21.27	21.24	21.21	21.17	21.20	0	
256QAM	12	6	21.25	21.26	21.23	21.26	21.19	0-3	0
	12	13	21.26	21.14	21.14	21.06	21.18		0
	25	0	21.26	21.28	21.19	21.21	21.15		0
	1	0	19.04	19.03	19.15	19.03	19.09	0-5	2
	1	12	19.20	19.28	19.20	19.15	19.03		2
	1	24	19.04	19.06	19.03	18.85	18.95		2
12	0	19.25	19.23	19.25	19.22	19.17	2		
12	6	19.23	19.25	19.27	19.19	19.19	2		
	12	13	19.21	19.18	19.10	19.09	19.17	2	
	25	0	19.21	19.27	19.16	19.17	19.19	2	

Table H-171
LTE Band 41 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.98	17.95	18.01	17.90	17.91	0	0
	1	36	17.99	18.01	17.90	17.84	17.89		0
	1	74	18.05	17.88	17.80	17.74	17.81		0
	36	0	17.90	18.01	17.94	17.90	17.95	0-1	0
	36	18	18.10	18.02	17.82	17.88	17.93		0
	36	37	18.00	17.90	17.78	17.87	17.83		0
	75	0	17.98	17.98	17.79	17.88	17.94		0
16QAM	1	0	18.10	18.04	17.84	17.93	17.90	0-1	0
	1	36	18.17	17.94	17.85	17.89	18.02		0
	1	74	18.05	17.85	17.59	17.72	17.94		0
	36	0	18.15	17.97	17.93	17.85	17.97	0-2	0
	36	18	17.94	18.01	17.83	17.88	17.96		0
	36	37	18.00	17.89	17.75	17.83	17.82		0
	75	0	17.99	17.98	17.80	17.89	17.93		0
64QAM	1	0	17.91	17.96	18.00	17.93	18.03	0-2	0
	1	36	17.99	18.23	18.06	17.99	17.97		0
	1	74	18.08	18.04	17.86	17.76	17.89		0
	36	0	17.95	18.01	17.93	17.89	17.92	0-3	0
	36	18	18.08	18.03	17.79	17.92	17.92		0
	36	37	17.99	17.89	17.78	17.86	17.84		0
	75	0	17.95	18.05	17.84	17.83	17.90		0
256QAM	1	0	17.88	17.85	17.78	17.78	17.92	0-5	0
	1	36	17.98	18.06	17.82	17.74	17.98		0
	1	74	17.89	17.84	17.57	17.59	17.72		0
	36	0	17.93	17.99	17.95	17.89	17.95		0
	36	18	18.10	18.02	17.81	17.87	17.95		0
	36	37	18.00	17.87	17.74	17.85	17.84		0
	75	0	17.96	17.98	17.83	17.84	17.97		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 87 of 426

Table H-172

LTE Band 41 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.96	17.94	17.99	17.94	17.97	0	0
	1	25	17.92	17.94	17.93	17.85	17.87		0
	1	49	17.97	17.92	17.90	17.82	17.91		0
	25	0	17.89	17.99	17.95	17.95	18.00	0-1	0
	25	12	18.02	18.02	17.95	17.94	18.02		0
	25	25	18.12	17.93	17.85	17.90	17.87		0
	50	0	18.00	18.01	17.83	17.91	17.97		0
16QAM	1	0	18.03	17.89	17.91	17.89	17.86	0-1	0
	1	25	18.06	17.97	17.93	17.75	17.84		0
	1	49	18.14	17.78	17.59	17.62	17.93		0
	25	0	18.03	18.02	18.01	17.96	18.05	0-2	0
	25	12	18.01	18.02	17.96	17.93	18.00		0
	25	25	18.02	17.94	17.81	17.87	17.89		0
	50	0	17.96	18.01	17.86	17.91	18.02		0
64QAM	1	0	17.88	18.02	17.96	17.98	18.05	0-2	0
	1	25	17.96	18.16	18.09	17.97	17.97		0
	1	49	17.97	17.84	18.01	17.89	17.96		0
	25	0	18.00	17.97	17.94	17.90	18.01	0-3	0
	25	12	18.01	18.04	17.91	17.92	18.01		0
	25	25	18.03	17.93	17.80	17.91	17.89		0
	50	0	17.93	17.97	17.83	17.90	17.98		0
256QAM	1	0	17.89	17.89	17.95	17.83	17.86	0-5	0
	1	25	17.99	17.96	17.77	17.74	17.86		0
	1	49	17.96	17.68	17.74	17.71	17.84		0
	25	0	17.94	17.96	17.93	17.95	17.99		0
	25	12	17.99	17.98	17.88	17.97	18.04		0
	25	25	17.96	17.89	17.84	17.93	17.87		0
	50	0	17.94	17.97	17.87	17.91	17.99		0

Table H-173

LTE Band 41 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	17.96	17.93	17.89	17.74	17.81	0	0
	1	12	17.92	17.98	17.88	17.84	17.93		0
	1	24	17.87	17.86	17.75	17.72	17.78		0
	12	0	17.96	18.05	17.91	17.94	17.99	0-1	0
	12	6	18.02	18.04	17.95	17.94	17.97		0
	12	13	18.10	17.99	17.90	17.86	17.94		0
	25	0	17.95	18.01	17.91	17.89	17.97		0
16QAM	1	0	18.02	17.95	17.99	17.86	17.99	0-1	0
	1	12	18.04	17.92	17.98	17.79	17.92		0
	1	24	18.10	17.95	17.62	17.71	17.90		0
	12	0	17.93	18.08	17.89	17.89	17.96	0-2	0
	12	6	17.98	18.06	17.91	17.90	18.00		0
	12	13	17.93	17.99	17.88	17.86	17.96		0
	25	0	17.97	18.02	17.92	17.88	17.97		0
64QAM	1	0	17.89	17.94	17.93	17.89	17.93	0-2	0
	1	12	18.10	18.06	17.95	17.88	18.05		0
	1	24	18.07	17.96	17.87	17.88	17.84		0
	12	0	17.96	18.01	17.94	17.85	17.96	0-3	0
	12	6	18.05	18.03	17.92	17.93	17.98		0
	12	13	18.00	17.94	17.89	17.86	17.95		0
	25	0	17.94	17.96	17.93	17.90	17.92		0
256QAM	1	0	17.84	17.88	17.78	17.85	17.90	0-5	0
	1	12	17.99	17.93	17.83	17.82	17.90		0
	1	24	17.89	17.64	17.65	17.71	17.76		0
	12	0	17.85	18.03	17.91	17.90	17.97		0
	12	6	17.99	17.98	17.90	17.92	17.94		0
	12	13	17.97	17.96	17.87	17.86	17.90		0
	25	0	17.95	18.02	17.95	17.88	17.94		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 88 of 426

Table H-174

LTE Band 41 Measured P_{limit} for DSI = 4 (Folder Open-Grip) – 15 MHz Bandwidth

LTE Band 41 15 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39765 (2507.5 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	11.11	11.05	11.08	10.91	10.89	0	0
	1	36	11.22	11.11	10.93	10.84	10.83		0
	1	74	11.20	11.07	10.83	10.75	10.71		0
	36	0	11.18	11.12	11.07	10.93	10.92	0-1	0
	36	18	11.27	11.20	10.95	10.86	10.92		0
	36	37	11.29	11.07	10.89	10.82	10.79		0
16QAM	75	0	11.23	11.15	10.94	10.88	10.90	0-1	0
	1	0	11.14	11.02	11.04	10.84	10.85		0
	1	36	11.22	11.13	10.90	10.92	10.81		0
	1	74	11.28	10.85	10.81	10.70	10.77	0-2	0
	36	0	11.17	11.14	11.06	10.94	10.95		0
	36	18	11.30	11.16	11.07	10.94	10.95		0
	36	37	11.31	11.02	10.92	10.85	10.80	0-2	0
	75	0	11.23	11.12	11.02	10.97	10.92		0
64QAM	1	0	10.95	11.22	11.14	11.08	11.00	0-2	0
	1	36	11.13	11.15	11.18	10.97	10.94		0
	1	74	11.14	11.06	11.02	10.85	10.84		0-3
	36	0	11.18	11.10	11.08	11.00	10.95	0	
	36	18	11.27	11.14	11.03	10.98	10.91	0	
	36	37	11.27	11.02	11.01	10.88	10.82	0	
256QAM	75	0	11.21	11.11	11.01	10.95	10.93	0-5	0
	1	0	10.97	11.03	11.01	10.92	10.88		0
	1	36	11.16	11.13	10.96	10.81	10.82		0
	1	74	11.08	10.95	10.76	10.73	10.78	0	
	36	0	11.12	11.13	11.03	10.99	10.98	0	
	36	18	11.28	11.12	11.01	10.96	10.92	0	
	36	37	11.23	11.07	10.94	10.83	10.84	0	
75	0	11.24	11.11	10.98	10.96	10.93	0		

Table H-175

LTE Band 41 Measured P_{limit} for DSI = 4 (Folder Open-Grip) – 10 MHz Bandwidth

LTE Band 41 10 MHzBandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39740 (2505 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	11.07	11.10	11.12	10.99	10.94	0	0
	1	25	11.18	11.08	11.01	10.88	10.90		0
	1	49	11.16	11.07	10.94	10.80	10.85		0
	25	0	11.14	11.17	11.12	10.99	10.97	0-1	0
	25	12	11.23	11.19	11.04	11.00	10.98		0
	25	25	11.25	11.15	10.95	10.85	10.85		0
16QAM	50	0	11.19	11.14	11.01	10.97	10.96	0-1	0
	1	0	11.10	11.03	10.97	10.92	10.89		0
	1	25	11.18	11.10	11.10	10.97	10.91		0
	1	49	11.24	10.95	10.82	10.86	10.76	0-2	0
	25	0	11.13	11.11	11.11	11.05	10.98		0
	25	12	11.26	11.17	11.05	11.03	11.01		0
64QAM	25	25	11.27	11.06	11.05	10.99	10.91	0-2	0
	50	0	11.19	11.16	11.06	11.03	11.02		0
	1	0	10.91	11.18	11.06	11.11	10.99		0-2
	1	25	11.09	11.06	11.10	11.04	11.12	0	
	1	49	11.10	11.08	11.06	10.98	10.99	0-3	
	25	0	11.14	11.09	11.13	11.08	11.05		0
256QAM	25	12	11.23	11.17	11.11	11.06	11.04		0-3
	25	25	11.23	11.06	11.10	11.02	10.99	0	
	50	0	11.17	11.11	11.07	11.02	11.02	0-5	
	1	0	10.93	11.04	11.03	11.04	10.95		0
	1	25	11.12	11.07	10.99	10.93	10.89		0
	1	49	11.04	10.87	10.98	10.81	10.72	0	
256QAM	25	0	11.08	11.10	11.07	11.03	10.99	0-5	0
	25	12	11.24	11.16	11.10	11.04	10.97		0
	25	25	11.19	11.06	11.04	10.99	10.96		0
	50	0	11.20	11.13	11.06	11.02	10.99	0	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 89 of 426

Table H-176
LTE Band 41 Measured P_{limit} for DSI = 4 (Folder Open-Grip) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel 39715 (2502.5 MHz)	Low-Mid Channel 40185 (2549.5 MHz)	Mid Channel 40620 (2593.0 MHz)	Mid-High Channel 41055 (2636.5 MHz)	High Channel 41490 (2680.0 MHz)	MPR Allowed per 3GPP [dB]
Conducted Power [dBm]								
QPSK	1	0	11.09	11.05	10.92	10.78	10.79	0
	1	12	11.20	11.13	11.00	10.88	10.86	
	1	24	11.18	11.01	10.86	10.77	10.74	
	12	0	11.16	11.16	11.11	10.97	10.96	0-1
	12	6	11.25	11.18	11.02	10.98	10.96	
	12	13	11.27	11.05	10.98	10.90	10.93	
	25	0	11.21	11.15	10.98	10.94	10.89	
16QAM	1	0	11.12	10.98	10.88	10.80	10.79	0-1
	1	12	11.20	11.14	11.08	10.91	10.83	
	1	24	11.26	10.82	10.86	10.80	10.80	
	12	0	11.15	11.16	11.05	10.97	10.94	0-2
	12	6	11.28	11.14	11.04	10.97	10.95	
	12	13	11.29	11.02	11.00	10.94	10.96	
	25	0	11.21	11.14	11.02	10.97	10.96	
64QAM	1	0	10.93	11.03	11.05	10.92	10.97	0-2
	1	12	11.11	11.21	11.15	10.95	11.12	
	1	24	11.12	11.02	10.94	10.89	10.86	
	12	0	11.16	11.12	11.01	11.00	11.00	0-3
	12	6	11.25	11.14	11.11	11.02	11.01	
	12	13	11.25	11.01	11.05	11.03	11.00	
	25	0	11.19	11.12	11.02	11.00	10.95	
256QAM	1	0	10.95	11.03	10.98	10.80	10.69	0-5
	1	12	11.14	11.10	10.99	10.92	10.96	
	1	24	11.06	10.94	10.82	10.79	10.63	
	12	0	11.10	11.14	11.08	11.01	10.98	
	12	6	11.26	11.13	11.07	11.01	10.96	
	12	13	11.26	11.04	11.04	10.91	10.93	
	25	0	11.27	11.15	11.02	10.99	10.93	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 90 of 426

Table H-177

LTE Band 41 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 15 MHz Bandwidth

LTE Band 41 15 MHz Bandwidth										
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)			
			Conducted Power [dBm]							
QPSK	1	0	18.36	18.41	18.45	18.43	18.40	0	0	
	1	36	18.46	18.43	18.46	18.34	18.39		0-1	0
	1	74	18.52	18.41	18.35	18.34	18.29			0
	36	0	18.42	18.49	18.43	18.43	18.47	0		
	36	18	18.51	18.50	18.32	18.37	18.46	0		
	36	37	18.53	18.40	18.31	18.37	18.32	0		
	75	0	18.44	18.51	18.32	18.40	18.42	0		
16QAM	1	0	18.26	18.45	18.39	18.42	18.37	0-1	0	
	1	36	18.46	18.41	18.35	18.18	18.28		0-2	0
	1	74	18.48	18.32	18.36	18.22	18.19			0
	36	0	18.40	18.51	18.45	18.42	18.48	0		
	36	18	18.51	18.50	18.30	18.38	18.44	0		
	36	37	18.52	18.42	18.22	18.34	18.31	0		
	75	0	18.45	18.50	18.30	18.34	18.43	0		
64QAM	1	0	18.43	18.57	18.61	18.38	18.50	0-2	0	
	1	36	18.62	18.54	18.42	18.42	18.57		0-3	0
	1	74	18.56	18.57	18.44	18.33	18.51			0
	36	0	18.33	18.50	18.40	18.39	18.48	0		
	36	18	18.47	18.50	18.30	18.37	18.46	0		
	36	37	18.48	18.40	18.26	18.31	18.31	0		
	75	0	18.43	18.47	18.32	18.36	18.41	0		
256QAM	1	0	18.23	18.40	18.31	18.32	18.40	0-5	0	
	1	36	18.45	18.46	18.36	18.46	18.47		0	
	1	74	18.46	18.30	18.12	18.10	18.16		0	
	36	0	18.32	18.46	18.43	18.40	18.47		0	
	36	18	18.47	18.46	18.33	18.40	18.45		0	
	36	37	18.48	18.36	18.24	18.31	18.32		0	
	75	0	18.44	18.50	18.30	18.39	18.44		0	

Table H-178

LTE Band 41 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 10 MHz Bandwidth

LTE Band 41 10 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	18.25	18.44	18.48	18.48	18.51	0	0
	1	25	18.33	18.44	18.38	18.39	18.42		0
	1	49	18.42	18.42	18.39	18.35	18.40		0
	25	0	18.31	18.47	18.48	18.47	18.53	0	
	25	12	18.44	18.52	18.48	18.50	18.56	0	
	25	25	18.39	18.41	18.37	18.42	18.42	0	
	50	0	18.40	18.45	18.40	18.47	18.51	0	
16QAM	1	0	18.31	18.39	18.42	18.34	18.43	0-1	0
	1	25	18.40	18.60	18.32	18.42	18.36		0
	1	49	18.30	18.25	18.17	18.29	18.24		0
	25	0	18.31	18.47	18.47	18.41	18.49	0	
	25	12	18.48	18.54	18.47	18.45	18.51	0	
	25	25	18.48	18.42	18.31	18.40	18.37	0	
	50	0	18.40	18.49	18.32	18.38	18.48	0	
64QAM	1	0	18.46	18.44	18.53	18.44	18.49	0-2	0
	1	25	18.54	18.53	18.62	18.52	18.51		0
	1	49	18.51	18.50	18.38	18.30	18.45		0
	25	0	18.32	18.47	18.45	18.42	18.47	0	
	25	12	18.40	18.52	18.45	18.40	18.51	0	
	25	25	18.40	18.41	18.29	18.39	18.34	0	
	50	0	18.44	18.44	18.37	18.41	18.51	0	
256QAM	1	0	18.22	18.35	18.33	18.41	18.41	0-5	0
	1	25	18.33	18.51	18.48	18.33	18.33		0
	1	49	18.34	18.37	18.13	18.22	18.19		0
	25	0	18.31	18.52	18.49	18.44	18.52		0
	25	12	18.44	18.54	18.47	18.50	18.50		0
	25	25	18.48	18.41	18.32	18.40	18.39		0
	50	0	18.41	18.50	18.38	18.43	18.50		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by:
DUT Type: Portable Handset		Technical Manager
		APPENDIX H: Page 91 of 426

Table H-179
LTE Band 41 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 5 MHz Bandwidth

LTE Band 41 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			39750 (2506.0 MHz)	40185 (2549.5 MHz)	40620 (2593.0 MHz)	41055 (2636.5 MHz)	41490 (2680.0 MHz)		
			Conducted Power [dBm]						
QPSK	1	0	18.26	18.38	18.33	18.30	18.37	0	0
	1	12	18.37	18.49	18.38	18.36	18.43		0
	1	24	18.40	18.35	18.28	18.26	18.30		0
	12	0	18.33	18.51	18.46	18.42	18.51	0-1	0
	12	6	18.39	18.52	18.45	18.44	18.50		0
	12	13	18.43	18.44	18.41	18.39	18.45		0
	25	0	18.41	18.47	18.42	18.41	18.47		0
16QAM	1	0	18.25	18.39	18.26	18.36	18.32	0-1	0
	1	12	18.50	18.44	18.28	18.26	18.35		0
	1	24	18.43	18.37	18.36	18.29	18.41		0
	12	0	18.32	18.49	18.41	18.38	18.44	0-2	0
	12	6	18.42	18.52	18.40	18.40	18.45		0
	12	13	18.47	18.50	18.38	18.33	18.42		0
	25	0	18.42	18.52	18.39	18.41	18.43		0
64QAM	1	0	18.39	18.45	18.36	18.39	18.41	0-2	0
	1	12	18.45	18.62	18.45	18.45	18.45		0
	1	24	18.44	18.44	18.25	18.30	18.42		0
	12	0	18.31	18.46	18.43	18.40	18.46	0-3	0
	12	6	18.45	18.51	18.47	18.43	18.48		0
	12	13	18.39	18.42	18.34	18.33	18.44		0
	25	0	18.44	18.45	18.37	18.34	18.43		0
256QAM	1	0	18.31	18.48	18.33	18.48	18.45	0-5	0
	1	12	18.45	18.48	18.29	18.21	18.42		0
	1	24	18.31	18.24	18.18	18.12	18.33		0
	12	0	18.37	18.52	18.45	18.41	18.48		0
	12	6	18.41	18.51	18.42	18.40	18.46		0
	12	13	18.42	18.48	18.43	18.40	18.46		0
	25	0	18.40	18.50	18.42	18.39	18.47		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 92 of 426

H.1.23 LTE Band 48 Antenna F

Table H-180

LTE Band 48 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open-Grip) – 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	10.75	10.50	10.48	10.54	0	0
	1	36	10.69	10.55	10.58	10.73		0
	1	74	10.75	10.59	10.65	10.75		0
	36	0	10.76	10.65	10.62	10.70	0-1	0
	36	18	10.78	10.74	10.71	10.78		0
	36	37	10.76	10.68	10.68	10.76		0
	75	0	10.72	10.72	10.68	10.83		0
16QAM	1	0	10.64	10.51	10.45	10.64	0-1	0
	1	36	10.81	10.63	10.63	10.61		0
	1	74	10.76	10.77	10.67	10.83		0
	36	0	10.77	10.68	10.62	10.69	0-2	0
	36	18	10.82	10.69	10.70	10.75		0
	36	37	10.81	10.66	10.66	10.75		0
	75	0	10.74	10.69	10.70	10.74		0
64QAM	1	0	10.75	10.50	10.55	10.58	0-2	0
	1	36	10.74	10.72	10.81	10.74		0
	1	74	10.87	10.65	10.75	10.93		0
	36	0	10.77	10.69	10.65	10.66	0-3	0
	36	18	10.87	10.73	10.72	10.78		0
	36	37	10.80	10.67	10.66	10.77		0
	75	0	10.75	10.70	10.73	10.80		0
256QAM	1	0	10.68	10.44	10.60	10.60	0-5	0
	1	36	10.79	10.67	10.61	10.79		0
	1	74	10.74	10.61	10.63	10.73		0
	36	0	10.81	10.65	10.65	10.72		0
	36	18	10.87	10.73	10.72	10.79		0
	36	37	10.79	10.67	10.67	10.75		0
	75	0	10.77	10.71	10.70	10.78		0

Table H-181

LTE Band 48 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open-Grip) – 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	10.76	10.63	10.61	10.64	0	0
	1	25	10.77	10.75	10.64	10.83		0
	1	49	10.83	10.73	10.68	10.84		0
	25	0	10.86	10.73	10.73	10.76	0-1	0
	25	12	10.89	10.76	10.77	10.81		0
	25	25	10.80	10.66	10.68	10.75		0
	50	0	10.78	10.71	10.77	10.81		0
16QAM	1	0	10.84	10.66	10.46	10.58	0-1	0
	1	25	10.89	10.67	10.66	10.74		0
	1	49	10.66	10.57	10.69	10.70		0
	25	0	10.88	10.73	10.69	10.76	0-2	0
	25	12	10.91	10.79	10.77	10.79		0
	25	25	10.82	10.69	10.64	10.73		0
	50	0	10.81	10.76	10.71	10.78		0
64QAM	1	0	10.80	10.67	10.56	10.69	0-2	0
	1	25	10.88	10.77	10.80	10.87		0
	1	49	10.79	10.71	10.78	10.87		0
	25	0	10.88	10.73	10.69	10.73	0-3	0
	25	12	10.91	10.78	10.72	10.81		0
	25	25	10.83	10.72	10.67	10.74		0
	50	0	10.82	10.79	10.74	10.77		0
256QAM	1	0	10.67	10.58	10.60	10.71	0-5	0
	1	25	10.74	10.73	10.64	10.77		0
	1	49	10.73	10.58	10.47	10.67		0
	25	0	10.88	10.74	10.68	10.76		0
	25	12	10.93	10.80	10.75	10.80		0
	25	25	10.84	10.65	10.68	10.75		0
	50	0	10.82	10.84	10.73	10.80		0

Table H-182

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 93 of 426

LTE Band 48 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open-Grip) – 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	10.75	10.64	10.63	10.67	0	0
	1	12	10.84	10.71	10.73	10.80		0
	1	24	10.72	10.58	10.64	10.73		0
	12	0	10.87	10.75	10.75	10.80	0-1	0
	12	6	10.83	10.82	10.76	10.85		0
	12	13	10.79	10.65	10.69	10.76		0
	25	0	10.80	10.78	10.75	10.81		0
16QAM	1	0	10.76	10.64	10.57	10.62	0-1	0
	1	12	10.83	10.67	10.54	10.77		0
	1	24	10.74	10.55	10.67	10.70		0
	12	0	10.84	10.72	10.71	10.78	0-2	0
	12	6	10.85	10.81	10.75	10.84		0
	12	13	10.82	10.66	10.65	10.77		0
	25	0	10.79	10.74	10.73	10.82		0
64QAM	1	0	10.85	10.66	10.67	10.80	0-2	0
	1	12	10.95	10.87	10.80	10.89		0
	1	24	10.86	10.75	10.71	10.89		0
	12	0	10.88	10.76	10.74	10.80	0-3	0
	12	6	10.87	10.83	10.83	10.86		0
	12	13	10.79	10.73	10.70	10.77		0
	25	0	10.78	10.76	10.73	10.83		0
256QAM	1	0	10.80	10.72	10.68	10.66	0-5	0
	1	12	10.91	10.72	10.70	10.82		0
	1	24	10.66	10.50	10.57	10.56		0
	12	0	10.91	10.84	10.73	10.81		0
	12	6	10.83	10.79	10.81	10.85		0
	12	13	10.82	10.63	10.65	10.75		0
	25	0	10.81	10.80	10.76	10.83		0

Table H-183

LTE Band 48 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	22.48	22.32	22.35	22.39	0	0
	1	36	22.58	22.40	22.48	22.44		0
	1	74	22.56	22.43	22.53	22.53		0
	36	0	21.91	21.82	21.88	21.87	0-1	0
	36	18	21.95	21.88	21.93	21.93		0
	36	37	21.93	21.82	21.89	21.90		0
	75	0	21.93	21.79	21.91	21.90		0
16QAM	1	0	21.77	21.72	21.67	21.80	0-1	0
	1	36	21.77	21.70	21.80	21.85		0
	1	74	21.82	21.76	21.84	21.83		0
	36	0	20.91	20.87	20.88	20.91	0-2	1
	36	18	20.99	20.90	20.95	20.93		1
	36	37	20.91	20.82	20.91	20.91		1
	75	0	20.97	20.75	20.85	20.99		1
64QAM	1	0	20.86	20.86	20.84	20.76	0-2	1
	1	36	20.92	20.86	20.89	21.06		1
	1	74	20.88	20.90	20.80	21.04		1
	36	0	19.92	19.87	19.88	19.88	0-3	2
	36	18	19.97	19.89	19.91	19.95		2
	36	37	19.90	19.81	19.88	19.90		2
	75	0	19.97	19.84	19.94	20.00		2
256QAM	1	0	17.78	17.75	17.69	17.74	0-5	4
	1	36	17.73	17.90	17.87	17.85		4
	1	74	17.72	17.73	17.74	17.83		4
	36	0	17.91	17.87	17.87	17.87	0-5	4
	36	18	17.96	17.89	17.94	17.95		4
	36	37	17.91	17.85	17.90	17.90		4
	75	0	18.00	17.86	17.94	17.95		4

Table H-184

LTE Band 48 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	22.50	22.38	22.47	22.45	0	0
	1	25	22.49	22.39	22.49	22.46		0
	1	49	22.56	22.44	22.61	22.53		0
	25	0	21.96	21.86	21.92	21.91	0-1	0
	25	12	21.97	21.83	21.96	21.97		0
	25	25	21.93	21.82	21.89	21.89		0
	50	0	21.88	21.80	21.99	21.91		0
16QAM	1	0	21.78	21.83	21.84	21.74	0-1	0
	1	25	21.89	21.85	21.75	21.89		0
	1	49	21.95	21.85	21.81	21.86		0
	25	0	20.99	20.92	20.93	20.94	0-2	1
	25	12	21.05	20.82	21.05	20.99		1
	25	25	20.96	20.81	20.91	20.88		1
	50	0	20.93	20.79	20.78	20.95		1
64QAM	1	0	21.00	20.85	20.86	20.88	0-2	1
	1	25	20.99	20.74	20.87	21.03		1
	1	49	20.88	20.91	20.84	20.92		1
	25	0	19.99	19.91	19.83	19.91	0-3	2
	25	12	20.03	19.84	19.94	19.96		2
	25	25	19.88	19.82	19.90	19.88		2
	50	0	19.93	19.89	19.98	19.95		2
256QAM	1	0	17.71	17.76	17.80	17.66	0-5	4
	1	25	17.93	17.79	17.93	17.88		4
	1	49	17.83	17.68	17.72	17.70		4
	25	0	17.96	17.92	17.92	17.92		4
	25	12	18.03	17.85	17.93	17.98		4
	25	25	17.94	17.88	17.90	17.85		4
	50	0	17.95	17.85	18.00	17.91		4

Table H-185

LTE Band 48 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 48								
5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	22.48	22.41	22.42	22.38	0	0
	1	12	22.54	22.47	22.52	22.47		0
	1	24	22.58	22.43	22.48	22.41		0
	12	0	21.90	21.86	21.90	21.87	0-1	0
	12	6	22.01	21.85	21.94	21.94		0
	12	13	21.88	21.81	21.83	21.87		0
	25	0	21.81	21.79	21.91	21.88		0
16QAM	1	0	21.84	21.73	21.73	21.80	0-1	0
	1	12	22.03	21.81	21.92	21.91		0
	1	24	21.91	21.93	21.79	21.77		0
	12	0	20.93	20.90	20.90	20.92	0-2	1
	12	6	20.99	20.85	20.95	20.97		1
	12	13	20.90	20.78	20.86	20.86		1
	25	0	20.86	20.82	20.94	20.89		1
64QAM	1	0	20.86	20.96	20.95	20.87	0-2	1
	1	12	21.01	21.04	21.00	20.98		1
	1	24	20.85	20.63	20.92	20.92		1
	12	0	19.96	19.87	19.93	19.87	0-3	2
	12	6	20.02	19.82	19.96	19.93		2
	12	13	19.90	19.77	19.85	19.90		2
	25	0	19.85	19.79	19.90	19.89		2
256QAM	1	0	17.72	17.78	17.86	17.69	0-5	4
	1	12	17.89	17.76	17.85	17.78		4
	1	24	17.67	17.78	17.59	17.66		4
	12	0	17.98	17.88	17.89	17.86		4
	12	6	17.96	17.81	17.98	17.91		4
	12	13	17.85	17.81	17.85	17.85		4
	25	0	17.91	17.79	17.89	17.86		4

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 95 of 426

Table H-186

LTE Band 48 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)			
			Conducted Power [dBm]						
QPSK	1	0	20.41	20.31	20.25	20.46	0	0	
	1	36	20.56	20.39	20.56	20.51		0	
	1	74	20.61	20.38	20.55	20.60		0	
	36	0	20.60	20.51	20.55	20.54	0-1	0	
	36	18	20.62	20.52	20.59	20.58		0	
	36	37	20.60	20.48	20.56	20.56		0	
16QAM	75	0	20.65	20.43	20.54	20.55	0		
	1	0	20.43	20.37	20.42	20.42	0		
	1	36	20.63	20.45	20.48	20.52	0-1	0	
	1	74	20.62	20.45	20.66	20.50		0	
	36	0	20.59	20.48	20.56	20.55	0-2	0	
	36	18	20.61	20.53	20.65	20.60		0	
	36	37	20.54	20.48	20.55	20.56		0	
	75	0	20.66	20.43	20.57	20.59		0	
	64QAM	1	0	20.54	20.49	20.60	20.45	0-2	0
		1	36	20.62	20.64	20.55	20.60		0
1		74	20.64	20.55	20.44	20.61	0		
36		0	19.81	19.81	19.85	19.85	0-3	0	
36		18	19.94	19.82	19.93	19.91		0	
36		37	19.92	19.77	19.86	19.89		0	
75		0	19.94	19.78	19.89	19.91		0	
256QAM		1	0	17.68	17.78	17.69	17.92	0-5	2
	1	36	17.85	17.82	17.82	17.84	2		
	1	74	17.90	17.72	17.79	17.83	2		
	36	0	17.87	17.83	17.88	17.86	2		
	36	18	17.97	17.86	17.90	17.89	2		
	36	37	17.88	17.79	17.84	17.84	2		
	75	0	17.93	17.85	17.90	17.94	2		

Table H-187

LTE Band 48 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	20.46	20.43	20.29	20.47	0	0
	1	25	20.61	20.38	20.28	20.40		0
	1	49	20.57	20.47	20.41	20.51		0
	25	0	20.63	20.56	20.54	20.57	0-1	0
	25	12	20.65	20.53	20.64	20.62		0
	25	25	20.58	20.49	20.56	20.58		0
	50	0	20.58	20.49	20.58	20.56		0
16QAM	1	0	20.47	20.39	20.51	20.53	0-1	0
	1	25	20.59	20.40	20.52	20.69		0
	1	49	20.61	20.45	20.62	20.56		0
	25	0	20.64	20.56	20.64	20.61	0-2	0
	25	12	20.64	20.54	20.67	20.62		0
	25	25	20.55	20.45	20.57	20.57		0
64QAM	50	0	20.60	20.45	20.59	20.59	0-2	0
	1	0	20.53	20.56	20.63	20.59		0
	1	25	20.78	20.66	20.62	20.64		0
	1	49	20.66	20.53	20.67	20.74	0-3	0
	25	0	19.93	19.84	19.94	19.85		0
	25	12	19.99	19.79	19.92	19.97		0
	25	25	19.87	19.79	19.87	19.83		0
256QAM	50	0	19.88	19.81	19.92	19.99	0-5	0
	1	0	17.92	17.86	17.72	17.80		2
	1	25	17.88	17.90	17.99	17.77		2
	1	49	17.80	17.75	17.79	17.85	0-5	2
	25	0	17.93	17.84	17.91	17.88		2
	25	12	17.97	17.79	17.95	17.86		2
	25	25	17.89	17.77	17.87	17.81		2
50	0	17.91	17.85	17.95	17.91	2		

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 96 of 426

Table H-188

LTE Band 48 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed-Grip) – 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth									
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]	
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)			
			Conducted Power [dBm]						
QPSK	1	0	20.58	20.49	20.44	20.40	0	0	
	1	12	20.60	20.53	20.52	20.53		0	
	1	24	20.54	20.48	20.49	20.45		0	
	12	0	20.67	20.58	20.66	20.61	0-1	0	
	12	6	20.74	20.56	20.69	20.64		0	
	12	13	20.63	20.53	20.52	20.56		0	
16QAM	25	0	20.61	20.55	20.64	20.57	0	0	
	1	0	20.59	20.46	20.56	20.57		0	
	1	12	20.65	20.55	20.61	20.60		0-1	0
	1	24	20.63	20.49	20.63	20.57	0		
	12	0	20.63	20.55	20.65	20.63	0-2		0
	12	6	20.76	20.53	20.71	20.64		0	
64QAM	12	13	20.58	20.52	20.57	20.62		0	0
	25	0	20.61	20.52	20.63	20.63	0		
	1	0	20.62	20.48	20.78	20.54	0-2		0
	1	12	20.76	20.63	20.61	20.77		0	
	1	24	20.76	20.49	20.65	20.46		0	
	12	0	20.01	19.87	19.93	19.94	0-3	0	
12	6	20.02	19.87	19.99	19.97	0			
12	13	19.91	19.79	19.88	19.96	0			
256QAM	25	0	19.91	19.81	19.92	19.96	0	0	
	1	0	17.76	17.80	17.83	17.79		0-5	2
	1	12	17.96	17.83	17.88	17.92			2
	1	24	17.79	17.65	17.85	17.83	0-5		2
	12	0	17.94	17.91	17.93	17.91		2	
	12	6	18.03	17.83	17.97	17.97		2	
256QAM	12	13	17.93	17.84	17.84	17.89	2	2	
	25	0	17.91	17.86	17.93	17.91		2	

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 97 of 426

H.1.24 LTE Band 48 Antenna C

Table H-189

LTE Band 48 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	23.27	22.70	23.22	23.07	0	0
	1	36	23.29	22.74	23.33	23.13		0
	1	74	23.19	22.75	23.35	23.18		0
	36	0	22.45	22.37	22.45	22.25	0-1	1
	36	18	22.45	22.41	22.49	22.32		1
	36	37	22.48	22.36	22.47	22.24		1
	75	0	22.41	22.40	22.47	22.30	1	
16QAM	1	0	21.95	21.51	22.33	22.03	0-1	1
	1	36	22.04	21.55	22.34	22.22		1
	1	74	22.10	21.60	22.42	22.23		1
	36	0	21.45	21.41	21.45	21.27	0-2	2
	36	18	21.42	21.45	21.32	21.33		2
	36	37	21.45	21.37	21.47	21.26		2
	75	0	21.40	21.30	21.50	21.32	2	
64QAM	1	0	21.13	20.47	21.34	21.26	0-2	2
	1	36	21.22	20.50	21.46	21.24		2
	1	74	21.27	20.53	21.48	21.32		2
	36	0	20.46	20.45	20.47	20.29	0-3	3
	36	18	20.41	20.43	20.49	20.32		3
	36	37	20.48	20.34	20.44	20.27		3
	75	0	20.43	20.36	20.51	20.33	3	
256QAM	1	0	18.06	18.00	18.27	18.21	0-5	5
	1	36	18.23	17.51	18.26	18.15		5
	1	74	18.10	17.55	18.40	18.17		5
	36	0	18.43	18.33	18.45	18.23		5
	36	18	18.41	18.39	18.49	18.29		5
	36	37	18.44	18.32	18.43	18.27		5
	75	0	18.43	18.20	18.50	18.32		5

Table H-190

LTE Band 48 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

LTE Band 48								
10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	23.25	22.96	23.34	23.07	0	0
	1	25	23.27	23.32	23.44	23.04		0
	1	49	23.14	23.22	23.42	23.00		0
	25	0	22.50	22.44	22.48	22.28	0-1	1
	25	12	22.45	22.45	22.53	22.36		1
	25	25	22.47	22.44	22.47	22.26		1
	50	0	22.43	22.40	22.50	22.31		1
16QAM	1	0	21.63	21.49	22.56	22.04	0-1	1
	1	25	21.75	21.55	22.48	22.16		1
	1	49	21.73	21.60	22.48	22.10		1
	25	0	21.53	21.43	21.50	21.31	0-2	2
	25	12	21.51	21.48	21.58	21.33		2
	25	25	21.47	21.40	21.47	21.31		2
	50	0	21.44	21.41	21.51	21.34	2	
64QAM	1	0	20.75	20.60	21.44	21.24	0-2	2
	1	25	20.76	20.50	21.54	21.33		2
	1	49	20.81	20.51	21.48	21.16		2
	25	0	20.52	20.48	20.51	20.34	0-3	3
	25	12	20.50	20.46	20.58	20.31		3
	25	25	20.47	20.35	20.46	20.27		3
	50	0	20.48	20.42	20.50	20.31		3
256QAM	1	0	17.71	17.60	18.40	17.92	0-5	5
	1	25	17.67	17.55	18.36	18.21		5
	1	49	17.59	17.55	18.43	17.99		5
	25	0	18.47	18.39	18.49	18.31		5
	25	12	18.46	18.42	18.57	18.31		5
	25	25	18.45	18.30	18.45	18.23		5
	50	0	18.46	18.42	18.57	18.41		5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 98 of 426

Table H-191
LTE Band 48 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	23.22	22.58	23.31	23.16	0	0
	1	12	23.44	22.63	23.42	23.21		0
	1	24	23.37	22.58	23.36	23.16		0
	12	0	22.50	22.43	22.50	22.32	0-1	1
	12	6	22.51	22.48	22.54	22.37		1
	12	13	22.43	22.37	22.44	22.32		1
	25	0	22.39	22.43	22.48	22.27		1
16QAM	1	0	21.79	21.60	21.74	22.19	0-1	1
	1	12	22.00	21.68	21.82	22.44		1
	1	24	21.89	21.70	21.83	22.22		1
	12	0	21.53	21.45	21.52	21.32	0-2	2
	12	6	21.50	21.40	21.60	21.36		2
	12	13	21.43	21.35	21.46	21.29		2
	25	0	21.49	21.44	21.52	21.32		2
64QAM	1	0	21.07	20.52	20.96	21.39	0-2	2
	1	12	21.11	20.55	20.93	21.33		2
	1	24	20.93	20.54	20.95	21.29		2
	12	0	20.50	20.41	20.50	20.32	0-3	3
	12	6	20.45	20.24	20.57	20.33		3
	12	13	20.41	20.36	20.41	20.35		3
	25	0	20.45	20.47	20.53	20.28		3
256QAM	1	0	17.98	17.65	17.84	18.09	0-5	5
	1	12	18.05	17.52	17.82	18.00		5
	1	24	17.97	17.69	17.70	18.06		5
	12	0	18.49	18.42	18.49	18.31		5
	12	6	18.49	18.44	18.49	18.30		5
	12	13	18.42	18.32	18.44	18.26		5
	25	0	18.45	18.46	18.51	18.30		5

Table H-192
LTE Band 48 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	20.56	20.53	20.46	20.44	0	0
	1	36	20.62	20.61	20.53	20.55		0
	1	74	20.61	20.67	20.55	20.72		0
	36	0	20.76	20.69	20.75	20.74	0-1	0
	36	18	20.79	20.79	20.84	20.80		0
	36	37	20.71	20.73	20.80	20.75		0
	75	0	20.70	20.76	20.80	20.77		0
16QAM	1	0	20.69	20.64	20.72	20.82	0-1	0
	1	36	20.85	20.72	20.81	20.84		0
	1	74	20.77	20.62	20.81	20.72		0
	36	0	20.75	20.72	20.77	20.69	0-2	0
	36	18	20.79	20.79	20.83	20.77		0
	36	37	20.74	20.73	20.78	20.75		0
	75	0	20.68	20.78	20.83	20.77		0
64QAM	1	0	20.70	20.74	20.82	20.69	0-2	0
	1	36	20.77	20.88	20.81	20.78		0
	1	74	20.74	20.79	20.89	20.86		0
	36	0	20.18	20.16	20.18	20.11	0-3	0
	36	18	20.21	20.17	20.24	20.20		0
	36	37	20.16	20.13	20.16	20.18		0
	75	0	20.11	20.23	20.20	20.25		0
256QAM	1	0	18.06	18.07	18.06	17.96	0-5	2
	1	36	18.04	18.11	18.16	18.04		2
	1	74	18.09	18.13	18.08	18.21		2
	36	0	18.15	18.13	18.20	18.16		2
	36	18	18.20	18.17	18.22	18.18		2
	36	37	18.11	18.15	18.18	18.17		2
	75	0	18.08	18.17	18.31	18.21		2

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 99 of 426

Table H-193

LTE Band 48 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	20.67	20.67	20.63	20.56	0	0
	1	25	20.64	20.71	20.58	20.64		0
	1	49	20.71	20.76	20.65	20.59		0
	25	0	20.80	20.77	20.83	20.78	0-1	0
	25	12	20.75	20.74	20.86	20.83		0
	25	25	20.75	20.75	20.79	20.78		0
16QAM	50	0	20.74	20.69	20.84	20.79	0	
	1	0	20.71	20.57	20.78	20.64	0-1	0
	1	25	20.84	20.84	20.78	20.60		0
	1	49	20.87	20.74	20.93	20.74		0
	25	0	20.80	20.83	20.80	20.78	0-2	0
	25	12	20.76	20.74	20.88	20.84		0
25	25	20.79	20.72	20.80	20.74	0		
64QAM	50	0	20.80	20.73	20.83	20.77	0-2	0
	1	0	20.45	20.75	20.78	20.84		0
	1	25	20.61	20.68	20.83	20.92		0
	1	49	20.45	20.86	20.91	20.87	0-3	0
	25	0	20.24	20.21	20.23	20.21		0
	25	12	20.19	20.13	20.30	20.22		0
256QAM	25	25	20.20	20.15	20.20	20.16	0-5	0
	50	0	20.17	20.14	20.29	20.24		0
	1	0	18.19	18.25	18.13	18.08		2
	1	25	18.19	18.12	18.18	18.11	2	
	1	49	18.28	18.04	18.05	17.98	2	
	25	0	18.21	18.16	18.27	18.19	2	

Table H-194

LTE Band 48 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	20.60	20.58	20.68	20.43	0	0
	1	12	20.71	20.68	20.71	20.66		0
	1	24	20.67	20.61	20.65	20.61		0
	12	0	20.79	20.76	20.83	20.76	0-1	0
	12	6	20.85	20.85	20.92	20.83		0
	12	13	20.71	20.69	20.86	20.81		0
	25	0	20.70	20.77	20.81	20.79		0
16QAM	1	0	20.72	20.67	20.76	20.67	0-1	0
	1	12	20.92	20.86	20.83	20.94		0
	1	24	20.64	20.71	20.85	20.89		0
	12	0	20.80	20.84	20.83	20.79	0-2	0
	12	6	20.85	20.81	20.90	20.80		0
	12	13	20.74	20.72	20.83	20.83		0
	25	0	20.74	20.78	20.84	20.77		0
64QAM	1	0	20.56	20.81	20.89	20.79	0-2	0
	1	12	20.57	20.81	20.95	20.86		0
	1	24	20.52	20.75	20.84	20.72		0
	12	0	20.24	20.19	20.21	20.17	0-3	0
	12	6	20.28	20.28	20.29	20.27		0
	12	13	20.15	20.11	20.31	20.25		0
	25	0	20.10	20.19	20.24	20.21		0
256QAM	1	0	18.29	17.99	18.18	17.99	0-5	2
	1	12	18.19	18.07	18.23	18.10		2
	1	24	18.25	18.01	18.06	17.98		2
	12	0	18.19	18.14	18.24	18.16		2
	12	6	18.27	18.23	18.29	18.26		2
	12	13	18.13	18.07	18.25	18.14		2
	25	0	18.12	18.20	18.22	18.19		2

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 100 of 426

Table H-195

LTE Band 48 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

LTE Band 48 15 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55315 (3557.5 MHz)	55765 (3602.5 MHz)	56215 (3647.5 MHz)	56665 (3692.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	12.84	12.70	12.67	12.58	0	0
	1	36	12.82	12.76	12.76	12.72		0
	1	74	12.90	12.82	12.75	12.70		0
	36	0	12.81	12.81	12.84	12.79	0-1	0
	36	18	12.87	12.85	12.88	12.81		0
	36	37	12.83	12.83	12.86	12.78		0
	75	0	12.85	12.85	12.88	12.80		0
16QAM	1	0	12.66	12.63	12.59	12.43	0-1	0
	1	36	12.65	12.69	12.62	12.68		0
	1	74	12.66	12.48	12.75	12.64		0
	36	0	12.69	12.69	12.71	12.69	0-2	0
	36	18	12.75	12.77	12.73	12.71		0
	36	37	12.72	12.70	12.72	12.70		0
	75	0	12.65	12.73	12.76	12.76		0
64QAM	1	0	12.53	12.70	12.70	12.67	0-2	0
	1	36	12.65	12.73	12.71	12.83		0
	1	74	12.73	12.77	12.75	12.66		0
	36	0	12.67	12.69	12.72	12.66	0-3	0
	36	18	12.73	12.69	12.78	12.72		0
	36	37	12.69	12.66	12.73	12.69		0
	75	0	12.64	12.70	12.80	12.74		0
256QAM	1	0	12.53	12.52	12.62	12.50	0-5	0
	1	36	12.77	12.56	12.72	12.65		0
	1	74	12.72	12.62	12.71	12.67		0
	36	0	12.65	12.67	12.71	12.67		0
	36	18	12.72	12.66	12.78	12.69		0
	36	37	12.68	12.65	12.71	12.73		0
	75	0	12.65	12.76	12.74	12.73		0

Table H-196

LTE Band 48 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

LTE Band 48 10 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55290 (3555.0 MHz)	55757 (3601.7 MHz)	56223 (3648.3 MHz)	56690 (3695.0 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	12.79	12.78	12.85	12.67	0	0
	1	25	12.79	12.77	12.78	12.72		0
	1	49	12.84	12.79	12.87	12.80		0
	25	0	12.91	12.88	12.95	12.77	0-1	0
	25	12	12.90	12.84	12.91	12.87		0
	25	25	12.86	12.81	12.87	12.77		0
	50	0	12.91	12.82	12.96	12.83		0
16QAM	1	0	12.76	12.53	12.64	12.57	0-1	0
	1	25	12.73	12.69	12.72	12.75		0
	1	49	12.68	12.62	12.72	12.68		0
	25	0	12.77	12.77	12.82	12.75	0-2	0
	25	12	12.74	12.76	12.84	12.78		0
	25	25	12.69	12.75	12.74	12.68		0
	50	0	12.68	12.69	12.80	12.78		0
64QAM	1	0	12.74	12.69	12.74	12.74	0-2	0
	1	25	12.87	12.74	12.87	12.87		0
	1	49	12.89	12.75	12.84	12.85		0
	25	0	12.76	12.75	12.79	12.73	0-3	0
	25	12	12.73	12.65	12.83	12.81		0
	25	25	12.69	12.71	12.77	12.73		0
	50	0	12.69	12.71	12.80	12.76		0
256QAM	1	0	12.56	12.56	12.68	12.46	0-5	0
	1	25	12.83	12.64	12.80	12.69		0
	1	49	12.55	12.53	12.58	12.62		0
	25	0	12.78	12.71	12.75	12.70		0
	25	12	12.70	12.66	12.82	12.77		0
	25	25	12.71	12.64	12.73	12.77		0
	50	0	12.72	12.65	12.82	12.65		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 101 of 426

Table H-197
LTE Band 48 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5
MHz Bandwidth

LTE Band 48 5 MHz Bandwidth								
Modulation	RB Size	RB Offset	Low Channel	Low-Mid Channel	Mid-High Channel	High Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			55265 (3552.5 MHz)	55748 (3600.8 MHz)	56232 (3649.2 MHz)	56715 (3697.5 MHz)		
			Conducted Power [dBm]					
QPSK	1	0	12.82	12.72	12.78	12.69	0	0
	1	12	12.87	12.83	12.89	12.79		0
	1	24	12.79	12.72	12.83	12.68		0
	12	0	12.90	12.87	12.93	12.80	0-1	0
	12	6	12.92	12.88	13.00	12.83		0
	12	13	12.82	12.81	12.84	12.81		0
	25	0	12.81	12.92	12.94	12.82		0
16QAM	1	0	12.80	12.74	12.72	12.56	0-1	0
	1	12	12.87	12.75	12.76	12.78		0
	1	24	12.73	12.61	12.63	12.69		0
	12	0	12.78	12.75	12.78	12.77	0-2	0
	12	6	12.78	12.81	12.82	12.80		0
	12	13	12.68	12.70	12.82	12.75		0
	25	0	12.71	12.79	12.79	12.75		0
64QAM	1	0	12.73	12.70	12.75	12.72	0-2	0
	1	12	12.87	12.69	12.78	12.89		0
	1	24	12.72	12.66	12.73	12.84		0
	12	0	12.73	12.72	12.80	12.76	0-3	0
	12	6	12.77	12.79	12.86	12.82		0
	12	13	12.66	12.64	12.77	12.75		0
	25	0	12.65	12.74	12.82	12.79		0
256QAM	1	0	12.58	12.65	12.60	12.69	0-5	0
	1	12	12.63	12.70	12.71	12.57		0
	1	24	12.54	12.48	12.59	12.58		0
	12	0	12.77	12.71	12.75	12.72		0
	12	6	12.76	12.75	12.87	12.77		0
	12	13	12.69	12.60	12.79	12.77		0
	25	0	12.67	12.71	12.75	12.73		0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 102 of 426

H.2 NR Lower Bandwidth RF Conducted Powers

H.2.1 NR Band n71 Antenna A and Antenna A+C

Table H-198

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.38	0	0.0
	1	80	24.19		0.0
	1	158	24.12		0.0
	80	0	23.31	0-1	1.0
	80	40	24.20	0	0.0
	80	80	23.22	0-1	1.0
	160	0	23.13		1.0
DFT-s-OFDM 16QAM	1	1	23.96	0-1	1.0
CP-OFDM QPSK	1	1	22.93	0-1.5	1.5

Table H-199

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.35	0	0.0
	1	67	24.27		0.0
	1	131	24.10		0.0
	64	0	23.23	0-1	1.0
	64	35	24.18	0	0.0
	64	69	23.15	0-1	1.0
	128	0	23.07		1.0
DFT-s-OFDM 16QAM	1	1	23.97	0-1	1.0
CP-OFDM QPSK	1	1	22.93	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 103 of 426

Table H-200

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.90	0	0.0
	1	53	23.91		0.0
	1	104	23.72		0.0
	50	0	22.97	0-1	1.0
	50	28	24.07	0	0.0
	50	56	22.89	0-1	1.0
	100	0	23.05		1.0
DFT-s-OFDM 16QAM	1	1	23.42	0-1	1.0
CP-OFDM QPSK	1	1	22.50	0-1.5	1.5

Table H-201

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.19	0	0.0
	1	40	24.17		0.0
	1	77	24.09		0.0
	36	0	23.25	0-1	1.0
	36	22	24.39	0	0.0
	36	43	23.11	0-1	1.0
	75	0	23.24		1.0
DFT-s-OFDM 16QAM	1	1	23.69	0-1	1.0
CP-OFDM QPSK	1	1	22.80	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 104 of 426

Table H-202

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.10	24.05	23.80	0	0.0
	1	26	24.19	24.04	23.87		0.0
	1	50	24.03	23.78	23.83		0.0
	25	0	23.31	23.08	22.89	0-1	1.0
	25	14	24.30	24.19	24.02	0	0.0
	25	27	23.21	23.11	22.93	0-1	1.0
	50	0	23.38	23.07	23.00		1.0
DFT-s-OFDM 16QAM	1	1	23.91	23.59	23.43	0-1	1.0
CP-OFDM QPSK	1	1	22.84	22.69	22.35	0-1.5	1.5

Table H-203

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.29	24.01	24.00	0	0.0
	1	13	24.35	23.89	23.98		0.0
	1	23	24.21	24.03	24.04		0.0
	12	0	23.30	23.21	23.14	0-1	1.0
	12	7	24.43	24.18	24.18	0	0.0
	12	13	23.29	23.09	23.11	0-1	1.0
	25	0	23.33	23.21	23.13		1.0
DFT-s-OFDM 16QAM	1	1	23.78	23.72	23.68	0-1	1.0
CP-OFDM QPSK	1	1	22.80	22.67	22.59	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 105 of 426

Table H-204

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.74	0	0.0
	1	80	18.62		0.0
	1	158	18.58		0.0
	80	0	18.71	0-1	0.0
	80	40	18.67	0	0.0
	80	80	18.45	0-1	0.0
	160	0	18.59		0.0
DFT-s-OFDM 16QAM	1	1	18.97	0-1	0.0
CP-OFDM QPSK	1	1	18.78	0-1.5	0.0

Table H-205

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.76	0	0.0
	1	67	18.65		0.0
	1	131	18.49		0.0
	64	0	18.61	0-1	0.0
	64	35	18.65	0	0.0
	64	69	18.46	0-1	0.0
	128	0	18.55		0.0
DFT-s-OFDM 16QAM	1	1	18.96	0-1	0.0
CP-OFDM QPSK	1	1	18.71	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 106 of 426

Table H-206

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.37	0	0.0
	1	53	18.25		0.0
	1	104	18.13		0.0
	50	0	18.40	0-1	0.0
	50	28	18.38	0	0.0
	50	56	18.22	0-1	0.0
	100	0	18.45		0.0
DFT-s-OFDM 16QAM	1	1	18.83	0-1	0.0
CP-OFDM QPSK	1	1	18.38	0-1.5	0.0

Table H-207

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.59	0	0.0
	1	40	18.39		0.0
	1	77	18.39		0.0
	36	0	18.46	0-1	0.0
	36	22	18.54	0	0.0
	36	43	18.37	0-1	0.0
	75	0	18.58		0.0
DFT-s-OFDM 16QAM	1	1	18.98	0-1	0.0
CP-OFDM QPSK	1	1	18.58	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 107 of 426

Table H-208

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.54	18.49	18.40	0	0.0
	1	26	18.65	18.43	18.33		0.0
	1	50	18.54	18.31	18.29		0.0
	25	0	18.71	18.49	18.40	0-1	0.0
	25	14	18.80	18.53	18.47	0	0.0
	25	27	18.65	18.40	18.32	0-1	0.0
	50	0	18.71	18.54	18.40		0.0
DFT-s-OFDM 16QAM	1	1	19.13	18.54	18.86	0-1	0.0
CP-OFDM QPSK	1	1	18.76	18.49	18.48	0-1.5	0.0

Table H-209

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.75	18.60	18.46	0	0.0
	1	13	18.68	18.48	18.41		0.0
	1	23	18.67	18.48	18.38		0.0
	12	0	18.87	18.60	18.54	0-1	0.0
	12	7	18.81	18.61	18.49	0	0.0
	12	13	18.82	18.57	18.47	0-1	0.0
	25	0	18.86	18.56	18.46		0.0
DFT-s-OFDM 16QAM	1	1	19.32	18.96	19.06	0-1	0.0
CP-OFDM QPSK	1	1	18.72	18.72	18.66	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 108 of 426

H.2.2 NR Band n71 Antenna E

Table H-210

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.45	0	0.0
	1	80	24.28		0.0
	1	158	24.00		0.0
	80	0	23.19	0-1	1.0
	80	40	24.28	0	0.0
	80	80	23.06	0-1	1.0
	160	0	23.16		1.0
DFT-s-OFDM 16QAM	1	1	23.99	0-1	1.0
CP-OFDM QPSK	1	1	22.88	0-1.5	1.5

Table H-211

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.35	0	0.0
	1	67	24.20		0.0
	1	131	24.05		0.0
	64	0	23.32	0-1	1.0
	64	35	24.26	0	0.0
	64	69	23.13	0-1	1.0
	128	0	23.19		1.0
DFT-s-OFDM 16QAM	1	1	24.00	0-1	1.0
CP-OFDM QPSK	1	1	22.99	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 109 of 426

Table H-212

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.90	0	0.0
	1	53	23.77		0.0
	1	104	23.64		0.0
	50	0	23.06	0-1	1.0
	50	28	24.02	0	0.0
	50	56	22.92	0-1	1.0
	100	0	23.09		1.0
DFT-s-OFDM 16QAM	1	1	23.48	0-1	1.0
CP-OFDM QPSK	1	1	22.62	0-1.5	1.5

Table H-213

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.21	0	0.0
	1	40	24.03		0.0
	1	77	24.03		0.0
	36	0	23.18	0-1	1.0
	36	22	24.32	0	0.0
	36	43	23.08	0-1	1.0
	75	0	23.25		1.0
DFT-s-OFDM 16QAM	1	1	23.83	0-1	1.0
CP-OFDM QPSK	1	1	22.74	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 110 of 426

Table H-214

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.36	24.13	23.86	0	0.0
	1	26	24.19	24.12	23.86		0.0
	1	50	24.34	23.85	23.81		0.0
	25	0	23.48	23.25	22.94	0-1	1.0
	25	14	24.54	24.28	23.97	0	0.0
	25	27	23.33	23.08	22.83	0-1	1.0
	50	0	23.40	23.14	22.99		1.0
DFT-s-OFDM 16QAM	1	1	23.91	23.70	23.50	0-1	1.0
CP-OFDM QPSK	1	1	22.86	22.70	22.39	0-1.5	1.5

Table H-215

NR Band n71 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.23	24.12	23.88	0	0.0
	1	13	24.32	24.13	23.81		0.0
	1	23	24.10	24.00	23.88		0.0
	12	0	23.49	23.23	22.98	0-1	1.0
	12	7	24.55	24.29	23.99	0	0.0
	12	13	23.40	23.05	23.01	0-1	1.0
	25	0	23.54	23.20	23.04		1.0
DFT-s-OFDM 16QAM	1	1	23.94	23.82	23.53	0-1	1.0
CP-OFDM QPSK	1	1	23.15	22.79	22.62	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 111 of 426

Table H-216

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n71 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.23	0	0.0
	1	80	18.96		0.0
	1	158	18.86		0.0
	80	0	19.03	0-1	0.0
	80	40	18.96	0-1	0.0
	80	80	18.76		0.0
	160	0	18.91		0.0
DFT-s-OFDM 16QAM	1	1	19.60	0-1	0.0
CP-OFDM QPSK	1	1	19.36	0-1.5	0.0

Table H-217

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n71 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.21	0	0.0
	1	67	18.92		0.0
	1	131	18.86		0.0
	64	0	18.99	0-1	0.0
	64	35	19.03	0-1	0.0
	64	69	18.88		0.0
	128	0	18.89		0.0
DFT-s-OFDM 16QAM	1	1	19.55	0-1	0.0
CP-OFDM QPSK	1	1	19.27	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 112 of 426

Table H-218

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n71 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.83	0	0.0
	1	53	18.70		0.0
	1	104	18.33		0.0
	50	0	18.85	0-1	0.0
	50	28	18.83	0	0.0
	50	56	18.62	0-1	0.0
	100	0	18.80		0.0
DFT-s-OFDM 16QAM	1	1	19.24	0-1	0.0
CP-OFDM QPSK	1	1	18.82	0-1.5	0.0

Table H-219

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n71 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			136100 (680.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.00	0	0.0
	1	40	18.84		0.0
	1	77	18.65		0.0
	36	0	18.97	0-1	0.0
	36	22	19.09	0	0.0
	36	43	18.83	0-1	0.0
	75	0	18.94		0.0
DFT-s-OFDM 16QAM	1	1	19.48	0-1	0.0
CP-OFDM QPSK	1	1	19.05	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 113 of 426

Table H-220

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n71 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133600 (668 MHz)	136100 (680.5 MHz)	138600 (693 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.08	18.83	18.66	0	0.0
	1	26	19.01	18.80	18.59		0.0
	1	50	18.87	18.63	18.61		0.0
	25	0	19.17	18.80	18.68	0-1	0.0
	25	14	19.08	18.97	18.68	0	0.0
	25	27	19.03	18.88	18.69	0-1	0.0
	50	0	19.16	18.97	18.66		0.0
DFT-s-OFDM 16QAM	1	1	19.55	19.28	18.25	0-1	0.0
CP-OFDM QPSK	1	1	19.12	18.90	18.72	0-1.5	0.0

Table H-221

NR Band n71 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n71 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	133100 (665.5 MHz)	136100 (680.5 MHz)	139100 (695.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.15	18.91	18.68	0	0.0
	1	13	19.22	18.78	18.72		0.0
	1	23	19.12	18.77	18.73		0.0
	12	0	19.28	18.95	18.76	0-1	0.0
	12	7	19.39	18.99	18.77	0	0.0
	12	13	19.27	18.88	18.75	0-1	0.0
	25	0	19.37	18.93	18.78		0.0
DFT-s-OFDM 16QAM	1	1	19.50	19.20	18.20	0-1	0.0
CP-OFDM QPSK	1	1	19.50	19.16	18.92	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 114 of 426

H.2.3 NR Band n12 Antenna A and Antenna A+C

Table H-222

NR Band n12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	24.18	0	0.0
	1	26	24.21		0.0
	1	50	24.04		0.0
	25	0	23.13	0-1	1.0
	25	14	24.26	0	0.0
	25	27	23.16	0-1	1.0
	50	0	23.18		1.0
DFT-s-OFDM 16QAM	1	1	23.83	0-1	1.0
CP-OFDM QPSK	1	1	22.75	0-1.5	1.5

Table H-223

NR Band n12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.08	24.06	23.92	0	0.0
	1	13	24.12	24.09	24.08		0.0
	1	23	24.06	24.09	24.00		0.0
	12	0	23.13	23.15	23.09	0-1	1.0
	12	7	24.17	24.20	24.15	0	0.0
	12	13	23.15	23.15	23.02	0-1	1.0
	25	0	23.16	23.14	23.00		1.0
DFT-s-OFDM 16QAM	1	1	23.80	23.69	23.63	0-1	1.0
CP-OFDM QPSK	1	1	22.67	22.64	22.64	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 115 of 426

Table H-224

NR Band n12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.50	0	0.0
	1	26	18.54		0.0
	1	50	18.40		0.0
	25	0	18.56	0-1	0.0
	25	14	18.63	0	0.0
	25	27	18.54	0-1	0.0
	50	0	18.50		0.0
DFT-s-OFDM 16QAM	1	1	18.92	0-1	0.0
CP-OFDM QPSK	1	1	18.59	0-1.5	0.0

Table H-225

NR Band n12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.40	18.48	18.39	0	0.0
	1	13	18.41	18.45	18.34		0.0
	1	23	18.47	18.40	18.34		0.0
	12	0	18.49	18.58	18.45	0-1	0.0
	12	7	18.50	18.58	18.40	0	0.0
	12	13	18.59	18.49	18.40	0-1	0.0
	25	0	18.56	18.58	18.43		0.0
DFT-s-OFDM 16QAM	1	1	18.99	18.96	18.92	0-1	0.0
CP-OFDM QPSK	1	1	18.54	18.69	18.50	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 116 of 426

H.2.4 NR Band n12 Antenna E

Table H-226

NR Band n12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.56	0	0.0
	1	26	23.71		0.0
	1	50	23.46		0.0
	25	0	22.62	0-1	1.0
	25	14	23.62	0	0.0
	25	27	22.56	0-1	1.0
	50	0	22.56		1.0
DFT-s-OFDM 16QAM	1	1	23.25	0-1	1.0
CP-OFDM QPSK	1	1	22.18	0-1.5	1.5

Table H-227

NR Band n12 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.50	23.55	23.48	0	0.0
	1	13	23.56	23.56	23.46		0.0
	1	23	23.51	23.48	23.32		0.0
	12	0	22.69	22.63	22.50	0-1	1.0
	12	7	23.71	23.62	23.52	0	0.0
	12	13	22.62	22.52	22.46	0-1	1.0
	25	0	22.60	22.60	22.47		1.0
DFT-s-OFDM 16QAM	1	1	23.20	23.40	22.98	0-1	1.0
CP-OFDM QPSK	1	1	22.22	22.20	22.13	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 117 of 426

Table H-228

NR Band n12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n12 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			141500 (707.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.50	0	0.0
	1	26	18.42		0.0
	1	50	18.29		0.0
	25	0	18.47	0-1	0.0
	25	14	18.48	0	0.0
	25	27	18.35	0-1	0.0
	50	0	18.42		0.0
DFT-s-OFDM 16QAM	1	1	18.98	0-1	0.0
CP-OFDM QPSK	1	1	18.49	0-1.5	0.0

Table H-229

NR Band n12 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n12 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	140300 (701.5 MHz)	141500 (707.5 MHz)	142700 (713.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.45	18.40	18.18	0	0.0
	1	13	18.44	18.43	18.29		0.0
	1	23	18.45	18.33	18.18		0.0
	12	0	18.47	18.45	18.24	0-1	0.0
	12	7	18.60	18.52	18.29	0	0.0
	12	13	18.46	18.31	18.22	0-1	0.0
	25	0	18.51	18.42	18.23		0.0
DFT-s-OFDM 16QAM	1	1	19.01	18.95	18.81	0-1	0.0
CP-OFDM QPSK	1	1	18.51	18.50	18.37	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 118 of 426

H.2.5 NR Band n14 Antenna A and Antenna A+C

Table H-230

NR Band n14 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.73	18.74	0	0.0
	1	13	18.88	18.80		0.0
	1	23	18.71	18.69		0.0
	12	0	18.87	18.80	0-1	0.0
	12	7	19.03	18.89	0	0.0
	12	13	18.81	18.73	0-1	0.0
	25	0	18.84	18.81		0.0
DFT-s-OFDM 16QAM	1	1	19.34	19.34	0-1	0.0
CP-OFDM QPSK	1	1	18.98	18.93	0-1.5	0.0

Table H-231

NR Band n14 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.34	24.34	0	0.0
	1	13	24.29	24.45		0.0
	1	23	24.28	24.33		0.0
	12	0	23.33	23.38	0-1	1.0
	12	7	24.39	24.42	0	0.0
	12	13	23.34	23.28	0-1	1.0
	25	0	23.42	23.37		1.0
DFT-s-OFDM 16QAM	1	1	23.99	23.94	0-1	1.0
CP-OFDM QPSK	1	1	23.02	22.93	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 119 of 426

H.2.6 NR Band n14 Antenna E

Table H-232

NR Band n14 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.96	23.82	0	0.0
	1	13	23.97	23.89		0.0
	1	23	23.90	23.87		0.0
	12	0	22.99	22.94	0-1	1.0
	12	7	23.97	24.04	0	0.0
	12	13	22.87	22.92	0-1	1.0
	25	0	23.01	22.89		1.0
DFT-s-OFDM 16QAM	1	1	23.59	23.56	0-1	1.0
CP-OFDM QPSK	1	1	22.55	22.43	0-1.5	1.5

Table H-233

NR Band n14 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n14 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	158100 (790.5 MHz)	159100 (795.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.86	18.67	0	0.0
	1	13	18.88	18.75		0.0
	1	23	18.69	18.62		0.0
	12	0	18.87	18.64	0-1	0.0
	12	7	18.91	18.87	0	0.0
	12	13	18.73	18.65	0-1	0.0
	25	0	18.80	18.77		0.0
DFT-s-OFDM 16QAM	1	1	19.41	19.30	0-1	0.0
CP-OFDM QPSK	1	1	19.06	18.82	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 120 of 426

H.2.7 NR Band n26 Antenna A and Antenna A+C

Table H-234

NR Band n26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.55	24.31	0	0.0
	1	40	24.28	24.29		0.0
	1	77	24.38	24.26		0.0
	36	0	23.28	23.32	0-1	1.0
	36	22	24.45	24.43	0	0.0
	36	43	23.35	23.21	0-1	1.0
	75	0	23.41	23.25		1.0
DFT-s-OFDM 16QAM	1	1	23.89	23.80	0-1	1.0
CP-OFDM QPSK	1	1	22.96	22.92	0-1.5	1.5

Table H-235

NR Band n26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.51	24.25	24.29	0	0.0
	1	26	24.43	24.35	24.12		0.0
	1	50	24.29	24.31	24.16		0.0
	25	0	23.41	23.22	23.12	0-1	1.0
	25	14	24.51	24.27	24.19	0	0.0
	25	27	23.39	23.31	23.11	0-1	1.0
	50	0	23.43	23.16	23.12		1.0
DFT-s-OFDM 16QAM	1	1	23.79	23.73	23.65	0-1	1.0
CP-OFDM QPSK	1	1	22.99	22.86	22.72	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 121 of 426

Table H-236

NR Band n26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.54	24.30	24.29	0	0.0
	1	13	24.58	24.28	24.21		0.0
	1	23	24.46	24.36	24.18		0.0
	12	0	23.57	23.26	23.25	0-1	1.0
	12	7	24.60	24.32	24.24	0	0.0
	12	13	23.48	23.25	23.15	0-1	1.0
	25	0	23.53	23.23	23.24		1.0
DFT-s-OFDM 16QAM	1	1	23.97	23.79	23.72	0-1	1.0
CP-OFDM QPSK	1	1	22.99	22.89	22.90	0-1.5	1.5

Table H-237

NR Band n26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.36	18.05	0	0.0
	1	40	18.19	17.95		0.0
	1	77	18.17	17.92		0.0
	36	0	18.27	17.99	0-1	0.0
	36	22	18.36	18.15	0	0.0
	36	43	18.14	17.92	0-1	0.0
	75	0	18.22	17.98		0.0
DFT-s-OFDM 16QAM	1	1	18.66	18.58	0-1	0.0
CP-OFDM QPSK	1	1	18.27	18.09	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 122 of 426

Table H-238

NR Band n26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.25	18.12	18.06	0	0.0
	1	26	18.22	18.15	18.09		0.0
	1	50	18.19	18.13	17.97		0.0
	25	0	18.24	18.17	18.09	0-1	0.0
	25	14	18.28	18.26	18.17	0	0.0
	25	27	18.24	18.13	17.96	0-1	0.0
	50	0	18.20	18.19	18.00		0.0
DFT-s-OFDM 16QAM	1	1	18.70	18.56	18.63	0-1	0.0
CP-OFDM QPSK	1	1	18.50	18.17	18.09	0-1.5	0.0

Table H-239

NR Band n26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.25	18.20	17.95	0	0.0
	1	13	18.28	18.21	18.04		0.0
	1	23	18.19	18.13	17.97		0.0
	12	0	18.28	18.23	18.02	0-1	0.0
	12	7	18.35	18.27	18.07	0	0.0
	12	13	18.23	18.15	17.93	0-1	0.0
	25	0	18.28	18.18	18.00		0.0
DFT-s-OFDM 16QAM	1	1	18.76	18.50	18.58	0-1	0.0
CP-OFDM QPSK	1	1	18.39	18.29	18.40	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 123 of 426

H.2.8 NR Band n26 Antenna E

Table H-240

NR Band n26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	24.08	23.62	0	0.0
	1	40	23.91	23.64		0.0
	1	77	23.78	23.61		0.0
	36	0	23.09	22.72	0-1	1.0
	36	22	24.07	23.78	0	0.0
	36	43	23.01	22.64	0-1	1.0
	75	0	23.03	22.74		1.0
DFT-s-OFDM 16QAM	1	1	23.77	23.43	0-1	1.0
CP-OFDM QPSK	1	1	22.67	22.47	0-1.5	1.5

Table H-241

NR Band n26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.12	23.78	23.69	0	0.0
	1	26	24.09	23.69	23.47		0.0
	1	50	23.94	23.74	23.56		0.0
	25	0	23.10	22.86	22.62	0-1	1.0
	25	14	24.22	23.83	23.64	0	0.0
	25	27	23.04	22.75	22.60	0-1	1.0
	50	0	23.10	22.83	22.60		1.0
DFT-s-OFDM 16QAM	1	1	23.87	23.57	23.14	0-1	1.0
CP-OFDM QPSK	1	1	22.73	22.50	22.18	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 124 of 426

Table H-242

NR Band n26 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	24.13	23.69	23.45	0	0.0
	1	13	24.21	23.76	23.53		0.0
	1	23	24.11	23.69	23.61		0.0
	12	0	23.21	22.79	22.67	0-1	1.0
	12	7	24.31	23.86	23.66	0	0.0
	12	13	23.18	22.78	22.62	0-1	1.0
	25	0	23.18	22.78	22.67		1.0
DFT-s-OFDM 16QAM	1	1	23.91	23.39	23.30	0-1	1.0
CP-OFDM QPSK	1	1	22.81	22.48	22.36	0-1.5	1.5

Table H-243

NR Band n26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n26 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	164300 (821.5 MHz)	168300 (841.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.92	19.66	0	0.0
	1	40	19.91	19.44		0.0
	1	77	19.79	19.54		0.0
	36	0	20.02	19.54	0-1	0.0
	36	22	20.03	19.67	0	0.0
	36	43	19.85	19.51	0-1	0.0
	75	0	19.93	19.53		0.0
DFT-s-OFDM 16QAM	1	1	20.55	20.12	0-1	0.0
CP-OFDM QPSK	1	1	20.18	19.72	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 125 of 426

Table H-244

NR Band n26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n26 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163800 (819 MHz)	166300 (831.5 MHz)	168800 (844 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.07	19.67	19.55	0	0.0
	1	26	19.88	19.69	19.46		0.0
	1	50	19.90	19.54	19.39		0.0
	25	0	19.97	19.61	19.46	0-1	0.0
	25	14	20.00	19.67	19.58	0	0.0
	25	27	19.87	19.54	19.38	0-1	0.0
	50	0	19.88	19.65	19.52		0.0
DFT-s-OFDM 16QAM	1	1	20.49	20.23	19.83	0-1	0.0
CP-OFDM QPSK	1	1	20.10	19.66	19.56	0-1.5	0.0

Table H-245

NR Band n26 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n26 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	163300 (816.5 MHz)	166300 (831.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.02	19.63	19.51	0	0.0
	1	13	20.09	19.63	19.61		0.0
	1	23	19.88	19.57	19.42		0.0
	12	0	20.12	19.68	19.58	0-1	0.0
	12	7	20.16	19.69	19.60	0	0.0
	12	13	19.96	19.57	19.52	0-1	0.0
	25	0	20.05	19.62	19.56		0.0
DFT-s-OFDM 16QAM	1	1	20.66	20.19	20.15	0-1	0.0
CP-OFDM QPSK	1	1	20.24	19.79	19.61	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 126 of 426

H.2.9 NR Band n5 Antenna A and Antenna A+C

Table H-246

NR Band n5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.98	0	0.0
	1	40	23.89		0.0
	1	77	23.88		0.0
	36	0	23.70	0-1	1.0
	36	22	23.94	0	0.0
	36	43	22.76	0-1	1.0
	75	0	22.90		1.0
DFT-s-OFDM 16QAM	1	1	23.63	0-1	1.0
CP-OFDM QPSK	1	1	22.50	0-1.5	1.5

Table H-247

NR Band n5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.93	0	0.0
	1	26	23.94		0.0
	1	50	23.90		0.0
	25	0	23.79	0-1	1.0
	25	14	23.95	0	0.0
	25	27	22.80	0-1	1.0
	50	0	22.92		1.0
DFT-s-OFDM 16QAM	1	1	23.65	0-1	1.0
CP-OFDM QPSK	1	1	22.60	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 127 of 426

Table H-248

NR Band n5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.94	23.95	23.77	0	0.0
	1	13	23.97	23.90	23.77		0.0
	1	23	23.97	23.83	23.68		0.0
	12	0	23.02	22.90	22.81	0-1	1.0
	12	7	24.08	23.90	23.88	0	0.0
	12	13	22.90	22.84	22.80	0-1	1.0
	25	0	22.87	22.87	22.74		1.0
DFT-s-OFDM 16QAM	1	1	22.89	23.80	23.33	0-1	1.0
CP-OFDM QPSK	1	1	22.69	22.50	22.55	0-1.5	1.5

Table H-249

NR Band n5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.27	0	0.0
	1	40	18.10		0.0
	1	77	17.94		0.0
	36	0	18.22	0-1	0.0
	36	22	18.09	0	0.0
	36	43	18.02	0-1	0.0
	75	0	18.03		0.0
DFT-s-OFDM 16QAM	1	1	18.56	0-1	0.0
CP-OFDM QPSK	1	1	18.42	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 128 of 426

Table H-250
NR Band n5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.12	0	0.0
	1	26	18.08		0.0
	1	50	18.09		0.0
	25	0	18.18	0-1	0.0
	25	14	18.16	0	0.0
	25	27	18.12	0-1	0.0
	50	0	18.17		0.0
DFT-s-OFDM 16QAM	1	1	18.73	0-1	0.0
CP-OFDM QPSK	1	1	18.35	0-1.5	0.0

Table H-251
NR Band n5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
Modulation	RB Size	RB Offset	Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
			165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.27	18.20	17.98	0	0.0
	1	13	18.29	18.02	17.91		0.0
	1	23	18.19	18.08	17.93		0.0
	12	0	18.28	18.20	17.99	0-1	0.0
	12	7	18.35	18.12	17.97	0	0.0
	12	13	18.23	18.14	18.01	0-1	0.0
	25	0	18.28	18.14	18.01		0.0
DFT-s-OFDM 16QAM	1	1	18.81	18.75	18.59	0-1	0.0
CP-OFDM QPSK	1	1	18.55	18.36	18.22	0-1.5	0.0

H.2.10 NR Band n5 Antenna E

Table H-252

NR Band n5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.90	0	0.0
	1	40	23.81		0.0
	1	77	23.63		0.0
	36	0	22.90	0-1	1.0
	36	22	23.87	0	0.0
	36	43	22.76	0-1	1.0
	75	0	22.78		1.0
DFT-s-OFDM 16QAM	1	1	23.60	0-1	1.0
CP-OFDM QPSK	1	1	22.45	0-1.5	1.5

Table H-253

NR Band n5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.68	0	0.0
	1	26	23.87		0.0
	1	50	23.73		0.0
	25	0	22.82	0-1	1.0
	25	14	23.85	0	0.0
	25	27	22.77	0-1	1.0
	50	0	22.80		1.0
DFT-s-OFDM 16QAM	1	1	23.58	0-1	1.0
CP-OFDM QPSK	1	1	22.38	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 130 of 426

Table H-254

NR Band n5 Measured P_{Max} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.89	23.74	23.56	0	0.0
	1	13	23.87	23.85	23.57		0.0
	1	23	23.78	23.78	23.64		0.0
	12	0	23.04	22.81	22.67	0-1	1.0
	12	7	24.05	23.90	23.66	0	0.0
	12	13	22.92	22.77	22.66	0-1	1.0
	25	0	22.97	22.79	22.65		1.0
DFT-s-OFDM 16QAM	1	1	23.59	23.48	23.35	0-1	1.0
CP-OFDM QPSK	1	1	22.62	22.64	22.40	0-1.5	1.5

Table H-255

NR Band n5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n5 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.88	0	0.0
	1	40	19.71		0.0
	1	77	19.67		0.0
	36	0	19.79	0-1	0.0
	36	22	19.76	0	0.0
	36	43	19.62	0-1	0.0
	75	0	19.70		0.0
DFT-s-OFDM 16QAM	1	1	20.30	0-1	0.0
CP-OFDM QPSK	1	1	19.85	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 131 of 426

Table H-256

NR Band n5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n5 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			167300 (836.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.68	0	0.0
	1	26	19.63		0.0
	1	50	19.57		0.0
	25	0	19.59	0-1	0.0
	25	14	19.71	0	0.0
	25	27	19.53	0-1	0.0
	50	0	19.63		0.0
DFT-s-OFDM 16QAM	1	1	20.23	0-1	0.0
CP-OFDM QPSK	1	1	19.75	0-1.5	0.0

Table H-257

NR Band n5 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n5 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	165300 (826.5 MHz)	167300 (836.5 MHz)	169300 (846.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.86	19.51	19.30	0	0.0
	1	13	19.74	19.53	19.48		0.0
	1	23	19.73	19.51	19.38		0.0
	12	0	19.82	19.62	19.54	0-1	0.0
	12	7	19.85	19.67	19.53	0	0.0
	12	13	19.73	19.55	19.34	0-1	0.0
	25	0	19.76	19.62	19.43		0.0
DFT-s-OFDM 16QAM	1	1	20.38	20.18	20.09	0-1	0.0
CP-OFDM QPSK	1	1	19.90	19.84	19.56	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 132 of 426

H.2.11 NR Band n70 Antenna B

Table H-258

NR Band n70 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.09	0	0.0
	1	26	23.10		0.0
	1	50	23.03		0.0
	25	0	22.13	0-1	1.0
	25	14	23.00	0	0.0
	25	27	22.13	0-1	1.0
	50	0	22.10		1.0
DFT-s-OFDM 16QAM	1	1	22.00	0-1	1.0
CP-OFDM QPSK	1	1	21.66	0-1.5	1.5

Table H-259

NR Band n70 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.20	23.68	0	0.0
	1	13	23.19	23.64		0.0
	1	23	23.17	23.63		0.0
	12	0	22.11	22.55	0-1	1.0
	12	7	23.20	23.60	0	0.0
	12	13	22.17	22.52	0-1	1.0
	25	0	22.21	22.57		1.0
DFT-s-OFDM 16QAM	1	1	22.14	22.47	0-1	1.0
CP-OFDM QPSK	1	1	21.82	22.17	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 133 of 426

Table H-260

NR Band n70 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.02	0	0.0
	1	26	20.19		0.0
	1	50	20.06		0.0
	25	0	20.14	0-1	0.0
	25	14	20.05	0	0.0
	25	27	20.08	0-1	0.0
	50	0	20.09		0.0
DFT-s-OFDM 16QAM	1	1	19.98	0-1	0.0
CP-OFDM QPSK	1	1	20.12	0-1.5	0.0

Table H-261

NR Band n70 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.17	20.23	0	0.0
	1	13	20.17	20.15		0.0
	1	23	20.11	20.19		0.0
	12	0	20.02	20.06	0-1	0.0
	12	7	20.04	20.08	0	0.0
	12	13	20.07	20.12	0-1	0.0
	25	0	20.10	20.14		0.0
DFT-s-OFDM 16QAM	1	1	19.99	20.00	0-1	0.0
CP-OFDM OPSK	1	1	20.22	20.23	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 134 of 426

Table H-262

NR Band n70 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.87	0	0.0
	1	26	11.92		0.0
	1	50	11.87		0.0
	25	0	11.91	0-1	0.0
	25	14	11.84	0	0.0
	25	27	11.88	0-1	0.0
	50	0	11.89		0.0
DFT-s-OFDM 16QAM	1	1	11.88	0-1	0.0
CP-OFDM QPSK	1	1	11.99	0-1.5	0.0

Table H-263

NR Band n70 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	11.97	11.92	0	0.0
	1	13	11.96	11.88		0.0
	1	23	11.99	11.93		0.0
	12	0	11.91	11.89	0-1	0.0
	12	7	11.97	11.91	0	0.0
	12	13	11.96	11.89	0-1	0.0
	25	0	11.96	11.91		0.0
DFT-s-OFDM 16QAM	1	1	11.96	11.98	0-1	0.0
CP-OFDM QPSK	1	1	12.10	12.02	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 135 of 426

H.2.12 NR Band n70 Antenna G

Table H-264

NR Band n70 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.60	0	0.0
	1	26	18.52		0.0
	1	50	18.48		0.0
	25	0	18.43	0-1	0.0
	25	14	18.48	0	0.0
	25	27	18.55	0-1	0.0
	50	0	18.47		0.0
DFT-s-OFDM 16QAM	1	1	18.69	0-1	0.0
CP-OFDM QPSK	1	1	18.73	0-1.5	0.0

Table H-265

NR Band n70 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.58	18.60	0	0.0
	1	13	18.70	18.55		0.0
	1	23	18.59	18.61		0.0
	12	0	18.55	18.49	0-1	0.0
	12	7	18.68	18.62	0	0.0
	12	13	18.53	18.58	0-1	0.0
	25	0	18.50	18.55		0.0
DFT-s-OFDM 16QAM	1	1	18.43	18.54	0-1	0.0
CP-OFDM OPSK	1	1	18.73	18.75	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 136 of 426

Table H-266

NR Band n70 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.55	0	0.0
	1	26	16.45		0.0
	1	50	16.44		0.0
	25	0	16.39	0-1	0.0
	25	14	16.50	0	0.0
	25	27	16.40	0-1	0.0
	50	0	16.49		0.0
DFT-s-OFDM 16QAM	1	1	16.44	0-1	0.0
CP-OFDM QPSK	1	1	16.62	0-1.5	0.0

Table H-267

NR Band n70 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.52	16.52	0	0.0
	1	13	16.61	16.58		0.0
	1	23	16.54	16.54		0.0
	12	0	16.42	16.44	0-1	0.0
	12	7	16.57	16.52	0	0.0
	12	13	16.52	16.47	0-1	0.0
	25	0	16.52	16.50		0.0
DFT-s-OFDM 16QAM	1	1	16.43	16.53	0-1	0.0
CP-OFDM OPSK	1	1	16.78	16.80	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 137 of 426

Table H-268

NR Band n70 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.50	0	0.0
	1	26	20.52		0.0
	1	50	20.56		0.0
	25	0	20.43	0-1	0.0
	25	14	20.51	0	0.0
	25	27	20.47	0-1	0.0
	50	0	20.53		0.0
DFT-s-OFDM 16QAM	1	1	20.46	0-1	0.0
CP-OFDM QPSK	1	1	20.74	0-1.5	0.0

Table H-269

NR Band n70 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	20.53	20.55	0	0.0
	1	13	20.59	20.59		0.0
	1	23	20.49	20.56		0.0
	12	0	20.44	20.55	0-1	0.0
	12	7	20.60	20.59	0	0.0
	12	13	20.48	20.59	0-1	0.0
	25	0	20.55	20.53		0.0
DFT-s-OFDM 16QAM	1	1	20.42	20.54	0-1	0.0
CP-OFDM QPSK	1	1	20.65	20.79	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 138 of 426

Table H-270
NR Band n70 Measured P_{Limit} for DSI = 4 (Folder Open – Grip) – 10 MHz Bandwidth

NR Band n70 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			340500 (1702.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.40	0	0.0
	1	26	10.42		0.0
	1	50	10.41		0.0
	25	0	10.40	0-1	0.0
	25	14	10.40	0	0.0
	25	27	10.40	0-1	0.0
	50	0	10.42		0.0
DFT-s-OFDM 16QAM	1	1	10.37	0-1	0.0
CP-OFDM QPSK	1	1	10.48	0-1.5	0.0

Table H-271
NR Band n70 Measured P_{Limit} for DSI = 4 (Folder Open – Grip) – 5 MHz Bandwidth

NR Band n70 5 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	339500 (1697.5 MHz)	341500 (1707.5 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.42	10.48	0	0.0
	1	13	10.44	10.36		0.0
	1	23	10.39	10.40		0.0
	12	0	10.31	10.41	0-1	0.0
	12	7	10.40	10.51	0	0.0
	12	13	10.40	10.34	0-1	0.0
	25	0	10.29	10.45		0.0
DFT-s-OFDM 16QAM	1	1	10.33	10.42	0-1	0.0
CP-OFDM QPSK	1	1	10.50	10.63	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 139 of 426

H.2.13 NR Band n66 Antenna B

H.2.14 NR Band n66 Antenna B

Table H-272
NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.52	0	0.0
	1	108	24.03		0.0
	1	214	24.00		0.0
	108	0	22.72	0-1	1.0
	108	54	23.92	0	0.0
	108	108	23.03	0-1	1.0
	216	0	22.89		1.0
DFT-s-OFDM 16QAM	1	1	22.55	0-1	1.0
CP-OFDM QPSK	1	1	22.05	0-1.5	1.5

Table H-273
NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.63	0	0.0
	1	94	24.06		0.0
	1	186	24.05		0.0
	90	0	22.84	0-1	1.0
	90	49	23.99	0	0.0
	90	98	23.12	0-1	1.0
	180	0	22.92		1.0
DFT-s-OFDM 16QAM	1	1	22.56	0-1	1.0
CP-OFDM QPSK	1	1	22.17	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 140 of 426

Table H-274

NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.67	0	0.0
	1	80	24.00		0.0
	1	158	24.03		0.0
	80	0	22.85	0-1	1.0
	80	40	23.97	0	0.0
	80	80	23.02	0-1	1.0
	160	0	22.92		1.0
DFT-s-OFDM 16QAM	1	1	22.60	0-1	1.0
CP-OFDM QPSK	1	1	22.27	0-1.5	1.5

Table H-275

NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.27	0	0.0
	1	67	23.57		0.0
	1	131	23.55		0.0
	64	0	22.37	0-1	1.0
	64	35	23.36	0	0.0
	64	69	22.52	0-1	1.0
	128	0	22.38		1.0
DFT-s-OFDM 16QAM	1	1	22.26	0-1	1.0
CP-OFDM QPSK	1	1	21.84	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 141 of 426

Table H-276

NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.04	23.99	24.04	0	0.0
	1	53	23.25	24.02	24.07		0.0
	1	104	23.39	24.11	24.15		0.0
	50	0	22.24	23.14	23.22	0-1	1.0
	50	28	23.27	24.08	24.14	0	0.0
	50	56	22.42	23.13	23.21	0-1	1.0
	100	0	22.32	23.13	23.17		1.0
DFT-s-OFDM 16QAM	1	1	21.89	22.81	22.93	0-1	1.0
CP-OFDM QPSK	1	1	21.66	22.59	22.71	0-1.5	1.5

Table H-277

NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.17	23.90	24.10	0	0.0
	1	40	23.23	23.94	24.15		0.0
	1	77	23.39	23.98	24.09		0.0
	36	0	22.22	23.00	23.12	0-1	1.0
	36	22	23.20	24.00	24.10	0	0.0
	36	43	22.32	22.96	23.15	0-1	1.0
	75	0	22.22	23.00	23.07		1.0
DFT-s-OFDM 16QAM	1	1	22.07	23.00	23.11	0-1	1.0
CP-OFDM QPSK	1	1	21.83	22.50	22.63	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 142 of 426

Table H-278

NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.24	24.05	24.06	0	0.0
	1	26	23.27	24.00	24.07		0.0
	1	50	23.31	24.06	24.06		0.0
	25	0	22.29	23.06	23.08	0-1	1.0
	25	14	23.24	24.08	24.09	0	0.0
	25	27	22.40	23.01	23.02	0-1	1.0
	50	0	22.26	23.04	23.04		1.0
DFT-s-OFDM 16QAM	1	1	22.00	22.98	23.11	0-1	1.0
CP-OFDM QPSK	1	1	21.76	22.57	22.62	0-1.5	1.5

Table H-279

NR Band n66 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.16	24.07	24.18	0	0.0
	1	13	23.22	24.09	24.24		0.0
	1	23	23.15	24.03	24.24		0.0
	12	0	22.00	23.08	23.21	0-1	1.0
	12	7	23.15	24.02	24.22	0	0.0
	12	13	22.13	23.09	23.16	0-1	1.0
	25	0	22.22	23.06	23.23		1.0
DFT-s-OFDM 16QAM	1	1	21.93	22.85	23.02	0-1	1.0
CP-OFDM QPSK	1	1	21.80	22.51	22.69	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 143 of 426

Table H-280

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.28	0	0.0
	1	108	17.80		0.0
	1	214	17.70		0.0
	108	0	17.63	0-1	0.0
	108	54	17.76	0	0.0
	108	108	17.71	0-1	0.0
	216	0	17.69		0.0
DFT-s-OFDM 16QAM	1	1	17.58	0-1	0.0
CP-OFDM QPSK	1	1	17.42	0-1.5	0.0

Table H-281

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.38	0	0.0
	1	94	17.89		0.0
	1	186	17.66		0.0
	90	0	17.71	0-1	0.0
	90	49	17.77	0	0.0
	90	98	17.79	0-1	0.0
	180	0	17.79		0.0
DFT-s-OFDM 16QAM	1	1	17.59	0-1	0.0
CP-OFDM QPSK	1	1	17.50	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 144 of 426

Table H-282

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.48	0	0.0
	1	80	17.75		0.0
	1	158	17.81		0.0
	80	0	17.71	0-1	0.0
	80	40	17.78	0	0.0
	80	80	17.82	0-1	0.0
	160	0	17.86		0.0
DFT-s-OFDM 16QAM	1	1	17.60	0-1	0.0
CP-OFDM QPSK	1	1	17.64	0-1.5	0.0

Table H-283

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.64	0	0.0
	1	67	17.83		0.0
	1	131	17.82		0.0
	64	0	17.76	0-1	0.0
	64	35	17.75	0	0.0
	64	69	17.81	0-1	0.0
	128	0	17.77		0.0
DFT-s-OFDM 16QAM	1	1	17.66	0-1	0.0
CP-OFDM QPSK	1	1	17.70	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 145 of 426

Table H-284

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.80	17.46	17.49	0	0.0
	1	53	16.98	17.62	17.72		0.0
	1	104	17.24	17.66	17.61		0.0
	50	0	17.02	17.56	17.73	0-1	0.0
	50	28	17.02	17.53	17.65	0	0.0
	50	56	17.33	17.69	17.74	0-1	0.0
	100	0	17.10	17.60	17.66		0.0
DFT-s-OFDM 16QAM	1	1	16.74	17.64	17.44	0-1	0.0
CP-OFDM QPSK	1	1	17.04	17.57	17.71	0-1.5	0.0

Table H-285

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.97	17.58	17.71	0	0.0
	1	40	17.07	17.63	17.56		0.0
	1	77	17.21	17.67	17.50		0.0
	36	0	17.11	17.57	17.63	0-1	0.0
	36	22	17.22	17.54	17.73	0	0.0
	36	43	17.16	17.68	17.64	0-1	0.0
	75	0	17.07	17.61	17.69		0.0
DFT-s-OFDM 16QAM	1	1	16.91	17.68	17.58	0-1	0.0
CP-OFDM QPSK	1	1	17.20	17.71	17.88	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 146 of 426

Table H-286

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.92	17.50	17.75	0	0.0
	1	26	17.03	17.62	17.59		0.0
	1	50	17.10	17.67	17.66		0.0
	25	0	17.10	17.62	17.76	0-1	0.0
	25	14	16.98	17.59	17.70	0	0.0
	25	27	17.20	17.73	17.82	0-1	0.0
	50	0	17.11	17.74	17.76		0.0
DFT-s-OFDM 16QAM	1	1	16.79	17.65	17.59	0-1	0.0
CP-OFDM QPSK	1	1	17.08	17.68	17.85	0-1.5	0.0

Table H-287

NR Band n66 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.87	17.54	17.76	0	0.0
	1	13	16.97	17.67	17.76		0.0
	1	23	16.98	17.66	17.71		0.0
	12	0	16.93	17.57	17.77	0-1	0.0
	12	7	16.85	17.61	17.79	0	0.0
	12	13	16.94	17.66	17.70	0-1	0.0
	25	0	17.10	17.71	17.83		0.0
DFT-s-OFDM 16QAM	1	1	16.80	17.69	17.52	0-1	0.0
CP-OFDM QPSK	1	1	17.08	17.71	17.79	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 147 of 426

Table H-288

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	12.12	0	0.0
	1	108	12.37		0.0
	1	214	12.37		0.0
	108	0	12.34	0-1	0.0
	108	54	12.30	0	0.0
	108	108	12.25	0-1	0.0
	216	0	12.29		0.0
DFT-s-OFDM 16QAM	1	1	12.17	0-1	0.0
CP-OFDM QPSK	1	1	12.21	0-1.5	0.0

Table H-289

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	12.13	0	0.0
	1	94	12.39		0.0
	1	186	12.34		0.0
	90	0	12.00	0-1	0.0
	90	49	12.28	0	0.0
	90	98	12.46	0-1	0.0
	180	0	11.93		0.0
DFT-s-OFDM 16QAM	1	1	12.20	0-1	0.0
CP-OFDM QPSK	1	1	12.24	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 148 of 426

Table H-290

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	12.40	0	0.0
	1	80	12.41		0.0
	1	158	12.36		0.0
	80	0	12.35	0-1	0.0
	80	40	12.39	0	0.0
	80	80	12.47	0-1	0.0
	160	0	12.36		0.0
DFT-s-OFDM 16QAM	1	1	12.25	0-1	0.0
CP-OFDM QPSK	1	1	12.35	0-1.5	0.0

Table H-291

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	12.21	0	0.0
	1	67	12.24		0.0
	1	131	12.17		0.0
	64	0	12.18	0-1	0.0
	64	35	12.13	0	0.0
	64	69	12.23	0-1	0.0
	128	0	12.15		0.0
DFT-s-OFDM 16QAM	1	1	12.18	0-1	0.0
CP-OFDM QPSK	1	1	12.23	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 149 of 426

Table H-292

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.80	12.16	12.34	0	0.0
	1	53	11.92	12.35	12.46		0.0
	1	104	12.14	12.36	12.48		0.0
	50	0	11.91	12.29	12.39	0-1	0.0
	50	28	12.02	12.36	12.54	0	0.0
	50	56	12.06	12.41	12.45	0-1	0.0
	100	0	12.01	12.30	12.47		0.0
DFT-s-OFDM 16QAM	1	1	12.02	12.40	12.51	0-1	0.0
CP-OFDM QPSK	1	1	11.74	12.17	12.40	0-1.5	0.0

Table H-293

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.83	12.26	12.33	0	0.0
	1	40	11.74	12.11	12.23		0.0
	1	77	11.92	12.19	12.27		0.0
	36	0	11.79	12.19	12.33	0-1	0.0
	36	22	11.94	12.17	12.28	0	0.0
	36	43	12.00	12.13	12.21	0-1	0.0
	75	0	11.88	12.18	12.31		0.0
DFT-s-OFDM 16QAM	1	1	11.89	12.19	12.32	0-1	0.0
CP-OFDM QPSK	1	1	11.98	12.34	12.46	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 150 of 426

Table H-294

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.79	12.18	12.27	0	0.0
	1	26	11.84	12.20	12.29		0.0
	1	50	12.03	12.06	12.32		0.0
	25	0	11.83	12.15	12.36	0-1	0.0
	25	14	11.85	12.10	12.39	0	0.0
	25	27	11.95	12.22	12.40	0-1	0.0
	50	0	11.89	12.16	12.43		0.0
DFT-s-OFDM 16QAM	1	1	11.78	12.17	12.30	0-1	0.0
CP-OFDM QPSK	1	1	11.93	12.18	12.44	0-1.5	0.0

Table H-295

NR Band n66 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.77	11.96	12.36	0	0.0
	1	13	11.84	12.06	12.37		0.0
	1	23	12.00	12.05	12.35		0.0
	12	0	11.83	11.95	12.41	0-1	0.0
	12	7	11.85	12.01	12.32	0	0.0
	12	13	11.80	12.06	12.37	0-1	0.0
	25	0	11.78	12.07	12.34		0.0
DFT-s-OFDM 16QAM	1	1	11.70	12.17	12.33	0-1	0.0
CP-OFDM QPSK	1	1	11.84	12.11	12.53	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 151 of 426

H.2.15 NR Band n66 Antenna G

Table H-296

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.56	0	0.0
	1	108	20.78		0.0
	1	214	20.93		0.0
	108	0	20.53	0-1	0.0
	108	54	20.82	0	0.0
	108	108	20.72	0-1	0.0
	216	0	20.67		0.0
DFT-s-OFDM 16QAM	1	1	20.87	0-1	0.0
CP-OFDM QPSK	1	1	20.87	0-1.5	0.0

Table H-297

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.65	0	0.0
	1	94	20.85		0.0
	1	186	20.78		0.0
	90	0	20.63	0-1	0.0
	90	49	20.69	0	0.0
	90	98	20.79	0-1	0.0
	180	0	20.66		0.0
DFT-s-OFDM 16QAM	1	1	20.87	0-1	0.0
CP-OFDM QPSK	1	1	20.72	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 152 of 426

Table H-298

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.60	0	0.0
	1	80	20.86		0.0
	1	158	20.90		0.0
	80	0	20.69	0-1	0.0
	80	40	20.80	0	0.0
	80	80	20.76	0-1	0.0
	160	0	20.72		0.0
DFT-s-OFDM 16QAM	1	1	20.87	0-1	0.0
CP-OFDM QPSK	1	1	20.81	0-1.5	0.0

Table H-299

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.74	0	0.0
	1	67	20.85		0.0
	1	131	20.72		0.0
	64	0	20.60	0-1	0.0
	64	35	20.80	0	0.0
	64	69	20.75	0-1	0.0
	128	0	20.70		0.0
DFT-s-OFDM 16QAM	1	1	20.88	0-1	0.0
CP-OFDM QPSK	1	1	20.79	0-1.5	0.0

Table H-300

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.28	20.54	20.47	0	0.0
	1	53	20.29	20.53	20.74		0.0
	1	104	20.26	20.59	20.73		0.0
	50	0	20.32	20.45	20.59	0-1	0.0
	50	28	20.26	20.59	20.68	0	0.0
	50	56	20.35	20.54	20.64	0-1	0.0
	100	0	20.39	20.60	20.71		0.0
DFT-s-OFDM 16QAM	1	1	20.25	20.87	20.55	0-1	0.0
CP-OFDM QPSK	1	1	20.56	20.64	20.60	0-1.5	0.0

Table H-301

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.37	20.64	20.66	0	0.0
	1	40	20.34	20.55	20.75		0.0
	1	77	20.38	20.59	20.72		0.0
	36	0	20.35	20.49	20.59	0-1	0.0
	36	22	20.35	20.63	20.76	0	0.0
	36	43	20.45	20.53	20.65	0-1	0.0
	75	0	20.34	20.50	20.64		0.0
DFT-s-OFDM 16QAM	1	1	20.41	20.87	20.72	0-1	0.0
CP-OFDM QPSK	1	1	20.63	20.70	20.85	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 154 of 426

Table H-302

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.37	20.57	20.66	0	0.0
	1	26	20.41	20.54	20.69		0.0
	1	50	20.39	20.50	20.68		0.0
	25	0	20.42	20.56	20.60	0-1	0.0
	25	14	20.41	20.58	20.66	0	0.0
	25	27	20.40	20.55	20.69	0-1	0.0
	50	0	20.40	20.51	20.59		0.0
DFT-s-OFDM 16QAM	1	1	20.43	20.88	20.60	0-1	0.0
CP-OFDM QPSK	1	1	20.63	20.66	20.84	0-1.5	0.0

Table H-303

NR Band n66 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.33	20.54	20.59	0	0.0
	1	13	20.37	20.62	20.71		0.0
	1	23	20.33	20.64	20.52		0.0
	12	0	20.35	20.58	20.59	0-1	0.0
	12	7	20.30	20.59	20.67	0	0.0
	12	13	20.25	20.57	20.61	0-1	0.0
	25	0	20.29	20.50	20.58		0.0
DFT-s-OFDM 16QAM	1	1	20.31	20.89	20.53	0-1	0.0
CP-OFDM QPSK	1	1	20.73	20.67	20.93	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 155 of 426

Table H-304

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.35	0	0.0
	1	108	19.35		0.0
	1	214	19.48		0.0
	108	0	19.25	0-1	0.0
	108	54	19.46	0	0.0
	108	108	19.34	0-1	0.0
	216	0	19.32		0.0
DFT-s-OFDM 16QAM	1	1	19.49	0-1	0.0
CP-OFDM QPSK	1	1	19.26	0-1.5	0.0

Table H-305

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.25	0	0.0
	1	94	19.49		0.0
	1	186	19.41		0.0
	90	0	19.25	0-1	0.0
	90	49	19.42	0	0.0
	90	98	19.37	0-1	0.0
	180	0	19.29		0.0
DFT-s-OFDM 16QAM	1	1	19.50	0-1	0.0
CP-OFDM QPSK	1	1	19.31	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 156 of 426

Table H-306

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.43	0	0.0
	1	80	19.47		0.0
	1	158	19.57		0.0
	80	0	19.24	0-1	0.0
	80	40	19.40	0	0.0
	80	80	19.49	0-1	0.0
	160	0	19.28		0.0
DFT-s-OFDM 16QAM	1	1	19.39	0-1	0.0
CP-OFDM QPSK	1	1	19.35	0-1.5	0.0

Table H-307

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.44	0	0.0
	1	67	19.45		0.0
	1	131	19.55		0.0
	64	0	19.27	0-1	0.0
	64	35	19.37	0	0.0
	64	69	19.46	0-1	0.0
	128	0	19.32		0.0
DFT-s-OFDM 16QAM	1	1	19.43	0-1	0.0
CP-OFDM QPSK	1	1	19.47	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 157 of 426

Table H-308

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.01	19.22	19.28	0	0.0
	1	53	18.91	19.23	19.32		0.0
	1	104	18.87	19.31	19.29		0.0
	50	0	18.98	19.24	19.27	0-1	0.0
	50	28	18.89	19.23	19.32	0	0.0
	50	56	18.90	19.21	19.33	0-1	0.0
	100	0	18.98	19.20	19.23		0.0
DFT-s-OFDM 16QAM	1	1	18.88	19.39	19.16	0-1	0.0
CP-OFDM QPSK	1	1	19.07	19.12	19.30	0-1.5	0.0

Table H-309

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.20	19.31	19.38	0	0.0
	1	40	19.06	19.23	19.25		0.0
	1	77	18.99	19.29	19.29		0.0
	36	0	18.99	19.24	19.23	0-1	0.0
	36	22	19.11	19.33	19.26	0	0.0
	36	43	18.92	19.20	19.25	0-1	0.0
	75	0	19.04	19.22	19.26		0.0
DFT-s-OFDM 16QAM	1	1	19.04	19.42	19.27	0-1	0.0
CP-OFDM QPSK	1	1	19.24	19.30	19.41	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 158 of 426

Table H-310

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.08	19.22	19.26	0	0.0
	1	26	19.12	19.23	19.28		0.0
	1	50	19.05	19.21	19.21		0.0
	25	0	19.02	19.24	19.29	0-1	0.0
	25	14	19.20	19.22	19.23	0	0.0
	25	27	19.03	19.19	19.29	0-1	0.0
	50	0	19.02	19.21	19.24		0.0
DFT-s-OFDM 16QAM	1	1	18.96	19.40	19.14	0-1	0.0
CP-OFDM QPSK	1	1	19.19	19.34	19.57	0-1.5	0.0

Table H-311

NR Band n66 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	18.97	19.21	19.25	0	0.0
	1	13	19.10	19.38	19.32		0.0
	1	23	18.98	19.22	19.32		0.0
	12	0	18.96	19.24	19.21	0-1	0.0
	12	7	19.13	19.33	19.32	0	0.0
	12	13	19.04	19.21	19.28	0-1	0.0
	25	0	18.99	19.27	19.27		0.0
DFT-s-OFDM 16QAM	1	1	18.97	19.39	19.26	0-1	0.0
CP-OFDM QPSK	1	1	19.20	19.43	19.50	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 159 of 426

Table H-312

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.55	0	0.0
	1	108	16.71		0.0
	1	214	16.79		0.0
	108	0	16.57	0-1	0.0
	108	54	16.71	0	0.0
	108	108	16.79	0-1	0.0
	216	0	16.75		0.0
DFT-s-OFDM 16QAM	1	1	16.90	0-1	0.0
CP-OFDM QPSK	1	1	16.78	0-1.5	0.0

Table H-313

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.66	0	0.0
	1	94	16.72		0.0
	1	186	16.79		0.0
	90	0	16.68	0-1	0.0
	90	49	16.68	0	0.0
	90	98	16.79	0-1	0.0
	180	0	16.66		0.0
DFT-s-OFDM 16QAM	1	1	16.90	0-1	0.0
CP-OFDM QPSK	1	1	16.77	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 160 of 426

Table H-314

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.70	0	0.0
	1	80	16.72		0.0
	1	158	16.85		0.0
	80	0	16.76	0-1	0.0
	80	40	16.70	0	0.0
	80	80	16.79	0-1	0.0
	160	0	16.77		0.0
DFT-s-OFDM 16QAM	1	1	16.89	0-1	0.0
CP-OFDM QPSK	1	1	16.81	0-1.5	0.0

Table H-315

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.75	0	0.0
	1	67	16.78		0.0
	1	131	16.79		0.0
	64	0	16.78	0-1	0.0
	64	35	16.78	0	0.0
	64	69	16.80	0-1	0.0
	128	0	16.78		0.0
DFT-s-OFDM 16QAM	1	1	16.92	0-1	0.0
CP-OFDM QPSK	1	1	16.88	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 161 of 426

Table H-316

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.66	16.68	16.81	0	0.0
	1	53	16.62	16.85	16.92		0.0
	1	104	16.67	16.84	16.88		0.0
	50	0	16.61	16.66	16.80	0-1	0.0
	50	28	16.64	16.74	16.91	0	0.0
	50	56	16.67	16.79	16.79	0-1	0.0
	100	0	16.63	16.89	16.83		0.0
DFT-s-OFDM 16QAM	1	1	16.62	16.90	16.67	0-1	0.0
CP-OFDM QPSK	1	1	16.66	16.82	16.76	0-1.5	0.0

Table H-317

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.68	16.90	16.91	0	0.0
	1	40	16.65	16.78	16.92		0.0
	1	77	16.59	16.81	16.97		0.0
	36	0	16.50	16.71	16.79	0-1	0.0
	36	22	16.72	16.90	16.93	0	0.0
	36	43	16.58	16.79	16.88	0-1	0.0
	75	0	16.53	16.80	16.79		0.0
DFT-s-OFDM 16QAM	1	1	16.58	16.93	16.83	0-1	0.0
CP-OFDM QPSK	1	1	16.68	16.94	16.89	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 162 of 426

Table H-318

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.69	16.79	16.99	0	0.0
	1	26	16.72	16.77	16.99		0.0
	1	50	16.77	16.80	16.96		0.0
	25	0	16.52	16.75	16.86	0-1	0.0
	25	14	16.63	16.74	16.99	0	0.0
	25	27	16.65	16.85	16.92	0-1	0.0
	50	0	16.58	16.76	16.87		0.0
DFT-s-OFDM 16QAM	1	1	16.61	16.89	16.75	0-1	0.0
CP-OFDM QPSK	1	1	16.74	16.75	17.03	0-1.5	0.0

Table H-319

NR Band n66 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.52	16.80	16.85	0	0.0
	1	13	16.75	16.89	16.97		0.0
	1	23	16.51	16.91	16.89		0.0
	12	0	16.56	16.71	16.89	0-1	0.0
	12	7	16.70	16.87	16.95	0	0.0
	12	13	16.47	16.80	16.82	0-1	0.0
	25	0	16.53	16.72	16.87		0.0
DFT-s-OFDM 16QAM	1	1	16.50	16.89	16.83	0-1	0.0
CP-OFDM QPSK	1	1	16.62	16.87	17.06	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 163 of 426

Table H-320

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 40 MHz Bandwidth

NR Band n66 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.33	0	0.0
	1	108	10.49		0.0
	1	214	10.71		0.0
	108	0	10.40	0-1	0.0
	108	54	10.46	0	0.0
	108	108	10.52	0-1	0.0
	216	0	10.39		0.0
DFT-s-OFDM 16QAM	1	1	10.75	0-1	0.0
CP-OFDM QPSK	1	1	10.46	0-1.5	0.0

Table H-321

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 35 MHz Bandwidth

NR Band n66 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.38	0	0.0
	1	94	10.54		0.0
	1	186	10.64		0.0
	90	0	10.34	0-1	0.0
	90	49	10.48	0	0.0
	90	98	10.52	0-1	0.0
	180	0	10.44		0.0
DFT-s-OFDM 16QAM	1	1	10.76	0-1	0.0
CP-OFDM QPSK	1	1	10.48	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 164 of 426

Table H-322

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 30 MHz Bandwidth

NR Band n66 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.52	0	0.0
	1	80	10.54		0.0
	1	158	10.71		0.0
	80	0	10.38	0-1	0.0
	80	40	10.52	0	0.0
	80	80	10.50	0-1	0.0
	160	0	10.51		0.0
DFT-s-OFDM 16QAM	1	1	10.74	0-1	0.0
CP-OFDM QPSK	1	1	10.41	0-1.5	0.0

Table H-323

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 25 MHz Bandwidth

NR Band n66 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			349000 (1745 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.42	0	0.0
	1	67	10.58		0.0
	1	131	10.66		0.0
	64	0	10.31	0-1	0.0
	64	35	10.55	0	0.0
	64	69	10.51	0-1	0.0
	128	0	10.43		0.0
DFT-s-OFDM 16QAM	1	1	10.75	0-1	0.0
CP-OFDM QPSK	1	1	10.43	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 165 of 426

Table H-324

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 20 MHz Bandwidth

NR Band n66 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	344000 (1720 MHz)	349000 (1745 MHz)	354000 (1770 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	10.17	10.30	10.41	0	0.0
	1	53	10.15	10.36	10.38		0.0
	1	104	10.25	10.40	10.42		0.0
	50	0	10.17	10.30	10.32	0-1	0.0
	50	28	10.18	10.43	10.42	0	0.0
	50	56	10.14	10.38	10.40	0-1	0.0
	100	0	10.10	10.35	10.36		0.0
DFT-s-OFDM 16QAM	1	1	10.13	10.74	10.29	0-1	0.0
CP-OFDM QPSK	1	1	10.26	10.32	10.47	0-1.5	0.0

Table H-325

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 15 MHz Bandwidth

NR Band n66 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343500 (1717.5 MHz)	349000 (1745 MHz)	354500 (1772.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	10.38	10.46	10.45	0	0.0
	1	40	10.21	10.47	10.37		0.0
	1	77	10.34	10.51	10.41		0.0
	36	0	10.17	10.29	10.46	0-1	0.0
	36	22	10.40	10.55	10.35	0	0.0
	36	43	10.15	10.44	10.47	0-1	0.0
	75	0	10.24	10.37	10.39		0.0
DFT-s-OFDM 16QAM	1	1	10.20	10.77	10.40	0-1	0.0
CP-OFDM QPSK	1	1	10.34	10.51	10.57	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 166 of 426

Table H-326

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 10 MHz Bandwidth

NR Band n66 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	343000 (1715 MHz)	349000 (1745 MHz)	355000 (1775 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	10.23	10.44	10.47	0	0.0
	1	26	10.40	10.48	10.56		0.0
	1	50	10.26	10.42	10.47		0.0
	25	0	10.30	10.36	10.52	0-1	0.0
	25	14	10.36	10.41	10.49	0	0.0
	25	27	10.36	10.39	10.52	0-1	0.0
	50	0	10.27	10.41	10.51		0.0
DFT-s-OFDM 16QAM	1	1	10.22	10.75	10.47	0-1	0.0
CP-OFDM QPSK	1	1	10.35	10.33	10.65	0-1.5	0.0

Table H-327

NR Band n66 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 5 MHz Bandwidth

NR Band n66 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	342500 (1712.5 MHz)	349000 (1745 MHz)	355500 (1777.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	10.16	10.44	10.51	0	0.0
	1	13	10.18	10.42	10.60		0.0
	1	23	10.11	10.36	10.49		0.0
	12	0	10.15	10.31	10.51	0-1	0.0
	12	7	10.31	10.44	10.59	0	0.0
	12	13	10.10	10.40	10.49	0-1	0.0
	25	0	10.11	10.34	10.52		0.0
DFT-s-OFDM 16QAM	1	1	10.20	10.75	10.53	0-1	0.0
CP-OFDM QPSK	1	1	10.39	10.42	10.76	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 167 of 426

H.2.16 NR Band n25 Antenna B

Table H-328

NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.43	0	0.0
	1	94	24.13		0.0
	1	186	23.94		0.0
	90	0	22.76	0-1	1.0
	90	49	23.97	0	0.0
	90	98	23.05	0-1	1.0
	180	0	22.88		1.0
DFT-s-OFDM 16QAM	1	1	22.39	0-1	1.0
CP-OFDM QPSK	1	1	22.01	0-1.5	1.5

Table H-329

NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.56	0	0.0
	1	80	24.05		0.0
	1	158	23.98		0.0
	80	0	22.80	0-1	1.0
	80	40	24.02	0	0.0
	80	80	23.10	0-1	1.0
	160	0	22.87		1.0
DFT-s-OFDM 16QAM	1	1	22.47	0-1	1.0
CP-OFDM QPSK	1	1	22.13	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 168 of 426

Table H-330
NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.72	0	0.0
	1	67	24.12		0.0
	1	131	24.04		0.0
	64	0	22.79	0-1	1.0
	64	35	23.99	0	0.0
	64	69	23.10	0-1	1.0
	128	0	22.93		1.0
DFT-s-OFDM 16QAM	1	1	22.47	0-1	1.0
CP-OFDM QPSK	1	1	22.19	0-1.5	1.5

Table H-331
NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.32	23.59	23.78	0	0.0
	1	53	23.28	23.82	23.88		0.0
	1	104	23.47	23.75	23.80		0.0
	50	0	22.35	22.76	22.87	0-1	1.0
	50	28	23.36	23.84	23.86	0	0.0
	50	56	22.41	22.87	22.83	0-1	1.0
	100	0	22.34	22.84	22.84		1.0
DFT-s-OFDM 16QAM	1	1	22.15	22.35	22.61	0-1	1.0
CP-OFDM QPSK	1	1	21.92	22.19	22.49	0-1.5	1.5

Table H-332

NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.43	23.75	23.81	0	0.0
	1	40	23.26	23.80	23.80		0.0
	1	77	23.35	23.75	23.82		0.0
	36	0	22.38	22.87	22.84	0-1	1.0
	36	22	23.36	23.82	23.79	0	0.0
	36	43	22.32	22.85	22.77	0-1	1.0
	75	0	22.36	22.84	22.81		1.0
DFT-s-OFDM 16QAM	1	1	22.32	22.57	22.67	0-1	1.0
CP-OFDM QPSK	1	1	22.00	22.30	22.43	0-1.5	1.5

Table H-333

NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.36	23.68	23.80	0	0.0
	1	26	23.38	23.82	23.76		0.0
	1	50	23.32	23.74	23.73		0.0
	25	0	22.43	22.85	22.89	0-1	1.0
	25	14	23.36	23.75	23.77	0	0.0
	25	27	22.43	22.88	22.86	0-1	1.0
	50	0	22.37	22.84	22.83		1.0
DFT-s-OFDM 16QAM	1	1	22.29	22.61	22.76	0-1	1.0
CP-OFDM OPSK	1	1	21.99	22.26	22.50	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 170 of 426

Table H-334

NR Band n25 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.46	23.92	23.79	0	0.0
	1	13	23.35	23.92	23.71		0.0
	1	23	23.32	23.95	23.74		0.0
	12	0	22.32	22.81	22.72	0-1	1.0
	12	7	23.30	23.72	23.69	0	0.0
	12	13	22.27	22.71	22.67	0-1	1.0
	25	0	22.36	22.79	22.76		1.0
DFT-s-OFDM 16QAM	1	1	22.36	22.82	22.55	0-1	1.0
CP-OFDM QPSK	1	1	22.10	22.45	22.37	0-1.5	1.5

Table H-335

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.44	0	0.0
	1	94	18.05		0.0
	1	186	17.97		0.0
	90	0	17.79	0-1	0.0
	90	49	17.99	0	0.0
	90	98	18.06	0-1	0.0
	180	0	17.88		0.0
DFT-s-OFDM 16QAM	1	1	17.42	0-1	0.0
CP-OFDM QPSK	1	1	17.57	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 171 of 426

Table H-336

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.53	0	0.0
	1	80	17.97		0.0
	1	158	17.95		0.0
	80	0	17.78	0-1	0.0
	80	40	17.94	0	0.0
	80	80	18.13	0-1	0.0
	160	0	17.88		0.0
DFT-s-OFDM 16QAM	1	1	17.43	0-1	0.0
CP-OFDM QPSK	1	1	17.72	0-1.5	0.0

Table H-337

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.67	0	0.0
	1	67	18.07		0.0
	1	131	18.04		0.0
	64	0	17.91	0-1	0.0
	64	35	17.95	0	0.0
	64	69	18.08	0-1	0.0
	128	0	17.93		0.0
DFT-s-OFDM 16QAM	1	1	17.54	0-1	0.0
CP-OFDM QPSK	1	1	17.86	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 172 of 426

Table H-338

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.27	17.61	17.83	0	0.0
	1	53	17.23	17.84	17.88		0.0
	1	104	17.44	17.80	17.80		0.0
	50	0	17.33	17.86	17.98	0-1	0.0
	50	28	17.27	17.88	17.98	0	0.0
	50	56	17.38	17.81	17.95	0-1	0.0
	100	0	17.25	17.82	17.98		0.0
DFT-s-OFDM 16QAM	1	1	17.17	17.44	17.72	0-1	0.0
CP-OFDM QPSK	1	1	17.48	17.78	18.15	0-1.5	0.0

Table H-339

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.20	17.57	17.72	0	0.0
	1	40	17.08	17.64	17.67		0.0
	1	77	17.15	17.59	17.63		0.0
	36	0	17.16	17.61	17.76	0-1	0.0
	36	22	17.12	17.59	17.70	0	0.0
	36	43	17.10	17.59	17.73	0-1	0.0
	75	0	17.12	17.60	17.73		0.0
DFT-s-OFDM 16QAM	1	1	17.16	17.47	17.79	0-1	0.0
CP-OFDM QPSK	1	1	17.39	17.75	17.93	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 173 of 426

Table H-340

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.35	17.66	17.78	0	0.0
	1	26	17.39	17.78	17.72		0.0
	1	50	17.31	17.72	17.68		0.0
	25	0	17.37	17.90	17.93	0-1	0.0
	25	14	17.35	17.81	17.78	0	0.0
	25	27	17.39	17.77	17.85	0-1	0.0
	50	0	17.36	17.85	17.85		0.0
DFT-s-OFDM 16QAM	1	1	17.22	17.57	17.68	0-1	0.0
CP-OFDM QPSK	1	1	17.52	17.86	17.97	0-1.5	0.0

Table H-341

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.46	17.90	17.70	0	0.0
	1	13	17.31	17.77	17.70		0.0
	1	23	17.26	17.81	17.67		0.0
	12	0	17.32	17.83	17.79	0-1	0.0
	12	7	17.28	17.75	17.66	0	0.0
	12	13	17.26	17.80	17.71	0-1	0.0
	25	0	17.31	17.90	17.82		0.0
DFT-s-OFDM 16QAM	1	1	17.31	17.78	17.57	0-1	0.0
CP-OFDM QPSK	1	1	17.57	18.02	17.80	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 174 of 426

Table H-342

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.57	0	0.0
	1	94	12.26		0.0
	1	186	12.01		0.0
	90	0	11.92	0-1	0.0
	90	49	12.14	0	0.0
	90	98	12.21	0-1	0.0
	180	0	11.97		0.0
DFT-s-OFDM 16QAM	1	1	11.59	0-1	0.0
CP-OFDM QPSK	1	1	11.65	0-1.5	0.0

Table H-343

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.66	0	0.0
	1	80	12.16		0.0
	1	158	12.10		0.0
	80	0	11.99	0-1	0.0
	80	40	12.20	0	0.0
	80	80	12.20	0-1	0.0
	160	0	12.03		0.0
DFT-s-OFDM 16QAM	1	1	11.74	0-1	0.0
CP-OFDM QPSK	1	1	11.72	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 175 of 426

Table H-344

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.78	0	0.0
	1	67	12.21		0.0
	1	131	12.18		0.0
	64	0	11.96	0-1	0.0
	64	35	12.16	0	0.0
	64	69	12.18	0-1	0.0
	128	0	12.07		0.0
DFT-s-OFDM 16QAM	1	1	11.80	0-1	0.0
CP-OFDM QPSK	1	1	11.93	0-1.5	0.0

Table H-345

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.45	11.76	12.04	0	0.0
	1	53	11.42	11.93	11.96		0.0
	1	104	11.61	12.05	11.86		0.0
	50	0	11.45	11.85	12.04	0-1	0.0
	50	28	11.54	11.97	12.03	0	0.0
	50	56	11.60	11.95	12.00	0-1	0.0
	100	0	11.50	11.93	12.08		0.0
DFT-s-OFDM 16QAM	1	1	11.47	11.77	12.03	0-1	0.0
CP-OFDM OPSK	1	1	11.62	11.78	12.18	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 176 of 426

Table H-346

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.60	11.90	12.02	0	0.0
	1	40	11.42	12.03	11.94		0.0
	1	77	11.59	12.03	11.91		0.0
	36	0	11.51	11.89	12.03	0-1	0.0
	36	22	11.57	11.96	11.99	0	0.0
	36	43	11.52	11.95	11.99	0-1	0.0
	75	0	11.57	11.98	12.01		0.0
DFT-s-OFDM 16QAM	1	1	11.52	11.89	12.02	0-1	0.0
CP-OFDM QPSK	1	1	11.61	11.99	12.20	0-1.5	0.0

Table H-347

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.54	11.79	12.07	0	0.0
	1	26	11.51	12.03	12.05		0.0
	1	50	11.42	12.00	11.93		0.0
	25	0	11.62	11.91	12.07	0-1	0.0
	25	14	11.52	12.02	11.95	0	0.0
	25	27	11.61	12.04	12.00	0-1	0.0
	50	0	11.58	11.90	12.01		0.0
DFT-s-OFDM 16QAM	1	1	11.59	11.80	11.90	0-1	0.0
CP-OFDM QPSK	1	1	11.77	11.89	12.00	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 177 of 426

Table H-348

NR Band n25 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.57	11.99	11.97	0	0.0
	1	13	11.47	11.91	11.94		0.0
	1	23	11.52	11.98	11.87		0.0
	12	0	11.53	12.06	11.98	0-1	0.0
	12	7	11.40	11.94	11.86	0	0.0
	12	13	11.49	11.99	11.93	0-1	0.0
	25	0	11.56	12.01	11.97		0.0
DFT-s-OFDM 16QAM	1	1	11.56	12.01	11.94	0-1	0.0
CP-OFDM QPSK	1	1	11.78	12.17	12.04	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 178 of 426

H.2.17 NR Band n25 Antenna G

Table H-349

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.73	0	0.0
	1	94	20.99		0.0
	1	186	20.85		0.0
	90	0	20.78	0-1	0.0
	90	49	20.96	0	0.0
	90	98	20.89	0-1	0.0
	180	0	20.83		0.0
DFT-s-OFDM 16QAM	1	1	21.01	0-1	0.0
CP-OFDM QPSK	1	1	20.84	0-1.5	0.0

Table H-350

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.75	0	0.0
	1	80	21.01		0.0
	1	158	21.02		0.0
	80	0	20.84	0-1	0.0
	80	40	20.86	0	0.0
	80	80	20.85	0-1	0.0
	160	0	20.85		0.0
DFT-s-OFDM 16QAM	1	1	21.03	0-1	0.0
CP-OFDM QPSK	1	1	20.91	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 179 of 426

Table H-351

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.93	0	0.0
	1	67	20.99		0.0
	1	131	20.98		0.0
	64	0	20.91	0-1	0.0
	64	35	20.90	0	0.0
	64	69	20.80	0-1	0.0
	128	0	20.75		0.0
DFT-s-OFDM 16QAM	1	1	21.03	0-1	0.0
CP-OFDM QPSK	1	1	21.05	0-1.5	0.0

Table H-352

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.48	20.77	20.80	0	0.0
	1	53	20.48	20.80	20.88		0.0
	1	104	20.55	20.77	20.89		0.0
	50	0	20.51	20.63	20.74	0-1	0.0
	50	28	20.60	20.76	20.88	0	0.0
	50	56	20.62	20.62	20.80	0-1	0.0
	100	0	20.62	20.78	20.89		0.0
DFT-s-OFDM 16QAM	1	1	20.56	21.02	20.74	0-1	0.0
CP-OFDM QPSK	1	1	20.67	20.74	20.96	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 180 of 426

Table H-353

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.62	20.84	20.79	0	0.0
	1	40	20.48	20.85	20.78		0.0
	1	77	20.54	20.73	21.00		0.0
	36	0	20.55	20.72	20.81	0-1	0.0
	36	22	20.67	20.79	20.87	0	0.0
	36	43	20.56	20.76	20.79	0-1	0.0
	75	0	20.60	20.68	20.82		0.0
DFT-s-OFDM 16QAM	1	1	20.63	21.01	20.86	0-1	0.0
CP-OFDM QPSK	1	1	20.92	20.87	21.11	0-1.5	0.0

Table H-354

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.53	20.73	20.86	0	0.0
	1	26	20.58	20.70	20.94		0.0
	1	50	20.60	20.76	20.87		0.0
	25	0	20.62	20.70	20.77	0-1	0.0
	25	14	20.60	20.84	20.87	0	0.0
	25	27	20.67	20.75	20.83	0-1	0.0
	50	0	20.61	20.67	20.82		0.0
DFT-s-OFDM 16QAM	1	1	20.67	21.03	20.82	0-1	0.0
CP-OFDM QPSK	1	1	20.88	20.92	21.02	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 181 of 426

Table H-355

NR Band n25 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	20.58	20.70	20.65	0	0.0
	1	13	20.43	20.62	20.82		0.0
	1	23	20.51	20.70	20.75		0.0
	12	0	20.50	20.61	20.69	0-1	0.0
	12	7	20.53	20.60	20.77	0	0.0
	12	13	20.48	20.58	20.75	0-1	0.0
	25	0	20.44	20.61	20.66		0.0
DFT-s-OFDM 16QAM	1	1	20.65	21.04	20.69	0-1	0.0
CP-OFDM QPSK	1	1	20.79	20.91	20.91	0-1.5	0.0

Table H-356

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.20	0	0.0
	1	94	19.35		0.0
	1	186	19.29		0.0
	90	0	19.28	0-1	0.0
	90	49	19.27	0	0.0
	90	98	19.23	0-1	0.0
	180	0	19.30		0.0
DFT-s-OFDM 16QAM	1	1	19.40	0-1	0.0
CP-OFDM QPSK	1	1	19.23	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 182 of 426

Table H-357

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.31	0	0.0
	1	80	19.38		0.0
	1	158	19.28		0.0
	80	0	19.26	0-1	0.0
	80	40	19.30	0	0.0
	80	80	19.38	0-1	0.0
	160	0	19.32		0.0
DFT-s-OFDM 16QAM	1	1	19.42	0-1	0.0
CP-OFDM QPSK	1	1	19.33	0-1.5	0.0

Table H-358

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.28	0	0.0
	1	67	19.39		0.0
	1	131	19.37		0.0
	64	0	19.23	0-1	0.0
	64	35	19.31	0	0.0
	64	69	19.33	0-1	0.0
	128	0	19.33		0.0
DFT-s-OFDM 16QAM	1	1	19.40	0-1	0.0
CP-OFDM QPSK	1	1	19.49	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 183 of 426

Table H-359

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.03	19.06	19.25	0	0.0
	1	53	19.08	19.21	19.28		0.0
	1	104	19.22	19.16	19.39		0.0
	50	0	19.03	19.07	19.26	0-1	0.0
	50	28	19.15	19.12	19.37	0	0.0
	50	56	19.07	19.15	19.26	0-1	0.0
	100	0	18.96	19.07	19.35		0.0
DFT-s-OFDM 16QAM	1	1	18.99	19.41	19.28	0-1	0.0
CP-OFDM QPSK	1	1	19.07	19.13	19.35	0-1.5	0.0

Table H-360

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.17	19.17	19.21	0	0.0
	1	40	19.08	19.22	19.28		0.0
	1	77	19.20	19.26	19.49		0.0
	36	0	19.08	19.04	19.25	0-1	0.0
	36	22	19.13	19.24	19.38	0	0.0
	36	43	19.01	19.15	19.29	0-1	0.0
	75	0	19.09	19.04	19.26		0.0
DFT-s-OFDM 16QAM	1	1	19.07	19.42	19.32	0-1	0.0
CP-OFDM QPSK	1	1	19.16	19.24	19.49	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 184 of 426

Table H-361

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.09	19.21	19.19	0	0.0
	1	26	19.14	19.22	19.18		0.0
	1	50	19.17	19.06	19.26		0.0
	25	0	18.99	19.13	19.23	0-1	0.0
	25	14	19.13	19.23	19.16	0	0.0
	25	27	18.98	19.12	19.09	0-1	0.0
	50	0	19.00	19.15	19.17		0.0
DFT-s-OFDM 16QAM	1	1	19.07	19.40	19.31	0-1	0.0
CP-OFDM QPSK	1	1	19.18	19.23	19.33	0-1.5	0.0

Table H-362

NR Band n25 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.08	19.17	19.21	0	0.0
	1	13	18.98	19.20	19.14		0.0
	1	23	18.95	19.17	19.04		0.0
	12	0	18.99	19.12	19.17	0-1	0.0
	12	7	19.10	19.23	19.24	0	0.0
	12	13	18.97	19.14	19.17	0-1	0.0
	25	0	19.02	19.08	19.08		0.0
DFT-s-OFDM 16QAM	1	1	19.16	19.41	19.17	0-1	0.0
CP-OFDM OPSK	1	1	19.13	19.26	19.31	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 185 of 426

Table H-363

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.79	0	0.0
	1	94	17.00		0.0
	1	186	16.94		0.0
	90	0	16.93	0-1	0.0
	90	49	16.85	0	0.0
	90	98	16.86	0-1	0.0
	180	0	16.79		0.0
DFT-s-OFDM 16QAM	1	1	16.87	0-1	0.0
CP-OFDM QPSK	1	1	16.92	0-1.5	0.0

Table H-364

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.86	0	0.0
	1	80	16.99		0.0
	1	158	17.03		0.0
	80	0	16.95	0-1	0.0
	80	40	16.86	0	0.0
	80	80	16.92	0-1	0.0
	160	0	16.92		0.0
DFT-s-OFDM 16QAM	1	1	16.90	0-1	0.0
CP-OFDM QPSK	1	1	17.01	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 186 of 426

Table H-365

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.02	0	0.0
	1	67	17.04		0.0
	1	131	17.08		0.0
	64	0	16.93	0-1	0.0
	64	35	16.82	0	0.0
	64	69	16.86	0-1	0.0
	128	0	16.80		0.0
DFT-s-OFDM 16QAM	1	1	16.95	0-1	0.0
CP-OFDM QPSK	1	1	17.06	0-1.5	0.0

Table H-366

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.53	16.64	16.87	0	0.0
	1	53	16.64	16.81	16.97		0.0
	1	104	16.66	16.65	16.98		0.0
	50	0	16.58	16.68	16.85	0-1	0.0
	50	28	16.61	16.84	16.90	0	0.0
	50	56	16.64	16.74	16.87	0-1	0.0
	100	0	16.67	16.77	16.83		0.0
DFT-s-OFDM 16QAM	1	1	16.62	16.80	16.80	0-1	0.0
CP-OFDM OPSK	1	1	16.65	16.79	17.00	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 187 of 426

Table H-367

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.63	16.81	16.97	0	0.0
	1	40	16.61	16.82	16.95		0.0
	1	77	16.63	16.72	17.06		0.0
	36	0	16.61	16.71	16.81	0-1	0.0
	36	22	16.68	16.84	16.95	0	0.0
	36	43	16.61	16.75	16.91	0-1	0.0
	75	0	16.64	16.78	16.91		0.0
DFT-s-OFDM 16QAM	1	1	16.65	16.83	16.98	0-1	0.0
CP-OFDM QPSK	1	1	16.71	16.84	17.04	0-1.5	0.0

Table H-368

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.71	16.73	16.94	0	0.0
	1	26	16.70	16.81	16.96		0.0
	1	50	16.69	16.65	16.92		0.0
	25	0	16.62	16.72	16.78	0-1	0.0
	25	14	16.61	16.84	16.91	0	0.0
	25	27	16.68	16.76	16.87	0-1	0.0
	50	0	16.63	16.77	16.79		0.0
DFT-s-OFDM 16QAM	1	1	16.62	16.80	16.90	0-1	0.0
CP-OFDM QPSK	1	1	16.84	16.95	16.99	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 188 of 426

Table H-369

NR Band n25 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.74	16.80	16.77	0	0.0
	1	13	16.60	16.81	16.89		0.0
	1	23	16.68	16.76	16.76		0.0
	12	0	16.71	16.79	16.87	0-1	0.0
	12	7	16.56	16.82	16.82	0	0.0
	12	13	16.56	16.71	16.79	0-1	0.0
	25	0	16.56	16.78	16.84		0.0
DFT-s-OFDM 16QAM	1	1	16.85	16.89	16.83	0-1	0.0
CP-OFDM QPSK	1	1	16.97	17.10	16.98	0-1.5	0.0

Table H-370

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 35 MHz Bandwidth

NR Band n25 35 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.94	0	0.0
	1	94	10.12		0.0
	1	186	10.12		0.0
	90	0	10.02	0-1	0.0
	90	49	10.06	0	0.0
	90	98	10.05	0-1	0.0
	180	0	10.03		0.0
DFT-s-OFDM 16QAM	1	1	10.20	0-1	0.0
CP-OFDM QPSK	1	1	10.13	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 189 of 426

Table H-371

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 30 MHz Bandwidth

NR Band n25 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.03	0	0.0
	1	80	10.13		0.0
	1	158	10.10		0.0
	80	0	10.00	0-1	0.0
	80	40	10.10	0	0.0
	80	80	10.01	0-1	0.0
	160	0	10.04		0.0
DFT-s-OFDM 16QAM	1	1	10.21	0-1	0.0
CP-OFDM QPSK	1	1	10.16	0-1.5	0.0

Table H-372

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 25 MHz Bandwidth

NR Band n25 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			376500 (1882.5 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.05	0	0.0
	1	67	10.14		0.0
	1	131	10.11		0.0
	64	0	10.07	0-1	0.0
	64	35	10.08	0	0.0
	64	69	10.13	0-1	0.0
	128	0	10.09		0.0
DFT-s-OFDM 16QAM	1	1	10.22	0-1	0.0
CP-OFDM QPSK	1	1	10.18	0-1.5	0.0

Table H-373

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 20 MHz Bandwidth

NR Band n25 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	372000 (1860 MHz)	376500 (1882.5 MHz)	381000 (1905 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	9.76	9.84	9.88	0	0.0
	1	53	9.70	9.94	10.02		0.0
	1	104	9.74	9.99	10.18		0.0
	50	0	9.85	9.86	10.01	0-1	0.0
	50	28	9.76	9.90	10.05	0	0.0
	50	56	9.76	9.91	10.05	0-1	0.0
	100	0	9.84	10.00	10.06		0.0
DFT-s-OFDM 16QAM	1	1	9.72	10.20	9.94	0-1	0.0
CP-OFDM QPSK	1	1	9.93	9.97	10.10	0-1.5	0.0

Table H-374

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 15 MHz Bandwidth

NR Band n25 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371500 (1857.5 MHz)	376500 (1882.5 MHz)	381500 (1907.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	9.75	9.93	9.99	0	0.0
	1	40	9.82	9.85	10.06		0.0
	1	77	9.88	9.91	10.22		0.0
	36	0	9.74	9.86	10.03	0-1	0.0
	36	22	9.88	9.98	10.11	0	0.0
	36	43	9.74	9.97	10.06	0-1	0.0
	75	0	9.76	9.90	10.10		0.0
DFT-s-OFDM 16QAM	1	1	9.78	10.20	10.02	0-1	0.0
CP-OFDM QPSK	1	1	9.99	10.03	10.13	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 191 of 426

Table H-375

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 10 MHz Bandwidth

NR Band n25 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	371000 (1855 MHz)	376500 (1882.5 MHz)	382000 (1910 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	9.79	9.87	9.96	0	0.0
	1	26	9.89	9.88	9.98		0.0
	1	50	9.81	9.80	9.96		0.0
	25	0	9.91	9.86	9.98	0-1	0.0
	25	14	9.82	9.92	10.08	0	0.0
	25	27	9.90	9.93	10.02	0-1	0.0
	50	0	9.85	9.92	10.02		0.0
DFT-s-OFDM 16QAM	1	1	9.80	10.23	10.11	0-1	0.0
CP-OFDM QPSK	1	1	10.04	10.01	10.14	0-1.5	0.0

Table H-376

NR Band n25 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 5 MHz Bandwidth

NR Band n25 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	370500 (1852.5 MHz)	376500 (1882.5 MHz)	382500 (1912.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	9.86	9.98	9.95	0	0.0
	1	13	9.80	9.90	9.98		0.0
	1	23	9.79	9.97	9.91		0.0
	12	0	9.75	9.92	10.08	0-1	0.0
	12	7	9.71	9.91	10.02	0	0.0
	12	13	9.79	9.86	9.93	0-1	0.0
	25	0	9.88	9.92	9.92		0.0
DFT-s-OFDM 16QAM	1	1	9.94	10.21	10.04	0-1	0.0
CP-OFDM OPSK	1	1	9.97	10.16	10.17	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 192 of 426

H.2.18 NR Band n30 Antenna B

Table H-377

NR Band n30 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	22.05	0	0.0
	1	13	22.05		0.0
	1	23	22.00		0.0
	12	0	21.05	0-1	1.0
	12	7	22.08	0	0.0
	12	13	21.03	0-1	1.0
	25	0	21.06		1.0
DFT-s-OFDM 16QAM	1	1	21.01	0-1	1.0
CP-OFDM QPSK	1	1	20.71	0-1.5	1.5

Table H-378

NR Band n30 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.16	0	0.0
	1	13	19.12		0.0
	1	23	19.04		0.0
	12	0	19.13	0-1	0.0
	12	7	19.12	0	0.0
	12	13	19.17	0-1	0.0
	25	0	19.16		0.0
DFT-s-OFDM 16QAM	1	1	19.26	0-1	0.0
CP-OFDM QPSK	1	1	19.20	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 193 of 426

Table H-379
NR Band n30 Measured P_{Limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5
MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.59	0	0.0
	1	13	10.57		0.0
	1	23	10.47		0.0
	12	0	10.54	0-1	0.0
	12	7	10.60	0	0.0
	12	13	10.57	0-1	0.0
	25	0	10.57		0.0
DFT-s-OFDM 16QAM	1	1	10.61	0-1	0.0
CP-OFDM QPSK	1	1	10.72	0-1.5	0.0

H.2.19 NR Band n30 Antenna G

Table H-380

NR Band n30 Measured P_{Limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	20.66	0	0.0
	1	13	20.72		0.0
	1	23	20.60		0.0
	12	0	20.64	0-1	0.0
	12	7	20.71	0	0.0
	12	13	20.60	0-1	0.0
	25	0	20.60		0.0
DFT-s-OFDM 16QAM	1	1	20.75	0-1	0.0
CP-OFDM QPSK	1	1	20.81	0-1.5	0.0

Table H-381

NR Band n30 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.42	0	0.0
	1	13	18.43		0.0
	1	23	18.39		0.0
	12	0	18.46	0-1	0.0
	12	7	18.48	0	0.0
	12	13	18.43	0-1	0.0
	25	0	18.46		0.0
DFT-s-OFDM 16QAM	1	1	18.98	0-1	0.0
CP-OFDM QPSK	1	1	18.53	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 195 of 426

Table H-382

NR Band n30 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.18	0	0.0
	1	13	18.16		0.0
	1	23	18.05		0.0
	12	0	18.24	0-1	0.0
	12	7	18.13	0	0.0
	12	13	18.10	0-1	0.0
	25	0	18.08		0.0
DFT-s-OFDM 16QAM	1	1	18.46	0-1	0.0
CP-OFDM QPSK	1	1	18.40	0-1.5	0.0

Table H-383

NR Band n30 Measured P_{Limit} for DSI = 4 (Folder Open – Grip) – 5 MHz Bandwidth

NR Band n30 5 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			462000 (2310 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.53	0	0.0
	1	13	9.54		0.0
	1	23	9.59		0.0
	12	0	9.52	0-1	0.0
	12	7	9.66	0	0.0
	12	13	9.58	0-1	0.0
	25	0	9.62		0.0
DFT-s-OFDM 16QAM	1	1	9.87	0-1	0.0
CP-OFDM QPSK	1	1	9.67	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 196 of 426

H.2.20 NR Band n7 Antenna B

Table H-384

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.25	0	0.0
	1	108	23.13		0.0
	1	214	22.93		0.0
	108	0	22.25	0-1	1.0
	108	54	23.09	0	0.0
	108	108	22.08	0-1	1.0
	216	0	22.09		1.0
DFT-s-OFDM 16QAM	1	1	22.23	0-1	1.0
CP-OFDM QPSK	1	1	21.80	0-1.5	1.5

Table H-385

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.17	0	0.0
	1	94	23.19		0.0
	1	186	22.94		0.0
	90	0	22.22	0-1	1.0
	90	49	23.12	0	0.0
	90	98	22.08	0-1	1.0
	180	0	22.09		1.0
DFT-s-OFDM 16QAM	1	1	22.22	0-1	1.0
CP-OFDM QPSK	1	1	21.77	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 197 of 426

Table H-386

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.20	0	0.0
	1	80	23.08		0.0
	1	158	22.89		0.0
	80	0	22.22	0-1	1.0
	80	40	23.12	0	0.0
	80	80	22.08	0-1	1.0
	160	0	22.10		1.0
DFT-s-OFDM 16QAM	1	1	22.24	0-1	1.0
CP-OFDM QPSK	1	1	21.85	0-1.5	1.5

Table H-387

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.19	0	0.0
	1	67	23.17		0.0
	1	131	23.06		0.0
	64	0	22.23	0-1	1.0
	64	35	22.99	0	0.0
	64	69	21.99	0-1	1.0
	128	0	22.23		1.0
DFT-s-OFDM 16QAM	1	1	22.25	0-1	1.0
CP-OFDM QPSK	1	1	21.83	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 198 of 426

Table H-388

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.13	22.93	22.90	0	0.0
	1	53	23.08	22.88	22.82		0.0
	1	104	22.94	22.94	22.75		0.0
	50	0	22.06	21.99	21.88	0-1	1.0
	50	28	23.03	22.98	22.85	0	0.0
	50	56	22.02	21.92	21.80	0-1	1.0
	100	0	22.07	21.97	21.86		1.0
DFT-s-OFDM 16QAM	1	1	22.22	22.09	21.88	0-1	1.0
CP-OFDM QPSK	1	1	21.65	21.59	21.46	0-1.5	1.5

Table H-389

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.12	22.96	22.82	0	0.0
	1	40	23.07	22.86	22.78		0.0
	1	77	22.96	22.92	22.80		0.0
	36	0	22.16	21.94	21.84	0-1	1.0
	36	22	23.03	22.91	22.85	0	0.0
	36	43	21.99	21.91	21.83	0-1	1.0
	75	0	22.04	21.93	21.87		1.0
DFT-s-OFDM 16QAM	1	1	22.20	22.02	21.51	0-1	1.0
CP-OFDM QPSK	1	1	21.70	21.54	21.21	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 199 of 426

Table H-390

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.08	22.98	22.83	0	0.0
	1	26	23.08	22.89	22.87		0.0
	1	50	23.07	22.86	22.83		0.0
	25	0	22.12	22.01	21.89	0-1	1.0
	25	14	23.04	22.91	22.78	0	0.0
	25	27	22.12	21.93	21.85	0-1	1.0
	50	0	22.14	21.92	21.84		1.0
DFT-s-OFDM 16QAM	1	1	22.31	21.96	21.72	0-1	1.0
CP-OFDM QPSK	1	1	21.89	21.57	21.52	0-1.5	1.5

Table H-391

NR Band n7 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.23	22.97	22.85	0	0.0
	1	13	23.11	22.96	22.82		0.0
	1	23	23.22	22.92	22.89		0.0
	12	0	22.09	21.82	21.75	0-1	1.0
	12	7	23.12	22.86	22.81	0	0.0
	12	13	22.12	21.87	21.82	0-1	1.0
	25	0	22.19	21.94	21.83		1.0
DFT-s-OFDM 16QAM	1	1	22.36	21.83	21.79	0-1	1.0
CP-OFDM OPSK	1	1	21.86	21.53	21.41	0-1.5	1.5

Table H-392

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.14	0	0.0
	1	108	19.07		0.0
	1	214	18.85		0.0
	108	0	19.09	0-1	0.0
	108	54	19.04	0	0.0
	108	108	19.02	0-1	0.0
	216	0	19.02		0.0
DFT-s-OFDM 16QAM	1	1	19.28	0-1	0.0
CP-OFDM QPSK	1	1	19.16	0-1.5	0.0

Table H-393

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.17	0	0.0
	1	94	18.99		0.0
	1	186	18.83		0.0
	90	0	19.07	0-1	0.0
	90	49	19.07	0	0.0
	90	98	18.96	0-1	0.0
	180	0	18.97		0.0
DFT-s-OFDM 16QAM	1	1	19.06	0-1	0.0
CP-OFDM QPSK	1	1	19.22	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 201 of 426

Table H-394

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.16	0	0.0
	1	80	19.02		0.0
	1	158	18.89		0.0
	80	0	19.09	0-1	0.0
	80	40	19.02	0	0.0
	80	80	18.98	0-1	0.0
	160	0	19.11		0.0
DFT-s-OFDM 16QAM	1	1	19.30	0-1	0.0
CP-OFDM QPSK	1	1	19.22	0-1.5	0.0

Table H-395

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.15	0	0.0
	1	67	19.13		0.0
	1	131	18.96		0.0
	64	0	19.11	0-1	0.0
	64	35	19.00	0	0.0
	64	69	18.97	0-1	0.0
	128	0	18.96		0.0
DFT-s-OFDM 16QAM	1	1	19.32	0-1	0.0
CP-OFDM QPSK	1	1	19.21	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 202 of 426

Table H-396

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.01	18.92	18.80	0	0.0
	1	53	18.97	18.85	18.85		0.0
	1	104	18.98	18.72	18.70		0.0
	50	0	19.01	18.96	18.85	0-1	0.0
	50	28	19.01	18.96	18.83	0	0.0
	50	56	18.98	18.82	18.76	0-1	0.0
	100	0	18.98	18.92	18.83		0.0
DFT-s-OFDM 16QAM	1	1	19.02	19.06	18.76	0-1	0.0
CP-OFDM QPSK	1	1	19.12	18.99	18.84	0-1.5	0.0

Table H-397

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.02	18.97	18.77	0	0.0
	1	40	18.92	18.81	18.78		0.0
	1	77	18.93	18.80	18.79		0.0
	36	0	18.99	18.93	18.87	0-1	0.0
	36	22	18.93	18.88	18.86	0	0.0
	36	43	18.95	18.89	18.77	0-1	0.0
	75	0	18.97	18.88	18.87		0.0
DFT-s-OFDM 16QAM	1	1	19.13	19.07	18.95	0-1	0.0
CP-OFDM QPSK	1	1	19.05	18.99	18.87	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 203 of 426

Table H-398

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.03	18.92	18.66	0	0.0
	1	26	19.03	18.92	18.71		0.0
	1	50	19.02	18.84	18.69		0.0
	25	0	19.07	18.96	18.70	0-1	0.0
	25	14	18.98	18.80	18.60	0	0.0
	25	27	19.03	18.90	18.66	0-1	0.0
	50	0	19.08	18.91	18.70		0.0
DFT-s-OFDM 16QAM	1	1	19.13	19.09	18.79	0-1	0.0
CP-OFDM QPSK	1	1	19.31	19.05	18.93	0-1.5	0.0

Table H-399

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.12	18.92	18.69	0	0.0
	1	13	19.18	18.90	18.75		0.0
	1	23	19.21	18.90	18.81		0.0
	12	0	19.04	18.82	18.57	0-1	0.0
	12	7	19.09	18.87	18.61	0	0.0
	12	13	19.07	18.82	18.64	0-1	0.0
	25	0	19.12	18.86	18.67		0.0
DFT-s-OFDM 16QAM	1	1	19.30	19.06	18.63	0-1	0.0
CP-OFDM QPSK	1	1	19.36	18.96	18.87	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 204 of 426

Table H-400

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.10	0	0.0
	1	108	11.11		0.0
	1	214	10.93		0.0
	108	0	11.13	0-1	0.0
	108	54	11.14	0	0.0
	108	108	10.95	0-1	0.0
	216	0	11.09		0.0
DFT-s-OFDM 16QAM	1	1	11.15	0-1	0.0
CP-OFDM QPSK	1	1	11.13	0-1.5	0.0

Table H-401

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.05	0	0.0
	1	94	11.13		0.0
	1	186	10.88		0.0
	90	0	11.11	0-1	0.0
	90	49	11.13	0	0.0
	90	98	11.05	0-1	0.0
	180	0	11.09		0.0
DFT-s-OFDM 16QAM	1	1	11.17	0-1	0.0
CP-OFDM QPSK	1	1	11.18	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 205 of 426

Table H-402

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.11	0	0.0
	1	80	11.05		0.0
	1	158	10.91		0.0
	80	0	11.12	0-1	0.0
	80	40	11.16	0	0.0
	80	80	11.05	0-1	0.0
	160	0	11.12		0.0
DFT-s-OFDM 16QAM	1	1	11.17	0-1	0.0
CP-OFDM QPSK	1	1	11.12	0-1.5	0.0

Table H-403

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	11.16	0	0.0
	1	67	11.16		0.0
	1	131	11.08		0.0
	64	0	11.14	0-1	0.0
	64	35	11.09	0	0.0
	64	69	11.07	0-1	0.0
	128	0	11.11		0.0
DFT-s-OFDM 16QAM	1	1	11.16	0-1	0.0
CP-OFDM QPSK	1	1	11.17	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 206 of 426

Table H-404

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.02	10.99	10.81	0	0.0
	1	53	10.97	10.95	10.76		0.0
	1	104	10.96	10.84	10.81		0.0
	50	0	11.05	10.99	10.77	0-1	0.0
	50	28	11.01	10.94	10.85	0	0.0
	50	56	11.00	10.90	10.85	0-1	0.0
	100	0	11.05	11.01	10.83		0.0
DFT-s-OFDM 16QAM	1	1	11.07	11.16	10.78	0-1	0.0
CP-OFDM QPSK	1	1	11.16	11.11	10.77	0-1.5	0.0

Table H-405

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.03	11.06	10.78	0	0.0
	1	40	10.98	10.90	10.80		0.0
	1	77	10.96	10.86	10.90		0.0
	36	0	11.01	11.04	10.85	0-1	0.0
	36	22	10.96	10.85	10.89	0	0.0
	36	43	10.99	10.91	10.88	0-1	0.0
	75	0	11.07	10.94	10.85		0.0
DFT-s-OFDM 16QAM	1	1	11.09	11.18	10.83	0-1	0.0
CP-OFDM QPSK	1	1	11.21	11.13	10.89	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 207 of 426

Table H-406

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.07	11.08	10.80	0	0.0
	1	26	10.96	10.98	10.77		0.0
	1	50	10.92	10.94	10.71		0.0
	25	0	11.10	11.00	10.80	0-1	0.0
	25	14	11.03	11.01	10.71	0	0.0
	25	27	11.03	10.97	10.72	0-1	0.0
	50	0	11.02	11.00	10.69		0.0
DFT-s-OFDM 16QAM	1	1	11.12	11.16	10.80	0-1	0.0
CP-OFDM QPSK	1	1	11.19	11.17	10.90	0-1.5	0.0

Table H-407

NR Band n7 Measured P_{limit} for DSI = 0/4 (Folder Open-Body, Folder Open – Grip) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	11.18	11.03	10.75	0	0.0
	1	13	11.16	11.02	10.80		0.0
	1	23	11.16	11.10	10.76		0.0
	12	0	11.16	11.02	10.75	0-1	0.0
	12	7	11.17	11.08	10.73	0	0.0
	12	13	11.19	11.06	10.80	0-1	0.0
	25	0	11.20	10.98	10.76		0.0
DFT-s-OFDM 16QAM	1	1	11.25	11.18	10.79	0-1	0.0
CP-OFDM QPSK	1	1	11.33	11.22	10.92	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 208 of 426

H.2.21 NR Band n7 Antenna G

Table H-408

NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.79	0	0.0
	1	108	17.79		0.0
	1	214	17.74		0.0
	108	0	17.82	0-1	0.0
	108	54	17.79	0	0.0
	108	108	17.79	0-1	0.0
	216	0	17.83		0.0
DFT-s-OFDM 16QAM	1	1	17.79	0-1	0.0
CP-OFDM QPSK	1	1	17.83	0-1.5	0.0

Table H-409

NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.71	0	0.0
	1	94	17.90		0.0
	1	186	17.70		0.0
	90	0	17.79	0-1	0.0
	90	49	17.83	0	0.0
	90	98	17.81	0-1	0.0
	180	0	17.82		0.0
DFT-s-OFDM 16QAM	1	1	17.80	0-1	0.0
CP-OFDM QPSK	1	1	17.79	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 209 of 426

Table H-410
NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.83	0	0.0
	1	80	17.89		0.0
	1	158	17.82		0.0
	80	0	17.74	0-1	0.0
	80	40	17.93	0	0.0
	80	80	17.80	0-1	0.0
	160	0	17.76		0.0
DFT-s-OFDM 16QAM	1	1	17.83	0-1	0.0
CP-OFDM QPSK	1	1	17.78	0-1.5	0.0

Table H-411
NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.80	0	0.0
	1	67	17.89		0.0
	1	131	17.95		0.0
	64	0	17.79	0-1	0.0
	64	35	17.87	0	0.0
	64	69	17.76	0-1	0.0
	128	0	17.75		0.0
DFT-s-OFDM 16QAM	1	1	17.85	0-1	0.0
CP-OFDM QPSK	1	1	17.84	0-1.5	0.0

Table H-412

NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.54	17.65	17.61	0	0.0
	1	53	17.60	17.61	17.69		0.0
	1	104	17.58	17.52	17.71		0.0
	50	0	17.61	17.54	17.65	0-1	0.0
	50	28	17.66	17.57	17.67	0	0.0
	50	56	17.61	17.59	17.70	0-1	0.0
	100	0	17.69	17.62	17.78		0.0
DFT-s-OFDM 16QAM	1	1	17.50	17.80	17.64	0-1	0.0
CP-OFDM QPSK	1	1	17.51	17.56	17.68	0-1.5	0.0

Table H-413

NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.50	17.65	17.63	0	0.0
	1	40	17.62	17.61	17.69		0.0
	1	77	17.57	17.58	17.74		0.0
	36	0	17.50	17.59	17.64	0-1	0.0
	36	22	17.67	17.64	17.72	0	0.0
	36	43	17.59	17.53	17.76	0-1	0.0
	75	0	17.64	17.55	17.65		0.0
DFT-s-OFDM 16QAM	1	1	17.51	17.81	17.61	0-1	0.0
CP-OFDM QPSK	1	1	17.52	17.63	17.69	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 211 of 426

Table H-414

NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.59	17.68	17.70	0	0.0
	1	26	17.61	17.65	17.56		0.0
	1	50	17.62	17.70	17.62		0.0
	25	0	17.62	17.66	17.64	0-1	0.0
	25	14	17.59	17.61	17.69	0	0.0
	25	27	17.54	17.64	17.55	0-1	0.0
	50	0	17.61	17.72	17.63		0.0
DFT-s-OFDM 16QAM	1	1	17.61	17.83	17.60	0-1	0.0
CP-OFDM QPSK	1	1	17.73	17.75	17.69	0-1.5	0.0

Table H-415

NR Band n7 Measured P_{limit} for DSI = 0 (Folder Open-Body) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.67	17.65	17.60	0	0.0
	1	13	17.70	17.65	17.69		0.0
	1	23	17.68	17.60	17.68		0.0
	12	0	17.64	17.64	17.62	0-1	0.0
	12	7	17.71	17.70	17.72	0	0.0
	12	13	17.60	17.64	17.71	0-1	0.0
	25	0	17.67	17.66	17.65		0.0
DFT-s-OFDM 16QAM	1	1	17.76	17.80	17.68	0-1	0.0
CP-OFDM OPSK	1	1	17.73	17.68	17.63	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 212 of 426

Table H-416
NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.09	0	0.0
	1	108	17.03		0.0
	1	214	17.03		0.0
	108	0	17.06	0-1	0.0
	108	54	17.07	0	0.0
	108	108	16.98	0-1	0.0
	216	0	17.22		0.0
DFT-s-OFDM 16QAM	1	1	16.97	0-1	0.0
CP-OFDM QPSK	1	1	17.16	0-1.5	0.0

Table H-417
NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.02	0	0.0
	1	94	17.08		0.0
	1	186	16.93		0.0
	90	0	17.00	0-1	0.0
	90	49	17.15	0	0.0
	90	98	17.08	0-1	0.0
	180	0	17.10		0.0
DFT-s-OFDM 16QAM	1	1	16.97	0-1	0.0
CP-OFDM QPSK	1	1	17.21	0-1.5	0.0

Table H-418

NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.13	0	0.0
	1	80	17.10		0.0
	1	158	17.13		0.0
	80	0	17.05	0-1	0.0
	80	40	17.12	0	0.0
	80	80	17.03	0-1	0.0
	160	0	17.07		0.0
DFT-s-OFDM 16QAM	1	1	17.00	0-1	0.0
CP-OFDM QPSK	1	1	17.16	0-1.5	0.0

Table H-419

NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.12	0	0.0
	1	67	17.08		0.0
	1	131	17.06		0.0
	64	0	17.01	0-1	0.0
	64	35	16.98	0	0.0
	64	69	17.07	0-1	0.0
	128	0	17.05		0.0
DFT-s-OFDM 16QAM	1	1	17.01	0-1	0.0
CP-OFDM QPSK	1	1	17.14	0-1.5	0.0

Table H-420

NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.85	16.99	16.89	0	0.0
	1	53	16.86	16.89	16.97		0.0
	1	104	16.86	16.91	17.01		0.0
	50	0	16.85	16.96	16.92	0-1	0.0
	50	28	16.84	16.92	16.97	0	0.0
	50	56	16.94	16.85	16.90	0-1	0.0
	100	0	16.93	16.93	17.03		0.0
DFT-s-OFDM 16QAM	1	1	16.74	16.89	16.84	0-1	0.0
CP-OFDM QPSK	1	1	16.82	16.89	17.03	0-1.5	0.0

Table H-421

NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.91	17.03	17.00	0	0.0
	1	40	16.90	16.92	17.02		0.0
	1	77	16.92	16.97	17.15		0.0
	36	0	16.76	16.96	16.96	0-1	0.0
	36	22	16.93	16.99	17.12	0	0.0
	36	43	16.74	16.82	17.00	0-1	0.0
	75	0	16.84	16.90	16.98		0.0
DFT-s-OFDM 16QAM	1	1	16.86	16.89	16.92	0-1	0.0
CP-OFDM QPSK	1	1	16.89	17.07	17.15	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 215 of 426

Table H-422

NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.01	17.03	16.96	0	0.0
	1	26	16.89	17.03	16.87		0.0
	1	50	16.88	16.87	16.90		0.0
	25	0	16.86	16.97	16.87	0-1	0.0
	25	14	16.89	16.98	16.83	0	0.0
	25	27	16.78	16.90	16.77	0-1	0.0
	50	0	16.85	16.91	16.86		0.0
DFT-s-OFDM 16QAM	1	1	16.79	16.89	16.82	0-1	0.0
CP-OFDM QPSK	1	1	16.98	16.95	17.10	0-1.5	0.0

Table H-423

NR Band n7 Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.89	17.00	16.92	0	0.0
	1	13	17.10	16.99	16.97		0.0
	1	23	16.82	16.99	16.88		0.0
	12	0	16.89	16.96	16.89	0-1	0.0
	12	7	17.07	17.00	16.92	0	0.0
	12	13	16.94	16.94	16.88	0-1	0.0
	25	0	16.93	16.92	16.82		0.0
DFT-s-OFDM 16QAM	1	1	16.97	16.96	16.86	0-1	0.0
CP-OFDM OPSK	1	1	17.04	16.95	17.20	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 216 of 426

Table H-424

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.35	0	0.0
	1	108	16.30		0.0
	1	214	16.13		0.0
	108	0	16.31	0-1	0.0
	108	54	16.33	0	0.0
	108	108	16.28	0-1	0.0
	216	0	16.38		0.0
DFT-s-OFDM 16QAM	1	1	16.65	0-1	0.0
CP-OFDM QPSK	1	1	16.42	0-1.5	0.0

Table H-425

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.26	0	0.0
	1	94	16.38		0.0
	1	186	16.19		0.0
	90	0	16.25	0-1	0.0
	90	49	16.35	0	0.0
	90	98	16.28	0-1	0.0
	180	0	16.33		0.0
DFT-s-OFDM 16QAM	1	1	16.66	0-1	0.0
CP-OFDM QPSK	1	1	16.40	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 217 of 426

Table H-426

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.28	0	0.0
	1	80	16.36		0.0
	1	158	16.28		0.0
	80	0	16.28	0-1	0.0
	80	40	16.33	0	0.0
	80	80	16.26	0-1	0.0
	160	0	16.31		0.0
DFT-s-OFDM 16QAM	1	1	16.65	0-1	0.0
CP-OFDM QPSK	1	1	16.44	0-1.5	0.0

Table H-427

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.36	0	0.0
	1	67	16.39		0.0
	1	131	16.47		0.0
	64	0	16.25	0-1	0.0
	64	35	16.36	0	0.0
	64	69	16.26	0-1	0.0
	128	0	16.24		0.0
DFT-s-OFDM 16QAM	1	1	16.67	0-1	0.0
CP-OFDM QPSK	1	1	16.47	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 218 of 426

Table H-428

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.14	16.17	16.09	0	0.0
	1	53	16.09	16.16	16.21		0.0
	1	104	16.16	16.20	16.30		0.0
	50	0	16.09	16.13	16.17	0-1	0.0
	50	28	16.18	16.19	16.20	0	0.0
	50	56	16.15	16.11	16.21	0-1	0.0
	100	0	16.20	16.13	16.23		0.0
DFT-s-OFDM 16QAM	1	1	16.07	16.65	16.11	0-1	0.0
CP-OFDM QPSK	1	1	16.19	16.14	16.20	0-1.5	0.0

Table H-429

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.19	16.18	16.24	0	0.0
	1	40	16.08	16.11	16.33		0.0
	1	77	16.18	16.24	16.29		0.0
	36	0	16.01	16.13	16.16	0-1	0.0
	36	22	16.11	16.17	16.28	0	0.0
	36	43	16.11	16.12	16.22	0-1	0.0
	75	0	16.04	16.13	16.20		0.0
DFT-s-OFDM 16QAM	1	1	16.05	16.66	16.13	0-1	0.0
CP-OFDM QPSK	1	1	16.17	16.22	16.29	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 219 of 426

Table H-430

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.27	16.21	16.27	0	0.0
	1	26	16.11	16.29	16.26		0.0
	1	50	16.12	16.22	16.09		0.0
	25	0	16.19	16.13	16.12	0-1	0.0
	25	14	16.13	16.33	16.16	0	0.0
	25	27	16.09	16.24	16.12	0-1	0.0
	50	0	16.17	16.18	16.19		0.0
DFT-s-OFDM 16QAM	1	1	16.16	16.66	16.14	0-1	0.0
CP-OFDM QPSK	1	1	16.38	16.35	16.29	0-1.5	0.0

Table H-431

NR Band n7 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.16	16.19	16.25	0	0.0
	1	13	16.24	16.33	16.18		0.0
	1	23	16.16	16.17	16.13		0.0
	12	0	16.17	16.13	16.14	0-1	0.0
	12	7	16.18	16.27	16.16	0	0.0
	12	13	16.22	16.15	16.17	0-1	0.0
	25	0	16.27	16.18	16.08		0.0
DFT-s-OFDM 16QAM	1	1	16.30	16.77	16.20	0-1	0.0
CP-OFDM QPSK	1	1	16.46	16.34	16.39	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 220 of 426

Table H-432

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 40 MHz Bandwidth

NR Band n7 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	8.50	0	0.0
	1	108	8.34		0.0
	1	214	8.42		0.0
	108	0	8.39	0-1	0.0
	108	54	8.43	0	0.0
	108	108	8.30	0-1	0.0
	216	0	8.38		0.0
DFT-s-OFDM 16QAM	1	1	8.39	0-1	0.0
CP-OFDM QPSK	1	1	8.46	0-1.5	0.0

Table H-433

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 35 MHz Bandwidth

NR Band n7 35 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	8.35	0	0.0
	1	94	8.48		0.0
	1	186	8.30		0.0
	90	0	8.33	0-1	0.0
	90	49	8.40	0	0.0
	90	98	8.44	0-1	0.0
	180	0	8.38		0.0
DFT-s-OFDM 16QAM	1	1	8.41	0-1	0.0
CP-OFDM QPSK	1	1	8.53	0-1.5	0.0

Table H-434

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 30 MHz Bandwidth

NR Band n7 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	8.46	0	0.0
	1	80	8.48		0.0
	1	158	8.27		0.0
	80	0	8.31	0-1	0.0
	80	40	8.45	0	0.0
	80	80	8.41	0-1	0.0
	160	0	8.42		0.0
DFT-s-OFDM 16QAM	1	1	8.43	0-1	0.0
CP-OFDM QPSK	1	1	8.53	0-1.5	0.0

Table H-435

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 25 MHz Bandwidth

NR Band n7 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			507000 (2535 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	8.35	0	0.0
	1	67	8.46		0.0
	1	131	8.29		0.0
	64	0	8.36	0-1	0.0
	64	35	8.42	0	0.0
	64	69	8.37	0-1	0.0
	128	0	8.29		0.0
DFT-s-OFDM 16QAM	1	1	8.47	0-1	0.0
CP-OFDM QPSK	1	1	8.57	0-1.5	0.0

Table H-436

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 20 MHz Bandwidth

NR Band n7 20 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502000 (2510 MHz)	507000 (2535 MHz)	512000 (2560 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	8.17	8.17	8.12	0	0.0
	1	53	8.06	8.26	8.08		0.0
	1	104	8.08	8.27	8.23		0.0
	50	0	8.17	8.12	8.15	0-1	0.0
	50	28	8.09	8.24	8.18	0	0.0
	50	56	8.14	8.15	8.20	0-1	0.0
	100	0	8.12	8.15	8.17		0.0
DFT-s-OFDM 16QAM	1	1	7.99	8.39	8.06	0-1	0.0
CP-OFDM QPSK	1	1	8.13	8.24	8.26	0-1.5	0.0

Table H-437

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 15 MHz Bandwidth

NR Band n7 15 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501500 (2507.5 MHz)	507000 (2535 MHz)	512500 (2562.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	8.28	8.22	8.19	0	0.0
	1	40	8.13	8.26	8.34		0.0
	1	77	8.11	8.28	8.44		0.0
	36	0	8.08	8.11	8.18	0-1	0.0
	36	22	8.13	8.19	8.27	0	0.0
	36	43	8.10	8.14	8.23	0-1	0.0
	75	0	8.13	8.12	8.17		0.0
DFT-s-OFDM 16QAM	1	1	8.04	8.41	8.21	0-1	0.0
CP-OFDM QPSK	1	1	8.27	8.29	8.34	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 223 of 426

Table H-438

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 10 MHz Bandwidth

NR Band n7 10 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501000 (2505 MHz)	507000 (2535 MHz)	513000 (2565 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	8.13	8.17	8.10	0	0.0
	1	26	8.09	8.30	8.20		0.0
	1	50	8.00	8.15	7.97		0.0
	25	0	8.16	8.22	8.09	0-1	0.0
	25	14	8.06	8.26	8.29	0	0.0
	25	27	8.02	8.24	8.08	0-1	0.0
	50	0	8.14	8.21	8.09		0.0
DFT-s-OFDM 16QAM	1	1	8.04	8.39	8.10	0-1	0.0
CP-OFDM QPSK	1	1	8.29	8.37	8.23	0-1.5	0.0

Table H-439

NR Band n7 Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 5 MHz Bandwidth

NR Band n7 5 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500500 (2502.5 MHz)	507000 (2535 MHz)	513500 (2567.5 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	8.16	8.19	8.18	0	0.0
	1	13	8.16	8.35	8.23		0.0
	1	23	8.16	8.22	8.09		0.0
	12	0	8.20	8.23	8.15	0-1	0.0
	12	7	8.23	8.38	8.29	0	0.0
	12	13	8.16	8.27	8.19	0-1	0.0
	25	0	8.16	8.24	8.18		0.0
DFT-s-OFDM 16QAM	1	1	8.14	8.42	8.05	0-1	0.0
CP-OFDM OPSK	1	1	8.34	8.40	8.36	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 224 of 426

H.2.22 NR Band n41 PC2/PC1.5 Path 1

Table H-440

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
Modulation	RB Size	RB Offset	Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
			508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.31	19.27	0	0.0
	1	123	19.35	19.34		0.0
	1	243	19.43	19.59		0.0
	120	0	19.31	19.36	0-1	0.0
	120	63	19.35	19.36	0	0.0
	120	125	19.39	19.44	0-1	0.0
	243	0	19.46	19.41		0.0
DFT-s-OFDM 16QAM	1	1	19.33	19.35	0-1	0.0
CP-OFDM QPSK	1	1	19.36	19.41	0-1.5	0.0

Table H-441

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
Modulation	RB Size	RB Offset	Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
			507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.21	19.35	0	0.0
	1	109	19.49	19.32		0.0
	1	215	19.36	19.47		0.0
	108	0	19.32	19.33	0-1	0.0
	108	55	19.39	19.39	0	0.0
	108	109	19.33	19.49	0-1	0.0
	216	0	19.34	19.44		0.0
DFT-s-OFDM 16QAM	1	1	19.38	19.33	0-1	0.0
CP-OFDM QPSK	1	1	19.26	19.29	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 225 of 426

Table H-442

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.25	19.39	0	0.0
	1	95	19.31	19.34		0.0
	1	187	19.47	19.53		0.0
	90	0	19.31	19.35	0-1	0.0
	90	50	19.42	19.42	0	0.0
	90	99	19.38	19.43	0-1	0.0
	180	0	19.45	19.44		0.0
DFT-s-OFDM 16QAM	1	1	19.40	19.40	0-1	0.0
CP-OFDM QPSK	1	1	19.36	19.43	0-1.5	0.0

Table H-443

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.09	19.03	19.18	0	0.0
	1	81	19.32	19.19	19.26		0.0
	1	160	19.14	19.33	19.53		0.0
	81	0	19.25	19.17	19.28	0-1	0.0
	81	41	19.27	19.25	19.24	0	0.0
	81	81	19.28	19.32	19.28	0-1	0.0
	162	0	19.39	19.21	19.30		0.0
DFT-s-OFDM 16QAM	1	1	19.11	19.05	19.31	0-1	0.0
CP-OFDM OPSK	1	1	19.17	19.05	19.38	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 226 of 426

Table H-444

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	19.36	19.26	19.45	0	0.0
	1	67	19.46	19.39	19.54		0.0
	1	131	19.44	19.49	19.73		0.0
	64	0	19.41	19.36	19.47	0-1	0.0
	64	35	19.49	19.49	19.58	0	0.0
	64	69	19.54	19.49	19.56	0-1	0.0
	128	0	19.48	19.44	19.53		0.0
DFT-s-OFDM 16QAM	1	1	19.46	19.23	19.76	0-1	0.0
CP-OFDM QPSK	1	1	19.40	19.33	19.80	0-1.5	0.0

Table H-445

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.16	19.27	19.41	19.48	0	0.0
	1	60	19.44	19.30	19.47	19.41		0.0
	1	117	19.45	19.48	19.92	19.59		0.0
	54	0	19.40	19.29	19.55	19.49	0-1	0.0
	54	33	19.49	19.34	19.56	19.54	0	0.0
	54	65	19.50	19.34	19.70	19.53	0-1	0.0
	108	0	19.39	19.32	19.58	19.48		0.0
DFT-s-OFDM 16QAM	1	1	19.45	19.22	19.67	19.30	0-1	0.0
CP-OFDM QPSK	1	1	19.06	19.38	19.52	19.52	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 227 of 426

Table H-446

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.17	18.99	19.12	19.20	0	0.0
	1	53	19.32	19.17	19.28	19.39		0.0
	1	104	19.22	19.29	19.42	19.38		0.0
	50	0	19.23	19.12	19.32	19.32	0-1	0.0
	50	28	19.35	19.14	19.35	19.35	0	0.0
	50	56	19.46	19.27	19.43	19.42	0-1	0.0
	100	0	19.45	19.36	19.48	19.44		0.0
DFT-s-OFDM 16QAM	1	1	19.01	19.14	19.27	19.24	0-1	0.0
CP-OFDM QPSK	1	1	19.18	19.22	19.38	19.20	0-1.5	0.0

Table H-447

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.18	19.24	19.16	19.33	19.40	0	0.0
	1	46	19.25	19.22	19.27	19.40	19.39		0.0
	1	90	19.37	19.42	19.41	19.50	19.44		0.0
	45	0	19.21	19.20	19.29	19.45	19.32	0-1	0.0
	45	24	19.30	19.28	19.30	19.33	19.46	0	0.0
	45	47	19.38	19.34	19.34	19.46	19.47	0-1	0.0
	90	0	19.35	19.32	19.32	19.40	19.41		0.0
DFT-s-OFDM 16QAM	1	1	19.32	19.34	19.10	19.56	19.35	0-1	0.0
CP-OFDM QPSK	1	1	19.35	19.52	19.22	19.41	19.51	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 228 of 426

Table H-448

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.28	19.31	19.25	19.43	19.38	0	0.0
	1	39	19.38	19.27	19.32	19.37	19.42		0.0
	1	76	19.52	19.32	19.43	19.49	19.50		0.0
	36	0	19.22	19.29	19.35	19.37	19.46	0-1	0.0
	36	21	19.29	19.21	19.36	19.39	19.43	0	0.0
	36	42	19.39	19.29	19.37	19.47	19.51	0-1	0.0
	75	0	19.34	19.39	19.26	19.45	19.41		0.0
DFT-s-OFDM 16QAM	1	1	19.39	19.31	19.18	19.39	19.39	0-1	0.0
CP-OFDM QPSK	1	1	19.60	19.61	19.33	19.60	19.51	0-1.5	0.0

Table H-449

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.31	19.38	19.36	19.44	19.52	0	0.0
	1	33	19.32	19.22	19.39	19.43	19.45		0.0
	1	63	19.37	19.31	19.41	19.43	19.64		0.0
	32	0	19.18	19.29	19.31	19.35	19.33	0-1	0.0
	32	17	19.25	19.33	19.32	19.43	19.43	0	0.0
	32	33	19.42	19.25	19.35	19.51	19.47	0-1	0.0
	64	0	19.30	19.31	19.34	19.43	19.40		0.0
DFT-s-OFDM 16QAM	1	1	19.28	19.41	19.40	19.48	19.52	0-1	0.0
CP-OFDM QPSK	1	1	19.48	19.46	19.54	19.51	19.76	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 229 of 426

Table H-450

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.27	19.13	19.07	19.40	19.37	0	0.0
	1	26	19.18	19.34	19.33	19.40	19.47		0.0
	1	49	19.20	19.26	19.43	19.47	19.25		0.0
	25	0	19.28	19.25	19.27	19.29	19.39	0-1	0.0
	25	13	19.26	19.28	19.29	19.41	19.40	0	0.0
	25	26	19.52	19.21	19.30	19.36	19.37	0-1	0.0
	50	0	19.30	19.36	19.29	19.36	19.34		0.0
DFT-s-OFDM 16QAM	1	1	19.10	19.21	19.12	19.52	19.36	0-1	0.0
CP-OFDM QPSK	1	1	18.87	19.42	19.28	19.31	19.39	0-1.5	0.0

Table H-451

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.26	19.15	19.26	19.36	19.39	0	0.0
	1	19	19.13	19.27	19.19	19.39	19.41		0.0
	1	36	19.34	19.42	19.41	19.55	19.50		0.0
	18	0	19.18	19.22	19.30	19.28	19.35	0-1	0.0
	18	10	19.32	19.27	19.23	19.34	19.35	0	0.0
	18	20	19.21	19.31	19.32	19.30	19.43	0-1	0.0
	36	0	19.28	19.28	19.32	19.39	19.39		0.0
DFT-s-OFDM 16QAM	1	1	19.12	19.25	19.39	19.29	19.67	0-1	0.0
CP-OFDM QPSK	1	1	19.24	19.35	19.44	19.38	19.49	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 230 of 426

Table H-452

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 0 (Folder Open-Body) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	19.24	19.24	19.24	19.27	19.56	0	0.0
	1	12	19.32	19.28	19.34	19.43	19.41		0.0
	1	22	19.37	19.18	19.39	19.43	19.62		0.0
	12	0	19.33	19.25	19.36	19.29	19.45	0-1	0.0
	12	6	19.34	19.20	19.29	19.35	19.42	0	0.0
	12	12	19.25	19.30	19.28	19.42	19.44	0-1	0.0
	24	0	19.22	19.22	19.27	19.31	19.45		0.0
DFT-s-OFDM 16QAM	1	1	19.36	19.40	19.42	19.39	19.51	0-1	0.0
CP-OFDM QPSK	1	1	19.73	19.60	19.32	19.39	19.71	0-1.5	0.0

Table H-453

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.42	16.54	0	0.0
	1	123	16.48	16.45		0.0
	1	243	16.73	16.69		0.0
	120	0	16.34	16.39	0-1	0.0
	120	63	16.46	16.45	0	0.0
	120	125	16.38	16.44	0-1	0.0
	243	0	16.38	16.51		0.0
DFT-s-OFDM 16QAM	1	1	16.43	16.52	0-1	0.0
CP-OFDM QPSK	1	1	16.34	16.53	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 231 of 426

Table H-454

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.29	16.44	0	0.0
	1	109	16.45	16.35		0.0
	1	215	16.54	16.67		0.0
	108	0	16.39	16.47	0-1	0.0
	108	55	16.44	16.50	0	0.0
	108	109	16.36	16.45	0-1	0.0
	216	0	16.43	16.55		0.0
DFT-s-OFDM 16QAM	1	1	16.22	16.45	0-1	0.0
CP-OFDM QPSK	1	1	16.35	16.56	0-1.5	0.0

Table H-455

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.27	16.43	0	0.0
	1	95	16.60	16.38		0.0
	1	187	16.44	16.49		0.0
	90	0	16.40	16.46	0-1	0.0
	90	50	16.46	16.49	0	0.0
	90	99	16.45	16.49	0-1	0.0
	180	0	16.39	16.46		0.0
DFT-s-OFDM 16QAM	1	1	16.31	16.51	0-1	0.0
CP-OFDM OPSK	1	1	16.33	16.60	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 232 of 426

Table H-456

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.26	16.17	16.27	0	0.0
	1	81	16.36	16.24	16.31		0.0
	1	160	16.29	16.49	16.46		0.0
	81	0	16.23	16.26	16.32	0-1	0.0
	81	41	16.35	16.37	16.38	0	0.0
	81	81	16.34	16.39	16.36	0-1	0.0
	162	0	16.35	16.41	16.42		0.0
DFT-s-OFDM 16QAM	1	1	16.20	16.18	16.20	0-1	0.0
CP-OFDM QPSK	1	1	16.41	16.21	16.42	0-1.5	0.0

Table H-457

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.50	16.43	16.76	0	0.0
	1	67	16.60	16.55	16.65		0.0
	1	131	16.63	16.70	16.78		0.0
	64	0	16.51	16.49	16.49	0-1	0.0
	64	35	16.63	16.68	16.64	0	0.0
	64	69	16.64	16.61	16.61	0-1	0.0
	128	0	16.57	16.56	16.61		0.0
DFT-s-OFDM 16QAM	1	1	16.49	16.43	16.46	0-1	0.0
CP-OFDM QPSK	1	1	16.60	16.69	16.77	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 233 of 426

Table H-458

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.57	16.40	16.76	16.68	0	0.0
	1	60	16.64	16.54	16.51	16.66		0.0
	1	117	16.63	16.70	16.76	16.75		0.0
	120	0	16.54	16.48	16.54	16.54	0-1	0.0
	120	33	16.62	16.54	16.54	16.52	0	0.0
	120	122	16.61	16.55	16.59	16.67	0-1	0.0
	240	0	16.59	16.45	16.60	16.62		0.0
DFT-s-OFDM 16QAM	1	1	16.51	16.38	16.55	16.50	0-1	0.0
CP-OFDM QPSK	1	1	16.57	16.41	16.54	16.89	0-1.5	0.0

Table H-459

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.31	16.40	16.35	16.36	0	0.0
	1	53	16.59	16.33	16.47	16.52		0.0
	1	104	16.61	16.50	16.58	16.60		0.0
	50	0	16.39	16.34	16.42	16.41	0-1	0.0
	50	28	16.59	16.46	16.52	16.59	0	0.0
	50	56	16.51	16.47	16.50	16.52	0-1	0.0
	100	0	16.47	16.49	16.54	16.56		0.0
DFT-s-OFDM 16QAM	1	1	16.25	16.25	16.16	16.30	0-1	0.0
CP-OFDM QPSK	1	1	16.39	16.32	16.34	16.44	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 234 of 426

Table H-460

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.34	16.40	16.31	16.45	16.41	0	0.0
	1	46	16.50	16.42	16.64	16.49	16.67		0.0
	1	90	16.58	16.43	16.46	16.46	16.48		0.0
	45	0	16.35	16.35	16.39	16.43	16.42	0-1	0.0
	45	24	16.58	16.46	16.52	16.58	16.52	0	0.0
	45	47	16.50	16.42	16.49	16.50	16.50	0-1	0.0
	90	0	16.42	16.36	16.42	16.45	16.43		0.0
DFT-s-OFDM 16QAM	1	1	16.36	16.36	16.43	16.41	16.43	0-1	0.0
CP-OFDM QPSK	1	1	16.62	16.39	16.41	16.73	16.49	0-1.5	0.0

Table H-461

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.51	16.38	16.53	16.59	16.55	0	0.0
	1	39	16.48	16.37	16.45	16.49	16.60		0.0
	1	76	16.71	16.61	16.64	16.59	16.70		0.0
	36	0	16.35	16.40	16.40	16.44	16.46	0-1	0.0
	36	21	16.49	16.36	16.55	16.58	16.47	0	0.0
	36	42	16.53	16.45	16.54	16.52	16.49	0-1	0.0
	75	0	16.45	16.36	16.44	16.48	16.45		0.0
DFT-s-OFDM 16QAM	1	1	16.51	16.44	16.58	16.57	16.54	0-1	0.0
CP-OFDM QPSK	1	1	16.52	16.57	16.67	16.44	16.68	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 235 of 426

Table H-462

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.52	16.49	16.51	16.68	16.63	0	0.0
	1	33	16.58	16.46	16.53	16.66	16.63		0.0
	1	63	16.74	16.57	16.74	16.63	16.67		0.0
	32	0	16.35	16.41	16.42	16.40	16.41	0-1	0.0
	32	17	16.55	16.42	16.52	16.53	16.54	0	0.0
	32	33	16.55	16.42	16.48	16.50	16.55	0-1	0.0
	64	0	16.46	16.35	16.44	16.53	16.45		0.0
DFT-s-OFDM 16QAM	1	1	16.59	16.67	16.47	16.69	16.49	0-1	0.0
CP-OFDM QPSK	1	1	16.45	16.67	16.53	16.73	16.88	0-1.5	0.0

Table H-463

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.49	16.29	16.43	16.67	16.57	0	0.0
	1	26	16.45	16.23	16.60	16.44	16.57		0.0
	1	49	16.35	16.39	16.43	16.51	16.60		0.0
	25	0	16.30	16.31	16.46	16.41	16.58	0-1	0.0
	25	13	16.52	16.24	16.42	16.45	16.55	0	0.0
	25	26	16.37	16.30	16.36	16.44	16.55	0-1	0.0
	50	0	16.39	16.30	16.52	16.47	16.48		0.0
DFT-s-OFDM 16QAM	1	1	16.43	16.49	16.48	16.45	16.45	0-1	0.0
CP-OFDM QPSK	1	1	16.36	16.32	16.54	16.68	16.62	0-1.5	0.0

Table H-464

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.46	16.43	16.56	16.45	16.68	0	0.0
	1	19	16.40	16.36	16.38	16.60	16.55		0.0
	1	36	16.60	16.38	16.68	16.58	16.72		0.0
	18	0	16.32	16.46	16.35	16.40	16.52	0-1	0.0
	18	10	16.33	16.56	16.56	16.57	16.67	0	0.0
	18	20	16.41	16.29	16.44	16.44	16.50	0-1	0.0
	36	0	16.34	16.39	16.37	16.38	16.43		0.0
DFT-s-OFDM 16QAM	1	1	16.52	16.41	16.36	16.35	16.54	0-1	0.0
CP-OFDM QPSK	1	1	16.48	16.47	16.51	16.45	16.52	0-1.5	0.0

Table H-465

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.48	16.50	16.48	16.54	16.73	0	0.0
	1	12	16.46	16.44	16.51	16.72	16.67		0.0
	1	22	16.62	16.48	16.69	16.67	16.72		0.0
	12	0	16.26	16.42	16.36	16.34	16.51	0-1	0.0
	12	6	16.44	16.39	16.41	16.57	16.60	0	0.0
	12	12	16.43	16.42	16.36	16.41	16.59	0-1	0.0
	24	0	16.47	16.41	16.39	16.39	16.59		0.0
DFT-s-OFDM 16QAM	1	1	16.38	16.53	16.52	16.50	16.73	0-1	0.0
CP-OFDM QPSK	1	1	16.60	16.59	16.59	16.53	16.69	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 237 of 426

Table H-466

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.31	16.67	0	0.0
	1	123	16.46	16.61		0.0
	1	243	16.65	16.76		0.0
	120	0	16.30	16.51	0-1	0.0
	120	63	16.43	16.57	0	0.0
	120	125	16.44	16.55	0-1	0.0
	243	0	16.42	16.64		0.0
DFT-s-OFDM 16QAM	1	1	16.21	16.45	0-1	0.0
CP-OFDM QPSK	1	1	16.50	16.32	0-1.5	0.0

Table H-467

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.52	16.70	0	0.0
	1	109	16.55	16.51		0.0
	1	215	16.73	16.87		0.0
	108	0	16.47	16.49	0-1	0.0
	108	55	16.58	16.67	0	0.0
	108	109	16.58	16.62	0-1	0.0
	216	0	16.75	16.68		0.0
DFT-s-OFDM 16QAM	1	1	16.65	16.50	0-1	0.0
CP-OFDM QPSK	1	1	16.80	16.72	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 238 of 426

Table H-468

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.31	16.59	0	0.0
	1	95	16.54	16.45		0.0
	1	187	16.59	16.75		0.0
	90	0	16.55	16.56	0-1	0.0
	90	50	16.70	16.62	0	0.0
	90	99	16.58	16.71	0-1	0.0
	180	0	16.52	16.63		0.0
DFT-s-OFDM 16QAM	1	1	16.43	16.63	0-1	0.0
CP-OFDM QPSK	1	1	16.33	16.43	0-1.5	0.0

Table H-469

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.44	16.38	16.49	0	0.0
	1	81	16.58	16.43	16.51		0.0
	1	160	16.52	16.75	16.65		0.0
	81	0	16.41	16.33	16.44	0-1	0.0
	81	41	16.56	16.53	16.57	0	0.0
	81	81	16.55	16.54	16.51	0-1	0.0
	162	0	16.43	16.60	16.62		0.0
DFT-s-OFDM 16QAM	1	1	16.43	16.41	16.48	0-1	0.0
CP-OFDM QPSK	1	1	16.25	16.24	16.48	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 239 of 426

Table H-470

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	16.31	16.38	16.46	0	0.0
	1	67	16.45	16.40	16.51		0.0
	1	131	16.57	16.72	16.72		0.0
	64	0	16.42	16.32	16.42	0-1	0.0
	64	35	16.60	16.59	16.48	0	0.0
	64	69	16.47	16.50	16.56	0-1	0.0
	128	0	16.37	16.41	16.45		0.0
DFT-s-OFDM 16QAM	1	1	16.35	16.28	16.58	0-1	0.0
CP-OFDM QPSK	1	1	16.42	16.50	16.40	0-1.5	0.0

Table H-471

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.69	16.49	16.69	16.63	0	0.0
	1	60	16.63	16.57	16.75	16.53		0.0
	1	117	16.82	16.81	16.66	16.94		0.0
	120	0	16.58	16.47	16.66	16.65	0-1	0.0
	120	33	16.70	16.58	16.71	16.65	0	0.0
	120	122	16.67	16.64	16.77	16.72	0-1	0.0
	240	0	16.59	16.51	16.72	16.73		0.0
DFT-s-OFDM 16QAM	1	1	16.57	16.37	16.70	16.71	0-1	0.0
CP-OFDM QPSK	1	1	16.39	16.63	16.76	16.71	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 240 of 426

Table H-472

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	16.56	16.49	16.68	16.64	0	0.0
	1	53	16.53	16.52	16.72	16.61		0.0
	1	104	16.68	16.83	16.82	16.83		0.0
	50	0	16.55	16.48	16.64	16.61	0-1	0.0
	50	28	16.69	16.59	16.75	16.75	0	0.0
	50	56	16.70	16.66	16.75	16.73	0-1	0.0
	100	0	16.60	16.61	16.67	16.72		0.0
DFT-s-OFDM 16QAM	1	1	16.40	16.28	16.49	16.43	0-1	0.0
CP-OFDM QPSK	1	1	16.46	16.55	16.48	16.71	0-1.5	0.0

Table H-473

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.38	16.42	16.40	16.65	16.51	0	0.0
	1	46	16.52	16.57	16.44	16.53	16.49		0.0
	1	90	16.70	16.49	16.58	16.55	16.64		0.0
	45	0	16.40	16.46	16.49	16.58	16.53	0-1	0.0
	45	24	16.57	16.49	16.51	16.59	16.54	0	0.0
	45	47	16.55	16.52	16.57	16.59	16.64	0-1	0.0
	90	0	16.53	16.45	16.52	16.62	16.51		0.0
DFT-s-OFDM 16QAM	1	1	16.42	16.49	16.13	16.52	16.56	0-1	0.0
CP-OFDM QPSK	1	1	16.57	16.68	16.45	16.58	16.60	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 241 of 426

Table H-474

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.38	16.49	16.41	16.52	16.52	0	0.0
	1	39	16.47	16.35	16.57	16.51	16.50		0.0
	1	76	16.62	16.54	16.49	16.35	16.59		0.0
	36	0	16.21	16.37	16.26	16.41	16.33	0-1	0.0
	36	21	16.41	16.37	16.39	16.52	16.47	0	0.0
	36	42	16.37	16.27	16.44	16.39	16.50	0-1	0.0
	75	0	16.34	16.26	16.25	16.43	16.40		0.0
DFT-s-OFDM 16QAM	1	1	16.18	16.35	16.37	16.41	16.53	0-1	0.0
CP-OFDM QPSK	1	1	16.40	16.30	16.30	16.52	16.37	0-1.5	0.0

Table H-475

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.48	16.60	16.46	16.68	16.59	0	0.0
	1	33	16.47	16.47	16.51	16.63	16.64		0.0
	1	63	16.60	16.48	16.59	16.60	16.72		0.0
	32	0	16.26	16.29	16.37	16.40	16.34	0-1	0.0
	32	17	16.39	16.36	16.50	16.50	16.49	0	0.0
	32	33	16.37	16.33	16.42	16.47	16.48	0-1	0.0
	64	0	16.39	16.31	16.40	16.47	16.44		0.0
DFT-s-OFDM 16QAM	1	1	16.45	16.32	16.23	16.43	16.35	0-1	0.0
CP-OFDM QPSK	1	1	16.21	16.26	16.19	16.53	16.43	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 242 of 426

Table H-476

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.20	16.37	16.21	16.30	16.41	0	0.0
	1	26	16.45	16.35	16.36	16.51	16.56		0.0
	1	49	16.48	16.37	16.42	16.33	16.47		0.0
	25	0	16.12	16.35	16.31	16.40	16.39	0-1	0.0
	25	13	16.40	16.30	16.41	16.48	16.51	0	0.0
	25	26	16.37	16.22	16.33	16.36	16.34	0-1	0.0
	50	0	16.31	16.24	16.38	16.42	16.34		0.0
DFT-s-OFDM 16QAM	1	1	16.26	16.35	16.23	16.36	16.41	0-1	0.0
CP-OFDM QPSK	1	1	16.32	16.20	16.27	16.29	16.27	0-1.5	0.0

Table H-477

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.38	16.31	16.60	16.51	16.49	0	0.0
	1	19	16.38	16.29	16.45	16.47	16.62		0.0
	1	36	16.46	16.45	16.51	16.53	16.60		0.0
	18	0	16.18	16.32	16.33	16.37	16.41	0-1	0.0
	18	10	16.38	16.42	16.41	16.50	16.53	0	0.0
	18	20	16.18	16.34	16.41	16.35	16.39	0-1	0.0
	36	0	16.25	16.27	16.30	16.37	16.36		0.0
DFT-s-OFDM 16QAM	1	1	16.25	16.26	16.32	16.31	16.51	0-1	0.0
CP-OFDM QPSK	1	1	16.33	16.23	16.49	16.34	16.33	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 243 of 426

Table H-478

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	16.40	16.49	16.43	16.53	16.38	0	0.0
	1	12	16.42	16.56	16.51	16.44	16.42		0.0
	1	22	16.50	16.53	16.48	16.61	16.61		0.0
	12	0	16.27	16.35	16.34	16.37	16.38	0-1	0.0
	12	6	16.33	16.43	16.36	16.50	16.45	0	0.0
	12	12	16.36	16.28	16.39	16.39	16.51	0-1	0.0
	24	0	16.29	16.39	16.32	16.41	16.43		0.0
DFT-s-OFDM 16QAM	1	1	16.20	16.43	16.39	16.44	16.35	0-1	0.0
CP-OFDM QPSK	1	1	16.32	16.65	16.30	16.48	16.61	0-1.5	0.0

Table H-479

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	9.32	9.35	0	0.0
	1	123	9.41	9.34		0.0
	1	243	9.65	9.62		0.0
	120	0	9.31	9.30	0-1	0.0
	120	63	9.42	9.39	0	0.0
	120	125	9.40	9.42	0-1	0.0
	243	0	9.46	9.34		0.0
DFT-s-OFDM 16QAM	1	1	9.26	9.35	0-1	0.0
CP-OFDM QPSK	1	1	8.97	9.49	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 244 of 426

Table H-480

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	9.24	9.41	0	0.0
	1	109	9.35	9.33		0.0
	1	215	9.66	9.58		0.0
	108	0	9.31	9.35	0-1	0.0
	108	55	9.43	9.38	0	0.0
	108	109	9.43	9.40	0-1	0.0
	216	0	9.46	9.38		0.0
DFT-s-OFDM 16QAM	1	1	9.18	9.27	0-1	0.0
CP-OFDM QPSK	1	1	8.93	9.13	0-1.5	0.0

Table H-481

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	9.17	9.33	0	0.0
	1	95	9.41	9.36		0.0
	1	187	9.47	9.56		0.0
	90	0	9.27	9.33	0-1	0.0
	90	50	9.46	9.46	0	0.0
	90	99	9.45	9.45	0-1	0.0
	180	0	9.37	9.41		0.0
DFT-s-OFDM 16QAM	1	1	9.14	9.39	0-1	0.0
CP-OFDM OPSK	1	1	9.13	9.26	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 245 of 426

Table H-482

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	9.13	9.23	9.22	0	0.0
	1	81	9.25	9.18	9.20		0.0
	1	160	9.48	9.56	9.42		0.0
	81	0	9.23	9.14	9.22	0-1	0.0
	81	41	9.42	9.27	9.31	0	0.0
	81	81	9.32	9.35	9.27	0-1	0.0
	162	0	9.32	9.28	9.29		0.0
DFT-s-OFDM 16QAM	1	1	9.19	9.03	9.18	0-1	0.0
CP-OFDM QPSK	1	1	9.00	9.16	9.04	0-1.5	0.0

Table H-483

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	9.33	9.42	9.57	0	0.0
	1	67	9.39	9.62	9.45		0.0
	1	131	9.68	9.60	9.70		0.0
	64	0	9.31	9.47	9.43	0-1	0.0
	64	35	9.52	9.48	9.52	0	0.0
	64	69	9.56	9.56	9.51	0-1	0.0
	128	0	9.44	9.51	9.42		0.0
DFT-s-OFDM 16QAM	1	1	9.24	9.43	9.54	0-1	0.0
CP-OFDM QPSK	1	1	9.39	9.29	9.41	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 246 of 426

Table H-484

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	9.43	9.52	9.60	9.65	0	0.0
	1	60	9.44	9.41	9.59	9.45		0.0
	1	117	9.46	9.71	9.74	9.71		0.0
	54	0	9.33	9.34	9.50	9.45	0-1	0.0
	54	33	9.42	9.35	9.59	9.45	0	0.0
	54	65	9.61	9.54	9.56	9.60	0-1	0.0
	108	0	9.44	9.44	9.57	9.46		0.0
DFT-s-OFDM 16QAM	1	1	9.19	9.45	9.38	9.47	0-1	0.0
CP-OFDM QPSK	1	1	9.21	9.45	9.41	9.32	0-1.5	0.0

Table H-485

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	9.17	9.20	9.43	9.36	0	0.0
	1	53	9.37	9.19	9.39	9.33		0.0
	1	104	9.42	9.56	9.49	9.37		0.0
	50	0	9.26	9.22	9.36	9.30	0-1	0.0
	50	28	9.39	9.45	9.56	9.44	0	0.0
	50	56	9.45	9.38	9.46	9.45	0-1	0.0
	100	0	9.47	9.33	9.45	9.32		0.0
DFT-s-OFDM 16QAM	1	1	8.98	9.08	9.26	9.21	0-1	0.0
CP-OFDM QPSK	1	1	9.14	9.14	9.27	9.18	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 247 of 426

Table H-486

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	9.27	9.24	9.25	9.41	9.40	0	0.0
	1	46	9.46	9.47	9.49	9.54	9.50		0.0
	1	90	9.42	9.50	9.47	9.33	9.41		0.0
	45	0	9.23	9.35	9.35	9.47	9.30	0-1	0.0
	45	24	9.43	9.51	9.50	9.44	9.42	0	0.0
	45	47	9.36	9.51	9.42	9.45	9.45	0-1	0.0
	90	0	9.33	9.45	9.37	9.42	9.37		0.0
DFT-s-OFDM 16QAM	1	1	9.21	9.44	9.33	9.52	9.28	0-1	0.0
CP-OFDM QPSK	1	1	9.11	9.42	9.27	9.42	9.33	0-1.5	0.0

Table H-487

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	9.40	9.45	9.59	9.57	9.45	0	0.0
	1	39	9.41	9.58	9.54	9.47	9.42		0.0
	1	76	9.58	9.61	9.58	9.40	9.56		0.0
	36	0	9.26	9.41	9.34	9.40	9.31	0-1	0.0
	36	21	9.34	9.53	9.49	9.43	9.43	0	0.0
	36	42	9.39	9.47	9.45	9.39	9.48	0-1	0.0
	75	0	9.30	9.48	9.35	9.35	9.41		0.0
DFT-s-OFDM 16QAM	1	1	9.28	9.43	9.33	9.57	9.33	0-1	0.0
CP-OFDM QPSK	1	1	9.26	9.53	9.41	9.34	9.36	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 248 of 426

Table H-488

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	9.33	9.50	9.45	9.67	9.55	0	0.0
	1	33	9.34	9.50	9.60	9.47	9.58		0.0
	1	63	9.48	9.68	9.57	9.65	9.53		0.0
	32	0	9.30	9.42	9.40	9.46	9.35	0-1	0.0
	32	17	9.33	9.26	9.56	9.47	9.50	0	0.0
	32	33	9.41	9.31	9.44	9.42	9.50	0-1	0.0
	64	0	9.27	9.39	9.45	9.40	9.46		0.0
DFT-s-OFDM 16QAM	1	1	9.21	9.64	9.52	9.52	9.39	0-1	0.0
CP-OFDM QPSK	1	1	9.13	9.52	9.43	9.39	9.33	0-1.5	0.0

Table H-489

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	9.24	9.40	9.29	9.37	9.37	0	0.0
	1	26	9.34	9.40	9.43	9.54	9.50		0.0
	1	49	9.52	9.47	9.43	9.50	9.45		0.0
	25	0	9.26	9.36	9.30	9.41	9.33	0-1	0.0
	25	13	9.36	9.50	9.49	9.35	9.41	0	0.0
	25	26	9.20	9.42	9.42	9.34	9.39	0-1	0.0
	50	0	9.33	9.54	9.31	9.42	9.35		0.0
DFT-s-OFDM 16QAM	1	1	9.13	9.28	9.27	9.43	9.31	0-1	0.0
CP-OFDM QPSK	1	1	9.23	9.28	9.28	9.30	9.03	0-1.5	0.0

Table H-490

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	9.35	9.41	9.35	9.62	9.47	0	0.0
	1	19	9.49	9.67	9.52	9.53	9.42		0.0
	1	36	9.36	9.52	9.51	9.57	9.48		0.0
	18	0	9.28	9.38	9.34	9.40	9.36	0-1	0.0
	18	10	9.46	9.59	9.40	9.55	9.43	0	0.0
	18	20	9.28	9.46	9.35	9.39	9.39	0-1	0.0
	36	0	9.26	9.39	9.33	9.31	9.43		0.0
DFT-s-OFDM 16QAM	1	1	9.24	9.36	9.44	9.37	9.42	0-1	0.0
CP-OFDM QPSK	1	1	9.11	9.28	9.40	9.39	9.31	0-1.5	0.0

Table H-491

NR Band n41 PC2/PC1.5 Antenna G Measured P_{limit} for DSI = 4 (Folder Open – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	9.54	9.59	9.53	9.84	9.50	0	0.0
	1	12	9.43	9.50	9.65	9.52	9.48		0.0
	1	22	9.39	9.63	9.55	9.73	9.66		0.0
	12	0	9.24	9.38	9.35	9.42	9.35	0-1	0.0
	12	6	9.36	9.49	9.52	9.32	9.53	0	0.0
	12	12	9.49	9.48	9.42	9.37	9.50	0-1	0.0
	24	0	9.41	9.45	9.40	9.29	9.52		0.0
DFT-s-OFDM 16QAM	1	1	9.37	9.46	9.42	9.38	9.42	0-1	0.0
CP-OFDM QPSK	1	1	9.12	9.40	9.26	9.55	9.34	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 250 of 426

Table H-492

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.20	19.06

Table H-493

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	18.91	18.97

Table H-494

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	19.30	18.96

Table H-495

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	19.65	19.58	18.94

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 251 of 426

Table H-496

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	19.70	19.52	18.97

Table H-497

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	19.66	18.53	19.41	19.09

Table H-498

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	19.50	18.84	19.31	18.92

Table H-499

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.69	18.83	19.43	19.16	19.29

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 252 of 426

Table H-500

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.61	19.02	19.37	19.69	19.48

Table H-501

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.42	18.93	19.88	19.28	18.80

Table H-502

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.33	18.94	19.34	19.19	19.38

Table H-503

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.44	19.01	19.82	19.69	19.42

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 253 of 426

Table H-504

NR Band n41 PC2/PC1.5 Antenna B Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	19.32	19.02	19.86	19.63	19.37

Table H-505

**NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 90 MHz Bandwidth**

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	17.71	17.43
SRS #3 Ant H	14.42	13.35
SRS #4 Ant D	14.28	14.31

Table H-506

**NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 80 MHz Bandwidth**

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	17.74	17.35
SRS #3 Ant H	14.36	13.36
SRS #4 Ant D	14.43	14.32

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 254 of 426

Table H-507

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	17.66	17.30
SRS #3 Ant H	14.41	13.21
SRS #4 Ant D	14.38	14.25

Table H-508

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	17.78	17.66	17.35
SRS #3 Ant H	14.27	14.25	13.21
SRS #4 Ant D	14.31	14.28	14.30

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 255 of 426

Table H-509

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	17.90	17.98	17.57
SRS #3 Ant H	14.27	14.69	13.42
SRS #4 Ant D	14.75	14.44	14.42

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	17.92	17.88	17.80	17.58
SRS #3 Ant H	14.27	14.71	14.13	13.35
SRS #4 Ant D	14.42	14.45	14.44	14.49

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 256 of 426

Table H-510

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	17.81	17.74	17.68	17.49
SRS #3 Ant H	14.08	14.69	14.01	13.24
SRS #4 Ant D	14.56	14.26	14.44	14.36

Table H-511

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.61	17.60	17.65	17.47	17.41
SRS #3 Ant H	14.05	14.54	14.45	13.64	13.20
SRS #4 Ant D	14.22	14.26	14.38	14.26	14.42

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 257 of 426

Table H-512

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.69	17.66	17.78	17.44	17.49
SRS #3 Ant H	14.08	14.54	14.57	13.71	13.31
SRS #4 Ant D	14.53	14.34	14.34	14.35	14.23

Table H-513

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.68	17.64	17.75	17.52	17.50
SRS #3 Ant H	13.95	14.37	14.55	13.69	13.29
SRS #4 Ant D	14.54	14.32	14.34	14.38	14.35

Table H-514

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.65	17.57	17.81	17.47	17.45
SRS #3 Ant H	13.87	14.36	14.46	13.62	13.21
SRS #4 Ant D	14.48	14.26	14.27	14.28	14.25

Table H-515

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.63	17.66	17.81	17.42	17.47
SRS #3 Ant H	13.92	14.35	14.48	13.58	13.20
SRS #4 Ant D	14.45	14.35	14.33	14.29	14.23

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 259 of 426

Table H-516

NR Band n41 PC2/PC1.5 Antenna B Path 1 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip), and
NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 3 (Folder Closed-Head), DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) - 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	17.65	17.69	17.82	17.45	17.51
SRS #3 Ant H	13.74	14.32	14.50	13.59	13.22
SRS #4 Ant D	14.48	14.46	14.32	14.38	14.22

Table H-517

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	11.27	10.96
SRS #3 Ant H	7.55	6.41
SRS #4 Ant D	7.49	7.40

Table H-518

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	11.29	11.02
SRS #3 Ant H	7.46	6.34
SRS #4 Ant D	7.49	7.44

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 260 of 426

Table H-519

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant B	11.24	10.92
SRS #3 Ant H	7.43	6.26
SRS #4 Ant D	7.35	7.35

Table H-520

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	11.30	11.28	10.98
SRS #3 Ant H	7.29	7.25	6.17
SRS #4 Ant D	7.45	7.42	7.32

Table H-521

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant B	11.44	11.49	11.14
SRS #3 Ant H	7.34	7.51	6.39
SRS #4 Ant D	7.61	7.74	7.63

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 261 of 426

Table H-522

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	11.40	11.28	11.30	11.03
SRS #3 Ant H	7.15	7.58	6.93	6.28
SRS #4 Ant D	7.55	7.54	7.62	7.61

Table H-523

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant B	11.32	11.18	11.25	11.02
SRS #3 Ant H	7.06	7.55	6.89	6.26
SRS #4 Ant D	7.50	7.52	7.44	7.45

Table H-524

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	11.07	11.20	11.10	10.89	10.85
SRS #3 Ant H	7.11	7.49	7.33	6.53	6.13
SRS #4 Ant D	7.22	7.35	7.38	7.29	7.35

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 262 of 426

Table H-525

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	11.22	11.35	11.39	11.07	11.06
SRS #3 Ant H	7.08	7.64	7.38	6.62	6.17
SRS #4 Ant D	7.45	7.57	7.55	7.41	7.48

Table H-526

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	11.16	11.26	11.24	10.96	10.87
SRS #3 Ant H	7.05	7.45	7.29	6.53	6.03
SRS #4 Ant D	7.33	7.35	7.57	7.25	7.27

Table H-527

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	11.16	11.27	11.28	10.99	10.98
SRS #3 Ant H	6.84	7.46	7.35	6.55	6.07
SRS #4 Ant D	7.43	7.44	7.46	7.29	7.33

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 263 of 426

Table H-528

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	11.01	11.18	11.18	10.90	10.83
SRS #3 Ant H	6.64	7.37	7.28	6.38	5.92
SRS #4 Ant D	7.30	7.37	7.41	7.20	7.29

Table H-529

NR Band n41 PC2/PC1.5 Antenna B, H, D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant B	10.92	11.20	11.18	10.87	10.82
SRS #3 Ant H	6.58	7.36	7.30	6.44	6.00
SRS #4 Ant D	7.34	7.29	7.29	7.25	7.23

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 264 of 426

H.2.1 NR Band n41 PC2/PC1.5 Antenna Path 2

Table H-530

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.84	23.99	0	0.0
	1	123	23.63	24.20		0.0
	1	243	23.57	24.40		0.0
	120	0	23.72	24.06	0-1	0.0
	120	63	23.63	24.14	0	0.0
	120	125	23.56	24.33	0-1	0.0
	243	0	23.59	24.18		0.0
DFT-s-OFDM 16QAM	1	1	23.70	24.00	0-1	0.0
CP-OFDM QPSK	1	1	23.97	24.02	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 265 of 426

Table H-531

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.82	24.05	0	0.0
	1	109	23.65	24.14		0.0
	1	215	23.62	24.35		0.0
	108	0	23.79	24.17	0-1	0.0
	108	55	23.70	24.29	0	0.0
	108	109	23.72	24.40	0-1	0.0
	216	0	23.77	24.24		0.0
DFT-s-OFDM 16QAM	1	1	23.69	24.05	0-1	0.0
CP-OFDM QPSK	1	1	23.92	24.07	0-1.5	0.0

Table H-532

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.86	24.19	0	0.0
	1	95	23.76	24.29		0.0
	1	187	23.71	24.38		0.0
	90	0	23.86	24.21	0-1	0.0
	90	50	23.78	24.28	0	0.0
	90	99	23.80	24.38	0-1	0.0
	180	0	23.80	24.32		0.0
DFT-s-OFDM 16QAM	1	1	23.80	24.17	0-1	0.0
CP-OFDM QPSK	1	1	23.87	24.30	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 266 of 426

Table H-533

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.80	23.78	23.94	0	0.0
	1	81	23.66	23.83	24.10		0.0
	1	160	23.62	24.10	24.28		0.0
	81	0	23.81	23.81	24.14	0-1	0.0
	81	41	23.65	23.79	24.08	0	0.0
	81	81	23.64	23.99	24.17	0-1	0.0
	162	0	23.66	23.88	24.11		0.0
DFT-s-OFDM 16QAM	1	1	23.67	23.60	23.95	0-1	0.0
CP-OFDM QPSK	1	1	23.85	23.65	24.00	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 267 of 426

Table H-534

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	23.95	23.83	24.29	0	0.0
	1	67	23.90	24.01	24.20		0.0
	1	131	23.76	24.16	24.38		0.0
	64	0	23.91	24.02	24.27	0-1	0.0
	64	35	23.89	24.16	24.31	0	0.0
	64	69	23.83	24.15	24.40	0-1	0.0
	128	0	23.93	24.14	24.29		0.0
DFT-s-OFDM 16QAM	1	1	23.87	23.82	24.16	0-1	0.0
CP-OFDM QPSK	1	1	23.90	24.10	24.43	0-1.5	0.0

Table H-535

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.87	23.89	24.18	24.36	0	0.0
	1	60	23.92	23.99	24.18	24.30		0.0
	1	117	23.96	24.20	24.48	24.53		0.0
	120	0	23.91	23.92	24.20	24.32	0-1	0.0
	120	33	23.90	23.94	24.18	24.32	0	0.0
	120	122	23.95	24.03	24.26	24.45	0-1	0.0
	240	0	24.00	24.06	24.31	24.33		0.0
DFT-s-OFDM 16QAM	1	1	23.84	23.84	23.90	24.32	0-1	0.0
CP-OFDM QPSK	1	1	23.98	24.00	24.26	24.32	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 268 of 426

Table H-536

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.77	23.66	23.89	23.99	0	0.0
	1	53	23.84	23.95	24.02	24.18		0.0
	1	104	23.73	23.91	24.12	24.12		0.0
	50	0	23.88	23.78	24.05	24.12	0-1	0.0
	50	28	23.87	23.79	24.15	24.10	0	0.0
	50	56	23.81	23.91	24.13	24.25	0-1	0.0
	100	0	23.78	23.79	24.02	24.14		0.0
DFT-s-OFDM 16QAM	1	1	23.64	23.78	23.64	23.98	0-1	0.0
CP-OFDM QPSK	1	1	23.80	23.59	23.85	24.06	0-1.5	0.0

Table H-537

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	23.76	23.62	23.75	24.03	24.10	0	0.0
	1	46	23.76	23.61	23.94	24.10	24.26		0.0
	1	90	23.74	23.70	23.99	24.16	24.22		0.0
	45	0	23.74	23.52	23.82	24.05	24.13	0-1	0.0
	45	24	23.73	23.51	23.89	24.15	24.22	0	0.0
	45	47	23.73	23.53	23.94	24.13	24.26	0-1	0.0
	90	0	23.72	23.67	23.92	24.09	24.28		0.0
DFT-s-OFDM 16QAM	1	1	23.75	23.44	23.71	23.80	24.03	0-1	0.0
CP-OFDM QPSK	1	1	23.80	23.58	23.86	24.10	24.12	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 269 of 426

Table H-538

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	23.89	23.74	23.97	24.16	24.14	0	0.0
	1	39	23.79	23.78	23.94	24.08	24.13		0.0
	1	76	23.88	23.93	24.01	24.20	24.38		0.0
	36	0	23.81	23.50	23.97	24.04	24.09	0-1	0.0
	36	21	23.76	23.52	23.92	24.06	24.17	0	0.0
	36	42	23.85	23.58	24.08	24.14	24.24	0-1	0.0
	75	0	23.79	23.61	23.96	24.05	24.14		0.0
DFT-s-OFDM 16QAM	1	1	23.87	24.11	23.84	24.00	24.25	0-1	0.0
CP-OFDM QPSK	1	1	23.82	24.01	23.83	24.15	24.14	0-1.5	0.0

Table H-539

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	23.81	23.70	23.98	24.18	24.14	0	0.0
	1	33	23.86	23.64	23.90	24.13	24.43		0.0
	1	63	23.72	23.77	24.06	24.24	24.40		0.0
	32	0	23.74	23.55	23.97	24.17	24.26	0-1	0.0
	32	17	23.75	23.53	23.99	24.12	24.25	0	0.0
	32	33	23.82	23.58	23.98	24.20	24.41	0-1	0.0
	64	0	23.77	23.58	23.99	24.19	24.32		0.0
DFT-s-OFDM 16QAM	1	1	23.73	23.57	23.94	24.06	24.16	0-1	0.0
CP-OFDM QPSK	1	1	23.87	23.76	24.02	24.22	24.29	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 270 of 426

Table H-540

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	23.74	23.58	23.77	23.93	24.05	0	0.0
	1	26	23.68	23.62	23.94	23.90	24.26		0.0
	1	49	23.76	23.73	24.03	24.00	24.07		0.0
	25	0	23.68	23.62	23.88	23.93	24.04	0-1	0.0
	25	13	23.71	23.53	23.83	23.87	24.09	0	0.0
	25	26	23.81	23.56	23.88	23.91	24.14	0-1	0.0
	50	0	23.78	23.56	23.88	23.93	24.18		0.0
DFT-s-OFDM 16QAM	1	1	23.67	23.48	23.62	23.93	23.88	0-1	0.0
CP-OFDM QPSK	1	1	23.93	23.74	23.71	23.96	23.93	0-1.5	0.0

Table H-541

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	23.45	23.67	23.93	23.97	24.24	0	0.0
	1	19	23.56	23.62	23.96	24.04	24.23		0.0
	1	36	23.80	23.70	23.93	24.31	24.27		0.0
	18	0	23.66	23.67	23.90	24.02	24.30	0-1	0.0
	18	10	23.73	23.68	24.03	24.12	24.40	0	0.0
	18	20	23.75	23.55	24.09	24.18	24.26	0-1	0.0
	36	0	23.74	23.60	23.84	23.93	24.18		0.0
DFT-s-OFDM 16QAM	1	1	23.86	23.68	23.85	24.03	24.17	0-1	0.0
CP-OFDM QPSK	1	1	23.82	23.52	23.77	24.01	24.26	0-1.5	0.0

Table H-542

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured $P_{\max}$ for DSI = 3 (Folder Closed-Head)– 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	23.90	23.48	23.90	24.10	24.25	0	0.0
	1	12	23.76	23.70	23.91	24.01	24.17		0.0
	1	22	23.67	23.70	23.99	24.07	24.40		0.0
	12	0	23.76	23.56	23.92	23.94	24.23	0-1	0.0
	12	6	23.75	23.50	23.83	23.90	24.25	0	0.0
	12	12	23.84	23.62	23.97	24.06	24.31	0-1	0.0
	24	0	23.74	23.60	23.88	23.92	24.28		0.0
DFT-s-OFDM 16QAM	1	1	23.80	23.62	23.79	23.98	24.19	0-1	0.0
CP-OFDM QPSK	1	1	23.83	23.76	23.91	23.99	24.34	0-1.5	0.0

Table H-543

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.21	17.17	0	0.0
	1	123	16.82	17.11		0.0
	1	243	16.94	17.44		0.0
	120	0	17.06	17.12	0-1	0.0
	120	63	16.90	17.07	0	0.0
	120	125	16.80	17.14	0-1	0.0
	243	0	16.85	17.14		0.0
DFT-s-OFDM 16QAM	1	1	17.12	17.16	0-1	0.0
CP-OFDM QPSK	1	1	17.17	17.30	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 272 of 426

Table H-544

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.22	17.11	0	0.0
	1	109	16.85	17.06		0.0
	1	215	16.80	17.34		0.0
	108	0	17.08	17.19	0-1	0.0
	108	55	17.00	17.14	0	0.0
	108	109	16.82	17.24	0-1	0.0
	216	0	16.95	17.19		0.0
DFT-s-OFDM 16QAM	1	1	17.08	17.18	0-1	0.0
CP-OFDM QPSK	1	1	17.19	17.21	0-1.5	0.0

Table H-545

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.07	17.13	0	0.0
	1	95	16.97	17.08		0.0
	1	187	16.85	17.28		0.0
	90	0	17.08	17.17	0-1	0.0
	90	50	17.00	17.14	0	0.0
	90	99	16.94	17.24	0-1	0.0
	180	0	17.06	17.19		0.0
DFT-s-OFDM 16QAM	1	1	17.08	17.05	0-1	0.0
CP-OFDM QPSK	1	1	17.27	17.24	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 273 of 426

Table H-546

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.02	16.71	17.08	0	0.0
	1	81	16.81	16.86	16.97		0.0
	1	160	16.65	17.09	17.22		0.0
	81	0	17.04	16.79	17.01	0-1	0.0
	81	41	16.81	16.78	16.91	0	0.0
	81	81	16.83	17.02	17.20	0-1	0.0
	162	0	16.88	16.86	17.01		0.0
DFT-s-OFDM 16QAM	1	1	16.87	16.57	16.95	0-1	0.0
CP-OFDM QPSK	1	1	17.01	16.79	16.95	0-1.5	0.0

Table H-547

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	17.29	16.97	17.35	0	0.0
	1	67	17.16	17.23	17.28		0.0
	1	131	17.04	17.37	17.57		0.0
	64	0	17.40	17.16	17.34	0-1	0.0
	64	35	17.35	17.15	17.51	0	0.0
	64	69	17.18	17.26	17.55	0-1	0.0
	128	0	17.24	17.16	17.38		0.0
DFT-s-OFDM 16QAM	1	1	17.24	16.93	17.25	0-1	0.0
CP-OFDM QPSK	1	1	17.40	17.16	17.27	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 274 of 426

Table H-548

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.36	16.88	17.14	17.39	0	0.0
	1	60	17.24	16.93	17.37	17.40		0.0
	1	117	17.10	17.19	17.41	17.60		0.0
	54	0	17.35	16.95	17.35	17.32	0-1	0.0
	54	27	17.24	16.88	17.24	17.27	0	0.0
	54	54	17.29	17.17	17.34	17.59	0-1	0.0
	108	0	17.35	17.01	17.32	17.37		0.0
DFT-s-OFDM 16QAM	1	1	17.32	16.77	17.15	17.23	0-1	0.0
CP-OFDM QPSK	1	1	17.34	16.93	17.33	17.36	0-1.5	0.0

Table H-549

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.12	16.68	16.98	17.18	0	0.0
	1	53	17.14	16.81	17.13	17.21		0.0
	1	104	16.98	17.05	17.10	17.30		0.0
	50	0	17.23	16.79	17.21	17.25	0-1	0.0
	50	28	17.22	16.85	17.26	17.32	0	0.0
	50	56	17.15	17.01	17.21	17.40	0-1	0.0
	100	0	17.20	16.83	17.27	17.31		0.0
DFT-s-OFDM 16QAM	1	1	17.01	16.60	16.98	17.08	0-1	0.0
CP-OFDM QPSK	1	1	17.14	16.68	17.10	17.18	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 275 of 426

Table H-550

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.15	16.87	16.93	17.13	17.20	0	0.0
	1	46	17.26	16.90	17.20	17.22	17.39		0.0
	1	90	17.15	16.84	17.10	17.17	17.40		0.0
	45	0	17.17	16.91	17.03	17.26	17.21	0-1	0.0
	45	24	17.15	16.77	17.00	17.19	17.32	0	0.0
	45	47	17.10	16.89	17.18	17.21	17.35	0-1	0.0
	90	0	17.17	16.92	17.06	17.23	17.27		0.0
DFT-s-OFDM 16QAM	1	1	17.12	16.87	16.81	17.04	17.11	0-1	0.0
CP-OFDM QPSK	1	1	17.34	17.11	16.90	17.20	17.29	0-1.5	0.0

Table H-551

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.31	17.00	17.03	17.22	17.26	0	0.0
	1	39	17.20	16.79	17.11	17.14	17.30		0.0
	1	76	17.17	16.90	17.13	17.23	17.41		0.0
	36	0	17.20	16.91	17.05	17.24	17.28	0-1	0.0
	36	21	17.22	16.86	17.04	17.16	17.29	0	0.0
	36	42	17.24	16.86	17.20	17.22	17.39	0-1	0.0
	75	0	17.27	16.92	17.06	17.22	17.36		0.0
DFT-s-OFDM 16QAM	1	1	17.22	17.02	16.96	17.29	17.21	0-1	0.0
CP-OFDM QPSK	1	1	17.32	17.12	16.99	17.32	17.47	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 276 of 426

Table H-552

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.28	16.95	17.03	17.23	17.27	0	0.0
	1	33	17.30	16.86	17.18	17.32	17.41		0.0
	1	63	17.22	16.83	17.23	17.17	17.42		0.0
	32	0	17.19	16.91	17.04	17.19	17.35	0-1	0.0
	32	17	17.12	16.86	17.02	17.13	17.35	0	0.0
	32	33	17.29	16.95	17.16	17.20	17.45	0-1	0.0
	64	0	17.20	16.92	17.07	17.21	17.41		0.0
DFT-s-OFDM 16QAM	1	1	17.17	16.96	17.05	17.25	17.28	0-1	0.0
CP-OFDM QPSK	1	1	17.28	17.03	17.11	17.32	17.27	0-1.5	0.0

Table H-553

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.14	16.85	16.90	17.09	17.23	0	0.0
	1	26	17.16	16.80	17.05	17.20	17.28		0.0
	1	49	17.10	16.92	17.05	17.16	17.31		0.0
	25	0	17.18	16.83	16.94	17.13	17.32	0-1	0.0
	25	13	17.16	16.77	16.94	17.10	17.29	0	0.0
	25	26	17.18	16.83	17.07	17.11	17.31	0-1	0.0
	50	0	17.20	16.82	17.07	17.13	17.32		0.0
DFT-s-OFDM 16QAM	1	1	16.98	16.83	16.86	17.04	17.18	0-1	0.0
CP-OFDM QPSK	1	1	17.12	16.93	16.99	17.21	17.27	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 277 of 426

Table H-554

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.20	16.89	16.95	17.13	17.36	0	0.0
	1	19	17.16	16.80	17.04	17.15	17.38		0.0
	1	36	17.20	16.82	17.06	17.19	17.37		0.0
	18	0	17.22	16.91	17.07	17.19	17.30	0-1	0.0
	18	10	17.23	16.84	17.02	17.23	17.36	0	0.0
	18	20	17.23	16.86	17.09	17.21	17.34	0-1	0.0
	36	0	17.15	16.80	17.04	17.06	17.28		0.0
DFT-s-OFDM 16QAM	1	1	17.11	16.92	16.94	17.11	17.22	0-1	0.0
CP-OFDM QPSK	1	1	17.14	16.95	17.00	17.19	17.35	0-1.5	0.0

Table H-555

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	17.21	16.93	17.05	17.17	17.42	0	0.0
	1	12	17.21	16.91	17.05	17.20	17.36		0.0
	1	22	17.22	16.88	17.19	17.24	17.47		0.0
	12	0	17.26	16.95	17.03	17.24	17.31	0-1	0.0
	12	6	17.18	16.85	16.95	17.19	17.30	0	0.0
	12	12	17.27	16.88	17.08	17.25	17.39	0-1	0.0
	24	0	17.18	16.88	17.03	17.14	17.30		0.0
DFT-s-OFDM 16QAM	1	1	17.21	16.87	17.04	17.18	17.29	0-1	0.0
CP-OFDM QPSK	1	1	17.31	16.97	17.12	17.31	17.39	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 278 of 426

Table H-556

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	508200 (2541 MHz)	528996 (2644.98 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.84	10.95	0	0.0
	1	123	10.59	10.76		0.0
	1	243	10.66	11.07		0.0
	120	0	10.72	10.90	0-1	0.0
	120	63	10.65	10.85	0	0.0
	120	125	10.50	10.88	0-1	0.0
	243	0	10.55	10.85		0.0
DFT-s-OFDM 16QAM	1	1	10.82	11.02	0-1	0.0
CP-OFDM QPSK	1	1	10.75	10.94	0-1.5	0.0

Table H-557

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	507204 (2536.02 MHz)	529998 (2649.99 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.77	10.94	0	0.0
	1	109	10.64	10.82		0.0
	1	215	10.56	11.07		0.0
	108	0	10.77	10.96	0-1	0.0
	108	55	10.60	10.91	0	0.0
	108	109	10.54	10.90	0-1	0.0
	216	0	10.63	10.97		0.0
DFT-s-OFDM 16QAM	1	1	10.74	11.04	0-1	0.0
CP-OFDM QPSK	1	1	10.85	11.01	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 279 of 426

Table H-558

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	506202 (2531.01 MHz)	531000 (2655 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.73	10.87	0	0.0
	1	95	10.63	10.75		0.0
	1	187	10.59	11.07		0.0
	90	0	10.78	10.96	0-1	0.0
	90	50	10.67	10.95	0	0.0
	90	99	10.49	10.96	0-1	0.0
	180	0	10.63	10.95		0.0
DFT-s-OFDM 16QAM	1	1	10.74	10.92	0-1	0.0
CP-OFDM QPSK	1	1	10.72	11.02	0-1.5	0.0

Table H-559

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	10.63	10.37	10.75	0	0.0
	1	81	10.65	10.69	10.65		0.0
	1	160	10.34	10.85	11.00		0.0
	81	0	10.61	10.54	10.73	0-1	0.0
	81	41	10.52	10.70	10.66	0	0.0
	81	81	10.45	10.82	10.84	0-1	0.0
	162	0	10.55	10.66	10.78		0.0
DFT-s-OFDM 16QAM	1	1	10.65	10.38	10.71	0-1	0.0
CP-OFDM QPSK	1	1	10.67	10.42	10.86	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 280 of 426

Table H-560

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth							
			Channel			MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)		
			Conducted Power [dBm]				
DFT-s-OFDM QPSK	1	1	10.91	10.69	11.04	0	0.0
	1	67	10.84	10.87	11.05		0.0
	1	131	10.72	11.15	11.32		0.0
	64	0	10.92	10.80	10.95	0-1	0.0
	64	35	10.99	11.03	11.04	0	0.0
	64	69	10.83	11.01	11.22	0-1	0.0
	128	0	10.89	10.89	11.05		0.0
DFT-s-OFDM 16QAM	1	1	11.01	10.56	11.02	0-1	0.0
CP-OFDM QPSK	1	1	10.84	10.67	11.10	0-1.5	0.0

Table H-561

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	10.94	10.47	11.05	10.94	0	0.0
	1	60	10.97	10.61	11.02	11.04		0.0
	1	117	10.84	10.84	11.07	11.28		0.0
	54	0	11.08	10.52	11.05	10.92	0-1	0.0
	54	27	10.99	10.58	10.98	10.95	0	0.0
	54	54	10.96	10.76	10.96	11.16	0-1	0.0
	108	0	10.96	10.64	11.05	10.96		0.0
DFT-s-OFDM 16QAM	1	1	10.94	10.53	10.97	10.98	0-1	0.0
CP-OFDM QPSK	1	1	10.93	10.46	11.02	11.03	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 281 of 426

Table H-562

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	10.72	10.28	10.82	10.76	0	0.0
	1	53	10.79	10.44	10.93	10.87		0.0
	1	104	10.60	10.75	10.86	10.95		0.0
	50	0	10.79	10.39	10.90	10.85	0-1	0.0
	50	28	10.83	10.54	11.03	10.95	0	0.0
	50	56	10.78	10.66	10.90	11.05	0-1	0.0
	100	0	10.81	10.47	10.93	10.91		0.0
DFT-s-OFDM 16QAM	1	1	10.74	10.42	10.97	10.78	0-1	0.0
CP-OFDM QPSK	1	1	10.82	10.33	10.84	10.81	0-1.5	0.0

Table H-563

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	10.81	10.61	10.59	10.93	10.77	0	0.0
	1	46	10.88	10.50	10.89	10.98	11.01		0.0
	1	90	10.75	10.55	10.93	10.85	11.13		0.0
	45	0	10.79	10.56	10.72	10.98	10.83	0-1	0.0
	45	24	10.83	10.48	10.84	10.96	10.90	0	0.0
	45	47	10.78	10.48	10.89	10.89	10.98	0-1	0.0
	90	0	10.81	10.46	10.82	10.97	10.97		0.0
DFT-s-OFDM 16QAM	1	1	10.83	10.75	10.65	10.86	10.77	0-1	0.0
CP-OFDM QPSK	1	1	10.73	10.59	10.56	11.02	10.86	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 282 of 426

Table H-564

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	10.87	10.67	10.65	11.08	10.91	0	0.0
	1	39	10.78	10.44	10.79	10.88	11.00		0.0
	1	76	10.76	10.54	10.95	10.89	11.09		0.0
	36	0	10.83	10.53	10.71	11.01	10.86	0-1	0.0
	36	21	10.79	10.42	10.82	10.91	10.91	0	0.0
	36	42	10.81	10.49	10.89	10.96	11.07	0-1	0.0
	75	0	10.80	10.45	10.83	10.95	10.96		0.0
DFT-s-OFDM 16QAM	1	1	10.94	10.77	10.71	11.06	10.91	0-1	0.0
CP-OFDM QPSK	1	1	10.82	10.64	10.72	11.01	10.91	0-1.5	0.0

Table H-565

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	10.83	10.72	10.75	11.02	10.98	0	0.0
	1	33	10.84	10.66	10.86	10.95	11.17		0.0
	1	63	10.79	10.56	10.90	10.86	11.16		0.0
	32	0	10.77	10.60	10.75	10.91	11.03	0-1	0.0
	32	17	10.76	10.59	10.84	10.97	11.01	0	0.0
	32	33	10.83	10.55	10.95	10.92	11.09	0-1	0.0
	64	0	10.80	10.60	10.78	10.93	10.97		0.0
DFT-s-OFDM 16QAM	1	1	10.87	10.66	10.88	11.05	10.97	0-1	0.0
CP-OFDM QPSK	1	1	10.97	10.65	10.78	11.02	10.95	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 283 of 426

Table H-566

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	10.64	10.65	10.65	10.87	10.85	0	0.0
	1	26	10.82	10.61	10.74	10.83	10.97		0.0
	1	49	10.77	10.52	10.84	10.79	11.07		0.0
	25	0	10.68	10.59	10.76	10.79	10.97	0-1	0.0
	25	13	10.72	10.64	10.84	10.91	11.01	0	0.0
	25	26	10.70	10.58	10.83	10.86	11.06	0-1	0.0
	50	0	10.70	10.62	10.79	10.79	11.01		0.0
DFT-s-OFDM 16QAM	1	1	10.64	10.74	10.63	10.85	10.86	0-1	0.0
CP-OFDM QPSK	1	1	10.63	10.64	10.60	10.86	10.91	0-1.5	0.0

Table H-567

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	10.74	10.47	10.72	10.90	11.02	0	0.0
	1	19	10.76	10.48	10.85	10.96	11.01		0.0
	1	36	10.81	10.44	10.86	10.87	11.11		0.0
	18	0	10.79	10.48	10.86	10.88	10.99	0-1	0.0
	18	10	10.84	10.55	10.91	10.96	11.07	0	0.0
	18	20	10.79	10.43	10.91	10.87	11.08	0-1	0.0
	36	0	10.78	10.49	10.86	10.88	11.05		0.0
DFT-s-OFDM 16QAM	1	1	10.84	10.56	10.77	11.01	11.13	0-1	0.0
CP-OFDM QPSK	1	1	10.80	10.55	10.77	10.93	11.05	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 284 of 426

Table H-568

NR Band n41 PC2/PC1.5 Antenna B Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth									
			Channel					MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)		
			Conducted Power [dBm]						
DFT-s-OFDM QPSK	1	1	10.90	10.62	10.86	10.97	11.08	0	0.0
	1	12	10.87	10.51	10.84	10.94	11.09		0.0
	1	22	10.94	10.56	10.90	11.00	11.13		0.0
	12	0	10.79	10.50	10.83	10.97	11.04	0-1	0.0
	12	6	10.77	10.46	10.83	10.93	11.05	0	0.0
	12	12	10.81	10.53	10.89	10.96	11.11	0-1	0.0
	24	0	10.75	10.46	10.85	10.86	11.04		0.0
DFT-s-OFDM 16QAM	1	1	10.86	10.65	10.85	10.87	11.14	0-1	0.0
CP-OFDM QPSK	1	1	10.90	10.62	10.81	10.99	11.20	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 285 of 426

Table H-569

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant G	14.61	14.96
SRS #3 Ant D	14.66	14.64
SRS #4 Ant H	8.75	7.96

Table H-570

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant G	14.70	15.00
SRS #3 Ant D	14.60	14.81
SRS #4 Ant H	8.75	7.98

Table H-571

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant G	14.67	14.95
SRS #3 Ant D	14.60	14.80
SRS #4 Ant H	8.79	7.93

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 286 of 426

Table H-572

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant G	14.65	14.73	13.68
SRS #3 Ant D	14.48	14.50	14.79
SRS #4 Ant H	8.68	8.71	6.91

Table H-573

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant G	14.86	14.97	13.73
SRS #3 Ant D	14.78	14.93	14.93
SRS #4 Ant H	8.74	8.97	6.88

Table H-574

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 1/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant G	14.88	14.22	14.90	14.85
SRS #3 Ant D	14.76	14.81	14.91	15.00
SRS #4 Ant H	8.69	8.96	8.49	7.06

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 287 of 426

Table H-575

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5 (Folder Closed-Body, Folder Closed – Grip) and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant G	14.73	14.43	14.88	13.89
SRS #3 Ant D	14.61	14.65	14.76	14.99
SRS #4 Ant H	8.53	8.88	8.38	7.40

Table H-576

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5 (Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip) and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	14.68	14.57	14.88	14.49	13.39
SRS #3 Ant D	14.58	14.41	14.78	14.71	14.97
SRS #4 Ant H	8.54	8.67	8.83	8.18	7.31

Table H-577

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5 (Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip) and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	14.71	14.51	14.79	14.76	14.13
SRS #3 Ant D	14.70	14.48	14.77	14.69	14.98
SRS #4 Ant H	8.44	8.76	8.84	8.08	7.45

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 288 of 426

Table H-578

**NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 25 MHz Bandwidth**

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	14.66	14.55	14.79	14.31	13.45
SRS #3 Ant D	14.62	14.45	14.73	14.69	14.98
SRS #4 Ant H	8.34	8.72	8.84	8.08	7.43

Table H-579

**NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth**

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	14.64	14.46	14.76	14.81	14.20
SRS #3 Ant D	14.57	14.40	14.64	14.69	14.96
SRS #4 Ant H	8.24	8.63	8.72	8.06	7.86

Table H-580

**NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5
(Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip)
and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth**

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	14.63	14.45	14.68	14.46	13.65
SRS #3 Ant D	14.62	14.38	14.68	14.56	14.95
SRS #4 Ant H	8.27	8.59	8.70	7.97	7.86

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 289 of 426

Table H-581

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 0/1/3/5 (Folder Open - Body, Folder Closed-Body, Folder Closed - Head, Folder Closed – Grip) and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	14.70	14.51	14.86	14.56	13.71
SRS #3 Ant D	14.78	14.55	14.77	14.71	14.95
SRS #4 Ant H	8.27	8.68	8.86	8.07	7.86

Table H-582

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 90 MHz Bandwidth

NR Band n41 90 MHz Bandwidth		
Channel		
Antenna	508200 (2541 MHz)	528996 (2644.98 MHz)
	Conducted Power [dBm]	
SRS #2 Ant G	9.43	9.89
SRS #3 Ant D	7.42	7.65
SRS #4 Ant H	7.78	6.99

Table H-583

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 80 MHz Bandwidth

NR Band n41 80 MHz Bandwidth		
Channel		
Antenna	507204 (2536.02 MHz)	529998 (2649.99 MHz)
	Conducted Power [dBm]	
SRS #2 Ant G	9.49	9.94
SRS #3 Ant D	7.42	7.71
SRS #4 Ant H	7.72	6.97

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 290 of 426

Table H-584

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 70 MHz Bandwidth

NR Band n41 70 MHz Bandwidth		
Channel		
Antenna	506202 (2531.01 MHz)	531000 (2655 MHz)
	Conducted Power [dBm]	
SRS #2 Ant G	9.48	9.99
SRS #3 Ant D	7.49	7.69
SRS #4 Ant H	7.70	6.94

Table H-585

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 60 MHz Bandwidth

NR Band n41 60 MHz Bandwidth			
Channel			
Antenna	505200 (2526 MHz)	518598 (2592.99 MHz)	531996 (2659.98 MHz)
	Conducted Power [dBm]		
SRS #2 Ant G	9.47	9.70	9.96
SRS #3 Ant D	7.37	7.49	7.73
SRS #4 Ant H	7.62	7.61	6.85

Table H-586

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 50 MHz Bandwidth

NR Band n41 50 MHz Bandwidth			
Channel			
Antenna	504204 (2521.02 MHz)	518598 (2592.99 MHz)	532998 (2664.99 MHz)
	Conducted Power [dBm]		
SRS #2 Ant G	9.71	9.96	9.90
SRS #3 Ant D	7.53	7.79	7.98
SRS #4 Ant H	7.72	7.90	7.06

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 291 of 426

Table H-587

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 45 MHz Bandwidth

NR Band n41 45 MHz Bandwidth				
Channel				
Antenna	503700 (2518.5 MHz)	513636 (2568.18 MHz)	523566 (2617.83 MHz)	533496 (2667.48 MHz)
	Conducted Power [dBm]			
SRS #2 Ant G	9.72	9.65	9.97	9.97
SRS #3 Ant D	7.61	7.50	7.83	7.99
SRS #4 Ant H	7.56	7.83	7.53	7.03

Table H-588

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n41 40 MHz Bandwidth				
Channel				
Antenna	503202 (2516.01 MHz)	513468 (2567.34 MHz)	523734 (2618.67 MHz)	534000 (2670 MHz)
	Conducted Power [dBm]			
SRS #2 Ant G	9.58	9.53	9.88	9.89
SRS #3 Ant D	7.42	7.46	7.68	7.83
SRS #4 Ant H	7.55	7.81	7.51	6.96

Table H-589

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 1 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 35 MHz Bandwidth

NR Band n41 35 MHz Bandwidth					
Channel					
Antenna	502704 (2513.52 MHz)	510648 (2553.24 MHz)	518598 (2592.99 MHz)	526548 (2632.74 MHz)	534498 (2672.49 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	9.55	9.42	9.79	9.83	9.92
SRS #3 Ant D	7.53	7.34	7.69	7.62	7.72
SRS #4 Ant H	7.41	7.69	7.81	7.14	6.87

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 292 of 426

Table H-590

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n41 30 MHz Bandwidth					
Channel					
Antenna	502200 (2511 MHz)	510402 (2552.01 MHz)	518598 (2592.99 MHz)	526800 (2634 MHz)	534996 (2674.98 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	9.61	9.44	9.81	9.86	9.94
SRS #3 Ant D	7.50	7.33	7.69	7.72	7.73
SRS #4 Ant H	7.52	7.71	7.80	7.24	6.95

Table H-591

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n41 25 MHz Bandwidth					
Channel					
Antenna	501702 (2508.51 MHz)	510150 (2550.75 MHz)	518598 (2592.99 MHz)	527052 (2635.26 MHz)	535500 (2677.5 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	9.54	9.35	9.76	9.79	9.81
SRS #3 Ant D	7.55	7.29	7.59	7.67	7.74
SRS #4 Ant H	7.34	7.62	7.79	7.14	6.84

Table H-592

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n41 20 MHz Bandwidth					
Channel					
Antenna	501204 (2506.02 MHz)	509898 (2549.49 MHz)	518598 (2592.99 MHz)	527298 (2636.49 MHz)	535998 (2679.99 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	9.60	9.35	9.74	9.78	9.90
SRS #3 Ant D	7.48	7.35	7.57	7.67	7.72
SRS #4 Ant H	7.36	7.67	7.85	7.16	6.86

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 293 of 426

Table H-593

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n41 15 MHz Bandwidth					
Channel					
Antenna	500700 (2503.5 MHz)	509652 (2548.26 MHz)	518598 (2592.99 MHz)	527550 (2637.75 MHz)	536496 (2682.48 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	9.54	9.34	9.68	9.71	9.91
SRS #3 Ant D	7.53	7.25	7.58	7.56	7.66
SRS #4 Ant H	7.29	7.54	7.72	7.04	6.76

Table H-594

NR Band n41 PC2/PC1.5 Antenna G Path 2 Measured P_{limit} for DSI = 4 (Folder Open – Grip) and

NR Band n41 PC2/PC1.5 Antenna H & D Path 2 Measured P_{limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n41 10 MHz Bandwidth					
Channel					
Antenna	500202 (2501.01 MHz)	509400 (2547 MHz)	518598 (2592.99 MHz)	527802 (2639.01 MHz)	537000 (2685 MHz)
	Conducted Power [dBm]				
SRS #2 Ant G	9.56	9.34	9.66	9.74	9.90
SRS #3 Ant D	7.58	7.30	7.60	7.56	7.61
SRS #4 Ant H	7.28	7.52	7.77	7.06	6.76

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 294 of 426

H.2.2 NR Band n48 Path 1

Table H-595
NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.70	19.62	19.65	19.73	0	0.0
	1	39	19.74	19.24	19.36	19.39		0.0
	1	76	19.78	19.55	19.68	19.47		0.0
	36	0	19.82	19.57	19.53	19.61	0-1	0.0
	36	21	19.65	19.54	19.46	19.48	0	0.0
	36	42	19.75	19.55	19.52	19.47	0-1	0.0
	75	0	19.69	19.54	19.50	19.59		0.0
DFT-s-OFDM 16QAM	1	1	19.71	19.74	19.79	19.68	0-1	0.0
CP-OFDM QPSK	1	1	19.81	19.56	19.67	19.36	0-1.5	0.0

Table H-596
NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.49	19.53	19.42	19.32	0	0.0
	1	26	19.46	19.35	19.39	19.43		0.0
	1	49	19.73	19.39	19.35	19.36		0.0
	25	0	19.66	19.53	19.49	19.46	0-1	0.0
	25	13	19.66	19.52	19.35	19.38	0	0.0
	25	26	19.71	19.57	19.38	19.42	0-1	0.0
	50	0	19.66	19.53	19.40	19.41		0.0
DFT-s-OFDM 16QAM	1	1	19.56	19.47	19.44	19.41	0-1	0.0
CP-OFDM QPSK	1	1	19.65	19.43	19.48	19.48	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 295 of 426

Table H-597

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.46	19.67	19.47	19.59	0	0.0
	1	19	19.52	19.31	19.36	19.38		0.0
	1	36	19.59	19.52	19.41	19.43		0.0
	18	0	19.60	19.47	19.47	19.65	0-1	0.0
	18	10	19.60	19.48	19.35	19.41	0	0.0
	18	20	19.71	19.57	19.34	19.38	0-1	0.0
	36	0	19.67	19.51	19.42	19.43		0.0
DFT-s-OFDM 16QAM	1	1	19.56	19.75	19.52	19.60	0-1	0.0
CP-OFDM QPSK	1	1	19.60	19.67	19.40	19.57	0-1.5	0.0

Table H-598

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	19.60	19.69	19.41	19.35	0	0.0
	1	12	19.74	19.69	19.42	19.41		0.0
	1	22	19.78	19.67	19.62	19.41		0.0
	12	0	19.68	19.57	19.52	19.47	0-1	0.0
	12	6	19.66	19.51	19.36	19.33	0	0.0
	12	12	19.73	19.48	19.50	19.53	0-1	0.0
	24	0	19.67	19.60	19.44	19.49		0.0
DFT-s-OFDM 16QAM	1	1	19.74	19.79	19.30	19.71	0-1	0.0
CP-OFDM QPSK	1	1	19.74	19.65	19.51	19.68	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 296 of 426

Table H-599

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.60	17.67	17.70	17.69	0	0.0
	1	39	17.31	17.50	17.42	17.51		0.0
	1	76	17.55	17.63	17.51	17.55		0.0
	36	0	17.76	17.59	17.61	17.65	0-1	0.0
	36	21	17.47	17.52	17.52	17.44	0	0.0
	36	42	17.52	17.69	17.52	17.51	0-1	0.0
	75	0	17.53	17.66	17.57	17.55		0.0
DFT-s-OFDM 16QAM	1	1	17.65	17.59	17.49	17.75	0-1	0.0
CP-OFDM QPSK	1	1	17.65	17.69	17.55	17.69	0-1.5	0.0

Table H-600

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.54	17.46	17.50	17.51	0	0.0
	1	26	17.45	17.45	17.49	17.57		0.0
	1	49	17.42	17.52	17.37	17.56		0.0
	25	0	17.56	17.50	17.42	17.55	0-1	0.0
	25	13	17.53	17.47	17.39	17.60	0	0.0
	25	26	17.48	17.55	17.47	17.51	0-1	0.0
	50	0	17.47	17.56	17.43	17.55		0.0
DFT-s-OFDM 16QAM	1	1	17.63	17.52	17.62	17.46	0-1	0.0
CP-OFDM QPSK	1	1	17.30	17.56	17.44	17.60	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 297 of 426

Table H-601

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.54	17.52	17.57	17.52	0	0.0
	1	19	17.45	17.57	17.45	17.53		0.0
	1	36	17.55	17.62	17.67	17.51		0.0
	18	0	17.50	17.51	17.44	17.45	0-1	0.0
	18	10	17.71	17.58	17.55	17.51	0	0.0
	18	20	17.61	17.49	17.47	17.52	0-1	0.0
	36	0	17.55	17.57	17.53	17.51		0.0
DFT-s-OFDM 16QAM	1	1	17.62	17.64	17.58	17.50	0-1	0.0
CP-OFDM QPSK	1	1	17.68	17.45	17.41	17.60	0-1.5	0.0

Table H-602

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	17.49	17.43	17.48	17.54	0	0.0
	1	12	17.60	17.75	17.47	17.58		0.0
	1	22	17.63	17.49	17.38	17.50		0.0
	12	0	17.65	17.61	17.44	17.43	0-1	0.0
	12	6	17.56	17.51	17.37	17.45	0	0.0
	12	12	17.62	17.55	17.34	17.51	0-1	0.0
	24	0	17.62	17.58	17.42	17.50		0.0
DFT-s-OFDM 16QAM	1	1	17.60	17.65	17.61	17.47	0-1	0.0
CP-OFDM QPSK	1	1	17.38	17.54	17.31	17.45	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 298 of 426

Table H-603

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	8.52	9.14	9.08	9.14	0	0.0
	1	39	8.39	8.75	8.94	8.76		0.0
	1	76	8.60	8.94	9.07	8.66		0.0
	36	0	8.55	8.96	8.97	9.04	0-1	0.0
	36	21	8.38	8.87	8.84	8.82	0	0.0
	36	42	8.47	8.94	8.92	8.79	0-1	0.0
	75	0	8.46	8.90	8.94	8.86		0.0
DFT-s-OFDM 16QAM	1	1	8.64	9.36	9.16	9.24	0-1	0.0
CP-OFDM QPSK	1	1	8.51	8.98	8.98	9.06	0-1.5	0.0

Table H-604

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	8.43	8.90	9.10	8.88	0	0.0
	1	26	8.43	9.11	8.89	8.69		0.0
	1	49	8.24	8.99	8.81	8.65		0.0
	25	0	8.36	9.00	8.89	8.83	0-1	0.0
	25	13	8.38	8.93	8.83	8.82	0	0.0
	25	26	8.35	8.97	8.89	8.76	0-1	0.0
	50	0	8.40	8.94	8.80	8.82		0.0
DFT-s-OFDM 16QAM	1	1	8.36	8.91	8.93	8.95	0-1	0.0
CP-OFDM QPSK	1	1	8.28	8.94	8.88	9.03	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 299 of 426

Table H-605

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	8.63	9.12	8.90	9.36	0	0.0
	1	19	8.46	9.03	8.98	8.84		0.0
	1	36	8.51	9.14	8.96	8.84		0.0
	18	0	8.38	9.02	8.92	9.00	0-1	0.0
	18	10	8.39	9.02	8.80	8.82	0	0.0
	18	20	8.44	8.97	8.95	8.77	0-1	0.0
	36	0	8.39	8.98	8.89	8.87		0.0
DFT-s-OFDM 16QAM	1	1	8.45	8.98	8.81	8.99	0-1	0.0
CP-OFDM QPSK	1	1	8.49	8.88	8.91	8.70	0-1.5	0.0

Table H-606

NR Band n48 Path 1 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	8.65	9.02	9.01	9.06	0	0.0
	1	12	8.52	8.97	8.97	8.93		0.0
	1	22	8.65	9.03	9.02	8.77		0.0
	12	0	8.53	8.94	8.96	8.81	0-1	0.0
	12	6	8.37	8.89	8.96	8.89	0	0.0
	12	12	8.46	8.95	9.01	8.83	0-1	0.0
	24	0	8.57	8.87	8.95	8.81		0.0
DFT-s-OFDM 16QAM	1	1	8.59	8.95	9.18	8.86	0-1	0.0
CP-OFDM QPSK	1	1	8.59	9.17	8.94	9.16	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 300 of 426

Table H-607

**NR Band n48 Antenna C Path 1 Measured P_{Max} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) and
NR Band n48 Antenna A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth**

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
SRS #2 Ant C	17.33	17.38	17.29	17.33
SRS #3 Ant G	14.59	14.29	14.50	14.54
SRS #4 Ant A	14.68	14.50	14.54	14.64

Table H-608

**NR Band n48 Antenna C Path 1 Measured P_{Max} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) and
NR Band n48 Antenna A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth**

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
#2 Ant C	17.27	17.05	17.10	16.95
#3 Ant G	14.71	14.65	14.43	14.36
#4 Ant A	14.60	14.28	14.37	14.58

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 301 of 426

Table H-609

**NR Band n48 Antenna C Path 1 Measured P_{Max} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) and
NR Band n48 Antenna A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth**

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
S #2 Ant C	17.03	17.39	17.42	17.26
S #3 Ant G	14.71	14.68	14.50	14.42
S #4 Ant A	14.65	14.36	14.69	14.65

Table H-610

**NR Band n48 Antenna C Path 1 Measured P_{Max} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) and
NR Band n48 Antenna A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth**

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
Ant C	17.65	17.55	17.43	17.10
Ant G	14.71	14.63	14.49	14.34
Ant A	14.69	14.24	14.47	14.66

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 302 of 426

Table H-611

NR Band n48 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant C	9.99	9.56	9.38	9.57
SRS #3 Ant G	7.83	7.58	7.79	7.77
SRS #4 Ant A	7.74	7.62	7.63	7.61

Table H-612

NR Band n48 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
2 Ant C	9.87	9.39	9.28	9.20
3 Ant G	7.92	7.69	7.35	7.31
4 Ant A	7.84	7.50	7.64	7.73

Table H-613

NR Band n48 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
#2 Ant C	9.90	9.40	9.15	9.12
#3 Ant G	7.92	7.71	7.41	7.28
#4 Ant A	7.86	7.45	7.70	7.78

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 303 of 426

Table H-614

NR Band n48 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
§ #2 Ant C	9.87	9.36	9.17	9.00
§ #3 Ant G	7.90	7.74	7.47	7.28
§ #4 Ant A	7.86	7.46	7.62	7.74

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 304 of 426

H.2.3 NR Band n48 Path 2

Table H-615

NR Band n48 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	24.05	23.90	23.89	23.90	0	0.0
	1	39	23.98	23.76	23.79	23.66		0.0
	1	76	24.14	24.01	23.86	23.54		0.0
	36	0	23.23	23.16	23.14	23.03	0-1	1.0
	36	21	24.03	23.80	23.71	23.57	0	0.0
	36	42	23.33	23.21	23.08	22.89	0-1	1.0
	75	0	23.07	23.11	23.08	23.02		1.0
DFT-s-OFDM 16QAM	1	1	23.42	23.48	23.06	23.18	0-1	1.0
CP-OFDM QPSK	1	1	22.95	22.66	22.73	22.46	0-1.5	1.5

Table H-616

NR Band n48 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	23.88	23.81	23.69	23.60	0	0.0
	1	26	24.01	23.63	23.73	23.92		0.0
	1	49	24.03	23.75	23.70	23.91		0.0
	25	0	23.26	23.12	22.98	23.50	0-1	1.0
	25	13	24.02	23.81	23.80	23.90	0	0.0
	25	26	23.31	23.04	23.00	23.49	0-1	1.0
	50	0	23.25	23.06	22.92	23.10		1.0
DFT-s-OFDM 16QAM	1	1	23.35	23.12	22.91	23.46	0-1	1.0
CP-OFDM QPSK	1	1	22.84	22.58	22.46	22.99	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 305 of 426

Table H-617
NR Band n48 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	24.05	23.92	23.81	23.67	0	0.0
	1	19	24.15	23.77	23.64	23.58		0.0
	1	36	24.08	23.90	23.77	23.65		0.0
	18	0	23.49	23.00	23.05	22.90	0-1	1.0
	18	10	24.37	23.81	23.71	23.66	0	0.0
	18	20	23.45	23.12	23.03	22.86	0-1	1.0
	36	0	23.14	23.05	23.01	22.91		1.0
DFT-s-OFDM 16QAM	1	1	23.34	23.08	22.96	23.07	0-1	1.0
CP-OFDM QPSK	1	1	22.99	22.87	22.46	22.55	0-1.5	1.5

Table H-618
NR Band n48 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	24.18	23.74	23.70	23.71	0	0.0
	1	12	24.06	23.97	23.78	23.55		0.0
	1	22	24.28	24.02	23.78	23.66		0.0
	12	0	23.47	23.16	23.00	22.87	0-1	1.0
	12	6	24.41	23.74	23.83	23.60	0	0.0
	12	12	23.45	23.18	22.91	22.81	0-1	1.0
	24	0	23.36	23.10	23.12	22.94		1.0
DFT-s-OFDM 16QAM	1	1	23.40	23.36	23.13	23.29	0-1	1.0
CP-OFDM QPSK	1	1	22.98	22.73	22.44	22.99	0-1.5	1.5

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 306 of 426

Table H-619
NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.43	18.33	18.36	18.43	0	0.0
	1	39	18.38	18.23	18.22	18.01		0.0
	1	76	18.50	18.33	18.28	18.01		0.0
	36	0	18.55	18.29	18.30	18.29	0-1	0.0
	36	21	18.42	18.20	18.31	18.11	0	0.0
	36	42	18.45	18.31	18.28	18.04	0-1	0.0
	75	0	18.46	18.28	18.30	18.15		0.0
DFT-s-OFDM 16QAM	1	1	18.45	18.42	18.50	17.83	0-1	0.0
CP-OFDM QPSK	1	1	18.45	18.74	18.42	17.90	0-1.5	0.0

Table H-620
NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.26	18.39	18.37	18.04	0	0.0
	1	26	18.25	18.21	18.16	17.99		0.0
	1	49	18.34	18.30	18.27	17.84		0.0
	25	0	18.22	18.21	18.23	17.98	0-1	0.0
	25	13	18.36	18.29	18.20	18.01	0	0.0
	25	26	18.34	18.32	18.28	17.91	0-1	0.0
	50	0	18.30	18.25	18.23	18.07		0.0
DFT-s-OFDM 16QAM	1	1	18.24	18.25	18.19	17.85	0-1	0.0
CP-OFDM QPSK	1	1	18.34	18.31	18.44	17.87	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 307 of 426

Table H-621

NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.26	18.45	18.30	18.40	0	0.0
	1	19	18.11	18.15	18.09	17.87		0.0
	1	36	18.33	18.26	18.39	18.00		0.0
	18	0	18.35	18.28	18.25	18.00	0-1	0.0
	18	10	18.33	18.31	18.33	18.03	0	0.0
	18	20	18.30	18.25	18.23	17.90	0-1	0.0
	36	0	18.38	18.18	18.13	17.97		0.0
DFT-s-OFDM 16QAM	1	1	18.40	18.36	18.32	17.98	0-1	0.0
CP-OFDM QPSK	1	1	18.24	18.35	18.15	18.53	0-1.5	0.0

Table H-622

NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	18.47	18.22	18.25	17.97	0	0.0
	1	12	18.30	18.32	18.27	17.87		0.0
	1	22	18.35	18.42	18.16	18.16		0.0
	12	0	18.38	18.21	18.25	18.03	0-1	0.0
	12	6	18.32	18.21	18.23	17.96	0	0.0
	12	12	18.38	18.29	18.20	17.92	0-1	0.0
	24	0	18.40	18.29	18.16	17.88		0.0
DFT-s-OFDM 16QAM	1	1	18.36	18.32	18.34	18.23	0-1	0.0
CP-OFDM QPSK	1	1	18.39	18.27	18.12	18.06	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 308 of 426

Table H-623

NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	9.68	9.55	9.40	9.43	0	0.0
	1	39	9.60	9.21	9.17	9.21		0.0
	1	76	9.84	9.36	9.33	9.15		0.0
	36	0	9.69	9.36	9.32	9.35	0-1	0.0
	36	21	9.73	9.38	9.15	9.25	0	0.0
	36	42	9.68	9.41	9.14	9.08	0-1	0.0
	75	0	9.75	9.35	9.22	9.24		0.0
DFT-s-OFDM 16QAM	1	1	9.65	9.51	9.55	9.43	0-1	0.0
CP-OFDM QPSK	1	1	9.65	9.57	9.51	9.47	0-1.5	0.0

Table H-624

NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	9.47	9.36	9.28	9.28	0	0.0
	1	26	9.57	9.28	9.21	8.95		0.0
	1	49	9.43	9.34	9.24	8.96		0.0
	25	0	9.55	9.28	9.36	9.17	0-1	0.0
	25	13	9.65	9.27	9.26	9.05	0	0.0
	25	26	9.60	9.38	9.19	9.10	0-1	0.0
	50	0	9.58	9.28	9.22	9.13		0.0
DFT-s-OFDM 16QAM	1	1	9.64	9.22	9.16	9.12	0-1	0.0
CP-OFDM QPSK	1	1	9.53	9.37	9.44	9.17	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 309 of 426

Table H-625

NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	9.43	9.31	9.29	9.10	0	0.0
	1	19	9.41	9.26	9.25	9.00		0.0
	1	36	9.37	9.40	9.17	8.99		0.0
	18	0	9.32	9.41	9.35	9.14	0-1	0.0
	18	10	9.29	9.41	9.26	9.09	0	0.0
	18	20	9.24	9.34	9.34	9.04	0-1	0.0
	36	0	9.19	9.38	9.24	9.09		0.0
DFT-s-OFDM 16QAM	1	1	9.41	9.39	9.50	9.19	0-1	0.0
CP-OFDM QPSK	1	1	9.25	9.29	9.24	9.33	0-1.5	0.0

Table H-626

NR Band n48 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth								
			Channel				MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)		
			Conducted Power [dBm]					
DFT-s-OFDM QPSK	1	1	9.63	9.60	9.38	9.33	0	0.0
	1	12	9.67	9.31	9.29	9.17		0.0
	1	22	9.63	9.60	9.22	9.08		0.0
	12	0	9.55	9.42	9.33	9.09	0-1	0.0
	12	6	9.51	9.29	9.31	9.09	0	0.0
	12	12	9.58	9.34	9.28	9.00	0-1	0.0
	24	0	9.58	9.46	9.24	9.10		0.0
DFT-s-OFDM 16QAM	1	1	9.54	9.58	9.33	9.24	0-1	0.0
CP-OFDM QPSK	1	1	9.65	9.37	9.11	9.22	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 310 of 426

Table H-627

NR Band n48 Antenna F Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	19.83	19.55	19.46	19.47

Table H-628

NR Band n48 Antenna F Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	19.64	19.33	19.32	19.45

Table H-629

NR Band n48 Antenna F Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	19.66	19.36	19.36	19.47

Table H-630

NR Band n48 Antenna F Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	19.64	19.36	19.38	19.48

Table H-631

**NR Band n48 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) and
NR Band n48 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth**

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.95	17.66	17.69	17.89
SRS #3 Ant A	14.08	14.54	14.80	14.70
SRS #4 Ant G	14.66	14.20	14.34	14.39

Table H-632

**NR Band n48 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) and
NR Band n48 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5 (Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth**

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.62	17.37	17.35	17.50
SRS #3 Ant A	14.11	14.50	14.43	14.20
SRS #4 Ant G	14.67	14.31	14.06	14.06

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 312 of 426

Table H-633

NR Band n48 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5
(Folder Closed-Body, Folder Closed – Grip) and

NR Band n48 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.62	17.37	17.32	17.47
SRS #3 Ant A	14.30	14.20	14.39	14.23
SRS #4 Ant G	14.73	14.27	14.10	14.02

Table H-634

NR Band n48 Antenna F Measured P_{Limit} for DSI = 1/5
(Folder Closed-Body, Folder Closed – Grip) and

NR Band n48 Antenna A & G Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	17.62	17.41	17.35	17.52
SRS #3 Ant A	14.23	14.16	14.30	14.25
SRS #4 Ant G	14.74	14.27	14.17	14.06

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 313 of 426

Table H-635

NR Band n48 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n48 30 MHz Bandwidth				
Channel				
Antenna	637668 (3565.02 MHz)	640334 (3605.01 MHz)	643000 (3645 MHz)	645666 (3684.99 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	9.77	9.47	9.34	9.40
SRS #3 Ant A	7.53	7.60	7.80	7.76
SRS #4 Ant G	7.59	7.21	7.40	7.26

Table H-636

NR Band n48 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n48 20 MHz Bandwidth				
Channel				
Antenna	637334 (3560.01 MHz)	640222 (3603.33 MHz)	643112 (3646.68 MHz)	646000 (3690 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	9.62	9.30	9.30	9.50
SRS #3 Ant A	7.42	7.24	7.50	7.49
SRS #4 Ant G	7.80	7.49	7.26	7.17

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 314 of 426

Table H-637

NR Band n48 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n48 15 MHz Bandwidth				
Channel				
Antenna	637168 (3557.52 MHz)	640166 (3602.49 MHz)	643166 (3647.49 MHz)	646166 (3692.49 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	9.62	9.31	9.32	9.47
SRS #3 Ant A	7.44	7.28	7.57	7.49
SRS #4 Ant G	7.89	7.54	7.33	7.18

Table H-638

NR Band n48 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n48 10 MHz Bandwidth				
Channel				
Antenna	637000 (3555 MHz)	640112 (3601.68 MHz)	643222 (3648.33 MHz)	646332 (3694.98 MHz)
	Conducted Power [dBm]			
SRS #2 Ant F	9.61	9.30	9.31	9.50
SRS #3 Ant A	7.44	7.16	7.54	7.49
SRS #4 Ant G	7.90	7.44	7.27	7.18

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 315 of 426

H.2.4 NR Band n77 Path 1

Table H-639
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.83	0	0.0
	1	123	19.53		0.0
	1	243	19.51		0.0
	120	0	19.71	0-1	0.0
	120	63	19.53	0	0.0
	120	125	19.63	0-1	0.0
	243	0	19.57		0.0
DFT-s-OFDM 16QAM	1	1	19.84	0-1	0.0
CP-OFDM QPSK	1	1	19.80	0-1.5	0.0

NR Band n77 90 MHz Bandwidth						
Modulation	RB Size	RB Offset	Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
			650000 (3750 MHz) Conducted Power [dBm]	662000 (3930 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.77	19.60	0	0.0
	1	123	19.39	19.75		0.0
	1	243	19.58	19.46		0.0
	120	0	19.49	19.68	0-1	0.0
	120	63	19.36	19.72	0	0.0
	120	125	19.38	19.63	0-1	0.0
	243	0	19.43	19.66		0.0
DFT-s-OFDM 16QAM	1	1	19.66	19.70	0-1	0.0
CP-OFDM QPSK	1	1	19.81	19.82	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 316 of 426

Table H-640
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.80	0	0.0
	1	109	19.51		0.0
	1	215	19.65		0.0
	108	0	19.73	0-1	0.0
	108	55	19.62	0	0.0
	108	109	19.63	0-1	0.0
	216	0	19.64		0.0
DFT-s-OFDM 16QAM	1	1	19.68	0-1	0.0
CP-OFDM QPSK	1	1	19.87	0-1.5	0.0

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.71	19.64	0	0.0
	1	109	19.31	19.74		0.0
	1	215	19.38	19.50		0.0
	108	0	19.53	19.72	0-1	0.0
	108	55	19.39	19.75	0	0.0
	108	109	19.38	19.70	0-1	0.0
	216	0	19.46	19.70		0.0
DFT-s-OFDM 16QAM	1	1	19.55	19.62	0-1	0.0
CP-OFDM QPSK	1	1	19.65	19.92	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 317 of 426

Table H-641
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.70	0	0.0
	1	95	19.58		0.0
	1	187	19.55		0.0
	90	0	19.67	0-1	0.0
	90	50	19.63	0	0.0
	90	99	19.63	0-1	0.0
	180	0	19.64		0.0
DFT-s-OFDM 16QAM	1	1	19.63	0-1	0.0
CP-OFDM QPSK	1	1	19.81	0-1.5	0.0

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.62	19.60	0	0.0
	1	95	19.34	19.76		0.0
	1	187	19.37	19.58		0.0
	90	0	19.55	19.77	0-1	0.0
	90	50	19.41	19.77	0	0.0
	90	99	19.44	19.73	0-1	0.0
	180	0	19.46	19.70		0.0
DFT-s-OFDM 16QAM	1	1	19.50	19.25	0-1	0.0
CP-OFDM QPSK	1	1	19.77	19.40	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 318 of 426

Table H-642
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.56	0	0.0
	1	81	19.52		0.0
	1	160	19.53		0.0
	81	0	19.61	0-1	0.0
	81	41	19.47	0	0.0
	81	81	19.53	0-1	0.0
	162	0	19.55		0.0
DFT-s-OFDM 16QAM	1	1	19.48	0-1	0.0
CP-OFDM QPSK	1	1	19.63	0-1.5	0.0

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.52	19.65	0	0.0
	1	81	19.27	19.60		0.0
	1	160	19.35	19.55		0.0
	81	0	19.42	19.61	0-1	0.0
	81	41	19.18	19.51	0	0.0
	81	81	19.29	19.56	0-1	0.0
	162	0	19.29	19.56		0.0
DFT-s-OFDM 16QAM	1	1	19.38	19.57	0-1	0.0
CP-OFDM QPSK	1	1	19.40	19.64	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 319 of 426

Table H-643
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.72	0	0.0
	1	67	19.76		0.0
	1	131	19.63		0.0
	64	0	19.84	0-1	0.0
	64	35	19.86	0	0.0
	64	69	19.80	0-1	0.0
	128	0	19.85		0.0
DFT-s-OFDM 16QAM	1	1	19.69	0-1	0.0
CP-OFDM QPSK	1	1	19.88	0-1.5	0.0

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.62	19.67	0	0.0
	1	67	19.47	19.87		0.0
	1	131	19.53	19.79		0.0
	64	0	19.56	19.92	0-1	0.0
	64	35	19.52	19.89	0	0.0
	64	69	19.58	19.79	0-1	0.0
	128	0	19.54	19.85		0.0
DFT-s-OFDM 16QAM	1	1	19.56	19.59	0-1	0.0
CP-OFDM QPSK	1	1	19.63	20.04	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 320 of 426

Table H-644
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.63	0	0.0
	1	53	19.64		0.0
	1	104	19.51		0.0
	50	0	19.63	0-1	0.0
	50	28	19.66	0	0.0
	50	56	19.64	0-1	0.0
	100	0	19.66		0.0
DFT-s-OFDM 16QAM	1	1	19.50	0-1	0.0
CP-OFDM QPSK	1	1	19.63	0-1.5	0.0

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.43	19.55	0	0.0
	1	53	19.41	19.64		0.0
	1	104	19.34	19.44		0.0
	50	0	19.37	19.76	0-1	0.0
	50	28	19.38	19.73	0	0.0
	50	56	19.37	19.72	0-1	0.0
	100	0	19.35	19.66		0.0
DFT-s-OFDM 16QAM	1	1	19.25	19.55	0-1	0.0
CP-OFDM QPSK	1	1	19.43	19.60	0-1.5	0.0

Table H-645
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.79	0	0.0
	1	39	19.65		0.0
	1	76	19.62		0.0
	36	0	19.66	0-1	0.0
	36	21	19.63	0	0.0
	36	42	19.67	0-1	0.0
	75	0	19.70		0.0
DFT-s-OFDM 16QAM	1	1	19.71	0-1	0.0
CP-OFDM QPSK	1	1	19.81	0-1.5	0.0

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.53	19.73	0	0.0
	1	39	19.34	19.64		0.0
	1	76	19.43	19.58		0.0
	36	0	19.39	19.78	0-1	0.0
	36	21	19.33	19.64	0	0.0
	36	42	19.38	19.77	0-1	0.0
	75	0	19.35	19.70		0.0
DFT-s-OFDM 16QAM	1	1	19.38	19.64	0-1	0.0
CP-OFDM QPSK	1	1	19.60	19.91	0-1.5	0.0

Table H-646
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.63	0	0.0
	1	33	19.69		0.0
	1	63	19.69		0.0
	32	0	19.67	0-1	0.0
	32	17	19.60	0	0.0
	32	33	19.64	0-1	0.0
	64	0	19.71		0.0
DFT-s-OFDM 16QAM	1	1	19.75	0-1	0.0
CP-OFDM QPSK	1	1	19.60	0-1.5	0.0

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.45	19.85	0	0.0
	1	33	19.44	19.65		0.0
	1	63	19.27	19.70		0.0
	32	0	19.44	19.82	0-1	0.0
	32	17	19.36	19.67	0	0.0
	32	33	19.38	19.77	0-1	0.0
	64	0	19.40	19.76		0.0
DFT-s-OFDM 16QAM	1	1	19.28	19.68	0-1	0.0
CP-OFDM QPSK	1	1	19.32	19.92	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 323 of 426

Table H-647
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.60	0	0.0
	1	26	19.45		0.0
	1	49	19.61		0.0
	25	0	19.57	0-1	0.0
	25	13	19.53	0	0.0
	25	26	19.44	0-1	0.0
	50	0	19.57		0.0
DFT-s-OFDM 16QAM	1	1	19.51	0-1	0.0
CP-OFDM QPSK	1	1	19.66	0-1.5	0.0

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.34	19.63	0	0.0
	1	26	19.31	19.54		0.0
	1	49	19.45	19.62		0.0
	25	0	19.38	19.67	0-1	0.0
	25	13	19.24	19.61	0	0.0
	25	26	19.41	19.68	0-1	0.0
	50	0	19.33	19.72		0.0
DFT-s-OFDM 16QAM	1	1	19.23	19.63	0-1	0.0
CP-OFDM QPSK	1	1	19.33	19.50	0-1.5	0.0

Table H-648
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.51	0	0.0
	1	19	19.65		0.0
	1	36	19.46		0.0
	18	0	19.55	0-1	0.0
	18	10	19.65	0	0.0
	18	20	19.57	0-1	0.0
	36	0	19.52		0.0
DFT-s-OFDM 16QAM	1	1	19.57	0-1	0.0
CP-OFDM QPSK	1	1	19.53	0-1.5	0.0

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.34	19.79	0	0.0
	1	19	19.28	19.50		0.0
	1	36	19.43	19.78		0.0
	18	0	19.45	19.73	0-1	0.0
	18	10	19.31	19.64	0	0.0
	18	20	19.42	19.72	0-1	0.0
	36	0	19.23	19.60		0.0
DFT-s-OFDM 16QAM	1	1	19.26	19.75	0-1	0.0
CP-OFDM OPSK	1	1	19.33	19.87	0-1.5	0.0

Table H-649
NR Band n77 Antenna F Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	19.51	0	0.0
	1	12	19.67		0.0
	1	22	19.71		0.0
	12	0	19.66	0-1	0.0
	12	6	19.50	0	0.0
	12	12	19.61	0-1	0.0
	24	0	19.64		0.0
DFT-s-OFDM 16QAM	1	1	19.62	0-1	0.0
CP-OFDM QPSK	1	1	19.75	0-1.5	0.0

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	19.32	19.71	0	0.0
	1	12	19.42	19.79		0.0
	1	22	19.41	19.58		0.0
	12	0	19.43	19.75	0-1	0.0
	12	6	19.42	19.69	0	0.0
	12	12	19.43	19.83	0-1	0.0
	24	0	19.38	19.72		0.0
DFT-s-OFDM 16QAM	1	1	19.47	19.66	0-1	0.0
CP-OFDM QPSK	1	1	19.50	19.79	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 326 of 426

Table H-650
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.39	0	0.0
	1	123	18.15		0.0
	1	243	18.21		0.0
	120	0	18.44	0-1	0.0
	120	63	18.16	0	0.0
	120	125	18.26	0-1	0.0
	243	0	18.27		0.0
DFT-s-OFDM 16QAM	1	1	18.44	0-1	0.0
CP-OFDM QPSK	1	1	18.55	0-1.5	0.0

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.21	18.60	0	0.0
	1	123	18.10	18.66		0.0
	1	243	18.16	18.35		0.0
	120	0	18.17	18.57	0-1	0.0
	120	63	18.03	18.64	0	0.0
	120	125	18.04	18.54	0-1	0.0
	243	0	18.05	18.60		0.0
DFT-s-OFDM 16QAM	1	1	18.09	18.59	0-1	0.0
CP-OFDM QPSK	1	1	18.34	18.62	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 327 of 426

Table H-651
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.42	0	0.0
	1	109	18.17		0.0
	1	215	18.21		0.0
	108	0	18.45	0-1	0.0
	108	55	18.24	0	0.0
	108	109	18.29	0-1	0.0
	216	0	18.28		0.0
DFT-s-OFDM 16QAM	1	1	18.50	0-1	0.0
CP-OFDM QPSK	1	1	18.47	0-1.5	0.0

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.59	18.58	0	0.0
	1	109	18.58	18.47		0.0
	1	215	18.44	18.34		0.0
	108	0	18.52	18.53	0-1	0.0
	108	55	18.56	18.53	0	0.0
	108	109	18.44	18.43	0-1	0.0
	216	0	18.53	18.47		0.0
DFT-s-OFDM 16QAM	1	1	18.62	18.54	0-1	0.0
CP-OFDM QPSK	1	1	18.45	18.51	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 328 of 426

Table H-652
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.38	0	0.0
	1	95	18.19		0.0
	1	187	18.15		0.0
	90	0	18.38	0-1	0.0
	90	50	18.22	0	0.0
	90	99	18.30	0-1	0.0
	180	0	18.30		0.0
DFT-s-OFDM 16QAM	1	1	18.34	0-1	0.0
CP-OFDM QPSK	1	1	18.55	0-1.5	0.0

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.49	18.54	0	0.0
	1	95	18.59	18.49		0.0
	1	187	18.44	18.44		0.0
	90	0	18.60	18.64	0-1	0.0
	90	50	18.63	18.64	0	0.0
	90	99	18.56	18.52	0-1	0.0
	180	0	18.65	18.59		0.0
DFT-s-OFDM 16QAM	1	1	18.44	18.54	0-1	0.0
CP-OFDM QPSK	1	1	18.70	18.54	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 329 of 426

Table H-653
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.32	0	0.0
	1	81	18.21		0.0
	1	160	18.15		0.0
	81	0	18.35	0-1	0.0
	81	41	18.11	0	0.0
	81	81	18.24	0-1	0.0
	162	0	18.28		0.0
DFT-s-OFDM 16QAM	1	1	18.44	0-1	0.0
CP-OFDM QPSK	1	1	18.48	0-1.5	0.0

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.61	18.58	0	0.0
	1	81	18.63	18.60		0.0
	1	160	18.51	18.39		0.0
	81	0	18.69	18.70	0-1	0.0
	81	41	18.60	18.57	0	0.0
	81	81	18.63	18.56	0-1	0.0
	162	0	18.57	18.61		0.0
DFT-s-OFDM 16QAM	1	1	18.65	18.57	0-1	0.0
CP-OFDM QPSK	1	1	18.37	18.48	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 330 of 426

Table H-654
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.33	0	0.0
	1	67	18.26		0.0
	1	131	18.25		0.0
	64	0	18.36	0-1	0.0
	64	35	18.34	0	0.0
	64	69	18.29	0-1	0.0
	128	0	18.32		0.0
DFT-s-OFDM 16QAM	1	1	18.45	0-1	0.0
CP-OFDM QPSK	1	1	18.41	0-1.5	0.0

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.64	18.70	0	0.0
	1	67	18.70	18.54		0.0
	1	131	18.59	18.44		0.0
	64	0	18.74	18.70	0-1	0.0
	64	35	18.55	18.58	0	0.0
	64	69	18.56	18.48	0-1	0.0
	128	0	18.67	18.64		0.0
DFT-s-OFDM 16QAM	1	1	18.32	18.68	0-1	0.0
CP-OFDM QPSK	1	1	18.67	18.61	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 331 of 426

Table H-655
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.21	0	0.0
	1	53	18.17		0.0
	1	104	18.14		0.0
	50	0	18.39	0-1	0.0
	50	28	18.28	0	0.0
	50	56	18.27	0-1	0.0
	100	0	18.30		0.0
DFT-s-OFDM 16QAM	1	1	18.41	0-1	0.0
CP-OFDM QPSK	1	1	18.35	0-1.5	0.0

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.67	18.64	0	0.0
	1	53	18.69	18.61		0.0
	1	104	18.58	18.51		0.0
	50	0	18.65	18.74	0-1	0.0
	50	28	18.48	18.42	0	0.0
	50	56	18.41	18.33	0-1	0.0
	100	0	18.72	18.69		0.0
DFT-s-OFDM 16QAM	1	1	18.55	18.45	0-1	0.0
CP-OFDM QPSK	1	1	18.51	18.56	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 332 of 426

Table H-656
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.33	0	0.0
	1	39	18.15		0.0
	1	76	18.26		0.0
	36	0	18.33	0-1	0.0
	36	21	18.18	0	0.0
	36	42	18.34	0-1	0.0
	75	0	18.25		0.0
DFT-s-OFDM 16QAM	1	1	18.27	0-1	0.0
CP-OFDM QPSK	1	1	18.47	0-1.5	0.0

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.56	18.60	0	0.0
	1	39	18.47	18.39		0.0
	1	76	18.56	18.41		0.0
	36	0	18.50	18.53	0-1	0.0
	36	21	18.47	18.46	0	0.0
	36	42	18.48	18.48	0-1	0.0
	75	0	18.52	18.48		0.0
DFT-s-OFDM 16QAM	1	1	18.54	18.52	0-1	0.0
CP-OFDM QPSK	1	1	18.38	18.57	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 333 of 426

Table H-657
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.28	0	0.0
	1	33	18.05		0.0
	1	63	18.25		0.0
	32	0	18.24	0-1	0.0
	32	17	18.14	0	0.0
	32	33	18.22	0-1	0.0
	64	0	18.19		0.0
DFT-s-OFDM 16QAM	1	1	18.26	0-1	0.0
CP-OFDM QPSK	1	1	18.42	0-1.5	0.0

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.98	18.62	0	0.0
	1	33	18.11	18.43		0.0
	1	63	18.12	18.45		0.0
	32	0	18.14	18.49	0-1	0.0
	32	17	17.96	18.39	0	0.0
	32	33	18.02	18.42	0-1	0.0
	64	0	18.05	18.39		0.0
DFT-s-OFDM 16QAM	1	1	18.03	18.37	0-1	0.0
CP-OFDM QPSK	1	1	18.02	18.25	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 334 of 426

Table H-658
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.27	0	0.0
	1	26	18.22		0.0
	1	49	18.24		0.0
	25	0	18.26	0-1	0.0
	25	13	18.19	0	0.0
	25	26	18.23	0-1	0.0
	50	0	18.28		0.0
DFT-s-OFDM 16QAM	1	1	18.18	0-1	0.0
CP-OFDM QPSK	1	1	18.33	0-1.5	0.0

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.59	18.78	0	0.0
	1	26	18.70	18.56		0.0
	1	49	18.65	18.62		0.0
	25	0	18.67	18.70	0-1	0.0
	25	13	18.62	18.64	0	0.0
	25	26	18.60	18.65	0-1	0.0
	50	0	18.71	18.59		0.0
DFT-s-OFDM 16QAM	1	1	18.43	18.63	0-1	0.0
CP-OFDM QPSK	1	1	18.61	18.63	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 335 of 426

Table H-659
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.32	0	0.0
	1	19	18.27		0.0
	1	36	18.24		0.0
	18	0	18.33	0-1	0.0
	18	10	18.36	0	0.0
	18	20	18.33	0-1	0.0
	36	0	18.27		0.0
DFT-s-OFDM 16QAM	1	1	18.21	0-1	0.0
CP-OFDM QPSK	1	1	18.40	0-1.5	0.0

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.29	18.48	0	0.0
	1	19	18.40	18.26		0.0
	1	36	18.35	18.32		0.0
	18	0	18.37	18.40	0-1	0.0
	18	10	18.32	18.34	0	0.0
	18	20	18.47	18.35	0-1	0.0
	36	0	18.41	18.29		0.0
DFT-s-OFDM 16QAM	1	1	18.13	18.33	0-1	0.0
CP-OFDM QPSK	1	1	18.31	18.33	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 336 of 426

Table H-660
NR Band n77 Antenna F Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	18.12	0	0.0
	1	12	18.18		0.0
	1	22	18.26		0.0
	12	0	18.22	0-1	0.0
	12	6	18.15	0	0.0
	12	12	18.20	0-1	0.0
	24	0	18.14		0.0
DFT-s-OFDM 16QAM	1	1	18.22	0-1	0.0
CP-OFDM QPSK	1	1	18.19	0-1.5	0.0

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	18.65	18.47	0	0.0
	1	12	18.48	18.43		0.0
	1	22	18.42	18.31		0.0
	12	0	18.41	18.46	0-1	0.0
	12	6	18.30	18.40	0	0.0
	12	12	18.44	18.37	0-1	0.0
	24	0	18.32	18.42		0.0
DFT-s-OFDM 16QAM	1	1	18.37	18.29	0-1	0.0
CP-OFDM QPSK	1	1	18.37	18.43	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 337 of 426

Table H-661

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.49	0	0.0
	1	123	9.39		0.0
	1	243	9.22		0.0
	120	0	9.36	0-1	0.0
	120	63	9.23	0	0.0
	120	125	9.17	0-1	0.0
	243	0	9.21		0.0
DFT-s-OFDM 16QAM	1	1	9.55	0-1	0.0
CP-OFDM QPSK	1	1	9.65	0-1.5	0.0

Table H-662

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.45	0	0.0
	1	109	9.32		0.0
	1	215	9.37		0.0
	108	0	9.39	0-1	0.0
	108	55	9.31	0	0.0
	108	109	9.14	0-1	0.0
	216	0	9.25		0.0
DFT-s-OFDM 16QAM	1	1	9.42	0-1	0.0
CP-OFDM QPSK	1	1	9.55	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 338 of 426

Table H-663

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.55	0	0.0
	1	95	9.24		0.0
	1	187	9.11		0.0
	90	0	9.30	0-1	0.0
	90	50	9.34	0	0.0
	90	99	9.27	0-1	0.0
	180	0	9.28		0.0
DFT-s-OFDM 16QAM	1	1	9.47	0-1	0.0
CP-OFDM QPSK	1	1	9.38	0-1.5	0.0

Table H-664

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.32	0	0.0
	1	81	9.23		0.0
	1	160	9.06		0.0
	81	0	9.18	0-1	0.0
	81	41	9.13	0	0.0
	81	81	9.07	0-1	0.0
	162	0	9.16		0.0
DFT-s-OFDM 16QAM	1	1	9.40	0-1	0.0
CP-OFDM QPSK	1	1	9.23	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 339 of 426

Table H-665

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.42	0	0.0
	1	67	9.40		0.0
	1	131	9.47		0.0
	64	0	9.42	0-1	0.0
	64	35	9.40	0	0.0
	64	69	9.43	0-1	0.0
	128	0	9.39		0.0
DFT-s-OFDM 16QAM	1	1	9.41	0-1	0.0
CP-OFDM QPSK	1	1	9.53	0-1.5	0.0

Table H-666

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.42	0	0.0
	1	53	9.23		0.0
	1	104	9.16		0.0
	50	0	9.36	0-1	0.0
	50	28	9.37	0	0.0
	50	56	9.30	0-1	0.0
	100	0	9.37		0.0
DFT-s-OFDM 16QAM	1	1	9.27	0-1	0.0
CP-OFDM QPSK	1	1	9.27	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 340 of 426

Table H-667

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.57	0	0.0
	1	39	9.32		0.0
	1	76	9.35		0.0
	36	0	9.47	0-1	0.0
	36	21	9.45	0	0.0
	36	42	9.42	0-1	0.0
	75	0	9.40		0.0
DFT-s-OFDM 16QAM	1	1	9.41	0-1	0.0
CP-OFDM QPSK	1	1	9.57	0-1.5	0.0

Table H-668

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.31	0	0.0
	1	33	9.26		0.0
	1	63	9.23		0.0
	32	0	9.20	0-1	0.0
	32	17	9.19	0	0.0
	32	33	9.16	0-1	0.0
	64	0	9.11		0.0
DFT-s-OFDM 16QAM	1	1	9.07	0-1	0.0
CP-OFDM QPSK	1	1	9.40	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 341 of 426

Table H-669

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.11	0	0.0
	1	26	9.18		0.0
	1	49	9.13		0.0
	25	0	9.18	0-1	0.0
	25	13	9.15	0	0.0
	25	26	9.11	0-1	0.0
	50	0	9.17		0.0
DFT-s-OFDM 16QAM	1	1	9.40	0-1	0.0
CP-OFDM QPSK	1	1	9.29	0-1.5	0.0

Table H-670

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz) Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.38	0	0.0
	1	19	9.18		0.0
	1	36	9.28		0.0
	18	0	9.22	0-1	0.0
	18	10	9.30	0	0.0
	18	20	9.33	0-1	0.0
	36	0	9.28		0.0
DFT-s-OFDM 16QAM	1	1	9.35	0-1	0.0
CP-OFDM QPSK	1	1	9.58	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 342 of 426

Table H-671

NR Band n77 Antenna F Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	9.05	0	0.0
	1	12	9.01		0.0
	1	22	9.14		0.0
	12	0	9.21	0-1	0.0
	12	6	9.09	0	0.0
	12	12	9.04	0-1	0.0
	24	0	9.02		0.0
DFT-s-OFDM 16QAM	1	1	9.52	0-1	0.0
CP-OFDM QPSK	1	1	9.18	0-1.5	0.0

Table H-672

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 90 MHz Bandwidth**

NR Band n77 DoD 90 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	18.17	
SRS #3 Ant G	14.32	
SRS #4 Ant A	14.58	

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.68	18.22
SRS #3 Ant G	13.65	14.62
SRS #4 Ant A	13.59	13.05

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 344 of 426

Table H-673

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 80 MHz Bandwidth**

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	18.17
SRS #3 Ant G	14.30
SRS #4 Ant A	14.50

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.73	18.18
SRS #3 Ant G	13.66	14.57
SRS #4 Ant A	13.60	12.99

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 345 of 426

Table H-674

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 70 MHz Bandwidth**

NR Band n77 DoD 70 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	18.17	
SRS #3 Ant G	14.28	
SRS #4 Ant A	14.45	

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.67	18.19
SRS #3 Ant G	13.63	14.54
SRS #4 Ant A	13.59	12.96

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 346 of 426

Table H-675

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 60 MHz Bandwidth**

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	18.16
SRS #3 Ant G	14.14
SRS #4 Ant A	14.45

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.71	18.05
SRS #3 Ant G	13.49	14.40
SRS #4 Ant A	13.48	12.80

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 347 of 426

Table H-676

NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	18.32	
SRS #3 Ant G	14.36	
SRS #4 Ant A	14.61	

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.71	18.36
SRS #3 Ant G	13.74	14.61
SRS #4 Ant A	13.77	13.02

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 348 of 426

Table H-677

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 40 MHz Bandwidth**

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	18.28
SRS #3 Ant G	14.26
SRS #4 Ant A	14.47

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.78	18.25
SRS #3 Ant G	13.57	14.48
SRS #4 Ant A	13.58	12.88

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 349 of 426

Table H-678

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth**

NR Band n77 DoD 30 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	18.29	
SRS #3 Ant G	14.27	
SRS #4 Ant A	14.49	

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.76	18.28
SRS #3 Ant G	13.54	14.46
SRS #4 Ant A	13.55	12.88

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 350 of 426

Table H-679

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 25 MHz Bandwidth**

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	18.30
SRS #3 Ant G	14.24
SRS #4 Ant A	14.49

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.71	18.27
SRS #3 Ant G	13.62	14.44
SRS #4 Ant A	13.64	12.83

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 351 of 426

Table H-680

NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	18.02
SRS #3 Ant G	14.21
SRS #4 Ant A	14.38

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.23	17.88
SRS #3 Ant G	13.56	14.37
SRS #4 Ant A	13.56	12.76

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 352 of 426

Table H-681

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth**

NR Band n77 DoD 15 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	18.20	
SRS #3 Ant G	14.21	
SRS #4 Ant A	14.38	

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.74	18.26
SRS #3 Ant G	13.51	14.38
SRS #4 Ant A	13.53	12.76

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 353 of 426

Table H-682

**NR Band n77 Antenna C, A & G Path 1 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth**

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	18.22
SRS #3 Ant G	14.33
SRS #4 Ant A	14.39

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	17.86	18.29
SRS #3 Ant G	13.63	14.40
SRS #4 Ant A	13.65	12.78

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 354 of 426

Table H-683

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.53
SRS #3 Ant G	7.40
SRS #4 Ant A	7.65

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.94	10.58
SRS #3 Ant G	6.42	7.33
SRS #4 Ant A	6.76	6.13

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 355 of 426

Table H-684

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.64
SRS #3 Ant G	7.39
SRS #4 Ant A	7.64

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.00	10.70
SRS #3 Ant G	6.44	7.31
SRS #4 Ant A	6.81	6.10

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 356 of 426

Table H-685

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	10.64	
SRS #3 Ant G	7.39	
SRS #4 Ant A	7.67	

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	9.99	10.77
SRS #3 Ant G	6.45	7.34
SRS #4 Ant A	6.81	6.11

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 357 of 426

Table H-686

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.47
SRS #3 Ant G	7.31
SRS #4 Ant A	7.55

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.00	10.61
SRS #3 Ant G	6.44	7.19
SRS #4 Ant A	6.71	6.04

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 358 of 426

Table H-687

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.73
SRS #3 Ant G	7.55
SRS #4 Ant A	7.75

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.27	10.87
SRS #3 Ant G	6.65	7.36
SRS #4 Ant A	7.01	6.27

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 359 of 426

Table H-688

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.63
SRS #3 Ant G	7.40
SRS #4 Ant A	7.68

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.11	10.75
SRS #3 Ant G	6.48	7.24
SRS #4 Ant A	6.86	6.18

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 360 of 426

Table H-689

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant C	10.61	
SRS #3 Ant G	7.41	
SRS #4 Ant A	7.71	

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.10	10.77
SRS #3 Ant G	6.47	7.25
SRS #4 Ant A	6.84	6.20

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 361 of 426

Table H-690

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.60
SRS #3 Ant G	7.38
SRS #4 Ant A	7.71

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.16	10.72
SRS #3 Ant G	6.50	7.19
SRS #4 Ant A	6.95	6.19

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 362 of 426

Table H-691

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.48
SRS #3 Ant G	7.27
SRS #4 Ant A	7.63

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.06	10.65
SRS #3 Ant G	6.47	7.11
SRS #4 Ant A	6.96	6.14

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 363 of 426

Table H-692

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.48
SRS #3 Ant G	7.26
SRS #4 Ant A	7.59

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.02	10.64
SRS #3 Ant G	6.41	7.11
SRS #4 Ant A	6.93	6.16

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 364 of 426

Table H-693

NR Band n77 Antenna A, C, G Path 1 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant C	10.52
SRS #3 Ant G	7.26
SRS #4 Ant A	7.74

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant C	10.09	10.63
SRS #3 Ant G	6.51	7.21
SRS #4 Ant A	6.99	6.16

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 365 of 426

H.2.5 NR Band n77 Path 2

Table H-694

NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.47	0	0.0
	1	123	23.23		0.0
	1	243	23.19		0.0
	120	0	23.38	0-1	0.0
	120	63	23.27	0	0.0
	120	125	23.21	0-1	0.0
	243	0	23.33		0.0
DFT-s-OFDM 16QAM	1	1	23.44	0-1	0.0
CP-OFDM QPSK	1	1	23.45	0-1.5	0.0

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.42	23.18	0	0.0
	1	123	23.11	23.06		0.0
	1	243	23.19	23.05		0.0
	120	0	23.24	23.03	0-1	0.0
	120	63	22.99	23.04	0	0.0
	120	125	23.03	23.04	0-1	0.0
	243	0	23.09	23.11		0.0
DFT-s-OFDM 16QAM	1	1	23.46	23.13	0-1	0.0
CP-OFDM QPSK	1	1	23.45	22.73	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 366 of 426

Table H-695
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.49	0	0.0
	1	109	23.21		0.0
	1	215	23.31		0.0
	108	0	23.41	0-1	0.0
	108	55	23.35	0	0.0
	108	109	23.31	0-1	0.0
	216	0	23.34		0.0
DFT-s-OFDM 16QAM	1	1	23.34	0-1	0.0
CP-OFDM QPSK	1	1	23.46	0-1.5	0.0

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.39	23.14	0	0.0
	1	109	22.98	22.98		0.0
	1	215	23.24	23.03		0.0
	108	0	23.25	23.07	0-1	0.0
	108	55	23.07	23.08	0	0.0
	108	109	23.07	23.05	0-1	0.0
	216	0	23.12	23.06		0.0
DFT-s-OFDM 16QAM	1	1	23.28	23.01	0-1	0.0
CP-OFDM QPSK	1	1	23.41	22.56	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 367 of 426

Table H-696
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.44	0	0.0
	1	95	23.17		0.0
	1	187	23.31		0.0
	90	0	23.41	0-1	0.0
	90	50	23.29	0	0.0
	90	99	23.26	0-1	0.0
	180	0	23.40		0.0
DFT-s-OFDM 16QAM	1	1	23.35	0-1	0.0
CP-OFDM QPSK	1	1	23.51	0-1.5	0.0

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.47	23.14	0	0.0
	1	95	23.10	22.94		0.0
	1	187	23.25	23.02		0.0
	90	0	23.25	23.03	0-1	0.0
	90	50	23.10	23.08	0	0.0
	90	99	23.22	23.09	0-1	0.0
	180	0	23.26	23.12		0.0
DFT-s-OFDM 16QAM	1	1	23.90	22.97	0-1	0.0
CP-OFDM QPSK	1	1	23.98	22.52	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 368 of 426

Table H-697

NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.31	0	0.0
	1	81	23.20		0.0
	1	160	23.21		0.0
	81	0	23.26	0-1	0.0
	81	41	23.05	0	0.0
	81	81	23.18	0-1	0.0
	162	0	23.21		0.0
DFT-s-OFDM 16QAM	1	1	23.27	0-1	0.0
CP-OFDM QPSK	1	1	23.35	0-1.5	0.0

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.67	23.17	0	0.0
	1	81	23.33	23.20		0.0
	1	160	23.36	23.25		0.0
	81	0	23.51	23.36	0-1	0.0
	81	41	23.28	23.28	0	0.0
	81	81	23.38	23.31	0-1	0.0
	162	0	23.46	23.34		0.0
DFT-s-OFDM 16QAM	1	1	23.66	23.16	0-1	0.0
CP-OFDM QPSK	1	1	23.76	22.88	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 369 of 426

Table H-698
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.46	0	0.0
	1	67	23.42		0.0
	1	131	23.46		0.0
	64	0	23.54	0-1	0.0
	64	35	23.54	0	0.0
	64	69	23.42	0-1	0.0
	128	0	23.50		0.0
DFT-s-OFDM 16QAM	1	1	23.46	0-1	0.0
CP-OFDM QPSK	1	1	23.49	0-1.5	0.0

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.72	23.45	0	0.0
	1	67	23.56	23.65		0.0
	1	131	23.58	23.48		0.0
	64	0	23.72	23.57	0-1	0.0
	64	35	23.66	23.61	0	0.0
	64	69	23.66	23.61	0-1	0.0
	128	0	23.68	23.60		0.0
DFT-s-OFDM 16QAM	1	1	23.61	23.49	0-1	0.0
CP-OFDM QPSK	1	1	23.88	22.98	0-1.5	0.0

Table H-699
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.40	0	0.0
	1	53	23.41		0.0
	1	104	23.27		0.0
	50	0	23.37	0-1	0.0
	50	28	23.33	0	0.0
	50	56	23.35	0-1	0.0
	100	0	23.34		0.0
DFT-s-OFDM 16QAM	1	1	23.35	0-1	0.0
CP-OFDM QPSK	1	1	23.32	0-1.5	0.0

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.59	23.29	0	0.0
	1	53	23.49	23.39		0.0
	1	104	23.48	23.31		0.0
	50	0	23.58	23.43	0-1	0.0
	50	28	23.49	23.39	0	0.0
	50	56	23.43	23.40	0-1	0.0
	100	0	23.51	23.46		0.0
DFT-s-OFDM 16QAM	1	1	23.51	23.21	0-1	0.0
CP-OFDM QPSK	1	1	23.71	23.08	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 371 of 426

Table H-700
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.43	0	0.0
	1	39	23.38		0.0
	1	76	23.26		0.0
	36	0	23.39	0-1	0.0
	36	21	23.27	0	0.0
	36	42	23.36	0-1	0.0
	75	0	23.34		0.0
DFT-s-OFDM 16QAM	1	1	23.40	0-1	0.0
CP-OFDM QPSK	1	1	23.47	0-1.5	0.0

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.51	23.47	0	0.0
	1	39	23.42	23.24		0.0
	1	76	23.42	23.37		0.0
	36	0	23.42	23.33	0-1	0.0
	36	21	23.28	23.27	0	0.0
	36	42	23.38	23.36	0-1	0.0
	75	0	23.42	23.36		0.0
DFT-s-OFDM 16QAM	1	1	23.51	23.27	0-1	0.0
CP-OFDM QPSK	1	1	23.46	23.01	0-1.5	0.0

Table H-701
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.39	0	0.0
	1	33	23.46		0.0
	1	63	23.33		0.0
	32	0	23.41	0-1	0.0
	32	17	23.31	0	0.0
	32	33	23.38	0-1	0.0
	64	0	23.37		0.0
DFT-s-OFDM 16QAM	1	1	23.43	0-1	0.0
CP-OFDM QPSK	1	1	23.42	0-1.5	0.0

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.42	23.49	0	0.0
	1	33	23.50	23.36		0.0
	1	63	23.43	23.30		0.0
	32	0	23.40	23.32	0-1	0.0
	32	17	23.35	23.28	0	0.0
	32	33	23.45	23.43	0-1	0.0
	64	0	23.49	23.41		0.0
DFT-s-OFDM 16QAM	1	1	23.90	22.82	0-1	0.0
CP-OFDM OPSK	1	1	23.58	22.67	0-1.5	0.0

Table H-702
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.20	0	0.0
	1	26	23.30		0.0
	1	49	23.23		0.0
	25	0	23.32	0-1	0.0
	25	13	23.37	0	0.0
	25	26	23.23	0-1	0.0
	50	0	23.25		0.0
DFT-s-OFDM 16QAM	1	1	23.38	0-1	0.0
CP-OFDM QPSK	1	1	23.36	0-1.5	0.0

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.55	23.19	0	0.0
	1	26	23.25	23.21		0.0
	1	49	23.38	23.47		0.0
	25	0	23.31	23.31	0-1	0.0
	25	13	23.34	23.28	0	0.0
	25	26	23.32	23.26	0-1	0.0
	50	0	23.38	23.25		0.0
DFT-s-OFDM 16QAM	1	1	23.19	22.86	0-1	0.0
CP-OFDM QPSK	1	1	23.39	22.53	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 374 of 426

Table H-703
NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.28	0	0.0
	1	19	23.29		0.0
	1	36	23.14		0.0
	18	0	23.32	0-1	0.0
	18	10	23.30	0	0.0
	18	20	23.28	0-1	0.0
	36	0	23.19		0.0
DFT-s-OFDM 16QAM	1	1	23.28	0-1	0.0
CP-OFDM QPSK	1	1	23.36	0-1.5	0.0

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.40	23.27	0	0.0
	1	19	23.37	23.10		0.0
	1	36	23.36	23.34		0.0
	18	0	23.47	23.26	0-1	0.0
	18	10	23.28	23.33	0	0.0
	18	20	23.39	23.31	0-1	0.0
	36	0	23.32	23.21		0.0
DFT-s-OFDM 16QAM	1	1	23.33	23.37	0-1	0.0
CP-OFDM QPSK	1	1	23.44	23.08	0-1.5	0.0

Table H-704

NR Band n77 Antenna C Path 2 Measured P_{Max} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	23.32	0	0.0
	1	12	23.29		0.0
	1	22	23.43		0.0
	12	0	23.35	0-1	0.0
	12	6	23.31	0	0.0
	12	12	23.45	0-1	0.0
	24	0	23.37		0.0
DFT-s-OFDM 16QAM	1	1	23.25	0-1	0.0
CP-OFDM QPSK	1	1	23.43	0-1.5	0.0

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	23.41	23.34	0	0.0
	1	12	23.63	23.38		0.0
	1	22	23.60	23.37		0.0
	12	0	23.45	23.35	0-1	0.0
	12	6	23.38	23.39	0	0.0
	12	12	23.45	23.45	0-1	0.0
	24	0	23.39	23.32		0.0
DFT-s-OFDM 16QAM	1	1	23.71	23.30	0-1	0.0
CP-OFDM QPSK	1	1	23.36	23.09	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 376 of 426

Table H-705
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.18	0	0.0
	1	123	16.91		0.0
	1	243	16.93		0.0
	120	0	17.02	0-1	0.0
	120	63	16.95	0	0.0
	120	125	16.87	0-1	0.0
	243	0	16.99		0.0
DFT-s-OFDM 16QAM	1	1	17.19	0-1	0.0
CP-OFDM QPSK	1	1	17.13	0-1.5	0.0

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.26	16.76	0	0.0
	1	123	16.88	16.71		0.0
	1	243	16.91	16.86		0.0
	120	0	17.24	16.73	0-1	0.0
	120	63	16.84	16.75	0	0.0
	120	125	16.92	16.78	0-1	0.0
	243	0	17.08	16.74		0.0
DFT-s-OFDM 16QAM	1	1	17.15	16.73	0-1	0.0
CP-OFDM QPSK	1	1	17.41	16.97	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 377 of 426

Table H-706
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.11	0	0.0
	1	109	16.95		0.0
	1	215	16.98		0.0
	108	0	17.04	0-1	0.0
	108	55	16.96	0	0.0
	108	109	16.94	0-1	0.0
	216	0	16.99		0.0
DFT-s-OFDM 16QAM	1	1	17.29	0-1	0.0
CP-OFDM QPSK	1	1	17.19	0-1.5	0.0

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.40	16.78	0	0.0
	1	109	16.93	16.76		0.0
	1	215	16.98	16.85		0.0
	108	0	17.12	16.72	0-1	0.0
	108	55	16.90	16.78	0	0.0
	108	109	16.91	16.78	0-1	0.0
	216	0	17.05	16.72		0.0
DFT-s-OFDM 16QAM	1	1	17.28	16.64	0-1	0.0
CP-OFDM QPSK	1	1	17.24	16.71	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 378 of 426

Table H-707
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.14	0	0.0
	1	95	16.92		0.0
	1	187	16.87		0.0
	90	0	17.06	0-1	0.0
	90	50	16.99	0	0.0
	90	99	16.93	0-1	0.0
	180	0	16.97		0.0
DFT-s-OFDM 16QAM	1	1	17.24	0-1	0.0
CP-OFDM QPSK	1	1	17.07	0-1.5	0.0

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.18	16.61	0	0.0
	1	95	16.90	16.69		0.0
	1	187	16.93	16.71		0.0
	90	0	17.12	16.77	0-1	0.0
	90	50	16.92	16.79	0	0.0
	90	99	16.91	16.76	0-1	0.0
	180	0	17.06	16.74		0.0
DFT-s-OFDM 16QAM	1	1	17.30	16.81	0-1	0.0
CP-OFDM QPSK	1	1	17.16	16.75	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 379 of 426

Table H-708
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	16.99	0	0.0
	1	81	16.95		0.0
	1	160	16.86		0.0
	81	0	16.90	0-1	0.0
	81	41	16.81	0	0.0
	81	81	16.78	0-1	0.0
	162	0	16.83		0.0
DFT-s-OFDM 16QAM	1	1	17.03	0-1	0.0
CP-OFDM QPSK	1	1	17.07	0-1.5	0.0

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.11	16.66	0	0.0
	1	81	16.93	16.76		0.0
	1	160	16.82	16.82		0.0
	81	0	17.12	16.81	0-1	0.0
	81	41	17.01	16.80	0	0.0
	81	81	16.91	16.73	0-1	0.0
	162	0	17.06	16.74		0.0
DFT-s-OFDM 16QAM	1	1	17.23	16.66	0-1	0.0
CP-OFDM QPSK	1	1	17.12	17.02	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 380 of 426

Table H-709
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.25	0	0.0
	1	67	17.28		0.0
	1	131	17.08		0.0
	64	0	17.17	0-1	0.0
	64	35	17.09	0	0.0
	64	69	17.12	0-1	0.0
	128	0	17.07		0.0
DFT-s-OFDM 16QAM	1	1	17.21	0-1	0.0
CP-OFDM QPSK	1	1	17.20	0-1.5	0.0

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.14	16.62	0	0.0
	1	67	16.78	16.67		0.0
	1	131	16.81	16.60		0.0
	64	0	16.91	16.61	0-1	0.0
	64	35	16.65	16.61	0	0.0
	64	69	16.81	16.68	0-1	0.0
	128	0	16.84	16.60		0.0
DFT-s-OFDM 16QAM	1	1	16.95	16.71	0-1	0.0
CP-OFDM QPSK	1	1	17.05	16.77	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 381 of 426

Table H-710
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.17	0	0.0
	1	53	17.08		0.0
	1	104	16.92		0.0
	50	0	17.12	0-1	0.0
	50	28	17.10	0	0.0
	50	56	17.05	0-1	0.0
	100	0	17.03		0.0
DFT-s-OFDM 16QAM	1	1	17.07	0-1	0.0
CP-OFDM QPSK	1	1	17.14	0-1.5	0.0

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.13	16.63	0	0.0
	1	53	16.94	16.74		0.0
	1	104	16.83	16.71		0.0
	50	0	16.97	16.79	0-1	0.0
	50	28	16.93	16.80	0	0.0
	50	56	16.94	16.83	0-1	0.0
	100	0	16.95	16.76		0.0
DFT-s-OFDM 16QAM	1	1	17.04	16.70	0-1	0.0
CP-OFDM QPSK	1	1	16.89	16.80	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 382 of 426

Table H-711
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.11	0	0.0
	1	39	16.97		0.0
	1	76	17.04		0.0
	36	0	17.00	0-1	0.0
	36	21	16.94	0	0.0
	36	42	16.98	0-1	0.0
	75	0	16.98		0.0
DFT-s-OFDM 16QAM	1	1	17.06	0-1	0.0
CP-OFDM QPSK	1	1	17.03	0-1.5	0.0

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	16.97	16.88	0	0.0
	1	39	16.89	16.86		0.0
	1	76	16.84	16.74		0.0
	36	0	16.97	16.83	0-1	0.0
	36	21	16.91	16.76	0	0.0
	36	42	16.94	16.81	0-1	0.0
	75	0	16.91	16.88		0.0
DFT-s-OFDM 16QAM	1	1	16.89	16.93	0-1	0.0
CP-OFDM QPSK	1	1	16.99	16.84	0-1.5	0.0

Table H-712
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.10	0	0.0
	1	33	17.04		0.0
	1	63	17.14		0.0
	32	0	17.13	0-1	0.0
	32	17	16.97	0	0.0
	32	33	17.08	0-1	0.0
	64	0	17.03		0.0
DFT-s-OFDM 16QAM	1	1	17.24	0-1	0.0
CP-OFDM QPSK	1	1	17.16	0-1.5	0.0

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.00	16.90	0	0.0
	1	33	16.88	16.80		0.0
	1	63	16.89	16.85		0.0
	32	0	17.06	16.84	0-1	0.0
	32	17	16.91	16.78	0	0.0
	32	33	16.96	16.87	0-1	0.0
	64	0	17.00	16.91		0.0
DFT-s-OFDM 16QAM	1	1	16.88	16.70	0-1	0.0
CP-OFDM QPSK	1	1	16.94	16.77	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 384 of 426

Table H-713
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.41	0	0.0
	1	26	17.36		0.0
	1	49	17.22		0.0
	25	0	17.21	0-1	0.0
	25	13	17.33	0	0.0
	25	26	17.15	0-1	0.0
	50	0	17.27		0.0
DFT-s-OFDM 16QAM	1	1	17.47	0-1	0.0
CP-OFDM QPSK	1	1	17.35	0-1.5	0.0

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.23	16.89	0	0.0
	1	26	17.28	17.06		0.0
	1	49	17.26	16.88		0.0
	25	0	17.34	17.01	0-1	0.0
	25	13	17.20	17.03	0	0.0
	25	26	17.30	17.01	0-1	0.0
	50	0	17.25	17.08		0.0
DFT-s-OFDM 16QAM	1	1	17.13	16.96	0-1	0.0
CP-OFDM QPSK	1	1	17.20	16.94	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 385 of 426

Table H-714
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.40	0	0.0
	1	19	17.37		0.0
	1	36	17.57		0.0
	18	0	16.78	0-1	0.0
	18	10	16.76	0	0.0
	18	20	16.80	0-1	0.0
	36	0	16.70		0.0
DFT-s-OFDM 16QAM	1	1	17.28	0-1	0.0
CP-OFDM QPSK	1	1	17.07	0-1.5	0.0

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.24	17.02	0	0.0
	1	19	17.30	17.00		0.0
	1	36	17.30	16.98		0.0
	18	0	17.36	17.06	0-1	0.0
	18	10	17.25	17.11	0	0.0
	18	20	17.27	17.06	0-1	0.0
	36	0	17.23	16.95		0.0
DFT-s-OFDM 16QAM	1	1	17.27	16.83	0-1	0.0
CP-OFDM QPSK	1	1	17.44	17.01	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 386 of 426

Table H-715
NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	17.45	0	0.0
	1	12	17.28		0.0
	1	22	17.41		0.0
	12	0	17.41	0-1	0.0
	12	6	17.30	0	0.0
	12	12	17.29	0-1	0.0
	24	0	17.60		0.0
DFT-s-OFDM 16QAM	1	1	17.83	0-1	0.0
CP-OFDM QPSK	1	1	17.47	0-1.5	0.0

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	17.37	17.07	0	0.0
	1	12	17.14	17.48		0.0
	1	22	17.34	17.29		0.0
	12	0	17.42	16.56	0-1	0.0
	12	6	17.27	16.62	0	0.0
	12	12	17.34	16.57	0-1	0.0
	24	0	17.28	16.63		0.0
DFT-s-OFDM 16QAM	1	1	17.35	17.08	0-1	0.0
CP-OFDM QPSK	1	1	17.23	16.88	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 387 of 426

Table H-716

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.45	0	0.0
	1	123	10.33		0.0
	1	243	10.16		0.0
	120	0	10.30	0-1	0.0
	120	63	10.31	0	0.0
	120	125	10.20	0-1	0.0
	243	0	10.23		0.0
DFT-s-OFDM 16QAM	1	1	10.44	0-1	0.0
CP-OFDM QPSK	1	1	10.33	0-1.5	0.0

NR Band n77 90 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.71	10.32	0	0.0
	1	123	10.40	10.46		0.0
	1	243	10.41	10.29		0.0
	120	0	10.58	10.30	0-1	0.0
	120	63	10.39	10.39	0	0.0
	120	125	10.35	10.31	0-1	0.0
	243	0	10.46	10.29		0.0
DFT-s-OFDM 16QAM	1	1	10.87	10.32	0-1	0.0
CP-OFDM QPSK	1	1	10.69	10.46	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 388 of 426

Table H-717

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.39	0	0.0
	1	109	10.23		0.0
	1	215	10.20		0.0
	108	0	10.42	0-1	0.0
	108	55	10.29	0	0.0
	108	109	10.14	0-1	0.0
	216	0	10.31		0.0
DFT-s-OFDM 16QAM	1	1	10.50	0-1	0.0
CP-OFDM QPSK	1	1	10.43	0-1.5	0.0

NR Band n77 80 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.70	10.30	0	0.0
	1	109	10.39	10.38		0.0
	1	215	10.49	10.29		0.0
	108	0	10.49	10.32	0-1	0.0
	108	55	10.43	10.37	0	0.0
	108	109	10.40	10.32	0-1	0.0
	216	0	10.49	10.31		0.0
DFT-s-OFDM 16QAM	1	1	10.58	10.37	0-1	0.0
CP-OFDM QPSK	1	1	10.53	10.39	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 389 of 426

Table H-718

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.42	0	0.0
	1	95	10.17		0.0
	1	187	10.24		0.0
	90	0	10.34	0-1	0.0
	90	50	10.35	0	0.0
	90	99	10.20	0-1	0.0
	180	0	10.29		0.0
DFT-s-OFDM 16QAM	1	1	10.39	0-1	0.0
CP-OFDM QPSK	1	1	10.51	0-1.5	0.0

NR Band n77 70 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.62	10.28	0	0.0
	1	95	10.40	10.32		0.0
	1	187	10.42	10.32		0.0
	90	0	10.50	10.30	0-1	0.0
	90	50	10.40	10.39	0	0.0
	90	99	10.37	10.27	0-1	0.0
	180	0	10.45	10.33		0.0
DFT-s-OFDM 16QAM	1	1	10.62	10.34	0-1	0.0
CP-OFDM QPSK	1	1	10.44	10.07	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 390 of 426

Table H-719

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.34	0	0.0
	1	81	10.12		0.0
	1	160	10.19		0.0
	81	0	10.22	0-1	0.0
	81	41	10.11	0	0.0
	81	81	10.11	0-1	0.0
	162	0	10.14		0.0
DFT-s-OFDM 16QAM	1	1	10.31	0-1	0.0
CP-OFDM QPSK	1	1	10.45	0-1.5	0.0

NR Band n77 60 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.61	10.15	0	0.0
	1	81	10.31	10.24		0.0
	1	160	10.30	10.17		0.0
	81	0	10.35	10.21	0-1	0.0
	81	41	10.25	10.20	0	0.0
	81	81	10.32	10.21	0-1	0.0
	162	0	10.31	10.21		0.0
DFT-s-OFDM 16QAM	1	1	10.58	10.07	0-1	0.0
CP-OFDM QPSK	1	1	10.54	10.26	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 391 of 426

Table H-720

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.47	0	0.0
	1	67	10.46		0.0
	1	131	10.33		0.0
	64	0	10.51	0-1	0.0
	64	35	10.51	0	0.0
	64	69	10.33	0-1	0.0
	128	0	10.40		0.0
DFT-s-OFDM 16QAM	1	1	10.56	0-1	0.0
CP-OFDM QPSK	1	1	10.45	0-1.5	0.0

NR Band n77 50 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.60	10.37	0	0.0
	1	67	10.51	10.47		0.0
	1	131	10.54	10.49		0.0
	64	0	10.58	10.44	0-1	0.0
	64	35	10.59	10.58	0	0.0
	64	69	10.58	10.42	0-1	0.0
	128	0	10.56	10.42		0.0
DFT-s-OFDM 16QAM	1	1	10.68	10.36	0-1	0.0
CP-OFDM QPSK	1	1	10.79	10.55	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 392 of 426

Table H-721

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.22	0	0.0
	1	53	10.30		0.0
	1	104	10.07		0.0
	50	0	10.28	0-1	0.0
	50	28	10.23	0	0.0
	50	56	10.26	0-1	0.0
	100	0	10.25		0.0
DFT-s-OFDM 16QAM	1	1	10.50	0-1	0.0
CP-OFDM QPSK	1	1	10.64	0-1.5	0.0

NR Band n77 40 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.50	10.20	0	0.0
	1	53	10.47	10.31		0.0
	1	104	10.41	10.19		0.0
	50	0	10.47	10.29	0-1	0.0
	50	28	10.49	10.29	0	0.0
	50	56	10.46	10.35	0-1	0.0
	100	0	10.47	10.30		0.0
DFT-s-OFDM 16QAM	1	1	10.48	10.21	0-1	0.0
CP-OFDM OPSK	1	1	10.50	10.19	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 393 of 426

Table H-722

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth					
			Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.30	0	0.0
	1	39	10.29		0.0
	1	76	10.23		0.0
	36	0	10.29	0-1	0.0
	36	21	10.25	0	0.0
	36	42	10.24	0-1	0.0
	75	0	10.31		0.0
DFT-s-OFDM 16QAM	1	1	10.42	0-1	0.0
CP-OFDM QPSK	1	1	10.53	0-1.5	0.0

NR Band n77 30 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.55	10.31	0	0.0
	1	39	10.53	10.29		0.0
	1	76	10.56	10.27		0.0
	36	0	10.49	10.37	0-1	0.0
	36	21	10.49	10.30	0	0.0
	36	42	10.45	10.40	0-1	0.0
	75	0	10.50	10.33		0.0
DFT-s-OFDM 16QAM	1	1	10.54	10.34	0-1	0.0
CP-OFDM QPSK	1	1	10.44	10.48	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 394 of 426

Table H-723

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.29	0	0.0
	1	33	10.41		0.0
	1	63	10.32		0.0
	32	0	10.37	0-1	0.0
	32	17	10.28	0	0.0
	32	33	10.31	0-1	0.0
	64	0	10.33		0.0
DFT-s-OFDM 16QAM	1	1	10.44	0-1	0.0
CP-OFDM QPSK	1	1	10.34	0-1.5	0.0

NR Band n77 25 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.58	10.37	0	0.0
	1	33	10.63	10.33		0.0
	1	63	10.46	10.41		0.0
	32	0	10.50	10.37	0-1	0.0
	32	17	10.50	10.28	0	0.0
	32	33	10.41	10.38	0-1	0.0
	64	0	10.47	10.34		0.0
DFT-s-OFDM 16QAM	1	1	10.58	10.46	0-1	0.0
CP-OFDM OPSK	1	1	10.42	10.43	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 395 of 426

Table H-724

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.20	0	0.0
	1	26	10.29		0.0
	1	49	10.33		0.0
	25	0	10.23	0-1	0.0
	25	13	10.18	0	0.0
	25	26	10.18	0-1	0.0
	50	0	10.17		0.0
DFT-s-OFDM 16QAM	1	1	10.36	0-1	0.0
CP-OFDM QPSK	1	1	10.34	0-1.5	0.0

NR Band n77 20 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.46	10.10	0	0.0
	1	26	10.22	10.21		0.0
	1	49	10.34	10.28		0.0
	25	0	10.43	10.22	0-1	0.0
	25	13	10.43	10.15	0	0.0
	25	26	10.49	10.21	0-1	0.0
	50	0	10.43	10.25		0.0
DFT-s-OFDM 16QAM	1	1	10.41	10.27	0-1	0.0
CP-OFDM QPSK	1	1	10.41	10.03	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 396 of 426

Table H-725

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.08	0	0.0
	1	19	10.07		0.0
	1	36	10.20		0.0
	18	0	10.15	0-1	0.0
	18	10	10.18	0	0.0
	18	20	10.22	0-1	0.0
	36	0	10.12		0.0
DFT-s-OFDM 16QAM	1	1	10.20	0-1	0.0
CP-OFDM QPSK	1	1	10.37	0-1.5	0.0

NR Band n77 15 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.48	10.25	0	0.0
	1	19	10.47	10.20		0.0
	1	36	10.37	10.16		0.0
	18	0	10.49	10.35	0-1	0.0
	18	10	10.38	10.37	0	0.0
	18	20	10.44	10.28	0-1	0.0
	36	0	10.38	10.31		0.0
DFT-s-OFDM 16QAM	1	1	10.33	10.41	0-1	0.0
CP-OFDM QPSK	1	1	10.59	10.23	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 397 of 426

Table H-726

NR Band n77 Antenna C Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open - Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth					
Modulation	RB Size	RB Offset	Channel	MPR Allowed per 3GPP [dB]	MPR [dB]
			633334 (3500.01 MHz)		
			Conducted Power [dBm]		
DFT-s-OFDM QPSK	1	1	10.31	0	0.0
	1	12	10.15		0.0
	1	22	10.22		0.0
	12	0	10.25	0-1	0.0
	12	6	10.24	0	0.0
	12	12	10.22	0-1	0.0
	24	0	10.12		0.0
DFT-s-OFDM 16QAM	1	1	10.24	0-1	0.0
CP-OFDM QPSK	1	1	10.29	0-1.5	0.0

NR Band n77 10 MHz Bandwidth						
			Channel		MPR Allowed per 3GPP [dB]	MPR [dB]
Modulation	RB Size	RB Offset	650000 (3750 MHz)	662000 (3930 MHz)		
			Conducted Power [dBm]			
DFT-s-OFDM QPSK	1	1	10.40	10.46	0	0.0
	1	12	10.60	10.28		0.0
	1	22	10.48	10.43		0.0
	12	0	10.57	10.40	0-1	0.0
	12	6	10.43	10.31	0	0.0
	12	12	10.54	10.42	0-1	0.0
	24	0	10.44	10.38		0.0
DFT-s-OFDM 16QAM	1	1	10.59	10.47	0-1	0.0
CP-OFDM QPSK	1	1	10.48	10.29	0-1.5	0.0

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 398 of 426

Table H-727

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.65	

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.73	19.72

Table H-728

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.68	

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.72	19.68

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 399 of 426

Table H-729

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.68	

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.70	19.67

Table H-730

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.63	

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.73	19.69

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 400 of 426

Table H-731

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.77	

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.74	19.71

Table H-732

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.74	

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.70	19.74

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 401 of 426

Table H-733

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.73	

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.66	19.72

Table H-734

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.76	

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.72	19.73

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 402 of 426

Table H-735

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.66	

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.73	19.76

Table H-736

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.66	

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.76	19.79

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 403 of 426

Table H-737

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 3 (Folder Closed-Head) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	20.66	

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	19.77	19.79

Table H-738

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5

(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5

(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.38	
SRS #3 Ant A	14.10	
SRS #4 Ant G	14.75	

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.81	18.37
SRS #3 Ant A	13.75	14.07
SRS #4 Ant G	13.06	13.90

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 405 of 426

Table H-739

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5

(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5

(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.36	
SRS #3 Ant A	14.11	
SRS #4 Ant G	14.76	

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.82	18.37
SRS #3 Ant A	13.74	14.07
SRS #4 Ant G	13.05	13.90

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 406 of 426

Table H-740

**NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5
(Folder Closed-Body, Folder Closed – Grip) and**

**NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 70 MHz Bandwidth**

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	18.33
SRS #3 Ant A	14.11
SRS #4 Ant G	14.76

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.90	18.37
SRS #3 Ant A	13.75	14.06
SRS #4 Ant G	13.05	13.90

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 407 of 426

Table H-741

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5

(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5

(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.34	
SRS #3 Ant A	13.95	
SRS #4 Ant G	14.61	

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.98	18.29
SRS #3 Ant A	13.63	13.93
SRS #4 Ant G	13.03	13.84

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 408 of 426

Table H-742

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5
(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.38	
SRS #3 Ant A	14.22	
SRS #4 Ant G	14.87	

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	18.04	18.41
SRS #3 Ant A	13.88	14.20
SRS #4 Ant G	13.20	13.95

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 409 of 426

Table H-743

**NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5 (Folder Closed-Body, Folder Closed – Grip) and
NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 40 MHz Bandwidth**

NR Band n77 DoD 40 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.36	
SRS #3 Ant A	14.10	
SRS #4 Ant G	14.75	

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.86	18.28
SRS #3 Ant A	13.73	14.09
SRS #4 Ant G	13.02	13.97

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 410 of 426

Table H-744

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5

(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5

(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.35	
SRS #3 Ant A	14.14	
SRS #4 Ant G	14.78	

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.83	18.28
SRS #3 Ant A	13.73	14.10
SRS #4 Ant G	13.01	13.97

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 411 of 426

Table H-745

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5

(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5

(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.36	
SRS #3 Ant A	14.16	
SRS #4 Ant G	14.76	

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.91	18.24
SRS #3 Ant A	13.78	14.03
SRS #4 Ant G	13.11	13.93

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 412 of 426

Table H-746

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5

(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5

(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.36	
SRS #3 Ant A	14.11	
SRS #4 Ant G	14.77	

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.82	18.28
SRS #3 Ant A	13.76	14.00
SRS #4 Ant G	13.09	13.80

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 413 of 426

Table H-747

**NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5
(Folder Closed-Body, Folder Closed – Grip) and**

**NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 15 MHz Bandwidth**

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	18.36
SRS #3 Ant A	14.12
SRS #4 Ant G	14.78

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.90	18.29
SRS #3 Ant A	13.75	14.01
SRS #4 Ant G	13.07	13.80

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 414 of 426

Table H-748

NR Band n77 Antenna F Path 2 Measured P_{Limit} for DSI = 1/5
(Folder Closed-Body, Folder Closed – Grip) and

NR Band n77 Antenna A & G Path 2 Measured P_{Limit} for DSI = 1/3/5
(Folder Closed-Body, Folder Closed-Head, Folder Closed – Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	18.47	
SRS #3 Ant A	14.14	
SRS #4 Ant G	14.81	

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	17.83	18.33
SRS #3 Ant A	13.77	14.03
SRS #4 Ant G	13.11	13.81

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 415 of 426

Table H-749

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 90 MHz Bandwidth

NR Band n77 DoD 90 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.39
SRS #3 Ant A	7.15
SRS #4 Ant G	7.68

NR Band n77 90 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.68	9.62
SRS #3 Ant A	6.82	7.21
SRS #4 Ant G	6.23	7.22

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 416 of 426

Table H-750

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 80 MHz Bandwidth

NR Band n77 DoD 80 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.40
SRS #3 Ant A	7.06
SRS #4 Ant G	7.70

NR Band n77 80 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.77	9.72
SRS #3 Ant A	6.78	7.14
SRS #4 Ant G	6.22	7.19

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 417 of 426

Table H-751

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 70 MHz Bandwidth

NR Band n77 DoD 70 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.32
SRS #3 Ant A	7.01
SRS #4 Ant G	7.70

NR Band n77 70 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.77	9.68
SRS #3 Ant A	6.79	7.17
SRS #4 Ant G	6.22	7.20

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 418 of 426

Table H-752

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 60 MHz Bandwidth

NR Band n77 DoD 60 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.26
SRS #3 Ant A	6.97
SRS #4 Ant G	7.63

NR Band n77 60 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.76	9.64
SRS #3 Ant A	6.71	7.03
SRS #4 Ant G	6.09	7.01

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 419 of 426

Table H-753

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 50 MHz Bandwidth

NR Band n77 DoD 50 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	9.25	
SRS #3 Ant A	7.20	
SRS #4 Ant G	7.91	

NR Band n77 50 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.84	9.57
SRS #3 Ant A	6.95	7.13
SRS #4 Ant G	6.39	7.20

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 420 of 426

Table H-754

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 40 MHz Bandwidth

NR Band n77 DoD 40 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.23
SRS #3 Ant A	7.37
SRS #4 Ant G	7.77

NR Band n77 40 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.70	9.62
SRS #3 Ant A	6.92	7.29
SRS #4 Ant G	6.23	7.08

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 421 of 426

Table H-755

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 30 MHz Bandwidth

NR Band n77 DoD 30 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	9.32	
SRS #3 Ant A	7.31	
SRS #4 Ant G	7.78	

NR Band n77 30 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.74	9.63
SRS #3 Ant A	6.91	7.30
SRS #4 Ant G	6.18	7.10

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 422 of 426

Table H-756

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 25 MHz Bandwidth

NR Band n77 DoD 25 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.29
SRS #3 Ant A	7.34
SRS #4 Ant G	7.79

NR Band n77 25 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.75	9.58
SRS #3 Ant A	6.98	7.26
SRS #4 Ant G	6.32	7.06

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 423 of 426

Table H-757

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 20 MHz Bandwidth

NR Band n77 DoD 20 MHz Bandwidth		
Channel		
Antenna	633334 (3500.01 MHz)	
	Conducted Power [dBm]	
SRS #2 Ant F	9.27	
SRS #3 Ant A	7.33	
SRS #4 Ant G	7.72	

NR Band n77 20 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.79	9.64
SRS #3 Ant A	6.92	7.19
SRS #4 Ant G	6.24	6.99

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 424 of 426

Table H-758

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 15 MHz Bandwidth

NR Band n77 DoD 15 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.29
SRS #3 Ant A	7.34
SRS #4 Ant G	7.71

NR Band n77 15 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.68	9.65
SRS #3 Ant A	6.90	7.21
SRS #4 Ant G	6.22	7.01

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 425 of 426

Table H-759

NR Band n77 Antenna A, F, G Path 2 Measured P_{Limit} for DSI = 0/4 (Folder Open - Body, Folder Open – Grip) – 10 MHz Bandwidth

NR Band n77 DoD 10 MHz Bandwidth	
Channel	
Antenna	633334 (3500.01 MHz)
	Conducted Power [dBm]
SRS #2 Ant F	9.30
SRS #3 Ant A	7.37
SRS #4 Ant G	7.74

NR Band n77 10 MHz Bandwidth		
Channel		
Antenna	650000 (3750 MHz)	662000 (3930 MHz)
	Conducted Power [dBm]	
SRS #2 Ant F	8.71	9.62
SRS #3 Ant A	6.93	7.32
SRS #4 Ant G	6.28	7.12

FCC ID: A3LSMF966U	SAR EVALUATION REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX H: Page 426 of 426