

APPENDIX A: RF EXPOSURE TEST PLOTS

Plot A-1 Verification Test Data

cDASY6 Module WPT Measurement Report

Device under test	Tool info	Scan info
Info: 85kHz Verification	DASY software version: cDASY6 Module WPT 2.8.0.5184	Center location: x: 698.57 mm, y: 37.97 mm, z: 267.92 mm
Serial number: 1031	Probe model, serial no. and configuration date: MAGPy-8H3D+E3Dv2, WP000261, 2024/08/14	Dimensions: x: 388.0 mm, y: 477.0 mm, z: 37.0 mm
Scenario: 85kHz Verification	Software version: 2.8.8, backend: 2.2.36	Resolution: x: 7.33 mm, y: 7.33 mm, z: 7.33 mm
		Completed on: 2025/04/07 10:05:11

Measurement results

Maximum H-field [RMS]:
MAGNITUDE: 130.91 A/m
x: 8.14 A/m, y: 108.50 A/m, z: 72.79 A/m

Maximum H-field location relative to DUT:
x: 62.33 mm, y: 143.00 mm, z: 8.50 mm


Maximum E-field [RMS]:
MAGNITUDE: 116.49 V/m
x: 10.67 V/m, y: 7.32 V/m, z: 115.77 V/m

Maximum E-field location relative to DUT:
x: 102.67 mm, y: -88.00 mm, z: 0.00 mm


Distance to -20.0 dB boundary:
52.88 mm

Offset relative to DUT:
x: 0.00 m, y: 0.00 m, z: 1.00 mm

H-field magnitude [RMS] at center location



H-field magnitude [RMS] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 85.00 kHz, $\sigma = 0.750$ S/m, tissue density = 1,000 kg/m³)

Distance [mm]	Peak incident fields [RMS]		Peak E _{ind} [V/m, RMS]			Peak J _{ind} [A/m ² , RMS]	psSAR [mW/kg]		H-field extent -20 dB radius [mm]	Sign	Vector potential	Warnings Boundary effect
	H _{inc} [A/m]	E _{inc} [V/m]	Cube avg.	Local	Line avg.		1g avg.	10g avg.				
0.00	238	116	3.09	3.14	3.13	2.16	5.57	4.36	180	1%	133%	44%
2.00	205	106	2.93	2.97	2.97	2.09	5.28	4.09	183	1%	133%	44%

Compliance evaluation (Field values at the peak frequency) (f=85.00 kHz, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]	RL [RMS]	BR [RMS]
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[A/m ²]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]	[A/m]	[V/m]	[V/m]	[mW/kg]
0.00	238	116	3.10	4.36	238	116	2.16	4.36	238	116	3.14	4.36	238	116	N/A	5.57	238	116	3.14	5.57
2.00	205	106	2.93	4.09	205	106	2.09	4.09	205	106	2.97	4.09	205	106	N/A	5.28	205	106	2.97	5.28

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR	RL	BR
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH	NS	TH
0.00	11.3	N/A	3.66	N/A	0.27	N/A	47.6	3.23	12.7	N/A	1.46	N/A	0.50	N/A	0.18	N/A	2.64	2.17	N/A	N/A
2.00	9.77	N/A	3.35	N/A	0.26	N/A	41.0	2.95	12.3	N/A	1.26	N/A	0.45	N/A	0.17	N/A	2.28	1.98	N/A	N/A

Document generated at 2025/04/07 12:20:52, simulation performed at 2025/04/07 10:22:53 using Sim4Life version 8.0.1.15737

FCC ID: A3LSMF966U		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 3/27/2025 – 4/27/2025	Apparatus/Device: Portable Handset		APPENDIX A: Page 1 of 2

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Plot A-2 Worst Case Test Data

cDASY6 Module WPT Measurement Report

Device under test

Info:
A3LSMF966U

Serial number:
1785M

Scenario:
Ping Signal Backside Folder Closed

Tool info

DASY software version:
cDASY6 Module WPT 2.8.0.5184

Probe model, serial no. and configuration date:
MAGPy-8H3D+E3Dv2, WP000261, 2024/08/14

Software version:
2.8.8, backend: 2.2.36

Scan info

Center location:
x: -25.92 mm, y: -176.85 mm, z: 25.68 mm

Dimensions:
x: 168.7 mm, y: 256.8 mm, z: 36.6 mm

Resolution:
x: 7.33 mm, y: 7.33 mm, z: 7.33 mm

Completed on:
2025/04/07 12:59:35

Measurement results

Maximum H-field [RMS]:
MAGNITUDE: 177.67 A/m
x: 41.76 A/m, y: 18.61 A/m, z: 171.69 A/m

Maximum H-field location relative to DUT:
x: -11.00 mm, y: 3.67 mm, z: 8.50 mm


Maximum E-field [RMS]:
MAGNITUDE: 29.73 V/m
x: 7.23 V/m, y: 2.04 V/m, z: 28.77 V/m

Maximum E-field location relative to DUT:
x: -29.33 mm, y: 14.67 mm, z: 0.00 m


Distance to -20.0 dB boundary:
29.33 mm

Offset relative to DUT:
x: 0.00 m, y: 0.00 m, z: 1.00 mm

H-field magnitude [RMS] at center location



H-field magnitude [RMS] at lowest plane



Incident fields and induced fields in the homogeneous phantom at the peak frequency (f = 144.84 kHz, $\sigma = 0.750$ S/m, tissue density = 1,000 kg/m³)

Distance [mm]	Peak incident fields [RMS]		Peak E _{ind} [V/m, RMS]			Peak J _{ind} [A/m ² , RMS]	psSAR [mW/kg]		H-field extent	Sign	Vector potential	Warnings
	H _{inc} [A/m]	E _{inc} [V/m]	Cube avg.	Local	Line avg.	Surface avg.	1g avg.	10g avg.	-20 dB radius [mm]			Boundary effect
0.00	384	29.7	1.60	1.65	1.65	0.974	0.886	0.392	32.6	6%	11%	7%
2.00	334	28.1	1.34	1.39	1.39	0.799	0.605	0.271	32.8	6%	11%	8%

Compliance evaluation (Field values at the peak frequency) (f=144.84 kHz, total field evaluation, coverage evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
0.00	384	29.7	8.46	0.392	384	29.7	0.975	0.392	384	29.7	4.79	0.392	384	29.7	N/A	0.886	384	29.7	12.3	0.886
2.00	334	28.1	7.10	0.271	334	28.1	0.800	0.271	334	28.1	4.04	0.271	334	28.1	N/A	0.605	334	28.1	10.4	0.605

Coverage factors: $W_{E_{ind}, cube avg.} = [5.29, 5.29]$, $W_{E_{ind}, local} = [7.47, 7.48]$, $W_{E_{ind}, line avg.} = [2.91, 2.91]$

Compliance evaluation (Exposure ratios) (with multi-frequency enhancement, total field evaluation, coverage evaluation)

Distance [mm]	ICNIRP 2010/2020				ICNIRP 1998				IEEE 2019				FCC				HC Code 6			
	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pJ _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR	pH _{inc}	pE _{inc}	pE _{ind}	psSAR
0.00	19.5	11.8	1.08	0.10	0.46	<0.01	79.7	1.22	3.59	<0.01	2.51	1.59	0.15	0.04	0.17	<0.01	237.0	0.19	N/A	<0.01
2.00	16.9	10.3	1.02	0.09	0.39	<0.01	69.3	1.16	2.95	<0.01	2.18	1.38	0.14	0.04	0.14	<0.01	206.0	0.18	N/A	<0.01

Coverage factors: $W_{E_{ind}, cube avg.} = [5.29, 5.29]$, $W_{E_{ind}, local} = [7.47, 7.48]$, $W_{E_{ind}, line avg.} = [2.91, 2.91]$

FCC ID: A3LSMF966U		WPT RF EXPOSURE EVALUATION REPORT	Reviewed by: Technical Manager
Test Dates: 3/27/2025 – 4/27/2025	Apparatus/Device: Portable Handset		APPENDIX A: Page 2 of 2