

TEST REPORT

Report Number: R16238088-E3a

Applicant : Samsung Electronics Co Ltd
129, Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 16677, Rep. of Korea

Model(s) : SM-F976U, SM-F976U1

FCC ID : A3LSMF976U

EUT Description : GSM/WCDMA/LTE/NR/SCS/NTN Phone + BT/BLE, DTS/UNII
a/b/g/n/ac/ax/be, UWB, WPT and NFC

Test Standard(s) : FCC 47 CFR PART 2, PART 22H, PART 90S, PART 25
ISED RSS-GEN ISSUE 5 + A1 + A2, RSS-132 ISSUE 4

Date Of Issue:
2026-05-01

Prepared by:
UL LLC
12 Laboratory Dr.
Durham, NC 27713 USA
TEL: (919) 549-1400



Revision History

<u>Rev.</u>	<u>Issue Date</u>	<u>Revisions</u>	<u>Revised By</u>
V1	2026-05-01	Initial Review	Noah Bennett

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....5

2. SUMMARY OF TEST RESULTS6

3. TEST METHODOLOGY7

4. FACILITIES AND ACCREDITATION7

5. DECISION RULES AND MEASUREMENT UNCERTAINTY.....8

5.1. METROLOGICAL TRACEABILITY8

5.2. DECISION RULES8

5.3. MEASUREMENT UNCERTAINTY8

5.4. SAMPLE CALCULATION8

6. EQUIPMENT UNDER TEST9

6.1. DESCRIPTION OF EUT9

6.2. MAXIMUM OUTPUT POWER9

6.3. MAXIMUM ANTENNA GAIN12

6.4. WORST-CASE CONFIGURATION AND MODE12

6.5. DESCRIPTION OF TEST SETUP13

7. TEST AND MEASUREMENT EQUIPMENT.....14

8. CONDUCTED TEST RESULTS19

8.1. OCCUPIED BANDWIDTH19

8.1.1. LTE BAND 26 (FCC PART 90S)21

8.1.2. 5G NR n26 (FCC PART 90S)22

8.1.3. LTE BAND 5&26 (FCC PART 22).....23

8.1.4. 5G NR n5&n26 (FCC PART 22)24

8.2. EMISSION MASK AND ADJACENT CHANNEL POWER.....25

8.2.1. LTE BAND 26 (FCC PART 90S)27

8.2.2. 5G NR n26 (FCC PART 90S)30

8.2.3. LTE BAND 5&26 (FCC PART 22).....32

8.2.4. 5G NR 5&n26 (FCC PART 22)36

8.2.5. LTE BAND 5&26 (Straddle)39

8.2.6. 5G NR n5&n26 (Straddle)41

8.3. OUT OF BAND EMISSIONS43

8.3.1. LTE BAND 26 (FCC PART 90S)44

8.3.2.	5G NR n26 (FCC PART 90S)	44
8.3.3.	LTE BAND 5&26 (FCC PART 22)	45
8.3.4.	5G NR n5&n26 (FCC PART 22)	46
8.4.	FREQUENCY LIMITS	47
8.4.1.	LTE BAND 5&26 (QPSK 10MHz BANDWIDTH, FCC PART 22)	48
8.4.2.	5G NR n5&n26 (BPSK 20MHz BANDWIDTH, FCC PART 22)	48
8.5.	PEAK-TO-AVERAGE POWER RATIO	49
8.5.1.	LTE BAND 26 (FCC PART 90S)	50
8.5.2.	5G NR n26 (FCC PART 90S)	52
8.5.3.	LTE BAND 5&26 (FCC PART 22)	53
8.5.4.	5G NR n5&n26 (FCC PART 22)	53
9.	RADIATED TEST RESULTS	54
9.1.	EFFECTIVE RADIATED POWER ERP/EIRP	55
9.1.1.	LTE BAND 26 (FCC PART 90S)	56
9.1.2.	5G NR n26 (FCC PART 90S)	58
9.1.3.	LTE BAND 5&26 (FCC PART 22)	60
9.1.4.	5G NR n5&n26 (FCC PART 22)	64
9.2.	FIELD STRENGTH OF SPURIOUS RADIATION	68
9.2.1.	LTE BAND 26 (FCC PART 90S & 22)	71
9.2.2.	5G NR n26 (FCC PART 90S & 22)	73
10.	SETUP PHOTOS	74

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: Samsung Electronics Co Ltd
129, Samsung-ro, Yeongtong-gu, Suwon-si,
Gyeonggi-do, 16677, Rep. of Korea

EUT DESCRIPTION: GSM/WCDMA/LTE/NR/SCS/NTN Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax/be,
UWB, WPT and NFC

SERIAL NUMBERS: ZBK0208M, ZBD0487M, ZAT0031M, ZBK0219M

SAMPLE RECEIVE DATE: 2026-03-09

DATE TESTED: 2026-03-09 – 2026-05-01

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR PART 2, PART 22H, PART 90S, PART 25	Complies
ISED RSS-GEN ISSUE 5 + A1 + A2, RSS-132 ISSUE 4	

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released For
UL LLC By:



Bob Delisi
Principal Engineer
Consumer Technology Division
UL LLC

Prepared By:



Noah Bennett
Engineer Project Associate
Consumer Technology Division
UL LLC

2. SUMMARY OF TEST RESULTS

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for correctly integrating customer-provided data with measurements performed by UL LLC.

Requirement Description	Band	Requirement Clause Number (FCC)	Requirement Clause Number (ISED)	Result	Remarks
RF Conducted Output Power	26 (90S)	2.1046, 90.635 (b)	--	Complies	None.
Effective Radiated Power	5, 26 (22)	22.913 (a)(5)	RSS132§5.4	Complies	None.
Occupied Bandwidth	5, 26	2.1049	RSS132, RSS-GEN§6.7	Complies	None.
Band Edge and Emission Mask	5, 26	2.1051, 22.917 (a), 90.691 (a)	RSS132§5.5	Complies	None.
Out of Band Emissions	5, 26	2.1051, 22.917 (a), 90.691 (a)	RSS132§5.5	Complies	None.
Frequency Stability	5, 26	2.1055, 22.355, 90.539, 90.213	RSS132§5.3	Complies	None.
Peak-to-Average Ratio	5, 26	22.913 (d)	RSS132§5.4	Complies	None.
Field Strength of Spurious Radiation	5, 26	2.1053, 22.917 (a), 90.691 (a)	RSS132§5.5	Complies	None.

SUPPLEMENTAL COVERAGE FROM SPACE (SCS)

Under section § 25.109 (f) of the FCC rules Space and SCS earth stations providing SCS are subject to technical rules in parts 2, 22, 24, and 27 of this chapter based on the operating frequency band. Section § 25.204 (g) specifies that earth stations providing SCS pursuant to §§ 25.125 and 25.115 shall comply with the power requirements and out-of-band emission limits corresponding to devices operating in parts 22, 24, or 27 of this chapter (e.g., §§ 22.913, 24.232, 27.50), as required for their operating frequencies. We have clarified through KDB inquiry that the technical requirements from Part 90R should be applied for SCS operations in the 700 MHz Public Safety Band.

The table below identifies the SCS frequencies available for use and, for each band, the applicable FCC Part 22, 24, 27, and 90R technical requirements, the air interfaces supported by the device for SCS use.

The bands available for SCS and the bands supported by the devices in the scope of this report are:

Band	Frequency		Part 22/24/27/90 Rule parts	3GPP Band	Supported	Applicable to This Report
	DL (MHz)	UL (MHz)				
600 MHz	614 – 652	663 – 698	27.5 (c) 27.50 (c) 27.53 (g)	71/n71	Yes	No
700 MHz	729 – 746	699 – 716	27.5 (c) 27.50 (c) 27.53 (g)	12/n12 17	Yes	No
	746 – 756	777 – 787	27.5 (b) 27.50 (b) 27.53 (f)	13/n13	Yes	No
	758 – 769	788 – 799	90R ^{Note 1}	14 / n14	Yes	No
	805 – 806				No	No
800 MHz	869 – 894	824 – 849	22H	WCDMA 5 5/n5 26/n26	Yes	Yes
Broadband PCS	1930 – 1995	1850 – 1915	24E	WCDMA 2 2/n2 25/n25	Yes	No

Note 1: Clarified through KDB inquiry that the technical requirements from Part 90R should be applied for SCS operations in the 700 MHz Public Safety Band.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with the following.
FCC published lists of [measurement procedures](#) for compliance testing.
ISED published lists of [normative test standards and acceptable alternatives procedures](#).

- ANSI C63.26:2015
- ANSI/TIA-603-E (2016)
- FCC 47 CFR Part 2, Part 22H, Part 90S, Part 25
- [FCC KDB 971168 D01](#): Power Meas License Digital Systems (ISED acceptable alternative procedure)
- [FCC KDB 971168 D02](#): Misc Rev Approv License Devices
- [FCC KDB 412172 D01](#): Determining ERP and EIRP
- [FCC KDB 273109 D02](#): Part 25 SCS and CMRS-Bands
- ISED RSS-Gen Issue 5 + A1 + A2, RSS-132 Issue 4

4. FACILITIES AND ACCREDITATION

UL LLC. is accredited by A2LA, certification #0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
☒	Building 2800 Suite Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A.	US0067	27265	825374

5. DECISION RULES AND MEASUREMENT UNCERTAINTY

5.1. METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

5.2. DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.52 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	4.88 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.24 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.37 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.17 dB
Occupied Channel Bandwidth	±0.39 %
Temperature	±0.9 °C
Supply voltages	±0.45 %
Time	±0.02 %

Uncertainty figures are valid to a confidence level of 95%.

5.4. SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)
 $36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} = 28.9 \text{ dBuV/m}$

6. EQUIPMENT UNDER TEST

6.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE/NR/SCS/NTN Phone + BT/BLE, DTS/UNII a/b/g/n/ac/ax/be, UWB, WPT and NFC.

Model differences:

Representative Model	Difference	Derivative Model
		SM-F976U1
SM-F976U	Hardware	Same as SM-F976U
	Software	Different UI

The EUT supports the following LTE and 5G NR Bands and their antenna configurations:

LTE & 5G NR Bands	Config 0	Config 1
LTE B5 & 5G NR n5	ANT A+C (Main 1)	ANT E (Sub 1)
LTE B26 & 5G NR n26 (Part 90S)		
LTE B26 & 5G NR n26 (Part 22H)		

6.2. MAXIMUM OUTPUT POWER

EIRP/ERP TEST PROCEDURE

ANSI C63.26:2015
KDB 971168 D01 Section 5.2

$$\text{ERP/EIRP} = P_{\text{Meas}} + G_T - L_C$$

where: ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

The EUT has different power levels for head use configuration and body use configuration. The tables below contain the highest of all configurations average conducted and peak EIRP/ERP output powers as follows:

LTE BAND 26 (FCC Part 90S)

Part 90S										
Conducted Limit (W)		100.00								
Antenna Gain (dBi)		-3.10								
Bandwidth (MHz)	Modulation	Low Frequency (MHz)	Upper Frequency (MHz)	Conducted Average (dBm)	Conducted Average (W)	ERP Average (dBm)	ERP Average (W)	99% BW (MHz)	99% BW (kHz)	Emission Designator
5.0	QPSK	816.5	821.5	24.82	0.30	19.57	0.091	4.521	4521	4M52G7W
	16QAM			23.62	0.23	18.37	0.069	4.521	4521	4M52D7W
10.0	QPSK	814.0	824.0	24.58	0.29	19.33	0.086	9.003	9003	9M00G7W
	16QAM			23.46	0.22	18.21	0.066	9.016	9016	9M02D7W

LTE BAND 26 (Straddle)

Part 90S										
Conducted Limit (W)		100.00								
Antenna Gain (dBi)		-3.10								
Bandwidth (MHz)	Modulation	Low Frequency (MHz)	Upper Frequency (MHz)	Conducted Average (dBm)	Conducted Average (W)	ERP Average (dBm)	ERP Average (W)	99% BW (MHz)	99% BW (kHz)	Emission Designator
5.0	QPSK	816.5	821.5	24.63	0.29	19.38	0.087	4.521	4521	4M52G7W
	16QAM			23.93	0.25	18.68	0.074	4.521	4521	4M52D7W
10.0	QPSK	819.0	829.0	24.39	0.27	19.14	0.082	9.003	9003	9M00G7W
	16QAM			23.71	0.23	18.46	0.070	9.016	9016	9M02D7W
15.0	QPSK	816.5	831.5	23.69	0.23	18.44	0.070	13.510	13510	13M5G7W
	16QAM			22.95	0.20	17.70	0.059	13.542	13542	13M5D7W

5G NR n26 (FCC Part 90S)

Part 90S										
Conducted Limit (W)		100.00								
Antenna Gain (dBi)		-3.50								
Bandwidth (MHz)	Modulation	Low Frequency (MHz)	Upper Frequency (MHz)	Conducted Average (dBm)	Conducted Average (W)	ERP Average (dBm)	ERP Average (W)	99% BW (MHz)	99% BW (kHz)	Emission Designator
5.0	BPSK	816.5	821.5	24.47	0.28	18.82	0.076	4.5137	4513.7	4M51G7W
	16QAM			23.99	0.25	18.34	0.068	4.5331	4533.1	4M53D7W
10.0	BPSK	814.0	824.0	24.32	0.27	18.67	0.074	8.9778	8977.8	8M98G7W
	16QAM			23.22	0.21	17.57	0.057	9.0054	9005.4	9M01D7W

5G NR n26 (Straddle)

Part 90S										
Conducted Limit (W)		100.00								
Antenna Gain (dBi)		-3.50								
Bandwidth (MHz)	Modulation	Low Frequency (MHz)	Upper Frequency (MHz)	Conducted Average (dBm)	Conducted Average (W)	ERP Average (dBm)	ERP Average (W)	99% BW (MHz)	99% BW (kHz)	Emission Designator
5.0	BPSK	816.5	821.5	24.07	0.26	18.42	0.070	4.5137	4513.7	4M51G7W
	16QAM			23.16	0.21	17.51	0.056	4.5331	4533.1	4M53D7W
10.0	BPSK	819.0	829.0	24.00	0.25	18.35	0.068	8.9778	8977.8	8M98G7W
	16QAM			22.95	0.20	17.30	0.054	9.0054	9005.4	9M01D7W
15.0	BPSK	816.5	831.5	23.98	0.25	18.33	0.068	13.453	13453	13M5G7W
	16QAM			22.94	0.20	17.29	0.054	13.511	13511	13M5D7W
20.0	BPSK	814.0	834.0	23.90	0.25	18.25	0.067	17.955	17955	18M0G7W
	16QAM			22.79	0.19	17.14	0.052	17.915	17915	17M9D7W

LTE BAND 5&26 (FCC Part 22)

Part 22/RSS 132								
ERP Limit (W)		7.00						
Bandwidth (MHz)	Modulation	Low Frequency	Upper Frequency	ERP Average	ERP Average	99% BW (MHz)	99% BW (kHz)	Emission Designator
5.0	QPSK	826.5	846.5	19.74	0.094	4.5147	4514.7	4M51G7W
	16QAM			18.87	0.077	4.5164	4516.4	4M52D7W
15.0	QPSK	829.0	844.0	19.58	0.091	13.51	13510	13M5G7W
	16QAM			18.70	0.074	13.542	13542	13M5D7W

5G NR n5&n26 (FCC Part 22)

Part 22/RSS 132								
ERP Limit (W)		7.00						
Bandwidth (MHz)	Modulation	Low Frequency (MHz)	Upper Frequency (MHz)	ERP Average (dBm)	ERP Average (W)	99% BW (MHz)	99% BW (kHz)	Emission Designator
5.0	BPSK	826.5	846.5	18.98	0.079	4.4923	4492.3	4M49G7W
	16QAM			18.00	0.063	4.5069	4506.9	4M51D7W
20.0	BPSK	826.5	846.5	18.81	0.076	17.955	17955	18M0G7W
	16QAM			17.82	0.061	17.915	17915	17M9D7W

6.3. MAXIMUM ANTENNA GAIN

The antenna(s) gain as provided by the manufacturer' are as follows:

Frequency Band	ANT A+C Antenna Gain (dBi)	ANT E Antenna Gain (dBi)
LTE B5 & 5G NR n5 824 – 849 MHz	-3.1	-4.2
LTE B26 & 5G NR n26 (Part 90) 814 – 824 MHz	-3.5	-4.5
LTE B26 & 5G NR n26 (Part 22) 824 – 849 MHz	-3.5	-4.5

6.4. WORST-CASE CONFIGURATION AND MODE

The worst-case scenario for all measurements is based upon an engineering evaluation made on conducted average power taken during pre-testing. The modulations with the highest output power were selected as worst-case. Conducted tests were performed on the worst-case antenna port per band. Full radiated Emissions Testing on each antenna was performed and reported.

Radiated spurious tests were conducted on wider bandwidth with 1RB to cover the entire 814 – 849 frequency range for both part 90S and 22H.

BPSK modulation applied only for 5G NR frequencies and has the same tune up power as QPSK modulations.

The DFT-s-OFDM and CP-OFDM waveforms were investigated, and DFT-s-OFDM was found to be the worst case.

Band FR1 n5 is covered by FR1 n26, as they share the same operating frequency range, and have equal output powers.

The following is the worst-case antenna port, and modulation, as tested:

LTE & 5G NR Bands	Worst-Case Antenna Port	Worst-Case Modulation
LTE B5 & 5G NR n5 824 – 849 MHz	ANT E (Sub 1)	LTE: QPSK 5G NR: BPSK
LTE B26 & 5G NR n26 (Part 90) 814 – 824 MHz	ANT A+C (Main 1)	
LTE B26 & 5G NR n26 (Part 22) 824 – 849 MHz	ANT A+C (Main 1)	

The EUT was investigated in three orthogonal orientations X/Y/Z on both Low Band (Fundamental Below 1GHz) Mid Band (Fundamental between 1-3GHz) and High Band (Fundamental above 3GHz) over all antennas to find the worst-case orientation. Additionally, the EUT was investigated between 3 folding positions, Fully Open, Fully Closed, and Half Open. For Simultaneous Tx scans in which there are two or more F_c ranges with different worst-case orientations, scans were performed in the orientation with the highest output power, and sufficient margin was added to cover other orientations. The following are the worst-case orientations:

LTE & 5G NR Bands	Config 0 Orientation	Config 1 Orientation
Low Band ($F_c < 1\text{GHz}$)	X, Open	X, Open
Mid Band ($1\text{GHz} < F_c < 3\text{GHz}$)	-	-
High Band ($F_c > 3\text{GHz}$)	-	-

Worst Case emissions from 9kHz-30Mhz, 30-1000MHz, 18-26.5GHz, and 26.5GHz-40GHz were done on the modes with the highest pre-tuned conducted average power per antenna. No emissions within 20dB were observed.

6.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
Power Adapter	Sony	XQZ-UC11-010-236-21	NA	NA

I/O CABLES

I/O Cable List						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	USB-C	1	USB-C	Shielded	<3m	Phone to power adapter

TEST SETUP

The EUT was connected to a base station simulator and set to transmit at max power for WWAN testing

SETUP DIAGRAM

Please see R16238088-EP1 for Setup Diagrams and Setup Photos.

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment Used - Radiated Disturbance Emissions Test Equipment (Morrisville – Chamber 4)

Equip. ID	Description	Manufacturer/Brand	Model Number	Last Cal.	Next Cal.
	0.009-30MHz				
8939	Passive Loop Antenna	EMCO	EM-6872	2024-11-18	2026-11-18
8940	Passive Loop Antenna	EMCO	EM-6871	2024-11-18	2026-11-18
	30-1000 MHz				
90628	Hybrid Broadband Antenna	Sunol Sciences Corp.	JB3	2026-02-09	2028-02-09
	1-18 GHz				
*206211	Double-Ridged Waveguide Horn Antenna, 1 to 18 GHz	ETS Lindgren	3117	2024-04-09	2026-04-30
	18-40 GHz				
204704	Horn Antenna, 18-26.5GHz	Com Power	AH-826	2025-07-15	2027-07-15
204705	Horn Antenna, 26-40GHz	Com Power	AH-640	2025-11-19	2027-11-19
	Gain-Loss Chains				
207638	Gain-loss string: 0.009-30MHz	Various	Various	2025-06-13	2026-06-13
207639	Gain-loss string: 25-1000MHz	Various	Various	2025-06-13	2026-06-13
207640	Gain-loss string: 1-18GHz	Various	Various	2025-06-13	2026-06-13
225795	Gain-loss string: 18-40GHz	Various	Various	2025-06-13	2026-06-13
	Receiver & Software				
*197954	Spectrum Analyzer	Rohde & Schwarz	ESW44	2025-04-21	2026-04-30
SOFTEMI	EMI Software	UL	Version 9.5 (18 Oct 2021)		
	Additional Equipment used				
241204	Environmental Meter	Fisher Scientific	15-077-963	2025-08-05	2027-08-05
213025	Wideband Radio Communications Tester	Rohde and Schwarz	CMW500	N/A	N/A
208720	Wideband Radio Communications Tester	Rohde and Schwarz	CMW500	N/A	N/A
21725	Radio Communications Tester	Rohde and Schwarz	CMX500	2025-11-25	2026-11-25
212167	Wideband Radio Communications Tester	Anritsu	MT8821C	N/A	N/A
198917*	1GHz high-pass filter, 2W, Fhigh =18GHz	Micro-Tronics	HPM18129-02	2025-03-13	2026-03-31

NOTES:

1. * Testing is completed before equipment expiration date.
2. **Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Test Equipment Used - Radiated Disturbance Emissions Test Equipment (Morrisville – Chamber 2)

Equip. ID	Description	Manufacturer/Brand	Model Number	Last Cal.	Next Cal.
	1-18 GHz				
86408	Double-Ridged Waveguide Horn Antenna, 1 to 18 GHz	ETS Lindgren	3117	2025-07-15	2027-07-15
	Gain-Loss Chains				
91977	Gain-loss string: 1-18GHz	Various	Various	2025-05-31	2026-05-31
	Receiver & Software				
197955	Spectrum Analyzer	Rohde & Schwarz	ESW44	2025-07-29	2026-07-29
SOFTEMI	EMI Software	UL	Version 9.5 (18 Oct 2021)		
	Additional Equipment used				
239540	Environmental Meter	Fisher Scientific	15-077-963	2025-08-05	2027-08-05
213025	Wideband Radio Communications Tester	Rohde and Schwarz	CMW500	N/A	N/A
198917*	1GHz high-pass filter, 2W, Fhigh =18GHz	Micro-Tronics	HPM18129-02	2025-03-13	2026-03-31

NOTES:

1. * Testing is completed before equipment expiration date.
2. **Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Test Equipment Used - Radiated Disturbance Emissions Test Equipment (Morrisville – Chamber 1)

Equip. ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
	1-18 GHz				
88761	Double-Ridged Waveguide Horn Antenna, 1 to 18 GHz	ETS Lindgren	3117	2025-11-19	2027-11-19
	Gain-Loss Chains				
91979	Gain-loss string: 1-18GHz	Various	Various	2025-05-31	2026-05-31
	Receiver & Software				
206496	Spectrum Analyzer	Rohde & Schwarz	ESW44	2025-07-29	2026-07-29
SOFTEMI	EMI Software	UL	Version 9.5 (18 Oct 2021)		
	Additional Equipment used				
241205	Environmental Meter	Fisher Scientific	15-077-963	2025-08-05	2027-08-05

NOTES:

1. * Testing is completed before equipment expiration date.
2. **Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

Wireless Conducted Measurement Equipment.

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
	Additional Equipment used				
90411	Spectrum Analyzer MY54490314	Keysight Technologies	N9030A	2026-03-03	2027-03-03
90416	Spectrum Analyzer MY54490254	Keysight Technologies	N9030A	2025-07-31	2026-07-31
212967	Wideband Radio Communications Tester 170733	Rohde and Schwarz	CMW500	2026-02-13	2027-02-13
212166	Wideband Radio Communications Tester	Anritsu	MT8000A	2026-02-23	2027-02-23
*262469	Humidity and Temperature Probe	Control Company	15-077-963	2025-04-28	2026-04-30
211055	Real-Time Peak Power Sensor	Boonton	RTP5000	2025-07-30	2026-07-30

Test Equipment Used - Wireless Conducted Attenuators, Cables, and Couplers

Equipment ID	Description	Manufacturer	Model Number	Last Cal.	Next Cal.
	Attenuators				
226569	2.92mm Coaxial 10dB Attenuator 40GHz	Fairview Microwave	SA4014-10	2025-09-02	2026-09-02
226554*	20dB Attenuator	CentricRF	C18S2-20	2025-03-19 2026-04-01	2026-03-31 2027-04-01
226552*	20dB Attenuator	CentricRF	C18S2-20	2025-03-19 2026-04-01	2026-03-31 2027-04-01
	Cables				
246257	SMA Cable	Huber + Suhner	104PEA	2025-09-05	2026-09-05
	Couplers				
238018*	Ultra-Wideband Directional Coupler 0.5-18GHz	Mini-Circuits	ZUDC10-183+	2025-04-48	2026-04-30

NOTES:

- * Testing is completed before equipment expiration date.
- **Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

8. CONDUCTED TEST RESULTS

8.1. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049
ISED: RSS132

LIMITS

For reporting purposes only.

TEST PROCEDURE

ANSI C63.26:2015: Section 5.4

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The 99% and -26dB bandwidths were measured with the spectrum analyzer at the middle channel in each band.

RESULTS

There is no limit required and power is the same for low, middle and high channel; therefore, only middle channel was tested.

LTE BAND 5&26(FCC PART 90S)

Band	Mode	RB Allocation/RB Offset	f(MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE BAND 26 (90S)	1.4MHz, QPSK	6/0	819.0	1.103	1.359
	1.4MHz, 16QAM			1.107	1.426
	3MHz, QPSK	15/0		2.721	3.073
	3MHz, 16QAM			2.718	3.122
	5MHz, QPSK	25/0		4.521	5.091
	5MHz, 16QAM			4.521	5.159
	10MHz, QPSK	50/0		9.000	10.05
	10MHz, 16QAM			9.016	10.130
	10MHz, QPSK	1/0		0.271	0.4745

5G NR n5&n26 (FCC PART 90S)

Band	Mode	RB Allocation/RB Offset	f(MHz)	99% BW (MHz)	-26dB BW (MHz)
5G NR n26 (Part 90S)	5MHz, BPSK	25/0	819.0	4.5137	5.147
	5MHz, 16QAM			4.5331	5.232
	10MHz, BPSK	50/0		8.9778	9.853
	10MHz, 16QAM			9.0054	9.800
	10MHz. BPSK	1/0		0.23091	0.337


LTE BAND 5&26 (FCC PART 22)

Band	Mode	RB Allocation/RB Offset	f(MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE BAND 5&26	1.4MHz, QPSK	6/0	836.5	1.1003	1.370
	1.4MHz, 16QAM			1.1053	1.407
	3MHz, QPSK	15/0		2.7148	3.119
	3MHz, 16QAM			2.7180	3.062
	5MHz, QPSK	25/0		4.5147	5.211
	5MHz, 16QAM			4.5164	5.185
	10MHz, QPSK	50/0		9.0002	10.07
	10MHz, 16QAM			8.9983	10.09
	15MHz, QPSK	75/0		13.510	15.09
	15MHz, 16QAM			13.542	14.92
	10MHz, QPSK	1/0		0.2607	0.4364


5G NR n5&n26 (FCC PART 22)

Band	Mode	RB Allocation/RB Offset	f(MHz)	99% BW (MHz)	-26dB BW (MHz)
5G NR n5&n26 (FCC Part 22)	5MHz, BPSK	25/0	836.5	4.4923	5.053
	5MHz, 16QAM			4.5069	5.140
	10MHz, BPSK	50/0		8.9754	9.805
	10MHz, 16QAM			8.9997	9.889
	15MHz, BPSK	75/0		13.453	14.51
	15MHz, 16QAM			13.511	14.60
	20MHz, BPSK	100/0		17.955	19.19
	20MHz, 16QAM			17.915	19.31
	20MHz, BPSK	1/0		0.24523	0.4242


8.1.1. LTE BAND 26 (FCC PART 90S)




LTE B26 1.4MHz QPSK Middle Channel RB6-0




LTE B26 3MHz QPSK Middle Channel RB15-0



LTE B26 5MHz QPSK Middle Channel RB25-0



LTE B26 10MHz QPSK Middle Channel RB50-0




LTE B26 10MHz QPSK Middle Channel RB1-0

Intentionally Blank


8.1.2. 5G NR n26 (FCC PART 90S)




8.1.3. LTE BAND 5&26 (FCC PART 22)




LTE B26 1.4MHz QPSK Middle Channel RB6-0




LTE B26 3MHz QPSK Middle Channel RB15-0




LTE B26 5MHz QPSK Middle Channel RB25-0



LTE B26 10MHz QPSK Middle Channel RB50-0




LTE B26 10MHz QPSK Middle Channel RB1-0




LTE B26 15MHz QPSK Middle Channel RB75-0


8.1.4. 5G NR n5&n26 (FCC PART 22)




5G NR n26 5MHz BPSK Middle Channel RB25-0




5G NR n26 10MHz BPSK Middle Channel RB50-0



5G NR n26 15MHz BPSK Middle Channel RB75-0



5G NR n26 20MHz BPSK Middle Channel RB100-0



5G NR n26 20MHz Middle High Channel RB1-0

Intentionally Blank

8.2. EMISSION MASK AND ADJACENT CHANNEL POWER

LIMITS

FCC: §22.917 (a)

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

FCC: §90.691 Emission mask requirements for EA-based systems.

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

NOTE: According to 971168 D02 Misc Rev Approv License Devices v02r01, Section VIII (c):

For Section 90.691(a) compliance testing, use RBW = 300 Hz for offsets less than 37.5 kHz from a channel edge; RBW = 100 kHz for offsets greater than 37.5 kHz is allowed.

ISED: RSS132§5.5

Equipment shall meet the unwanted emission limits specified below:

- (i) In the first 1.0 MHz band immediately outside and adjacent to each of the sub-bands specified in Section 5.1, the power of emissions per any 1% of the occupied bandwidth shall be attenuated below the transmitter output power P (dBW) by at least $43 + 10 \log(p)$ dB.
- (ii) After the first 1.0 MHz immediately outside and adjacent to each of the sub-bands, the power of emissions in any 100 kHz bandwidth shall be attenuated below the transmitter output power P (dBW) by at least $43 + 10 \log(p)$ dB. If the measurement is performed using 1% of the occupied bandwidth, power integration over 100 kHz is required.

p is the output power specified in watts.

TEST PROCEDURE

For Spectrum Emission Mask plots, the spectrum analyzer is configured to sweep with a moving integration window, the width of which can be adjusted to different sizes across the sweep. The window width is configured to be greater than or equal to the required reference bandwidth. The center frequencies of the integration window for the different integration windows was set such that the upper and lower edges of the windows are aligned with the transition points in the reference bandwidths. This is achieved by setting the start / stop frequencies of the window with an offset equal to the reference bandwidth / 2 from the transition point.


The transmitter output was connected to a base station simulator and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

For each band edge measurement:


1. Set the spectrum analyzer span to include the block edge frequency.
2. Set a marker to point the corresponding band edge frequency in each test case.
3. Set display line at -13 dBm
4. Set resolution bandwidth to at least 1% of emission bandwidth.

RESULTS


8.2.1. LTE BAND 26 (FCC PART 90S)




LTE B26 1.4MHz QPSK Low Channel RB1-0




LTE B26 1.4MHz QPSK High Channel RB1-5




LTE B26 1.4MHz QPSK Low Channel RB6-0



LTE B26 1.4MHz QPSK High Channel RB6-0




LTE B26 3MHz QPSK Low Channel RB1-0




LTE B26 3MHz QPSK High Channel RB1-04






LTE B26 10MHz QPSK Middle Channel RB1-0




LTE B26 10MHz QPSK Middle Channel RB1-49



LTE B26 10MHz QPSK Middle Channel RB50-0

Intentionally Blank



8.2.3. LTE BAND 5&26 (FCC PART 22)

