

LTE Band 41 5MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K23557 Date: 06-20-16 Test Engineer: JH Park Configuration: EUT / X-Position Mode: LTE Band 41, QPSK , 5MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Ware house								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	2557.50	14.58	V	1.9	9.1	21.84	33.0	-11.2	
	2557.50	14.10	H	1.9	9.1	21.36	33.0	-11.6	
	Mid Ch								
	2605.00	13.89	V	1.9	10.4	22.38	33.0	-10.6	
	2605.00	13.83	H	1.9	10.4	22.32	33.0	-10.7	
	High Ch								
	2652.50	13.29	V	1.9	10.3	21.73	33.0	-11.3	
	2652.50	14.58	H	1.9	10.3	23.02	33.0	-10.0	
	Rev. 3.17.11								
	Note: For Band 4 EIRP limit is 30dBm								
LTE Band 41 5MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K23557 Date: 06-20-16 Test Engineer: JH Park Configuration: EUT / X-Position Mode: LTE Band 41 16QAM, 5MHz Test Equipment: Receiving: 3117[00168724] and Chamber 1 SMA Cables Substitution: 3115[00161451] Substitution, 3m SMA Cable Ware house								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	EIRP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBi)	(dBm)	(dBm)	(dB)	
	Low Ch								
	2557.50	14.09	V	1.9	9.1	21.35	33.0	-11.7	
	2557.50	13.48	H	1.9	9.1	20.74	33.0	-12.3	
	Mid Ch								
	2605.00	12.97	V	1.9	10.4	21.46	33.0	-11.5	
	2605.00	12.92	H	1.9	10.4	21.41	33.0	-11.6	
	High Ch								
	2652.50	12.25	V	1.9	10.3	20.69	33.0	-12.3	
	2652.50	13.14	H	1.9	10.3	21.58	33.0	-11.4	
	Rev. 3.17.11								
	Note: For Band 4 EIRP limit is 30dBm								

LTE Band 5

LTE

Band 5

10MHz

QPSK

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)

Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
829.00	14.23	V	1.1	-1.5	11.65	38.5	-26.8	
829.00	19.46	H	1.1	-1.5	16.88	38.5	-21.6	
Mid Ch								
836.50	14.30	V	1.1	-1.4	11.81	38.5	-26.6	
836.50	19.42	H	1.1	-1.4	16.93	38.5	-21.5	
High Ch								
844.00	13.81	V	1.1	-1.3	11.42	38.5	-27.0	
844.00	20.60	H	1.1	-1.3	18.18	38.5	-20.3	

Rev. 3.17.11

Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm

LTE

Band 5

10MHz

16QAM

High Frequency Substitution Measurement

UL Korea, Ltd. Suwon Laboratory Chamber 2

Company:

Project #:

Date:

Test Engineer:

Configuration:

Mode:

Test Equipment:

Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT)

Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Margin (dB)	Notes
Low Ch								
829.00	13.30	V	1.1	-1.5	10.72	38.5	-27.7	
829.00	18.49	H	1.1	-1.5	15.91	38.5	-22.5	
Mid Ch								
836.50	13.32	V	1.1	-1.4	10.81	38.5	-27.6	
836.50	18.32	H	1.1	-1.4	15.81	38.5	-22.6	
High Ch								
844.00	12.53	V	1.1	-1.3	10.11	38.5	-28.3	
844.00	20.24	H	1.1	-1.3	17.82	38.5	-20.6	

Rev. 3.17.11

Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm

LTE Band 5 5MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K23557 Date: 06-21-16 Test Engineer: YH Lim Configuration: EUT ONLY, X Position Mode: LTE5 5MHz FUND QPSK Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	826.50	15.31	V	1.1	-1.5	12.71	38.5	-25.7	
	826.50	18.93	H	1.1	-1.5	16.33	38.5	-22.1	
	Mid Ch								
	836.50	13.34	V	1.1	-1.4	10.85	38.5	-27.6	
	836.50	19.10	H	1.1	-1.4	16.61	38.5	-21.8	
	High Ch								
	846.50	12.93	V	1.6	-1.3	10.05	38.5	-28.4	
	846.50	18.48	H	1.6	-1.3	15.60	38.5	-22.8	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								
LTE Band 5 5MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2 Company: Samsung Project #: 16K23557 Date: 06-21-16 Test Engineer: YH Lim Configuration: EUT ONLY, X Position Mode: LTE5 5MHz FUND 16QAM Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	826.50	14.35	V	1.1	-1.5	11.75	38.5	-26.7	
	826.50	17.97	H	1.1	-1.5	15.37	38.5	-23.1	
	Mid Ch								
	836.50	12.32	V	1.1	-1.4	9.83	38.5	-28.6	
	836.50	18.05	H	1.1	-1.4	15.56	38.5	-22.9	
	High Ch								
	846.50	11.85	V	1.1	-1.3	9.47	38.5	-29.0	
	846.50	17.48	H	1.1	-1.3	15.10	38.5	-23.4	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								

LTE Band 5 3MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K23557 Date: 06-21-16 Test Engineer: YH Lim Configuration: EUT ONLY, X Position Mode: LTE5 3MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	825.50	15.15	V	1.1	-1.5	12.55	38.5	-25.9	
	825.50	21.44	H	1.1	-1.5	18.84	38.5	-19.6	
	Mid Ch								
	836.50	13.72	V	1.1	-1.4	11.23	38.5	-27.2	
	836.50	20.73	H	1.1	-1.4	18.24	38.5	-20.2	
	High Ch								
	847.50	11.65	V	1.6	-1.3	8.77	38.5	-29.7	
	847.50	20.83	H	1.6	-1.3	17.95	38.5	-20.5	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								
LTE Band 5 3MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K23557 Date: 06-21-16 Test Engineer: YH Lim Configuration: EUT ONLY, X Position Mode: LTE5 3MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	825.50	14.43	V	1.1	-1.5	11.83	38.5	-26.6	
	825.50	20.37	H	1.1	-1.5	17.77	38.5	-20.7	
	Mid Ch								
	836.50	12.66	V	1.1	-1.4	10.17	38.5	-28.3	
	836.50	19.71	H	1.1	-1.4	17.22	38.5	-21.2	
	High Ch								
	847.50	10.79	V	1.1	-1.3	8.41	38.5	-30.0	
	847.50	19.78	H	1.1	-1.3	17.40	38.5	-21.1	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								

LTE Band 5 1.4MHz QPSK	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K23557 Date: 06-21-16 Test Engineer: YH Lim Configuration: EUT ONLY, X Position Mode: LTE5 1.4MHz FUND QPSK								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.70	12.92	V	1.1	-1.5	10.32	38.5	-28.1	
	824.70	18.01	H	1.1	-1.5	15.41	38.5	-23.0	
	Mid Ch								
	836.50	12.34	V	1.1	-1.4	9.85	38.5	-28.6	
	836.50	18.14	H	1.1	-1.4	15.65	38.5	-22.8	
	High Ch								
	848.30	10.62	V	1.6	-1.3	7.74	38.5	-30.7	
	848.30	17.28	H	1.6	-1.3	14.40	38.5	-24.0	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								
LTE Band 5 1.4MHz 16QAM	High Frequency Substitution Measurement UL Korea, Ltd. Suwon Laboratory Chamber 2								
	Company: Samsung Project #: 16K23557 Date: 06-21-16 Test Engineer: YH Lim Configuration: EUT ONLY, X Position Mode: LTE5 1.4MHz FUND 16QAM								
	Test Equipment: Receiving: VULB9163-749, and 3m Chamber N-type Cable (Setup this one for testing EUT) Substitution: Dipole S/N: 00164753, 3m SMA Cable Warehouse.								
	f	SG reading	Ant. Pol.	Cable Loss	Antenna Gain	ERP	Limit	Margin	Notes
	MHz	(dBm)	(H/V)	(dB)	(dBd)	(dBm)	(dBm)	(dB)	
	Low Ch								
	824.70	11.88	V	1.1	-1.5	9.28	38.5	-29.2	
	824.70	16.69	H	1.1	-1.5	14.09	38.5	-24.4	
	Mid Ch								
	836.50	11.32	V	1.1	-1.4	8.83	38.5	-29.6	
	836.50	16.93	H	1.1	-1.4	14.44	38.5	-24.0	
	High Ch								
	848.30	9.60	V	1.1	-1.3	7.22	38.5	-31.2	
	848.30	16.24	H	1.1	-1.3	13.86	38.5	-24.6	
	Rev. 3.17.11 Note: For Band 13/17 ERP limit is 34.77dBm; For Band 26 limit is 50dBm								

11.2. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238 and §27. 53

LIMIT

Part 22.917(a) & Part 24.238(a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

Part 27: (m)(4) For mobile station, the attenuation factor shall be not less than $43 + 10 \log (P)$ dB at the channel edge and $(55 + 10 \log (P))$ dB at the 5.5 MHz from the channel edges.

TEST PROCEDURE

ANSI / TIA / EIA 603D Clause 2.2.12; ESU40 setting reference to 971168 D01 v02r02

For peak power measurement with a ESU40:

- a) Set the RBW = 100KHz for emission below 1GHz and 1MHz for emissions above 1GHz
- b) Set VBW $\geq 3 \times$ RBW;
- c) Set span ≥ 1.5 times the OBW;
- d) Sweep time = auto couple;
- e) Detector = peak;
- f) Ensure that the number of measurement points $\geq$ span/RBW;
- g) Trace mode = max hold;

RESULTS

GSM 1900

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		16K23557							
Date:		06-16-16							
Test Engineer:		JH Park							
Configuration:		EUT / AC Adapter, X Position							
Mode:		GPRS 1900							
Chamber			Pre-amplifier		Filter		Limit		
Chamber 2			AFS42		Filter 1		Part 24		
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.7004	-12.1	V	3.0	40.5	1.0	-51.6	-13.0	-38.6	
5.5506	-4.8	V	3.0	40.8	1.0	-44.6	-13.0	-31.6	
7.4008	-4.1	V	3.0	40.8	1.0	-43.8	-13.0	-30.8	
3.7000	-12.1	H	3.0	40.5	1.0	-51.6	-13.0	-38.6	
5.5506	-7.6	H	3.0	40.8	1.0	-47.4	-13.0	-34.4	
7.4008	-5.5	H	3.0	40.8	1.0	-45.3	-13.0	-32.3	
Mid Ch, 1880.0MHz									
3.7600	-13.2	V	3.0	40.5	1.0	-52.7	-13.0	-39.7	
5.6400	-6.5	V	3.0	40.8	1.0	-46.3	-13.0	-33.3	
7.5200	-3.9	V	3.0	40.7	1.0	-43.6	-13.0	-30.6	
3.7600	-14.4	H	3.0	40.5	1.0	-54.0	-13.0	-41.0	
5.6400	-8.7	H	3.0	40.8	1.0	-48.5	-13.0	-35.5	
7.5200	-4.9	H	3.0	40.7	1.0	-44.6	-13.0	-31.6	
High Ch, 1909.8 MHz									
3.8196	-13.8	V	3.0	40.6	1.0	-53.4	-13.0	-40.4	
5.7294	-3.3	V	3.0	40.8	1.0	-43.1	-13.0	-30.1	
7.6392	-3.1	V	3.0	40.7	1.0	-42.7	-13.0	-29.7	
3.8196	-15.8	H	3.0	40.6	1.0	-55.4	-13.0	-42.4	
5.7294	-7.1	H	3.0	40.8	1.0	-46.9	-13.0	-33.9	
7.6392	-2.8	H	3.0	40.7	1.0	-42.4	-13.0	-29.4	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		16K23557							
Date:		06-16-16							
Test Engineer:		JH Park							
Configuration:		EUT / AC Adapter, X Position							
Mode:		EGPRS 1900 MHz							
Chamber			Pre-amplifier		Filter		Limit		
Chamber 2			AFS42		Filter 1		Part 24		
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3.7004	-18.3	V	3.0	40.5	1.0	-57.8	-13.0	-44.8	
5.5506	-9.9	V	3.0	40.8	1.0	-49.8	-13.0	-36.8	
7.4008	-9.7	V	3.0	40.8	1.0	-49.5	-13.0	-36.5	
3.7000	-18.5	H	3.0	40.5	1.0	-58.0	-13.0	-45.0	
5.5500	-11.0	H	3.0	40.8	1.0	-50.8	-13.0	-37.8	
7.4000	-10.6	H	3.0	40.8	1.0	-50.4	-13.0	-37.4	
Mid Ch, 1880.0MHz									
3.7600	-15.4	V	3.0	40.5	1.0	-54.9	-13.0	-41.9	
5.6400	-11.8	V	3.0	40.8	1.0	-51.6	-13.0	-38.6	
7.5200	-8.8	V	3.0	40.7	1.0	-48.6	-13.0	-35.6	
3.7600	-15.9	H	3.0	40.5	1.0	-55.4	-13.0	-42.4	
5.6400	-12.4	H	3.0	40.8	1.0	-52.2	-13.0	-39.2	
7.5200	-9.0	H	3.0	40.7	1.0	-48.7	-13.0	-35.7	
High Ch, 1909.8 MHz									
3.8196	-12.8	V	3.0	40.6	1.0	-52.4	-13.0	-39.4	
5.7294	-10.9	V	3.0	40.8	1.0	-50.7	-13.0	-37.7	
7.6392	-7.7	V	3.0	40.7	1.0	-47.4	-13.0	-34.4	
3.8196	-14.9	H	3.0	40.6	1.0	-54.5	-13.0	-41.5	
5.7294	-12.6	H	3.0	40.8	1.0	-52.4	-13.0	-39.4	
7.6392	-7.7	H	3.0	40.7	1.0	-47.4	-13.0	-34.4	
Rev. 03.03.09 Note: No other emissions were detected above the system noise floor.									

WCDMA Band 5

WCDMA
Band 5
REL99

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		16K23557							
Date:		06-10-16							
Test Engineer:		YH Lim							
Configuration:		EUT / AC Adapter, X Position							
Mode:		Tx, REL99,850MHz							
Chamber		Pre-amplifier		Filter		Limit			
Chamber 2		AFS42		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.40MHz									
1.6520	-19.7	V	3.0	39.1	1.0	-57.8	-13.0	-44.8	
2.4790	-16.3	V	3.0	39.5	1.0	-54.8	-13.0	-41.8	
3.3056	-16.5	V	3.0	40.1	1.0	-55.6	-13.0	-42.6	
1.6520	-17.1	H	3.0	39.1	1.0	-55.2	-13.0	-42.2	
2.4790	-14.6	H	3.0	39.5	1.0	-53.1	-13.0	-40.1	
3.3056	-16.6	H	3.0	40.1	1.0	-55.7	-13.0	-42.7	
Mid Ch, 836.6MHz									
1.6732	-18.2	V	3.0	39.1	1.0	-56.3	-13.0	-43.3	
2.5098	-17.3	V	3.0	39.5	1.0	-55.8	-13.0	-42.8	
3.3464	-16.4	V	3.0	40.1	1.0	-55.5	-13.0	-42.5	
1.6732	-15.8	H	3.0	39.1	1.0	-53.9	-13.0	-40.9	
2.5098	-13.9	H	3.0	39.5	1.0	-52.4	-13.0	-39.4	
3.3464	-16.6	H	3.0	40.1	1.0	-55.7	-13.0	-42.7	
High Ch, 846.6MHz									
1.6932	-19.1	V	3.0	39.1	1.0	-57.2	-13.0	-44.2	
2.5390	-16.1	V	3.0	39.6	1.0	-54.6	-13.0	-41.6	
3.3860	-16.0	V	3.0	40.2	1.0	-55.2	-13.0	-42.2	
1.6932	-19.9	H	3.0	39.1	1.0	-58.1	-13.0	-45.1	
2.5390	-11.4	H	3.0	39.6	1.0	-50.0	-13.0	-37.0	
3.3860	-16.4	H	3.0	40.2	1.0	-55.6	-13.0	-42.6	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

WCDMA
Band 5
HSDPA

UL Korea, Ltd Suwon Laboratory Above 1GHz High Frequency Substitution Measurement									
Company:		Samsung							
Project #:		16K23557							
Date:		06-10-16							
Test Engineer:		YH Lim							
Configuration:		EUT / AC Adapter, X Position							
Mode:		Tx, HSDPA,850MHz							
Chamber		Pre-amplifier		Filter		Limit			
Chamber 2		AFS42		Filter 1		Part 22			
f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.40MHz									
1.6520	-19.8	V	3.0	39.1	1.0	-57.9	-13.0	-44.9	
2.4790	-16.5	V	3.0	39.5	1.0	-55.0	-13.0	-42.0	
3.3056	-16.6	V	3.0	40.1	1.0	-55.7	-13.0	-42.7	
1.6520	-18.0	H	3.0	39.1	1.0	-56.1	-13.0	-43.1	
2.4790	-16.0	H	3.0	39.5	1.0	-54.5	-13.0	-41.5	
3.3056	-16.6	H	3.0	40.1	1.0	-55.7	-13.0	-42.7	
Mid Ch, 836.6MHz									
1.6732	-18.2	V	3.0	39.1	1.0	-56.3	-13.0	-43.3	
2.5098	-18.3	V	3.0	39.5	1.0	-56.8	-13.0	-43.8	
3.3464	-16.4	V	3.0	40.1	1.0	-55.6	-13.0	-42.6	
1.6732	-17.7	H	3.0	39.1	1.0	-55.8	-13.0	-42.8	
2.5098	-16.9	H	3.0	39.5	1.0	-55.4	-13.0	-42.4	
3.3464	-16.7	H	3.0	40.1	1.0	-55.9	-13.0	-42.9	
High Ch, 846.6MHz									
1.6932	-19.2	V	3.0	39.1	1.0	-57.3	-13.0	-44.3	
2.5390	-16.5	V	3.0	39.6	1.0	-55.0	-13.0	-42.0	
3.3860	-16.1	V	3.0	40.2	1.0	-55.2	-13.0	-42.2	
1.6932	-19.7	H	3.0	39.1	1.0	-57.8	-13.0	-44.8	
2.5390	-16.7	H	3.0	39.6	1.0	-55.3	-13.0	-42.3	
3.3860	-16.5	H	3.0	40.2	1.0	-55.7	-13.0	-42.7	
Rev. 03.03.09									
Note: No other emissions were detected above the system noise floor.									

WCDMA Band 2

WCDMA

Band 2

REL99

UL Korea, Ltd Suwon Laboratory

Above 1GHz High Frequency Substitution Measurement

Company: Samsung

Project #: 16K23557

Date: 06-13-16

Test Engineer: YH Lim

Configuration: EUT / AC Adapter, X Position

Mode: Tx, REL99, 1900MHz

Chamber

Pre-amplifier

Filter

Limit

Chamber 2

AFS42

Filter 1

Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.7048	-12.2	V	3.0	40.5	1.0	-51.7	-13.0	-38.7	
5.5572	-11.1	V	3.0	40.8	1.0	-51.0	-13.0	-38.0	
7.4096	-8.7	V	3.0	40.8	1.0	-48.5	-13.0	-35.5	
3.7048	-12.7	H	3.0	40.5	1.0	-52.2	-13.0	-39.2	
5.5572	-11.3	H	3.0	40.8	1.0	-51.1	-13.0	-38.1	
7.4096	-8.2	H	3.0	40.8	1.0	-48.0	-13.0	-35.0	
Mid Ch, 1880MHz									
3.7600	-11.3	V	3.0	40.5	1.0	-50.8	-13.0	-37.8	
5.6400	-9.0	V	3.0	40.8	1.0	-48.8	-13.0	-35.8	
7.5200	-8.4	V	3.0	40.7	1.0	-48.2	-13.0	-35.2	
3.7600	-13.3	H	3.0	40.5	1.0	-52.9	-13.0	-39.9	
5.6400	-11.2	H	3.0	40.8	1.0	-51.0	-13.0	-38.0	
7.5200	-7.5	H	3.0	40.7	1.0	-47.2	-13.0	-34.2	
High Ch, 1907.6MHz									
3.8152	-4.6	V	3.0	40.6	1.0	-44.2	-13.0	-31.2	
5.7228	-7.0	V	3.0	40.8	1.0	-46.8	-13.0	-33.8	
7.6304	-5.8	V	3.0	40.7	1.0	-45.4	-13.0	-32.4	
3.8152	-9.7	H	3.0	40.6	1.0	-49.3	-13.0	-36.3	
5.7228	-9.4	H	3.0	40.8	1.0	-49.2	-13.0	-36.2	
7.6304	-4.4	H	3.0	40.7	1.0	-44.1	-13.0	-31.1	

Rev. 03.03.09

Note: No other emissions were detected above the system noise floor.

WCDMA

Band 2

HSDPA

UL Korea, Ltd Suwon Laboratory

Above 1GHz High Frequency Substitution Measurement

Company: Samsung

Project #: 16K23557

Date: 06-13-16

Test Engineer: YH Lim

Configuration: EUT / AC Adapter, X Position

Mode: Tx, HSDPA, 1900MHz

Chamber

Pre-amplifier

Filter

Limit

Chamber 2

AFS42

Filter 1

Part 24

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3.7048	-12.2	V	3.0	40.5	1.0	-51.7	-13.0	-38.7	
5.5572	-11.2	V	3.0	40.8	1.0	-51.1	-13.0	-38.1	
7.4096	-8.9	V	3.0	40.8	1.0	-48.7	-13.0	-35.7	
3.7048	-13.4	H	3.0	40.5	1.0	-52.9	-13.0	-39.9	
5.5572	-11.7	H	3.0	40.8	1.0	-51.6	-13.0	-38.6	
7.4096	-9.0	H	3.0	40.8	1.0	-48.8	-13.0	-35.8	
Mid Ch, 1880MHz									
3.7600	-11.4	V	3.0	40.5	1.0	-50.9	-13.0	-37.9	
5.6400	-9.6	V	3.0	40.8	1.0	-49.4	-13.0	-36.4	
7.5200	-8.8	V	3.0	40.7	1.0	-48.5	-13.0	-35.5	
3.7600	-13.4	H	3.0	40.5	1.0	-53.0	-13.0	-40.0	
5.6400	-11.1	H	3.0	40.8	1.0	-50.9	-13.0	-37.9	
7.5200	-8.1	H	3.0	40.7	1.0	-47.8	-13.0	-34.8	
High Ch, 1907.6MHz									
3.8152	-5.4	V	3.0	40.6	1.0	-45.0	-13.0	-32.0	
5.7228	-7.6	V	3.0	40.8	1.0	-47.4	-13.0	-34.4	
7.6304	-6.9	V	3.0	40.7	1.0	-46.5	-13.0	-33.5	
3.8152	-10.1	H	3.0	40.6	1.0	-49.7	-13.0	-36.7	
5.7228	-8.8	H	3.0	40.8	1.0	-48.6	-13.0	-35.6	
7.6304	-6.2	H	3.0	40.7	1.0	-45.8	-13.0	-32.8	

Rev. 03.03.09

Note: No other emissions were detected above the system noise floor.

LTE

Band 41

15MHz

QPSK

Chamber

Chamber 2

Pre-amplifier

AFS42

Filter

Filter 1

Limit

FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-9.9	V	3.0	40.9	1.0	-49.8	-25.0	-24.8	
7.6875	-10.3	V	3.0	40.6	1.0	-50.0	-25.0	-25.0	
10.2500	0.7	V	3.0	39.5	1.0	-37.8	-25.0	-12.8	
5.1250	-10.4	H	3.0	40.9	1.0	-50.3	-25.0	-25.3	
7.6875	-10.5	H	3.0	40.6	1.0	-50.2	-25.0	-25.2	
10.2500	-7.1	H	3.0	39.5	1.0	-45.6	-25.0	-20.6	
Mid Ch, (2605 MHz)									
5.2100	0.7	V	3.0	40.9	1.0	-39.2	-25.0	-14.2	
7.8150	-10.8	V	3.0	40.6	1.0	-50.4	-25.0	-25.4	
10.4200	2.5	V	3.0	39.4	1.0	-35.8	-25.0	-10.8	
5.2100	-4.4	H	3.0	40.9	1.0	-44.3	-25.0	-19.3	
7.8150	-9.7	H	3.0	40.6	1.0	-49.2	-25.0	-24.2	
10.4200	-2.9	H	3.0	39.4	1.0	-41.3	-25.0	-16.3	
High Ch, (2647.5 MHz)									
5.2950	-4.4	V	3.0	40.9	1.0	-44.3	-25.0	-19.3	
7.9425	-11.3	V	3.0	40.5	1.0	-50.8	-25.0	-25.8	
10.5900	-5.2	V	3.0	39.3	1.0	-43.4	-25.0	-18.4	
5.2950	-4.2	H	3.0	40.9	1.0	-44.0	-25.0	-19.0	
7.9425	-11.2	H	3.0	40.5	1.0	-50.7	-25.0	-25.7	
10.5900	-8.7	H	3.0	39.3	1.0	-47.0	-25.0	-22.0	

Rev. 03.03.09

Note: No other emissions were detected above the system noise floor.

LTE

Band 41

15MHz

16QAM

Chamber

Chamber 2

Pre-amplifier

AFS42

Filter

Filter 1

Limit

FCC Part 27

f GHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, (2562.5 MHz)									
5.1250	-10.0	V	3.0	40.9	1.0	-49.9	-25.0	-24.9	
7.6875	-11.1	V	3.0	40.6	1.0	-50.7	-25.0	-25.7	
10.2500	0.3	V	3.0	39.5	1.0	-38.2	-25.0	-13.2	
5.1250	-11.0	H	3.0	40.9	1.0	-50.9	-25.0	-25.9	
7.6875	-10.3	H	3.0	40.6	1.0	-49.9	-25.0	-24.9	
10.2500	-7.0	H	3.0	39.5	1.0	-45.5	-25.0	-20.5	
Mid Ch, (2605 MHz)									
5.2100	1.0	V	3.0	40.9	1.0	-38.9	-25.0	-13.9	
7.8150	-10.4	V	3.0	40.6	1.0	-49.9	-25.0	-24.9	
10.4200	2.6	V	3.0	39.4	1.0	-35.8	-25.0	-10.8	
5.2100	-5.1	H	3.0	40.9	1.0	-45.0	-25.0	-20.0	
7.8150	-9.2	H	3.0	40.6	1.0	-48.7	-25.0	-23.7	
10.4200	-3.2	H	3.0	39.4	1.0	-41.6	-25.0	-16.6	
High Ch, (2647.5 MHz)									
5.2950	-3.1	V	3.0	40.9	1.0	-43.0	-25.0	-18.0	
7.9425	-11.0	V	3.0	40.5	1.0	-50.5	-25.0	-25.5	
10.5900	-4.5	V	3.0	39.3	1.0	-42.7	-25.0	-17.7	
5.2950	-3.0	H	3.0	40.9	1.0	-42.8	-25.0	-17.8	
7.9425	-11.9	H	3.0	40.5	1.0	-51.3	-25.0	-26.3	
10.5900	-8.5	H	3.0	39.3	1.0	-46.8	-25.0	-21.8	

Rev. 03.03.09

Note: No other emissions were detected above the system noise floor.

