

FCC LTE REPORT

FCC Certification

Applicant Name:
SAMSUNG Electronics Co., Ltd.**Date of Issue:**

June 29, 2017

Location:

HCT CO., LTD.,

Address:129, Samsung-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Rep. of Korea74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA**Report No.:** HCT-R-1706-F058-2**HCT FRN:** 0005866421**FCC ID:** A3LSMG1650**APPLICANT:** SAMSUNG Electronics Co., Ltd.**FCC Model(s):** SM-G1650**EUT Type:** Mobile Phone**FCC Classification:** Licensed Portable Transmitter Held to Ear (PCE)**FCC Rule Part(s):** §2 , §27

Mode (MHz)	Tx Frequency (MHz)	Emission Designator	Modulation	EIRP	
				Max. Power (W)	Max. Power (dBm)
LTE – Band38 / 41 (5)	2557.5 – 2652.5	4M50G7D	QPSK	0.286	24.57
		4M50W7D	16QAM	0.201	23.03
LTE – Band38 / 41 (10)	2560.0 – 2650.0	8M95G7D	QPSK	0.277	24.42
		8M96W7D	16QAM	0.200	23.02
LTE – Band38 / 41 (15)	2562.5 – 2647.5	13M4G7D	QPSK	0.243	23.86
		13M4W7D	16QAM	0.179	22.54
LTE – Band38 / 41 (20)	2565.0 – 2645.0	17M9G7D	QPSK	0.238	23.76
		17M9W7D	16QAM	0.176	22.46

The measurements shown in this report were made in accordance with the procedures specified in CFR47 section §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S. C. 853(a)

**Report prepared by : Kwon Jeong**
Engineer of Telecommunication Testing Center**Report approved by : Jong Seok Lee**
Manager of Telecommunication Testing Center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-R-1706-F058	June 15, 2017	- First Approval Report
HCT-R-1706-F058-1	June 27, 2017	- Added the LTE Band 38 in the report. - Added the channel edge of LTE Band 38.
HCT-R-1706-F058-2	June 29, 2017	- Removed the Tx Frequency(LTE 38) on page 1. - Revised the general information on page 4.

Table of Contents

1. GENERAL INFORMATION	4
2. INTRODUCTION	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY	5
3. DESCRIPTION OF TESTS.....	6
3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	6
3.2 OCCUPIED BANDWIDTH.	7
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	8
3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	9
4. LIST OF TEST EQUIPMENT	10
5. MEASUREMENT UNCERTAINTY	11
6. SUMMARY OF TEST RESULTS	12
7. SAMPLE CALCULATION	13
8. TEST DATA	15
8.1 EQUIVALENT ISOTROPIC RADIATED POWER (Band 38/41)	15
8.2 RADIATED SPURIOUS EMISSIONS	17
8.2.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 38/41 LTE)	17
8.2.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 38/41 LTE)	18
8.2.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 38/41 LTE)	19
8.2.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 38/41 LTE)	20
8.3 OCCUPIED BANDWIDTH	21
8.4 CONDUCTED SPURIOUS EMISSIONS	22
8.4.1 CHANNEL EDGE	23
8.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE	25
8.5.1 FREQUENCY STABILITY (5 MHz Band 38/41 LTE)	25
8.5.2 FREQUENCY STABILITY (10 MHz Band 38/41 LTE)	26
8.5.3 FREQUENCY STABILITY (15 MHz Band 38/41 LTE)	27
8.5.4 FREQUENCY STABILITY (20 MHz Band 38/41 LTE)	28
9. TEST PLOTS.....	29

MEASUREMENT REPORT

1. GENERAL INFORMATION

Applicant Name:	SAMSUNG Electronics Co., Ltd.
Address:	129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
FCC ID:	A3LSMG1650
Application Type:	Certification
FCC Classification:	Licensed Portable Transmitter Held to Ear (PCE)
FCC Rule Part(s):	§2 , §27
EUT Type:	Mobile Phone
FCC Model(s):	SM-G1650
LTE Band 38/41	2557.5 MHz – 2652.5 MHz
Tx Frequency:	2560.0 MHz – 2650.0 MHz 2562.5 MHz – 2647.5 MHz 2565.0 MHz – 2645.0 MHz
Max. RF Output Power:	Band 38 / 41 (5 MHz) : 0.286 W (QPSK) (24.57 dBm) 0.201 W (16-QAM) (23.03 dBm) Band 38 / 41 (10 MHz) : 0.277 W (QPSK) (24.42 dBm) 0.200 W (16-QAM) (23.02 dBm) Band 38 / 41 (15 MHz) : 0.243 W (QPSK) (23.86 dBm) 0.179 W (16-QAM) (22.54 dBm) Band 38 / 41 (20 MHz) : 0.238 W (QPSK) (23.76 dBm) 0.176 W (16-QAM) (22.46 dBm)
Emission Designator(s):	Band 38 / 41 (5 MHz) : 4M50G7D (QPSK) / 4M50W7D (16-QAM) Band 38 / 41 (10 MHz) : 8M95G7D (QPSK) / 8M96W7D (16-QAM) Band 38 / 41 (15 MHz) : 13M4G7D (QPSK) / 13M4W7D (16-QAM) Band 38 / 41 (20 MHz) : 17M9G7D (QPSK) / 17M9W7D (16-QAM)
Date(s) of Tests:	May 09, 2017 ~ June 27, 2017
Test Information:	LTE Band 41(2550 - 2655 MHz) overlaps the entire frequency range of LTE Band 38 (2570 - 2620 MHz). Therefore, test data provided in this report covers Band 41 as well as Band 38.

2. INTRODUCTION

2.1. EUT DESCRIPTION

The SAMSUNG Electronics Co., Ltd. SM-G1650 Mobile Phone consists of LTE Band 38 and 41.

2.2. MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

2.3. TEST FACILITY

The Fully-anechoic chamber and conducted measurement facility used to collect the radiated data are located at the **74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.**

3. DESCRIPTION OF TESTS

3.1 EIRP RADIATED POWER AND RADIATED SPURIOUS EMISSIONS

Note: EIRP(Equivalent Isotropic Radiated Power)

Test Procedure

Radiated emission measurements are performed in the Fully-anechoic chamber. The equipment under test is placed on a non-conductive table 3-meters away from the receive antenna in accordance with ANSI/TIA-603-D-2010 Clause 2.2.17. The turntable is rotated through 360 degrees, and the receiving antenna scans in order to determine the level of the maximized emission. The level and position of the maximized emission is recorded with the spectrum analyzer using RMS detector.

A half wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator and the previously recorded signal was duplicated.

The power is calculated by the following formula;

$$P_{d(dBm)} = P_{g(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dB)}$$

Where: P_d is the dipole equivalent power and P_g is the generator output power into the substitution antenna.


The maximum EIRP is calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps are repeated with the receiving antenna in both vertical and horizontal polarization. the difference between the gain of the horn and an isotropic antenna are taken into consideration

Radiated spurious emissions

1. Frequency Range : 9 kHz ~ 10th Harmonics of highest channel fundamental frequency.
2. Measured distance : 30 MHz ~ 11 GHz at 3 m
11 GHz ~ 27 GHz at 1m
3. The EUT was setup to maximum output power.
4. The high, low and a middle channel were tested for out of band measurements.

3.2 OCCUPIED BANDWIDTH.

Test set-up



(Configuration of conducted Emission measurement)

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

Test Procedure

OBW is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 4.2.

The EUT makes a call to the communication simulator. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels(low, middle and high operational range.)

The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth

3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

Test Procedure

Spurious and harmonic emissions at antenna terminal is tested in accordance with KDB971168 D01 Power Meas License Digital Systems v02r02, October 17, 2014, Section 6.0.


The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power. The 1 MHz RBW was used to scan from 30 MHz to 26.5 GHz. And limit is -25 dBm. The high, low and a middle channel were tested for out of band measurements.

- Channel Edge Requirement : In the 1MHz bands immediately outside and adjacent to the channel, a resolution bandwidth of at least 2 % of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit is -10 dBm on all frequencies between the channel edge and 5 MHz from the channel edge, -13 dBm on all frequencies between 5 MHz and X MHz from the channel edge, -25 dBm on all frequencies more than X MHz from channel edge, where X is the greater of 6 MHz or the actual emission bandwidth. In addition, the attenuation factor shall not be less than -13 dBm on all frequencies between 2490.5 MHz and 2496 MHz and -25 dBm at below 2490.5 MHz.

3.4 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

Test Set-up



* Nominal Operating Voltage

Test Procedure

Frequency stability is tested in accordance with ANSI/TIA-603-D-2010 section 2.2.2.

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 100 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

NOTE: The EUT is tested down to the battery endpoint.

4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Date	Calibration Interval	Calibration Due
REOHDE & SCHWARZ	SCU 18 / AMPLIFIER	10094	04/24/2017	Annual	04/24/2018
Wainwright	WHK1.2/15G-10EF/H.P.F	4	04/10/2017	Annual	04/10/2018
Wainwright	WHK3.3/18G-10EF/H.P.F	2	04/10/2017	Annual	04/10/2018
Hewlett Packard	11667B / Power Splitter	10545	02/15/2017	Annual	02/15/2018
Hewlett Packard	11667B / Power Splitter	11275	05/04/2017	Annual	05/04/2018
Agilent	E3632A/DC Power Supply	KR75303243	07/12/2016	Annual	07/12/2017
Schwarzbeck	UHAP/ Dipole Antenna	557	03/31/2017	Biennial	03/31/2019
Schwarzbeck	UHAP/ Dipole Antenna	558	03/31/2017	Biennial	03/31/2019
ESPEC	SU-642 / Chamber	0093008124	03/31/2017	Annual	03/31/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna	147	09/09/2016	Biennial	09/09/2018
Schwarzbeck	BBHA 9120D/ Horn Antenna	1298	10/14/2016	Biennial	10/14/2018
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170342	04/25/2017	Biennial	04/25/2019
Schwarzbeck	BBHA 9170/ Horn Antenna(15~40GHz)	BBHA9170124	04/25/2017	Biennial	04/25/2019
Agilent	N9020A/Signal Analyzer	MY51110074	11/28/2016	Annual	11/28/2017
Hewlett Packard	8493C/ATTENUATOR	17280	06/22/2017	Annual	06/22/2018
REOHDE & SCHWARZ	FSV40-N/Spectrum Analyzer	101068-SZ	09/23/2016	Annual	09/23/2017
Agilent	8960 (E5515C)/ Base Station	MY48360800	10/19/2016	Annual	10/19/2017
Schwarzbeck	FMZB1513/ Loop Antenna(9kHz~30MHz)	1513-175	04/06/2017	Biennial	04/06/2019
Schwarzbeck	VULB9160/ Bilog Antenna	3150	09/30/2016	Biennial	09/30/2018
Schwarzbeck	VULB9160/ Bilog Antenna	3368	10/14/2016	Biennial	10/14/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6200863156	02/15/2017	Annual	02/15/2018
Anritsu Corp.	MT8820C/Wideband Radio Communication Tester	6201026545	02/13/2017	Annual	02/13/2018
REOHDE & SCHWARZ	SMB100A/ SIGNAL GENERATOR (100kHz~40GHz)	177633	07/18/2016	Annual	07/18/2017

5. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4:2014.

All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty ($\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	6.07

6. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 27.53(m)(4)	Channel Edge / Conducted Spurious Emissions.	$< 40 + 10\log_{10} (P[\text{Watts}])$ at Channel edges $< 43 + 10\log_{10} (P[\text{Watts}])$ between 5 and X MHz from Channel edges $< 55 + 10\log_{10} (P[\text{Watts}])$ beyond X MHz beyond from Channel edges		PASS
2.1046	Conducted Output Power (See note1)	N/A		PASS
2.1055, 27.54	Frequency stability	Emission must remain in band		PASS
27.50(h)(2)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1053, 27.53(m)(4)	Undesirable Emissions	$< 40 + 10\log_{10} (P[\text{Watts}])$ at Channel edges $< 43 + 10\log_{10} (P[\text{Watts}])$ between 5 and X MHz from Channel edges $< 55 + 10\log_{10} (P[\text{Watts}])$ beyond X MHz beyond from Channel edges		PASS

Note:

1. See SAR Report.

7. SAMPLE CALCULATION

A. EIRP Sample Calculation

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain (dBi)	C.L	Pol.	Limit	EIRP	
	channel	Freq.(MHz)						W	W	dBm
LTE Band 38/41	40740	2605.0	-30.45	5.33	10.72	1.62	V	< 2.00	0.028	14.43

$$\text{EIRP} = \text{Substitute LEVEL(dBm)} + \text{Ant. Gain} - \text{CL(Cable Loss)}$$

- 1) The EUT mounted on a wooden tripod is 2.5 meter above test site ground level.
- 2) During the test , the turn table is rotated until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of Equivalent Isotropic Radiated Power (**EIRP**).

B. Emission Designator

QPSK Modulation

5 MHz Bandwidth

Emission Designator = 4M50G7D

LTE BW = 4.50 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

10 MHz Bandwidth

Emission Designator = 8M95G7D

LTE BW = 8.95 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

15 MHz Bandwidth

Emission Designator = 13M5G7D

LTE BW = 13.47 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

20 MHz Bandwidth

Emission Designator = 18M0G7D

LTE BW = 18.03 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

16QAM Modulation

5 MHz Bandwidth

Emission Designator = 4M51W7D

LTE BW = 4.51 MHz

W = main carrier modulated in a combination of two or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

10 MHz Bandwidth

Emission Designator = 8M94W7D

LTE BW = 8.94 MHz

W = main carrier modulated in a combination of two or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

15 MHz Bandwidth

Emission Designator = 13M5W7D

LTE BW = 13.47MHz

W = main carrier modulated in a combination of two or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

20 MHz Bandwidth

Emission Designator = 18M0W7D

LTE BW = 18.03 MHz

W = main carrier modulated in a combination of two or more of the following modes;

amplitude, angle, pulse

7 = Quantized/Digital Info

D = Data transmission; telemetry; telecommand

8. TEST DATA

8.1 EQUIVALENT ISOTROPIC RADIATED POWER (Band 38/41)

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2557.5	5 MHz	QPSK	-21.24	14.77	10.99	2.39	H	< 2.00	0.217	23.37
		16-QAM	-22.66	13.35	10.99	2.39	H		0.157	21.95
2605.0		QPSK	-20.81	15.22	11.03	2.40	H		0.243	23.85
		16-QAM	-22.50	13.53	11.03	2.40	H		0.164	22.16
2652.5		QPSK	-20.15	15.93	11.07	2.43	H		0.286	24.57
		16-QAM	-21.69	14.39	11.07	2.43	H		0.201	23.03

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2560.0	10 MHz	QPSK	-21.14	14.94	11.00	2.39	H	< 2.00	0.226	23.55
		16-QAM	-22.39	13.69	11.00	2.39	H		0.170	22.30
2605.0		QPSK	-20.67	15.36	11.03	2.40	H		0.251	23.99
		16-QAM	-22.28	13.75	11.03	2.40	H		0.173	22.38
2650.0		QPSK	-20.30	15.78	11.07	2.43	H		0.277	24.42
		16-QAM	-21.70	14.38	11.07	2.43	H		0.200	23.02

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2562.5	15 MHz	QPSK	-20.90	15.12	11.00	2.39	H	< 2.00	0.236	23.73
		16-QAM	-22.49	13.53	11.00	2.39	H		0.164	22.14
2605.0		QPSK	-20.88	15.15	11.03	2.40	H		0.239	23.78
		16-QAM	-22.45	13.58	11.03	2.40	H		0.166	22.21
2647.5		QPSK	-20.86	15.22	11.07	2.43	H		0.243	23.86
		16-QAM	-22.18	13.90	11.07	2.43	H		0.179	22.54

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

Freq (MHz)	Bandwidth	Modulation	Measured Level (dBm)	Substitute Level (dBm)	Ant. Gain(dBi)	C.L	Pol	Limit	EIRP	
								W	W	dBm
2565.0	20 MHz	QPSK	-21.22	14.75	11.00	2.39	H	< 2.00	0.217	23.36
		16-QAM	-22.43	13.54	11.00	2.39	H		0.164	22.15
2605.0		QPSK	-21.12	14.91	11.03	2.40	H		0.226	23.54
		16-QAM	-22.63	13.40	11.03	2.40	H		0.160	22.03
2645.0		QPSK	-20.96	15.12	11.07	2.43	H		0.238	23.76
		16-QAM	-22.26	13.82	11.07	2.43	H		0.176	22.46

Note: All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method

according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:

The EUT was placed on a non-conductive styrofoam resin table 3-meters from the receive antenna. Turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For LTE signals, RBW = 1-5% of the OBW, not to exceed 1MHz, VBW $\geq 3 \times$ RBW, Detector = RMS. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is z plane in LTE mode. Also worst case of detecting Antenna is horizontal polarization in LTE mode.

8.2 RADIATED SPURIOUS EMISSIONS

8.2.1 RADIATED SPURIOUS EMISSIONS (5 MHz Band 38/41 LTE)

- OPERATING FREQUENCY : 2652.50 MHz
- MEASURED OUTPUT POWER: 24.57 dBm = 0.286 W
- MODULATION SIGNAL: 5 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 49.57 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40265 (2557.5)	5,115.00	-39.46	12.74	-51.69	3.44	H	-42.39	66.96
	7,672.50	-43.76	11.59	-51.65	4.25	H	-44.31	68.88
	10,230.00	-45.68	10.89	-49.85	5.08	V	-44.04	68.61
	15,345.00	-58.42	15.14	-62.65	6.29	H	-53.80	78.37
40740 (2605.0)	5,210.00	-33.59	12.88	-47.07	3.48	H	-37.67	62.24
	7,815.00	-44.80	11.50	-53.16	4.24	H	-45.90	70.47
	10,420.00	-49.61	10.78	-52.35	5.07	V	-46.64	71.21
41215 (2652.5)	5,305.00	-32.34	13.01	-46.73	3.51	H	-37.23	61.80
	7,957.50	-42.43	11.37	-49.03	4.37	H	-42.03	66.60
	10,610.00	-42.32	10.72	-45.62	5.14	V	-40.04	64.61

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.2.2 RADIATED SPURIOUS EMISSIONS (10 MHz Band 38/41 LTE)

- OPERATING FREQUENCY : 2650.00 MHz
- MEASURED OUTPUT POWER: 24.42 dBm = 0.277 W
- MODULATION SIGNAL: 10 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 49.42 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40290 (2560.0)	5,120.00	-38.44	12.57	-50.24	3.44	H	-41.11	65.53
	7,680.00	-47.02	11.58	-55.34	4.26	H	-48.02	72.44
	10,240.00	-48.79	10.88	-53.11	5.06	H	-47.29	71.71
40740 (2605.0)	5,210.00	-33.03	12.88	-46.51	3.48	H	-37.11	61.53
	7,815.00	-42.49	11.50	-50.85	4.24	H	-43.59	68.01
	10,420.00	-46.50	10.78	-49.24	5.07	H	-43.53	67.95
	15,630.00	-59.31	16.32	-64.01	6.40	H	-54.09	78.51
41190 (2650.0)	5,300.00	-35.56	13.00	-50.26	3.51	H	-40.77	65.19
	7,950.00	-40.14	11.37	-46.55	4.37	H	-39.55	63.97
	10,600.00	-47.39	10.72	-51.27	5.14	H	-45.69	70.11
	15,900.00	-55.97	17.02	-62.71	6.43	H	-52.12	76.54

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.2.3 RADIATED SPURIOUS EMISSIONS (15 MHz Band 38/41 LTE)

- OPERATING FREQUENCY : 2647.50 MHz
- MEASURED OUTPUT POWER: 23.86 dBm = 0.243 W
- MODULATION SIGNAL: 15 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10}(W) =$ 48.86 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40315 (2562.5)	5,125.00	-39.43	12.75	-51.14	3.44	H	-41.83	65.69
	7,687.50	-50.34	11.58	-58.83	4.26	H	-51.51	75.37
	10,250.00	-46.17	10.88	-50.72	5.04	H	-44.88	68.74
40740 (2605.0)	5,210.00	-37.93	12.88	-51.41	3.48	H	-42.01	65.87
	7,815.00	-43.19	11.50	-51.55	4.24	H	-44.29	68.15
	10,420.00	-46.68	10.78	-49.42	5.07	H	-43.71	67.57
41165 (2647.5)	5,295.00	-37.42	12.99	-52.18	3.51	H	-42.70	66.56
	7,942.50	-40.55	11.38	-47.42	4.36	H	-40.40	64.26
	10,590.00	-47.59	10.72	-51.76	5.14	H	-46.18	70.04

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.2.4 RADIATED SPURIOUS EMISSIONS (20 MHz Band 38/41 LTE)

- OPERATING FREQUENCY : 2645.00 MHz
- MEASURED OUTPUT POWER: 23.76 dBm = 0.238 W
- MODULATION SIGNAL: 20 MHz QPSK
- DISTANCE: 1 meters
- LIMIT: $55 + 10 \log_{10} (W) =$ 48.76 dBc

Ch	Freq (MHz)	Measured Level (dBm)	Ant. Gain (dBi)	Substitute Level (dBm)	C.L	Pol	EIRP (dBm)	dBc
40340 (2565.0)	5,130.00	-41.86	12.76	-53.31	3.44	H	-43.99	67.75
	7,695.00	-49.43	11.57	-58.07	4.26	H	-50.76	74.52
	10,260.00	-45.76	10.87	-50.88	5.00	H	-45.01	68.77
40740 (2605.0)	5,210.00	-37.83	12.88	-51.31	3.48	H	-41.91	65.67
	7,815.00	-43.07	11.50	-51.43	4.24	H	-44.17	67.93
	10,420.00	-46.33	10.78	-49.07	5.07	H	-43.36	67.12
41140 (2645.0)	7,935.00	-47.83	11.40	-55.03	4.37	H	-48.00	71.76
	10,580.00	-48.91	10.72	-53.11	5.13	H	-47.52	71.28

- NOTES:**
1. Radiated Spurious Emission Measurements at 1 meter and 3 meters by Substitution Method according to ANSI/TIA/EIA-603-D-2010 June 24, 2010:
 2. We are performed all frequency to 10th harmonics from 9 kHz. Measurements above show only up to 3 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
 3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
 4. All of RB size has been tested for emissions and EIRP, with the 1RB configuration observed as the worst case
 5. We are performed 16QAM and QPSK modulations. The worst case data are reported in the table above.

8.3 OCCUPIED BANDWIDTH

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	Data (MHz)
38/41	5 MHz	2605.0	QPSK	25	0	4.4982
			16-QAM	25	0	4.5035
	10 MHz	2605.0	QPSK	50	0	8.9529
			16-QAM	50	0	8.9578
	15 MHz	2605.0	QPSK	75	0	13.383
			16-QAM	75	0	13.447
	20 MHz	2605.0	QPSK	100	0	17.881
			16-QAM	100	0	17.863

- Plots of the EUT's Occupied Bandwidth are shown Page 30 ~ 33.

8.4 CONDUCTED SPURIOUS EMISSIONS

■FACTORS FOR FREQUENCY

Frequency Range (GHz)	Factor [dB]
0.03 – 1	25.27
1 – 5	27.98
5 – 10	28.59
10 – 15	29.12
15 – 20	29.49
Above 20	30.13

NOTES:

Factor(dB) = Cable Loss + Attenuator +Power Splitter

Band	Band Width (MHz)	Frequency (MHz)	Frequency of Maximum Harmonic (GHz)	Factor (dB)	Measurement Maximum Data (dBm)	Result (dBm)	Limit (dBm)
38/41	5	2557.5	24.1021	30.13	-68.244	-38.114	-25.00
		2605.0	5.2064	28.59	-67.449	-38.859	
		2652.5	25.7864	30.13	-68.303	-38.173	
	10	2560.0	3.0674	27.98	-68.148	-40.168	
		2605.0	3.1372	27.98	-68.112	-40.132	
		2650.0	3.0883	27.98	-68.014	-40.034	
	15	2562.5	24.9436	30.13	-68.376	-38.246	
		2605.0	3.1262	27.98	-68.885	-40.905	
		2647.5	3.0524	27.98	-67.957	-39.977	
	20	2565.0	3.6366	27.98	-68.750	-40.770	
		2605.0	5.1930	28.59	-67.808	-39.218	
		2645.0	3.6162	27.98	-68.202	-40.222	

NOTES:

1. Conducted Spurious Emissions was Tested QPSK Modulation, Resource Block Size 1 and Resource Block Offset 0
2. Result (dBm) = Measurement Maximum Data (dBm) + Factor (dB)

- Plots of the EUT's Conducted Spurious Emissions are shown Page 46 ~ 57.

8.4.1 CHANNEL EDGE

Band 38

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
Band 38	5 MHz	2572.5	QPSK	25	0	-23.10	-23.37	-18.52	-23.11
		2595.0	QPSK	25	0	-24.32	-23.84	-18.21	-23.28
		2617.5	QPSK	25	0	-24.20	-23.68	-18.81	-23.47
	10 MHz	2575.0	QPSK	50	0	-20.15	-22.51	-18.59	-23.87
		2595.0	QPSK	50	0	-24.47	-25.21	-21.64	-25.23
		2615.0	QPSK	50	0	-23.75	-24.26	-23.09	-27.30
	15 MHz	2577.5	QPSK	75	0	-22.45	-27.55	-20.55	-25.81
		2595.0	QPSK	75	0	-26.46	-27.50	-20.43	-24.96
		2612.5	QPSK	75	0	-26.45	-26.45	-21.54	-29.17
	20 MHz	2580.0	QPSK	100	0	-22.98	-27.16	-19.35	-25.38
		2595.0	QPSK	100	0	-24.97	-26.59	-21.57	-25.18
		2610.0	QPSK	100	0	-25.97	-27.06	-22.70	-29.63
Limit						-10.0		-10.0	
Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
						Lower	Upper	Lower	Upper
Band 38	5 MHz	2572.5	QPSK	25	0	-29.40	-31.88	-30.68	-32.82
		2595.0	QPSK	25	0	-29.71	-31.24	-31.26	-31.79
		2617.5	QPSK	25	0	-29.30	-31.26	-30.93	-32.16
	10 MHz	2575.0	QPSK	50	0	-23.11	-28.13	-31.96	-35.68
		2595.0	QPSK	50	0	-22.89	-25.61	-30.76	-31.33
		2615.0	QPSK	50	0	-23.88	-27.06	-31.50	-33.06
	15 MHz	2577.5	QPSK	75	0	-21.75	-28.51	-31.10	-33.92
		2595.0	QPSK	75	0	-22.76	-26.79	-31.61	-33.89
		2612.5	QPSK	75	0	-24.02	-28.64	-33.33	-35.72
	20 MHz	2580.0	QPSK	100	0	-22.79	-27.24	-31.19	-34.60
		2595.0	QPSK	100	0	-23.03	-26.91	-31.64	-34.93
		2610.0	QPSK	100	0	-24.05	-27.78	-31.80	-34.82
Limit						-13.0		-25.0	

Note:

1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth.
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. Plots of the EUT's Band Edge are shown Page 34 ~ 39

Band 41

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	C.E ~ (C.E ± 1MHz)		(C.E ± 1 MHz) ~ (C.E ± 5 MHz)	
						Lower	Upper	Lower	Upper
Band 41	5 MHz	2557.5	QPSK	25	0	-22.86	-23.23	-24.70	-24.74
		2605.0	QPSK	25	0	-23.80	-23.72	-21.61	-23.91
		2652.5	QPSK	25	0	-22.31	-22.56	-20.93	-23.44
	10 MHz	2560.0	QPSK	50	0	-23.73	-23.37	-27.85	-29.24
		2605.0	QPSK	50	0	-21.33	-20.99	-23.50	-26.42
		2650.0	QPSK	50	0	-23.23	-22.98	-23.43	-26.35
	15 MHz	2562.5	QPSK	75	0	-23.53	-25.44	-24.93	-29.55
		2605.0	QPSK	75	0	-25.75	-24.62	-23.63	-25.75
		2647.5	QPSK	75	0	-23.91	-24.28	-22.47	-28.11
	20 MHz	2565.0	QPSK	100	0	-25.37	-25.92	-23.68	-28.95
		2605.0	QPSK	100	0	-27.20	-26.56	-24.98	-28.29
		2645.0	QPSK	100	0	-25.55	-25.14	-22.14	-28.56
Limit						-10.0		-10.0	

Band	Band Width	Frequency (MHz)	Modulation	Resource Block Size	Resource Block Offset	(C.E ± 5 MHz) ~ (C.E ± X MHz)		Above (C.E ± X MHz)	
						Lower	Upper	Lower	Upper
Band 41	5 MHz	2557.5	QPSK	25	0	-31.77	-31.41	-33.52	-32.84
		2605.0	QPSK	25	0	-30.32	-29.60	-31.80	-30.72
		2652.5	QPSK	25	0	-27.48	-29.53	-29.04	-31.01
	10 MHz	2560.0	QPSK	50	0	-27.95	-29.53	-35.92	-35.49
		2605.0	QPSK	50	0	-25.18	-26.41	-34.10	-34.21
		2650.0	QPSK	50	0	-22.94	-26.63	-30.23	-33.48
	15 MHz	2562.5	QPSK	75	0	-27.41	-29.87	-38.39	-37.18
		2605.0	QPSK	75	0	-24.10	-26.80	-34.01	-35.79
		2647.5	QPSK	75	0	-22.55	-29.60	-31.13	-39.00
	20 MHz	2565.0	QPSK	100	0	-27.64	-31.00	-43.45	-39.61
		2605.0	QPSK	100	0	-25.34	-26.67	-33.23	-36.07
		2645.0	QPSK	100	0	-23.28	-30.09	-29.00	-44.53
Limit						-13.0		-25.0	

Note:


1. C.E = Channel Edge
2. X = X is the greater of 6MHz or the actual emission bandwidth.
3. X = 6MHz(5MHz Bandwidth), 10MHz(10MHz Bandwidth), 15MHz(15MHz Bandwidth), 20MHz(20MHz Bandwidth)
4. Plots of the EUT's Band Edge are shown Page 40 ~ 45

8.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

8.5.1 FREQUENCY STABILITY (5 MHz Band 38/41 LTE)

- OPERATING FREQUENCY: 2605.000,000 Hz
- CHANNEL: 40740 (5 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2604 999 996	0.0	0.000 000	0.000
100%		-30	2605 000 008	11.6	0.000 000	0.004
100%		-20	2605 000 006	10.1	0.000 000	0.004
100%		-10	2605 000 001	4.4	0.000 000	0.002
100%		0	2605 000 003	6.3	0.000 000	0.002
100%		+10	2605 000 000	3.4	0.000 000	0.001
100%		+30	2605 000 005	8.5	0.000 000	0.003
100%		+40	2605 000 004	7.4	0.000 000	0.003
100%		+50	2605 000 004	7.3	0.000 000	0.003
Batt. Endpoint	3.60	+20	2605 000 003	6.4	0.000 000	0.002



8.5.2 FREQUENCY STABILITY (10 MHz Band 38/41 LTE)

- OPERATING FREQUENCY: 2605.000,000 Hz
- CHANNEL: 40740 (10 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2605 000 004	0.0	0.000 000	0.000
100%		-30	2605 000 012	7.8	0.000 000	0.003
100%		-20	2605 000 002	-2.5	0.000 000	-0.001
100%		-10	2604 999 998	-6.0	0.000 000	-0.002
100%		0	2605 000 002	-2.5	0.000 000	-0.001
100%		+10	2605 000 012	7.3	0.000 000	0.003
100%		+30	2605 000 000	-4.4	0.000 000	-0.002
100%		+40	2604 999 999	-5.6	0.000 000	-0.002
100%		+50	2604 999 998	-5.8	0.000 000	-0.002
Batt. Endpoint	3.60	+20	2604 999 998	-6.3	0.000 000	-0.002



8.5.3 FREQUENCY STABILITY (15 MHz Band 38/41 LTE)

- OPERATING FREQUENCY: 2605.000,000 Hz
- CHANNEL: 40740 (15 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band


Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2605 000 007	0.0	0.000 000	0.000
100%		-30	2605 000 015	7.8	0.000 000	0.003
100%		-20	2605 000 003	-4.4	0.000 000	-0.002
100%		-10	2605 000 004	-3.5	0.000 000	-0.001
100%		0	2605 000 013	5.9	0.000 000	0.002
100%		+10	2605 000 014	6.3	0.000 000	0.002
100%		+30	2605 000 003	-3.8	0.000 000	-0.001
100%		+40	2605 000 014	6.3	0.000 000	0.002
100%		+50	2605 000 011	3.7	0.000 000	0.001
Batt. Endpoint	3.60	+20	2605 000 002	-5.3	0.000 000	-0.002



8.5.4 FREQUENCY STABILITY (20 MHz Band 38/41 LTE)


- OPERATING FREQUENCY: 2605.000,000 Hz
- CHANNEL: 40740 (20 MHz)
- REFERENCE VOLTAGE: 3.85 VDC
- DEVIATION LIMIT: Emission must remain in band

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.85	+20(Ref)	2605 000 008	0.0	0.000 000	0.000
100%		-30	2605 000 015	6.8	0.000 000	0.003
100%		-20	2605 000 005	-3.1	0.000 000	-0.001
100%		-10	2605 000 003	-5.4	0.000 000	-0.002
100%		0	2605 000 015	6.6	0.000 000	0.003
100%		+10	2605 000 016	7.2	0.000 000	0.003
100%		+30	2605 000 006	-2.8	0.000 000	-0.001
100%		+40	2605 000 014	5.2	0.000 000	0.002
100%		+50	2605 000 013	4.5	0.000 000	0.002
Batt. Endpoint	3.60	+20	2605 000 003	-5.6	0.000 000	-0.002




9. TEST PLOTS


BAND 38/41. Occupied Bandwidth Plot (5 MHz Ch.40740 QPSK RB 25)




BAND 38/41. Occupied Bandwidth Plot (5 MHz Ch.40740 16-QAM RB 25)




BAND 38/41. Occupied Bandwidth Plot (10 MHz Ch.40740 QPSK RB 50)




BAND 38/41. Occupied Bandwidth Plot (10 MHz Ch.40740 16-QAM RB 50)




BAND 38/41. Occupied Bandwidth Plot (15 MHz Ch.40740 QPSK RB 75)




BAND 38/41. Occupied Bandwidth Plot (15 MHz Ch.40740 16-QAM RB 75)




BAND 38/41. Occupied Bandwidth Plot (20 MHz Ch.40740 QPSK RB 100)




BAND 38/41. Occupied Bandwidth Plot (20 MHz Ch.40740 16-QAM RB 100)




BAND 38. Low Channel Edge Plot (5 MHz Ch.37775 QPSK RB 25)



BAND 38. Mid Channel Edge Plot (5 MHz Ch.38000 QPSK RB 25)




BAND 38. High Channel Edge Plot (5 MHz Ch.38225 QPSK RB 25)



BAND 38. Low Channel Edge Plot (10 MHz Ch.37800 QPSK RB 50)




BAND 38. Mid Channel Edge Plot (10 MHz Ch.38000 QPSK RB 50)



BAND 38. High Channel Edge Plot (10 MHz Ch.38200 QPSK RB 50)




BAND 38. Low Channel Edge Plot (15 MHz Ch.37825 QPSK RB 75)



BAND 38. Mid Channel Edge Plot (15 MHz Ch.38000 QPSK RB 75)



BAND 38. High Channel Edge Plot (15 MHz Ch.38175 QPSK RB 75)




BAND 38. Low Channel Edge Plot (20 MHz Ch.37850 QPSK RB 100)




BAND 38. Mid Channel Edge Plot (20 MHz Ch.38000 QPSK RB 100)




BAND 38. High Channel Edge Plot (20 MHz Ch.38150 QPSK RB 100)




BAND 41. Low Channel Edge Plot (5 MHz Ch.40265 QPSK RB 25)




BAND 41. Mid Channel Edge Plot (5 MHz Ch.40740 QPSK RB 25)



BAND 41. High Channel Edge Plot (5 MHz Ch.41215 QPSK RB 25)



BAND 41. Low Channel Edge Plot (10 MHz Ch.40290 QPSK RB 50)




BAND 41. Mid Channel Edge Plot (10 MHz Ch.40740 QPSK RB 50)




BAND 41. High Channel Edge Plot (10 MHz Ch.41190 QPSK RB 50)




BAND 41. Low Channel Edge Plot (15 MHz Ch.40315 QPSK RB 75)




BAND 41. Mid Channel Edge Plot (15 MHz Ch.40740 QPSK RB 75)



BAND 41. High Channel Edge Plot (15 MHz Ch.41165 QPSK RB 75)



BAND 41. Low Channel Edge Plot (20 MHz Ch.40340 QPSK RB 100)




BAND 41. Mid Channel Edge Plot (20 MHz Ch.40740 QPSK RB 100)




BAND 41. High Channel Edge Plot (20 MHz Ch.41140 QPSK RB 100)




BAND 38/41. Conducted Spurious Plot 1 (5 MHz Ch.40265 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (5 MHz Ch. 40265 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (5 MHz Ch.40740 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (5 MHz Ch. 40740 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (5 MHz Ch.41215 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (5 MHz Ch. 41215 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (10 MHz Ch.40290 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (10 MHz Ch. 40290 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (10 MHz Ch.40740 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (10 MHz Ch. 40740 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (10 MHz Ch. 41190 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (10 MHz Ch. 41190 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (15 MHz Ch.40315 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (15 MHz Ch. 40315 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (15 MHz Ch.40740 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (15 MHz Ch. 40740 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (15 MHz Ch.41165 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (15 MHz Ch. 41165 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (20 MHz Ch.40340 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 2 (20 MHz Ch. 40340 QPSK RB 1, Offset 0)




BAND 38/41. Conducted Spurious Plot 1 (20 MHz Ch.40740 QPSK RB 1, Offset 0)



BAND 38/41. Conducted Spurious Plot 2 (20 MHz Ch. 40740 QPSK RB 1, Offset 0)



BAND 38/41. Conducted Spurious Plot 1 (20 MHz Ch.41140 QPSK RB 1, Offset 0)



BAND 38/41. Conducted Spurious Plot 2 (20 MHz Ch. 41140 QPSK RB 1, Offset 0)

