FCC 47 CFR Parts 1 & 2
Published RF Exposure KDB Procedures
IEEE Std 1528-2013

SAR EVALUATION REPORT

For
GSM/WCDMA Phone + Bluetooth & WLAN 2.4GHz b/g/n

Model: SM-355M/DS & SM-355M
FCC ID: A3LSMG355M

Report Number: 14I17720-S5A
Issue Date: 5/20/2014

Prepared for
Samsung Electronics Co., Ltd.
416, Maetan 3-Dong, Yeongtong-Gu
Suwon-City, GyeonGggi-Do 443-742, South Korea

Prepared by
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	5/15/2014	Initial Issue	--
A	5/20/2014	Report revised based on the Reviewer's comments: 1. Appendix Sec. 15.3. Corrected and updated ConvF for Highest SAR results – Plot No. 5, 6, 11 2. Sec. 12.2., 12.4. Updated SAR 3. Sec. 14.2., 14.4. Updated Simultaneous SAR for GSM 1900 & W-CDMA II	Vinky Ip

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Table of Contents

1. Attestation of Test Results 5

2. Test Methodology 6

3. Facilities and Accreditation 6

4. Calibration and Uncertainty 7

4.1. Measuring Instrument Calibration 7

4.2. Measurement Uncertainty 7

5. Measurement System Description and Setup 8

6. SAR Measurement Procedure 9

6.1. Normal SAR Measurement Procedure 9

6.2. Volume Scan Procedures 11

7. Device Under Test 12

7.1. General Information 12

7.2. Wireless Technologies 12

7.3. RF Output Power Tolerance 13

7.4. Simultaneous Transmission Condition 13

8. RF Exposure Conditions 14

8.1. Head Exposure Conditions 14

8.2. Body-worn Accessory Exposure Conditions 14

8.3. Hotspot Exposure Conditions and Wi-Fi Direct 14

9. RF Output Power Measurement 15

9.1. GSM 15

9.2. W-CDMA 16

9.3. Wi-Fi (2.4 GHz Band) 20

9.4. Bluetooth 20

10. Tissue Dielectric Properties 21

10.1. Composition of Ingredients for the Tissue Material Used in the SAR Tests 22

10.2. Tissue Dielectric Parameter Check Results 23

11. System Performance Check 24

11.1. System Performance Check Measurement Conditions 24

11.2. Reference SAR Values for System Performance Check 24

11.3. System Performance Check Results 25

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888

FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

12. SAR Test Results 26
12.1. GSM850 26
12.2. GSM1900 27
12.3. W-CDMA Band V 27
12.4. W-CDMA Band II 27
12.5. Wi-Fi (DTS Band) 28
12.6. Bluetooth 29
12.6.1. Standalone SAR Test Exclusion Considerations 29
12.6.2. Estimated SAR 29
13. SAR Measurement Variability 30
13.1. The Highest Measured SAR Configuration in Each Frequency Band 30
13.2. Repeated Measurement Results 30
14. Simultaneous Transmission SAR Analysis 31
14.1. Sum of the SAR for GSM850 & Wi-Fi & BT 32
14.2. Sum of the SAR for GSM1900 & Wi-Fi & BT 32
14.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT 33
14.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT 33
15. Appendixes 34
15.1. Photos and Antenna Locations 34
15.2. System Performance Check Plots 34
15.3. Highest SAR Test Plots 34
15.4. Calibration Certificate for E-Field Probe EX3DV4 - SN 3871 34
15.5. Calibration Certificate for E-Field Probe EX3DV4 - SN 3531 34
15.6. Calibration Certificate for E-Field Probe EX3DV3 - SN 3936 34
15.7. Calibration Certificate for D835V2 - SN 4d002 34
15.8. Calibration Certificate for D1900V2- SN 5d163 34
15.9. Calibration Certificate for D2450V2 - SN 899 34

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1. Attestation of Test Results

Applicant	Samsung Electronics			
DUT description	GSM/WCDMA Phone + Bluetooth & WLAN 2.4GHz b/g/n			
Model	SM-355M/DS & SM-355M			
Test device is	An identical prototype			
Device category	Portable			
Exposure category	General Population/Uncontrolled Exposure			
Date tested	5/6/2014 – 5/9/2014			
The highest reported SAR values	RF exposure condition	Licensed	DTS	UNII
	Head	0.314 W/kg	0.098 W/kg	N/A
	Body-worn Accessory	0.940 W/kg	0.075 W/kg	N/A
	Wireless Router (Hotspot)	0.940 W/kg	0.075 W/kg	N/A
	Simultaneous Transmission	1.015 W/kg		
Applicable Standards	FCC 47 CFR Parts 1 & 2 Published RF Exposure KDB Procedures, and TCB workshop updates IEEE Std 1528-2013			
Test Results	Pass			

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government (NIST Handbook 150, Annex A). This report is written to support regulatory compliance of the applicable standards stated above.

Approved & Released By:

Devin Chang
WiSE Senior Engineer
UL Verification Services Inc.

Prepared By:

Vinky Ip
WiSE Laboratory Technician
UL Verification Services Inc.

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

2. Test Methodology

The tests documented in this report were performed in accordance with FCC 47 CFR Parts 1 & 2, IEEE STD 1528-2013, the following FCC Published RF exposure KDB procedures, and TCB workshop updates:

- 447498 D01 General RF Exposure Guidance v05r02
- 648474 D04 Handset SAR v01r02
- 941225 D01 SAR test for 3G devices v02
- 941225 D02 HSPA and 1x Advanced v02r02
- 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- 941225 D06 Hotspot Mode SAR v01r01
- 248227 D01 SAR Meas for 802 11abg v01r02
- 865664 D02 SAR Reporting v01r01
- 690783 D01 SAR Listings on Grants v01r03

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

47173 Benicia Street	47266 Benicia Street
SAR Lab A	SAR Lab 1
SAR Lab B	SAR Lab 2
SAR Lab C	SAR Lab 3
SAR Lab D	SAR Lab 4
SAR Lab E	
SAR Lab F	

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at http://www.ccsemc.com.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

4. Calibration and Uncertainty

4.1. Measuring Instrument Calibration

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations, and is traceable to recognized national standards.

Tissue Dielectric Properties

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
ENA Network Analyzer	Agilent	E5071B	MY42100131	2/24/2015
Dielectronic Probe kit	SPEAG	DAK-3.5	1082	9/10/2014
Dielectronic Probe kit	SPEAG	DAK-3.5 Short	SM DAK 200 BA	N/A
Thermometer	Control Company	4242	122529163	9/19/2014

System Performance Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Synthesized Signal Generator	Agilent	8665B	3438A0063	6/13/2014
Power Meter	HP	438A	2822A05684	10/10/2014
Power Sensor	Agilent	8481A	2237A31744	10/2/02014
Power Sensor	Agilent	8481A	2349A36506	9/30/2014
Amplifier	MITEQ	AMF-4D-00400600-50-30P	1795093	N/A
Directional coupler	Werlatone	C8060-102	2711	N/A
DC Power Supply	AMETEK	XHR60-18	1308A01935	N/A
E-Field Probe	SPEAG	EX3DV4	3871	12/11/2014
E-Field Probe	SPEAG	EX3DV4	3531	11/21/2014
E-Field Probe	SPEAG	EX3DV4	3936	7/22/2014
Data Acquisition Electronics	SPEAG	DAE3	427	1/21/2015
Data Acquisition Electronics	SPEAG	DAE4	1359	2/17/2015
Data Acquisition Electronics	SPEAG	DAE4	1380	7/15/2014
System Validation Dipole	SPEAG	D835V2	4d002	9/10/2014
System Validation Dipole	SPEAG	D1900V2	5d163	9/17/2014
System Validation Dipole	SPEAG	D2450V2	899	11/15/2014

Others

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Power Meter	Agilent	N1911A	MY53060016	8/13/2014
Power Sensor	Agilent	N1921A	MY52200012	9/25/2014
Callbox	R&S	CMW 500	140259-mn	7/25/2015

4.2. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5. Measurement System Description and Setup

The DASY5 system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6. SAR Measurement Procedure

6.1. Normal SAR Measurement Procedure

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE Standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	½·δ·ln(2) ± 0.5 mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: Δx_{Area}, Δy_{Area}	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: Δx_{Zoom}, Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the area scan based *1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

Step 5: Z-Scan (FCC only)

The Z Scan measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. In order to get a reasonable extrapolation the extrapolated distance should not be larger than the step size in Z-direction.

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6.2. Volume Scan Procedures

Step 1: Repeat Step 1-4 in Section 6.1

Step 2: Volume Scan
Volume Scans are used to assess peak SAR and averaged SAR measurements in largely extended 3-dimensional volumes within any phantom. This measurement does not need any previous area scan. The grid can be anchored to a user specific point or to the current probe location.

Step 3: Power drift measurement
The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000
FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7. Device Under Test

7.1. General Information

Operating Configuration(s)	Held to head, Body-worn (Voice call)
Mobile Hotspot	Wi-Fi Hotspot mode permits the device to share its cellular data connection with other Wi-Fi -enabled devices. ☒ Mobile Hotspot (Wi-Fi 2.4 GHz) ☐ Mobile Hotspot (Wi-Fi 5 GHz)
Wi-Fi Direct	Wi-Fi Direct enabled devices transfer data directly between each other ☒ Wi-Fi Direct (Wi-Fi 2.4 GHz) ☐ Wi-Fi Direct (Wi-Fi 5 GHz)
Device dimension	Overall (Length x Width): 130 mm x 68mm Overall Diagonal: 139mm Display Diagonal: 115mm
Back Cover	☒ Normal Battery Cover ☐ Normal Battery Cover with NFC ☐Wireless Charger Battery Cover ☐ Wireless Charger Battery Cover with NFC
Accessory	☒ Headset
Battery Options	☒ Standard – Lithium-ion battery, Rating 3.8 Vdc, 7.6 Wh ☐ Extended (large capacity)

7.2. Wireless Technologies

Wireless Technology and Frequency Bands	GSM: 850 / 1900 W-CDMA Band: V / II Wi-Fi : 2.4 GHz Bluetooth: 2.4 GHz.
Mode	GSM - ☒ Voice (GMSK) - ☒ GPRS (GMSK) - ☒ EGPRS (8PSK) (Rx Only) W-CDMA - ☒ UMTS Rel. 99 (Voice & Data) - ☒ HSDPA (Rel. 5) - ☒ HSUPA (Rel. 6) - ☒ HSPA+ (Rel. 6) Wi-Fi 2.4GHz (802.11b/g/n) - ☒ 802.11b - ☒ 802.11g - ☒ 802.11n (HT20) Bluetooth - ☒ Version 4.0 LE
Duty Cycle	GSM Voice: 12.5%; GPRS 1 Slot: 12.5%; 2 Slots: 25%, 3 Slots: 37.5%,4 Slots: 50%, W-CDMA: 100% Wi-Fi 802.11b/g/n: 100% Bluetooth: 32.25% (DH1), 66.68% (DH3), 77.52% (DH5)
GPRS Multi-Slot Class	☐ Class 8 - One Up ☐ Class 10 - Two Up ☒ Class 12 - Four Up ☐ Class 33 - Four Up
DTM (Dual Transfer Mode)	☐ Supported
VoIP (GPRS)	☒ Supported
SV-LTE & SV-DO	☐ Supported

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.3. RF Output Power Tolerance

Upper limit (dB): 0.5 ~ -1.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
GSM850	Voice	32.5	**33.0**
	GPRS 1 slot	32.5	**33.0**
	GPRS 2 slots	31.0	**31.5**
	GPRS 3 slots	29.5	**30.0**
	GPRS 4 slots	27.5	**28.0**
GSM1900	Voice	29.5	**30.0**
	GPRS 1 slot	29.5	**30.0**
	GPRS 2 slots	27.5	**28.0**
	GPRS 3 slots	26.0	**26.5**
	GPRS 4 slots	24.5	**25.0**
W-CDMA Band V	R99	22.5	**23.0**
	HSDPA	22.0	**22.5**
	HSUPA	20.0	**20.5**
	HSPA+	20.0	**20.5**
W-CDMA Band II	R99	22.0	**22.5**
	HSDPA	21.5	**22.0**
	HSUPA	20.5	**21.0**
	HSPA+	20.5	**21.0**
Upper limit (dB): 0.5 ~ -1.5		RF Output Power (dBm)	
RF Air interface	Mode	Target	Max. tune-up tolerance limit
WiFi 2.4 GHz	802.11b	16.0	**16.5**
	802.11g	14.0	**14.5**
	802.11n HT20	12.0	**12.5**
Bluetooth		12.0	**12.5**
Bluetooth LE		8.0	**8.5**

7.4. Simultaneous Transmission Condition

Item	Capable Transmit Configurations	RF Exposure Condition			Notes
		Head	Body-worn Accessory	Wireless Router (Hotspot) & Wi-Fi Direct	
1	GSM 850/1900 Voice + Wi-Fi 2.4GHz	v	v	v	
2	GSM 850/1900 (GPRS) + Wi-Fi 2.4GHz (VoIP)	v	v	v	
3	WCDMA Band V/II + Wi-Fi 2.4GHz	v	v	v	
4	GSM 850/1900 Voice + BT		v		
5	GSM 850/1900 (GPRS) + BT(VoIP)		v		
6	WCDMA Band V/II + BT		v		

Notes:
1. Wi-Fi 2.4GHz supports Hotspot and Wi-Fi Direct.
2. GPRS, and WCDMA, support Hotspot.
3. VoIP is support in GPRS, and WCDMA.
4. Wi-Fi 2.4 GHz Radio cannot transmit simultaneously with Bluetooth Radio.

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

8. RF Exposure Conditions

Refer to Appendix "Antenna Locations and Separation Distances" for the specific details of the antenna-to-antenna and antenna-to-edge(s) distances.

8.1. Head Exposure Conditions

For WWAN, and Wi-Fi

Test Configurations	SAR Required	Note
Left Touch	Yes	
Left Tilt (15°)	Yes	
Right Touch	Yes	
Right Tilt (15°)	Yes	

8.2. Body-worn Accessory Exposure Conditions

For WWAN

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	

For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	

8.3. Hotspot Exposure Conditions and Wi-Fi Direct

For WWAN

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	
Edge 1 (Top)	119 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 941225 D06 Hot Spot SAR
Edge 2 (Right)	3 mm	Yes	
Edge 3 (Bottom)	1.5 mm	Yes	
Edge 4 (Left)	2 mm	Yes	

For Wi-Fi

Test Configurations	Antenna-to-edge/surface	SAR Required	Note
Rear	<25 mm	Yes	
Front	<25 mm	Yes	
Edge 1 (Top)	5 mm	Yes	
Edge 2 (Right)	9 mm	Yes	
Edge 3 (Bottom)	115 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 648474 D04 Handset SAR
Edge 4 (Left)	44 mm	No	SAR is not required because the distance from the antenna to the edge is > 25 mm as per KDB 648474 D04 Handset SAR

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9. RF Output Power Measurement

9.1. GSM

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)
850	GSM (Voice)	CS1	1	128	824.2	32.2	23.2
				190	836.6	32.4	23.4
				251	848.8	32.4	23.4
	GPRS (GMSK)	CS1	1	128	824.2	32.2	23.2
				190	836.6	32.4	23.4
				251	848.8	32.4	23.4
			2	128	824.2	30.8	24.8
				190	836.6	31.0	25.0
				251	848.8	31.0	25.0
			3	128	824.2	28.4	24.1
				190	836.6	28.5	24.2
				251	848.8	28.6	24.3
			4	128	824.2	26.5	23.5
				190	836.6	26.6	23.6
				251	848.8	26.8	23.8

EGPRS(8PSK) is Rx only

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 2 time slots, based on the output power measurements above

Band	Mode	Coding Scheme	Time Slots	Ch No.	Freq. (MHz)	Burst Pwr (dBm)	Frame Pwr (dBm)
1900	GSM (Voice)	CS1	1	512	1850.2	28.8	19.8
				661	1880.0	28.9	19.9
				810	1909.8	28.6	19.6
	GPRS (GMSK)	CS1	1	512	1850.2	28.6	19.6
				661	1880.0	28.9	19.9
				810	1909.8	28.4	19.4
			2	512	1850.2	28.0	22.0
				661	1880.0	28.0	22.0
				810	1909.8	27.8	21.8
			3	512	1850.2	26.2	21.9
				661	1880.0	26.2	21.9
				810	1909.8	25.9	21.6
			4	512	1850.2	23.7	20.7
				661	1880.0	23.7	20.7
				810	1909.8	23.5	20.5

EGPRS(8PSK) is Rx only

Notes:

The worst-case configuration and mode for SAR testing is determined to be as follows:

- Head & Body-worn Accessory: GMSK Voice Mode
- Hotspot mode: GMSK (GPRS) mode with 2 time slots, based on the output power measurements above

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.2. W-CDMA

Release 99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	βc/βd	8/15

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	Avg Pwr (dBm)
W-CDMA Band V	Rel 99 (RMC, 12.2 kbps)	4132	826.4	22.1
		4183	836.6	22.1
		4233	846.6	22.0
W-CDMA Band II	Rel 99 (RMC, 12.2 kbps)	9262	1852.4	21.2
		9400	1880.0	21.4
		9538	1907.6	21.2

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000
FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

HSDPA

The following 4 Sub-tests were completed according to Release 5 / 6 procedures in section 5.2 of 3GPP TS34.121-1. A summary of these settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm 2			
	βc	2/15	12/15	15/15	15/15
	βd	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	βc/βd	2/15	12/15	15/8	15/4
	βhs	4/15	24/15	30/15	30/15
	MPR (dB)	0	0	0.5	0.5
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	Ahs=βhs/βc	30/15			

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	21.9
		4183	836.6	0	22.1
		4233	846.6	0	21.0
	Subtest 2	4132	826.4	0	21.9
		4183	836.6	0	22.2
		4233	846.6	0	22.1
	Subtest 3	4132	826.4	0.5	21.9
		4183	836.6	0.5	21.9
		4233	846.6	0.5	22.0
	Subtest 4	4132	826.4	0.5	21.9
		4183	836.6	0.5	22.0
		4233	846.6	0.5	21.9
W-CDMA Band II	Subtest 1	9262	1852.4	0	21.4
		9400	1880.0	0	21.6
		9538	1907.6	0	21.4
	Subtest 2	9262	1852.4	0	21.3
		9400	1880.0	0	21.5
		9538	1907.6	0	21.4
	Subtest 3	9262	1852.4	0.5	21.0
		9400	1880.0	0.5	21.1
		9538	1907.6	0.5	20.9
	Subtest 4	9262	1852.4	0.5	21.0
		9400	1880.0	0.5	21.2
		9538	1907.6	0.5	21.0

Maximum output power levels that are possible for all subtests reported.

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

HSPA (HSDPA & HSUPA)

The following 5 Sub-tests were completed according to Release 7 procedures in section 5.2 of 3GPP TS34.121. A summary of these settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	βc	11/15	6/15	15/15	2/15	15/15
	βd	15/15	15/15	9/15	15/15	0
	βec	209/225	12/15	30/15	2/15	5/15
	βc/βd	11/15	11/15	15/9	2/15	15/0
	βhs	22/15	12/15	30/15	4/15	5/15
	βed	1309/225	94/75	47/15 47/15	56/75	47/15
	CM (dB)	1	3	2	3	1
	MPR (dB)	0	2	1	2	0
HSDPA Specific Settings	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
	Ahs = βhs/βc	30/15				
HSUPA Specific Settings	E-DPDCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
	Reference E-TFCI PO	27	27	27	27	27
	Maximum Channelisation Codes	2xSF2				SF4

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Measured Results

Band	Mode	UL Ch No.	Freq. (MHz)	MPR	Avg Pwr (dBm)
W-CDMA Band V	Subtest 1	4132	826.4	0	19.4
		4183	836.6	0	19.6
		4233	846.6	0	19.6
	Subtest 2	4132	826.4	2	17.3
		4183	836.6	2	17.6
		4233	846.6	2	17.6
	Subtest 3	4132	826.4	1	18.6
		4183	836.6	1	19.0
		4233	846.6	1	18.9
	Subtest 4	4132	826.4	2	18.1
		4183	836.6	2	18.4
		4233	846.6	2	18.4
	Subtest 5	4132	826.4	0	19.8
		4183	836.6	0	20.1
		4233	846.6	0	20.0
W-CDMA Band II	Subtest 1	9262	1852.4	0	20.5
		9400	1880.0	0	20.6
		9538	1907.6	0	20.4
	Subtest 2	9262	1852.4	2	17.7
		9400	1880.0	2	17.8
		9538	1907.6	2	17.8
	Subtest 3	9262	1852.4	1	19.1
		9400	1880.0	1	19.3
		9538	1907.6	1	19.2
	Subtest 4	9262	1852.4	2	18.7
		9400	1880.0	2	18.8
		9538	1907.6	2	18.6
	Subtest 5	9262	1852.4	0	20.5
		9400	1880.0	0	20.6
		9538	1907.6	0	20.3

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

9.3. Wi-Fi (2.4 GHz Band)

Required Test Channels per KDB 248227 D01

Mode	Band	GHz	Channel	"Default Test Channels"	
				802.11b	802.11g
802.11b/g	2.4 GHz	**2.412**	1#	√	∇
		2.437	6	√	∇
		2.462	11#	√	∇

Notes:
√ = "default test channels"
∇ = possible 802.11g channels with maximum average output ¼ dB ≥ the "default test channels"
= when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels should be tested.

Measured Results

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
2.4 (DTS)	802.11b	1 Mbps	1	2412	16.5	Yes
			6	2437	16.5	
			11	2462	16.5	
	802.11g	6 Mbps	1	2412	14.2	No
			6	2437	14.2	
			11	2462	14.2	
	802.11n (HT20)	MCS0	1	2412	12.0	No
			6	2437	12.1	
			11	2462	12.1	

Note(s):

Per KDB 248227 D01, SAR is not required for 802.11g/HT20 channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.

Power measurements to determine worst-case data rates

Mode	Ch #	Freq. (MHz)	Data Rate	Avg Pwr (dBm)	SAR test (Yes/No)
802.11b	6	2437	1 Mbps	16.5	Yes
			2 Mbps	16.5	No
			5.5 Mbps	16.5	No
			11 Mbps	16.5	No

9.4. Bluetooth

Maximum tune-up tolerance limit is 12.5 dBm from the rated nominal maximum output power. This power level qualifies for exclusion of SAR testing.

Refer to Standalone SAR Test Exclusion Considerations Section.

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

10. Tissue Dielectric Properties

IEEE Std 1528-2013

Target Frequency (MHz)	Head	
	ε_r	σ (S/m)
300	45.3	0.87
450	43.5	0.87
750	*41.9*	*0.89*
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1500	*40.4*	*1.23*
1640	*40.2*	*1.31*
1750	*40.1*	*1.37*
1800	40.0	1.40
1900	40.0	1.40
2000	40.0	1.40
2100	*39.8*	*1.49*
2300	*39.5*	*1.67*
2450	39.2	1.80
2600	*39.0*	*1.96*
3000	38.5	2.40
3500	*37.9*	*2.91*
4000	*37.4*	*3.43*
4500	*36.8*	*3.94*
5000	*36.2*	*4.45*
5200	*36.0*	*4.66*
5400	*35.8*	*4.86*
5600	*35.5*	*5.07*
5800	35.3	5.27
6000	*35.1*	*5.48*

NOTE—For convenience, permittivity and conductivity values at some frequencies that are not part of the original data from Drossos et al. [B60] or the extension to 5800 MHz are provided (i.e., the values shown in italics). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6000 MHz that were linearly extrapolated from the values at 3000 MHz and 5800 MHz.

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ε_r	σ (S/m)	ε_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

10.1. Composition of Ingredients for the Tissue Material Used in the SAR Tests

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Salt: 99+% Pure Sodium Chloride
Sugar: 98+% Pure Sucrose
Water: De-ionized, 16 MΩ+ resistivity
HEC: Hydroxyethyl Cellulose
DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]
Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether

MSL/HSL750 (Body and Head liquids for 700 – 800 MHz)

Item	Head Tissue Simulation Liquids HSL750 Muscle (body) Tissue Simulation Liquids MSL750
Type No	SL AAH 075
Manufacturer	SPEAG
The item is composed of the following ingredients:	
H^2O	Water, 35 – 58%
Sucrese	Sugar, white, refined, 40-60%
NaCl	Sodium Chloride, 0-6%
Hydroxyethel-cellulsoe	Medium Viscosity (CAS# 9004-62-0), <0.3%
Preventol-D7	Preservative: aqueous preparation, (CAS# 55965-84-9), containing 5-chloro-2-methyl-3(2H)-isothiazolone and 2-methyyl-3(2H)-isothiazolone, 0.1-0.7%

MSL/HSL1750 (Body and Head liquids for 1700 – 1800 MHz)

Item	Head Tissue Simulation Liquids HSL1750 Muscle (body) Tissue Simulation Liquids MSL1750
Type No	SL AAM 175
Manufacturer	SPEAG
-The item is composed of the following ingredients:	
H^2O	Water, 52 – 75%
C8H18O3	Diethylene glycol monobutyl ether (DGBE), 25-48%
NaCl	Sodium Chloride, <1.0%

Simulating Liquids for 5 GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000
FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

10.2. Tissue Dielectric Parameter Check Results

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within ± 2°C of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

SAR Room 1

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
5/6/2014	Body 2450	e'	53.2500	Relative Permittivity (ε_r):	53.25	52.70	1.04	5
		e''	14.8800	Conductivity (σ):	2.03	1.95	3.95	5
	Body 2410	e'	53.3800	Relative Permittivity (ε_r):	53.38	52.76	1.18	5
		e''	14.8200	Conductivity (σ):	1.99	1.91	4.11	5
	Body 2475	e'	53.1700	Relative Permittivity (ε_r):	53.17	52.67	0.95	5
		e''	14.9400	Conductivity (σ):	2.06	1.99	3.57	5
5/8/2014	Head 2450	e'	40.0500	Relative Permittivity (ε_r):	40.05	39.20	2.17	5
		e''	13.6700	Conductivity (σ):	1.86	1.80	3.46	5
	Head 2410	e'	40.2000	Relative Permittivity (ε_r):	40.20	39.28	2.34	5
		e''	13.5400	Conductivity (σ):	1.81	1.76	3.07	5
	Head 2475	e'	39.9500	Relative Permittivity (ε_r):	39.95	39.17	2.00	5
		e''	13.7600	Conductivity (σ):	1.89	1.83	3.64	5

SAR Room 2

Date	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
5/6/2014	Head 1900	e'	40.3400	Relative Permittivity (ε_r):	40.34	40.00	0.85	5
		e''	13.5900	Conductivity (σ):	1.44	1.40	2.55	5
	Head 1850	e'	40.5800	Relative Permittivity (ε_r):	40.58	40.00	1.45	5
		e''	13.4100	Conductivity (σ):	1.38	1.40	-1.47	5
	Head 1910	e'	40.3000	Relative Permittivity (ε_r):	40.30	40.00	0.75	5
		e''	13.6300	Conductivity (σ):	1.45	1.40	3.40	5
5/6/2014	Body 1900	e'	51.6000	Relative Permittivity (ε_r):	51.60	53.30	-3.19	5
		e''	14.9200	Conductivity (σ):	1.58	1.52	3.70	5
	Body 1850	e'	51.8100	Relative Permittivity (ε_r):	51.81	53.30	-2.80	5
		e''	14.7100	Conductivity (σ):	1.51	1.52	-0.45	5
	Body 1910	e'	51.5600	Relative Permittivity (ε_r):	51.56	53.30	-3.26	5
		e''	14.9600	Conductivity (σ):	1.59	1.52	4.53	5

SAR Room 4

	Freq. (MHz)	Liquid Parameters			Measured	Target	Delta (%)	Limit ±(%)
5/7/2014	Head 835	e'	40.3700	Relative Permittivity (ε_r):	40.37	41.50	-2.72	5
		e''	19.8900	Conductivity (σ):	0.92	0.90	2.61	5
	Head 820	e'	40.5700	Relative Permittivity (ε_r):	40.57	41.60	-2.48	5
		e''	19.9300	Conductivity (σ):	0.91	0.90	1.14	5
	Head 850	e'	40.1700	Relative Permittivity (ε_r):	40.17	41.50	-3.20	5
		e''	19.8500	Conductivity (σ):	0.94	0.92	2.53	5
5/7/2014	Body 835	e'	53.1900	Relative Permittivity (ε_r):	53.19	55.20	-3.64	5
		e''	21.8500	Conductivity (σ):	1.01	0.97	4.58	5
	Body 820	e'	53.3500	Relative Permittivity (ε_r):	53.35	55.28	-3.49	5
		e''	21.9400	Conductivity (σ):	1.00	0.97	3.29	5
	Body 850	e'	53.0300	Relative Permittivity (ε_r):	53.03	55.16	-3.86	5
		e''	21.7800	Conductivity (σ):	1.03	0.99	4.28	5

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

11. System Performance Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are remeasured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

11.1. System Performance Check Measurement Conditions

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 ±0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be ≥ 15.0 cm ± 0.5 cm for SAR measurements ≤ 3 GHz and ≥ 10.0 cm ± 0.5 cm for measurements > 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
  For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
  For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

11.2. Reference SAR Values for System Performance Check

The reference SAR values can be obtained from the calibration certificate of system validation dipoles

System Dipole	Serial No.	Cal. Date	Freq. (MHz)	Target SAR Values (mW/g)		
				1g/10g	Head	Body
D835V2	4d002	11/15/2013	835	1g	9.49	9.43
				10g	6.18	6.21
D1900V2	5d163	9/17/2013	1900	1g	40.9	40.1
				10g	21.2	21.2
D2450V2	899	9/10/2013	2450	1g	51.3	49.7
				10g	23.9	23.3

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000
FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

11.3. System Performance Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within 10% of the manufacturer calibrated dipole SAR target.

SAR Room 1

Date Tested	System Dipole		T.S. Liquid		Measured Results			Target (Ref. Value)	Delta ±10 %	Est./Zoom Ratio	Plot No.
	Type	Serial #			Area Scan	Zoom Scan	Normalize to 1 W				
5/6/2014	D2450V2	899	Body	1g	5.49	5.41	54.1	49.70	8.85	1.46	1,2
				10g	2.390	2.510	25.1	23.30	7.73		
5/8/2014	D2450V2	899	Head	1g	5.23	5.14	51.4	51.30	0.19	1.72	
				10g	2.240	2.340	23.4	23.90	-2.09		

SAR Room 2

Date Tested	System Dipole		T.S. Liquid		Measured Results			Target (Ref. Value)	Delta ±10 %	Est./Zoom Ratio	Plot No.
	Type	Serial #			Area Scan	Zoom Scan	Normalize to 1 W				
5/6/2014	D1900V2	5d163	Head	1g	4.21	4.04	40.4	40.90	-1.22	4.04	3,4
				10g	2.18	2.08	20.8	21.20	-1.89		
5/6/2014	D1900V2	5d163	Body	1g	4.11	4.03	40.3	40.10	0.50	1.95	
				10g	2.11	2.11	21.1	21.20	-0.47		

SAR Room 4

Date Tested	System Dipole		T.S. Liquid		Measured Results			Target (Ref. Value)	Delta ±10 %	Est./Zoom Ratio	Plot No.
	Type	Serial #			Area Scan	Zoom Scan	Normalize to 1 W				
5/7/2014	D835V2	4d002	Head	1g	0.987	0.959	9.6	9.49	1.05	2.84	
				10g	0.665	0.629	6.3	6.18	1.78		
5/7/2014	D835V2	4d002	Body	1g	0.993	0.981	9.8	9.43	4.03	1.21	5,6
				10g	0.664	0.645	6.5	6.21	3.86		

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

12. SAR Test Results

SAR Test Reduction criteria are as follows:

KDB 447498 D01 General RF Exposure Guidance:
Testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:

- ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

KDB 648474 D04 Handset SAR:
With headset attached, when the reported SAR for body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

KDB 941225 D01 SAR test for 3G devices:
Body SAR is also measured for HSPA when the maximum average output of each RF channel with HSPA active is at least ¼ dB higher than that measured without HSPA using 12.2 kbps RMC or the maximum SAR for 12.2 kbps RMC is above 75% of the SAR limit. Body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 with power control algorithm 2.

12.1. GSM850

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	190	836.6	33.0	32.4	0.240	0.276	1
			Left Tilt	190	836.6	33.0	32.4	0.138	0.158	
			Right Touch	190	836.6	33.0	32.4	0.229	0.263	
			Rightt Tilt	190	836.6	33.0	32.4	0.154	0.177	
Head VoIP	GPRS 2 Slots	0	Left Touch	190	836.6	31.5	31.0	0.280	**0.314**	2
			Left Tilt	190	836.6	31.5	31.0	0.159	0.178	
			Right Touch	190	836.6	31.5	31.0	0.274	0.307	
			Rightt Tilt	190	836.6	31.5	31.0	0.185	0.208	
Body-worn	Voice	10	Rear	190	836.6	33.0	32.4	0.490	0.563	3
			Front	190	836.6	33.0	32.4	0.373	0.428	
Body-worn(VoIP) & Hotspot	GPRS 2 Slots	10	Rear	190	836.6	31.5	31.0	0.574	0.644	4
			Front	190	836.6	31.5	31.0	0.433	0.486	
Hotspot			Edge 2	190	836.6	31.5	31.0	0.291	0.327	
			Edge 3	190	836.6	31.5	31.0	0.096	0.108	
			Edge 4	190	836.6	31.5	31.0	0.327	0.367	

UL Verification Services Inc. FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

12.2. GSM1900

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Voice	0	Left Touch	661	1880.0	30.0	28.9	0.061	0.078	
			Left Tilt	661	1880.0	30.0	28.9	0.023	0.030	
			Right Touch	661	1880.0	30.0	28.9	0.096	0.123	5
			Rightt Tilt	661	1880.0	30.0	28.9	0.022	0.029	
Head VoIP	GPRS 2 Slots	0	Left Touch	661	1880.0	28.0	28.0	0.108	0.108	
			Left Tilt	661	1880.0	28.0	28.0	0.039	0.039	
			Right Touch	661	1880.0	28.0	28.0	0.158	0.158	6
			Rightt Tilt	661	1880.0	28.0	28.0	0.040	0.040	
Body-worn	Voice	10	Rear	661	1880.0	30.0	28.9	0.431	0.555	7
			Front	661	1880.0	30.0	28.9	0.162	0.209	
Body-worn(VoIP) & Hotspot	GPRS 2 Slots	10	Rear	661	1880.0	28.0	28.0	0.600	0.600	8
			Front	661	1880.0	28.0	28.0	0.251	0.251	
Hotspot			Edge 2	661	1880.0	28.0	28.0	0.074	0.074	
			Edge 3	661	1880.0	28.0	28.0	0.367	0.367	
			Edge 4	661	1880.0	28.0	28.0	0.035	0.035	

12.3. W-CDMA Band V

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	4183	836.6	23.0	22.1	0.146	0.180	
			Left Tilt	4183	836.6	23.0	22.1	0.086	0.106	
			Right Touch	4183	836.6	23.0	22.1	0.153	0.188	9
			Rightt Tilt	4183	836.6	23.0	22.1	0.097	0.119	
Body-worn & Hptspot	Rel 99 RMC	10	Rear	4183	836.6	23.0	22.1	0.330	0.406	10
			Front	4183	836.6	23.0	22.1	0.249	0.306	
Hotspot	Rel 99 RMC	10	Edge 2	4183	836.6	23.0	22.1	0.146	0.180	
			Edge 3	4183	836.6	23.0	22.1	0.049	0.061	
			Edge 4	4183	836.6	23.0	22.1	0.152	0.187	

12.4. W-CDMA Band II

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	Rel 99 RMC	0	Left Touch	9400	1880.0	22.5	21.4	0.141	0.182	
			Left Tilt	9400	1880.0	22.5	21.4	0.040	0.051	
			Right Touch	9400	1880.0	22.5	21.4	0.187	0.241	11
			Rightt Tilt	9400	1880.0	22.5	21.4	0.049	0.063	
Body-worn & Hptspot	Rel 99 RMC	10	Rear	9262	1852.4	22.5	21.2	0.697	**0.940**	12
			Rear	9400	1880.0	22.5	21.4	0.690	0.889	
			Rear	9538	1907.6	22.5	21.2	0.619	0.835	
			Front	9400	1880.0	22.5	21.4	0.287	0.370	
Hotspot	Rel 99 RMC	10	Edge 2	9400	1880.0	22.5	21.4	0.091	0.117	
			Edge 3	9400	1880.0	22.5	21.4	0.422	0.544	
			Edge 4	9400	1880.0	22.5	21.4	0.040	0.052	

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

12.5. Wi-Fi (DTS Band)

RF Exposure Conditions	Mode	Dist. (mm)	Test Position	Ch #.	Freq. (MHz)	Power (dBm)		1-g SAR (W/kg)		Plot No.
						Tune-up limit	Meas.	Meas.	Scaled	
Head	802.11b 1 Mbps	0	Left Touch	6	2437.0	16.5	16.5	0.098	**0.098**	13
			Left Tilt	6	2437.0	16.5	16.5	0.053	0.053	
			Right Touch	6	2437.0	16.5	16.5	0.059	0.059	
			Rightt Tilt	6	2437.0	16.5	16.5	0.043	0.043	
Body-worn & Hptspot	802.11b 1 Mbps	10	Rear	6	2437.0	16.5	16.5	0.075	**0.075**	14
			Front	6	2437.0	16.5	16.5	0.021	0.021	
Hotspot	802.11b 1 Mbps	10	Edge 1	6	2437.0	16.5	16.5	0.030	0.030	
			Edge 2	6	2437.0	16.5	16.5	0.029	0.029	

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000
FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

12.6. Bluetooth

12.6.1. Standalone SAR Test Exclusion Considerations

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]·[√f(GHz)] ≤ 3.0, for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{(GHz)}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Body-worn Accessory Exposure Conditions

Max. tune-up tolerance limit		Min. test separation distance (mm)	Frequency (GHz)	Result
(dBm)	(mW)			
12.5	18	10	2.480	2.8

Conclusion:

The computed value is < 3; therefore, Bluetooth qualifies for Standalone SAR test exclusion.

12.6.2. Estimated SAR

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

- *(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]·[√$f_{(GHz)}$/x]* W/kg for test separation distances ≤ 50 mm;
  where x = 7.5 for 1-g SAR, and x = 18.75 for 10-g SAR.
- 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Estimated SAR Result for Body-worn Accessory Conditions:

Test Configuration	Max. tune-up tolerance limit (mW)	Min. test separation distance (mm)	Frequency (GHz)	Estimated 1-g SAR (W/kg)
Rear/Front	18	10	2.480	0.378

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

13. SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

13.1. The Highest Measured SAR Configuration in Each Frequency Band

Frequency Band (MHz)	Air Interface	Head (W/kg)	Body-worn Accessory (W/kg)	Hotspot/Wi-Fi Direct (W/kg)	Repeated SAR (Yes/No)
850	GSM 850		0.574		No
	WCDMA Band V		0.330		No
1900	GSM 1900		0.600		No
	WCDMA Band II		0.697		No
2400	Wi-Fi 802.11b		0.098		No

13.2. Repeated Measurement Results

Head Exposure Condition
Not Applicable.

Body-worn Accessory Exposure Condition
Not Applicable.

Hotspot Mode Exposure Conditions
Not Applicable.

Note(s):

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not > 1.20.

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

14. Simultaneous Transmission SAR Analysis

KDB 447498 D01 General RF Exposure Guidance, introduces a new formula for calculating the SAR to Peak Location Ratio (SPLSR) between pairs of simultaneously transmitting antennas:

$$SPLSR = (SAR_1 + SAR_2)^{1.5} / Ri$$

Where:

SAR_1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition

SAR_2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first

Ri is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured for both antennas in the pair, it is determined by the actual x, y, and z coordinates in the 1-g SAR for each SAR Peak Location; based on the extrapolated and interpolated result in the zoom scan measurement using the formula:

$$[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$$

A new threshold of 0.04 is also introduced in the KDB 447498. Thus, in order for a pair of simultaneously transmitting antennas, with the sum of 1-g SAR > 1.6 W/kg, to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$(SAR_1 + SAR_2)^{1.5} / Ri < 0.04$$

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000
FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

14.1. Sum of the SAR for GSM850 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			∑ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM850	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.314	0.098		0.412	No
	Left Tilt	① + ②	0.178	0.053		0.231	No
	Right Touch	① + ②	0.307	0.059		0.366	No
	Right Tilt	① + ②	0.208	0.043		0.251	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.644	0.075		0.719	No
		① + ③	0.644		0.378	1.022	No
	Front	① + ②	0.486	0.021		0.507	No
		① + ③	0.486		0.378	0.864	No
Hotspot	Edge 1	① + ②	0.000	0.030		0.030	No
	Edge 2	① + ②	0.327	0.029		0.355	No
	Edge 3	① + ②	0.108	0.000		0.108	No
	Edge 4	① + ②	0.367	0.000		0.367	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because the either sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

14.2. Sum of the SAR for GSM1900 & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			∑ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① GSM1900	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.108	0.098		0.206	No
	Left Tilt	① + ②	0.039	0.053		0.091	No
	Right Touch	① + ②	0.158	0.059		0.217	No
	Right Tilt	① + ②	0.040	0.043		0.083	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.600	0.075		0.675	No
		① + ③	0.600		0.378	0.978	No
	Front	① + ②	0.251	0.021		0.272	No
		① + ③	0.251		0.378	0.629	No
Hotspot	Edge 1	① + ②	0.000	0.030		0.030	No
	Edge 2	① + ②	0.074	0.029		0.103	No
	Edge 3	① + ②	0.367	0.000		0.367	No
	Edge 4	① + ②	0.035	0.000		0.035	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because the either sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

UL Verification Services Inc.
FORM NO: CCSUP4031G
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

14.3. Sum of the SAR for WCDMA Band V & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			∑ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① W-CDMA Band V	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.180	0.098		0.278	No
	Left Tilt	① + ②	0.106	0.053		0.159	No
	Right Touch	① + ②	0.188	0.059		0.247	No
	Right Tilt	① + ②	0.119	0.043		0.162	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.406	0.075		0.481	No
		① + ③	0.406		0.378	0.784	No
	Front	① + ②	0.306	0.021		0.327	No
		① + ③	0.306		0.378	0.684	No
Hotspot	Edge 1	① + ②	0.000	0.030		0.030	No
	Edge 2	① + ②	0.180	0.029		0.209	No
	Edge 3	① + ②	0.061	0.000		0.061	No
	Edge 4	① + ②	0.187	0.000		0.187	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because the either sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

14.4. Sum of the SAR for WCDMA Band II & Wi-Fi & BT

RF Exposure conditions	Test Position		Simultaneous Transmission Scenario			∑ 1-g SAR (mW/g)	SPLSR (Yes/ No)
			① W-CDMA Band II	② Wi-Fi(DTS)	③ Bluetooth		
Head	Left Touch	① + ②	0.182	0.098		0.280	No
	Left Tilt	① + ②	0.051	0.053		0.104	No
	Right Touch	① + ②	0.241	0.059		0.300	No
	Right Tilt	① + ②	0.063	0.043		0.106	No
Body-worn Accessory & Hotspot	Rear	① + ②	0.940	0.075		**1.015**	No
		① + ③	0.940		0.378	1.318	No
	Front	① + ②	0.370	0.021		0.391	No
		① + ③	0.370		0.378	0.748	No
Hotspot	Edge 1	① + ②	0.000	0.030		0.030	No
	Edge 2	① + ②	0.117	0.029		0.146	No
	Edge 3	① + ②	0.544	0.000		0.544	No
	Edge 4	① + ②	0.052	0.000		0.052	No

SAR to Peak Location Separation Ratio (SPLSR)

As the Sum of the SAR is not greater than 1.6 W/kg SPLSR assessment is not required.

Conclusion:

Simultaneous transmission SAR measurement (Volume Scan) is not required because either the sum of the 1-g SAR is < 1.6 W/kg or the SPLSR is < 0.04 for all circumstances that require SPLSR calculation.

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

15. Appendixes

Refer to separated files for the following appendixes.

15.1. Photos and Antenna Locations

15.2. System Performance Check Plots

15.3. Highest SAR Test Plots

15.4. Calibration Certificate for E-Field Probe EX3DV4 - SN 3871

15.5. Calibration Certificate for E-Field Probe EX3DV4 - SN 3531

15.6. Calibration Certificate for E-Field Probe EX3DV3 - SN 3936

15.7. Calibration Certificate for D835V2 - SN 4d002

15.8. Calibration Certificate for D1900V2- SN 5d163

15.9. Calibration Certificate for D2450V2 - SN 899

END OF REPORT

UL Verification Services Inc.
47173 BENICIA STREET, FREMONT, CA 94538, USA
TEL: (510) 771-1000 FAX: (510) 661-0888
FORM NO: CCSUP4031G
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.