PCTEST ENGINEERING LABORATORY, INC.
7185 Oakland Mills Road, Columbia, MD 21046 USA
Tel. +1.410.290.6652 / Fax +1.410.290.6654
http://www.pctestlab.com

# SAR EVALUATION REPORT

**Applicant Name:**
Samsung Electronics, Co. Ltd.
129, Samsung-ro, Maetan dong,
Yeongtong-gu, Suwon-si
Gyeonggi-do 443-742, Korea

**Date of Testing:**
11/05/14 - 12/19/14
**Test Site/Location:**
PCTEST Lab, Columbia, MD, USA
**Document Serial No.:**
0Y1411052080-R1.A3L

**FCC ID:** **A3LSMG360V**

**APPLICANT:** **SAMSUNG ELECTRONICS, CO. LTD.**

**DUT Type:** Portable Handset
**Application Type:** Certification
**FCC Rule Part(s):** CFR §2.1093
**Model(s):** SM-G360V, SM-S820L

| Equipment Class | Band & Mode | Tx Frequency | SAR | | |
|---|---|---|---|---|---|
| | | | 1 gm Head (W/kg) | 1 gm Body-Worn (W/kg) | 1 gm Hotspot (W/kg) |
| PCE | Cell. CDMA/EVDO | 824.70 - 848.31 MHz | 0.72 | 0.91 | 0.96 |
| PCE | PCS CDMA/EVDO | 1851.25 - 1908.75 MHz | 1.09 | 0.83 | 0.87 |
| PCE | LTE Band 13 | 779.5 - 784.5 MHz | 0.52 | 0.94 | 0.94 |
| PCE | LTE Band 4 (AWS) | 1710.7 - 1754.3 MHz | 1.03 | 0.91 | 0.91 |
| PCE | LTE Band 2 (PCS) | 1850.7 - 1909.3 MHz | 1.06 | 0.94 | 0.95 |
| DTS | 2.4 GHz WLAN | 2412 - 2462 MHz | 0.20 | 0.11 | 0.11 |
| DSS/DTS | Bluetooth | 2402 - 2480 MHz | N/A | | |
| **Simultaneous SAR per KDB 690783 D01v01r03:** | | | 1.17 | 1.27 | 1.07 |

Note: This revised Test Report (S/N: 0Y1411052080-R1.A3L) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

Randy Ortanez
President

The SAR Tick is an initiative of the Mobile Manufacturers Forum (MMF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MMF. Further details can be obtained by emailing: sartick@mmfai.info.


© 2014 PCTEST Engineering Laboratory, Inc.

# TABLE OF CONTENTS


1 DEVICE UNDER TEST ....3

2 LTE INFORMATION ....7

3 INTRODUCTION ....8

4 DOSIMETRIC ASSESSMENT ....9

5 DEFINITION OF REFERENCE POINTS .... 10

6 TEST CONFIGURATION POSITIONS FOR HANDSETS .... 11

7 RF EXPOSURE LIMITS .... 14

8 FCC MEASUREMENT PROCEDURES .... 15

9 RF CONDUCTED POWERS .... 19

10 SYSTEM VERIFICATION .... 28

11 SAR DATA SUMMARY .... 30

12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS .... 37

13 SAR MEASUREMENT VARIABILITY .... 40

14 EQUIPMENT LIST .... 41

15 MEASUREMENT UNCERTAINTIES .... 42

16 CONCLUSION .... 43

17 REFERENCES .... 44

APPENDIX A: SAR TEST PLOTS

APPENDIX B: SAR DIPOLE VERIFICATION PLOTS

APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES

APPENDIX D: SAR TISSUE SPECIFICATIONS

APPENDIX E: SAR SYSTEM VALIDATION

APPENDIX F: SAR TEST SETUP PHOTOGRAPHS




© 2014 PCTEST Engineering Laboratory, Inc.

# 1 DEVICE UNDER TEST

## 1.1 Device Overview

| Band & Mode | Operating Modes | Tx Frequency |
|---|---|---|
| Cell. CDMA/EVDO | Voice/Data | 824.70 - 848.31 MHz |
| PCS CDMA/EVDO | Voice/Data | 1851.25 - 1908.75 MHz |
| LTE Band 13 | Voice/Data | 779.5 - 784.5 MHz |
| LTE Band 4 (AWS) | Voice/Data | 1710.7 - 1754.3 MHz |
| LTE Band 2 (PCS) | Voice/Data | 1850.7 - 1909.3 MHz |
| 2.4 GHz WLAN | Data | 2412 - 2462 MHz |
| Bluetooth | Data | 2402 - 2480 MHz |

## 1.2 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v05.

| Mode / Band | | Modulated Average (dBm) |
|---|---|---|
| Cell. CDMA/EVDO | Maximum | **25.0** |
| | Nominal | **24.5** |
| PCS CDMA/EVDO | Maximum | **25.0** |
| | Nominal | **24.5** |

| Mode / Band | | Modulated Average (dBm) |
|---|---|---|
| LTE Band 13 | Maximum | **24.0** |
| | Nominal | **23.5** |
| LTE Band 4 (AWS) | Maximum | **23.5** |
| | Nominal | **23.0** |
| LTE Band 2 (PCS) | Maximum | **22.7** |
| | Nominal | **22.2** |

| Mode / Band | | Modulated Average (dBm) |
|---|---|---|
| IEEE 802.11b (2.4 GHz) | Maximum | **13.5** |
| | Nominal | **13.0** |
| IEEE 802.11g (2.4 GHz) | Maximum | **13.0** |
| | Nominal | **12.5** |
| IEEE 802.11n (2.4 GHz) | Maximum | **13.0** |
| | Nominal | **12.5** |
| Bluetooth | Maximum | **12.0** |
| | Nominal | **11.5** |
| Bluetooth LE | Maximum | **3.5** |
| | Nominal | **3.0** |


© 2014 PCTEST Engineering Laboratory, Inc.

## 1.3 Sides for SAR Testing

The overall dimensions of this device are > 9 × 5 cm. The overall diagonal dimension of the device is < 160 mm and the diagonal display is < 150 mm. Exact antenna dimensions and separation distances are shown in the Technical Descriptions in the FCC filing.

**Table 1-1**
**Mobile Hotspot Sides for SAR Testing**

| Mode | Back | Front | Top | Bottom | Right | Left |
|---|---|---|---|---|---|---|
| Cell. EVDO | Yes | Yes | No | Yes | Yes | Yes |
| PCS EVDO | Yes | Yes | No | Yes | Yes | Yes |
| LTE Band 13 | Yes | Yes | No | Yes | Yes | Yes |
| LTE Band 4 (AWS) | Yes | Yes | No | Yes | Yes | Yes |
| LTE Band 2 (PCS) | Yes | Yes | No | Yes | Yes | Yes |
| 2.4 GHz WLAN | Yes | Yes | No | No | No | Yes |

Note: Particular DUT edges were not required to be evaluated for Wireless Router SAR if the edges were greater than 2.5 cm from the transmitting antenna according to FCC KDB Publication 941225 D06v01 guidance, page 2. The distances between the transmit antennas and the edges of the device are included in the filing.

## 1.4 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D05v01, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the DUT are shown in Figure 1-1 and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.




**Figure 1-1**
**Simultaneous Transmission Paths**

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v05 3) procedures.


© 2014 PCTEST Engineering Laboratory, Inc.

**Table 1-2**
**Simultaneous Transmission Scenarios**

| No. | Capable Transmit Configuration | Head | Body-Worn Accessory | Wireless Router | Notes |
|---|---|---|---|---|---|
| 1 | 1x CDMA voice + 2.4 GHz WI-FI | Yes | Yes | N/A | |
| 2 | 1x CDMA voice + 2.4 GHz Bluetooth | N/A | Yes | N/A | |
| 3 | LTE + 2.4 GHz WI-FI | Yes | Yes | Yes | |
| 4 | LTE + 2.4 GHz Bluetooth | N/A | Yes | N/A | |
| 5 | CDMA/EVDO data + 2.4 GHz WI-FI | Yes* | Yes* | Yes | *-Pre-installed VOIP applications are considered. |
| 6 | CDMA/EVDO data + 2.4 GHz Bluetooth | N/A | Yes* | N/A | *-Pre-installed VOIP applications are considered. |
| 7 | 1x CDMA voice + CDMA/EVDO data | N/A | N/A | N/A | Not supported by HW |
| 8 | CDMA/EVDO data + LTE | N/A | N/A | N/A | Not supported by HW |
| 9 | 1x CDMA voice + LTE | N/A | N/A | N/A | Not supported by HW |
| 10 | 1x CDMA voice + LTE + 2.4 GHz WI-FI | N/A | N/A | N/A | Not supported by HW |

1. 2.4 GHz WLAN, and 2.4 GHz Bluetooth share the same antenna path and cannot transmit simultaneously.
2. All licensed modes share the same antenna path and cannot transmit simultaneously.
3. Per the manufacturer, WIFI Direct is not expected to be used in conjunction with a held-to-ear or body-worn accessory voice call. Therefore, there are no simultaneous transmission scenarios involving WIFI direct beyond that listed in the above table.
4. This device supports VoLTE.

## 1.5 SAR Test Exclusions Applied

### (A) WIFI/BT

Per FCC KDB 447498 D01v05, the 1g SAR exclusion threshold for distances <50mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)} * \sqrt{Frequency(GHz)} \leq 3.0$$

Based on the maximum conducted power of Bluetooth (rounded to the nearest mW) and the antenna to user separation distance, body-worn Bluetooth SAR was not required; [(16/10)* √2.480] = 2.5 < 3.0. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

### (B) Licensed Transmitter(s)

LTE SAR for the higher modulations and lower bandwidths were not tested since the maximum average output power of all required channels and configurations was not more than 0.5 dB higher than the highest bandwidth; and the reported LTE SAR for the highest bandwidth was less than 1.45 W/kg for all configurations according to FCC KDB 941225 D05v02.

CDMA 1X Advanced technology was not required for SAR since the maximum output powers for 1x Advanced was not more than 0.25 dB higher than the maximum measured powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg.

## 1.6 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

## 1.7 Guidance Applied

- IEEE 1528-2003
- FCC KDB Publication 941225 D01v03, D05v02r03, D06v01r01 (2G/3G/4G and Hotspot)
- FCC KDB Publication 248227 D01v01r02 (SAR Considerations for 802.11 Devices)


© 2014 PCTEST Engineering Laboratory, Inc.

- FCC KDB Publication 447498 D01v05r02 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r03, D02v01r01 (SAR Measurements up to 6 GHz)

## 1.8 Device Serial Numbers

Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

| | Head Serial Number | Body-Worn Serial Number | Hotspot Serial Number |
|---|---|---|---|
| Cell. CDMA/EVDO | 0511-4 | 0511-4 | 0511-4 |
| PCS CDMA/EVDO | 0511-4 | 0511-4 | 0511-4 |
| LTE Band 13 | 0511-4 | 0511-4 | 0511-4 |
| LTE Band 4 (AWS) | 2811-7 | 2811-7 | 2811-7 |
| LTE Band 2 (PCS) | 2811-3 | 2811-3 | 2811-3 |
| 2.4 GHz WLAN | 0511-4 | 0511-4 | 0511-4 |


© 2014 PCTEST Engineering Laboratory, Inc.

# 2 LTE INFORMATION

| LTE Information | | | |
|---|---|---|---|
| **FCC ID** | **A3LSMG360V** | | |
| Form Factor | Portable Handset | | |
| Frequency Range of each LTE transmission band | LTE Band 13 (779.5 - 784.5 MHz) | | |
| | LTE Band 4 (AWS) (1710.7 - 1754.3 MHz) | | |
| | LTE Band 2 (PCS) (1850.7 - 1909.3 MHz) | | |
| Channel Bandwidths | LTE Band 13: 5 MHz, 10 MHz | | |
| | LTE Band 4 (AWS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz | | |
| | LTE Band 2 (PCS): 1.4 MHz, 3 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz | | |
| Channel Numbers and Frequencies (MHz) | Low | Mid | High |
| LTE Band 13: 5 MHz | 779.5 (23205) | 782 (23230) | 784.5 (23255) |
| LTE Band 13: 10 MHz | 782 (23230) | 782 (23230) | 782 (23230) |
| LTE Band 4 (AWS): 1.4 MHz | 1710.7 (19957) | 1732.5 (20175) | 1754.3 (20393) |
| LTE Band 4 (AWS): 3 MHz | 1711.5 (19965) | 1732.5 (20175) | 1753.5 (20385) |
| LTE Band 4 (AWS): 5 MHz | 1712.5 (19975) | 1732.5 (20175) | 1752.5 (20375) |
| LTE Band 4 (AWS): 10 MHz | 1715 (20000) | 1732.5 (20175) | 1750 (20350) |
| LTE Band 4 (AWS): 15 MHz | 1717.5 (20025) | 1732.5 (20175) | 1747.5 (20325) |
| LTE Band 4 (AWS): 20 MHz | 1720 (20050) | 1732.5 (20175) | 1745 (20300) |
| LTE Band 2 (PCS): 1.4 MHz | 1850.7 (18607) | 1880 (18900) | 1909.3 (19193) |
| LTE Band 2 (PCS): 3 MHz | 1851.5 (18615) | 1880 (18900) | 1908.5 (19185) |
| LTE Band 2 (PCS): 5 MHz | 1852.5 (18625) | 1880 (18900) | 1907.5 (19175) |
| LTE Band 2 (PCS): 10 MHz | 1855 (18650) | 1880 (18900) | 1905 (19150) |
| LTE Band 2 (PCS): 15 MHz | 1857.5 (18675) | 1880 (18900) | 1902.5 (19125) |
| LTE Band 2 (PCS): 20 MHz | 1860 (18700) | 1880 (18900) | 1900 (19100) |
| UE Category | 3 | | |
| Modulations Supported in UL | QPSK, 16QAM | | |
| LTE MPR Permanently implemented per 3GPP TS 36.101 section 6.2.3~6.2.5? (manufacturer attestation to be provided) | YES | | |
| A-MPR (Additional MPR) disabled for SAR Testing? | YES | | |


© 2014 PCTEST Engineering Laboratory, Inc.

# 3 INTRODUCTION

The FCC and Industry Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

## 3.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 3-1).

**Equation 3-1**
**SAR Mathematical Equation**

$$SAR = \frac{d}{dt}\left(\frac{dU}{dm}\right) = \frac{d}{dt}\left(\frac{dU}{\rho dv}\right)$$

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

σ = conductivity of the tissue-simulating material (S/m)
ρ = mass density of the tissue-simulating material (kg/m$^3$)
E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


© 2014 PCTEST Engineering Laboratory, Inc.

# 4 DOSIMETRIC ASSESSMENT

## 4.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01 and IEEE 1528-2013:



**Figure 4-1**
**Sample SAR Area Scan**

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01 (See Table 4-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):

   a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 4-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).

   b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.

   c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.

**Table 4-1**
**Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01***

| Frequency | Maximum Area Scan Resolution (mm) ($\Delta x_{area}$, $\Delta y_{area}$) | Maximum Zoom Scan Resolution (mm) ($\Delta x_{zoom}$, $\Delta y_{zoom}$) | Maximum Zoom Scan Spatial Resolution (mm) | | | Minimum Zoom Scan Volume (mm) (x,y,z) |
|---|---|---|---|---|---|---|
| | | | Uniform Grid | Graded Grid | | |
| | | | $\Delta z_{zoom}(n)$ | $\Delta z_{zoom}(1)$* | $\Delta z_{zoom}(n>1)$* | |
| ≤ 2 GHz | ≤ 15 | ≤ 8 | ≤ 5 | ≤ 4 | ≤ 1.5*$\Delta z_{zoom}(n-1)$ | ≥ 30 |
| 2-3 GHz | ≤ 12 | ≤ 5 | ≤ 5 | ≤ 4 | ≤ 1.5*$\Delta z_{zoom}(n-1)$ | ≥ 30 |
| 3-4 GHz | ≤ 12 | ≤ 5 | ≤ 4 | ≤ 3 | ≤ 1.5*$\Delta z_{zoom}(n-1)$ | ≥ 28 |
| 4-5 GHz | ≤ 10 | ≤ 4 | ≤ 3 | ≤ 2.5 | ≤ 1.5*$\Delta z_{zoom}(n-1)$ | ≥ 25 |
| 5-6 GHz | ≤ 10 | ≤ 4 | ≤ 2 | ≤ 2 | ≤ 1.5*$\Delta z_{zoom}(n-1)$ | ≥ 22 |

*Also compliant to IEEE 1528-2013 Table 6


© 2014 PCTEST Engineering Laboratory, Inc.

# 5 DEFINITION OF REFERENCE POINTS

## 5.1 EAR REFERENCE POINT

Figure 5-2 shows the front, back and side views of the SAM Twin Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point (ERP), and "RE" is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 5-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front), also called the Reference Pivoting Line, is not perpendicular to the reference plane (see Figure 5-1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




**Figure 5-1**
**Close-Up Side view of ERP**

## 5.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the acoustic output located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Figure 5-3). The acoustic output was than located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at its top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.

**Figure 5-2**
**Front, back and side view of SAM Twin Phantom**




**Figure 5-3**
**Handset Vertical Center & Horizontal Line Reference Points**


© 2014 PCTEST Engineering Laboratory, Inc.

# 6 TEST CONFIGURATION POSITIONS FOR HANDSETS

## 6.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity ε = 3 and loss tangent δ = 0.02.

## 6.2 Positioning for Cheek

1. The test device was positioned with the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.

**Figure 6-1 Front, Side and Top View of Cheek Position**

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the pinna.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the reference plane.
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical was respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the device contact with the ear, the device was rotated about the NF line until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 6-2).

## 6.3 Positioning for Ear / 15º Tilt

With the test device aligned in the “Cheek Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15degrees.
2. The phone was then rotated around the horizontal line by 15 degrees.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the handset touched the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. In this situation, the tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 6-2).


© 2014 PCTEST Engineering Laboratory, Inc.




**Figure 6-2 Front, Side and Top View of Ear/15º Tilt Position**




**Figure 6-3**
**Side view w/ relevant markings**

## 6.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. Per IEEE 1528-2013, a rotated SAM phantom is necessary to allow probe access to such regions. Both SAM heads of the TwinSAM-Chin20 are rotated 20 degrees around the NF line. Each head can be removed from the table for emptying and cleaning.

Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document FCC KDB Publication 648474 D04_v01. The SAR required in these regions of SAM should be measured using a flat phantom. The phone should be positioned with a separation distance of 4 mm between the ear reference point (ERP) and the outer surface of the flat phantom shell. While maintaining this distance at the ERP location, the low (bottom) edge of the phone should be lowered from the phantom to establish the same separation distance between the peak SAR location identified by the truncated partial SAR distribution measured with the SAM phantom. The distance from the peak SAR location to the phone is determined by the straight line passing perpendicularly through the phantom surface. When it is not feasible to maintain 4 mm separation at the ERP while also establishing the required separation at the peak SAR location, the top edge of the phone will be allowed to touch the phantom with a separation < 4 mm at the ERP. The phone should not be tilted to the left or right while placed in this inclined position to the flat phantom.

## 6.5 Body-Worn Accessory Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6-4). Per FCC KDB Publication 648474 D04v01, Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB Publication 447498 D01v05 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.




**Figure 6-4**
**Sample Body-Worn Diagram**

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories


© 2014 PCTEST Engineering Laboratory, Inc.

that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

## 6.6 Extremity Exposure Configurations

Devices that are designed or intended for use on extremities or mainly operated in extremity only exposure conditions; i.e., hands, wrists, feet and ankles, may require extremity SAR evaluation. When the device also operates in close proximity to the user's body, SAR compliance for the body is also required. The 1-g body and 10-g extremity SAR Exclusion Thresholds found in KDB Publication 44798 D01v05 should be applied to determine SAR test requirements.

Per KDB Publication 447498 D01v05, Cell phones (handsets) are not normally designed to be used on extremities or operated in extremity only exposure conditions. The maximum output power levels of handsets generally do not require extremity SAR testing to show compliance. Therefore, extremity SAR was not evaluated for this device.

## 6.7 Wireless Router Configurations

Some battery-operated handsets have the capability to transmit and receive user data through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v01 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device containing transmitting antennas within 2.5 cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v05 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.


© 2014 PCTEST Engineering Laboratory, Inc.

# 7 RF EXPOSURE LIMITS

## 7.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

## 7.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 7-1**
**SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

| HUMAN EXPOSURE LIMITS | | |
|---|---|---|
| | UNCONTROLLED ENVIRONMENT *General Population* (W/kg) or (mW/g) | CONTROLLED ENVIRONMENT *Occupational* (W/kg) or (mW/g) |
| **Peak Spatial Average SAR** Head | 1.6 | 8.0 |
| **Whole Body SAR** | 0.08 | 0.4 |
| **Peak Spatial Average SAR** Hands, Feet, Ankle, Wrists, etc. | 4.0 | 20 |

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.


© 2014 PCTEST Engineering Laboratory, Inc.

# 8 FCC MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

## 8.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v05, When SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r02.

## 8.2 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 “SAR Measurement Procedures for 3G Devices” v02, October 2007.

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a “point SAR” at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. If the power drift deviated by more than 5%, the SAR test and drift measurements were repeated.

## 8.3 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01 “SAR Measurement Procedures for 3G Devices” v02, October 2007.

### 8.3.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by “SAR Measurement Procedures for 3G Devices” v02, October 2007. Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the “All Up” condition.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 8-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse $SCH_0$ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH0 data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 8-2 was applied.


© 2014 PCTEST Engineering Laboratory, Inc.

**Table 8-1**
**Parameters for Max. Power for RC1**

| Parameter | Units | Value |
|---|---|---|
| $I_{or}$ | dBm/1.23 MHz | -104 |
| $\frac{\text{Pilot } E_c}{I_{or}}$ | dB | -7 |
| $\frac{\text{Traffic } E_c}{I_{or}}$ | dB | -7.4 |

**Table 8-2**
**Parameters for Max. Power for RC3**

| Parameter | Units | Value |
|---|---|---|
| $I_{or}$ | dBm/1.23 MHz | -86 |
| $\frac{\text{Pilot } E_c}{I_{or}}$ | dB | -7 |
| $\frac{\text{Traffic } E_c}{I_{or}}$ | dB | -7.4 |

5. FCHs were configured at full rate for maximum SAR with “All Up” power control bits.

### 8.3.2 CDMA2000 1x Advanced

This device additionally supports 1x Advanced. Conducted powers were measured using SO75 with RC8 on the uplink and RC11 on the downlink per KDB Publication 941225 D01v03. Smart blanking was disabled for all measurements. The EUT was configured with forward power control Mode 000 and reverse power control at 400 bps. Conducted powers were measured on an Agilent 8960 Series 10 Wireless Communications Test Set, Model E5515C using the CDMA2000 1x Advanced application, Option E1962B-410.

Based on the maximum output power measured for 1x Advanced, SAR is required for 1x advanced when the maximum output for 1x Advanced is more than 0.25 dB higher than the maximum measured for 1x. Also, if the measured SAR in any 1x mode exposure conditions (head, body etc.) is larger than 1.2 W/kg, the highest of those configurations above 1.2 W/kg for each exposure condition in 1x Advanced has to be repeated. All measured SAR in 1x mode higher than 1.5 W/kg must be repeated for 1x Advanced.

### 8.3.3 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

Head SAR was additionally evaluated using EVDO Rev. A to support compliance for VoIP operations. See Section 8.3.5 for EVDO Rev. A configuration parameters.

### 8.3.4 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + $SCH_n$) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + $SCH_n$) with FCH at full rate and $SCH_0$ enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR was measured using TDSO / SO32 with power control bits in the “All Up”

Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.


© 2014 PCTEST Engineering Laboratory, Inc.

### 8.3.5 Handsets with EVDO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for EV-DO is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots would be configured in the downlink for both Rev. 0 and Rev. A.

### 8.3.6 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 per KDB Publication 941225 D01 procedures for "1x Ev-Do data Devices". SAR for Subtype 2 Physical layer configurations is not required for Rev. A when the maximum average output of each RF channels is less than that measured in Subtype 0/1 Physical layer configurations. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for the RF channels in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations.

SAR is not required for 1x RTT for Ev-Do devices that also support 1x RTT voice and/or data operations, when the maximum average output of each channel is less than 1⁄4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0. Otherwise, CDMA "Body-SAR Measurement" procedures for "CDMA 2000 1x Handsets" were applied.

## 8.4 SAR Measurement Conditions for LTE

LTE modes were tested according to FCC KDB 941225 D05v02 publication. Please see notes after the tabulated SAR data for required test configurations. Establishing connections with base station simulators ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. The R&S CMW500 was used for LTE output power measurements and SAR testing. Closed loop power control was used so the UE transmits with maximum output power during SAR testing. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

### 8.4.1 Spectrum Plots for RB Configurations

A properly configured base station simulator was used for SAR tests and power measurements. Therefore, spectrum plots for RB configurations were not required to be included in this report.

### 8.4.2 MPR

MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.

### 8.4.3 A-MPR

A-MPR (Additional MPR) has been disabled for all SAR tests by setting NS=01 on the base station simulator.


© 2014 PCTEST Engineering Laboratory, Inc.

### 8.4.4 Required RB Size and RB Offsets for SAR Testing

According to FCC KDB 941225 D05v02r01:

a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
   i. The required channel and offset combination with the highest maximum output power is required for SAR.
   ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
   iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to ½ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is <1.45 W/kg.

## 8.5 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 b/g/n transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v01r02 for more details.

### 8.5.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

### 8.5.2 Frequency Channel Configurations [24]

For 2.4 GHz, the highest average RF output power channel between the low, mid and high channel at the lowest data rate was selected for SAR evaluation in 802.11b mode. 802.11g/n modes and higher data rates for 802.11b were additionally evaluated for SAR if the output power of the respective mode was 0.25 dB or higher than the powers of the SAR configurations tested in the 802.11b mode.

If the maximum extrapolated peak SAR of the zoom scan for the highest output channel was less than 1.6 W/kg and if the 1g averaged SAR was less than 0.8 W/kg, SAR testing was not required for the other test channels in the band.


© 2014 PCTEST Engineering Laboratory, Inc.

# 9 RF CONDUCTED POWERS

## 9.1 CDMA Conducted Powers

| Band | Channel | Frequency | SO55 [dBm] | SO55 [dBm] | SO75 [dBm] | TDSO SO32 [dBm] | TDSO SO32 [dBm] | 1x EvDO Rev. 0 [dBm] | 1x EvDO Rev. A [dBm] |
|---|---|---|---|---|---|---|---|---|---|
| | F-RC | MHz | RC1 | RC3 | RC11 | FCH+SCH | FCH | (RTAP) | (RETAP) |
| Cellular | 1013 | 824.7 | 24.32 | 24.34 | 24.20 | 24.33 | 24.32 | 24.44 | 24.43 |
| | 384 | 836.52 | 24.26 | 24.28 | 24.17 | 24.31 | 24.36 | 24.41 | 24.39 |
| | 777 | 848.31 | 24.33 | 24.31 | 24.23 | 24.36 | 24.38 | 24.38 | 24.36 |
| PCS | 25 | 1851.25 | 24.16 | 24.18 | 23.93 | 24.27 | 24.28 | 24.14 | 24.09 |
| | 600 | 1880 | 24.42 | 24.38 | 24.10 | 24.33 | 24.42 | 24.39 | 24.38 |
| | 1175 | 1908.75 | 24.59 | 24.57 | 24.44 | 24.62 | 24.55 | 24.59 | 24.57 |

Note: RC1 is only applicable for IS-95 compatibility.

Per KDB Publication 941225 D01v03:

1. Head SAR was tested with SO55 RC3. SO55 RC1 was not required since the average output power was not more than 0.25 dB than the SO55 RC3 powers.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. Ev-Do and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers.
3. Hotspot SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. If the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, then Rev. A SAR is not required. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for that RF channel in Rev. 0. SAR is not required for 1x RTT for Ev-Do hotspot devices when the maximum average output of each channel is less than 1⁄4 dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0.
4. Head SAR was additionally evaluated with EVDO Rev. A to determine compliance for held-to-ear VoIP operations.
5. CDMA 1x Advanced technology was not required for SAR since the maximum output powers for 1x Advanced was not more than 0.25 dB higher than the maximum measured powers for 1x and the measured SAR in any 1x mode exposure conditions was not greater than 1.2 W/kg. See Section 8.3.2 for 1x Advanced test set up.

**Figure 9-1**
**Power Measurement Setup**


© 2014 PCTEST Engineering Laboratory, Inc.

## 9.2 LTE Conducted Powers

### 9.2.1 LTE Band 13

**Table 9-1**
**LTE Band 13 Conducted Powers - 10 MHz Bandwidth**

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Mid | 782.0 | 23230 | 10 | QPSK | 1 | 0 | **23.91** | 0 | 0 |
| | 782.0 | 23230 | 10 | QPSK | 1 | 25 | 23.23 | 0 | 0 |
| | 782.0 | 23230 | 10 | QPSK | 1 | 49 | 23.24 | 0 | 0 |
| | 782.0 | 23230 | 10 | QPSK | 25 | 0 | **22.49** | 0-1 | 1 |
| | 782.0 | 23230 | 10 | QPSK | 25 | 12 | 22.20 | 0-1 | 1 |
| | 782.0 | 23230 | 10 | QPSK | 25 | 25 | 22.12 | 0-1 | 1 |
| | 782.0 | 23230 | 10 | QPSK | 50 | 0 | 22.35 | 0-1 | 1 |
| | 782.0 | 23230 | 10 | 16QAM | 1 | 0 | 23.00 | 0-1 | 1 |
| | 782.0 | 23230 | 10 | 16QAM | 1 | 25 | 22.61 | 0-1 | 1 |
| | 782.0 | 23230 | 10 | 16QAM | 1 | 49 | 22.60 | 0-1 | 1 |
| | 782.0 | 23230 | 10 | 16QAM | 25 | 0 | 21.61 | 0-2 | 2 |
| | 782.0 | 23230 | 10 | 16QAM | 25 | 12 | 21.31 | 0-2 | 2 |
| | 782.0 | 23230 | 10 | 16QAM | 25 | 25 | 21.20 | 0-2 | 2 |
| | 782.0 | 23230 | 10 | 16QAM | 50 | 0 | 21.44 | 0-2 | 2 |

**Table 9-2**
**LTE Band 13 Conducted Powers - 5 MHz Bandwidth**

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Mid | 782.0 | 23230 | 5 | QPSK | 1 | 0 | 23.72 | 0 | 0 |
| | 782.0 | 23230 | 5 | QPSK | 1 | 12 | 23.20 | 0 | 0 |
| | 782.0 | 23230 | 5 | QPSK | 1 | 24 | 23.25 | 0 | 0 |
| | 782.0 | 23230 | 5 | QPSK | 12 | 0 | 22.42 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | QPSK | 12 | 6 | 22.25 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | QPSK | 12 | 13 | 22.15 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | QPSK | 25 | 0 | 22.24 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | 16-QAM | 1 | 0 | 23.00 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | 16-QAM | 1 | 12 | 22.57 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | 16-QAM | 1 | 24 | 22.58 | 0-1 | 1 |
| | 782.0 | 23230 | 5 | 16-QAM | 12 | 0 | 21.53 | 0-2 | 2 |
| | 782.0 | 23230 | 5 | 16-QAM | 12 | 6 | 21.36 | 0-2 | 2 |
| | 782.0 | 23230 | 5 | 16-QAM | 12 | 13 | 21.25 | 0-2 | 2 |
| | 782.0 | 23230 | 5 | 16-QAM | 25 | 0 | 21.34 | 0-2 | 2 |

Note: LTE Band 13 at 5 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.


© 2014 PCTEST Engineering Laboratory, Inc.

### 9.2.2 LTE Band 4 (AWS)

**Table 9-3**
**LTE Band 4 (AWS) Conducted Powers - 20 MHz Bandwidth**

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Mid | 1732.5 | 20175 | 20 | QPSK | 1 | 0 | 23.16 | 0 | 0 |
| | 1732.5 | 20175 | 20 | QPSK | 1 | 50 | **23.47** | 0 | 0 |
| | 1732.5 | 20175 | 20 | QPSK | 1 | 99 | 23.24 | 0 | 0 |
| | 1732.5 | 20175 | 20 | QPSK | 50 | 0 | 21.97 | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | QPSK | 50 | 25 | **22.09** | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | QPSK | 50 | 50 | 21.63 | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | QPSK | 100 | 0 | 21.89 | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | 16QAM | 1 | 0 | 21.54 | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | 16QAM | 1 | 50 | 21.93 | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | 16QAM | 1 | 99 | 21.50 | 0-1 | 1 |
| | 1732.5 | 20175 | 20 | 16QAM | 50 | 0 | 21.11 | 0-2 | 2 |
| | 1732.5 | 20175 | 20 | 16QAM | 50 | 25 | 21.17 | 0-2 | 2 |
| | 1732.5 | 20175 | 20 | 16QAM | 50 | 50 | 20.78 | 0-2 | 2 |
| | 1732.5 | 20175 | 20 | 16QAM | 100 | 0 | 21.05 | 0-2 | 2 |

Note: LTE Band 4 (AWS) at 20 MHz bandwidth does not support three non-overlapping channels. Per KDB Publication 941225 D05v02, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**Table 9-4**
**LTE Band 4 (AWS) Conducted Powers - 15 MHz Bandwidth**

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1717.5 | 20025 | 15 | QPSK | 1 | 0 | 22.51 | 0 | 0 |
| | 1717.5 | 20025 | 15 | QPSK | 1 | 36 | 22.62 | 0 | 0 |
| | 1717.5 | 20025 | 15 | QPSK | 1 | 74 | 22.55 | 0 | 0 |
| | 1717.5 | 20025 | 15 | QPSK | 36 | 0 | 21.71 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | QPSK | 36 | 18 | 21.57 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | QPSK | 36 | 37 | 21.76 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | QPSK | 75 | 0 | 21.68 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | 16QAM | 1 | 0 | 21.87 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | 16QAM | 1 | 36 | 21.83 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | 16QAM | 1 | 74 | 21.55 | 0-1 | 1 |
| | 1717.5 | 20025 | 15 | 16QAM | 36 | 0 | 20.70 | 0-2 | 2 |
| | 1717.5 | 20025 | 15 | 16QAM | 36 | 18 | 20.57 | 0-2 | 2 |
| | 1717.5 | 20025 | 15 | 16QAM | 36 | 37 | 20.65 | 0-2 | 2 |
| | 1717.5 | 20025 | 15 | 16QAM | 75 | 0 | 20.58 | 0-2 | 2 |
| Mid | 1732.5 | 20175 | 15 | QPSK | 1 | 0 | 22.93 | 0 | 0 |
| | 1732.5 | 20175 | 15 | QPSK | 1 | 36 | 23.16 | 0 | 0 |
| | 1732.5 | 20175 | 15 | QPSK | 1 | 74 | 22.74 | 0 | 0 |
| | 1732.5 | 20175 | 15 | QPSK | 36 | 0 | 22.11 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | QPSK | 36 | 18 | 22.16 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | QPSK | 36 | 37 | 21.84 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | QPSK | 75 | 0 | 21.99 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | 16QAM | 1 | 0 | 22.14 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | 16QAM | 1 | 36 | 22.42 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | 16QAM | 1 | 74 | 21.93 | 0-1 | 1 |
| | 1732.5 | 20175 | 15 | 16QAM | 36 | 0 | 21.16 | 0-2 | 2 |
| | 1732.5 | 20175 | 15 | 16QAM | 36 | 18 | 21.22 | 0-2 | 2 |
| | 1732.5 | 20175 | 15 | 16QAM | 36 | 37 | 20.89 | 0-2 | 2 |
| | 1732.5 | 20175 | 15 | 16QAM | 75 | 0 | 20.96 | 0-2 | 2 |
| High | 1747.5 | 20325 | 15 | QPSK | 1 | 0 | 23.35 | 0 | 0 |
| | 1747.5 | 20325 | 15 | QPSK | 1 | 36 | 23.07 | 0 | 0 |
| | 1747.5 | 20325 | 15 | QPSK | 1 | 74 | 22.97 | 0 | 0 |
| | 1747.5 | 20325 | 15 | QPSK | 36 | 0 | 22.02 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | QPSK | 36 | 18 | 21.75 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | QPSK | 36 | 37 | 21.97 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | QPSK | 75 | 0 | 21.89 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | 16QAM | 1 | 0 | 22.27 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | 16QAM | 1 | 36 | 21.62 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | 16QAM | 1 | 74 | 21.86 | 0-1 | 1 |
| | 1747.5 | 20325 | 15 | 16QAM | 36 | 0 | 21.12 | 0-2 | 2 |
| | 1747.5 | 20325 | 15 | 16QAM | 36 | 18 | 20.75 | 0-2 | 2 |
| | 1747.5 | 20325 | 15 | 16QAM | 36 | 37 | 20.69 | 0-2 | 2 |
| | 1747.5 | 20325 | 15 | 16QAM | 75 | 0 | 20.87 | 0-2 | 2 |


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 9-5
## LTE Band 4 (AWS) Conducted Powers - 10 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1715 | 20000 | 10 | QPSK | 1 | 0 | 22.50 | 0 | 0 |
| | 1715 | 20000 | 10 | QPSK | 1 | 25 | 22.71 | 0 | 0 |
| | 1715 | 20000 | 10 | QPSK | 1 | 49 | 22.76 | 0 | 0 |
| | 1715 | 20000 | 10 | QPSK | 25 | 0 | 21.65 | 0-1 | 1 |
| | 1715 | 20000 | 10 | QPSK | 25 | 12 | 21.57 | 0-1 | 1 |
| | 1715 | 20000 | 10 | QPSK | 25 | 25 | 21.58 | 0-1 | 1 |
| | 1715 | 20000 | 10 | QPSK | 50 | 0 | 21.51 | 0-1 | 1 |
| | 1715 | 20000 | 10 | 16QAM | 1 | 0 | 21.56 | 0-1 | 1 |
| | 1715 | 20000 | 10 | 16QAM | 1 | 25 | 21.89 | 0-1 | 1 |
| | 1715 | 20000 | 10 | 16QAM | 1 | 49 | 21.50 | 0-1 | 1 |
| | 1715 | 20000 | 10 | 16QAM | 25 | 0 | 20.66 | 0-2 | 2 |
| | 1715 | 20000 | 10 | 16QAM | 25 | 12 | 20.73 | 0-2 | 2 |
| | 1715 | 20000 | 10 | 16QAM | 25 | 25 | 20.75 | 0-2 | 2 |
| | 1715 | 20000 | 10 | 16QAM | 50 | 0 | 20.57 | 0-2 | 2 |
| Mid | 1732.5 | 20175 | 10 | QPSK | 1 | 0 | 22.86 | 0 | 0 |
| | 1732.5 | 20175 | 10 | QPSK | 1 | 25 | 23.44 | 0 | 0 |
| | 1732.5 | 20175 | 10 | QPSK | 1 | 49 | 22.82 | 0 | 0 |
| | 1732.5 | 20175 | 10 | QPSK | 25 | 0 | 22.25 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | QPSK | 25 | 12 | 22.09 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | QPSK | 25 | 25 | 21.88 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | QPSK | 50 | 0 | 22.07 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | 16QAM | 1 | 0 | 21.97 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | 16QAM | 1 | 25 | 22.00 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | 16QAM | 1 | 49 | 21.69 | 0-1 | 1 |
| | 1732.5 | 20175 | 10 | 16QAM | 25 | 0 | 21.28 | 0-2 | 2 |
| | 1732.5 | 20175 | 10 | 16QAM | 25 | 12 | 21.12 | 0-2 | 2 |
| | 1732.5 | 20175 | 10 | 16QAM | 25 | 25 | 21.01 | 0-2 | 2 |
| | 1732.5 | 20175 | 10 | 16QAM | 50 | 0 | 20.87 | 0-2 | 2 |
| High | 1750 | 20350 | 10 | QPSK | 1 | 0 | 23.15 | 0 | 0 |
| | 1750 | 20350 | 10 | QPSK | 1 | 25 | 23.12 | 0 | 0 |
| | 1750 | 20350 | 10 | QPSK | 1 | 49 | 23.08 | 0 | 0 |
| | 1750 | 20350 | 10 | QPSK | 25 | 0 | 21.76 | 0-1 | 1 |
| | 1750 | 20350 | 10 | QPSK | 25 | 12 | 21.79 | 0-1 | 1 |
| | 1750 | 20350 | 10 | QPSK | 25 | 25 | 21.73 | 0-1 | 1 |
| | 1750 | 20350 | 10 | QPSK | 50 | 0 | 21.66 | 0-1 | 1 |
| | 1750 | 20350 | 10 | 16QAM | 1 | 0 | 21.77 | 0-1 | 1 |
| | 1750 | 20350 | 10 | 16QAM | 1 | 25 | 21.92 | 0-1 | 1 |
| | 1750 | 20350 | 10 | 16QAM | 1 | 49 | 21.95 | 0-1 | 1 |
| | 1750 | 20350 | 10 | 16QAM | 25 | 0 | 20.99 | 0-2 | 2 |
| | 1750 | 20350 | 10 | 16QAM | 25 | 12 | 20.71 | 0-2 | 2 |
| | 1750 | 20350 | 10 | 16QAM | 25 | 25 | 20.77 | 0-2 | 2 |
| | 1750 | 20350 | 10 | 16QAM | 50 | 0 | 20.55 | 0-2 | 2 |

## Table 9-6
## LTE Band 4 (AWS) Conducted Powers - 5 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1712.5 | 19975 | 5 | QPSK | 1 | 0 | 22.69 | 0 | 0 |
| | 1712.5 | 19975 | 5 | QPSK | 1 | 12 | 23.25 | 0 | 0 |
| | 1712.5 | 19975 | 5 | QPSK | 1 | 24 | 23.07 | 0 | 0 |
| | 1712.5 | 19975 | 5 | QPSK | 12 | 0 | 21.62 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | QPSK | 12 | 6 | 21.69 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | QPSK | 12 | 13 | 22.03 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | QPSK | 25 | 0 | 21.70 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | 16-QAM | 1 | 0 | 21.81 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | 16-QAM | 1 | 12 | 22.36 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | 16-QAM | 1 | 24 | 22.20 | 0-1 | 1 |
| | 1712.5 | 19975 | 5 | 16-QAM | 12 | 0 | 20.58 | 0-2 | 2 |
| | 1712.5 | 19975 | 5 | 16-QAM | 12 | 6 | 20.68 | 0-2 | 2 |
| | 1712.5 | 19975 | 5 | 16-QAM | 12 | 13 | 20.82 | 0-2 | 2 |
| | 1712.5 | 19975 | 5 | 16-QAM | 25 | 0 | 20.54 | 0-2 | 2 |
| Mid | 1732.5 | 20175 | 5 | QPSK | 1 | 0 | 23.42 | 0 | 0 |
| | 1732.5 | 20175 | 5 | QPSK | 1 | 12 | 23.41 | 0 | 0 |
| | 1732.5 | 20175 | 5 | QPSK | 1 | 24 | 23.00 | 0 | 0 |
| | 1732.5 | 20175 | 5 | QPSK | 12 | 0 | 22.35 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | QPSK | 12 | 6 | 22.20 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | QPSK | 12 | 13 | 22.02 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | QPSK | 25 | 0 | 22.21 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | 16-QAM | 1 | 0 | 21.96 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | 16-QAM | 1 | 12 | 22.27 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | 16-QAM | 1 | 24 | 22.41 | 0-1 | 1 |
| | 1732.5 | 20175 | 5 | 16-QAM | 12 | 0 | 21.20 | 0-2 | 2 |
| | 1732.5 | 20175 | 5 | 16-QAM | 12 | 6 | 21.11 | 0-2 | 2 |
| | 1732.5 | 20175 | 5 | 16-QAM | 12 | 13 | 20.90 | 0-2 | 2 |
| | 1732.5 | 20175 | 5 | 16-QAM | 25 | 0 | 21.14 | 0-2 | 2 |
| High | 1752.5 | 20375 | 5 | QPSK | 1 | 0 | 22.93 | 0 | 0 |
| | 1752.5 | 20375 | 5 | QPSK | 1 | 12 | 23.42 | 0 | 0 |
| | 1752.5 | 20375 | 5 | QPSK | 1 | 24 | 23.42 | 0 | 0 |
| | 1752.5 | 20375 | 5 | QPSK | 12 | 0 | 22.19 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | QPSK | 12 | 6 | 22.16 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | QPSK | 12 | 13 | 22.28 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | QPSK | 25 | 0 | 22.13 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | 16-QAM | 1 | 0 | 22.31 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | 16-QAM | 1 | 12 | 22.47 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | 16-QAM | 1 | 24 | 22.46 | 0-1 | 1 |
| | 1752.5 | 20375 | 5 | 16-QAM | 12 | 0 | 21.34 | 0-2 | 2 |
| | 1752.5 | 20375 | 5 | 16-QAM | 12 | 6 | 21.49 | 0-2 | 2 |
| | 1752.5 | 20375 | 5 | 16-QAM | 12 | 13 | 21.47 | 0-2 | 2 |
| | 1752.5 | 20375 | 5 | 16-QAM | 25 | 0 | 21.20 | 0-2 | 2 |


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 9-7
## LTE Band 4 (AWS) Conducted Powers - 3 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1711.5 | 19965 | 3 | QPSK | 1 | 0 | 22.69 | 0 | 0 |
| | 1711.5 | 19965 | 3 | QPSK | 1 | 7 | 22.87 | 0 | 0 |
| | 1711.5 | 19965 | 3 | QPSK | 1 | 14 | 22.84 | 0 | 0 |
| | 1711.5 | 19965 | 3 | QPSK | 8 | 0 | 21.53 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | QPSK | 8 | 4 | 21.65 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | QPSK | 8 | 7 | 21.71 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | QPSK | 15 | 0 | 21.64 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | 16-QAM | 1 | 0 | 21.97 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | 16-QAM | 1 | 7 | 21.78 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | 16-QAM | 1 | 14 | 22.12 | 0-1 | 1 |
| | 1711.5 | 19965 | 3 | 16-QAM | 8 | 0 | 20.72 | 0-2 | 2 |
| | 1711.5 | 19965 | 3 | 16-QAM | 8 | 4 | 20.68 | 0-2 | 2 |
| | 1711.5 | 19965 | 3 | 16-QAM | 8 | 7 | 20.61 | 0-2 | 2 |
| | 1711.5 | 19965 | 3 | 16-QAM | 15 | 0 | 20.59 | 0-2 | 2 |
| Mid | 1732.5 | 20175 | 3 | QPSK | 1 | 0 | 23.48 | 0 | 0 |
| | 1732.5 | 20175 | 3 | QPSK | 1 | 7 | 23.34 | 0 | 0 |
| | 1732.5 | 20175 | 3 | QPSK | 1 | 14 | 23.20 | 0 | 0 |
| | 1732.5 | 20175 | 3 | QPSK | 8 | 0 | 22.29 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | QPSK | 8 | 4 | 22.25 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | QPSK | 8 | 7 | 22.12 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | QPSK | 15 | 0 | 22.13 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | 16-QAM | 1 | 0 | 22.41 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | 16-QAM | 1 | 7 | 22.15 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | 16-QAM | 1 | 14 | 22.49 | 0-1 | 1 |
| | 1732.5 | 20175 | 3 | 16-QAM | 8 | 0 | 21.24 | 0-2 | 2 |
| | 1732.5 | 20175 | 3 | 16-QAM | 8 | 4 | 21.05 | 0-2 | 2 |
| | 1732.5 | 20175 | 3 | 16-QAM | 8 | 7 | 21.30 | 0-2 | 2 |
| | 1732.5 | 20175 | 3 | 16-QAM | 15 | 0 | 21.33 | 0-2 | 2 |
| High | 1753.5 | 20385 | 3 | QPSK | 1 | 0 | 23.47 | 0 | 0 |
| | 1753.5 | 20385 | 3 | QPSK | 1 | 7 | 23.42 | 0 | 0 |
| | 1753.5 | 20385 | 3 | QPSK | 1 | 14 | 22.97 | 0 | 0 |
| | 1753.5 | 20385 | 3 | QPSK | 8 | 0 | 21.86 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | QPSK | 8 | 4 | 21.87 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | QPSK | 8 | 7 | 21.80 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | QPSK | 15 | 0 | 21.79 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | 16-QAM | 1 | 0 | 22.24 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | 16-QAM | 1 | 7 | 22.43 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | 16-QAM | 1 | 14 | 22.14 | 0-1 | 1 |
| | 1753.5 | 20385 | 3 | 16-QAM | 8 | 0 | 20.78 | 0-2 | 2 |
| | 1753.5 | 20385 | 3 | 16-QAM | 8 | 4 | 20.73 | 0-2 | 2 |
| | 1753.5 | 20385 | 3 | 16-QAM | 8 | 7 | 20.73 | 0-2 | 2 |
| | 1753.5 | 20385 | 3 | 16-QAM | 15 | 0 | 20.95 | 0-2 | 2 |

## Table 9-8
## LTE Band 4 (AWS) Conducted Powers -1.4 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1710.7 | 19957 | 1.4 | QPSK | 1 | 0 | 22.63 | 0 | 0 |
| | 1710.7 | 19957 | 1.4 | QPSK | 1 | 2 | 22.93 | 0 | 0 |
| | 1710.7 | 19957 | 1.4 | QPSK | 1 | 5 | 22.94 | 0 | 0 |
| | 1710.7 | 19957 | 1.4 | QPSK | 3 | 0 | 22.55 | 0 | 0 |
| | 1710.7 | 19957 | 1.4 | QPSK | 3 | 2 | 22.63 | 0 | 0 |
| | 1710.7 | 19957 | 1.4 | QPSK | 3 | 3 | 22.61 | 0 | 0 |
| | 1710.7 | 19957 | 1.4 | QPSK | 6 | 0 | 21.58 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 1 | 0 | 21.86 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 1 | 2 | 21.95 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 1 | 5 | 22.17 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 3 | 0 | 21.59 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 3 | 2 | 21.61 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 3 | 3 | 21.64 | 0-1 | 1 |
| | 1710.7 | 19957 | 1.4 | 16-QAM | 6 | 0 | 20.62 | 0-2 | 2 |
| Mid | 1732.5 | 20175 | 1.4 | QPSK | 1 | 0 | 23.39 | 0 | 0 |
| | 1732.5 | 20175 | 1.4 | QPSK | 1 | 2 | 23.35 | 0 | 0 |
| | 1732.5 | 20175 | 1.4 | QPSK | 1 | 5 | 23.45 | 0 | 0 |
| | 1732.5 | 20175 | 1.4 | QPSK | 3 | 0 | 23.07 | 0 | 0 |
| | 1732.5 | 20175 | 1.4 | QPSK | 3 | 2 | 23.07 | 0 | 0 |
| | 1732.5 | 20175 | 1.4 | QPSK | 3 | 3 | 22.99 | 0 | 0 |
| | 1732.5 | 20175 | 1.4 | QPSK | 6 | 0 | 22.32 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 1 | 0 | 21.62 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 1 | 2 | 22.37 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 1 | 5 | 22.28 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 3 | 0 | 21.99 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 3 | 2 | 22.29 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 3 | 3 | 22.23 | 0-1 | 1 |
| | 1732.5 | 20175 | 1.4 | 16-QAM | 6 | 0 | 20.87 | 0-2 | 2 |
| High | 1754.3 | 20393 | 1.4 | QPSK | 1 | 0 | 23.26 | 0 | 0 |
| | 1754.3 | 20393 | 1.4 | QPSK | 1 | 2 | 23.46 | 0 | 0 |
| | 1754.3 | 20393 | 1.4 | QPSK | 1 | 5 | 23.22 | 0 | 0 |
| | 1754.3 | 20393 | 1.4 | QPSK | 3 | 0 | 23.22 | 0 | 0 |
| | 1754.3 | 20393 | 1.4 | QPSK | 3 | 2 | 23.10 | 0 | 0 |
| | 1754.3 | 20393 | 1.4 | QPSK | 3 | 3 | 23.08 | 0 | 0 |
| | 1754.3 | 20393 | 1.4 | QPSK | 6 | 0 | 22.22 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 1 | 0 | 22.38 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 1 | 2 | 22.42 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 1 | 5 | 22.35 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 3 | 0 | 22.07 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 3 | 2 | 22.22 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 3 | 3 | 22.21 | 0-1 | 1 |
| | 1754.3 | 20393 | 1.4 | 16-QAM | 6 | 0 | 21.42 | 0-2 | 2 |


© 2014 PCTEST Engineering Laboratory, Inc.

## 9.2.3 LTE Band 2 (PCS)

**Table 9-9**
**LTE Band 2 (PCS) Conducted Powers - 20 MHz Bandwidth**

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1860 | 18700 | 20 | QPSK | 1 | 0 | **22.45** | 0 | 0 |
| | 1860 | 18700 | 20 | QPSK | 1 | 50 | 21.98 | 0 | 0 |
| | 1860 | 18700 | 20 | QPSK | 1 | 99 | 22.06 | 0 | 0 |
| | 1860 | 18700 | 20 | QPSK | 50 | 0 | 20.81 | 0-1 | 1 |
| | 1860 | 18700 | 20 | QPSK | 50 | 25 | 20.70 | 0-1 | 1 |
| | 1860 | 18700 | 20 | QPSK | 50 | 50 | 20.50 | 0-1 | 1 |
| | 1860 | 18700 | 20 | QPSK | 100 | 0 | 20.50 | 0-1 | 1 |
| | 1860 | 18700 | 20 | 16QAM | 1 | 0 | 21.36 | 0-1 | 1 |
| | 1860 | 18700 | 20 | 16QAM | 1 | 50 | 20.99 | 0-1 | 1 |
| | 1860 | 18700 | 20 | 16QAM | 1 | 99 | 20.83 | 0-1 | 1 |
| | 1860 | 18700 | 20 | 16QAM | 50 | 0 | 19.84 | 0-2 | 2 |
| | 1860 | 18700 | 20 | 16QAM | 50 | 25 | 19.50 | 0-2 | 2 |
| | 1860 | 18700 | 20 | 16QAM | 50 | 50 | 19.53 | 0-2 | 2 |
| | 1860 | 18700 | 20 | 16QAM | 100 | 0 | 19.59 | 0-2 | 2 |
| Mid | 1880.0 | 18900 | 20 | QPSK | 1 | 0 | 22.25 | 0 | 0 |
| | 1880.0 | 18900 | 20 | QPSK | 1 | 50 | 22.13 | 0 | 0 |
| | 1880.0 | 18900 | 20 | QPSK | 1 | 99 | 21.79 | 0 | 0 |
| | 1880.0 | 18900 | 20 | QPSK | 50 | 0 | **21.27** | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | QPSK | 50 | 25 | 21.02 | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | QPSK | 50 | 50 | 20.50 | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | QPSK | 100 | 0 | 20.86 | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | 16QAM | 1 | 0 | 20.71 | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | 16QAM | 1 | 50 | 20.81 | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | 16QAM | 1 | 99 | 20.82 | 0-1 | 1 |
| | 1880.0 | 18900 | 20 | 16QAM | 50 | 0 | 20.07 | 0-2 | 2 |
| | 1880.0 | 18900 | 20 | 16QAM | 50 | 25 | 19.81 | 0-2 | 2 |
| | 1880.0 | 18900 | 20 | 16QAM | 50 | 50 | 19.54 | 0-2 | 2 |
| | 1880.0 | 18900 | 20 | 16QAM | 100 | 0 | 19.73 | 0-2 | 2 |
| High | 1900 | 19100 | 20 | QPSK | 1 | 0 | 21.50 | 0 | 0 |
| | 1900 | 19100 | 20 | QPSK | 1 | 50 | 22.14 | 0 | 0 |
| | 1900 | 19100 | 20 | QPSK | 1 | 99 | 21.52 | 0 | 0 |
| | 1900 | 19100 | 20 | QPSK | 50 | 0 | 20.52 | 0-1 | 1 |
| | 1900 | 19100 | 20 | QPSK | 50 | 25 | 20.90 | 0-1 | 1 |
| | 1900 | 19100 | 20 | QPSK | 50 | 50 | 20.78 | 0-1 | 1 |
| | 1900 | 19100 | 20 | QPSK | 100 | 0 | 20.59 | 0-1 | 1 |
| | 1900 | 19100 | 20 | 16QAM | 1 | 0 | 20.64 | 0-1 | 1 |
| | 1900 | 19100 | 20 | 16QAM | 1 | 50 | 21.50 | 0-1 | 1 |
| | 1900 | 19100 | 20 | 16QAM | 1 | 99 | 20.88 | 0-1 | 1 |
| | 1900 | 19100 | 20 | 16QAM | 50 | 0 | 19.56 | 0-2 | 2 |
| | 1900 | 19100 | 20 | 16QAM | 50 | 25 | 19.81 | 0-2 | 2 |
| | 1900 | 19100 | 20 | 16QAM | 50 | 50 | 19.67 | 0-2 | 2 |
| | 1900 | 19100 | 20 | 16QAM | 100 | 0 | 19.57 | 0-2 | 2 |

**Table 9-10**
**LTE Band 2 (PCS) Conducted Powers - 15 MHz Bandwidth**

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1857.5 | 18675 | 15 | QPSK | 1 | 0 | 22.41 | 0 | 0 |
| | 1857.5 | 18675 | 15 | QPSK | 1 | 36 | 21.94 | 0 | 0 |
| | 1857.5 | 18675 | 15 | QPSK | 1 | 74 | 22.40 | 0 | 0 |
| | 1857.5 | 18675 | 15 | QPSK | 36 | 0 | 20.64 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | QPSK | 36 | 18 | 20.63 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | QPSK | 36 | 37 | 20.60 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | QPSK | 75 | 0 | 20.53 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | 16QAM | 1 | 0 | 21.49 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | 16QAM | 1 | 36 | 21.05 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | 16QAM | 1 | 74 | 21.04 | 0-1 | 1 |
| | 1857.5 | 18675 | 15 | 16QAM | 36 | 0 | 19.55 | 0-2 | 2 |
| | 1857.5 | 18675 | 15 | 16QAM | 36 | 18 | 19.54 | 0-2 | 2 |
| | 1857.5 | 18675 | 15 | 16QAM | 36 | 37 | 19.55 | 0-2 | 2 |
| | 1857.5 | 18675 | 15 | 16QAM | 75 | 0 | 19.51 | 0-2 | 2 |
| Mid | 1880.0 | 18900 | 15 | QPSK | 1 | 0 | 22.23 | 0 | 0 |
| | 1880.0 | 18900 | 15 | QPSK | 1 | 36 | 21.86 | 0 | 0 |
| | 1880.0 | 18900 | 15 | QPSK | 1 | 74 | 21.55 | 0 | 0 |
| | 1880.0 | 18900 | 15 | QPSK | 36 | 0 | 21.14 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | QPSK | 36 | 18 | 20.74 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | QPSK | 36 | 37 | 20.55 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | QPSK | 75 | 0 | 20.58 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | 16QAM | 1 | 0 | 21.50 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | 16QAM | 1 | 36 | 21.45 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | 16QAM | 1 | 74 | 20.83 | 0-1 | 1 |
| | 1880.0 | 18900 | 15 | 16QAM | 36 | 0 | 19.96 | 0-2 | 2 |
| | 1880.0 | 18900 | 15 | 16QAM | 36 | 18 | 19.68 | 0-2 | 2 |
| | 1880.0 | 18900 | 15 | 16QAM | 36 | 37 | 19.51 | 0-2 | 2 |
| | 1880.0 | 18900 | 15 | 16QAM | 75 | 0 | 19.67 | 0-2 | 2 |
| High | 1902.5 | 19125 | 15 | QPSK | 1 | 0 | 21.55 | 0 | 0 |
| | 1902.5 | 19125 | 15 | QPSK | 1 | 36 | 21.56 | 0 | 0 |
| | 1902.5 | 19125 | 15 | QPSK | 1 | 74 | 21.50 | 0 | 0 |
| | 1902.5 | 19125 | 15 | QPSK | 36 | 0 | 20.66 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | QPSK | 36 | 18 | 20.76 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | QPSK | 36 | 37 | 20.52 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | QPSK | 75 | 0 | 20.51 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | 16QAM | 1 | 0 | 20.53 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | 16QAM | 1 | 36 | 20.93 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | 16QAM | 1 | 74 | 20.50 | 0-1 | 1 |
| | 1902.5 | 19125 | 15 | 16QAM | 36 | 0 | 19.83 | 0-2 | 2 |
| | 1902.5 | 19125 | 15 | 16QAM | 36 | 18 | 19.70 | 0-2 | 2 |
| | 1902.5 | 19125 | 15 | 16QAM | 36 | 37 | 19.52 | 0-2 | 2 |
| | 1902.5 | 19125 | 15 | 16QAM | 75 | 0 | 19.57 | 0-2 | 2 |


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 9-11
## LTE Band 2 (PCS) Conducted Powers - 10 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1855 | 18650 | 10 | QPSK | 1 | 0 | 22.46 | 0 | 0 |
| | 1855 | 18650 | 10 | QPSK | 1 | 25 | 22.00 | 0 | 0 |
| | 1855 | 18650 | 10 | QPSK | 1 | 49 | 22.09 | 0 | 0 |
| | 1855 | 18650 | 10 | QPSK | 25 | 0 | 20.81 | 0-1 | 1 |
| | 1855 | 18650 | 10 | QPSK | 25 | 12 | 20.55 | 0-1 | 1 |
| | 1855 | 18650 | 10 | QPSK | 25 | 25 | 20.51 | 0-1 | 1 |
| | 1855 | 18650 | 10 | QPSK | 50 | 0 | 20.53 | 0-1 | 1 |
| | 1855 | 18650 | 10 | 16QAM | 1 | 0 | 21.45 | 0-1 | 1 |
| | 1855 | 18650 | 10 | 16QAM | 1 | 25 | 20.78 | 0-1 | 1 |
| | 1855 | 18650 | 10 | 16QAM | 1 | 49 | 20.56 | 0-1 | 1 |
| | 1855 | 18650 | 10 | 16QAM | 25 | 0 | 20.03 | 0-2 | 2 |
| | 1855 | 18650 | 10 | 16QAM | 25 | 12 | 19.63 | 0-2 | 2 |
| | 1855 | 18650 | 10 | 16QAM | 25 | 25 | 19.56 | 0-2 | 2 |
| | 1855 | 18650 | 10 | 16QAM | 50 | 0 | 19.50 | 0-2 | 2 |
| Mid | 1880.0 | 18900 | 10 | QPSK | 1 | 0 | 22.10 | 0 | 0 |
| | 1880.0 | 18900 | 10 | QPSK | 1 | 25 | 21.72 | 0 | 0 |
| | 1880.0 | 18900 | 10 | QPSK | 1 | 49 | 21.55 | 0 | 0 |
| | 1880.0 | 18900 | 10 | QPSK | 25 | 0 | 20.93 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | QPSK | 25 | 12 | 20.68 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | QPSK | 25 | 25 | 20.56 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | QPSK | 50 | 0 | 20.66 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | 16QAM | 1 | 0 | 21.16 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | 16QAM | 1 | 25 | 20.89 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | 16QAM | 1 | 49 | 21.19 | 0-1 | 1 |
| | 1880.0 | 18900 | 10 | 16QAM | 25 | 0 | 20.08 | 0-2 | 2 |
| | 1880.0 | 18900 | 10 | 16QAM | 25 | 12 | 19.82 | 0-2 | 2 |
| | 1880.0 | 18900 | 10 | 16QAM | 25 | 25 | 19.67 | 0-2 | 2 |
| | 1880.0 | 18900 | 10 | 16QAM | 50 | 0 | 19.63 | 0-2 | 2 |
| High | 1905 | 19150 | 10 | QPSK | 1 | 0 | 21.87 | 0 | 0 |
| | 1905 | 19150 | 10 | QPSK | 1 | 25 | 21.75 | 0 | 0 |
| | 1905 | 19150 | 10 | QPSK | 1 | 49 | 21.50 | 0 | 0 |
| | 1905 | 19150 | 10 | QPSK | 25 | 0 | 20.74 | 0-1 | 1 |
| | 1905 | 19150 | 10 | QPSK | 25 | 12 | 20.57 | 0-1 | 1 |
| | 1905 | 19150 | 10 | QPSK | 25 | 25 | 20.53 | 0-1 | 1 |
| | 1905 | 19150 | 10 | QPSK | 50 | 0 | 20.54 | 0-1 | 1 |
| | 1905 | 19150 | 10 | 16QAM | 1 | 0 | 21.05 | 0-1 | 1 |
| | 1905 | 19150 | 10 | 16QAM | 1 | 25 | 20.85 | 0-1 | 1 |
| | 1905 | 19150 | 10 | 16QAM | 1 | 49 | 20.53 | 0-1 | 1 |
| | 1905 | 19150 | 10 | 16QAM | 25 | 0 | 19.85 | 0-2 | 2 |
| | 1905 | 19150 | 10 | 16QAM | 25 | 12 | 19.56 | 0-2 | 2 |
| | 1905 | 19150 | 10 | 16QAM | 25 | 25 | 19.57 | 0-2 | 2 |
| | 1905 | 19150 | 10 | 16QAM | 50 | 0 | 19.73 | 0-2 | 2 |

## Table 9-12
## LTE Band 2 (PCS) Conducted Powers - 5 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1852.5 | 18625 | 5 | QPSK | 1 | 0 | 22.23 | 0 | 0 |
| | 1852.5 | 18625 | 5 | QPSK | 1 | 12 | 21.97 | 0 | 0 |
| | 1852.5 | 18625 | 5 | QPSK | 1 | 24 | 22.14 | 0 | 0 |
| | 1852.5 | 18625 | 5 | QPSK | 12 | 0 | 20.82 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | QPSK | 12 | 6 | 20.82 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | QPSK | 12 | 13 | 20.55 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | QPSK | 25 | 0 | 20.74 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | 16-QAM | 1 | 0 | 21.40 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | 16-QAM | 1 | 12 | 20.81 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | 16-QAM | 1 | 24 | 20.57 | 0-1 | 1 |
| | 1852.5 | 18625 | 5 | 16-QAM | 12 | 0 | 19.85 | 0-2 | 2 |
| | 1852.5 | 18625 | 5 | 16-QAM | 12 | 6 | 19.61 | 0-2 | 2 |
| | 1852.5 | 18625 | 5 | 16-QAM | 12 | 13 | 19.54 | 0-2 | 2 |
| | 1852.5 | 18625 | 5 | 16-QAM | 25 | 0 | 19.76 | 0-2 | 2 |
| Mid | 1880.0 | 18900 | 5 | QPSK | 1 | 0 | 21.60 | 0 | 0 |
| | 1880.0 | 18900 | 5 | QPSK | 1 | 12 | 21.62 | 0 | 0 |
| | 1880.0 | 18900 | 5 | QPSK | 1 | 24 | 21.56 | 0 | 0 |
| | 1880.0 | 18900 | 5 | QPSK | 12 | 0 | 20.76 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | QPSK | 12 | 6 | 20.66 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | QPSK | 12 | 13 | 20.53 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | QPSK | 25 | 0 | 20.69 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | 16-QAM | 1 | 0 | 20.82 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | 16-QAM | 1 | 12 | 20.70 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | 16-QAM | 1 | 24 | 21.07 | 0-1 | 1 |
| | 1880.0 | 18900 | 5 | 16-QAM | 12 | 0 | 19.54 | 0-2 | 2 |
| | 1880.0 | 18900 | 5 | 16-QAM | 12 | 6 | 19.81 | 0-2 | 2 |
| | 1880.0 | 18900 | 5 | 16-QAM | 12 | 13 | 19.52 | 0-2 | 2 |
| | 1880.0 | 18900 | 5 | 16-QAM | 25 | 0 | 19.56 | 0-2 | 2 |
| High | 1907.5 | 19175 | 5 | QPSK | 1 | 0 | 21.95 | 0 | 0 |
| | 1907.5 | 19175 | 5 | QPSK | 1 | 12 | 22.00 | 0 | 0 |
| | 1907.5 | 19175 | 5 | QPSK | 1 | 24 | 21.50 | 0 | 0 |
| | 1907.5 | 19175 | 5 | QPSK | 12 | 0 | 20.80 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | QPSK | 12 | 6 | 20.60 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | QPSK | 12 | 13 | 20.50 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | QPSK | 25 | 0 | 20.65 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | 16-QAM | 1 | 0 | 20.70 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | 16-QAM | 1 | 12 | 21.06 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | 16-QAM | 1 | 24 | 20.95 | 0-1 | 1 |
| | 1907.5 | 19175 | 5 | 16-QAM | 12 | 0 | 19.72 | 0-2 | 2 |
| | 1907.5 | 19175 | 5 | 16-QAM | 12 | 6 | 19.56 | 0-2 | 2 |
| | 1907.5 | 19175 | 5 | 16-QAM | 12 | 13 | 19.50 | 0-2 | 2 |
| | 1907.5 | 19175 | 5 | 16-QAM | 25 | 0 | 19.83 | 0-2 | 2 |


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 9-13
## LTE Band 2 (PCS) Conducted Powers - 3 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1851.5 | 18615 | 3 | QPSK | 1 | 0 | 22.42 | 0 | 0 |
| | 1851.5 | 18615 | 3 | QPSK | 1 | 7 | 22.44 | 0 | 0 |
| | 1851.5 | 18615 | 3 | QPSK | 1 | 14 | 22.06 | 0 | 0 |
| | 1851.5 | 18615 | 3 | QPSK | 8 | 0 | 20.87 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | QPSK | 8 | 4 | 20.85 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | QPSK | 8 | 7 | 20.83 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | QPSK | 15 | 0 | 20.81 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | 16-QAM | 1 | 0 | 20.53 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | 16-QAM | 1 | 7 | 20.90 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | 16-QAM | 1 | 14 | 20.83 | 0-1 | 1 |
| | 1851.5 | 18615 | 3 | 16-QAM | 8 | 0 | 19.85 | 0-2 | 2 |
| | 1851.5 | 18615 | 3 | 16-QAM | 8 | 4 | 19.85 | 0-2 | 2 |
| | 1851.5 | 18615 | 3 | 16-QAM | 8 | 7 | 19.88 | 0-2 | 2 |
| | 1851.5 | 18615 | 3 | 16-QAM | 15 | 0 | 19.89 | 0-2 | 2 |
| Mid | 1880.0 | 18900 | 3 | QPSK | 1 | 0 | 21.96 | 0 | 0 |
| | 1880.0 | 18900 | 3 | QPSK | 1 | 7 | 21.80 | 0 | 0 |
| | 1880.0 | 18900 | 3 | QPSK | 1 | 14 | 21.51 | 0 | 0 |
| | 1880.0 | 18900 | 3 | QPSK | 8 | 0 | 20.70 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | QPSK | 8 | 4 | 20.57 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | QPSK | 8 | 7 | 20.61 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | QPSK | 15 | 0 | 20.61 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | 16-QAM | 1 | 0 | 20.51 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | 16-QAM | 1 | 7 | 20.99 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | 16-QAM | 1 | 14 | 20.71 | 0-1 | 1 |
| | 1880.0 | 18900 | 3 | 16-QAM | 8 | 0 | 19.95 | 0-2 | 2 |
| | 1880.0 | 18900 | 3 | 16-QAM | 8 | 4 | 19.89 | 0-2 | 2 |
| | 1880.0 | 18900 | 3 | 16-QAM | 8 | 7 | 19.56 | 0-2 | 2 |
| | 1880.0 | 18900 | 3 | 16-QAM | 15 | 0 | 19.55 | 0-2 | 2 |
| High | 1908.5 | 19185 | 3 | QPSK | 1 | 0 | 21.55 | 0 | 0 |
| | 1908.5 | 19185 | 3 | QPSK | 1 | 7 | 21.50 | 0 | 0 |
| | 1908.5 | 19185 | 3 | QPSK | 1 | 14 | 21.62 | 0 | 0 |
| | 1908.5 | 19185 | 3 | QPSK | 8 | 0 | 20.52 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | QPSK | 8 | 4 | 20.56 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | QPSK | 8 | 7 | 20.54 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | QPSK | 15 | 0 | 20.58 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | 16-QAM | 1 | 0 | 20.66 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | 16-QAM | 1 | 7 | 20.51 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | 16-QAM | 1 | 14 | 20.63 | 0-1 | 1 |
| | 1908.5 | 19185 | 3 | 16-QAM | 8 | 0 | 19.75 | 0-2 | 2 |
| | 1908.5 | 19185 | 3 | 16-QAM | 8 | 4 | 19.57 | 0-2 | 2 |
| | 1908.5 | 19185 | 3 | 16-QAM | 8 | 7 | 19.50 | 0-2 | 2 |
| | 1908.5 | 19185 | 3 | 16-QAM | 15 | 0 | 19.51 | 0-2 | 2 |

## Table 9-14
## LTE Band 2 (PCS) Conducted Powers -1.4 MHz Bandwidth

| | Frequency [MHz] | Channel | Bandwidth [MHz] | Modulation | RB Size | RB Offset | Conducted Power [dBm] | MPR Allowed per 3GPP [dB] | MPR [dB] |
|---|---|---|---|---|---|---|---|---|---|
| Low | 1850.7 | 18607 | 1.4 | QPSK | 1 | 0 | 22.48 | 0 | 0 |
| | 1850.7 | 18607 | 1.4 | QPSK | 1 | 2 | 22.00 | 0 | 0 |
| | 1850.7 | 18607 | 1.4 | QPSK | 1 | 5 | 22.50 | 0 | 0 |
| | 1850.7 | 18607 | 1.4 | QPSK | 3 | 0 | 21.78 | 0 | 0 |
| | 1850.7 | 18607 | 1.4 | QPSK | 3 | 2 | 21.94 | 0 | 0 |
| | 1850.7 | 18607 | 1.4 | QPSK | 3 | 3 | 21.91 | 0 | 0 |
| | 1850.7 | 18607 | 1.4 | QPSK | 6 | 0 | 20.91 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 1 | 0 | 21.09 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 1 | 2 | 20.51 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 1 | 5 | 20.60 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 3 | 0 | 20.67 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 3 | 2 | 20.52 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 3 | 3 | 20.54 | 0-1 | 1 |
| | 1850.7 | 18607 | 1.4 | 16-QAM | 6 | 0 | 19.69 | 0-2 | 2 |
| Mid | 1880.0 | 18900 | 1.4 | QPSK | 1 | 0 | 21.71 | 0 | 0 |
| | 1880.0 | 18900 | 1.4 | QPSK | 1 | 2 | 21.66 | 0 | 0 |
| | 1880.0 | 18900 | 1.4 | QPSK | 1 | 5 | 21.54 | 0 | 0 |
| | 1880.0 | 18900 | 1.4 | QPSK | 3 | 0 | 21.58 | 0 | 0 |
| | 1880.0 | 18900 | 1.4 | QPSK | 3 | 2 | 21.60 | 0 | 0 |
| | 1880.0 | 18900 | 1.4 | QPSK | 3 | 3 | 21.53 | 0 | 0 |
| | 1880.0 | 18900 | 1.4 | QPSK | 6 | 0 | 20.63 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 1 | 0 | 20.57 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 1 | 2 | 20.58 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 1 | 5 | 20.55 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 3 | 0 | 20.73 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 3 | 2 | 21.00 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 3 | 3 | 20.81 | 0-1 | 1 |
| | 1880.0 | 18900 | 1.4 | 16-QAM | 6 | 0 | 20.23 | 0-2 | 2 |
| High | 1909.3 | 19193 | 1.4 | QPSK | 1 | 0 | 21.61 | 0 | 0 |
| | 1909.3 | 19193 | 1.4 | QPSK | 1 | 2 | 21.85 | 0 | 0 |
| | 1909.3 | 19193 | 1.4 | QPSK | 1 | 5 | 21.93 | 0 | 0 |
| | 1909.3 | 19193 | 1.4 | QPSK | 3 | 0 | 21.53 | 0 | 0 |
| | 1909.3 | 19193 | 1.4 | QPSK | 3 | 2 | 21.57 | 0 | 0 |
| | 1909.3 | 19193 | 1.4 | QPSK | 3 | 3 | 21.50 | 0 | 0 |
| | 1909.3 | 19193 | 1.4 | QPSK | 6 | 0 | 20.50 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 1 | 0 | 20.52 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 1 | 2 | 21.33 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 1 | 5 | 20.98 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 3 | 0 | 20.73 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 3 | 2 | 20.50 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 3 | 3 | 21.06 | 0-1 | 1 |
| | 1909.3 | 19193 | 1.4 | 16-QAM | 6 | 0 | 19.60 | 0-2 | 2 |


© 2014 PCTEST Engineering Laboratory, Inc.

## 9.3 WLAN Conducted Powers

**Table 9-15**
**IEEE 802.11b Average RF Power**

| Mode | Freq [MHz] | Channel | 802.11b Conducted Power [dBm] | | | |
|---|---|---|---|---|---|---|
| | | | Data Rate [Mbps] | | | |
| | | | 1 | 2 | 5.5 | 11 |
| 802.11b | 2412 | 1* | 12.41 | 12.44 | 12.51 | 12.52 |
| 802.11b | 2437 | 6* | 13.32 | 13.35 | 13.38 | 13.44 |
| 802.11b | 2462 | 11* | **13.36** | 13.37 | 13.36 | 13.42 |

(*) – indicates default channels per KDB Publication 248227 D01v01r02.

**Table 9-16**
**IEEE 802.11g Average RF Power**

| Mode | Freq [MHz] | Channel | 802.11g Conducted Power [dBm] | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Data Rate [Mbps] | | | | | | | |
| | | | 6 | 9 | 12 | 18 | 24 | 36 | 48 | 54 |
| 802.11g | 2412 | 1 | 11.55 | 11.46 | 11.53 | 11.49 | 11.51 | 11.46 | 11.53 | 11.49 |
| 802.11g | 2437 | 6 | 12.81 | 12.80 | 12.87 | 12.87 | 12.85 | 12.85 | 12.89 | 12.88 |
| 802.11g | 2462 | 11 | 12.85 | 12.85 | 12.89 | 12.89 | 12.89 | 12.90 | 12.86 | 12.93 |

**Table 9-17**
**IEEE 802.11n Average RF Power**

| Mode | Freq [MHz] | Channel | 802.11n (2.4GHz) Conducted Power [dBm] | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | Data Rate [Mbps] | | | | | | | |
| | | | 6.5 | 13 | 19.5 | 26 | 39 | 52 | 58.5 | 65 |
| 802.11n | 2412 | 1 | 11.52 | 11.60 | 11.58 | 11.55 | 11.59 | 11.60 | 11.68 | 11.60 |
| 802.11n | 2437 | 6 | 12.79 | 12.82 | 12.82 | 12.82 | 12.75 | 12.79 | 12.79 | 12.84 |
| 802.11n | 2462 | 11 | 12.78 | 12.83 | 12.83 | 12.76 | 12.80 | 12.86 | 12.79 | 12.80 |

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012/April 2013 FCC/TCB Meeting Notes:

- For 2.4 GHz operations, highest average RF output power channel for the lowest data rate for IEEE 802.11b were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
- When the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other channels is not required. Otherwise, the other default (or corresponding required) test channels were additionally tested using the lowest data rate.
- The bolded data rate and channel above were tested for SAR.




**Figure 9-2**
**Power Measurement Setup**


© 2014 PCTEST Engineering Laboratory, Inc.

# 10 SYSTEM VERIFICATION

## 10.1 Tissue Verification

**Table 10-1**
**Measured Tissue Properties**

| Calibrated for Tests Performed on: | Tissue Type | Tissue Temp During Calibration (C°) | Measured Frequency (MHz) | Measured Conductivity, σ (S/m) | Measured Dielectric Constant, ε | TARGET Conductivity, σ (S/m) | TARGET Dielectric Constant, ε | % dev σ | % dev ε |
|---|---|---|---|---|---|---|---|---|---|
| 11/10/2014 | 750H | 21.6 | 740 | 0.881 | 40.436 | 0.893 | 41.994 | -1.34% | -3.71% |
| | | | 755 | 0.894 | 40.265 | 0.894 | 41.916 | 0.00% | -3.94% |
| | | | 770 | 0.914 | 40.132 | 0.895 | 41.838 | 2.12% | -4.08% |
| | | | 785 | 0.938 | 40.066 | 0.896 | 41.760 | 4.69% | -4.06% |
| 11/10/2014 | 835H | 21.3 | 820 | 0.914 | 41.768 | 0.899 | 41.578 | 1.67% | 0.46% |
| | | | 835 | 0.929 | 41.568 | 0.900 | 41.500 | 3.22% | 0.16% |
| | | | 850 | 0.943 | 41.375 | 0.916 | 41.500 | 2.95% | -0.30% |
| 12/8/2014 | 1750H | 21.0 | 1710 | 1.362 | 39.606 | 1.348 | 40.142 | 1.04% | -1.34% |
| | | | 1750 | 1.398 | 39.405 | 1.371 | 40.079 | 1.97% | -1.68% |
| | | | 1790 | 1.439 | 39.176 | 1.394 | 40.016 | 3.23% | -2.10% |
| 11/13/2014 | 1900H | 21.3 | 1850 | 1.397 | 38.835 | 1.400 | 40.000 | -0.21% | -2.91% |
| | | | 1880 | 1.427 | 38.686 | 1.400 | 40.000 | 1.93% | -3.29% |
| | | | 1910 | 1.460 | 38.554 | 1.400 | 40.000 | 4.29% | -3.61% |
| 11/24/2014 | 1900H | 22.5 | 1850 | 1.356 | 40.002 | 1.400 | 40.000 | -3.14% | 0.01% |
| | | | 1880 | 1.386 | 39.902 | 1.400 | 40.000 | -1.00% | -0.24% |
| | | | 1910 | 1.415 | 39.815 | 1.400 | 40.000 | 1.07% | -0.46% |
| 12/19/2014 | 2450H | 21.9 | 2401 | 1.704 | 39.184 | 1.756 | 39.287 | -2.96% | -0.26% |
| | | | 2450 | 1.756 | 38.948 | 1.800 | 39.200 | -2.44% | -0.64% |
| | | | 2499 | 1.812 | 38.819 | 1.853 | 39.138 | -2.21% | -0.82% |
| 11/12/2014 | 750B | 22.9 | 740 | 0.974 | 56.099 | 0.963 | 55.570 | 1.14% | 0.95% |
| | | | 755 | 0.988 | 56.011 | 0.964 | 55.512 | 2.49% | 0.90% |
| | | | 770 | 1.001 | 55.757 | 0.965 | 55.453 | 3.73% | 0.55% |
| | | | 785 | 1.012 | 55.456 | 0.966 | 55.395 | 4.76% | 0.11% |
| 11/5/2014 | 835B | 21.6 | 820 | 0.944 | 53.755 | 0.969 | 55.258 | -2.58% | -2.72% |
| | | | 835 | 0.960 | 53.584 | 0.970 | 55.200 | -1.03% | -2.93% |
| | | | 850 | 0.973 | 53.444 | 0.988 | 55.154 | -1.52% | -3.10% |
| 11/11/2014 | 835B | 21.7 | 820 | 0.935 | 53.196 | 0.969 | 55.258 | -3.51% | -3.73% |
| | | | 835 | 0.948 | 53.049 | 0.970 | 55.200 | -2.27% | -3.90% |
| | | | 850 | 0.964 | 52.901 | 0.988 | 55.154 | -2.43% | -4.08% |
| 12/8/2014 | 1750B | 20.9 | 1710 | 1.464 | 52.207 | 1.463 | 53.537 | 0.07% | -2.48% |
| | | | 1750 | 1.508 | 52.023 | 1.488 | 53.432 | 1.34% | -2.64% |
| | | | 1790 | 1.555 | 51.886 | 1.514 | 53.326 | 2.71% | -2.70% |
| 11/10/2014 | 1900B | 21.0 | 1850 | 1.512 | 52.968 | 1.520 | 53.300 | -0.53% | -0.62% |
| | | | 1880 | 1.547 | 52.866 | 1.520 | 53.300 | 1.78% | -0.81% |
| | | | 1910 | 1.583 | 52.818 | 1.520 | 53.300 | 4.14% | -0.90% |
| 11/24/2014 | 1900B | 22.5 | 1850 | 1.528 | 52.798 | 1.520 | 53.300 | 0.53% | -0.94% |
| | | | 1880 | 1.553 | 52.706 | 1.520 | 53.300 | 2.17% | -1.11% |
| | | | 1910 | 1.582 | 52.551 | 1.520 | 53.300 | 4.08% | -1.41% |
| 12/17/2014 | 2450B | 24.3 | 2401 | 1.856 | 50.927 | 1.903 | 52.765 | -2.47% | -3.48% |
| | | | 2450 | 1.922 | 50.754 | 1.950 | 52.700 | -1.44% | -3.69% |
| | | | 2499 | 1.984 | 50.582 | 2.019 | 52.638 | -1.73% | -3.91% |

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.


© 2014 PCTEST Engineering Laboratory, Inc.

## 10.2 Test System Verification

Prior to SAR assessment, the system is verified to ±10% of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix E.

**Table 10-2**
**System Verification Results**

| System Verification TARGET & MEASURED | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| SAR System # | Tissue Frequency (MHz) | Tissue Type | Date: | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Dipole SN | Probe SN | Measured $SAR_{1g}$ (W/kg) | 1 W Target $SAR_{1g}$ (W/kg) | 1 W Normalized $SAR_{1g}$ (W/kg) | $Deviation_{1g}$ (%) |
| J | 750 | HEAD | 11/10/2014 | 22.7 | 21.6 | 0.100 | 1003 | 3022 | 0.772 | 8.370 | 7.720 | -7.77% |
| C | 835 | HEAD | 11/10/2014 | 22.4 | 21.3 | 0.100 | 4d132 | 3333 | 0.969 | 9.270 | 9.690 | 4.53% |
| J | 1750 | HEAD | 12/08/2014 | 21.6 | 21.0 | 0.100 | 1008 | 3022 | 3.550 | 36.900 | 35.500 | -3.79% |
| C | 1900 | HEAD | 11/13/2014 | 22.9 | 21.3 | 0.100 | 5d148 | 3333 | 4.000 | 40.700 | 40.000 | -1.72% |
| H | 1900 | HEAD | 11/24/2014 | 23.2 | 22.5 | 0.100 | 5d141 | 3319 | 4.270 | 40.100 | 42.700 | 6.48% |
| G | 2450 | HEAD | 12/19/2014 | 24.4 | 21.9 | 0.100 | 797 | 3258 | 4.920 | 51.800 | 49.200 | -5.02% |
| J | 750 | BODY | 11/12/2014 | 23.3 | 22.3 | 0.100 | 1003 | 3022 | 0.917 | 8.770 | 9.170 | 4.56% |
| C | 835 | BODY | 11/05/2014 | 22.5 | 21.6 | 0.100 | 4d132 | 3213 | 0.990 | 9.580 | 9.900 | 3.34% |
| C | 835 | BODY | 11/11/2014 | 22.8 | 21.7 | 0.100 | 4d132 | 3333 | 1.030 | 9.580 | 10.300 | 7.52% |
| J | 1750 | BODY | 12/08/2014 | 21.0 | 20.9 | 0.100 | 1008 | 3022 | 3.950 | 37.600 | 39.500 | 5.05% |
| B | 1900 | BODY | 11/10/2014 | 22.1 | 21.0 | 0.100 | 5d148 | 3318 | 4.030 | 39.300 | 40.300 | 2.54% |
| H | 1900 | BODY | 11/24/2014 | 20.6 | 22.0 | 0.100 | 5d141 | 3319 | 3.760 | 40.600 | 37.600 | -7.39% |
| E | 2450 | BODY | 12/17/2014 | 24.5 | 24.3 | 0.100 | 797 | 3332 | 4.940 | 49.400 | 49.400 | 0.00% |




**Figure 10-1**
**System Verification Setup Diagram**

**Figure 10-2**
**System Verification Setup Photo**


© 2014 PCTEST Engineering Laboratory, Inc.

# 11 SAR DATA SUMMARY

## 11.1 Standalone Head SAR Data

**Table 11-1**
**Cell. CDMA Head SAR**

| MEASUREMENT RESULTS | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | (W/kg) | | (W/kg) | |
| 836.52 | 384 | Cell. CDMA | RC3 / SO55 | 25.0 | 24.28 | 0.00 | Right | Cheek | 0511-4 | 1:1 | 0.481 | 1.180 | 0.568 | |
| 836.52 | 384 | Cell. CDMA | RC3 / SO55 | 25.0 | 24.28 | 0.01 | Right | Tilt | 0511-4 | 1:1 | 0.380 | 1.180 | 0.448 | |
| 836.52 | 384 | Cell. CDMA | RC3 / SO55 | 25.0 | 24.28 | -0.01 | Left | Cheek | 0511-4 | 1:1 | 0.550 | 1.180 | 0.649 | |
| 836.52 | 384 | Cell. CDMA | RC3 / SO55 | 25.0 | 24.28 | 0.01 | Left | Tilt | 0511-4 | 1:1 | 0.410 | 1.180 | 0.484 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. A | 25.0 | 24.39 | -0.04 | Right | Cheek | 0511-4 | 1:1 | 0.527 | 1.151 | 0.607 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. A | 25.0 | 24.39 | 0.09 | Right | Tilt | 0511-4 | 1:1 | 0.394 | 1.151 | 0.453 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. A | 25.0 | 24.39 | 0.01 | Left | Cheek | 0511-4 | 1:1 | 0.623 | 1.151 | 0.717 | A1 |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. A | 25.0 | 24.39 | -0.05 | Left | Tilt | 0511-4 | 1:1 | 0.406 | 1.151 | 0.467 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | |

**Table 11-2**
**PCS CDMA Head SAR**

| MEASUREMENT RESULTS | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode/Band | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side | Test Position | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | (W/kg) | | (W/kg) | |
| 1880.00 | 600 | PCS CDMA | RC3 / SO55 | 25.0 | 24.38 | 0.05 | Right | Cheek | 0511-4 | 1:1 | 0.414 | 1.153 | 0.477 | |
| 1880.00 | 600 | PCS CDMA | RC3 / SO55 | 25.0 | 24.38 | -0.03 | Right | Tilt | 0511-4 | 1:1 | 0.309 | 1.153 | 0.356 | |
| 1851.25 | 25 | PCS CDMA | RC3 / SO55 | 25.0 | 24.18 | -0.03 | Left | Cheek | 0511-4 | 1:1 | 0.616 | 1.208 | 0.744 | |
| 1880.00 | 600 | PCS CDMA | RC3 / SO55 | 25.0 | 24.38 | -0.01 | Left | Cheek | 0511-4 | 1:1 | 0.757 | 1.153 | 0.873 | |
| 1908.75 | 1175 | PCS CDMA | RC3 / SO55 | 25.0 | 24.57 | 0.02 | Left | Cheek | 0511-4 | 1:1 | 0.711 | 1.104 | 0.785 | |
| 1880.00 | 600 | PCS CDMA | RC3 / SO55 | 25.0 | 24.38 | -0.01 | Left | Tilt | 0511-4 | 1:1 | 0.308 | 1.153 | 0.355 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. A | 25.0 | 24.38 | -0.05 | Right | Cheek | 0511-4 | 1:1 | 0.610 | 1.153 | 0.703 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. A | 25.0 | 24.38 | 0.03 | Right | Tilt | 0511-4 | 1:1 | 0.417 | 1.153 | 0.481 | |
| 1851.25 | 25 | PCS CDMA | EVDO Rev. A | 25.0 | 24.09 | 0.16 | Left | Cheek | 0511-4 | 1:1 | 0.763 | 1.233 | 0.941 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. A | 25.0 | 24.38 | 0.10 | Left | Cheek | 0511-4 | 1:1 | 0.942 | 1.153 | 1.086 | A2 |
| 1908.75 | 1175 | PCS CDMA | EVDO Rev. A | 25.0 | 24.57 | 0.12 | Left | Cheek | 0511-4 | 1:1 | 0.868 | 1.104 | 0.958 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. A | 25.0 | 24.38 | 0.19 | Left | Tilt | 0511-4 | 1:1 | 0.360 | 1.153 | 0.415 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | |


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 11-3
## LTE Band 13 Head SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.07 | 0 | Right | Cheek | QPSK | 1 | 0 | 0511-4 | 1:1 | 0.424 | 1.021 | 0.433 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.05 | 1 | Right | Cheek | QPSK | 25 | 0 | 0511-4 | 1:1 | 0.283 | 1.125 | 0.318 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.05 | 0 | Right | Tilt | QPSK | 1 | 0 | 0511-4 | 1:1 | 0.285 | 1.021 | 0.291 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.07 | 1 | Right | Tilt | QPSK | 25 | 0 | 0511-4 | 1:1 | 0.187 | 1.125 | 0.210 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.04 | 0 | Left | Cheek | QPSK | 1 | 0 | 0511-4 | 1:1 | 0.509 | 1.021 | 0.520 | A3 |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.17 | 1 | Left | Cheek | QPSK | 25 | 0 | 0511-4 | 1:1 | 0.338 | 1.125 | 0.380 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.15 | 0 | Left | Tilt | QPSK | 1 | 0 | 0511-4 | 1:1 | 0.275 | 1.021 | 0.281 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.06 | 1 | Left | Tilt | QPSK | 25 | 0 | 0511-4 | 1:1 | 0.178 | 1.125 | 0.200 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | | |

## Table 11-4
## LTE Band 4 (AWS) Head SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | 0.11 | 0 | Right | Cheek | QPSK | 1 | 50 | 2811-7 | 1:1 | 0.434 | 1.007 | 0.437 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | -0.05 | 1 | Right | Cheek | QPSK | 50 | 25 | 2811-7 | 1:1 | 0.330 | 1.099 | 0.363 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | 0.05 | 0 | Right | Tilt | QPSK | 1 | 50 | 2811-7 | 1:1 | 0.418 | 1.007 | 0.421 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | 0.01 | 1 | Right | Tilt | QPSK | 50 | 25 | 2811-7 | 1:1 | 0.308 | 1.099 | 0.338 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | -0.16 | 0 | Left | Cheek | QPSK | 1 | 50 | 2811-7 | 1:1 | 1.020 | 1.007 | 1.027 | A4 |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | 0.07 | 1 | Left | Cheek | QPSK | 50 | 25 | 2811-7 | 1:1 | 0.713 | 1.099 | 0.784 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 21.89 | 0.09 | 1 | Left | Cheek | QPSK | 100 | 0 | 2811-7 | 1:1 | 0.662 | 1.151 | 0.762 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | 0.13 | 0 | Left | Tilt | QPSK | 1 | 50 | 2811-7 | 1:1 | 0.417 | 1.007 | 0.420 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | -0.09 | 1 | Left | Tilt | QPSK | 50 | 25 | 2811-7 | 1:1 | 0.312 | 1.099 | 0.343 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | 0.15 | 0 | Left | Cheek | QPSK | 1 | 50 | 2811-7 | 1:1 | 1.020 | 1.007 | 1.027 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | | |

Note: Variability data is highlighted blue in the table above.

## Table 11-5
## LTE Band 2 (PCS) Head SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Side | Test Position | Modulation | RB Size | RB Offset | Device Serial Number | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.00 | 0 | Right | Cheek | QPSK | 1 | 0 | 2811-3 | 1:1 | 0.528 | 1.059 | 0.559 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | 0.05 | 1 | Right | Cheek | QPSK | 50 | 0 | 2811-3 | 1:1 | 0.363 | 1.104 | 0.401 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.09 | 0 | Right | Tilt | QPSK | 1 | 0 | 2811-3 | 1:1 | 0.311 | 1.059 | 0.329 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | -0.02 | 1 | Right | Tilt | QPSK | 50 | 0 | 2811-3 | 1:1 | 0.241 | 1.104 | 0.266 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.08 | 0 | Left | Cheek | QPSK | 1 | 0 | 2811-3 | 1:1 | 0.996 | 1.059 | 1.055 | A5 |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 22.7 | 22.25 | 0.15 | 0 | Left | Cheek | QPSK | 1 | 0 | 2811-3 | 1:1 | 0.860 | 1.109 | 0.954 | |
| 1900.00 | 19100 | High | LTE Band 2 (PCS) | 20 | 22.7 | 22.14 | -0.02 | 0 | Left | Cheek | QPSK | 1 | 50 | 2811-3 | 1:1 | 0.862 | 1.138 | 0.981 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | 0.02 | 1 | Left | Cheek | QPSK | 50 | 0 | 2811-3 | 1:1 | 0.673 | 1.104 | 0.743 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 20.86 | 0.04 | 1 | Left | Cheek | QPSK | 100 | 0 | 2811-3 | 1:1 | 0.689 | 1.213 | 0.836 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.06 | 0 | Left | Tilt | QPSK | 1 | 0 | 2811-3 | 1:1 | 0.259 | 1.059 | 0.274 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | 0.05 | 1 | Left | Tilt | QPSK | 50 | 0 | 2811-3 | 1:1 | 0.213 | 1.104 | 0.235 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.15 | 0 | Left | Cheek | QPSK | 1 | 0 | 2811-3 | 1:1 | 0.979 | 1.059 | 1.037 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | | |

Note: Variability data is highlighted blue in the table above.


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 11-6
## DTS Head SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Side | Test Position | Device Serial Number | Data Rate (Mbps) | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | 0.12 | Right | Cheek | 2811-7 | 1 | 1:1 | 0.190 | 1.033 | 0.196 | A6 |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | 0.17 | Right | Tilt | 2811-7 | 1 | 1:1 | 0.048 | 1.033 | 0.050 | |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | 0.14 | Left | Cheek | 2811-7 | 1 | 1:1 | 0.081 | 1.033 | 0.084 | |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | 0.05 | Left | Tilt | 2811-7 | 1 | 1:1 | 0.043 | 1.033 | 0.044 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | |

## 11.2 Standalone Body-Worn SAR Data

## Table 11-7
## CDMA Body-Worn SAR Data

| MEASUREMENT RESULTS | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing | Device Serial Number | Duty Cycle | Side | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | (W/kg) | | (W/kg) | |
| 824.70 | 1013 | Cell. CDMA | TDSO / SO32 | 25.0 | 24.32 | 0.02 | 10 mm | 0511-4 | 1:1 | back | 0.653 | 1.169 | 0.763 | |
| 836.52 | 384 | Cell. CDMA | TDSO / SO32 | 25.0 | 24.36 | 0.03 | 10 mm | 0511-4 | 1:1 | back | 0.782 | 1.159 | 0.906 | |
| 848.31 | 777 | Cell. CDMA | TDSO / SO32 | 25.0 | 24.38 | 0.00 | 10 mm | 0511-4 | 1:1 | back | 0.784 | 1.153 | 0.904 | A7 |
| 1851.25 | 25 | PCS CDMA | TDSO / SO32 | 25.0 | 24.28 | 0.01 | 10 mm | 0511-4 | 1:1 | back | 0.582 | 1.180 | 0.687 | |
| 1880.00 | 600 | PCS CDMA | TDSO / SO32 | 25.0 | 24.42 | -0.01 | 10 mm | 0511-4 | 1:1 | back | 0.727 | 1.143 | 0.831 | A9 |
| 1908.75 | 1175 | PCS CDMA | TDSO / SO32 | 25.0 | 24.55 | -0.09 | 10 mm | 0511-4 | 1:1 | back | 0.720 | 1.109 | 0.798 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | |

## Table 11-8
## LTE Body-Worn SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.01 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.881 | 1.021 | 0.900 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.06 | 1 | 0511-4 | QPSK | 25 | 0 | 10 mm | back | 1:1 | 0.638 | 1.125 | 0.718 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.35 | -0.02 | 1 | 0511-4 | QPSK | 50 | 0 | 10 mm | back | 1:1 | 0.634 | 1.161 | 0.736 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.08 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.918 | 1.021 | 0.937 | A11 |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | -0.04 | 0 | 2811-7 | QPSK | 1 | 50 | 10 mm | back | 1:1 | 0.905 | 1.007 | 0.911 | A12 |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | -0.06 | 1 | 2811-7 | QPSK | 50 | 25 | 10 mm | back | 1:1 | 0.714 | 1.099 | 0.785 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 21.89 | -0.05 | 1 | 2811-7 | QPSK | 100 | 0 | 10 mm | back | 1:1 | 0.688 | 1.151 | 0.792 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.04 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.885 | 1.059 | 0.937 | A14 |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 22.7 | 22.25 | -0.06 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.759 | 1.109 | 0.842 | |
| 1900.00 | 19100 | High | LTE Band 2 (PCS) | 20 | 22.7 | 22.14 | 0.10 | 0 | 2811-3 | QPSK | 1 | 50 | 10 mm | back | 1:1 | 0.649 | 1.138 | 0.739 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | -0.07 | 1 | 2811-3 | QPSK | 50 | 0 | 10 mm | back | 1:1 | 0.563 | 1.104 | 0.622 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 20.86 | -0.12 | 1 | 2811-3 | QPSK | 100 | 0 | 10 mm | back | 1:1 | 0.555 | 1.213 | 0.673 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | | |

Note: Variability data is highlighted blue in the table above.


© 2014 PCTEST Engineering Laboratory, Inc.

**Table 11-9**
**DTS Body-Worn SAR**

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | -0.01 | 10 mm | 2811-7 | 1 | back | 1:1 | 0.106 | 1.033 | **0.109** | A16 |
| **ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population** | | | | | | | **Body<br>1.6 W/kg (mW/g)**<br>averaged over 1 gram | | | | | | | | |

## 11.3 Standalone Wireless Router SAR Data

**Table 11-10**
**CDMA Hotspot SAR Data**

| MEASUREMENT RESULTS | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing | Device Serial Number | Duty Cycle | Side | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | (W/kg) | | (W/kg) | |
| 824.70 | 1013 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.44 | -0.07 | 10 mm | 0511-4 | 1:1 | back | 0.669 | 1.138 | 0.761 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.41 | 0.01 | 10 mm | 0511-4 | 1:1 | back | 0.807 | 1.146 | 0.925 | |
| 848.31 | 777 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.38 | -0.04 | 10 mm | 0511-4 | 1:1 | back | 0.833 | 1.153 | **0.960** | A8 |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.41 | 0.02 | 10 mm | 0511-4 | 1:1 | front | 0.681 | 1.146 | 0.780 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.41 | -0.20 | 10 mm | 0511-4 | 1:1 | bottom | 0.122 | 1.146 | 0.140 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.41 | 0.06 | 10 mm | 0511-4 | 1:1 | right | 0.609 | 1.146 | 0.698 | |
| 824.70 | 1013 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.44 | 0.04 | 10 mm | 0511-4 | 1:1 | left | 0.591 | 1.138 | 0.673 | |
| 836.52 | 384 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.41 | 0.02 | 10 mm | 0511-4 | 1:1 | left | 0.713 | 1.146 | 0.817 | |
| 848.31 | 777 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.38 | 0.00 | 10 mm | 0511-4 | 1:1 | left | 0.808 | 1.153 | 0.932 | |
| 848.31 | 777 | Cell. CDMA | EVDO Rev. 0 | 25.0 | 24.38 | 0.09 | 10 mm | 0511-4 | 1:1 | back | 0.825 | 1.153 | 0.951 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.39 | -0.04 | 10 mm | 0511-4 | 1:1 | back | 0.651 | 1.151 | 0.749 | |
| 1851.25 | 25 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.14 | 0.06 | 10 mm | 0511-4 | 1:1 | front | 0.594 | 1.219 | 0.724 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.39 | 0.08 | 10 mm | 0511-4 | 1:1 | front | 0.758 | 1.151 | 0.872 | A10 |
| 1908.75 | 1175 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.59 | 0.04 | 10 mm | 0511-4 | 1:1 | front | 0.679 | 1.099 | 0.746 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.39 | -0.03 | 10 mm | 0511-4 | 1:1 | bottom | 0.631 | 1.151 | 0.726 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.39 | 0.04 | 10 mm | 0511-4 | 1:1 | right | 0.182 | 1.151 | 0.209 | |
| 1880.00 | 600 | PCS CDMA | EVDO Rev. 0 | 25.0 | 24.39 | -0.10 | 10 mm | 0511-4 | 1:1 | left | 0.478 | 1.151 | 0.550 | |
| **ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population** | | | | | | | **Body<br>1.6 W/kg (mW/g)**<br>averaged over 1 gram | | | | | | | |

Note: Variability data is highlighted blue in the table above.


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 11-11
## LTE Band 13 Hotspot SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.01 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.881 | 1.021 | 0.900 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.06 | 1 | 0511-4 | QPSK | 25 | 0 | 10 mm | back | 1:1 | 0.638 | 1.125 | 0.718 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.35 | -0.02 | 1 | 0511-4 | QPSK | 50 | 0 | 10 mm | back | 1:1 | 0.634 | 1.161 | 0.736 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.02 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | front | 1:1 | 0.661 | 1.021 | 0.675 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.07 | 1 | 0511-4 | QPSK | 25 | 0 | 10 mm | front | 1:1 | 0.475 | 1.125 | 0.534 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.02 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | bottom | 1:1 | 0.101 | 1.021 | 0.103 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.03 | 1 | 0511-4 | QPSK | 25 | 0 | 10 mm | bottom | 1:1 | 0.063 | 1.125 | 0.071 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.03 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | right | 1:1 | 0.526 | 1.021 | 0.537 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.03 | 1 | 0511-4 | QPSK | 25 | 0 | 10 mm | right | 1:1 | 0.399 | 1.125 | 0.449 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.05 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | left | 1:1 | 0.674 | 1.021 | 0.688 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 23.0 | 22.49 | 0.00 | 1 | 0511-4 | QPSK | 25 | 0 | 10 mm | left | 1:1 | 0.608 | 1.125 | 0.684 | |
| 782.00 | 23230 | Mid | LTE Band 13 | 10 | 24.0 | 23.91 | -0.08 | 0 | 0511-4 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.918 | 1.021 | 0.937 | A11 |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | |

Note: Variability data is highlighted blue in the table above.

## Table 11-12
## LTE Band 4 (AWS) Hotspot SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | -0.04 | 0 | 2811-7 | QPSK | 1 | 50 | 10 mm | back | 1:1 | 0.905 | 1.007 | 0.911 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | -0.06 | 1 | 2811-7 | QPSK | 50 | 25 | 10 mm | back | 1:1 | 0.714 | 1.099 | 0.785 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 21.89 | -0.05 | 1 | 2811-7 | QPSK | 100 | 0 | 10 mm | back | 1:1 | 0.688 | 1.151 | 0.792 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | 0.07 | 0 | 2811-7 | QPSK | 1 | 50 | 10 mm | front | 1:1 | 0.906 | 1.007 | 0.912 | A13 |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | 0.04 | 1 | 2811-7 | QPSK | 50 | 25 | 10 mm | front | 1:1 | 0.710 | 1.099 | 0.780 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 21.89 | 0.00 | 1 | 2811-7 | QPSK | 100 | 0 | 10 mm | front | 1:1 | 0.690 | 1.151 | 0.794 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | -0.12 | 0 | 2811-7 | QPSK | 1 | 50 | 10 mm | bottom | 1:1 | 0.536 | 1.007 | 0.540 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | 0.00 | 1 | 2811-7 | QPSK | 50 | 25 | 10 mm | bottom | 1:1 | 0.393 | 1.099 | 0.432 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | -0.05 | 0 | 2811-7 | QPSK | 1 | 50 | 10 mm | right | 1:1 | 0.115 | 1.007 | 0.116 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | 0.09 | 1 | 2811-7 | QPSK | 50 | 25 | 10 mm | right | 1:1 | 0.087 | 1.099 | 0.096 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 23.5 | 23.47 | -0.02 | 0 | 2811-7 | QPSK | 1 | 50 | 10 mm | left | 1:1 | 0.533 | 1.007 | 0.537 | |
| 1732.50 | 20175 | Mid | LTE Band 4 (AWS) | 20 | 22.5 | 22.09 | -0.02 | 1 | 2811-7 | QPSK | 50 | 25 | 10 mm | left | 1:1 | 0.376 | 1.099 | 0.413 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | |


© 2014 PCTEST Engineering Laboratory, Inc.

## Table 11-13
## LTE Band 2 (PCS) Hotspot SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | | Mode | Bandwidth [MHz] | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | MPR [dB] | Device Serial Number | Modulation | RB Size | RB Offset | Spacing | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.04 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.885 | 1.059 | 0.937 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 22.7 | 22.25 | -0.06 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | back | 1:1 | 0.759 | 1.109 | 0.842 | |
| 1900.00 | 19100 | High | LTE Band 2 (PCS) | 20 | 22.7 | 22.14 | 0.10 | 0 | 2811-3 | QPSK | 1 | 50 | 10 mm | back | 1:1 | 0.649 | 1.138 | 0.739 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | -0.07 | 1 | 2811-3 | QPSK | 50 | 0 | 10 mm | back | 1:1 | 0.563 | 1.104 | 0.622 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 20.86 | -0.12 | 1 | 2811-3 | QPSK | 100 | 0 | 10 mm | back | 1:1 | 0.555 | 1.213 | 0.673 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | -0.04 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | front | 1:1 | 0.895 | 1.059 | 0.948 | A15 |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 22.7 | 22.25 | 0.14 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | front | 1:1 | 0.787 | 1.109 | 0.873 | |
| 1900.00 | 19100 | High | LTE Band 2 (PCS) | 20 | 22.7 | 22.14 | 0.13 | 0 | 2811-3 | QPSK | 1 | 50 | 10 mm | front | 1:1 | 0.737 | 1.138 | 0.839 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | 0.04 | 1 | 2811-3 | QPSK | 50 | 0 | 10 mm | front | 1:1 | 0.594 | 1.104 | 0.656 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 20.86 | -0.01 | 1 | 2811-3 | QPSK | 100 | 0 | 10 mm | front | 1:1 | 0.587 | 1.213 | 0.712 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.03 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | bottom | 1:1 | 0.488 | 1.059 | 0.517 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | 0.05 | 1 | 2811-3 | QPSK | 50 | 0 | 10 mm | bottom | 1:1 | 0.291 | 1.104 | 0.321 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | -0.03 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | right | 1:1 | 0.097 | 1.059 | 0.103 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | 0.00 | 1 | 2811-3 | QPSK | 50 | 0 | 10 mm | right | 1:1 | 0.055 | 1.104 | 0.061 | |
| 1860.00 | 18700 | Low | LTE Band 2 (PCS) | 20 | 22.7 | 22.45 | 0.06 | 0 | 2811-3 | QPSK | 1 | 0 | 10 mm | left | 1:1 | 0.388 | 1.059 | 0.411 | |
| 1880.00 | 18900 | Mid | LTE Band 2 (PCS) | 20 | 21.7 | 21.27 | -0.08 | 1 | 2811-3 | QPSK | 50 | 0 | 10 mm | left | 1:1 | 0.270 | 1.104 | 0.298 | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | | | |

## Table 11-14
## WLAN Hotspot SAR

| MEASUREMENT RESULTS | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| FREQUENCY | | Mode | Service | Maximum Allowed Power [dBm] | Conducted Power [dBm] | Power Drift [dB] | Spacing | Device Serial Number | Data Rate (Mbps) | Side | Duty Cycle | SAR (1g) | Scaling Factor | Scaled SAR (1g) | Plot # |
| MHz | Ch. | | | | | | | | | | | (W/kg) | | (W/kg) | |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | -0.01 | 10 mm | 2811-7 | 1 | back | 1:1 | 0.106 | 1.033 | **0.109** | A16 |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | 0.05 | 10 mm | 2811-7 | 1 | front | 1:1 | 0.066 | 1.033 | 0.068 | |
| 2462 | 11 | IEEE 802.11b | DSSS | 13.5 | 13.36 | -0.01 | 10 mm | 2811-7 | 1 | left | 1:1 | 0.106 | 1.033 | **0.109** | |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | |

## 11.4 SAR Test Notes

General Notes:

1. The test data reported are the worst-case SAR values according to test procedures specified in IEEE 1528-2003 and FCC KDB Publication 447498 D01v05.
2. Batteries are fully charged at the beginning of the SAR measurements.
3. Liquid tissue depth was at least 15.0 cm for all frequencies.
4. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
5. SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v05.
6. Device was tested using a fixed spacing for body-worn accessory testing. A separation distance of 10 mm was considered because the manufacturer has determined that there will be body-worn accessories available in the marketplace for users to support this separation distance.
7. Per FCC KDB Publication 648474 D04v01, body-worn SAR was evaluated without a headset connected to the device. Since the standalone reported body-worn SAR was ≤ 1.2 W/kg, no additional body-worn SAR evaluations using a headset cable were required.


© 2014 PCTEST Engineering Laboratory, Inc.

8. Per FCC KDB 865664 D01 v01, variability SAR tests were performed when the measured SAR results for a frequency band were greater than 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 13 for variability analysis.
9. During SAR Testing for the Wireless Router conditions per FCC KDB Publication 941225 D06v01, the actual Portable Hotspot operation (with actual simultaneous transmission of a transmitter with WIFI) was not activated (See Section 6.7 for more details).

CDMA Notes:

1. Head SAR for CDMA2000 mode was tested under RC3/SO55 per FCC KDB Publication 941225 D01v03.
2. Body-Worn SAR was tested with 1x RTT with TDSO / SO32 FCH Only. EVDO and TDSO / SO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO / SO32 FCH only powers, per FCC KDB Publication 941225 D01v03.
3. CDMA Wireless Router SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0 according to KDB 941225 D01 procedures for data devices. Since the average output power of Subtype 2 for Rev. A is less than the Rev. 0 power levels, EVDO Rev. A SAR is not required. SAR is not required for 1x RTT for Ev-Do hotspot devices when the maximum average output of each channel is less than ¼ dB higher than that measured in Subtype 0/1 Physical Layer configurations for Rev. 0.
4. Head SAR was additionally evaluated using EVDO Rev. A to determine compliance for VoIP operations.
5. Per FCC KDB Publication 447498 D01v05, if the reported (scaled) SAR measured at the middle channel or highest output power channel for each test configuration is ≤ 0.8 W/kg then testing at the other channels is not required for such test configuration(s). When the maximum output power variation across the required test channels is > ½ dB, instead of the middle channel, the highest output power channel was used.

LTE Notes:

1. LTE Considerations: LTE test configurations are determined according to SAR Evaluation Considerations for LTE Devices in FCC KDB Publication 941225 D05v02r01. The general test procedures used for testing can be found in Section 8.4.4.
2. MPR is permanently implemented for this device by the manufacturer. The specific manufacturer target MPR is indicated alongside the SAR results. MPR is enabled for this device, according to 3GPP TS36.101 Section 6.2.3 – 6.2.5 under Table 6.2.3-1.
3. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

WLAN Notes:

1. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 D01v01r02 and October 2012 FCC/TCB Meeting Notes for 2.4 GHz WIFI operations: Highest average RF output power channel for the lowest data rate was selected for SAR evaluation in 802.11b. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers over all channels and data rates were not more than 0.25 dB higher than the tested channel in the lowest data rate of IEEE 802.11b mode.
2. WIFI transmission was verified using an uncalibrated spectrum analyzer.
3. Since the maximum extrapolated peak SAR of the zoom scan for the maximum output channel is <1.6 W/kg and the reported 1g averaged SAR is <0.8 W/kg, SAR testing on other default channels was not required.


© 2014 PCTEST Engineering Laboratory, Inc.

# 12 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

## 12.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v05 are applicable to handsets with built-in unlicensed transmitters such as 802.11b/g/n and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

## 12.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05 IV.C.1.iii and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05 4.3.2 2), the following equation must be used to estimate the standalone 1g SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(GHz)}}{7.5} * \frac{(\text{Max Power of channel, mW})}{\text{Min. Separation Distance, mm}}$$

**Table 12-1**
**Estimated SAR**

| Mode | Frequency | Maximum Allowed Power | Separation Distance (Body) | Estimated SAR (Body) |
|---|---|---|---|---|
| | [MHz] | [dBm] | [mm] | [W/kg] |
| Bluetooth | 2480 | 12.00 | 10 | 0.336 |

Note: Held-to ear configurations are not applicable to Bluetooth operations and therefore were not considered for simultaneous transmission. Per KDB Publication 447498 D01v05, the maximum power of the channel was rounded to the nearest mW before calculation.

## 12.3 Head SAR Simultaneous Transmission Analysis

**Table 12-2**
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Held to Ear)**

| Simult Tx | Configuration | Cell. CDMA SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) | Simult Tx | Configuration | Cell. EVDO SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|---|
| Head SAR | Right Cheek | 0.568 | 0.196 | **0.764** | Head SAR | Right Cheek | 0.607 | 0.196 | **0.803** |
| | Right Tilt | 0.448 | 0.050 | 0.498 | | Right Tilt | 0.453 | 0.050 | 0.503 |
| | Left Cheek | 0.649 | 0.084 | 0.733 | | Left Cheek | 0.717 | 0.084 | 0.801 |
| | Left Tilt | 0.484 | 0.044 | 0.528 | | Left Tilt | 0.467 | 0.044 | 0.511 |


© 2014 PCTEST Engineering Laboratory, Inc.

| Simult Tx | Configuration | PCS CDMA SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Head SAR | Right Cheek | 0.477 | 0.196 | 0.673 |
| | Right Tilt | 0.356 | 0.050 | 0.406 |
| | Left Cheek | 0.873 | 0.084 | **0.957** |
| | Left Tilt | 0.355 | 0.044 | 0.399 |

| Simult Tx | Configuration | PCS EVDO SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Head SAR | Right Cheek | 0.703 | 0.196 | 0.899 |
| | Right Tilt | 0.481 | 0.050 | 0.531 |
| | Left Cheek | 1.086 | 0.084 | **1.170** |
| | Left Tilt | 0.415 | 0.044 | 0.459 |

| Simult Tx | Configuration | LTE Band 13 SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Head SAR | Right Cheek | 0.433 | 0.196 | **0.629** |
| | Right Tilt | 0.291 | 0.050 | 0.341 |
| | Left Cheek | 0.520 | 0.084 | 0.604 |
| | Left Tilt | 0.281 | 0.044 | 0.325 |

| Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Head SAR | Right Cheek | 0.437 | 0.196 | 0.633 |
| | Right Tilt | 0.421 | 0.050 | 0.471 |
| | Left Cheek | 1.027 | 0.084 | **1.111** |
| | Left Tilt | 0.420 | 0.044 | 0.464 |

| Simult Tx | Configuration | LTE Band 2 (PCS) SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Head SAR | Right Cheek | 0.559 | 0.196 | 0.755 |
| | Right Tilt | 0.329 | 0.050 | 0.379 |
| | Left Cheek | 1.055 | 0.084 | **1.139** |
| | Left Tilt | 0.274 | 0.044 | 0.318 |

## 12.4 Body-Worn Simultaneous Transmission Analysis

**Table 12-3**
**Simultaneous Transmission Scenario with 2.4 GHz WLAN (Body-Worn at 1.0 cm)**

| Configuration | Mode | CDMA/LTE SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Back Side | Cell. CDMA | 0.906 | 0.109 | 1.015 |
| Back Side | PCS CDMA | 0.831 | 0.109 | 0.940 |
| Back Side | LTE Band 13 | 0.937 | 0.109 | 1.046 |
| Back Side | LTE Band 4 | 0.911 | 0.109 | 1.020 |
| Back Side | LTE Band 2 | 0.937 | 0.109 | 1.046 |

**Table 12-4**
**Simultaneous Transmission Scenario with Bluetooth (Body-Worn at 1.0 cm)**

| Configuration | Mode | CDMA/LTE SAR (W/kg) | Bluetooth SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Back Side | Cell. CDMA | 0.906 | 0.336 | 1.242 |
| Back Side | PCS CDMA | 0.831 | 0.336 | 1.167 |
| Back Side | LTE Band 13 | 0.937 | 0.336 | **1.273** |
| Back Side | LTE Band 4 | 0.911 | 0.336 | 1.247 |
| Back Side | LTE Band 2 | 0.937 | 0.336 | **1.273** |

Note: Bluetooth SAR was not required to be measured per FCC KDB 447498. Estimated SAR results were used in the above table to determine simultaneous transmission SAR test exclusion.


© 2014 PCTEST Engineering Laboratory, Inc.

## 12.5 Hotspot SAR Simultaneous Transmission Analysis

Per FCC KDB Publication 941225 D06v01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("-").

**Table 12-5**
**Simultaneous Transmission Scenario (2.4 GHz Hotspot at 1.0 cm)**

| Simult Tx | Configuration | Cell. EVDO SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Body SAR | Back | 0.960 | 0.109 | **1.069** |
| | Front | 0.780 | 0.068 | 0.848 |
| | Top | - | - | 0.000 |
| | Bottom | 0.140 | - | 0.140 |
| | Right | 0.698 | - | 0.698 |
| | Left | 0.932 | 0.109 | 1.041 |

| Simult Tx | Configuration | PCS EVDO SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Body SAR | Back | 0.749 | 0.109 | 0.858 |
| | Front | 0.872 | 0.068 | **0.940** |
| | Top | - | - | 0.000 |
| | Bottom | 0.726 | - | 0.726 |
| | Right | 0.209 | - | 0.209 |
| | Left | 0.550 | 0.109 | 0.659 |

| Simult Tx | Configuration | LTE Band 13 SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Body SAR | Back | 0.937 | 0.109 | **1.046** |
| | Front | 0.675 | 0.068 | 0.743 |
| | Top | - | - | 0.000 |
| | Bottom | 0.103 | - | 0.103 |
| | Right | 0.537 | - | 0.537 |
| | Left | 0.688 | 0.109 | 0.797 |

| Simult Tx | Configuration | LTE Band 4 (AWS) SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Body SAR | Back | 0.911 | 0.109 | **1.020** |
| | Front | 0.912 | 0.068 | 0.980 |
| | Top | - | - | 0.000 |
| | Bottom | 0.540 | - | 0.540 |
| | Right | 0.116 | - | 0.116 |
| | Left | 0.537 | 0.109 | 0.646 |

| Simult Tx | Configuration | LTE Band 2 (PCS) SAR (W/kg) | 2.4 GHz WLAN SAR (W/kg) | Σ SAR (W/kg) |
|---|---|---|---|---|
| Body SAR | Back | 0.937 | 0.109 | **1.046** |
| | Front | 0.948 | 0.068 | 1.016 |
| | Top | - | - | 0.000 |
| | Bottom | 0.517 | - | 0.517 |
| | Right | 0.103 | - | 0.103 |
| | Left | 0.411 | 0.109 | 0.520 |

## 12.6 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v05 and IEEE 1528-2013 Section 6.3.4.1.2.


© 2014 PCTEST Engineering Laboratory, Inc.

# 13 SAR MEASUREMENT VARIABILITY

## 13.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
2) A second repeated measurement was preformed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.
4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

**Table 13-1**
**Head SAR Measurement Variability Results**

| HEAD VARIABILITY RESULTS | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Band | FREQUENCY | | Mode/Band | Service | Side | Test Position | Measured SAR (1g) | 1st Repeated SAR (1g) | Ratio | 2nd Repeated SAR (1g) | Ratio | 3rd Repeated SAR (1g) | Ratio |
| | MHz | Ch. | | | | | (W/kg) | (W/kg) | | (W/kg) | | (W/kg) | |
| 1750 | 1732.50 | 20175 | LTE Band 4 (AWS) | QPSK, 1 RB, 50 RB Offset | Left | Cheek | 1.020 | 1.020 | 1.00 | N/A | N/A | N/A | N/A |
| 1900 | 1860.00 | 18700 | LTE Band 2 (PCS) | QPSK, 1 RB, 0 RB Offset | Left | Cheek | 0.996 | 0.979 | 1.02 | N/A | N/A | N/A | N/A |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | Head<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | |

**Table 13-2**
**Body SAR Measurement Variability Results**

| BODY VARIABILITY RESULTS | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Band | FREQUENCY | | Mode | Service | Side | Spacing | Measured SAR (1g) | 1st Repeated SAR (1g) | Ratio | 2nd Repeated SAR (1g) | Ratio | 3rd Repeated SAR (1g) | Ratio |
| | MHz | Ch. | | | | | (W/kg) | (W/kg) | | (W/kg) | | (W/kg) | |
| 835 | 848.31 | 777 | Cell. CDMA | EVDO Rev. 0 | back | 10 mm | 0.833 | 0.825 | 1.01 | N/A | N/A | N/A | N/A |
| 750 | 782.00 | 23230 | LTE Band 13 | QPSK, 1 RB, 0 RB Offset | back | 10 mm | 0.881 | 0.918 | 1.04 | N/A | N/A | N/A | N/A |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT<br>Spatial Peak<br>Uncontrolled Exposure/General Population | | | | | Body<br>1.6 W/kg (mW/g)<br>averaged over 1 gram | | | | | | | | |

## 13.2 Measurement Uncertainty

The measured SAR was <1.5 W/kg for all frequency bands. Therefore, per KDB Publication 865664 D01v01, the extended measurement uncertainty analysis per IEEE 1528-2003 was not required.


© 2014 PCTEST Engineering Laboratory, Inc.

# 14 EQUIPMENT LIST

| Manufacturer | Model | Description | Cal Date | Cal Interval | Cal Due | Serial Number |
|---|---|---|---|---|---|---|
| SPEAG | DAK-3.5 | Dielectric Assessment Kit | 5/6/2014 | Annual | 5/6/2015 | 1070 |
| SPEAG | D750V3 | 750 MHz Dipole | 1/20/2014 | Annual | 1/20/2015 | 1003 |
| SPEAG | D835V2 | 835 MHz SAR Dipole | 7/10/2014 | Annual | 7/10/2015 | 4d132 |
| SPEAG | D1765V2 | 1750 MHz SAR Dipole | 5/7/2014 | Annual | 5/7/2015 | 1008 |
| SPEAG | D1900V2 | 1900 MHz SAR Dipole | 2/27/2014 | Annual | 2/27/2015 | 5d148 |
| SPEAG | D1900V2 | 1900 MHz SAR Dipole | 4/9/2014 | Annual | 4/9/2015 | 5d141 |
| SPEAG | D2450V2 | 2450 MHz SAR Dipole | 1/21/2014 | Annual | 1/21/2015 | 797 |
| SPEAG | ES3DV2 | SAR Probe | 8/19/2014 | Annual | 8/19/2015 | 3022 |
| SPEAG | ES3DV3 | SAR Probe | 10/24/2014 | Annual | 10/24/2015 | 3333 |
| SPEAG | ES3DV3 | SAR Probe | 4/17/2014 | Annual | 4/17/2015 | 3319 |
| SPEAG | ES3DV3 | SAR Probe | 2/25/2014 | Annual | 2/25/2015 | 3258 |
| SPEAG | ES3DV3 | SAR Probe | 4/11/2014 | Annual | 4/11/2015 | 3213 |
| SPEAG | ES3DV3 | SAR Probe | 3/19/2014 | Annual | 3/19/2015 | 3318 |
| SPEAG | ES3DV3 | SAR Probe | 9/18/2014 | Annual | 9/18/2015 | 3332 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 8/12/2014 | Annual | 8/12/2015 | 1322 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 10/23/2014 | Annual | 10/23/2015 | 1408 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 4/11/2014 | Annual | 4/11/2015 | 1368 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 2/26/2014 | Annual | 2/26/2015 | 665 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 11/18/2013 | Annual | 11/18/2014 | 1407 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 1/22/2014 | Annual | 1/22/2015 | 1272 |
| SPEAG | DAE4 | Dasy Data Acquisition Electronics | 9/17/2014 | Annual | 9/17/2015 | 1323 |
| Agilent | E4438C | ESG Vector Signal Generator | 4/1/2014 | Annual | 4/1/2015 | MY47270002 |
| Agilent | E4438C | ESG Vector Signal Generator | 4/25/2014 | Annual | 4/25/2015 | MY42082385 |
| Agilent | E4438C | ESG Vector Signal Generator | 4/15/2014 | Annual | 4/15/2015 | MY45090700 |
| Agilent | E5515C | Wireless Communications Test Set | 5/9/2013 | Biennial | 5/9/2015 | GB43304447 |
| Agilent | 8648D | (9kHz-4GHz) Signal Generator | 4/15/2014 | Annual | 4/15/2015 | 3629U00687 |
| Agilent | N5182A | MXG Vector Signal Generator | 4/15/2014 | Annual | 4/15/2015 | MY47420651 |
| Agilent | E4438C | ESG Vector Signal Generator | 3/31/2014 | Annual | 3/31/2015 | MY42082659 |
| Agilent | 8753ES | S-Parameter Network Analyzer | 5/22/2014 | Annual | 5/22/2015 | US39170118 |
| Agilent | N5182A | MXG Vector Signal Generator | 4/15/2014 | Annual | 4/15/2015 | MY47420800 |
| Agilent | 8594A | (9kHz-2.9GHz) Spectrum Analyzer | N/A | N/A | N/A | 3051A00187 |
| Agilent | N9020A | MXA Signal Analyzer | 10/27/2014 | Annual | 10/27/2015 | US46470561 |
| Agilent | E8257D | (250kHz-20GHz) Signal Generator | 4/15/2014 | Annual | 4/15/2015 | MY45470194 |
| Amplifier Research | 15S1G6 | Amplifier | CBT | N/A | CBT | 433976 |
| Amplifier Research | 15S1G6 | Amplifier | CBT | N/A | CBT | 433977 |
| Amplifier Research | 15S1G6 | Amplifier | CBT | N/A | CBT | 433975 |
| Amplifier Research | 15S1G6 | Amplifier | CBT | N/A | CBT | 433978 |
| Anritsu | MA24106A | USB Power Sensor | 1/3/2014 | Annual | 1/3/2015 | 1349509 |
| Anritsu | MT8820C | Radio Communication Analyzer | 12/12/2013 | Annual | 12/12/2014 | 6200901190 |
| Anritsu | MA24106A | USB Power Sensor | 1/3/2014 | Annual | 1/3/2015 | 1344554 |
| Anritsu | MA2411B | Pulse Power Sensor | 3/25/2014 | Annual | 3/25/2015 | 1207470 |
| Anritsu | MA24106A | USB Power Sensor | 5/14/2014 | Annual | 5/14/2015 | 1231535 |
| Anritsu | MA24106A | USB Power Sensor | 5/14/2014 | Annual | 5/14/2015 | 1248508 |
| Anritsu | MA2411B | Pulse Power Sensor | 2/3/2014 | Annual | 2/3/2015 | 1339018 |
| Anritsu | ML2469A | Power Meter | 3/14/2014 | Annual | 3/14/2015 | 1306009 |
| Anritsu | ML2495A | Power Meter | 10/31/2013 | Biennial | 10/31/2015 | 0941001 |
| COMTech | AR85729-5 | Solid State Amplifier | CBT | N/A | CBT | M1S5A00-009 |
| COMTECH | AR85729-5/5759B | Solid State Amplifier | CBT | N/A | CBT | M3W1A00-1002 |
| Control Company | 36934-158 | Wall-Mounted Thermometer | 4/29/2014 | Biennial | 4/29/2016 | 122014488 |
| Control Company | 61220-416 | Long-Stem Thermometer | 4/29/2014 | Biennial | 4/29/2016 | 111331323 |
| Fisher Scientific | 15-077-960 | Digital Thermometer | 12/4/2013 | Biennial | 12/4/2015 | 130764558 |
| MCL | BW-N6W5+ | 6dB Attenuator | CBT | N/A | CBT | 1139 |
| MiniCircuits | VLF-6000+ | Low Pass Filter | CBT | N/A | CBT | N/A |
| MiniCircuits | SLP-2400+ | Low Pass Filter | CBT | N/A | CBT | R8979500903 |
| MiniCircuits | VLF-6000+ | Low Pass Filter | CBT | N/A | CBT | N/A |
| Mini-Circuits | BW-N20W5+ | DC to 18 GHz Precision Fixed 20 dB Attenuator | CBT | N/A | CBT | N/A |
| Mini-Circuits | NLP-1200+ | Low Pass Filter DC to 1000 MHz | CBT | N/A | CBT | N/A |
| Mini-Circuits | NLP-2950+ | Low Pass Filter DC to 2700 MHz | CBT | N/A | CBT | N/A |
| Mini-Circuits | BW-N20W5 | Power Attenuator | CBT | N/A | CBT | 1226 |
| Mitutoyo | CD-6"CSX | Digital Caliper | 5/8/2014 | Biennial | 5/8/2016 | 13264165 |
| Mitutoyo | CD-6"CSX | Digital Caliper | 5/8/2014 | Biennial | 5/8/2016 | 13264162 |
| Narda | 4014C-6 | 4 - 8 GHz SMA 6 dB Directional Coupler | CBT | N/A | CBT | N/A |
| Narda | BW-S3W2 | Attenuator (3dB) | CBT | N/A | CBT | 120 |
| Narda | 4772-3 | Attenuator (3dB) | CBT | N/A | CBT | 9406 |
| Pasternack | PE2209-10 | Bidirectional Coupler | CBT | N/A | CBT | N/A |
| Pasternack | PE2208-6 | Bidirectional Coupler | CBT | N/A | CBT | N/A |
| Rohde & Schwarz | CMW500 | Radio Communication Tester | 4/23/2014 | Annual | 4/23/2015 | 112347 |
| Rohde & Schwarz | CMW500 | Radio Communication Tester | 9/2/2014 | Annual | 9/2/2015 | 111427 |
| Rohde & Schwarz | CMW500 | Radio Communication Tester | 10/4/2013 | Biennial | 10/4/2015 | 108798 |
| Seekonk | NC-100 | Torque Wrench | 3/18/2014 | Biennial | 3/18/2016 | 22313 |
| Seekonk | NC-100 | Torque Wrench 5/16", 8" lbs | 3/18/2014 | Biennial | 3/18/2016 | N/A |
| Tektronix | RSA6114A | Real Time Spectrum Analyzer | 4/16/2014 | Annual | 4/16/2015 | B010177 |
| VWR | 36934-158 | Wall-Mounted Thermometer | 8/8/2013 | Biennial | 8/8/2015 | 130477877 |
| VWR | 36934-158 | Wall-Mounted Thermometer | 4/29/2014 | Biennial | 4/29/2016 | 111859323 |

Note:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment was used solely within its valid calibration period.


© 2014 PCTEST Engineering Laboratory, Inc.

# 15 MEASUREMENT UNCERTAINTIES

Applicable for frequencies less than 3000 MHz.

| a | b | c | d | e= f(d,k) | f | g | h = c x f/e | i = c x g/e | k |
|---|---|---|---|---|---|---|---|---|---|
| Uncertainty Component | IEEE 1528 Sec. | Tol. (± %) | Prob. Dist. | Div. | $c_i$ 1gm | $c_i$ 10 gms | 1gm $u_i$ (± %) | 10gms $u_i$ (± %) | $v_i$ |
| **Measurement System** | | | | | | | | | |
| Probe Calibration | E.2.1 | 6.0 | N | 1 | 1.0 | 1.0 | 6.0 | 6.0 | ∞ |
| Axial Isotropy | E.2.2 | 0.25 | N | 1 | 0.7 | 0.7 | 0.2 | 0.2 | ∞ |
| Hemishperical Isotropy | E.2.2 | 1.3 | N | 1 | 1.0 | 1.0 | 1.3 | 1.3 | ∞ |
| Boundary Effect | E.2.3 | 0.4 | N | 1 | 1.0 | 1.0 | 0.4 | 0.4 | ∞ |
| Linearity | E.2.4 | 0.3 | N | 1 | 1.0 | 1.0 | 0.3 | 0.3 | ∞ |
| System Detection Limits | E.2.5 | 5.1 | N | 1 | 1.0 | 1.0 | 5.1 | 5.1 | ∞ |
| Readout Electronics | E.2.6 | 1.0 | N | 1 | 1.0 | 1.0 | 1.0 | 1.0 | ∞ |
| Response Time | E.2.7 | 0.8 | R | 1.73 | 1.0 | 1.0 | 0.5 | 0.5 | ∞ |
| Integration Time | E.2.8 | 2.6 | R | 1.73 | 1.0 | 1.0 | 1.5 | 1.5 | ∞ |
| RF Ambient Conditions | E.6.1 | 3.0 | R | 1.73 | 1.0 | 1.0 | 1.7 | 1.7 | ∞ |
| Probe Positioner Mechanical Tolerance | E.6.2 | 0.4 | R | 1.73 | 1.0 | 1.0 | 0.2 | 0.2 | ∞ |
| Probe Positioning w/ respect to Phantom | E.6.3 | 2.9 | R | 1.73 | 1.0 | 1.0 | 1.7 | 1.7 | ∞ |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | E.5 | 1.0 | R | 1.73 | 1.0 | 1.0 | 0.6 | 0.6 | ∞ |
| **Test Sample Related** | | | | | | | | | |
| Test Sample Positioning | E.4.2 | 6.0 | N | 1 | 1.0 | 1.0 | 6.0 | 6.0 | 287 |
| Device Holder Uncertainty | E.4.1 | 3.32 | R | 1.73 | 1.0 | 1.0 | 1.9 | 1.9 | ∞ |
| Output Power Variation - SAR drift measurement | 6.6.2 | 5.0 | R | 1.73 | 1.0 | 1.0 | 2.9 | 2.9 | ∞ |
| **Phantom & Tissue Parameters** | | | | | | | | | |
| Phantom Uncertainty (Shape & Thickness tolerances) | E.3.1 | 4.0 | R | 1.73 | 1.0 | 1.0 | 2.3 | 2.3 | ∞ |
| Liquid Conductivity - deviation from target values | E.3.2 | 5.0 | R | 1.73 | 0.64 | 0.43 | 1.8 | 1.2 | ∞ |
| Liquid Conductivity - measurement uncertainty | E.3.3 | 3.8 | N | 1 | 0.64 | 0.43 | 2.4 | 1.6 | 6 |
| Liquid Permittivity - deviation from target values | E.3.2 | 5.0 | R | 1.73 | 0.60 | 0.49 | 1.7 | 1.4 | ∞ |
| Liquid Permittivity - measurement uncertainty | E.3.3 | 4.5 | N | 1 | 0.60 | 0.49 | 2.7 | 2.2 | 6 |
| **Combined Standard Uncertainty (k=1)** | RSS | | | | | | 12.1 | 11.7 | 299 |
| **Expanded Uncertainty** (95% CONFIDENCE LEVEL) | k=2 | | | | | | 24.2 | 23.5 | |

The above measurement uncertainties are according to IEEE Std. 1528-2003


© 2014 PCTEST Engineering Laboratory, Inc.

# 16 CONCLUSION

## 16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]


© 2014 PCTEST Engineering Laboratory, Inc.

# 17 REFERENCES


[1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.

[2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.

[3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.

[4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.

[5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

[6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.

[7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.

[8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.

[9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.

[10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.

[11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.

[12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.

[13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.

[14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.

[15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.

[16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

[17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

[18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.




© 2014 PCTEST Engineering Laboratory, Inc.

[19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hoschschule Zürich, Dosimetric Evaluation of the Cellular Phone.

[20] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.

[21] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.

[22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009

[23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07

[24] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227 D01v01r02

[25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D02-D04

[26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04

[27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02

[28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02

[29] Anexo à Resolução No. 533, de 10 de Septembro de 2009.

[30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.


© 2014 PCTEST Engineering Laboratory, Inc.

# APPENDIX A: SAR TEST DATA

© 2014 PCTEST Engineering Laboratory, Inc.

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1
Medium: 835 Head, Medium parameters used (interpolated):
f = 836.52 MHz; $\sigma$ = 0.93 S/m; $\varepsilon_r$ = 41.548; $\rho$ = 1000 kg/m$^3$
Phantom section: Left Section

Test Date: 11-10-2014; Ambient Temp: 22.4°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3333; ConvF(6.33, 6.33, 6.33); Calibrated: 10/24/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014
Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: Cell. EVDO Rev. A, Left Head, Cheek, Mid.ch**

**Area Scan (9x15x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 27.220 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 0.791 W/kg
**SAR(1 g) = 0.623 W/kg**




0 dB = 0.694 W/kg = -1.59 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Head, Medium parameters used:
f = 1880 MHz; $\sigma$ = 1.427 S/m; $\varepsilon_r$ = 38.686; $\rho$ = 1000 kg/m$^3$
Phantom section: Left Section

Test Date: 11-13-2014; Ambient Temp: 22.9°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3333; ConvF(5.11, 5.11, 5.11); Calibrated: 10/24/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: PCS EVDO Rev. A, Left Head, Cheek, Mid.ch**

**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 26.790 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 1.43 W/kg
**SAR(1 g) = 0.942 W/kg**




0 dB = 1.12 W/kg = 0.49 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1
Medium: 750 Head, Medium parameters used (interpolated):
f = 782 MHz; $\sigma$ = 0.933 S/m; $\varepsilon_r$ = 40.079; $\rho$ = 1000 kg/m$^3$
Phantom section: Left Section

Test Date: 11-10-2014; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: ES3DV2 - SN3022; ConvF(6.39, 6.39, 6.39); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 13, Left Head, Cheek, Mid.ch,**
**QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset**

**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.057 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 0.648 W/kg
**SAR(1 g) = 0.509 W/kg**




0 dB = 0.555 W/kg = -2.56 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-7**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1
Medium: 1750 Head, Medium parameters used (interpolated):
f = 1732.5 MHz; $\sigma$ = 1.382 S/m; $\varepsilon_r$ = 39.493; $\rho$ = 1000 kg/m$^3$
Phantom section: Left Section

Test Date: 12-08-2014; Ambient Temp: 21.6°C; Tissue Temp: 21.0°C

Probe: ES3DV2 - SN3022; ConvF(5.04, 5.04, 5.04); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Left Head, Cheek, Mid.ch,**
**QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset**

**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.354 V/m; Power Drift = -0.16 dB
Peak SAR (extrapolated) = 1.57 W/kg
**SAR(1 g) = 1.02 W/kg**




0 dB = 1.20 W/kg = 0.79 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-3**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1
Medium: 1900 Head, Medium parameters used (interpolated):
f = 1860 MHz; $\sigma$ = 1.366 S/m; $\varepsilon_r$ = 39.969; $\rho$ = 1000 kg/m$^3$
Phantom section: Left Section

Test Date: 11-24-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.05, 5.05, 5.05); Calibrated: 4/17/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 4/11/2014
Phantom: SAM; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 2 (PCS), Left Head, Cheek, Low.ch,**
**QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset**

**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 27.46 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.55 W/kg
**SAR(1 g) = 0.996 W/kg**




0 dB = 1.22 W/kg = 0.86 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-7**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1
Medium: 2450 Head, Medium parameters used (interpolated):
f = 2462 MHz; $\sigma$ = 1.77 S/m; $\varepsilon_r$ = 38.916; $\rho$ = 1000 kg/m$^3$
Phantom section: Right Section

Test Date: 12-19-2014; Ambient Temp: 24.4°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (7); SEMCAD X Version 14.6.10 (7164)

## Mode: IEEE 802.11b, Right Head, Cheek, Ch 11, 1 Mbps

**Area Scan (10x17x1):** Measurement grid: dx=12mm, dy=12mm
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.422 V/m; Power Drift = 0.12 dB
Peak SAR (extrapolated) = 0.424 W/kg
**SAR(1 g) = 0.190 W/kg**




0 dB = 0.256 W/kg = -5.92 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, CDMA; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: 835 Body, Medium parameters used (interpolated):
f = 848.31 MHz; $\sigma$ = 0.972 S/m; $\varepsilon_r$ = 53.46; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-05-2014; Ambient Temp: 22.5°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.18, 6.18, 6.18); Calibrated: 4/11/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 11/18/2013
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: Cell. CDMA, Body SAR, Back side, High.ch**

**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 28.905 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 0.979 W/kg
**SAR(1 g) = 0.784 W/kg**




0 dB = 0.859 W/kg = -0.66 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, CDMA; Frequency: 848.31 MHz; Duty Cycle: 1:1
Medium: 835 Body, Medium parameters used (interpolated):
f = 848.31 MHz; $\sigma$ = 0.962 S/m; $\varepsilon_r$ = 52.918; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-11-2014; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: Cell. EVDO Rev. 0, Body SAR, Back side, High.ch**

**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 30.010 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.06 W/kg
**SAR(1 g) = 0.833 W/kg**




0 dB = 0.916 W/kg = -0.38 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Body, Medium parameters used:
f = 1880 MHz; $\sigma$ = 1.547 S/m; $\varepsilon_r$ = 52.866; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-10-2014; Ambient Temp: 22.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 6/19/2014
Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: PCS CDMA, Body SAR, Back side, Mid.ch**

**Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 21.339 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 1.30 W/kg
**SAR(1 g) = 0.727 W/kg**




0 dB = 0.869 W/kg = -0.61 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, CDMA; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: 1900 Body, Medium parameters used:
f = 1880 MHz; $\sigma$ = 1.547 S/m; $\varepsilon_r$ = 52.866; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-10-2014; Ambient Temp: 22.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 6/19/2014
Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: PCS EVDO Rev. 0, Body SAR, Front side, Mid.ch**

**Area Scan (9x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.202 V/m; Power Drift = 0.08 dB
Peak SAR (extrapolated) = 1.36 W/kg
**SAR(1 g) = 0.758 W/kg**




0 dB = 0.928 W/kg = -0.32 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 0511-4**

Communication System: UID 0, LTE Band 13; Frequency: 782 MHz; Duty Cycle: 1:1
Medium: 750 Body, Medium parameters used (interpolated):
f = 782 MHz; $\sigma$ = 1.01 S/m; $\varepsilon_r$ = 55.516; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-12-2014; Ambient Temp: 23.3°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(6.02, 6.02, 6.02); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 13, Body SAR, Back side, Mid.ch,**
**QPSK, 10 MHz Bandwidth, 1 RB, 0 RB Offset**

**Area Scan (8x13x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 31.388 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.14 W/kg
**SAR(1 g) = 0.918 W/kg**




0 dB = 1.00 W/kg = 0.00 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-7**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1
Medium: 1750 Body, Medium parameters used (interpolated):
f = 1732.5 MHz; $\sigma$ = 1.489 S/m; $\varepsilon_r$ = 52.104; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 21.0°C; Tissue Temp: 20.9°C

Probe: ES3DV2 - SN3022; ConvF(4.7, 4.7, 4.7); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Body SAR, Back side, Mid.ch,**
**QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset**

**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.691 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.52 W/kg
**SAR(1 g) = 0.905 W/kg**




0 dB = 1.09 W/kg = 0.37 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-7**

Communication System: UID 0, LTE Band 4 (AWS); Frequency: 1732.5 MHz; Duty Cycle: 1:1
Medium: 1750 Body, Medium parameters used (interpolated):
f = 1732.5 MHz; $\sigma$ = 1.489 S/m; $\varepsilon_r$ = 52.104; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 21.0°C; Tissue Temp: 20.9°C

Probe: ES3DV2 - SN3022; ConvF(4.7, 4.7, 4.7); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 4 (AWS), Body SAR, Front side, Mid.ch,**
**QPSK, 20 MHz Bandwidth, 1 RB, 50 RB Offset**

**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.680 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.49 W/kg
**SAR(1 g) = 0.906 W/kg**




0 dB = 1.07 W/kg = 0.29 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-3**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1
Medium: 1900 Body, Medium parameters used (interpolated):
f = 1860 MHz; $\sigma$ = 1.536 S/m; $\varepsilon_r$ = 52.767; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-24-2014; Ambient Temp: 20.6°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3319; ConvF(4.67, 4.67, 4.67); Calibrated: 4/17/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 4/11/2014
Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 2 (PCS), Body SAR, Back side, Low.ch, QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset**

**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.63 V/m; Power Drift = 0.04 dB
Peak SAR (extrapolated) = 1.43 W/kg
**SAR(1 g) = 0.885 W/kg**




0 dB = 0.994 W/kg = -0.03 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-3**

Communication System: UID 0, LTE Band 2 (PCS); Frequency: 1860 MHz; Duty Cycle: 1:1
Medium: 1900 Body, Medium parameters used (interpolated):
f = 1860 MHz; $\sigma$ = 1.536 S/m; $\varepsilon_r$ = 52.767; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-24-2014; Ambient Temp: 20.6°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3319; ConvF(4.67, 4.67, 4.67); Calibrated: 4/17/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 4/11/2014
Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

**Mode: LTE Band 2 (PCS), Body SAR, Front side, Low.ch, QPSK, 20 MHz Bandwidth, 1 RB, 0 RB Offset**

**Area Scan (8x12x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.68 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 1.47 W/kg
**SAR(1 g) = 0.895 W/kg**




0 dB = 1.03 W/kg = 0.13 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: A3LSMG360V; Type: Portable Handset; Serial: 2811-7**

Communication System: UID 0, IEEE 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1
Medium: 2450 Body, Medium parameters used (interpolated):
f = 2462 MHz; $\sigma$ = 1.937 S/m; $\varepsilon_r$ = 50.712; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-17-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.3°C

Probe: ES3DV3 - SN3332; ConvF(4.31, 4.31, 4.31); Calibrated: 9/18/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 9/17/2014
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## Mode: IEEE 802.11b, Body SAR, Ch 11, 1 Mbps, Back Side

**Area Scan (9x14x1):** Measurement grid: dx=12mm, dy=12mm
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.929 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 0.208 W/kg
**SAR(1 g) = 0.106 W/kg**




0 dB = 0.134 W/kg = -8.73 dBW/kg

# APPENDIX B: SYSTEM VERIFICATION

© 2014 PCTEST Engineering Laboratory, Inc.

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 750 MHz; Type: D750V3; Serial: 1003**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1
Medium: 750 Head, Medium parameters used (interpolated):
f = 750 MHz; $\sigma$ = 0.89 S/m; $\varepsilon_r$ = 40.322; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-10-2014; Ambient Temp: 22.7°C; Tissue Temp: 21.6°C

Probe: ES3DV2 - SN3022; ConvF(6.39, 6.39, 6.39); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 750 MHz System Verification

**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.15 W/kg
**SAR(1 g) = 0.772 W/kg**
Deviation(1 g): -7.77%




0 dB = 0.901 W/kg = -0.45 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 835 MHz; Type: D835V2; Serial: 4d132**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: 835 Head, Medium parameters used:
f = 835 MHz; $\sigma$ = 0.929 S/m; $\varepsilon_r$ = 41.568; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-10-2014; Ambient Temp: 22.4°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3333; ConvF(6.33, 6.33, 6.33); Calibrated: 10/24/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014
Phantom: Sub TWIN SAM; Type: QD000P40CC; Serial: TP-1357
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.44 W/kg
**SAR(1 g) = 0.969 W/kg**
Deviation(1 g): 4.53%




0 dB = 1.13 W/kg = 0.53 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1750 MHz; Type: D1765V2; Serial: 1008**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1
Medium: 1750 Head, Medium parameters used:
f = 1750 MHz; $\sigma$ = 1.398 S/m; $\varepsilon_r$ = 39.405; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 21.6°C; Tissue Temp: 21.0°C

Probe: ES3DV2 - SN3022; ConvF(5.04, 5.04, 5.04); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: SAM with CRP v4.0; Type: QD000P40CD; Serial: TP:1800
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 1750 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 6.36 W/kg
**SAR(1 g) = 3.55 W/kg**
Deviation(1 g): -3.79%




0 dB = 4.38 W/kg = 6.41 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Head, Medium parameters used (interpolated):
f = 1900 MHz; $\sigma$ = 1.449 S/m; $\varepsilon_r$ = 38.598; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-13-2014; Ambient Temp: 22.9°C; Tissue Temp: 21.3°C

Probe: ES3DV3 - SN3333; ConvF(5.11, 5.11, 5.11); Calibrated: 10/24/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 7.23 W/kg
**SAR(1 g) = 4 W/kg**
Deviation(1 g): -1.72%




0 dB = 5.11 W/kg = 7.08 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Head, Medium parameters used (interpolated):
f = 1900 MHz; $\sigma$ = 1.405 S/m; $\varepsilon_r$ = 39.844; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-24-2014; Ambient Temp: 23.2°C; Tissue Temp: 22.5°C

Probe: ES3DV3 - SN3319; ConvF(5.05, 5.05, 5.05); Calibrated: 4/17/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 4/11/2014
Phantom: SAM; Type: QD000P40CD; Serial: TP:1758
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 7.81 W/kg
**SAR(1 g) = 4.27 W/kg**
Deviation(1 g): 6.48%




0 dB = 5.50 W/kg = 7.40 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: 2450 Head, Medium parameters used:
f = 2450 MHz; $\sigma$ = 1.756 S/m; $\varepsilon_r$ = 38.948; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-19-2014; Ambient Temp: 24.4°C; Tissue Temp: 21.9°C

Probe: ES3DV3 - SN3258; ConvF(4.52, 4.52, 4.52); Calibrated: 2/25/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn665; Calibrated: 2/26/2014
Phantom: SAM Front; Type: SAM; Serial: 1686
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 10.2 W/kg
**SAR(1 g) = 4.92 W/kg**
Deviation(1 g): -5.02%




0 dB = 6.51 W/kg = 8.14 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 750 MHz; Type: D750V3; Serial: 1003**

Communication System: UID 0, CW; Frequency: 750 MHz; Duty Cycle: 1:1
Medium: 750 Body, Medium parameters used (interpolated):
f = 750 MHz; $\sigma$ = 0.983 S/m; $\varepsilon_r$ = 56.04; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-12-2014; Ambient Temp: 23.3°C; Tissue Temp: 22.3°C

Probe: ES3DV2 - SN3022; ConvF(6.02, 6.02, 6.02); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 750 MHz System Verification

**Area Scan (7x15x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.33 W/kg
**SAR(1 g) = 0.917 W/kg**
Deviation(1 g): 4.56%




0 dB = 1.07 W/kg = 0.29 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 835 MHz; Type: D835V2; Serial: 4d132**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: 835 Body, Medium parameters used:
f = 835 MHz; $\sigma$ = 0.96 S/m; $\varepsilon_r$ = 53.584; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-05-2014; Ambient Temp: 22.5°C; Tissue Temp: 21.6°C

Probe: ES3DV3 - SN3213; ConvF(6.18, 6.18, 6.18); Calibrated: 4/11/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1407; Calibrated: 11/18/2013
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.45 W/kg
**SAR(1 g) = 0.990 W/kg**
Deviation(1 g): 3.34%




0 dB = 1.15 W/kg = 0.61 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 835 MHz; Type: D835V2; Serial: 4d132**

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1
Medium: 835 Body, Medium parameters used:
f = 835 MHz; $\sigma$ = 0.948 S/m; $\varepsilon_r$ = 53.049; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-11-2014; Ambient Temp: 22.8°C; Tissue Temp: 21.7°C

Probe: ES3DV3 - SN3333; ConvF(6.12, 6.12, 6.12); Calibrated: 10/24/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1408; Calibrated: 10/23/2014
Phantom: Main TWIN SAM; Type: QD000P40CC; Serial: TP-1406
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 835 MHz System Verification

**Area Scan (7x14x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 1.49 W/kg
**SAR(1 g) = 1.03 W/kg**
Deviation(1 g): 7.52%




0 dB = 1.20 W/kg = 0.79 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1750 MHz; Type: D1765V2; Serial: 1008**

Communication System: UID 0, CW; Frequency: 1750 MHz; Duty Cycle: 1:1
Medium: 1750 Body, Medium parameters used:
f = 1750 MHz; $\sigma$ = 1.508 S/m; $\varepsilon_r$ = 52.023; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-08-2014; Ambient Temp: 21.0°C; Tissue Temp: 20.9°C

Probe: ES3DV2 - SN3022; ConvF(4.7, 4.7, 4.7); Calibrated: 8/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1322; Calibrated: 8/12/2014
Phantom: ELI v5.0; Type: QDOVA001BB; Serial: 1226
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 1750 MHz System Verification

**Area Scan (7x9x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 6.84 W/kg
**SAR(1 g) = 3.95 W/kg**
Deviation(1 g): 5.05%




0 dB = 4.86 W/kg = 6.87 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d148**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Body, Medium parameters used (interpolated):
f = 1900 MHz; $\sigma$ = 1.571 S/m; $\varepsilon_r$ = 52.834; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-10-2014; Ambient Temp: 22.1°C; Tissue Temp: 21.0°C

Probe: ES3DV3 - SN3318; ConvF(4.6, 4.6, 4.6); Calibrated: 3/19/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1272; Calibrated: 6/19/2014
Phantom: Sub Twin Sam v5.0; Type: QD000P40CD; Serial: TP:1626
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 7.22 W/kg
**SAR(1 g) = 4.03 W/kg**
Deviation(1 g): 2.54%




0 dB = 5.08 W/kg = 7.06 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 1900 MHz; Type: D1900V2; Serial: 5d141**

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: 1900 Body, Medium parameters used (interpolated):
f = 1900 MHz; $\sigma$ = 1.572 S/m; $\varepsilon_r$ = 52.603; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 11-24-2014; Ambient Temp: 20.6°C; Tissue Temp: 22.0°C

Probe: ES3DV3 - SN3319; ConvF(4.67, 4.67, 4.67); Calibrated: 4/17/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1368; Calibrated: 4/11/2014
Phantom: ELI left; Type: QDOVA002AA; Serial: TP:1202
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 1900 MHz System Verification

**Area Scan (7x10x1):** Measurement grid: dx=15mm, dy=15mm
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 6.58 W/kg
**SAR(1 g) = 3.76 W/kg**
Deviation(1 g): -7.39%




0 dB = 4.76 W/kg = 6.78 dBW/kg

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 797**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1
Medium: 2450 Body, Medium parameters used:
f = 2450 MHz; $\sigma$ = 1.922 S/m; $\varepsilon_r$ = 50.754; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section; Space: 1.0 cm

Test Date: 12-17-2014; Ambient Temp: 24.5°C; Tissue Temp: 24.3°C

Probe: ES3DV3 - SN3332; ConvF(4.31, 4.31, 4.31); Calibrated: 9/18/2014;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1323; Calibrated: 9/17/2014
Phantom: SAM 5.0 front; Type: QD000P40CD; Serial: TP:-1648
Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7164)

## 2450 MHz System Verification

**Area Scan (8x9x1):** Measurement grid: dx=12mm, dy=12mm
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Input Power: 20.0 dBm (100 mW)
Peak SAR (extrapolated) = 10.0 W/kg
**SAR(1 g) = 4.94 W/kg**
Deviation(1 g): 0.00%




0 dB = 6.45 W/kg = 8.10 dBW/kg