FCC CFR47 PART 15 SUBPART C

ANT+
CERTIFICATION TEST REPORT

FOR

GSM/WCDMA Phone + Bluetooth, WLAN 2.4GHz b/g/n & ANT+

MODEL NUMBER: SM-G530H; SM-G530H/DS

FCC ID: A3LSMG530H

REPORT NUMBER: 14U18490-E5

ISSUE DATE: AUGUST 18, 2014

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	8/18/14	Initial Issue	P. Zhang

UL VERIFICATION SERVICES INC. FORM NO: CCSUP4701D
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS 4

2. TEST METHODOLOGY 5

3. FACILITIES AND ACCREDITATION 5

4. CALIBRATION AND UNCERTAINTY 5

4.1. MEASURING INSTRUMENT CALIBRATION 5

4.2. SAMPLE CALCULATION 5

4.3. MEASUREMENT UNCERTAINTY 6

5. EQUIPMENT UNDER TEST 7

5.1. DESCRIPTION OF EUT 7

5.2. MAXIMUM OUTPUT FUNDAMENTAL FIELD STRENGTH 7

5.3. DESCRIPTION OF AVAILABLE ANTENNAS 7

5.4. WORST-CASE CONFIGURATION AND MODE 7

5.5. DESCRIPTION OF TEST SETUP 8

6. TEST AND MEASUREMENT EQUIPMENT 10

7. LIMITS AND RESULTS 11

7.1. 99% BANDWIDTH 11

7.2. TRANSMITTER RADIATED EMISSIONS 14

7.2.1. DUTY CYCLE 16
7.2.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION 17
7.2.3. TRANSMITTER RESTRICTED BAND EDGES 18
7.2.4. SPURIOUS BELOW 1 GHz 23

8. AC POWER LINE CONDUCTED EMISSIONS 26

9. SETUP PHOTOS 30

END OF REPORT 36

UL VERIFICATION SERVICES INC. FORM NO: CCSUP4701D
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

1. ATTESTATION OF TEST RESULTS

COMPANY NAME:	SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION:	GSM/WCDMA Phone + Bluetooth, WLAN 2.4GHz b/g/n & ANT+
MODEL:	SM-G530H; SM-G530H/DS
SERIAL NUMBER:	1935709(Radiated) & 1935710(Conducted)
DATE TESTED:	AUGUST 4-18, 2014

APPLICABLE STANDARDS

STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For

UL Verification Services Inc. By:

PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

Tested By:

R. ALEGRE
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☒ Chamber A	☐ Chamber D
☐ Chamber B	☒ Chamber E
☐ Chamber C	☐ Chamber F
☐ Chamber G	☒ Chamber H

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at http://ts.nist.gov/standards/scopes/2000650.htm.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA Phone + Bluetooth, WLAN 2.4GHz b/g/n & ANT+.

5.2. MAXIMUM OUTPUT FUNDAMENTAL FIELD STRENGTH

The ANT+ mode has maximum output fundamental field strength as follows:

Frequency Range (MHz)	Mode	Peak E-field Strength (dBuV/m)	Avg E-field Strength (dBuV/m)	Distance (m)
2402 - 2480	ANT +	90.10	89.55	3.00

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -1.86dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that Z orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Z orientation.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	**Manufacturer**	**Model**	**Serial Number**	**FCC ID**
AC Adapter	Samsung	SM-G530H	ETA0U93CBC	N/A
Earphone	Samsung	GH59	N/A	N/A

I/O CABLES

I/O Cable List						
Cable No	**Port**	**# of identical ports**	**Connector Type**	**Cable Type**	**Cable Length (m)**	**Remarks**
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is set to continuously transmit in ANT + test mode

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SETUP DIAGRAM FOR TESTS



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	**Manufacturer**	**Model**	**Asset**	**Cal Due**
Antenna, Biconolog, 30MHz-1 GHz	Sunol Sciences	JB1	C01171	02/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/14
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00980	11/14/14
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	01/28/15
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01052	10/22/14
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/14
CBT Bluetooth Tester	R & S	CBT	None	07/12/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/14
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/14
LISN, 30 MHz	FCC	50/250-25-2	C00626	01/14/15
Reject Filter, 2.4GHz	Micro-Tronics	BRM50702	N02684	CNR

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7. LIMITS AND RESULTS

7.1. 99% BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Frequency (MHz)	99% Bandwidth (MHz)
2402	0.89117
2442	0.88846
2480	0.89184

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

99% BANDWIDTH





This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

99% BANDWIDTH HIGH CH



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2. TRANSMITTER RADIATED EMISSIONS

TEST PROCEDURE

ANSI C63.4

LIMIT

IC RSS-210, A2.9
FCC 15.249

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHZ, and 24.0–24.25 GHz.
(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

RESULTS

7.2.1. DUTY CYCLE



Duty Cycle = ON time / Period = 0.2 / 62.5 = 0.32%
Duty Cycle = 20log(0.3%) = -49.9
VBW= 1/T= 1s/(0.2us X 2 X 10)=250KHz

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

47173 BENICIA STREET, FREMONT, CA 94538, USA

Project #:	14U18490
Report #:	14U18490
Date& Time:	08/08/14
Test Engr:	J. Semana, R. Alegre

Company:	Samsung
EUT Description:	GSM/WCDMA/LTE + BLUETOOTH & WLAN (2.4 GHZ) BAR PHONE
Test Configuration :	X POSITION
Type of Test:	FCC
Mode of Operation:	Transmitting : ANT+ mode

M% = ((t1+t2+t3+...)/T) * 66.83% = 0.32%

Av Reading = Pk Reading + 20*log(M%)
20 * log (M%) = -49.90

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC_B	Av Limit FCC_B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
2402.00	65.79	65.65	32.10	-9.60	0.00	88.29	88.15	114.00	94.00	-25.71	-5.85	3mV	0.00	1.00
2402.00	57.15	56.47	32.10	-9.00	0.00	80.25	79.57	114.00	94.00	-33.75	-14.43	3mH	0.00	2.00
Mid channel														
2442.00	63.13	62.48	32.10	-9.60	0.00	85.63	84.98	114.00	94.00	-28.37	-9.02	3mV	0.00	1.00
2442.00	56.36	52.69	32.10	-9.60	0.00	78.86	75.19	114.00	94.00	-35.14	-18.81	3mH	0.00	2.00
High channel														
2480.00	67.60	67.05	32.10	-9.60	0.00	90.10	89.55	114.00	94.00	-23.90	-4.45	3mV	0.00	1.00
2480.00	56.53	55.76	32.10	-9.60	0.00	79.03	78.26	114.00	94.00	-34.97	-15.74	3mH	0.00	2.00

AVG VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2.3. TRANSMITTER RESTRICTED BAND EDGES

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.385	40.56	PK	32.2	-23.9	48.86	-	-	74	-25.14	315	111	H
4	* 2.381	28.92	VB1T	32.2	-23.5	37.62	54	-16.38	-	-	315	111	H
1	2.4	38.91	PK	32.3	-23.7	47.51	-	-	74	-26.49	315	111	H
3	2.4	28.5	VB1T	32.3	-23.7	37.1	54	-16.9	-	-	315	111	H
5	2.401	40.79	PK	32.3	-23.7	49.39	-	-	-	-	315	111	H
6	2.401	28.61	VB1T	32.3	-23.7	37.21	-	-	-	-	315	111	H

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.386	41.51	PK	32.2	-24	49.71	-	-	74	-24.29	26	336	V
4	* 2.383	29.12	VB1T	32.2	-23.7	37.62	54	-16.38	-	-	26	336	V
1	2.4	38.03	PK	32.3	-23.7	46.63	-	-	74	-27.37	26	336	V
3	2.4	28.17	VB1T	32.3	-23.7	36.77	54	-17.23	-	-	26	336	V
5	2.401	40.18	PK	32.3	-23.7	48.78	-	-	-	-	26	336	V
6	2.401	29	VB1T	32.3	-23.7	37.6	-	-	-	-	26	336	V

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.23	PK	32.7	-23.5	47.43	-	-	74	-26.57	350	329	H
3	* 2.484	28.56	VB1T	32.7	-23.5	37.76	54	-16.24	-	-	350	329	H
4	2.55	29.27	VB1T	32.9	-23.1	39.07	54	-14.93	-	-	350	329	H
2	2.562	41.17	PK	32.9	-23.7	50.37	-	-	74	-23.63	350	329	H

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T136 (dB/m)	Amp/Cbl/ Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	37.83	PK	32.7	-23.5	47.03	-	-	74	-26.97	328	283	V
3	* 2.484	28.37	VB1T	32.7	-23.5	37.57	54	-16.43	-	-	328	283	V
2	2.539	41.43	PK	32.9	-23.5	50.83	-	-	74	-23.17	328	283	V
4	2.549	29.18	VB1T	32.9	-23.2	38.88	54	-15.12	-	-	328	283	V

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

HARMONICS AND SPURIOUS EMISSIONS ABOVE 1GHz

HARMONICS

FCC, VCCI, CISPR, CE, AUSTEL, NZ
UL, CSA, TUV, BSMI, DHHS, NVLAP

47173 BENICIA STREET, FREMONT, CA 94538, USA

Project #:	14U18490
Report #:	14U18490
Date& Time:	08/08/14
Test Engr:	J. Semana, R. Alegre
Company:	Samsung
EUT Description:	GSM/WCDMA + BLUETOOTH & WLAN (2.4 GHZ) BAR PHONE
Test Configuration :	X POSITION
Type of Test:	FCC
Mode of Operation:	Transmitting : ANT+ mode

M% = ((t1+t2+t3+...)/T) * 66.83% = 0.32%

Av Reading = Pk Reading + 20*log(M%)
20 * log (M%) = -49.90

Freq. (MHz)	Pk Rdg (dBuV)	Av Rdg (dBuV)	AF (dB)	Closs (dB)	Pre-amp (dB)	Pk Level (dBuV/m)	Av Level (dBuV/m)	Pk Limit FCC_B	Av Limit FCC_B	Pk Margin (dB)	Avg Margin (dB)	Pol (H/V)	Az (Deg)	Height (Meter)
Low channel														
4804.00	42.39	33.15	32.10	-22.80	0.00	51.69	42.45	74.00	54.00	-22.31	-11.55	3mV	0.00	1.00
4804.00	43.05	33.53	32.10	-22.80	0.00	52.35	42.83	74.00	54.00	-21.65	-11.17	3mH	0.00	2.00
Mid channel														
4884.00	44.08	33.96	32.10	-22.80	0.00	53.38	43.26	74.00	54.00	-20.62	-10.74	3mV	0.00	1.00
4884.00	44.50	33.95	32.10	-22.80	0.00	53.80	43.25	74.00	54.00	-20.20	-10.75	3mH	0.00	2.00
High channel														
4960.00	43.79	33.68	32.10	-22.80	0.00	53.09	42.98	74.00	54.00	-20.92	-11.02	3mV	0.00	1.00
4960.00	42.97	33.58	32.10	-22.80	0.00	52.27	42.88	74.00	54.00	-21.73	-11.12	3mH	0.00	2.00

AVG VB=1/Ton, Voltage Averaging Max Hold where: Ton is the duration of the packet

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

7.2.4. SPURIOUS BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (HORIZONTAL)

HORIZONTAL PLOT



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

SPURIOUS EMISSIONS 30 TO 1000 MHz (VERTICAL)

VERTICAL PLOT



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Trace Markers

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	* 73.7325	46.55	PK	8.1	-28.3	26.35	40	-13.65	0-360	101	V
6	92.3475	43.47	PK	8.2	-28.1	23.57	43.52	-19.95	0-360	101	V
4	143.1775	36	PK	12.7	-27.5	21.2	43.52	-22.32	0-360	200	H
3	186.145	39.2	PK	10.9	-27	23.1	43.52	-20.42	0-360	101	H
1	221.3	46.37	PK	10.7	-26.7	30.37	46.02	-15.65	0-360	101	H
2	600	39.58	PK	18.4	-25.3	32.68	46.02	-13.34	0-360	200	H

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band
PK - Peak detector

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

8. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

RSS-Gen 7.2.2

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

ANSI C63.4 - 2009

RESULTS

This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

6 WORST EMISSIONS

Line-L1 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.1725	42.73	PK	1.2	0	43.93	64.8	-20.87	-	-
2	.1725	24.94	Av	1.2	0	26.14	-	-	54.8	-28.66
3	.2895	36.65	PK	.6	0	37.25	60.5	-23.25	-	-
4	.2895	18.8	Av	.6	0	19.4	-	-	50.5	-31.1
5	.771	32.62	PK	.3	0	32.92	56	-23.08	-	-
6	.771	18.36	Av	.3	0	18.66	-	-	46	-27.34
7	1.5315	29.75	PK	.2	.1	30.05	56	-25.95	-	-
8	1.5315	14.6	Av	.2	.1	14.9	-	-	46	-31.1
9	2.004	30.84	PK	.2	.1	31.14	56	-24.86	-	-
10	2.004	15.23	Av	.2	.1	15.53	-	-	46	-30.47
11	4.146	32.04	PK	.2	.1	32.34	56	-23.66	-	-
12	4.146	17.32	Av	.2	.1	17.62	-	-	46	-28.38

Line-L2 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
13	.1815	40.89	PK	1.2	0	42.09	64.4	-22.31	-	-
14	.1815	18.76	Av	1.2	0	19.96	-	-	54.4	-34.44
15	.402	36.53	PK	.4	0	36.93	57.8	-20.87	-	-
16	.402	22.25	Av	.4	0	22.65	-	-	47.8	-25.15
17	.78	30.62	PK	.3	0	30.92	56	-25.08	-	-
18	.78	16.97	Av	.3	0	17.27	-	-	46	-28.73
19	1.851	28.55	PK	.2	.1	28.85	56	-27.15	-	-
20	1.851	16.03	Av	.2	.1	16.33	-	-	46	-29.67
21	2.4045	33.12	PK	.2	.1	33.42	56	-22.58	-	-
22	2.4045	9.9	Av	.2	.1	10.2	-	-	46	-35.8
23	16.5435	35.49	PK	.3	.2	35.99	60	-24.01	-	-
24	16.5435	15.41	Av	.3	.2	15.91	-	-	50	-34.09

PK - Peak detector
Av - average detection

UL VERIFICATION SERVICES INC. FORM NO: CCSUP4701D
47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888
This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

LINE 1 RESULTS



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

LINE 2 RESULTS



This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.