



FCC CFR47 PART 15 SUBPART C

**BLUETOOTH LOW ENERGY
CERTIFICATION TEST REPORT**

FOR

GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC

MODEL NUMBER: SM-G530M

FCC ID: A3LSMG530M

REPORT NUMBER: 14I18800-E3

ISSUE DATE: SEPT 18, 2014

Prepared for
SAMSUNG ELECTRONICS CO., LTD.
416, MAETAN 3-DONG, YEONGTONG-GU
SUWON-CITY, GYEONGGI-DO 443-742, SOUTH KOREA

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

Issue			
Rev.	Date	Revisions	Revised By
--	9/18/14	Initial Issue	P. Zhang

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	6
4.1. MEASURING INSTRUMENT CALIBRATION	6
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY	7
5. EQUIPMENT UNDER TEST	8
5.1. DESCRIPTION OF EUT	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. WORST-CASE CONFIGURATION AND MODE	9
5.5. DESCRIPTION OF TEST SETUP.....	10
6. TEST AND MEASUREMENT EQUIPMENT	12
7. SUMMARY	13
8. ANTENNA PORT TEST RESULTS	14
8.1. 6 dB BANDWIDTH.....	14
8.2. 99% BANDWIDTH.....	18
8.3. OUTPUT POWER.....	22
8.4. AVERAGE POWER.....	26
8.5. POWER SPECTRAL DENSITY	27
8.6. CONDUCTED SPURIOUS EMISSIONS.....	31
9. RADIATED TEST RESULTS.....	38
9.1. LIMITS AND PROCEDURE	38
9.2. TRANSMITTER ABOVE 1 GHz	40
9.1. WORST-CASE BELOW 1 GHz.....	53
10. AC POWER LINE CONDUCTED EMISSIONS	56

11. SETUP PHOTOS.....61

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SAMSUNG ELECTRONICS CO., LTD.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC
MODEL: SM-G530M
SERIAL NUMBER: 1935734(Radiated) & 1935735(Conducted)
DATE TESTED: AUGUST 8-12, 2014

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



PENG ZHANG
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

STEVEN TRAN
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A	☐ Chamber D
☐ Chamber B	☐ Chamber E
☐ Chamber C	☐ Chamber F
☒ Chamber G	☐ Chamber H

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 18000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone + Bluetooth, WLAN 2.4GHz b/g/n & NFC

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2402-2480	BLE	1.30	1.35

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, with a maximum gain of -1.86 dBi.

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	Samsung	SM-G530M	ETA0U83EWE	N/A
Headset	Samsung	SM-G530M	EHS61ASWE	N/A

I/O CABLES


I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1m	N/A

TEST SETUP

The EUT is continuously communicating to the Bluetooth tester during the tests.

EUT was set in the Hidden menu mode to enable BLE communications.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C00986	4/1/2015
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01179	2/26/2015
EMI Test Receiver, 9KHz-7GHz	R & S	ESCI 7	100773	8/15/2015
Preamplifier, 1300 MHz	Agilent / HP	8447D	C00580	5/8/2015
Preamplifier, 26.5 GHz	Agilent / HP	8449B	C01063	10/22/2014
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	N/A	3/6/2015
Antenna, Horn, 18 GHz	ETS	3117	C01022	2/21/2015
Antenna, Horn, 26.5 GHz	ARA	MWH-1826/B	C00589	12/17/2014
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/2014
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/2014
LISN, 30 MHz	FCC	50/250-25-2	C00626	1/14/2015

7. SUMMARY

The model FCC ID: A3LSMG530M shares the same enclosure and circuit board as mode FCC ID: A3LSMG530F. The WLAN/Bluetooth circuitry and layout, including antenna, are almost identical between the two units. The WLAN/Bluetooth antenna and surrounding circuitry is the same between these two units.

After confirming through preliminary radiated emissions that the performance of the A3LSMG530F BT remains representative of this model (FCC ID: A3LSMG530M) test data for FCC ID: A3LSMG530F is being submitted for this application.

Radiated emissions were fully re-evaluated against FCC Part 15B requirements for digital devices and results indicated no significant differences between the two versions.

FCC Part Section	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.247 (a)(2)	RSS-210 A8.2(a)	Occupied Band width (6dB)	>500KHz	Conducted	Pass	638 kHz
2.1051, 15.247 (d)	RSS-210 A8.5	Band Edge / Conducted Spurious Emission	-20dBc		Pass	-52.68 dBm
15.247	RSS-210 A8.4	TX conducted output power	<30dBm		Pass	1.3 dBm
15.247	RSS-210 A8.2	PSD	<8dBm		Pass	-14.23 dBm
15.207 (a)	RSS-GEN 7.2.2	AC Power Line conducted emissions	Section 10	Radiated	Pass	48.83dBuV(AV)
15.205, 15.209	RSS-210 Clause 2.6, RSS-210 Clause 6	Radiated Spurious Emission	< 54dBuV/m		Pass	42.91 dBuV/m

8. ANTENNA PORT TEST RESULTS

8.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.

RESULTS


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.6550	0.5
Middle	2440	0.6380	0.5
High	2480	0.6460	0.5

6 dB BANDWIDTH PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.2. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

TEST PROCEDURE


Reference to KDB558074 D01 DTS Meas Guidance v03r02: The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0531
Middle	2440	1.0487
High	2480	1.0547

99% BANDWIDTH PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE


Peak power is measured using KDB558074 D01 DTS Meas Guidance v03r02 under section 9.1.1 utilizing spectrum analyzer.

RESULTS


Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2402	1.300	30	-28.700
Middle	2440	0.300	30	-29.700
High	2480	0.700	30	-29.300

OUTPUT POWER PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.4. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

RESULTS

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	1.18
Middle	2440	0.26
High	2480	0.7

8.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST PROCEDURE


Power Spectral Density was performed utilizing the “Method PKPSD (Peak PSD)” under KDB558074 D01 DTS Meas Guidance v03r02

RESULTS


Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-14.23	8	-22.23
Middle	2440	-15.07	8	-23.07
High	2480	-14.70	8	-22.70

POWER SPECTRAL DENSITY PLOTS


LOW CHANNEL



MID CHANNEL



HIGH CHANNEL



8.6. CONDUCTED SPURIOUS EMISSIONS

LIMITS

FCC §15.247 (d)

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


RESULTS

SPURIOUS EMISSIONS, LOW CHANNEL

LOW CHANNEL BANDEDGE




LOW CHANNEL SPURIOUS




SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL REFERENCE




MID CHANNEL SPURIOUS




SPURIOUS EMISSIONS, HIGH CHANNEL

HIGH CHANNEL BANDEDGE



HIGH CHANNEL SPURIOUS



9. RADIATED TEST RESULTS

9.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4 - 2009. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and add duty cycle factor for average measurements. Duty cycle factor = $10 \log(1/x)$. For this sample: $DCF = 10 \log(1/0.62) = 2.05 \text{ dB}$

(Spectrum Analyzer round it up to 2.1dB)


The spectrum from 1GHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

9.2. TRANSMITTER ABOVE 1 GHz

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

LOW CHANNEL RESTRICTED, PEAK and AVERAGE, HORIZONTAL



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Filter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	40.82	PK	32.1	-23.1	0	49.82	-	-	74	-24.18	177	371	H
2	* 2.332	43.1	PK	31.9	-23.1	0	51.9	-	-	74	-22.1	177	371	H
3	* 2.39	30.28	RMS	32.1	-23.1	2.05	41.33	54	-12.67	-	-	177	371	H
4	* 2.367	31.47	RMS	32	-23.1	2.05	42.42	54	-11.58	-	-	177	371	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)

LOW CHANNEL RESTRICTED, PEAK and AVERAGE, VERTICAL



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/Filter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.347	43.37	PK	32	-23.1	0	52.27	-	-	74	-21.73	0	392	V
4	* 2.365	31.37	RMS	32	-23.2	2.05	42.22	54	-11.78	-	-	0	392	V
1	* 2.39	40.32	PK	32.1	-23.1	0	49.32	-	-	74	-24.68	0	392	V
3	* 2.39	30.48	RMS	32.1	-23.1	2.05	41.53	54	-12.47	-	-	0	392	V


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)

HIGH CHANNEL RESTRICTED, PEAK and AVERAGE, HORIZONTAL



Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fitter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.22	PK	32.3	-22.8	0	49.72	-	-	74	-24.28	281	372	H
3	* 2.484	30.59	RMS	32.3	-22.8	2.05	42.14	54	-11.86	-	-	281	372	H
2	2.511	43.5	PK	32.3	-22.8	0	53	-	-	74	-21	281	372	H
4	2.549	31.16	RMS	32.4	-22.7	2.05	42.91	54	-11.09	-	-	281	372	H


* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection

RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)

HIGH CHANNEL RESTRICTED, PEAK and AVERAGE, VERTICAL



Trace Markers


Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cb/r/Filter/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	39.74	PK	32.3	-22.8	0	49.24	-	-	74	-24.76	337	362	V
3	* 2.484	30.69	RMS	32.3	-22.8	2.05	42.24	54	-11.76	-	-	337	362	V
4	2.523	31.26	RMS	32.4	-22.8	2.05	42.91	54	-11.09	-	-	337	362	V
2	2.556	42.89	PK	32.4	-22.7	0	52.59	-	-	74	-21.41	337	362	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector


RMS - RMS detection

HARMONICS AND SPURIOUS EMISSIONS



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

LOW CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
6	* 1.308	33.87	PK	30.1	-23.8	0	40.17	-	-	74	-33.83	0-360	200	V
3	* 8.031	30.26	PK	35.7	-28.1	0	37.86	-	-	74	-36.14	0-360	100	H
4	* 3.751	32.02	PK	33.2	-31.2	0	34.02	-	-	74	-39.98	0-360	200	H
5	* 4.878	30.55	PK	34	-30.2	0	34.35	-	-	74	-39.65	0-360	200	H
2	* 9.115	28.1	PK	36.2	-26.3	0	38	-	-	74	-36	0-360	100	V
1	9.607	28.79	PK	36.7	-25.2	0	40.29	-	-	-	-	0-360	100	V


PK - Peak detector

RADIATED EMISSIONS

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Filtr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 9.116	38.11	PK2	36.2	-26.2	0	48.11	-	-	74	-25.89	306	249	V
* 9.114	26.12	MAV1	36.2	-26.3	2.05	38.07	54	-15.93	-	-	306	249	V


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

MID CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

MID CHANNEL DATA


TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T862 (dB/m)	Amp/Cb/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 1.338	35.88	PK	28.7	-26	0	38.58	-	-	74	-35.42	0-360	100	H
6	* 12.254	28.75	PK	38.8	-26.5	0	41.05	-	-	74	-32.95	0-360	101	H
3	* 4.551	34.55	PK	33.8	-33.3	0	35.05	-	-	74	-38.95	0-360	201	V
2	2.059	35.68	PK	31.3	-25.2	0	41.78	-	-	-	-	0-360	201	H
5	5.972	33.91	PK	35.2	-32	0	37.11	-	-	-	-	0-360	101	H
4	10.372	30.07	PK	37.5	-26.9	0	40.67	-	-	-	-	0-360	101	V

PK - Peak detector


FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013

HIGH CHANNEL HORIZONTAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL VERTICAL



Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

HIGH CHANNEL DATA

TRACE MARKERS

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
6	* 1.358	34.44	PK	29.6	-23.8	0	40.24	-	-	74	-33.76	0-360	100	H
4	* 11.376	29.17	PK	38.1	-26.2	0	41.07	-	-	74	-32.93	0-360	200	H
1	* 3.582	32.65	PK	33	-31.5	0	34.15	-	-	74	-39.85	0-360	200	V
5	* 4.123	32.19	PK	33.5	-31	0	34.69	-	-	74	-39.31	0-360	200	H
2	* 7.415	29.92	PK	35.7	-28.6	0	37.02	-	-	74	-36.98	0-360	100	V
3	9.919	28.99	PK	36.9	-25.6	0	40.29	-	-	-	-	0-360	200	V

PK - Peak detector

RADIATED EMISSIONS


Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Ftr /Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 3.581	40.54	PK2	33	-31.5	0	42.04	-	-	74	-31.96	136	386	V
* 3.584	28.78	MAV1	33	-31.6	2.05	32.23	54	-21.77	-	-	136	386	V

FCC Part15 Subpart C T186 2400MHz Spurious Emissions.TST 12746Rev 9.5 12 Jun 2013


9.1. WORST-CASE BELOW 1 GHz

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION)

HORIZONTAL PLOT



VERTICAL PLOT



BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	Hybrid	Amp/Cbl (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	57.5825	50.49	PK	10.4	-30.6	0	30.29	40	-9.71	0-360	401	H
2	57.625	53.1	PK	10.4	-30.6	0	32.9	40	-7.1	0-360	100	V
3	103.1	41.99	PK	13.8	-30.1	0	25.69	43.52	-17.83	0-360	100	V
4	149.2125	45.91	PK	15.8	-29.6	0	32.11	43.52	-11.41	0-360	201	H
5	600	37.59	PK	21.3	-27.1	0	31.79	46.02	-14.23	0-360	301	H
6	600.1	43.69	PK	21.3	-27.1	0	37.89	46.02	-8.13	0-360	301	V

PK - Peak detector

10. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 [*]	56 to 46 [*]
0.5-5	56	46
5-30	60	50

^{*} Decreases with the logarithm of the frequency.


TEST PROCEDURE

ANSI C63.4 - 2009

RESULTS

6 WORST EMISSIONS

LINE 1 PLOT




LINE 1 RESULTS

Line-L1 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBUV)	Det	T24 IL L1 (dB)	LC Cables 1&3 (dB)	Corrected Reading dBUV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
1	.3525	48.33	PK	.5	0	48.83	58.9	-10.07	-	-
2	.3525	36.09	Av	.5	0	36.59	-	-	48.9	-12.31
3	.483	42.28	PK	.4	0	42.68	56.3	-13.62	-	-
4	.483	29.9	Av	.4	0	30.3	-	-	46.3	-16
5	.7125	42.31	PK	.3	0	42.61	56	-13.39	-	-
6	.7125	28.4	Av	.3	0	28.7	-	-	46	-17.3
7	2.3865	44.31	PK	.2	.1	44.61	56	-11.39	-	-
8	2.3865	25.99	Av	.2	.1	26.29	-	-	46	-19.71
9	11.643	46.02	PK	.2	.2	46.42	60	-13.58	-	-
10	11.643	28.99	Av	.2	.2	29.39	-	-	50	-20.61
11	14.802	49.41	PK	.2	.2	49.81	60	-10.19	-	-
12	14.802	30.94	Av	.2	.2	31.34	-	-	50	-18.66

LINE 2 PLOT



LINE 2 RESULTS

Line-L2 .15 - 30MHz

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	T24 IL L2 (dB)	LC Cables 2&3 (dB)	Corrected Reading dBuV	CISPR 22 Class B QP	Margin to Limit (dB)	CISPR 22 Class B Avg	Margin to Limit (dB)
13	.42	45.27	PK	.4	0	45.67	57.4	-11.73	-	-
14	.42	30.73	Av	.4	0	31.13	-	-	47.4	-16.27
15	.5505	41.46	PK	.3	0	41.76	56	-14.24	-	-
16	.5505	27.17	Av	.3	0	27.47	-	-	46	-18.53
17	1.014	42.3	PK	.3	0	42.6	56	-13.4	-	-
18	1.014	24.84	Av	.3	0	25.14	-	-	46	-20.86
19	1.8915	41.91	PK	.2	.1	42.21	56	-13.79	-	-
20	1.8915	24.37	Av	.2	.1	24.67	-	-	46	-21.33
21	4.5195	43.23	PK	.2	.1	43.53	56	-12.47	-	-
22	4.5195	26.07	Av	.2	.1	26.37	-	-	46	-19.63
23	8.6415	44.31	PK	.2	.1	44.61	60	-15.39	-	-
24	8.6415	25.04	Av	.2	.1	25.34	-	-	50	-24.66

PK - Peak detector

Av - average detection