



129 Samsung-ro,  
Yeongtong-gu, Suwon-Si,  
Gyeonggi-Do, 16677  
Korea  
Tel: 82-31-8062-4278  
Fax: 82-31-279-9985

# FCC TEST REPORT

**Manufacturer: SAMSUNG Electronics Co., Ltd.**

**Model: SM-G550FY**

**FCC ID: A3LSMG550FY**

**Application Type: Certification**

**EUT Type: Portable Handset**

All measurements reported here are in accordance with FCC Rules,  
47CFR Part2, Part22, and Part24.

Prepared By .....  
DH Ju  
Test Engineer

Date ..... 2015.09.17

Checked and Authorized By .....  
WT Jang  
Technical Manager

Date ..... 2015.09.17



## Revision History

| Rev. # | Issue Date | Revisions       | Revised By |
|--------|------------|-----------------|------------|
| 1      | 2015.09.17 | ▪ Initial issue | DH Ju      |

– End of this page –

## Table of Contents

|                                                                |           |
|----------------------------------------------------------------|-----------|
| <b>§2.1033 General Information .....</b>                       | <b>4</b>  |
| <b>1. INTRODUCTION .....</b>                                   | <b>5</b>  |
| 1.1. General.....                                              | 5         |
| <b>2. PRODUCT INFORMATION .....</b>                            | <b>5</b>  |
| 2.1. Equipment Description .....                               | 5         |
| 2.2. Device Capabilities .....                                 | 5         |
| <b>3. DESCRIPTION OF TESTS .....</b>                           | <b>6</b>  |
| 3.1. Evaluation Procedure.....                                 | 6         |
| 3.2. Radiated Measurements .....                               | 6         |
| 3.3. EMI Suppression Device(s)/Modifications .....             | 6         |
| <b>4. TEST EQUIPMENT LIST .....</b>                            | <b>7</b>  |
| <b>5. SAMPLE CALCULATIONS .....</b>                            | <b>8</b>  |
| <b>6. TEST RESULTS .....</b>                                   | <b>9</b>  |
| 6.1. Summary .....                                             | 9         |
| 6.2. Occupied Bandwidth .....                                  | 10        |
| 6.3. Spurious and Harmonic Emissions at Antenna Terminal ..... | 14        |
| 6.4. Band Edge Emissions at Antenna Terminal .....             | 40        |
| 6.5. Peak-Average Ratio .....                                  | 50        |
| 6.6. Frequency Stability / Temperature Variation .....         | 53        |
| 6.7. Radiated Power (ERP/EIRP).....                            | 57        |
| 6.8. Radiated Spurious Emissions Measurements .....            | 60        |
| <b>7. CONCLUSION.....</b>                                      | <b>68</b> |

**§2.1033 General Information**

|                                |                                                                                                                                                                                                                      |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>APPLICANT:</b>              | Samsung Electronics Co., Ltd.                                                                                                                                                                                        |
| <b>APPLICANT ADDRESS:</b>      | 129 Samsung-ro,<br>Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea                                                                                                                                                 |
| <b>TEST SITE:</b>              | Samsung Electronics Co., Ltd.                                                                                                                                                                                        |
| <b>TEST SITE ADDRESS:</b>      | 129 Samsung-ro,<br>Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea                                                                                                                                                 |
| <b>FCC RULE PART(S):</b>       | §2, §22, §24                                                                                                                                                                                                         |
| <b>TEST PROCEDURE(S):</b>      | ANSI/TIA-603-D-2010, KDB971168 v02r02                                                                                                                                                                                |
| <b>BASE MODEL:</b>             | SM-G550FY                                                                                                                                                                                                            |
| <b>FCC ID:</b>                 | A3LSMG550FY                                                                                                                                                                                                          |
| <b>FCC CLASSIFICATION:</b>     | PCS Licensed Transmitter Held to Ear (PCE)                                                                                                                                                                           |
| <b>MODE:</b>                   | GSM / EDGE / WCDMA                                                                                                                                                                                                   |
| <b>EMISSION DESIGNATOR:</b>    | 247KGXW (GSM850), 245KG7W (EDGE850)<br>244KGXW (GSM1900), 246KG7W (EDGE1900)<br>4M12F9W (WCDMA850)<br>4M20F9W (WCDMA1900)                                                                                            |
| <b>TX FREQUENCY RANGE</b>      | 824.2 – 848.8MHz (GSM850, EDGE850)<br>1850.2 – 1909.8MHz (GSM1900, EDGE1900)<br>826.4 – 846.6MHz (WCDMA850)<br>1852.4 – 1907.6MHz (WCDMA1900)                                                                        |
| <b>RX FREQUENCY RANGE</b>      | 869.2 – 893.8MHz (GSM850, EDGE850)<br>1930.2 – 1989.8MHz (GSM1900, EDGE1900)<br>871.4 – 891.6MHz (WCDMA850)<br>1932.4 – 1987.6MHz (WCDMA1900)                                                                        |
| <b>MAX POWER RATING:</b>       | 0.656 W ERP GSM850 (28.17 dBm)<br>0.283 W ERP EDGE850 (24.52 dBm)<br>1.121 W EIRP GSM1900 (30.49 dBm)<br>0.628 W EIRP EDGE1900 (27.98 dBm)<br>0.035 W ERP WCDMA850 (15.48 dBm)<br>0.135 W EIRP WCDMA1900 (21.29 dBm) |
| <b>TEST DEVICE SERIAL NO.:</b> | FCM-031-A & FCM-031-B                                                                                                                                                                                                |
| <b>DATE(S) OF TEST:</b>        | August 28 – September 14 , 2015                                                                                                                                                                                      |



## **1. INTRODUCTION**

### **1.1. General**

These measurement tests were conducted at SAMSUNG ELECTRONICS CO., LTD. (SUWON). The site address is 129 Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea.

## **2. PRODUCT INFORMATION**

### **2.1. Equipment Description**

The Equipment Under Test (EUT) is the Samsung Portable Handset FCC ID: A3LSMG550FY. The test data contained in this report pertains only to the emissions due to the EUT's 2G/3G licensed transmitters.

### **2.2. Device Capabilities**

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, Bluetooth (1x, EDR, LE, HS)

– End of this page –

### 3. DESCRIPTION OF TESTS

#### 3.1. Evaluation Procedure

The measurement procedures described in the "Land Mobile FM or PM -Communications Equipment-Measurements and Performance Standards" (ANSI/TIA-603-D-2010) and "Measurement Guidance for Certification of Licensed Digital Transmitters" (KDB 971168 v02r02) were used in the measurement of the Samsung Portable Handset FCC ID: A3LSMG550FY.

#### 3.2. Radiated Measurements

The radiated and spurious measurements were made at the full anechoic chamber. The equipment under test was placed on the Turn Device at the same height and a distance of 3-meters from the measuring antenna.

The turn device is designed for mobile device measurements. Different sized devices can be mounted on the mounting bracket made of Rohacell.

The turn device is mounted onto a turntable to have both 360° vertical and horizontal rotation. The measurement was made for each horizontal/vertical position in combination with horizontally and vertically polarized measuring antenna.

The substitution antenna will replace the EUT antenna at the same position. The frequency of the signal generator shall be set to the frequencies that were measured on the EUT. The output level of the signal generator shall be adjusted until an equal or a known related level that was measured from the EUT. This level was recorded. For emissions above 1 GHz, the above procedure is repeated by using horn antennas and dBi gain is taken into consideration.

The power of the emission is calculated using the following formula:

$$P_{d[dBm]} = P_{g[dBm]} - \text{cable loss}_{[dB]} + \text{antenna gain}_{[dBd, dBi]}$$

Where  $P_d$  is the dipole equivalent power,  $P_g$  is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole(dBd) or an isotropic source(dBi). The cable connects the generator to the substitute antenna and the substitute level is equal to  $P_{g[dBm]} - \text{cable loss}_{[dB]}$ .

Radiated power levels and radiated spurious emissions levels are investigated per ANSI/TIA-603-D-2010.

#### 3.3. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.



#### 4. TEST EQUIPMENT LIST

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

| Description                           | Model           | Serial No. | Manufacturer | Cal. Date  | Cal. Due   |
|---------------------------------------|-----------------|------------|--------------|------------|------------|
| Wireless Communications Test Set      | E5515C          | GB42230535 | Agilent      | 2015-01-08 | 2016-01-08 |
| Wireless Communications Test Set      | E5515C          | MY53201087 | Agilent      | 2014-11-06 | 2015-11-06 |
| PSA Series Spectrum Analyzer          | E4440A          | MY46187454 | Agilent      | 2015-03-12 | 2016-03-12 |
| EMI TEST RECEIVER                     | ESI             | 836119/010 | R&S          | 2014-10-17 | 2015-10-17 |
| PSG Analog Signal Generator           | E8257D          | MY51501209 | Agilent      | 2014-11-07 | 2015-11-07 |
| EPM Series Power Meter                | E4419B          | GB41293846 | Agilent      | 2014-09-22 | 2015-09-22 |
| POWER SENSOR                          | E9300H          | MY41495838 | Agilent      | 2014-09-23 | 2015-09-23 |
| DC Power Supply                       | E3632A          | MY40027718 | Agilent      | 2015-05-15 | 2016-05-15 |
| Temperature Humidity Chamber          | SH-241          | 92000548   | Espec        | 2014-11-11 | 2015-11-11 |
| Loop Antenna                          | HFH2-Z2         | 100276     | R&S          | 2014-05-19 | 2016-05-19 |
| DIPOLE ANTENNA                        | UHA 9105        | 9105-2412  | Schwarzbeck  | 2013-10-16 | 2015-10-16 |
| LOG PERIODIC DIPOLE ANTENNA           | HL040           | 353255/020 | R&S          | 2014-10-15 | 2016-10-15 |
| DOUBLE-RIDGED HORN Antenna            | HF906           | 360306/011 | R&S          | 2015-01-30 | 2017-01-30 |
| HORN Antenna                          | BBHA 9120       | 9120D-636  | Schwarzbeck  | 2015-01-30 | 2017-01-30 |
| HORN Antenna & Pre-amplifier assembly | HAP18-26N       | 216250     | Flann        | 2014-01-09 | 2016-01-09 |
| HORN Antenna & Pre-amplifier assembly | HAP18-26N       | 216251     | Flann        | 2015-04-30 | 2017-04-30 |
| PRE-AMPLIFIER                         | 8449B           | 3008A02672 | Agilent      | 2014-11-25 | 2015-11-25 |
| RF Power Amplifier                    | 5S1G4           | 304866     | AR           | 2015-02-09 | 2016-02-09 |
| Hygrothermograph Data Logger          | SK-L200TH2a     | 5077       | SATO         | 2014-10-31 | 2015-10-31 |
| Hygrothermograph Data Logger          | SK-L200TH2a     | 5078       | SATO         | 2014-10-31 | 2015-10-31 |
| Hygrothermograph Data Logger          | SK-L200TH2a     | 5110       | SATO         | 2014-10-31 | 2015-10-31 |
| Power Divider                         | 11636B          | 58456      | Agilent      | 2015-04-27 | 2016-04-27 |
| Highpass filter                       | WHK3.0/18G-10SS | 206        | Wainwright   | 2015-01-07 | 2016-01-07 |
| Highpass filter                       | WHV1.0/15G-10SS | 1          | Wainwright   | 2015-04-13 | 2016-04-13 |
| Attenuator 10dB                       | 8491B           | MY39264180 | Agilent      | 2015-06-23 | 2016-06-23 |
| Attenuator 20dB                       | 8493C           | 74158      | Agilent      | 2015-08-20 | 2016-08-20 |
| Network Analyzer                      | 8753E           | JP38160590 | HP           | 2015-06-23 | 2016-06-23 |

Table 4-1 Test Equipment

## 5. SAMPLE CALCULATIONS

### 5.1. GSM Emission Designator

Emission Designator = 250KGXW

GSM BW = 250kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### 5.2. EDGE Emission Designator

Emission Designator = 250KG7W

EDGE BW = 250kHz

G = Phase Modulation

7 = Quantized/Digital Info

W = Combination (Audio/Data)

### 5.3. WCDMA Emission Designator

Emission Designator = 4M16F9W

WCDMA BW = 4.16MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### 5.4. Spurious Radiated Emission

Example: Spurious emission at 3700.40MHz

The receive spectrum analyzer reading at 3 meters with the EUT on the turn device was -81.0dBm. The gain of the substituted antenna is 8.1dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0dB at 3700.40MHz. So 6.1dB is added to the signal generator reading of -30.9dBm yielding -24.80dBm. The fundamental EIRP was 25.50dBm so this harmonic was 25.50dBm - (-24.80) = 50.3dBc.

## 6. TEST RESULTS

### 6.1. Summary

| FCC Part Section(s)              | Test Description                         | Test Limit                                                                            | Test Condition | Test Result | Reference          |
|----------------------------------|------------------------------------------|---------------------------------------------------------------------------------------|----------------|-------------|--------------------|
| TRANSMITTER MODE (TX)            |                                          |                                                                                       |                |             |                    |
| 2.1049                           | Occupied Bandwidth                       | N/A                                                                                   | CONDUCTED      | PASS        | Section 6.2        |
| 2.1051<br>22.917(a)<br>24.238(a) | Conducted Band Edge / Spurious Emissions | $> 43 + 10 \log_{10}(P[\text{Watts}])$ at Band Edge and for all out-of-band emissions |                | PASS        | Sections 6.3, 6.4  |
| 24.232(d)                        | Peak-Average Ratio                       | $< 13 \text{ dB}$                                                                     |                | PASS        | Section 6.5        |
| 2.1046                           | Transmitter Conducted Output Power       | N/A                                                                                   |                | PASS        | See FCC SAR Report |
| 2.1055<br>22.355<br>24.235       | Frequency Stability                      | $< 2.5 \text{ ppm}$ (part 22) Emission must remain in band (Part 24)                  |                | PASS        | Section 6.6        |
| 22.913(a.2)                      | Effective Radiated Power                 | $< 7 \text{ Watts max. ERP}$                                                          | RADIATED       | PASS        | Section 6.7        |
| 24.232(c)                        | Equivalent Isotropic Radiated Power      | $< 2 \text{ Watts max. EIRP}$                                                         |                | PASS        | Section 6.7        |
| 2.1053<br>22.917(a)<br>24.238(a) | Radiated Spurious Emissions              | $> 43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions                  |                | PASS        | Section 6.8        |

Table 6-1. Summary of Test Results

#### Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is SAMSUNG Electronics "Measurement Automation System", Version 4.1.11.

## 6.2. Occupied Bandwidth

§2.1049

### Test Overview

The Occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

### Test Procedure Used

KDB 971168 v02r02 – Section 4.2

### Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% Occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1~5% of the expected OBW
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2~7 were repeated after changing the RBW such that it would be within 1~5% of the 99% occupied bandwidth observed in Step 7

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-1. Test Instruments & Measurement Setup




## Test Plots




Plot 6-1. Occupied Bandwidth Plot (Cellular GSM Mode - Ch.251)




Plot 6-2. Occupied Bandwidth Plot (EDGE850 Mode - Ch.128)




Plot 6-3. Occupied Bandwidth Plot (PCS GSM Mode - Ch.810)



Plot 6-4. Occupied Bandwidth Plot (EDGE1900 Mode - Ch.512)



Plot 6-5. Occupied Bandwidth Plot (Cellular WCDMA Mode - Ch.4233(DL4458))



Plot 6-6. Occupied Bandwidth Plot (PCS WCDMA Mode - Ch.9538(DL9938))

### 6.3. Spurious and Harmonic Emissions at Antenna Terminal §2.1051 §22.917(a) §24.238(a)

#### Test Overview

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is  $43 + 10 \log_{10}(P_{\text{Watts}})$ , where P is the transmitter power in Watts. Limit equivalent to -13dBm, calculation shown below.

$$\begin{aligned}43 + 10 \log_{10}(1.567\text{W}) &= 44.95 \text{ dB} \\1.567\text{W} &= 31.95 \text{ dBm} \\31.95 \text{ dBm} - 44.95 \text{ dB} &= -13 \text{ dBm}\end{aligned}$$

#### Test Procedure Used

KDB 971168 v02r02 – Section 6.0

#### Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 12GHz for Cell, 20GHz for PCS (separated into at least two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Max Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-2. Test Instruments & Measurement Setup

### Test Notes


1. Compliance with the applicable limits is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater for Part 22 and 1 MHz or greater for Part 24. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.
2. The offset which applied to above 4GHz frequencies is the worst-case value of the RF path-loss<sup>1</sup> in the frequency range 4GHz to 20GHz.

---


<sup>1</sup> RF path-loss = EUT output – Spectrum Analyzer input




## Test Plots




Plot 6-7. Conducted Spurious Plot (Cellular GSM Mode - Ch.128)




Plot 6-8. Conducted Spurious Plot (Cellular GSM Mode - Ch.128)




Plot 6-9. Conducted Spurious Plot (Cellular GSM Mode - Ch.128)




Plot 6-10. Conducted Spurious Plot (Cellular GSM Mode - Ch.190)




Plot 6-11. Conducted Spurious Plot (Cellular GSM Mode - Ch.190)




Plot 6-12. Conducted Spurious Plot (Cellular GSM Mode - Ch.190)




Plot 6-13. Conducted Spurious Plot (Cellular GSM Mode - Ch.251)




Plot 6-14. Conducted Spurious Plot (Cellular GSM Mode - Ch.251)




Plot 6-15. Conducted Spurious Plot (Cellular GSM Mode - Ch.251)




Plot 6-16. Conducted Spurious Plot (PCS GSM Mode - Ch.512)




Plot 6-17. Conducted Spurious Plot (PCS GSM Mode - Ch.512)




Plot 6-18. Conducted Spurious Plot (PCS GSM Mode - Ch.512)




Plot 6-19. Conducted Spurious Plot (PCS GSM Mode - Ch.512)




Plot 6-20. Conducted Spurious Plot (PCS GSM Mode - Ch.512)




Plot 6-21. Conducted Spurious Plot (PCS GSM Mode - Ch.661)




Plot 6-22. Conducted Spurious Plot (PCS GSM Mode - Ch.661)




Plot 6-23. Conducted Spurious Plot (PCS GSM Mode - Ch.661)




Plot 6-24. Conducted Spurious Plot (PCS GSM Mode - Ch.661)




Plot 6-25. Conducted Spurious Plot (PCS GSM Mode - Ch.661)




Plot 6-26. Conducted Spurious Plot (PCS GSM Mode - Ch.810)




Plot 6-27. Conducted Spurious Plot (PCS GSM Mode - Ch.810)




Plot 6-28. Conducted Spurious Plot (PCS GSM Mode - Ch.810)




Plot 6-29. Conducted Spurious Plot (PCS GSM Mode - Ch.810)




Plot 6-30. Conducted Spurious Plot (PCS GSM Mode - Ch.810)




Plot 6-31. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4132(DL4357))




Plot 6-32. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4132(DL4357))




Plot 6-33. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4132(DL4357))




Plot 6-34. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4183(DL4408))




Plot 6-35. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4183(DL4408))




Plot 6-36. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4183(DL4408))




Plot 6-37. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4233(DL4458))




Plot 6-38. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4233(DL4458))




Plot 6-39. Conducted Spurious Plot (Cellular WCDMA Mode - Ch.4233(DL4458))




Plot 6-40. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9262(DL9662))




Plot 6-41. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9262(DL9662))




Plot 6-42. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9262(DL9662))




Plot 6-43. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9262(DL9662))




Plot 6-44. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9262(DL9662))




Plot 6-45. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9400(DL9800))




Plot 6-46. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9400(DL9800))




Plot 6-47. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9400(DL9800))




Plot 6-48. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9400(DL9800))




Plot 6-49. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9400(DL9800))




Plot 6-50. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9538(DL9938))




Plot 6-51. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9538(DL9938))



Plot 6-52. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9538(DL9938))



Plot 6-53. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9538(DL9938))



Plot 6-54. Conducted Spurious Plot (PCS WCDMA Mode - Ch.9538(DL9938))

#### 6.4. Band Edge Emissions at Antenna Terminal §2.1051 § 22.917(a) §24.238(a)

##### Test Overview

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is  $43 + 10\log_{10}(P_{\text{Watts}})$ , where P is the transmitter power in Watts. Limit equivalent to -13dBm, calculation shown below.

$$43 + 10\log_{10}(1.567\text{W}) = 44.95 \text{ dB}$$

$$1.567\text{W} = 31.95 \text{ dBm}$$

$$31.95 \text{ dBm} - 44.95 \text{ dB} = -13 \text{ dBm}$$

##### Test Procedure Used

KDB 971168 v02r02 – Section 6.0

##### Test Settings

1. Start and stop frequency were set such that the band edge would be placed at the edge of the plot for GSM, in the center of the plot for WCDMA.
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW > 1% of the emission bandwidth
4. VBW  $\geq 3 \times$  RBW
5. Detector = RMS
6. Number of sweep points  $\geq 2 \times$  Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-3. Test Instruments & Measurement Setup

### Test Notes

1. Per 22.917(b) and 24.238(b), in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to demonstrate compliance with the out-of-band emissions limit.


Example:

In Case of GSM,  $0.01 \times 273 \text{ KHz} = 2.73 \text{ KHz}$


A resolution BW of 3 KHz was used for measurement at the band edges.




## Test Plots




Plot 6-55. Lower Band Edge Plot (Cellular GSM Mode – Ch.128)




Plot 6-56. Lower Band Edge Plot (Cellular GSM Mode – Ch.128)




Plot 6-57. Upper Band Edge Plot (Cellular GSM Mode – Ch.251)




Plot 6-58. Upper Band Edge Plot (Cellular GSM Mode – Ch.251)




Plot 6-59. Lower Band Edge Plot (PCS GSM Mode – Ch.512)




Plot 6-60. Lower Band Edge Plot (PCS GSM Mode – Ch.512)




Plot 6-61. Upper Band Edge Plot (PCS GSM Mode – Ch.810)




Plot 6-62. Upper Band Edge Plot (PCS GSM Mode – Ch.810)




Plot 6-63. Lower Band Edge Plot (Cellular WCDMA Mode - Ch.4132(DL4357))




Plot 6-64. Extended Lower Band Edge Plot (Cellular WCDMA Mode - Ch.4132(DL4357))




Plot 6-65. Upper Band Edge Plot (Cellular WCDMA Mode - Ch.4233(DL4458))




Plot 6-66. Extended Upper Band Edge Plot (Cellular WCDMA Mode - Ch.4233(DL4458))




Plot 6-67. Lower Band Edge Plot (PCS WCDMA Mode - Ch.9262(DL9662))



Plot 6-68. Extended Lower Band Edge Plot (PCS WCDMA Mode - Ch.9262(DL9662))



Plot 6-69. Upper Band Edge Plot (PCS WCDMA Mode - Ch.9538(DL9938))



Plot 6-70. Extended Upper Band Edge Plot (PCS WCDMA Mode - Ch.9538(DL9938))

## 6.5. Peak-Average Ratio §24.232(d)

### Test Overview

A peak to average ratio measurement is performed at the conducted port of the EUT. The spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

### Test Procedure Used

KDB 971168 v02r02 – Section 5.7.1

### Test Settings

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect 1 million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer was set to use an interval "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 6-4. Test Instruments & Measurement Setup


# Test Plots



Plot 6-71. Peak-Average Ratio Plot (PCS GSM Mode - Ch.661)



Plot 6-72. Peak-Average Ratio Plot (EDGE1900 Mode - Ch.661)



Plot 6-73. Peak-Average Ratio Plot (PCS WCDMA Mode - Ch.9400(DL9800))



6.6. Frequency Stability / Temperature Variation  
§2.1055 §22.355 §24.229 §24.235

Test Overview and Limit

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

1. Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
2. Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for other than hand carried battery equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point(=Batt.End) which shall be specified by the manufacturer.

For part 22, the frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency. For part 24, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure Used

ANSI/TIA-603-D-2010

Test Settings

1. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of time sufficient to stabilize EUT at each temperature level shall be allowed prior to frequency measurement.

– End of this page –

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-5. Test Instruments & Measurement Setup

### Test Notes

1. MCF is the Measured Carrier Frequency  
ACF is the Assigned Carrier Frequency
2. Calculate the ppm frequency error by the following:

$$\text{ppm error} = \left( \frac{\text{MCF}_{[\text{MHz}]} - \text{ACF}_{[\text{MHz}]}}{\text{ACF}_{[\text{MHz}]}} \right) \times 10^6$$

3. For part 24, the fundamental emission should stay within the authorized frequency block. But, based on the results of the frequency stability test at the center channel, the frequency deviation results measured are very small. As such it is determined that the channels at the band edge would remain in-band when the maximum measured frequency deviation noted during the frequency stability tests is applied. Therefore the device is determined to remain operating in band over the temperature and voltage range as tested.

Mode : Cellular GSM  
Channel : 190  
Operating Frequency : 836.6 MHz  
Reference Voltage : 3.80 VDC

| Voltage [%] | Power [VDC] | Temp [°C] | ACF [MHz] | MCF [MHz]  | Freq. Dev. [Hz] | ppm error | Limit [ppm] |
|-------------|-------------|-----------|-----------|------------|-----------------|-----------|-------------|
| 100 %       | 3.80        | -30       | 836.6     | 836.599979 | -20.67          | -0.025    | ±2.5        |
|             |             | -20       | 836.6     | 836.599987 | -13.24          | -0.016    |             |
|             |             | -10       | 836.6     | 836.599977 | -23.16          | -0.028    |             |
|             |             | 0         | 836.6     | 836.599979 | -20.88          | -0.025    |             |
|             |             | +10       | 836.6     | 836.599975 | -24.78          | -0.030    |             |
|             |             | +20       | 836.6     | 836.599976 | -23.78          | -0.028    |             |
|             |             | +30       | 836.6     | 836.599978 | -22.39          | -0.027    |             |
|             |             | +40       | 836.6     | 836.599977 | -23.19          | -0.028    |             |
|             |             | +50       | 836.6     | 836.599977 | -22.89          | -0.027    |             |
| Batt.End    | 3.40        | +20       | 836.6     | 836.599979 | -21.39          | -0.026    |             |

Table 6-2. Frequency Stability Data (Cellular GSM Mode - Ch.190)

Mode : PCS GSM  
Channel : 661  
Operating Frequency : 1880 MHz  
Reference Voltage : 3.850 VDC

| Voltage [%] | Power [VDC] | Temp [°C] | ACF [MHz] | MCF [MHz]    | Freq. Dev. [Hz] | ppm error |
|-------------|-------------|-----------|-----------|--------------|-----------------|-----------|
| 100 %       | 3.80        | -30       | 1880      | 1,879.999994 | -6.50           | -0.003    |
|             |             | -20       | 1880      | 1,879.999989 | -11.35          | -0.006    |
|             |             | -10       | 1880      | 1,879.999990 | -10.43          | -0.006    |
|             |             | 0         | 1880      | 1,879.999990 | -9.63           | -0.005    |
|             |             | +10       | 1880      | 1,879.999990 | -10.22          | -0.005    |
|             |             | +20       | 1880      | 1,879.999989 | -10.93          | -0.006    |
|             |             | +30       | 1880      | 1,879.999989 | -11.14          | -0.006    |
|             |             | +40       | 1880      | 1,879.999990 | -9.93           | -0.005    |
|             |             | +50       | 1880      | 1,879.999990 | -10.45          | -0.006    |
| Batt.End    | 3.40        | +20       | 1880      | 1,879.999990 | -9.74           | -0.005    |

Table 6-3. Frequency Stability Data (PCS GSM Mode - Ch.661)

Mode : Cellular WCDMA  
Channel : 4183  
Operating Frequency : 836.6 MHz  
Reference Voltage : 3.80 VDC

| Voltage [%] | Power [VDC] | Temp [°C] | ACF [MHz] | MCF [MHz]  | Freq. Dev. [Hz] | ppm error | Limit [ppm] |
|-------------|-------------|-----------|-----------|------------|-----------------|-----------|-------------|
| 100 %       | 3.80        | -30       | 836.6     | 836.600003 | 3.47            | 0.004     | ±2.5        |
|             |             | -20       | 836.6     | 836.600003 | 3.04            | 0.004     |             |
|             |             | -10       | 836.6     | 836.600002 | 2.27            | 0.003     |             |
|             |             | 0         | 836.6     | 836.600004 | 4.30            | 0.005     |             |
|             |             | +10       | 836.6     | 836.600003 | 2.90            | 0.003     |             |
|             |             | +20       | 836.6     | 836.600006 | 5.61            | 0.007     |             |
|             |             | +30       | 836.6     | 836.600003 | 3.46            | 0.004     |             |
|             |             | +40       | 836.6     | 836.600003 | 2.95            | 0.004     |             |
|             |             | +50       | 836.6     | 836.600003 | 3.45            | 0.004     |             |
| Batt.End    | 3.40        | +20       | 836.6     | 836.600007 | 6.57            | 0.008     |             |

Table 6-4. Frequency Stability Data (Cellular WCDMA Mode - Ch.4183)

Mode : PCS WCDMA  
Channel : 9400  
Operating Frequency : 1880 MHz  
Reference Voltage : 3.80 VDC

| Voltage [%] | Power [VDC] | Temp [°C] | ACF [MHz] | MCF [MHz]    | Freq. Dev. [Hz] | ppm error |
|-------------|-------------|-----------|-----------|--------------|-----------------|-----------|
| 100 %       | 3.80        | -30       | 1880      | 1,880.000007 | 7.33            | 0.004     |
|             |             | -20       | 1880      | 1,880.000006 | 6.30            | 0.003     |
|             |             | -10       | 1880      | 1,880.000011 | 10.69           | 0.006     |
|             |             | 0         | 1880      | 1,880.000010 | 9.67            | 0.005     |
|             |             | +10       | 1880      | 1,880.000008 | 7.85            | 0.004     |
|             |             | +20       | 1880      | 1,880.000009 | 8.81            | 0.005     |
|             |             | +30       | 1880      | 1,880.000009 | 9.04            | 0.005     |
|             |             | +40       | 1880      | 1,880.000009 | 8.72            | 0.005     |
|             |             | +50       | 1880      | 1,880.000008 | 7.59            | 0.004     |
| Batt.End    | 3.40        | +20       | 1880      | 1,880.000008 | 8.26            | 0.004     |

Table 6-5. Frequency Stability Data (PCS WCDMA Mode - Ch.9400)



6.7. Radiated Power (ERP/EIRP)  
§22.913(a)(2) §24.232(c)

Test Overview

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using dipole antennas. Measurements on signals operating above 1GHz are performed using broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedure Used

KDB 971168 v02r02 – Section 5.2.1

ANSI/TIA-603-D-2010 – Section 2.2.17

Test Settings

1. Radiated power measurements are performed using the signal analyzer's "channel power" measurement capability for signals with continuous operation. For signals with burst transmission, the signal analyzer's "time domain power" measurement capability is used
2. RBW = 1 – 5% of the expected OBW, not to exceed 1MHz
3. VBW  $\geq 3 \times$  RBW
4. Span = 1.5 times the OBW
5. No. of sweep points  $\geq 2 \times$  span / RBW
6. Detector = RMS
7. Trigger is set to "free run" for signals with continuous operation with the sweep times set to "auto". Trigger is set to enable triggering only on full power bursts with the sweep time set less than or equal to the transmission burst duration
8. The integration bandwidth was roughly set equal to the measured OBW of the signal for signals with continuous operation. For signals with burst transmission, the "gating" function was enabled to ensure that measurements are performed during times in which the transmitter is operating at its maximum power
9. Trace mode = trace averaging (RMS) over 100 sweeps
10. The trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-6. Test Instruments & Measurement Setup

### Test Notes

1. This device employs GSM, GPRS and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
2. This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1".
3. The EUT was tested with its standard battery.
4. The EUT was tested with Turn Device and the worst case test setup is reported in the tables below.

### Test Results

| Mode    | Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>Reading<br>[dBm] | S/G<br>Level<br>[dBm] | Substitute<br>Level<br>[dBm] | Ant.<br>Gain<br>[dBd] | ERP<br>[dBm] | ERP<br>Limit<br>[dBm] | Margin<br>[dB] |
|---------|----------------|---------------------|---------------------|-----------|-------------------------|-----------------------|------------------------------|-----------------------|--------------|-----------------------|----------------|
|         |                |                     | Azimuth             | Elevation |                         |                       |                              |                       |              |                       |                |
| GSM850  | 824.2          | H                   | 296                 | 170       | -4.67                   | -6.25                 | 29.28                        | -1.11                 | 28.17        | 38.45                 | 10.28          |
| GSM850  | 836.6          | H                   | 292                 | 135       | -5.85                   | -6.25                 | 29.14                        | -1.28                 | 27.86        | 38.45                 | 10.59          |
| GSM850  | 848.8          | H                   | 288                 | 110       | -7.36                   | -6.36                 | 28.83                        | -1.44                 | 27.39        | 38.45                 | 11.06          |
| EDGE850 | 824.2          | H                   | 296                 | 170       | -8.32                   | -9.90                 | 25.63                        | -1.11                 | 24.52        | 38.45                 | 13.93          |

Table 6-6. ERP (Cellular GSM)

| Mode     | Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>Reading<br>[dBm] | S/G<br>Level<br>[dBm] | Substitute<br>Level<br>[dBm] | Ant.<br>Gain<br>[dBi] | EIRP<br>[dBm] | EIRP<br>Limit<br>[dBm] | Margin<br>[dB] |
|----------|----------------|---------------------|---------------------|-----------|-------------------------|-----------------------|------------------------------|-----------------------|---------------|------------------------|----------------|
|          |                |                     | Azimuth             | Elevation |                         |                       |                              |                       |               |                        |                |
| GSM1900  | 1850.2         | V                   | 133                 | 100       | -15.24                  | -12.42                | 20.00                        | 9.58                  | 29.58         | 33.01                  | 3.43           |
| GSM1900  | 1880.0         | V                   | 227                 | 80        | -14.84                  | -11.16                | 21.02                        | 9.47                  | 30.49         | 33.01                  | 2.52           |
| GSM1900  | 1909.8         | V                   | 126                 | 100       | -17.20                  | -13.36                | 18.74                        | 9.27                  | 28.01         | 33.01                  | 5.00           |
| EDGE1900 | 1880.0         | V                   | 227                 | 80        | -17.35                  | -13.67                | 18.51                        | 9.47                  | 27.98         | 33.01                  | 5.03           |

Table 6-7. EIRP (PCS GSM)

| Mode     | Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>Reading<br>[dBm] | S/G<br>Level<br>[dBm] | Substitute<br>Level<br>[dBm] | Ant.<br>Gain<br>[dBd] | ERP<br>[dBm] | ERP<br>Limit<br>[dBm] | Margin<br>[dB] |
|----------|----------------|---------------------|---------------------|-----------|-------------------------|-----------------------|------------------------------|-----------------------|--------------|-----------------------|----------------|
|          |                |                     | Azimuth             | Elevation |                         |                       |                              |                       |              |                       |                |
| WCDMA850 | 826.4          | H                   | 291                 | 145       | -17.42                  | -18.91                | 16.62                        | -1.14                 | 15.48        | 38.45                 | 22.97          |
| WCDMA850 | 836.6          | H                   | 293                 | 125       | -18.44                  | -18.83                | 16.60                        | -1.28                 | 15.32        | 38.45                 | 23.13          |
| WCDMA850 | 846.6          | H                   | 289                 | 110       | -19.48                  | -18.75                | 16.53                        | -1.41                 | 15.12        | 38.45                 | 23.33          |

Table 6-8. ERP (Cellular WCDMA)

| Mode      | Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>Reading<br>[dBm] | S/G<br>Level<br>[dBm] | Substitute<br>Level<br>[dBm] | Ant.<br>Gain<br>[dBi] | EIRP<br>[dBm] | EIRP<br>Limit<br>[dBm] | Margin<br>[dB] |
|-----------|----------------|---------------------|---------------------|-----------|-------------------------|-----------------------|------------------------------|-----------------------|---------------|------------------------|----------------|
|           |                |                     | Azimuth             | Elevation |                         |                       |                              |                       |               |                        |                |
| WCDMA1900 | 1852.4         | V                   | 132                 | 90        | -24.15                  | -21.20                | 11.17                        | 9.58                  | 20.75         | 33.01                  | 12.26          |
| WCDMA1900 | 1880.0         | V                   | 228                 | 70        | -24.04                  | -20.34                | 11.82                        | 9.47                  | 21.29         | 33.01                  | 11.72          |
| WCDMA1900 | 1907.6         | V                   | 220                 | 80        | -25.44                  | -21.57                | 10.47                        | 9.30                  | 19.77         | 33.01                  | 13.24          |

Table 6-9. EIRP (PCS WCDMA)



6.8. Radiated Spurious Emissions Measurements  
§2.1053 §22.917(a) §24.238(a)

Test Overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI/TIA-603-D-2010 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using dipole antennas. Measurements on signals operating above 1GHz are performed using broadband horn antennas. All measurements are performed as peak measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

Test Procedure Used

KDB 971168 v02r02 – Section 5.8

ANSI/TIA-603-D-2010 – Section 2.2.12

Test Settings

1. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
2. VBW  $\geq 3 \times$  RBW
3. Span = 1.5 times the OBW
4. No. of sweep points  $\geq 2 \times$  span / RBW
5. Detector = Max Peak
6. Trace mode = max hold
7. The trace was allowed to stabilize

– End of this page –

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-7. Test Instruments & Measurement Setup

### Test Notes

1. This device employs GSM, GPRS and EDGE capabilities. The EUT was tested under all configurations and the highest power is reported in GSM mode using a Power Control Level of "0" in the PCS Band and "5" in the Cellular Band.
2. This device employs UMTS technology with WCDMA (AMR/RMC), HSDPA and HSUPA capabilities. For WCDMA and HSUPA transmission, all configurations were investigated and the worst case UMTS emissions were found in RMC WCDMA mode at 12.2kbps with HSDPA inactive and TPC bits all set to "1".
3. The EUT was tested with its standard battery.
4. The EUT was tested with Turn Device and the worst case test setup is reported in the tables below.
5. The spectrum is measured from 9kHz to the 10<sup>th</sup> harmonic of the fundamental frequency of the transmitter. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.

# Test Results

Operating Frequency : 824.2 MHz  
Channel : 128  
Measured Output Power : 28.17 dBm = 0.656 Watt  
Modulation Signal : GSM(GMSK)  
Distance : 3 meters  
Limit :  $43 + 10 \log_{10}(W)$  = 41.17 dBc  
RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBd] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 1648.4         | H                   | 293                 | 160       | -63.23                  | -58.20               | 3.76              | 9.09                  | -52.87                |
| 2472.6         | H                   | 233                 | 20        | -62.64                  | -53.54               | 4.73              | 10.38                 | -47.89                |
| 3296.8         | H                   | 48                  | 45        | -65.29                  | -52.87               | 5.51              | 10.44                 | -47.93                |
| 4121.0         | H                   | Noise floor         |           | -67.74                  | -51.90               | 6.12              | 10.43                 | -47.59                |

Table 6-10. Radiated Spurious Data (Cellular GSM Mode - Ch.128)

Operating Frequency : 836.6 MHz  
Channel : 190  
Measured Output Power : 27.86 dBm = 0.611 Watt  
Modulation Signal : GSM(GMSK)  
Distance : 3 meters  
Limit :  $43 + 10 \log_{10}(W)$  = 40.86 dBc  
RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBd] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 1673.2         | H                   | 22                  | 40        | -63.15                  | -57.39               | 3.75              | 9.27                  | -51.87                |
| 2509.8         | H                   | 229                 | 22        | -62.75                  | -53.18               | 4.73              | 10.37                 | -47.54                |
| 3346.4         | V                   | 181                 | 36        | -65.47                  | -52.22               | 5.60              | 10.43                 | -47.39                |

Table 6-11. Radiated Spurious Data (Cellular GSM Mode - Ch.190)

Operating Frequency : 848.8 MHz  
 Channel : 251  
 Measured Output Power : 27.39 dBm = 0.548 Watt  
 Modulation Signal : GSM(GMSK)  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 40.39 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBd] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 1697.6         | H                   | 54.30               | 30.60     | -62.68                  | -56.91               | 3.74              | 9.44                  | -51.21                |
| 2546.4         | H                   | 184.00              | 179.70    | -62.88                  | -53.30               | 4.68              | 10.28                 | -47.70                |
| 3395.2         | H                   | 112.40              | 145.20    | -66.01                  | -52.97               | 5.50              | 10.41                 | -48.06                |

Table 6-12. Radiated Spurious Data (Cellular GSM Mode - Ch.251)

Operating Frequency : 1850.2 MHz  
 Channel : 512  
 Measured Output Power : 29.58 dBm = 0.908 Watt  
 Modulation Signal : GSM(GMSK)  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 42.58 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBi] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 3700.4         | V                   | 341                 | 179       | -60.21                  | -45.11               | 5.91              | 10.58                 | -40.43                |
| 5550.6         | H                   | 294                 | 90        | -58.33                  | -38.62               | 7.39              | 11.32                 | -34.70                |
| 7400.8         | H                   | 290                 | 135       | -66.63                  | -42.77               | 8.13              | 10.05                 | -40.86                |
| 9251.0         | H                   | 291                 | 90        | -61.62                  | -34.20               | 10.09             | 11.24                 | -33.04                |

Table 6-13. Radiated Spurious Data (PCS GSM Mode - Ch.512)

Operating Frequency : 1880.0 MHz  
 Channel : 661  
 Measured Output Power : 30.49 dBm = 1.121 Watt  
 Modulation Signal : GSM(GMSK)  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 43.49 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBi] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 3760.0         | H                   | 203                 | 67        | -65.14                  | -49.51               | 5.97              | 10.54                 | -44.94                |
| 5640.0         | H                   | 285                 | 151       | -64.86                  | -46.00               | 7.37              | 11.17                 | -42.20                |
| 7520.0         | H                   | 311                 | 20        | -66.22                  | -42.44               | 8.30              | 10.32                 | -40.42                |
| 9400.0         | H                   | 291                 | 92        | -66.88                  | -40.03               | 9.56              | 11.20                 | -38.39                |

Table 6-14. Radiated Spurious Data (PCS GSM Mode - Ch.661)

Operating Frequency : 1909.8 MHz  
 Channel : 810  
 Measured Output Power : 28.01 dBm = 0.632 Watt  
 Modulation Signal : GSM(GMSK)  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 41.01 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBi] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 3819.6         | V                   | 22                  | 51        | -66.29                  | -50.74               | 5.97              | 10.54                 | -46.17                |
| 5729.4         | H                   | 285                 | 151       | -64.93                  | -45.78               | 7.44              | 11.08                 | -42.14                |
| 7639.2         | V                   | 158                 | 7         | -67.09                  | -42.94               | 8.66              | 10.33                 | -41.27                |
| 9549.0         | H                   | 291                 | 92        | -67.54                  | -39.85               | 9.62              | 11.46                 | -38.02                |

Table 6-15. Radiated Spurious Data (PCS GSM Mode - Ch.810)

Operating Frequency : 826.4 MHz  
 Channel : 4132  
 Measured Output Power : 15.48 dBm = 0.035 Watt  
 Modulation Signal : WCDMA  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 28.48 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBd] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 1652.8         | H                   | 25                  | 170       | -65.06                  | -59.90               | 3.76              | 9.12                  | -54.54                |
| 2479.2         | H                   | 108                 | 45        | -65.88                  | -56.70               | 4.73              | 10.38                 | -51.05                |
| 3305.6         | H                   | 354                 | 125       | -65.34                  | -52.79               | 5.52              | 10.44                 | -47.88                |
| 4132.0         | V                   | Noise floor         |           | -67.27                  | -51.45               | 6.14              | 10.46                 | -47.12                |

Table 6-16. Radiated Spurious Data (Cellular WCDMA Mode - Ch.4132)

Operating Frequency : 836.6 MHz  
 Channel : 4183  
 Measured Output Power : 15.32 dBm = 0.034 Watt  
 Modulation Signal : WCDMA  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 28.32 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBd] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 1673.2         | V                   | 5                   | 178       | -65.13                  | -59.39               | 3.75              | 9.27                  | -53.87                |
| 2509.8         | V                   | 245                 | 124       | -65.91                  | -56.07               | 4.73              | 10.37                 | -50.43                |
| 3346.4         | V                   | 194                 | 177       | -65.27                  | -52.02               | 5.60              | 10.43                 | -47.19                |
| 4183.0         | V                   | Noise floor         |           | -67.36                  | -51.29               | 6.23              | 10.59                 | -46.93                |

Table 6-17. Radiated Spurious Data (Cellular WCDMA Mode - Ch.4183)

Operating Frequency : 846.6 MHz  
 Channel : 4233  
 Measured Output Power : 15.12 dBm = 0.033 Watt  
 Modulation Signal : WCDMA  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 28.12 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBd] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 1693.2         | H                   | 162                 | 112       | -64.73                  | -58.96               | 3.74              | 9.41                  | -53.29                |
| 2539.8         | H                   | 94                  | 159       | -65.65                  | -56.07               | 4.69              | 10.30                 | -50.46                |
| 3386.4         | V                   | 25                  | 149       | -65.19                  | -52.30               | 5.51              | 10.41                 | -47.40                |
| 4233.0         | H                   | Noise floor         |           | -67.52                  | -52.08               | 6.38              | 10.73                 | -47.73                |

Table 6-18. Radiated Spurious Data (Cellular WCDMA Mode - Ch.4233)

Operating Frequency : 1852.4 MHz  
 Channel : 9262  
 Measured Output Power : 20.75 dBm = 0.119 Watt  
 Modulation Signal : WCDMA  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 33.75 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBi] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 3704.8         | H                   | 295                 | 90        | -63.65                  | -48.67               | 5.91              | 10.58                 | -44.01                |
| 5557.2         | V                   | 63                  | 8         | -63.05                  | -43.50               | 7.39              | 11.30                 | -39.59                |
| 7409.6         | H                   | 59                  | 45        | -66.52                  | -42.66               | 8.15              | 10.07                 | -40.74                |
| 9262.0         | H                   | Noise floor         |           | -67.28                  | -39.90               | 10.05             | 11.24                 | -38.71                |

Table 6-19. Radiated Spurious Data (PCS WCDMA Mode - Ch.9262)

Operating Frequency : 1880.0 MHz  
 Channel : 9400  
 Measured Output Power : 21.29 dBm = 0.135 Watt  
 Modulation Signal : WCDMA  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 34.29 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBi] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 3760.0         | H                   | 311                 | 179       | -66.20                  | -50.57               | 5.97              | 10.54                 | -46.00                |
| 5640.0         | V                   | 173                 | 3         | -64.93                  | -45.97               | 7.37              | 11.17                 | -42.17                |
| 7520.0         | H                   | 201                 | 98        | -66.49                  | -42.71               | 8.30              | 10.32                 | -40.69                |

Table 6-20. Radiated Spurious Data (PCS WCDMA Mode - Ch.9400)

Operating Frequency : 1907.6 MHz  
 Channel : 9538  
 Measured Output Power : 19.77 dBm = 0.095 Watt  
 Modulation Signal : WCDMA  
 Distance : 3 meters  
 Limit :  $43 + 10 \log_{10}(W)$  = 32.77 dBc  
 RSE Limit : -13 dBm

| Freq.<br>[MHz] | Ant<br>Pol<br>(H/V) | EUT Pol<br>[degree] |           | S/A<br>reading<br>[dBm] | S/G<br>Lev.<br>[dBm] | Tx<br>C/L<br>[dB] | Ant.<br>Gain<br>[dBi] | RSE<br>Level<br>[dBm] |
|----------------|---------------------|---------------------|-----------|-------------------------|----------------------|-------------------|-----------------------|-----------------------|
|                |                     | Azimuth             | Elevation |                         |                      |                   |                       |                       |
| 3815.2         | V                   | 168                 | 149       | -65.83                  | -50.34               | 5.97              | 10.54                 | -45.77                |
| 5722.8         | H                   | 334                 | 95        | -65.88                  | -46.75               | 7.44              | 11.09                 | -43.10                |
| 7630.4         | V                   | 220                 | 76        | -67.36                  | -43.23               | 8.64              | 10.33                 | -41.54                |

Table 6-21. Radiated Spurious Data (PCS WCDMA Mode - Ch.9538)



## **7. CONCLUSION**

The data collected relate only the item(s) tested and show that the Samsung Portable Handset FCC ID: A3LSMG550FY compliance with all the requirements of Parts 2, 22, 24 of the FCC rules.

– End of this report –